INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 46, NO. 12 **DECEMBER 21, 1963**

AUTHOR INDEX TO THE JOURNAL

The reference number in parentheses refers to the *monthly* issue of *The Journal;* the numbers following are the *page* numbers.

Aboaf, J. A. Effects of very high pressures on glass; results obtained using a tetrahedral anvil apparatus, (6) 296–97.
Accountius, O. E. See Voruz, T. A.
Aleshin, Eugene. See McKee, W. D., Jr.
Alford, W. J., and Stephens, D. L. Chemical polishing and etching techniques for Al_2O_3 single crystals, (4) 193–94.
Alper, A. M. See Doman, R. C.
Amato, I., Colombo, R. L., and Protti, A. M. Influence of stoichiometry on the rate of grain growth of UO_2, (8) 407.
Argyle, J. F., and Hummel, F. A. Dilatometric and X-ray data for lead compounds, II, (1) 10–14.
Arroyo, L. See Cierva, P. de la.
Ashbee, K. H. G., and Smallman, R. E. Stress-strain behavior of titanium dioxide (rutile) single crystals, (5) 211–14.
Atlas, L. M., Nagao, Hikaru, and Nakamura, H. H. Correction: Control of dielectric constant and loss in alumina ceramics (October issue, 1962), (4) 196.
Aukrust, Egil, and Muan, Arnulf. Stabilities of $CoO \cdot Al_2O_3$, $CoO \cdot Cr_2O_3$, and $2CoO \cdot SiO_2$, (7) 358; Phase relations in the system cobalt oxide—manganese oxide in air, (10) 511.
Austerman, S. B. Growth of beryllia single crystals, (1) 6–10.

Bailey, Donald. Microscopy of steam-cured asbestos portland cement products, (7) 348–51.
Barmore, W. L. See Vandervoort, R. R.
Barr, J. B. See Doman, R. C.
Baskin, Y., and Schell, D. C. Phase studies in the binary system $MgO–Ta_2O_5$, (4) 174–77.
Bauleke, M. P., and McDowell, K. O. System lead oxide–zinc oxide, (5) 243.
Baun, W. L., and McDevitt, N. T. Infrared absorption spectra of rare-earth oxides in the region 800 to 240 cm^{-1}, (6) 294.
Bayer, Gerhard. New perovskite-type compounds A_2BTeO_6, (12) 604–605.
Beck, P. W. See Brockman, F. G.
Benedetto, B. di. See DiBenedetto, B.
Benson, G. C., Freeman, P. I., and Dempsey, E. Calculation of cohesive and surface energies of thorium and uranium dioxides, (1) 43–47.
Berg, Daniel. See Hirayama, Chikara.
Bergeron, C. G., Russell, C. K., and Friedberg, A. L. Thermal analysis of lead borate glasses during crystallization, (5) 246–47.
Blair, G. E. See Hamblen, D. P.
Blank, B., Rossington, D. R., and Weinland, L. A. Adsorption of admixtures on portland cement, (8) 395–99.
Block, S., Molin, J., and Piermarini, G. X-ray study of a cadmium borate glass, (11) 557.
Bogardus, E. H., and Roy, Rustum. Residual stresses in two-phase systems as determined by changes in transition temperature, (12) 573–76.
Bonner, W. A. See Van Uitert, L. G.
Boston, J. R. See Stiefbold, D. R.
Boyer, W. H. See Van Dreser, M. L.
Brauchtun, W. R. Barium zirconate-lead titanate ferroelectric ceramics, (3) 141–44.
Brindley, G. W. See Layden, G. K.
Brissette, L. A. See Spriggs, R. M.
Brittain, J. O. See Hirthe, W. M.
Brockman, F. G., Beck, P. W., and Steneck, W. G. Magnetostrictive ferrites with small change in coupling coefficient from 0° to 20°C, (4) 167–70.
Brown, W. R. See Kirchner, H. P.
Brownell, W. E. Reactions between alkaline-earth sulfates and cristobalite, (3) 125–28.
Buchanan, R. C. See Cooper, A. R., Jr.
Buckley, J. D., and Wilson, H. H. Destabilization of zirconia by cyclic heating, (10) 510.
Budworth, D. W., and Pask, J. A. Flow stresses on the {100} and {110} planes in LiF, and the plasticity of polycrystals, (11) 560–61.
Buessem, W. R., and Butler, S. R. Valence changes of iron and manganese in manganese ferrite, (9) 442–46.
Burk, Maksymilian. Thermal conductivity of beryllia ceramics from −200° to 150°C, (3) 150–51.
Butler, S. R. See Buessem, W. R.
Buyers, A. G. Ceramic-metal bonding stable in excess of 2248°K, (5) 244–45.

Carlson, W. A., Sanford, E. A., and Crandall, W. B. Study of crystallization of glass coatings on metal by electron microscopy, (6) 249–53.
Carlson, W. G. See Tien, T. Y.
Carroll, D. F. System $PuO_2–ZrO_2$, (4) 194–95; Thermal expansion of plutonium nitride, (8) 406.
Chaklader, A. C. D. X-ray study of quartz-cristobalite transformation, (2) 66–71; Geometric model for quartz-cristobalite transformation, (4) 192–93; see also Misra, S. K.
Chandler, B. A. See Sjodahl, L. H.
Chapman, A. T. Phase studies in BeO–metal oxide systems using a porous-collector technique, (4) 171–74.
Charles, R. J. Some structural and electrical properties of lithium silicate glasses, (5) 235–43.
Charvat, F. R. See Kingery, W. D.
Chatterji S., and Jeffery, J. W. Studies of early stages of paste hydration of cement compounds, II, (4) 187–91; Studies of early stages of paste hydration of different types of portland cements, (6) 268–73.
Chen, F. P. H. Kinetic studies of crystallization of synthetic mica glass, (10) 476–84.
Chikalla, T. D. Melting behavior in the system $UO_2–PuO_2$, (7) 323–28.
Christensen, J. A. Thermal expansion and change in volume of uranium dioxide on melting, (12) 607–608.
Chung, Dae-Hyun, Swica, J. J., and Crandall, W. B. Relation of single-crystal elastic constants to polycrystalline isotropic elastic moduli of MgO, (9) 452–57.
Cierva, P. de la, and Arroyo, L. Study of optical glass surfaces by leaching with nitric acid: I, Polishing lines, (6) 273–76.
Clevenger, T. R., Jr. Effect of Fe^{4+} in the system $SrFeO_3–SrTiO_3$, (5) 207–10.
Cline, C. F. See Smith, D. K.
Coble, R. L. See Paladino, A. E.
Coble, R. L., and Ellis, J. S. Hot-pressing alumina: Mechanisms of material transport, (9) 438–41.
Coble, R. L., and Guerard, Y. H. Creep of polycrystalline aluminum oxide, (7) 353–54.
Colombo, R. L. See Amato, I.
Conley, R. F. Rapid particle-size analysis of ceramic clays by packing-volume technique, (1) 1–5.
Cook, R. L. See Wilcox, D. L.
Cooper, A. R., Jr., and Buchanan, R. C. Calculation of temperature distribution in glass tanks by use of a special-purpose electric analog, (12) 588–92.
Copley, S. M. See Hulse, C. O.
Crandall, W. B. See Carlson, W. A.; Chung, Dae-Hyun; Hasselman, D. P. H.
Cutler, I. B. See Johnson, D. L.

Datta, R. K., and Roy, Rustum. Phase transitions in $LiAl_5O_8$, (8) 388–90.
De la Cierva, P. See Cierva, P. de la.
Dempsey, E. See Benson, G. C.
DiBenedetto, B. See Waugh, J. S.
DiMarcello, F. V. See Gallagher, P. K.; MacChesney, J. B.
Doman, R. C., Barr, J. B., McNally, R. N., and Alper, A. M. Phase equilibria in the system CaO–MgO, (7) 313–16.

Eichelberger, J. F., Hudgens, C. R., Jones, L. V., Pish, G., Rhinehammer, T. B., Tucker, P. A., and Wittenberg, L. J. Phase equilibria for the ternary fused-salt system NaF–BeF_2–UF_4, (6) 279–83.
Elkington, W. E., Thomas, G., and Washburn, J. Damage produced by moving dislocation in MgO, (7) 307–13.
Ellis, J. S. See Coble, R. L.
Eppler, R. A. Glass formation and recrystallization in the lithium metasilicate region of the system $Li_2O–Al_2O_3–SiO_2$, (2) 97–101.
Ern, V. Differential thermal analysis of a cubic modification of $BaTiO_3$, (6) 295–96.
Eyring, H. See Gabrysh, W. F.

Fang, J. H. Comment on comment by J. F. Sarver, (5) 247.
Flood, H., and Knapp, W. J. Acid-base equilibria in the system $PbO–SiO_2$, (2) 61–65.
Folweiler, R. C. See Gannon, R. E.
Foster, W. R. See Gentile, A. L.
Freeman, P. I. See Benson, G. C.
Friedberg, A. L. See Bergeron, C. G.
Friedman, H. A. See Thoma, R. E.
Fuhrman, N., Hower, L. D., Jr., and Holden, R. B. Low-temperature sintering of uranium dioxide, (3) 114–21.
Fulrath, R. M. See Rossi, R. C.

Gabrysh, A. F. See Gabrysh, W. F.
Gabrysh, W. F., Eyring, H., Lin-Sen, Pan, and Gabrysh, A. F. Rheological factors for bentonite suspensions, (11) 523–29.
Gallagher, P. K. See MacChesney, J. B.
Gallagher, P. K., and Schrey, Frank. Thermal decomposition of some substituted barium titanyl oxalates and its effect on the semiconducting properties of the doped materials, (12) 567–73.
Gallagher, P. K., Schrey, Frank, and DiMarcello, F. V. Preparation of semiconducting titanates by chemical methods, (8) 359–65.
Gannon, R. E., Folweiler, R. C., and Vasilos, T. Pyrolytic synthesis of titanium diboride, (10) 496–99.
Gentile, A. L., and Foster, W. R. Calcium hexaluminate and its stability relations in the system $CaO–Al_2O_3–SiO_2$, (2) 74–76.
Giess, E. A. Equations and tables for analyzing solid-state reaction kinetics, (8) 374–76; see also Lefever, R. A.
Gillam, E., and Holden, J. P. Structure of nickel oxide containing alumina, (12) 601–604.
Glasser, F. P., and Glasser, L. S. D. Crystal chemistry of some AB_2O_4 compounds, (8) 377–80.
Glasser, L. S. D. See Glasser, F. P.
Goodman, G. Electrical conduction anomaly in samarium-doped barium titanate, (1) 48–54.
Grodkiewicz, W. H., and Van Uitert, L. G. Synthesis of forsterite, diopside, akermanite, and wollastonite from molten PbO, (7) 356.
Grossman, L. N. High-temperature thermophysical properties of uranium monocarbide, (6) 264–67; On the question of a phase change in zirconium monocarbide, (9) 457–58.
Guerard, Y. H. See Coble, R. L.

Hagy, H. E. Experimental evaluation of beam-bending method of determining glass viscosities in the range 10^8 to 10^{13} poises, (2) 93–97.
Hall, L. L. See Morgan, C. S.
Hamblen, D. P., Weidel, R. A., and Blair, G. E. Preparation of ceramic semiconductors from high-vanadium glasses, (10) 499–504.
Hamilton, B. G. See Rigby, G. R.
Hammond, M. L., and Ravitz, S. F. Influence of environment on brittle fracture of silica, (7) 329–32.
Handwerk, J. H., White, G. D., and Hill, D. C. Ceramic nuclear fuels in the system $UO_2–ZrO_2–CaO$, (1) 29–32.
Hanlon, J. E. See Phillips, W. L., Jr.
Hanna, Rinoud. Elastic moduli of polycrystalline magnesia alumina spinel, (2) 106.

Hansen, W. C. Comment on paper, "Studies of early stages of paste hydration of cement compounds, II," by S. Chatterji and J. W. Jeffery, (9) 459.
Hasselman, D. P. H. Experimental and calculated Young's moduli of zirconium carbide containing a dispersed phase of graphite, (2) 103–104; Thermal shock by radiation heating, (5) 229–34; Elastic energy at fracture and surface energy as design criteria for thermal shock, (11) 535–40; Relation between effects of porosity on strength and on Young's modulus of elasticity of polycrystalline materials, (11) 564–65.
Hasselman, D. P. H., and Crandall, W. B. Thermal shock analysis of spherical shapes, II, (9) 434–37.
Hebert, G. M. See Thoma, R. E.
Hill, D. C. See Handwerk, J. H.
Hirayama, Chikara, and Berg, Daniel. Dielectric properties of glasses in the system Nb_2O_5–Na_2O–SiO_2, (2) 85–88.
Hirota, E. See Kubota, B.
Hirthe, W. M., and Brittain, J. O. High-temperature steady-state creep in rutile, (9) 411–17.
Ho, S.-M. See Lin, F. C.
Hoch, Michael. See Vardi, Joseph.
Hoch, Michael, and Vardi, Joseph. Thermal conductivity of TiC, (5) 245.
Hoenig, C. L. See Neimark, L. A.
Hoh, S. R., and Pirigyi, F. E. Barium titanates with improved insulation resistance and time constant, (11) 516–18.
Holden, J. P. See Gillam, E.
Holden, R. B. See Fuhrman, N.
Hower, L. D., Jr. See Fuhrman, N.
Hudgens, C. R. See Eichelberger, J. F.
Huggins, R. A. See Stiefbold, D. R.
Hulse, C. O., Copley, S. M., and Pask, J. A. Effect of crystal orientation on plastic deformation of magnesium oxide, (7) 317–23.
Hummel, F. A. See Argyle, J. F.
Hutta, J. J. See Phillips, Bert.
Hutton, R. F. See Rigby, G. R.

Iida, Y. See Kubota, B.
Insley, Herbert. See Thoma, R. E.

Jeffery, J. W. See Chatterji, S.
Jewett, R. P. See Voruz, T. A.
Johnson, D. L., and Cutler, I. B. Diffusion sintering: I, Initial stage sintering models and their application to shrinkage of powder compacts, (11) 541–45; II, Initial sintering kinetics of alumina, (11) 545–50.
Jones, L. V. See Eichelberger, J. F.

Kestigian, Michael. Preparation of $Cd_2Nb_2O_7$ single crystals from a CdF_2 melt, (11) 563–64.
Kingery, W. D., Woulbroun, J. M., and Charvat, F. R. Effects of applied pressure on densification during sintering in the presence of a liquid phase, (8) 391–95.
Kirchner, H. P., and Knoll, Peter. Silicon carbide whiskers, (6) 299–300.
Kirchner, H. P., Merz, K. M., and Brown, W. R. Thermal expansion of uranium pyrophosphate and of ceramic bodies in the system UO_2–UP_2O_7, (3) 137–41.
Kittel, J. H. See Neimark, L. A.
Klein, M. J., Rough, F. A., and Simons, C. C. Structure and annealing behavior of explosively shocked magnesia single crystals, (7) 356–58.
Knapp, W. J. See Flood, H.
Knoll, Peter. See Kirchner, H. P.
Koonce, S. E. See Williams, J. C.
Kruger, O. L. Phase studies on arc-melted plutonium-carbon alloys near the monocarbide composition, (2) 80–85.
Kubota, B., Nishikawa, T., Yanese, A., Hirota, E., Mihara, T., and Iida, Y. Modified ferromagnetic chromium dioxide, (11) 550–56.

Layden, G. K. System Al_2O_3–Nb_2O_5, (10) 506.
Layden, G. K., and Brindley, G. W. Kinetics of vapor-phase hydration of magnesium oxide, (11) 518–22.
Lefever, R. A., and Giess, E. A. Suggested mechanism for formation of hopper crystals in flux systems, (3) 153–54.
Leipold, M. H. See Nielsen, T. H.
Levin, E. M., and Mauer, F. A. Improved sample holder for X-ray diffractometer furnace, (1) 59–60.
Li, C. H. See Stokes, R. J.
Lin, F. C., and Ho, S.-M. Chemical durability of arsenic-sulfur-iodine glasses, (1) 24–28.
Lin-Sen, Pan. See Gabrysh, W. F.
Long, S. A., and McGee, T. D. Effect of grain boundaries on plastic deformation of sodium chloride, (12) 583–87.

McBrayer, R. D., Palmour, Hayne, III, and Mehta, P. K. Chemical etching of defect structures in alumina-rich spinel single crystals, (10) 504–505.
McCallum, I. S. See Perrotta, A. J.
MacChesney, J. B., Gallagher, P. K., and DiMarcello, F. V. Stabilized barium titanate ceramics for capacitor dielectrics, (5) 197–202.
McClelland, J. D., and Zehms, E. H. End-point density of hot-pressed alumina, (2) 77–80.
McDevitt, N. T. See Baun, W. L.
McDowell, K. O. See Bauleke, M. P.
McGee, T. D. See Long, S. A.
McKee, W. D., Jr., and Aleshin, Eugene. Aluminum oxide-titanium oxide solid solution, (1) 54–58.
Mackenzie, J. D. High-pressure effects on oxide glasses: I, Densification in rigid state, (10) 461–70; II, Subsequent heat treatment, (10) 470–76.
McNally, R. N. See Doman, R. C.
Marcello, F. V. Di. See DiMarcello, F. V.
Mark, S. D. See Shaffer, P. T. B.
Matsuo, Yoshihiro, and Sasaki, Hiromu. PbO-rich side of the system PbO–TiO_2, (8) 409–10.
Mauer, F. A. See Levin, E. M.
Mehta, P. K. See McBrayer, R. D.
Merz, K. M. See Kirchner, H. P.
Mihara, T. See Kubota, B.
Misra, S. K., and Chaklader, A. C. D. System copper oxide–alumina, (10) 509.
Mistler, R. E., Ploetz, G. L., and Smith, J. A. Thermal expansion of polycrystalline lanthanum and neodymium sesquioxides, (11) 561–62.
Molin, J. See Block, S.
Moran, V. J. Structure in the fracture surface of silicate glass, (2) 102–103.
Morgan, C. S., Hall, L. L., and Yust, C. S. Sintering of sodium chloride, (11) 559–60.
Muan, Arnulf. See Aukrust, Egil; Riboud, P. V.; Speidel, D. H.
Mueller, A. See Murthy, M. K.
Murthy, M. K. Phosphate–halide systems: II, Infrared spectra of glasses in the system $NaPO_3$–NaF, (11) 558–59.
Murthy, M. K., and Mueller, A. Phosphate–halide systems: I, Constitution of $NaPO_3$–NaF glasses, (11) 530–35.

Nagao, Hikaru. See Atlas, L. M.
Nakamura, H. H. See Atlas, L. M.
Navias, Louis. Preparation and properties of spinel made by vapor transport and diffusion in the system MgO–Al_2O_3: III, Effect of time and intermittent cooling on diffusion pattern, (3) 152.
Neimark, L. A., Kittel, J. H., and Hoenig, C. L. Irradiation of metal-fiber-reinforced thoria-urania, (5) 219–24.
Newnham, R. E., Redman, M. J., and Santoro, R. P. Crystal structure of yttrium and other rare-earth borates, (6) 253–56.
Nielsen, T. H., and Leipold, M. H. Thermal expansion in air of ceramic oxides to 2200°C, (8) 381–87.
Nishikawa, T. See Kubota, B.
Norris, L. F., and Parravano, G. Sintering of zinc oxide, (9) 449–52.

Paladino, A. E. See Waugh, J. S.
Paladino, A. E., and Coble, R. L. Effect of grain boundaries on diffusion-controlled processes in aluminum oxide, (3) 133–36; Correction, (9) 460.
Palmour, Hayne, III. See McBrayer, R. D.
Parravano, G. See Norris, L. F.
Pask, J. A. See Budworth, D. W.; Hulse, C. O.; Scott, W. D.
Perrotta, A. J., and McCallum, I. S. Germanate spinels, (8) 408–409.
Peters, F. G. See Sinclair, W. R.
Phillips, Bert, Hutta, J. J., and Warshaw, I. Phase equilibria in the system NiO–Al_2O_3–SiO_2, (12) 579–83.
Phillips, W. L., Jr., and Hanlon, J. E. Oxygen penetration into single crystals of calcium fluoride, (9) 447–49.
Piermarini, G. See Block, S.
Pirigyi, F. E. See Hoh, S. R.
Pish, G. See Eichelberger, J. F.
Ploetz, G. L. See Mistler, R. E.
Protti, A. M. See Amato, I.
Pulliam, G. R. Decorated dislocations in magnesia crystals, (5) 202–206.

Rao, Bh. V. J. Influence of TiO_2 on properties of glasses in the system K_2O–PbO–SiO_2–TiO_2 and its relation to structure, (3) 107–14.
Rau, R. C. Electron microscopy of sintered beryllia, (10) 484–88.
Ravitz, S. F. See Hammond, M. L.
Redman, M. J. See Newnham, R. E.
Renkey, A. L. See Ruh, Edwin.
Revesz, A. G., and Zaininger, K. H. An amorphous modification of gallium-arsenic(V) oxide, (12) 606.
Rhinehammer, T. B. See Eichelberger, J. F.
Riboud, P. V., and Muan, Arnulf. Melting relations of CaO-manganese oxide and MgO-manganese oxide mixtures in air, (1) 33–36.
Rigby, G. R., Hutton, R. F., and Hamilton, B. G. Reactions occurring in basic brick, (7) 332–42.
Rindone, G. E. See Stewart, D. R.
Rossi, R. C., and Fulrath, R. M. Epitaxial growth of spinel by reaction in the solid state, (3) 145–49.
Rossington, D. R. See Blank, B.
Rough, F. A. See Klein, M. J.
Roy, Rustum. See Bogardus, E. H Datta, R. K.
Rubin, J. J. See Van Uitert, L. G.
Ruh, Edwin. See Scott, R. K.
Ruh, Edwin, and Renkey, A. L. Thermal conductivity of refractory castables, (2) 89–92.
Ruh, Robert. Reactions of zirconia and titanium at elevated temperatures, (7) 301–307.
Russell, C. K. See Bergeron, C. G.
Ryan, J. R. See Smoot, T. W.

Sanford, E. A. See Carlson, W. A.
Santoro, R. P. See Newnham, R. E.
Sarver, J. F. Comment on note: "Vegard's law and the system alumina-chromia," by R. M. Spriggs and S. L. Bender, (1) 58; Thermal-expansion data for rutile-type GeO_2, (4) 195–96.
Sasaki, Hiromu. See Matsuo, Yoshihiro.
Schatz, E. A. Isomorphous substitution for silicon in fluorphlogopite, (2) 71–73.
Schell, D. C. See Baskin, Y.
Schneider, S. J. Discrepancy in conversion of early melting-point temperatures, (7) 354–55.
Schrey, Frank. See Gallagher, P. K.
Scott, R. K., and Ruh, Edwin. Design and performance of a high-temperature X-ray diffractometer furnace, (11) 513–15.
Scott, W. D., and Pask, J. A. Deformation and fracture of polycrystalline lithium fluoride, (6) 284–93.
Shaffer, P. T. B., and Mark, S. D. Inert-atmosphere dilatometer for use to 2000°C, (2) 104–106; Evidence for high-temperature forms of zirconium and tantalum monocarbides, (4) 177–79.
Shalek, P. D. Preparation and properties of uranium and thorium monosulfides, (4) 155–61.
Shaw, R. R. Rapid orientation of sapphire monocrystals, (4) 184–86.
Simons, C. C. See Klein, M. J.
Sinclair, W. R. See Williams, J. C.
Sinclair, W. R., and Peters, F. G. Preparation of oxide glass films by reactive sputtering, (1) 20–23.
Sjodahl, L. H., and Chandler, B. A. Single-crystal elastic constants of BeO from polycrystalline measurements, (7) 351–52.
Smallman, R. E. See Ashbee, K. H. G.
Smith, D. K., and Cline, C. F. X-ray investigation of polymorphism in ZrC, (11) 566.
Smith, J. A. See Mistler, R. E.
Smoot, T. W., and Ryan, J. R. Initial temperatures of zirconia phase changes and solid-solution reactions, (12) 597–600.
Speidel, D. H., and Muan, Arnulf. System manganese oxide-Cr_2O_3 in air, (12) 577–78.
Spriggs, R. M. See Vasilos, T.
Spriggs, R. M., Brissette, L. A., and Vasilos, T. Preparation of magnesium oxide of submicron grain size and very high density, (10) 508–509.
Spriggs, R. M., and Vasilos, T. Effect of grain size on transverse bend strength of alumina and magnesia, (5) 224–28.
Steneck, W. G. See Brockman, F. G.
Stephens, D. L. See Alford, W. J.
Stewart, D. R., and Rindone, G. E. High-temperature energy relations in borates: Alkaline-earth and lead borate compounds and their glasses, (12) 593–96.
Stiefbold, D. R., Boston, J. R., and Huggins, R. A. New dislocation etchant for magnesium oxide, (10) 507.
Stokes, R. J., and Li, C. H. Dislocations and the tensile strength of magnesium oxide, (9) 423–34.
Subbarao, E. C. See Tien, T. Y.
Sucov, E. W. Diffusion of oxygen in vitreous silica, (1) 14–20; Phonon scattering and glass inhomogeneity, (3) 154.
Swica, J. J. See Chung, Dae-Hyun.

Takamori, Takeshi. Effects of thermomechanical history on properties of glasses, (8) 366–70.
Taylor, R. W. Liquidus temperatures in the system FeO–Fe_2O_3–TiO_2, (6) 276–79.
Thoma, R. E., Insley, Herbert, Hebert, G. M., Friedman, H. A., and Weaver, C. F. Phase equilibria in the system NaF–ThF_4–UF_4, (1) 37–42.
Thomas, G. See Elkington, W. E.
Tien, T. Y., and Carlson, W. G. Influence of oxygen partial pressure on properties of semiconducting barium titanate, (6) 297–98.
Tien, T. Y., and Subbarao, E. C. Grain growth in $Ca_{0.16}Zr_{0.84}O_{1.84}$, (10) 489–92.
Treffner, W. S., and Williams, R. M. Heat evolution tests with calcium aluminate binders and castables, (8) 399–406.
Tucker, P. A. See Eichelberger, J. F.

Vandervoort, R. R., and Barmore, W. L. Compressive creep of polycrystalline beryllium oxide, (4) 180–84.
Van Dreser, M. L., and Boyer, W. H. High-temperature firing of basic refractories, (6) 257–64.
Van Hook, H. J. Phase relations in the garnet region of the system Y_2O_3–Fe_2O_3–FeO–Al_2O_3, (3) 121–24; Influence of oxygen pressure on incongruent melting temperature of yttrium iron garnet, (5) 248.
Van Uitert, L. G. See Grodkiewicz, W. H.
Van Uitert, L. G., Rubin, J. J., and Bonner, W. A. Preparation of single crystals of tungstates and molybdates of a number of divalent metal ions, (10) 512.
Vardi, Joseph. See Hoch, Michael.
Vardi, Joseph, and Hoch, Michael. Thermal conductivity of anisotropic solids at high temperatures—the thermal conductivity of molded and pyrolytic graphites, (3) 129–32.

Vasilos, T. See Gannon, R. E.; Spriggs, R. M.
Vasilos, T., and Spriggs, R. M. Pressure sintering: Mechanisms and microstructures for alumina and magnesia, (10) 493–96.
Vorres, K. S. Estimation of phase diagrams for systems of two binary compounds, (8) 410.
Voruz, T. A., Jewett, R. P., and Accountius, O. E. Direct observation of dislocations in sapphire, (9) 459–60.

Wantman, R. See Waugh, J. S.
Warshaw, I. See Phillips, Bert.
Washburn, J. See Elkington, W. E.
Watts, A. S. Control of the properties of glazes by the aid of eutectics: Part IV, The alkali–B_2O_3–SiO_2 systems; Part V, The system PbO–B_2O_3–SiO_2, (8) 371–73.
Waugh, J. S., Paladino, A. E., diBenedetto, B., and Wantman, R. Effect of dislocations and reduction of single-crystal $SrTiO_3$, (1) 60.
Weaver, C. F. See Thoma, R. E.
Weidel, R. A. See Hamblen, D. P.
Weinland, L. See Blank, B.
White, G. D. See Handwerk, J. H.
Whiteway, S. G. Density and permeability of sintered slip-cast magnesia, (5) 215–18.
Wilcox, D. L., and Cook, R. L. Dielectric behavior in the systems $PbHfO_3$–$BaHfO_3$ and $PbHfO_3$–$SrHfO_3$, (7) 343–48.
Williams, J. C., Sinclair, W. R., and Koonce, S. E. Preparation of thin mullite films, (4) 161–67.
Williams, R. M. See Treffner, W. S.
Wilson, H. H. See Buckley, J. D.
Wittenberg, L. J. See Eichelberger, J. F.
Wolten, G. M. Diffusionless phase transformations in zirconia and hafnia, (9) 418–22.
Woulbroun, J. M. See Kingery, W. D.

Yanese, A. See Kubota, B.
Yust, C. S. See Morgan, C. S.

Zaininger, K. H. See Revesz, A. G.
Zehms, E. H. See McClelland, J. D.

SUBJECT INDEX TO THE JOURNAL

Volume 46, 1963

The reference number in parentheses refers to the *monthly* issue of *The Journal;* the number following is the *page* number.

Acids, salicylic, adsorption on cement compounds, (8) 397.
Adsorption, of admixtures on portland cement, (8) 395.
Akermanite, synthesis from molten PbO, (7) 356.
Alkaline earths, borate compounds, glasses from, (12) 593.
Alumina. See also *Aluminum, oxide; Phase diagrams; Systems.*
cell, for densification experiments, (10) 462.
ceramics, dielectric constant and loss in, correction of paper on, (4) 196.
change in unit-cell dimensions as function of Ti_2O_3 content, (1) 57.
dope, for Ni oxide, (12) 601.
effect of grain boundaries on diffusion-controlled processes in, (3) 133.
hot-pressed, end-point density of, (2) 77.
hot-pressing, mechanisms of material transport, (9) 438.
initial sintering kinetics of, (11) 545.
polycrystalline, creep of, (7) 353.
pressure sintering of, (10) 493.
single crystals, chemical polishing and etching techniques, (4) 193.
transverse bend strength, effect of grain size on, (5) 224.
Aluminum, oxide, effect of grain boundaries on diffusion-controlled processes in, correction, (9) 460; oxide, thermal expansion in air, (8) 383; see also *Alumina.*
Analog, electric, for calculating temperature distribution in glass tanks, (12) 588.
Analysis. See also *Electron diffraction; Microscopy; Thermal analysis; X rays.*
chemical, of ZrC-TaC mixtures, (4) 178.
chromatographic, of $NaPO_3$-NaF glasses, (11) 531.
emission spectrographic, of La and Nd sesquioxides, (11) 562.
spectrochemical, of Ba titanates, (8) 361.
spectrographic, of ZrO_2 and HfO_2, (9) 419.
Annealing, behavior, of SiO_2 glass, (10) 471; of MgO single crystals explosively shocked, (7) 356.
Arsenic, content, effect on durability of As-S glasses, (1) 26; (V) oxide, Ga-, amorphous modification of, (12) 606; see also *Systems.*
Atmospheres, effect on grain growth in calcium zirconate, (10) 492; effect on O-to-metal atom ratios in system UO_2-(Zr,Ca)O, (1) 32.

Barium. See also *Systems.*
titanate, cubic modification, DTA of, (6) 295.
with improved insulation resistance and time constant, (11) 516.
Sm-doped, electrical conduction anomaly in, (1) 48.
semiconducting, effect of O partial pressure on properties, (6) 297.
semiconducting, preparation by chemical methods, (8) 359.
stabilized, for capacitor dielectrics, (5) 197.
titanyl oxalates, substituted, effect of thermal decomposition on semiconducting properties of doped materials, (12) 567.
zirconate, -$PbTiO_3$ ferroelectric ceramics, (3) 141.
Beam-bending apparatus, for determining glass viscosities, (2) 94.
Bentonite, suspensions, rheological factors, (11) 523.
Beryllia. See *Beryllium, oxide.*
Beryllium. See also *Phase diagrams; Systems.*
oxide, diffusion coefficients calculated from creep data, correction of paper, (9) 460.
polycrystalline, compressive creep of, (4) 180.
single-crystal elastic constants, from polycrystalline measurements, (7) 351.
single crystals, growth of, (1) 6.
sintered, electron microscopy of, (10) 484.
thermal conductivity from −200° to 150°C, (3) 150.
Binders, Ca aluminate, and castables, heat evolution tests, (8) 399; synthetic, properties of, (8) 403.
Bonding, ceramic-metal, stable in excess of 2248°K, (5) 244.
Borates, high-temperature energy relations in, (12) 593; Y, crystal structure of, (6) 253.
Boron, oxide, substitution for Al_2O_3 in fluorphlogopite, (2) 72; trioxide, densification as function of pressure, (10) 466; see also *Boron.*

Cadmium, niobate, single crystals, preparation from CdF_2 melt, (11) 563.
Calcium. See also *Phase diagrams; Systems.*
$Ca_{0.15}Zr_{0.85}O_{1.85}$, grain growth in, (10) 489.
diborate, X-ray diffraction data for, (12) 593.
fluoride, single crystals, oxygen penetration into, (9) 447.
hexaluminate, stability relations in system CaO-Al_2O_3-SiO_2, (2) 74.
lignosulfonate, on type I portland cement, (8) 397.
oxide, thermal expansion in air, (8) 383.
Carbon, Pu-, alloys, arc-melted, phase studies on, (2) 80; see also *Phase diagrams; Systems.*
Cathodes, Al-Si alloy, reactive sputtering, (4) 162.
Cement, asbestos portland, steam-cured, microscopy of, (7) 348.
compounds, early stages of paste hydration, II, (4) 187; comment on paper, (9) 459.
portland, adsorption of admixtures on, (8) 395.
portland, early stages of paste hydration, (6) 268.
Cerium. See *Systems.*
Chemical analysis. See *Analysis.*
Chemical properties, of ferrites, relation to coupling coefficient, (4) 168.
Chromium, dioxide, modified ferromagnetic, (11) 550; see also *Phase diagrams; Systems.*
Clays, particle-size analysis, rapid, by packing-volume technique, (1) 1.
Coatings, glass, on metal, study of crystallization, (6) 249; mullite, thin, preparation of, (4) 161; oxide glass, preparation by reactive sputtering, (1) 20.
Cobalt, $CoO·Al_2O_3$, $CoO·Cr_2O_3$, and $2CoO·SiO_2$, stabilities of, (7) 358; see also *Phase diagrams; Systems.*
Compression, assembly, for testing rutile single crystals, (5) 212; orientation of specimens for, (9) 413.
Conductivity, electrical, in Al_2O_3, calculation from diffusion coefficients, (3) 136; anomaly, in Sm-doped $BaTiO_3$, (1) 48.
Conductivity, thermal, of BeO ceramics from −200° to 150°C, (3) 150.
of molded and pyrolytic graphites, (3) 129.
of refractory castables, (2) 89.
of TiC, (5) 245.
of UC, (6) 265.
of ZrO_2-Ti compositions, (7) 306.
Cooling, intermittent, effect on diffusion pattern of spinel, (3) 152.
Copper, -Bi compact, densification during sintering, (8) 393; see also *Phase diagrams; Systems.*
Corrections, on "Effect of grain boundaries on diffusion-controlled processes in aluminum oxide," (9) 460; of paper "Control of dielectric constant and loss in alumina ceramics," (4) 196.
Corrosion, water, data for UO_2-CaO-ZrO_2 composition, (1) 32.
Corundum, crystals, in standardization of quartz powders, (2) 68.
Cracking, micro-, in BeO after creep testing, (4) 183.
Cracks, propagation and arrest, factors affecting, (11) 540.
Creep, of basic refractories, effect of firing temperature, (6) 263.
compressive, of polycrystalline BeO, (4) 180.
high-temperature steady-state, in rutile, (9) 411.
of polycrystalline Al_2O_3, (7) 353.
in polycrystalline oxides, (3) 134.
Cristobalite, quartz-, transformation, geometric model, (4) 192; quartz-, transformation, X-ray study, (2) 66; reactions with alkaline-earth sulfates, (3) 125.
Crushing and grinding, of quartz crystals, effect on peak intensities and background scattering, (2) 67.
Crystal chemistry, of AB_2O_6 compounds, (8) 377.
Crystallites, size, effect on conversion of quartz, (11) 515.
Crystallization, behavior, of lead borate glasses, DTA study of, (5) 246.
of glass coatings on metal, study by electron microscopy, (6) 249.
path, of garnet phase, (3) 124.
re-, in Li metasilicate region of system Li_2O-Al_2O_3-SiO_2 (2) 97.
re-, of MgO crystals explosively shocked, (7) 357.
of reactively sputtered alumina-silica film, effect of heat treatment, (4) 163.
of synthetic mica glass, kinetic studies, (10) 476.
Crystallography, of BeO, (10) 484.
data, for $5NaF·3UF_4$, (6) 281.
data, of system MgO–Ta_2O_5, (4) 175.
data, for YBO_3 and rare-earth borates with pseudovaterite structure, (6) 255.
Crystals, bi-, of NaCl, grain boundaries in, (12) 584.
dislocations, effect on oxidation and reduction of single-crystal $SrTiO_3$, (1) 60.
dislocations, in sapphire, (9) 459.
formation in alite, C_3A, and C_4AF during hydration, (4) 189.
Ge and B phosphate-substituted crystals, optical and X-ray properties, (2) 72.
hopper, formation mechanism in flux systems, (3) 153.
lattice, constants, of CrO_2 modifications, (11) 554.
parameters, of doped and pure NiO, (12) 602.
spacings and relative intensities for perovskite-type compounds, (12) 604.
Li Ti silicate, orientation in crystallized glass nucleated with Pt, (6) 251.
orientation, effect on plastic deformation of MgO, (7) 317.
properties, for NaF-ThF_4 and NaF-UF_4 compounds, (1) 39.

Crystals (*continued*)
single, of AB_2O_4 compounds, preparation, (8) 378.
single, of tungstates and molybdates of divalent metal ions, (10) 512.
structure, of Y and other rare-earth borates, (6) 253.
twinning, in BeO, (10) 488.
whiskers, as platelet support in BeO, (1) 7.

Decomposition, of Mg and Ca sulfates, (3) 127; of synthetic mica glass-ceramic, (10) 480; thermal, of substituted Ba titanyl oxalates, effect on semiconducting properties of doped materials, (12) 567.
Deformation, elastic and plastic, of glasses, effect of thermomechanical history, (8) 370.
plastic, of MgO, effect of crystal orientation, (7) 317.
plastic, of NaCl, effect of grain boundaries, (12) 583.
of polycrystalline LiF, (6) 284.
vs. time, for polycrystalline Al_2O_3, (7) 354.
Densification, of oxide glasses in rigid state, (10) 461.
Density, bulk, of MgO, relation to elastic moduli, (9) 455.
bulk, of slip-cast MgO, effect of sintering time on, (5) 217.
end-point, of hot-pressed alumina, (2) 77.
of glass, effect of heat treatment, (10) 480.
of glass, as function of time, (6) 296.
of magnesia alumina spinel, effect of heating, (2) 106.
of SiO_2 and GeO_2 modifications, relation to refractive index, (10) 464.
of sinterd slip-cast MgO, (5) 215.
-time data, for MgO pressure sintered, (10) 495; (10) 508.
of UO_2 pellets, dependence on sintering temperature, (3) 117.
Destabilization, of zirconia by cyclic heating, (10) 510.
Devitrification, of SiO_2 glass at low temperatures, (10) 476.
Dielectrics. See also *Ferroelectricity and ferroelectric materials.*
behavior, in systems $PbHfO_3$-$BaHfO_3$ and $PbHfO_3$-$SrHfO_3$, (7) 343.
capacitor, stabilized $BaTiO_3$ for, (5) 197.
constant, and loss, in alumina ceramics, correction of paper on, (4) 196.
constant, relative, of $BaTiO_3$, as function of temperature, (11) 517.
data, for lithium silicate glasses, (5) 236.
properties, of glasses in system Nb_2O_5-Na_2O-SiO_2, (2) 85.
Diffraction. See *Electron diffraction; X rays.*
Diffusion, coefficients, in alumina, (7) 353.
on Al_2O_3 and BeO, measured vs. calculated, (3) 134.
in Al_2O_3 and MgO vs. reciprocal temperature, (10) 495.
of BeO, (4) 183.
of CaF_2 oxidized in air, (9) 448.
as mechanism for material transport in contacting spheres, (9) 441.
models, values of constants for, (11) 543.
of oxygen in vitreous silica, (1) 14.
Dilatometers, inert-atmosphere, for use to 2000°C, (2) 104.
Diopside, synthesis from molten PbO, (7) 356.

Elasticity, constants, single-crystal, of BeO, from polycrystalline measurements, (7) 351.
constants, single-crystal, relation to polycrystalline isotropic elastic moduli of MgO, (9) 452.
elastic data, on ThO_2 and UO_2, (1) 46.
moduli, of polycrystalline magnesia alumina spinel, (2) 106.
of polycrystalline materials, effect of porosity on, (11) 564.
Young's modulus, of ZrC with dispersed graphite phase, (2) 103.
Electric properties, of Ge mica, (2) 73; of Li silicate glasses, (5) 235.
Electric resistivity. See *Resistivity.*
Electrodes, sputtering, composition, (1) 21.
Electron diffraction, of gypsum crystal, (6) 271.
Emissivity, spectral, of ZrC and TaC, (4) 179.
Emittance, spectral, of ZrC, (9) 458; of UC, measurement, (6) 265.
Enamels. See *Coatings.*
Energy, activation, for grain-boundary migration in high-purity metals, (10) 492.
activation, for sintering, grain growth, and diffusion in Al_2O_3, (11) 549.
effective and surface, of Th and U dioxides, calculation of, (1) 43.
elastic, at fracture, as design criteria for thermal shock, (11) 535.
high temperature relations in borates, (12) 593.
surface, of quartz, effect of environment, (7) 333.
Entropy of Ca, Sr, and Ba diborates, (12) 594.
Environment, effect on brittle fracture of SiO_2, (7) 329.
Epitaxy in periclase-grown spinel, (3) 148.
Equilibrium studies, acid-base, in system PbO-SiO_2, (2) 61.
of arc-melted Pu-C alloys, (2) 80.
in UO-metal oxide systems, using porous-collector technique, (4) 171.
liquidus relations, in garnet region of system Y_2O_3-Fe_2O_3-FeO-Al_2O_3, (3) 121.
Equilibrium studies (*continued*)
in system CaO–MgO, (7) 313.
in system MgO–Ta_2O_5, (4) 174.
Etchant, dislocation, for MgO, (10) 507.
Etching, chemical, of defect structures in Al_2O_3-rich spinel single crystals, (10) 504; techniques, for Al_2O_3 single crystals, (4) 193.
Eutectics, in control of glaze properties, IV, V, (8) 371.
Expansion, thermal, in air, of ceramic oxides to 2200°C, (8) 381.
of carbides, (2) 105.
data, for rutile-type GeO_2, (4) 195.
of glasses, effect of thermomechanical history, (8) 366.
of glasses in system K_2O–PbO–SiO_2–TiO_2, effect of TiO_2, (3) 109.
linear, of perovskites and apatites, (1) 11.
linear, of scheelite-type compounds, (1) 12.
of lithia aluminosilicates, (2) 100.
of polycrystalline La and Nd sesquioxides, (11) 561.
of PuN, (8) 406.
of UO_2 on melting, (12) 607.
of UP_2O_7 and ceramic bodies in system UO_2-UP_2O_7, (3) 137.

Ferrites, magnetostrictive, with small change in coupling coefficient, (4) 167.
Ferroelectricity and ferroelectric materials, Ba-ZrO_3-$PbTiO_3$, hot-pressed, (3) 141.
Films. See *Coatings.*
Filtration, apparatus, for separation of liquid phase from equilibrium solid phases of fused-salt mixtures, (6) 281.
Firing, high-temperature, of basic refractories, (6) 257.
Flow, model, of bentonite-thickener flow units, (11) 529; stresses, on crystal planes in LiF, (11) 560.
Fluorine, effect on low-temperature sinterability of UO_2, (3) 119; loss, in $NaPO_3$-NaF melts, (11) 533.
Fluorphlogopite, isomorphous substitution for Si in, (2) 71.
Force, coercive, for CrO_2 modifications, (11) 554.
Formation, conditions, of As-S glass, (1) 28; of hopper crystals in flux sytems, (3) 153.
Forsterite, synthesis from molten PbO, (7) 356.
Fracture, brittle, of SiO_2, effect of environment, (7) 329.
of polycrystalline LiF, (6) 284.
surface, of silicate glass, structure in, (2) 102.
surface, of NaCl bicrystal, (12) 585.
Fuels, ceramic nuclear, in system UO_2-ZrO_2-CaO, (1) 29.
Furnaces, crystal joining, (12) 584.
glass tank, calculation of temperature distribution in by special electric analog, (12) 589.
for growth of BeO single crystals, (1) 6.
high-temperature resistance, (4) 178.
high-temperature resistance, for study of system UO_2-PuO_2, (7) 324.
high-temperature X-ray diffractometer, design and performance, (11) 513.
induction, ultra-high-frequency, schematic cross section, (8) 382.
open-hearth, MgO-chrome brick after service in roof, (7) 333.
for porous-collector experiments, (4) 172.
quenching, with controlled atmosphere, (9) 444.
strip-resistance, for determining solidus and liquidus temperatures, (12) 580.
and temperature control, in quenching in system Mn oxide-Cr_2O_3 in air, (12) 577.
vacuum, for heat-treating contacting spheres with coaxial load, (9) 439.
X-ray diffractometer, improved sample holder for, (1) 59.

Gallium, -arsenic (V) oxide, amorphous modification of, (12) 606.
Garnets, Y Qe, effect of O pressure on incongruent melting temperatures, (5) 248.
Germanium, dioxide, high-pressure effects on, (10) 464; oxide, rutile-type, thermal-expansion data for, (4) 195.
Glass, alkaline earth and lead borate, (12) 593.
As-S-I, chemical durability, (1) 24.
boron oxide, densified, annealing of, (10) 473.
Cd borate, X-ray study of, (11) 557.
-cristobalite, determination of residual stresses by transition temperature changes, (12) 574.
effect of very high pressures on, (6) 296.
fibers, equipment for drawing, (1) 16.
formation, in Li metasilicate region of system Li_2O-Al_2O_3-SiO_2, (2) 97.
GeO, films, preparation by reactive sputtering, (1) 23.
high-vanadium, ceramic semiconductors from, (10) 499.
inhomogeneity, and phonon scattering, (3) 154.
lead borate, thermal analysis during crystallization, (5) 246.
Li silicate, structural and electric properties, (5) 235.
mica, synthetic, kinetic study of crystallization, (10) 476.
Nb_2O_5-Na_2O-SiO_2, dielectric properties, (2) 85.
optical, study of surfaces by leaching with nitric acid, I, (6) 273.
oxide, high-pressure effects on, I, (10) 461; II, (10) 470.
K_2O-PbO-SiO_2-TiO_2, effect of TiO_2 on properties and structure, (3) 107.
Glass (*continued*)
properties, effect of thermomechanical history, (8) 366.
silica, annealing behavior, (10) 471.
silica, preparation by reactive sputtering, (1) 22.
silicate, structure in fracture surface, (2) 102.
soda-silica, structure of, (1) 18.
$NaPO_3$-NaF, constitution of, (11) 530.
stannate, films, preparation by reactive sputtering, (1) 23.
in system $NaPO_3$-NaF, infrared spectra of, (11) 558.
viscosity, in range 10^8 to 10^{15} poises, determination by beam-bending method, (2) 93.
Glazes, properties, control by aid of eutectics, IV, V, (8) 371.
Glycerin, bentonite suspensions in, rheology of, (11) 525.
Grain boundaries, effect on diffusion-controlled processes in Al_2O_3, (3) 133; correction, (9) 460; effect on plastic deformation of NaCl, (12) 583.
Grain growth, in $Ca_{0.15}Zr_{0.85}O_{1.85}$, (10) 489; of UO_2, effect of stoichiometry on rate, (8) 407.
Graphites, molded and pyrolytic, thermal conductivity of, (3) 129.
Grease, Bentone, rheology of bentonite suspensions in, (11) 526.
Grinding and polishing, chemical polishing, of Al_2O_3 single crystals, (4) 193; polishing lines, on optical glass surfaces, (6) 273.
Grinding and polishing apparatus, for polishing MgO crystals, (7) 308.
Gypsum, needle crystals, in rapid-hardening cement, (6) 270.

Hafnium, oxide, diffusionless phase transformations in, (9) 418.
Halides, -cristobalite, determination of residual stresses by transition temperature changes, (12) 574.
Hardness, changes, in MgO single crystals explosively shocked, (7) 357; micro-, of Ti and ZrO_2 phases, (7) 305.
Heat. See also *Conductivity, thermal; Temperature.*
evolution, with Ca aluminate binders and castables, (8) 399.
of solution, and heat content, of alkaline earth and lead borate glasses, (12) 594.
treatment, effect on synthetic mica glass, (10) 478.
treatment, of hot-pressed MgO, effect on tensile strength, (9) 431.
Heaters, ceramic, for cyclic heating of ZrO_2, (10) 510.
Heating, cyclic, in destabilization of ZrO_2, (10) 510.
radiation, thermal shock by, (5) 229.
Holmium, sesquioxide, infrared absorption spectrum of, (6) 294.
Hydration, balance, diagram of, (11) 520.
of cements, heat effects on, (8) 400.
paste, of cement compounds, early stages of, II, (4) 187; comment on paper, (9) 459.
early stages, of portland cements, (6) 268.
vapor-phase, of MgO, kinetics of, (11) 518.
Hydrogen ion concentration, effect on chemical durability of As-S-I glasses, (1) 26.

Ice, -methanol compacts, densification during pressing, (8) 394.
Insulation, thermal, castables, thermal conductivity of, (2) 92.
Iodine, content, effect on durability of As-S-I glasses, (1) 26; see also *Systems.*
Iron, ions, diffusion into MgO single crystals, (5) 202; Fe^{+3}, effect in system $SrFeO_3$-$SrTiO_3$, (5) 207; in manganese ferrite, valence changes of, (9) 442; see also *Phase diagrams; Systems.*
Irradiation, of metal-fiber-reinforced ThO_2-UO_2, (5) 219.

Kinetics, of crystallization of synthetic mica glass, (10) 476.
initial sintering, of Al_2O_3, (11) 545.
of quartz transformation, (2) 69.
solid-state reaction, equations and tables for analyzing, (8) 374.
of vapor-phase hydration of MgO, (11) 518.

Lanthanum, sesquioxide, polycrystalline, thermal expansion of, (11) 561; see also *Systems.*
Leaching, nitric acid, effect on optical glass surfaces, (6) 273.
Lead. See also *Systems.*
borate compounds, glasses from, (12) 593.
compounds, dilatometric and X-ray data, II, (1) 10.
oxide, molten, synthesis of forsterite, diopside, akermanite, and wollastonite from, (7) 356.
PbO solid solution with $PbTiO_3$, crystallography of, (8) 409.
titanate, $BaZrO_3$-, ferroelectric ceramics, (3) 141.
Liquidus, data, for CaO-MgO, (7) 314; diagram, of system Li_2MoO_4·1.25MoO_3-BeO, (1) 8.
Lithium. See also *Phase diagrams; Systems.*
aluminate, phase transitions in, (8) 388.
fluoride, flow stresses on crystal planes and plasticity of polycrystals, (11) 560.
fluoride, polycrystalline, deformation and fracture, (6) 284.
metasilicate, region, of system Li_2O-Al_2O_3-SiO_2, glass formation and recrystallization in, (2) 97.

Magnesia. See also *Magnesium, oxide; Phase diagrams; Systems.*
crystals, decorated dislocations in, (5) 202.
damage from moving dislocations in, (7) 307.
pressure sintering of, (10) 493.
single-crystal elastic constants, relation to polycrystalline isotropic elastic moduli, (9) 452.
single crystals, explosively shocked, structure and annealing behavior, (7) 356.
sintered slip-cast, density and permeability, (5) 215.
transverse bend strength, effect of grain size on, (5) 224.
Magnesiowüstite, spacing of prismatic loops in, (5) 205.
Magnesium, oxide. See also *Magnesia.*
dislocation etchant for, (10) 507.
dislocations and tensile strength, (9) 423.
effect of crystal orientation on plastic deformation, (7) 317.
kinetics of vapor-phase hydration of, (11) 518.
of submicron grain size and high density, (10) 508.
thermal expansion in air, (8) 383.
Magnetic properties, reciprocal susceptibility, of $ErBO_3$, temperature dependence, (6) 256.
Magnetization, saturation, of CrO_2 modifications, (11) 554.
Manganese, in manganese ferrite, valence changes of, (9) 442; see also *Phase diagrams; Systems.*
Melting, behavior, in system UO_2-PuO_2, (7) 323.
points, early, discrepancy in conversion of, (7) 354.
points, of US-ThS solid solutions, (4) 159.
relations, of CaO-manganese oxide and MgO-manganese oxide mixtures in air, (1) 33.
temperature, incongruent, of Y Fe garnet, effect of O pressure, (5) 248.
Melts, PbO-SiO_2, activities in, (2) 63.
Metals, glass coatings on, study of crystallization, (6) 249; ions, divalent, preparation of single crystals of tungstates and molybdates of, (10) 512.
Mica, Ge, electrical properties of, (2) 73; glass, synthetic, kinetic study of crystallization, (10) 476.
Micrographs, electron, of CrO_2 modifications, (11) 552.
Micrography, of UO_2 pellets, (3) 118.
Microscopes, electron, Pt specimen support in, (4) 163.
Microscopy, electron, of BeO, preparation of sections, (10) 485.
of sintered BeO, (10) 484.
in study of crystallization of glass coatings on metal, (6) 249.
of steam-cured asbestos portland cement products, (7) 348.
Models, mechanical, proposed, for effect of porosity on strength, (11) 565.
Molybdates, of divalent metal ions, preparation of single crystals, (10) 512.
Molybdenum, fibers, in UO_2, (5) 223; see also *Systems.*
Mullite, crystal habit, effect of method of preparation, (4) 167; films, thin, preparation of, (4) 161.

Neodymium, sesquioxide, polycrystalline, thermal expansion of, (11) 561.
Nickel, oxide, Al_2O_3-doped, structure of, (12) 601; oxide, high-temperature loss, (12) 580; see also *Phase diagrams; Systems.*
Niobium, oxide, effect on dielectric properties of glasses in system Nb_2O_5-Na_2O-SiO_2, (2) 85; see also *Phase diagrams; Systems.*
Nitric acid, leaching, effect on optical glass surfaces, (6) 273.
Nucleation, crack, of MgO bicrystals under compression, (9) 428; frequency, in synthetic mica glass, (10) 479; of pairs at grown-in dislocations in MgO crystals, (7) 312.

Optical properties, of Ge and B phosphate-substituted crystals, (2) 72; of $NaF \cdot 4UF_4$, (6) 283; of uniaxial sapphire crystals, (4) 185.
Orientation, data, for slip systems in individual LiF grains, (6) 290; rapid, of sapphire monocrystals, (4) 184.
Oxidation, rates, for commercial uranium oxide lots, (3) 115; of $SrTiO_3$, single-crystal, effect of dislocations, (1) 60.
Oxides, ceramic, thermal expansion in air to 2200°C, (8) 381.
Oxygen. See also *Systems.*
diffusion, in vitreous silica, (1) 14.
penetration, into single crystals of CaF_2, (9) 447.
pressure, effect on incongruent melting temperature of Y Fe garnet, (5) 248.
effect on properties of Mn ferrite, (9) 445.
(partial), effect on properties of semiconducting $BaTiO_3$, (6) 297.

Packing-volume technique, for rapid particle-size analysis of clays, (1) 1.
Particle size, analysis, rapid, of clays by packing-volume technique, (1) 1.
determinations, of La-doped $BaTiO_3$, (12) 570.
distribution, of sintered slip-cast MgO, (5) 216.
effect on conversion of quartz, (11) 515.
effect on transverse bend strength of Al_2O_3 and MgO, (5) 224.
Particle size (*continued*)
of quartz crystals, effect on peak intensities and background scattering, (2) 67.
submicron, of MgO, (10) 508.
of UO_2 sintered in two stages, (3) 119.
Periclase, crystals, in standardization of quartz powders, (2) 68.
Permeability, of sintered slip-cast MgO, (5) 215.
Perovskites, in system $SrFeO_3$-$SrTiO_3$, properties of, (5) 208; -type compounds A_2BTeO_6, (12) 604.
Phase diagrams, of CuO-Al_2O_3 and Cu_2O-Al_2O_3, (10) 509.
of system Al_2O_3-Nb_2O_5, (10) 506.
CaO-Al_2O_3-SiO_2, revision, (2) 76.
CaO-MgO, (7) 314.
CaO-Mn oxide and MgO-Mn oxide, in air, (1) 35.
CaO-ZrO_2, (1) 30.
Co oxide-Mn oxide, (10) 511.
FeO-Fe_2O_3-TiO_2, (6) 278.
Li_2O-Al_2O_3-SiO_2, after crystallization of glasses, (2) 99.
MgO-Ta_2O_5, preliminary, (4) 175.
Mn oxide-Cr_2O_3 in air, (12) 578.
NiO-Al_2O_3-SiO_2, (12) 580.
Pu-C, (2) 81.
NaF-BeF_2-UF_4, (6) 282.
NaF-ThF_4 and NaF-UF_4, (1) 38.
NaF-ThF_4-UF_4, (1) 39.
NaF-UF_4, (6) 280.
of two binary compounds, estimation of, (8) 410.
UO_2-ZrO_2, (1) 29.
Y_2O_3-Fe_2O_3-FeO-Al_2O_3, (3) 122.
tentative, of CaO-Mn oxide and MgO-Mn oxide above 1000°C, (1) 36.
Phonons, scattering, and glass inhomogeneity, (3) 154.
Photomicrography, of quartz-cristobalite transformation, (2) 70.
Physical properties, of ferrites, relation to coupling coefficient, (4) 168.
Piezoelectricity, data, for $BaZrO_3$-$PbTiO_3$ ceramics, (3) 144.
Plasticity, in LiF, as-cut single-crystal, (6) 286; of LiF polycrystals, (11) 560.
Plutonium, carbide, lattice constants of, (2) 84; -C alloys, arc-melted, phase studies on, (2) 80; nitride, thermal expansion of, (8) 406; see also *Phase diagrams; Systems.*
Polarization, saturation, in $BaTiO_3$, relation to resistivity, (1) 52.
Polymorphism, in ZrC, X-ray study of, (11) 566.
Porcelain, high-alumina, material properties of, (5) 233; high-alumina, thermal properties of, (9) 436.
Porosity, of Al_2O_3 and MgO, relation to grain size, (5) 228; of polycrystalline materials, effect on strength and Young's modulus, (11) 564.
Potassium. See also *Systems.*
Powder, compacts, initial stage sintering models, application to shrinkage of, (11) 541.
Pressing, hot, of alumina, mechanisms of material transport in, (9) 441.
Pressure, applied, effect on densification during sintering in presence of liquid phase, (8) 391.
effect on density of hot-pressed Al_2O_3, (2) 78.
high, effect on glass, (6) 296.
high, effect on oxide glasses, I, (10) 461; II, (10) 470.
negative and positive, effect on transition temperatures in two phase systems, (12) 573.
water vapor, of hydrated MgO, dependence of reaction rate on, (11) 522.

Quartz, conversion, factors affecting, (11) 515; -cristobalite transformation, geometric model, (4) 192; -cristobalite transformation, X-ray study, (2) 66.

Rare earths, oxides, infrared absorption spectra of, (6) 294.
Recrystallization. See *Crystallization.*
Reduction, of $SrTiO_3$, single-crystal, effect of dislocations, (1) 60.
Refractive index, of glass, change after heat treatment, (10) 480; of SiO_2 and GeO_2 modifications, relation to density, (10) 464; of spinel specimens, changes in, (3) 152.
Refractories, basic, brick, reactions in, (7) 332.
basic, high-temperature firing of, (6) 257.
castable, thermal conductivity of, (2) 89.
chromite, effect of grain size, (6) 261.
melting point temperatures, discrepancy in conversion of, (7) 354.
Resistivity, electric, of $BaTiO_3$, as function of temperature, (11) 517.
of high-V glasses, effect of composition, (10) 501.
of La-doped $BaTiO_3$, (8) 360.
of La-doped $BaTiO_3$, as function of temperature, (12) 570.
of Sm-doped $BaTiO_3$, (1) 50.
of UC, (6) 265.
of ZrC, (9) 458.
Rheology, factors, for bentonite suspensions, (11) 523.
Rupture, modulus, of chromite refractory, effect of firing temperature, (6) 260.
Rutile, high-temperature steady-state creep in, (9) 411; see also *Titanium, dioxide.*

Sapphire, dislocations in, direct observation of, (9) 459; monocrystals, rapid orientation, (4) 184.
Semiconductors, ceramic, preparation from high-V glasses, (10) 499.
Shear, role in densification of rigid glass, (10) 469.
Shock, thermal, analysis of spherical shapes, II, (9) 434.
effect on crystallized glass, (6) 252.
elastic energy at fracture and surface energy as design criteria for, (11) 535.
by radiation heating, (5) 229.
Shrinkage, equations, for Al_2O_3 compacts, reconsideration, (11) 541; studies, Al_2O_3 powders used in, (11) 546; of UO_2 during solidification, (12) 607.
Silica. See also *Phase diagrams; Systems.*
effect on hot modulus of rupture of chromite refractory, (6) 261.
fused, densification as function of pressure, (10) 462.
fused, in high pressure tests, (6) 296.
melts, with alkali oxides, (2) 61.
reaction with alkaline-earth sulfates, (3) 127.
vitreous, oxygen diffusion in, (1) 14.
Silicon, carbide, whiskers, (6) 299; isomorphous substitution in fluorphlogopite, (2) 71; see also *Systems.*
Silver, chloride, cell, for densification experiments, (10) 462.
Sintering, of Al_2O_3, (3) 135.
behavior, of U and Th monosulfides, (4) 156.
diffusion, I, (11) 541; II, (11) 545.
low-temperature, of UO_2, (3) 114.
models, (11) 542.
of powdered materials containing liquid phase effect of applied pressure, (8) 391.
pressure, of Al_2O_3 and MgO, (10) 493.
of NaCl, (11) 559.
solid-state, of anorthite and CaO $6Al_2O_3$, (2) 75.
time, effect on permeability of slip-cast MgO, (5) 216.
of zinc oxide, (9) 449.
Sodium. See also *Phase diagrams; Systems.*
chloride, effect of grain boundaries on plastic deformation, (12) 583.
sintering of, (11) 559.
structure, numbering of slip systems in, (6) 291.
-water compacts, densification during sintering, (8) 393.
Solids, anisotropic, thermal conductivity at high temperatures, (3) 129.
Solid state, reaction, in epitaxial growth of spinel, (3) 145; reaction kinetics, equations and tables for analyzing, (8) 374.
Solutions, solid, Al_2O_3-TiO_2, (1) 54.
data, for CaO-MgO, (7) 314.
limits, for U_3O_8-ZrO_2-CaO mixtures, (1) 31.
of Ni aluminate in NiO at 1300°C, (12) 603.
US-UN, lattice parameters of, (4) 159.
Spectra, infrared, of glasses in system $NaPO_3$-NaF, (11) 558.
infrared absorption, of α-quartz, α-cristobalite, fused silica, and densified SiO_2 glass, (10) 464.
of $LiAl_5O_8$, (8) 389.
of rare-earth oxides, (6) 294.
Spectrography, of ZrC-TaC mixtures, (4) 178.
Spectroscopy, of $BaTiO_3$, (5) 198.
Spheres, fractured by thermal shock, prediction of type of failure, (11) 540; micro-, ZnO, sintering of, (9) 450; thermal shock analysis of, II, (9) 434.
Spinel, as bond in chromite refractories, effect on properties, (6) 262.
epitaxial growth by solid state reaction, (3) 145.
germanate, synthesis of, (8) 408.
made by vapor transport and diffusion in system MgO-Al_2O_3, III, (3) 152.
magnesia alumina, polycrystalline, elastic moduli of, (2) 106.
Mg aluminate, hot-pressed, microstructure of, (8) 386.
single crystals, Al_2O_3-rich, chemical etching of defect structures in, (10) 504.
Sputtering, multielectrode, in preparation of glass films, (1) 23; reactive, in preparation of oxide glass films, (1) 20.
Stability, of CoO-Al_2O_3, CoO-Cr_2O_3, and 2CoO-SiO_2, (7) 358; relations, of Ca hexaluminate in system CaO-Al_2O_3-SiO_2, (2) 74.
Stoichiometry, effect on rate of grain growth of UO_2 (8) 407.
Strength, tensile, apparatus for determining, (7) 330.
of MgO, relation to dislocations, (9) 423.
measurements in SiC whiskers, (6) 299.
transverse bend, of Al_2O_3 and MgO, effect of grain size, (5) 224.
Stress, critical shear, for hot-pressed Al_2O_3, Arrhenius plot, (2) 79.
relaxation, for Bentone-grease system, (11) 527.
residual, in two phase systems, determination by transition temperature changes, (12) 573.
-strain behavior, of TiO_2 single crystals, (5) 211.
-strain curves, for MgO, (7) 318.
for MgO crystals, (9) 424.
for single-crystal LiF, (6) 287.
Strontium, diborate, X-ray diffraction data for, (12) 593; $Sr(Fe_{1-x}Ti_x)O_3$, magnetic and electric properties, (5) 208; titanate, single-crystal, effect of dislocations on oxidation and reduction, (1) 60; see also *Systems.*
Structure, in fracture surface of silicate glass, (2) 102.
of Li silicate glasses, (5) 235.

Structure (*continued*)
of MgO single crystals explosively shocked, (7) 356.
of mica glass, effect of heat treatment, (10) 479.
micro-, of basic refractories, (6) 258.
of BeO, (4) 181.
of hot-pressed MgO in air, (8) 385.
of MgO crystals, (9) 430.
of pores in BeO, (10) 485.
of pressure-sintered Al_2O_3 and MgO, (10) 493.
of Sm-doped $BaTiO_3$, (1) 50.
of sintered $Ca_{0.16}Zr_{0.84}O_{1.84}$, (10) 490.
of nickel oxide, Al_2O_3-doped, (12) 601.
of pyrolytic TiB_2, (10) 498.
Sulfates, alkaline-earth, reactions with cristobalite (3) 125.
Sulfur. See *Systems.*
Surface, condition, of hot-pressed MgO, effect on tensile strength, (9) 431.
Synthesis, of forsterite, diopside, akermanite, and wollastonite from molten PbO, (7) 356; pyrolytic, of TiB_2, (10) 496.
Syatems, Al_2O_3-Cr_2O_3, applicability of Vegard's law, comment on note, (1) 58; comment on comment, (5) 247.
Al_2O_3-Nb_2O_5, compounds in, (10) 506.
As-S-I, glass-forming region in, (1) 25.
$BaTiO_3$-La_2O_3·$3TiO_2$, electronic phenomena in, (5) 199.
$BaZrO_3$-$PbTiO_3$, unit-cell parameters and axial ratio vs. composition, (3) 143.
BeO-metal oxide, phase studies using porous-collector technique, (4) 171.
CaO-MgO, liquidus, solidus, and subsolidus, (7) 313.
CaO-Mn oxide, melting relations in air, (1) 33.
CaO-ZrO_2, temperature of solid solution reactions, (12) 600.
CeO_2-ZrO_2, temperature of solid solution reactions, (12) 599.
cobalt oxide-manganese oxide, phase relations in air, (10) 511.
CuO-Al_2O_3, phase equilibrium study, (10) 509.
flux, mechanism for formation of hopper crystals in, (3) 153.
Fe-Mn-O, isothermal section at 1330°C, (9) 445.
FeO-Fe_2O_3-TiO_2, liquidus temperatures in, (6) 277.
$PbHfO_3$-$BaHfO_3$, and $PbHfO_3$-$SrHfO_3$, dielectric behavior in, (7) 343.
PbO-B_2O_3-SiO_2, solubility of glasses in, (8) 373.
PbO-SiO_2, acid-base equilibria in, (2) 61.
PbO-TeO_2, glasses in, (1) 21.
PbO-TiO_2, PbO-rich side, (8) 409.
PbO-ZnO, suggested equilibrium diagram, (5) 243.
$LiAlGeO_4$-Zn_2GeO_4, subsolidus equilibrium data in, (8) 408.
Li_2MoO_4·1.25MoO_3-BeO, approximate liquidus diagram, (1) 8.
Li_2O-Al_2O_3-SiO_2, glass formation and recrystallization in Li metasilicate region, (2) 97.
Li_2O-Al_2O_3-SiO_2, proposed liquidus relations in, (2) 100.
Li_2O-B_2O_3-SiO_2, solubility and fusion behavior of glasses in, (8) 371.
MgO-Al_2O_3, spinel made by vapor transport and diffusion in, III, (3) 152.
MgO-Mn oxide, melting relations in air, (1) 33.
MgO-Ta_2O_5, preliminary phase diagram of, (4) 175.
MgO-ZrO_2-BeO, temperature of first melting in, (4) 173.
Mn oxide-Cr_2O_3, in air, (12) 577.
NiO-Al_2O_3-SiO_2, phase equilibria in, (12) 579.
phosphate-halide, I, (11) 530; II, (11) 558.
Pu-C, phase diagram, (2) 81.
PuO_2-ZrO_2, potential nuclear fuels in, (4) 194.
K_2O-B_2O_3-SiO_2, solubility and fusion behavior of glasses in, (8) 371.
K_2O-PbO-SiO_2-TiO_2, glasses in, effect of TiO_2 on properties and structure, (3) 107.
NaF-BeF_2-UF_4, fused-salt, phase equilibria for, (6) 279.
NaF-ThF_4-UF_4, phase equilibria in, (1) 37.
Na_2O-B_2O_3-SiO_2, solubility and fusion behavior of glasses in, (8) 372.
$NaPO_3$-NaF, infrared spectra of glasses in, (11) 558.
$SrFeO_3$-$SrTiO_3$, effect of Fe^{4+} in, (5) 207.
of two binary compounds, estimation of phase diagrams for, (8) 410.

Systems (*continued*)
two phase, determination of residual stresses by transition temperature changes, (12) 573.
UO_2-PuO_2, melting behavior in, (7) 323.
UO_2-UP_2O_7, thermal expansion of ceramic bodies in, (3) 137.
UO_2-ZrO_2-CaO, ceramic nuclear fuels in, (1) 29.
Y_3O_5-Fe_2O_3-FeO-Al_2O_3, phase relations in garnet region, (3) 121.
ZrO_2-BeO, porous-collector experiments in, (4) 172.
ZrO_2-Y_2O_3, temperature of solid solution reactions, (12) 597.

Tantalum, bonding with ZrO_2, for high-temperature stability, (5) 244; monocarbide, high-temperature forms, (4) 177; see also *Phase diagrams; Systems.*
Tellurium, in CrO_3, effect on decomposition temperature, (11) 551; -trirutiles, existence of, (12) 604; see also *Systems.*
Temperature, Curie, of CrO_2 modifications, (11) 554.
dependence, of lattice constants of $BaTiO_3$, (1) 53.
distribution, in glass tanks, calculation by special electric analog, (12) 588.
effect on, density of hot-pressed Al_2O_3, (2) 78.
dislocation substructure in MgO, (7) 310.
solid-state reaction kinetics, (8) 376.
gradients, radial, for graphites, (3) 130.
homogenization, effect on composition and volatility of US, (4) 156.
initial, of ZrO_2 phase changes and solid solution reactions, (12) 597.
liquidus, in system FeO-Fe_2O_3-TiO_2, (6) 276.
melting-point, early, discrepancy in conversion of, (7) 354.
test, effect on chemical durability of As-S and As-S-I glasses, (1) 27.
Thermal analysis, data, of Ba titanyl oxalates, (12) 568.
differential, of $BaTiO_3$ cubic modification, (6) 295.
differential, of US and ThS in dynamic air, (4) 160.
of lead borate glasses during crystallization, (5) 246.
Thermal properties, of high-alumina porcelain ceramic, (9) 436; of low-melting As-S-I glasses, (1) 25.
Thermobalances, with radiation and convection shield assembly, (9) 443.
Thermophysical properties, high-temperature, of UC, (6) 264.
Thickness, film, effect on progressive crystallization of alumina-silica film, (4) 164.
Thorium, dioxide, calculation of cohesive and surface energy, (1) 43; monosulfide, preparation and properties, (4) 155; oxide, -UO_2, metal-fiber-reinforced, irradiation of, (5) 219; see also *Phase diagrams; Systems.*
Thulium, borate, X-ray diffraction data, (6) 254.
Time, constants, of $BaTiO_3$, as function of temperature, (11) 517.
dependence, of density of hot-pressed Al_2O_3, (2) 78.
effect on chemical durability of As-S-I glasses, (1) 26.
effect on diffusion pattern of spinel, (3) 152.
Titania, effect on glass properties in system K_2O-PbO-SiO_2-TiO_2, (3) 107; see also *Phase diagrams; Systems.*
Titanium. See also *Phase diagrams; Systems.*
carbide, thermal conductivity of, (5) 245.
diboride, pyrolytic synthesis of, (10) 496.
dioxide, single crystals, stress-strain behavior, (5) 211; see also *Rutile.*
excess, effect on properties of semiconducting titanates, (8) 363.
and ZrO_2, reactions at high temperatures, (7) 301.
Titration, of SO_2, apparatus for, (3) 126.
Transmission, specimen preparation, (7) 308; spectral, of high-V glasses, (10) 503.
Tridymite, hexagonal structures related to, (8) 378.
Tungstates, of divalent metal ions, preparation of single crystals, (10) 512.

Uranium. See also *Phase diagrams; Systems.*
dioxide, calculation of cohesive and surface energy, (1) 43.
effect of stoichiometry on rate of grain growth, (8) 407.

Uranium, carbide (*continued*)
low-temperature sintering, (3) 114.
thermal expansion and volume change on melting, (12) 607.
monocarbide, high-temperature thermophysical properties of, (6) 264.
monosulfide, preparation and properties, (4) 155.
pyrophosphate, thermal expansion of, (3) 137.
in transformation of quartz, (2) 69.

Valence, changes, of Fe and Mn in manganese ferrite, (9) 442.
Vanadium, V_2O_5/metaphosphate compositions, (10) 500.
Vapors, effect on surface energy of quartz and fracture strength of SiO_2 rods, (7) 331.
Vegard's law, relation to system alumina-chromia, comment on note, (1) 58; comment on comment, (5) 247.
Viscosity, of glass, in range 10^8 to 10^{15} poises, determination by beam-bending method, (2) 93; non-Newtonian, in bentonite suspensions, (11) 528; of synthetic mica glass, (10) 477.
Volume, changes, in basic brick, (7) 338; changes, on melting of UO_2, (12) 607.

Water, attack, of glasses in system K_2O-PbO-SiO_2-TiO_2, (3) 110.
Weight, loss, of $NaPO_3$-NaF glasses vs. melting time, (11) 533.
Whiskers (crystalline), of SiC, (6) 299.
Wollastonite, synthesis from molten PbO, (7) 356.

X rays, constants, of Sm-doped $BaTiO_3$, (1) 50.
data, semiquantitative, for Li_2O-Al_2O_3-SiO_2 glasses, (2) 100.
data, for synthetic mica glass with various heat treatments, (10) 480.
diffraction, in identification of hydrated compounds, (6) 269.
diffraction data, for compounds with apatite-type structure, (1) 12.
for compounds with perovskite-type structure, (1) 11.
for cubic UP_2O_7, (3) 139.
for 2PbO·GeO_2 and PbO·Al_2O_3, (1) 14.
for $PbWO_4$ and $PbMoO_4$, (1) 13.
for NaF·$4UF_4$, (6) 283.
for Sr diborate, Ca diborate, (12) 593.
for synthesized germanate spinels, (8) 408.
for YBO_3 and $TmBO_3$, (6) 254.
diffraction patterns, of CrO_2, (11) 553.
diffraction powder data, for compounds in system Al_2O_3-Nb_2O_5, (10) 506.
phase analysis, of CaO·$6Al_2O_3$, (2) 75.
powder data, for $BaAl_2O_4$-type compounds, (8) 379.
powder diffraction data, for Mg-Ta_2O_5 compounds, (4) 176.
powder patterns, of I, II, and II-metastable forms of $LiAlSi_2O_6$, (8) 389.
properties, of Ge and B phosphate-substituted crystals, (2) 72.
study, of Cd borate glass, (11) 557.
of polymorphism in ZrC, (11) 566.
of quartz-cristobalite transformation, (2) 66.

Young's modulus. See *Elasticity.*
Yttrium, borate, crystal structure, (6) 253; see also *Phase diagrams; Systems.*

Zinc, oxide, sintering of, (9) 449; see also *Systems.*
Zirconia. See also *Phase diagrams; Systems.*
analysis of, (4) 195.
bonding with Ta for high-temperature stability (5) 244.
compositions, CaO-stabilized, (1) 30.
destabilization by cyclic heating, (10) 510.
diffusionless phase transformations in, (9) 418.
phase changes, and solid solution reactions, initial temperatures of, (12) 597.
and Ti, reactions at high temperatures, (7) 301.
Zirconium. See also *Phase diagrams; Systems.*
carbide, with dispersed graphite phase, Young's moduli of, (2) 103.
carbide, X-ray study of polymorphism in, (11) 566.
monocarbide, high-temperature forms, (4) 177.
monocarbide, phase change in ,(9) 457.

Cumulative Index Available 1918–1955

A complete cumulative index to the Journal of The American Ceramic Society, and The Ceramic Bulletin from their beginnings through 1955, is available from The American Ceramic Society, 4055 N. High St , Columbus 14, Ohio, at $5 a copy. It includes 16,803 references in the subject index and 6288 in the index to authors.

JOURNAL
of the
American Ceramic Society

A MONTHLY PUBLICATION DEVOTED TO THE ARTS AND SCIENCES RELATED TO THE SILICATE INDUSTRIES

VOLUME 46, 1963

Charles S. Pearce, *Editor*
Herbert Insley, *Consulting Editor*
Virginia Benedict, *Assistant Editor*
Margie K. Reser, *Assistant Editor*
M. Geraldine Smith, *Assistant Editor*
Olive Scott, *Editorial Assistant*

Committee on Publications: W. J. Smothers, *Chairman;* Paul R. Jones, Edward E. Mueller, and Howard F. McMurdie

Executive, Editorial, and Advertising Offices: **4055 North High Street, Columbus 14, Ohio**
Publication Office: **Easton, Pennsylvania**

Officers of The American Ceramic Society

1963–1964

Society Officers

President: PAUL V. JOHNSON
Structural Clay Products Research Foundation, Geneva, Ill.
President-Elect: ELBURT F. OSBORN, 207 Old Main
Pennsylvania State University, University Park, Pa.
Vice-Presidents:
HOWARD P. BONEBRAKE, Aluminum Co. of America
1501 Alcoa Bldg., Pittsburgh 19, Pa.
CLAIR R. OBERST, Industrial Ceramic Products, Inc.
965 W. Fifth Ave., Columbus 12, Ohio
JAMES S. OWENS, Champion Spark Plug Co., Ceramic Div.
3525 Butler Ave., Detroit 11, Mich.
Treasurer: HENRY H. BLAU, Dept. of Ceramic Engineering
Ohio State University, 124 W. 17th Ave., Columbus 10, Ohio
General Secretary: FRANK P. REID
American Ceramic Society
4055 N. High St., Columbus 14, Ohio
Past-President: JOHN H. KOENIG
Rutgers, The State University, School of Ceramics
New Brunswick, N. J.
Past-President: JOHN S. NORDYKE, 440 Sulgrave Rd.
Pittsburgh 11, Pa. (Hammond Lead Products, Inc.)

Division Officers

Basic Science Division

Trustee: HOWARD F. MCMURDIE (1966)
National Bureau of Standards, Washington 25, D. C.
Chairman: IVAN B. CUTLER, 220 Mines Bldg.
University of Utah, Salt Lake City 12, Utah
Chairman-Elect: J. H. WESTBROOK. General Electric Co.
Research Lab., Room 3C2, Schenectady, N. Y.
Vice-Chairman: JOHN B. WACHTMAN, JR.
National Bureau of Standards, Washington 25, D. C.
Secretary: ALBERT E. PALADINO, JR., Raytheon Co.
Solid State Physics Group, 28 Seyon St., Waltham 54, Mass.

Ceramic-Metal Systems Division

Trustee: BENJAMIN J. SWEO (1964)
Ferro Corp., 4150 E. 56th St., Cleveland 5, Ohio
Chairman: GEORGE WARREN
Pfaudler-Permutit, Inc., 1000 West Ave., Rochester 3, N. Y.
Vice-Chairman: GRANT E. MILLER
Ferro Corp., 4150 E. 56th St., Cleveland 5, Ohio
Secretary: JESSE D. WALTON, JR., 2080 Fairway Circle N. E.
Atlanta 19, Ga. (Georgia Institute of Technology)

Design Division

Trustee: JULES R. GULDEN (1964)
Syracuse China Corp., Syracuse 1, N. Y.
Chairman: J. RUSSELL PRICE, Fairmeadows, Box 324
R.R. 3, Esmond 17, R. I. (Doulton & Co., Inc.)
Vice-Chairman: ALFRED DUBE
425 11th St., Lincoln, Ill. (Stetson Corp.)
Vice-Chairman: ROBERT TURNER
Alfred University, Alfred, N. Y.
Secretary: VIVIKA P. HEINO, Briar Hill Rd., R. R. 1
Concord, N. H (Rhode Island School of Design)

Electronics Division

Trustee: WILLIAM W. COFFEEN (1966)
73 Ellisen Rd., Watchung, N. J. (M & T Chemicals, Inc.)
Chairman: WILLARD E. HAUTH, JR , 1218 Blanchard Ave.
Flint 3, Mich. (AC Spark Plug Div., General Motors Corp.)
Vice-Chairman: ALEXIS G. PINCUS, General Electric Co.
Research Lab., Box 1088, Schenectady, N. Y.
Secretary: SEYMOUR BLUM
Raytheon Co., Research Div., Waltham 54, Mass

Glass Division

Trustee: NORBERT J. KREIDL (1965)
Bausch & Lomb, Inc., Rochester 2, N. Y.
Chairman: FRED W. MOWREY, 4312 Fairlawn Dr.
Kingsport, Tenn. (American-Saint Gobain Corp.)
Vice-Chairman: ROBERT D. MAURER
Corning Glass Works, Corning, N. Y.
Second Vice-Chairman: HAROLD E. SIMPSON
Alfred University, Alfred, N. Y.
Secretary: FAY V. TOOLEY, 611 W. Oregon
Urbana, Ill. (University of Illinois)

Materials & Equipment Division

Trustee: SCROOP W. ENLOE, JR. (1966)
Harris Clay Co., Spruce Pine, N. C.
Chairman: JOHN MCLAREN
Box 75, East Liverpool, Ohio (Bell Operations)
Chairman-Elect: NEIL T. MORRISON, Bell Research
157 Virginia Ave., Chester, W. Va.
Vice-Chairman: WILLIAM G. COULTER, 322 38th St., N.W.
Canton, Ohio (Pemco Div , Glidden Co.)
Secretary: GEORGE A. WIEAND, Pennsylvania Glass Sand Corp.
Two Gateway Center, Pittsburgh 22, Pa.

Refractories Division

Trustee: RALPH R. RHODES (1964)
1729 Powell St., Norristown, Pa. (E. J. Lavino & Co.)
Chairman: THOMAS S. SHEVLIN, University of Washington
Ceramic Engineering Div., Seattle 5, Wash.
Vice-Chairman: STEPHEN D. STODDARD, 1460 Myrtle St.
Los Alamos, N. M. (Los Alamos Scientific Lab.)
Secretary: ROBERT W. LIMES, Republic Steel Corp.
Research Center, 6801 Brecksville Rd., Cleveland 31, Ohio

Structural Clay Products Division

Trustee: ARTHUR J. BLUME (1966)
Murray Tile Co., Inc., Lewisport, Ky.
Chairman: ARTHUR J. JABBUSCH, Pomona Pipe Products Co.
Winston-Salem Rd., Greensboro, N. C.
Chairman-Elect: PAUL D. MARTINO
Cannelton Sewer Pipe Co., Cannelton, Ind.
Vice-Chairman: GEORGE J. BISHOP, III
Columbia Brick & Tile Co., Box 3207, Columbia, S. C.
Secretary: HAROLD W. EMRICH, 1740 S. Monaco St.
Denver 22, Colo. (Denver Brick & Pipe Co.)

White Wares Division

Trustee: ARNO M. ILLING (1965) 276 Compton Ridge Dr.
Cincinnati 15, Ohio (Cambridge Tile Mfg. Co.)
Chairman: FRANK P. FONVIELLE, JR., 500 W. College Ave.
Dentists' Supply Co. of New York, York, Pa.
Chairman-Elect: WALTER W. PERKINS, 871 Jacoby Rd.
Copley 21, Ohio (United States Stoneware Co.)
Vice-Chairman: ALFREDO POLAR
ATCO Ceramics Corp., Keyport, N. J.
Secretary: GEORGE J. HUND, 227 Poplar Ave. N.W.
Canton, Ohio (Sparta Ceramics Co.)

National Institute of Ceramic Engineers

Trustee: EDWARD C. HENRY (1965) 730 Crawford Ave.
Syracuse 10, N. Y. (General Electric Co.)
President: WILLIAM W. COFFEEN
73 Ellisen Rd., Watchung, N. J. (M & T Chemicals Inc)
President-Elect: WINSTON DUCKWORTH
Battelle Memorial Institute, 505 King Ave., Columbus 1, Ohio
Vice-President: EDWARD E. MUELLER, Pemco Div., Glidden Co.
5601 Eastern Ave., Baltimore 24, Md.
Secretary-Treasurer: WILLIAM O. BRANDT
O. Hommel Co., Box 475, Pittsburgh 30, Pa.

Ceramic Educational Council

Trustee: GILBERT C. ROBINSON (1965)
Clemson College, Clemson, S. C.
President: WILLIS E. MOODY, School of Ceramic Engineering
Georgia Institute of Technology, Atlanta 13, Ga.
President-Elect: G. EDWIN LOREY, Missouri School of Mines
Dept. of Ceramic Engineering, Rolla, Mo.
Vice-President: FLOYD A. HUMMEL
Pennsylvania State University, University Park, Pa.
Secretary-Treasurer: PAUL R. JONES, Dept. of Chem. Eng.
West Virginia University, Morgantown, W. Va.

TABLE OF CONTENTS

VOLUME 46, 1963

January [No. 1], pp. 1–60

1. Robert F. Conley: Rapid Particle-Size Analysis of Ceramic Clays by Packing-Volume Technique ... 1–5
2. Stanley B. Austerman: Growth of Beryllia Single Crystals ... 6–10
3. J. F. Argyle and F. A. Hummel: Dilatometric and X-Ray Data for Lead Compounds, II ... 10–14
4. Eugene W. Sucov: Diffusion of Oxygen in Vitreous Silica ... 14–20
5. W. Robert Sinclair and F. G. Peters: Preparation of Oxide Glass Films by Reactive Sputtering ... 20–23
6. F. C. Lin and S.-M. Ho: Chemical Durability of Arsenic-Sulfur-Iodine Glasses ... 24–28
7. J. H. Handwerk, G. D. White, and D. C. Hill: Ceramic Nuclear Fuels in the System UO_2–ZrO_2–CaO ... 29–32
8. P. V. Riboud and Arnulf Muan: Melting Relations of CaO-Manganese Oxide and MgO-Manganese Oxide Mixtures in Air ... 33–36
9. R. E. Thoma, Herbert Insley, G. M. Hebert, H. A. Friedman, and C. F. Weaver: Phase Equilibria in the System NaF–ThF_4–UF_4 ... 37–42
10. G. C. Benson, P. I. Freeman, and E. Dempsey: Calculation of Cohesive and Surface Energies of Thorium and Uranium Dioxides ... 43–47
11. G. Goodman: Electrical Conduction Anomaly in Samarium-Doped Barium Titanate ... 48–54
12. William Dean McKee, Jr., and Eugene Aleshin: Aluminum Oxide-Titanium Oxide Solid Solution ... 54–58

Discussions and Notes

James F. Sarver: Comment on Note, "Vegard's Law and the System Alumina–Chromia," by R. M. Spriggs and S. L. Bender ... 58
Ernest M. Levin and Floyd A. Mauer: Improved Sample Holder for X-Ray Diffractometer Furnace ... 59–60
J. S. Waugh, A. E. Paladino, B. diBenedetto, and R. Wantman: Effect of Dislocations on Oxidation and Reduction of Single-Crystal $SrTiO_3$ ... 60

February [No. 2], pp. 61–106

13. H. Flood and W. J. Knapp: Acid-Base Equilibria in the System PbO–SiO_2 ... 61–65
14. A. C. D. Chaklader: X-Ray Study of Quartz-Cristobalite Transformation ... 66–71
15. Elihu A. Schatz: Isomorphous Substitution for Silicon in Fluorphlogopite ... 71–73
16. Anthony L. Gentile and Wilfrid R. Foster: Calcium Hexaluminate and Its Stability Relations in the System CaO–Al_2O_3–SiO_2 ... 74–76
17. J. D. McClelland and E. H. Zehms: End-Point Density of Hot-Pressed Alumina ... 77–80
18. Owen L. Kruger: Phase Studies on Arc-Melted Plutonium-Carbon Alloys Near the Monocarbide Composition ... 80–85
19. Chikara Hirayama and Daniel Berg: Dielectric Properties of Glasses in the System Nb_2O_5–Na_2O–SiO_2 ... 85–88
20. Edwin Ruh and Albert L. Renkey: Thermal Conductivity of Refractory Castables ... 89–92
21. H. E. Hagy: Experimental Evaluation of Beam-Bending Method of Determining Glass Viscosities in the Range 10^9 to 10^{15} Poises ... 93–97
22. R. A. Eppler: Glass Formation and Recrystallization in the Lithium Metasilicate Region of the System Li_2O–Al_2O_3–SiO_2 ... 97–101

Discussions and Notes

V. J. Moran: Structure in the Fracture Surface of Silicate Glass ... 102–103
D. P. H. Hasselman: Experimental and Calculated Young's Moduli of Zirconium Carbide Containing a Dispersed Phase of Graphite ... 103–104
Peter T. B. Shaffer and Stanley D. Mark: Inert-Atmosphere Dilatometer for Use to 2000°C ... 104–106
Rinoud Hanna: Elastic Moduli of Polycrystalline Magnesia Alumina Spinel ... 106

March [No. 3], pp. 107–54

23. Bh. V. Janakirama Rao: Influence of TiO_2 on Properties of Glasses in the System K_2O–PbO–SiO_2–TiO_2 and Its Relation to Structure ... 107–14
24. N. Fuhrman, L. D. Hower, Jr., and R. B. Holden: Low-Temperature Sintering of Uranium Dioxide ... 114–21
25. H. J. Van Hook: Phase Relations in the Garnet Region of the System Y_2O_3–Fe_2O_3–FeO–Al_2O_3 ... 121–24
26. W. E. Brownell: Reactions Between Alkaline-Earth Sulfates and Cristobalite ... 125–28
27. Joseph Vardi and Michael Hoch: Thermal Conductivity of Anisotropic Solids at High Temperatures—The Thermal Conductivity of Molded and Pyrolytic Graphites ... 129–32
28. A. E. Paladino and R. L. Coble: Effect of Grain Boundaries on Diffusion-Controlled Processes in Aluminum Oxide ... 133–36
29. Henry P. Kirchner, Kenneth M. Merz, and W. Richard Brown: Thermal Expansion of Uranium Pyrophosphate and of Ceramic Bodies in the System UO_2–UP_2O_7 ... 137–41
30. W. R. Bratschun: Barium Zirconate-Lead Titanate Ferroelectric Ceramics ... 141–44
31. Ronald C. Rossi and Richard M. Fulrath: Epitaxial Growth of Spinel by Reaction in the Solid State ... 145–49

Discussions and Notes

Maksymilian Burk: Thermal Conductivity of Beryllia Ceramics from −200° to 150°C 150–51
Louis Navias: Preparation and Properties of Spinel Made by Vapor Transport and Diffusion in the System MgO–Al_2O_3: III, Effect of Time and Intermittent Cooling on Diffusion Pattern 152
R. A. Lefever and E. A. Giess: Suggested Mechanism for Formation of Hopper Crystals in Flux Systems 153–54
Eugene W. Sucov: Phonon Scattering and Glass Inhomogeneity 154

April [No. 4], pp. 155–96

32. P. D. Shalek: Preparation and Properties of Uranium and Thorium Monosulfides 155–61
33. J. C. Williams, W. R. Sinclair, and S. E. Koonce: Preparation of Thin Mullite Films 161–67
34. F. G. Brockman, P. W. Beck, and W. G. Steneck: Magnetostrictive Ferrites with Small Change in Coupling Coefficient from 0° to 20°C 167–70
35. A. T. Chapman: Phase Studies in BeO–Metal Oxide Systems Using a Porous-Collector Technique 171–74
36. Y. Baskin and D. C. Schell: Phase Studies in the Binary System MgO–Ta_2O_5 174–77
37. Peter T. B. Shaffer: Evidence for High-Temperature Forms of Zirconium and Tantalum Monocarbides 177–79
38. Richard R. Vandervoort and Willis L. Barmore: Compressive Creep of Polycrystalline Beryllium Oxide 180–84
39. Robert R. Shaw: Rapid Orientation of Sapphire Monocrystals 184–86
40. S. Chatterji and J. W. Jeffery: Studies of Early Stages of Paste Hydration of Cement Compounds, II 187–91

Discussions and Notes

A. C. D. Chaklader: Geometric Model for Quartz-Cristobalite Transformation 192–93
W. J. Alford and D. L. Stephens: Chemical Polishing and Etching Techniques for Al_2O_3 Single Crystals 193–94
D. F. Carroll: The System PuO_2–ZrO_2 194–95
James F. Sarver: Thermal-Expansion Data for Rutile-Type GeO_2 195–96
Leon M. Atlas, Hikaru Nagao, and H. Henry Nakamura: Correction: Control of Dielectric Constant and Loss in Alumina Ceramics (October issue, 1962) 196

May [No. 5], pp. 197–248

41. J. B. MacChesney, P. K. Gallagher, and F. V. DiMarcello: Stabilized Barium Titanate Ceramics for Capacitor Dielectrics 197–202
42. George R. Pulliam: Decorated Dislocations in Magnesia Crystals 202–206
43. Thomas R. Clevenger, Jr.: Effect of Fe^{4+} in the System $SrFeO_3$–$SrTiO_3$ 207–10
44. K. H. G. Ashbee and R. E. Smallman: Stress-Strain Behavior of Titanium Dioxide (Rutile) Single Crystals 211–14
45. S. G. Whiteway: Density and Permeability of Sintered Slip-Cast Magnesia 215–18
46. L. A. Neimark, J. H. Kittel, and C. L. Hoenig: Irradiation of Metal-Fiber-Reinforced Thoria-Urania 219–24
47. R. M. Spriggs and T. Vasilos: Effect of Grain Size on Transverse Bend Strength of Alumina and Magnesia 224–28
48. D. P. H. Hasselman: Thermal Shock by Radiation Heating 229–34
49. R. J. Charles: Some Structural and Electrical Properties of Lithium Silicate Glasses 235–43

Discussions and Notes

M. P. Bauleke and K. O. McDowell: The System Lead Oxide–Zinc Oxide 243
A. G. Buyers: Ceramic-Metal Bonding Stable in Excess of 2248°K 244–45
Michael Hoch and Joseph Vardi: Thermal Conductivity of TiC 245
C. G. Bergeron, C. K. Russell, and A. L. Friedberg: Thermal Analysis of Lead Borate Glasses During Crystallization 246–47
J. H. Fang: Comment on Comment by J. F. Sarver 247
H. J. Van Hook: Influence of Oxygen Pressure on Incongruent Melting Temperature of Yttrium Iron Garnet 248

June [No. 6], pp. 249–300

50. W. A. Carlson, E. A. Sanford, and W. B. Crandall: Study of Crystallization of Glass Coatings on Metal by Electron Microscopy 249–53
51. R. E. Newnham, M. J. Redman, and R. P. Santoro: Crystal Structure of Yttrium and Other Rare-Earth Borates 253–56
52. M. L. Van Dreser and W. H. Boyer: High-Temperature Firing of Basic Refractories 257–64
53. L. N. Grossman: High-Temperature Thermophysical Properties of Uranium Monocarbide 264–67
54. S. Chatterji and J. W. Jeffery: Studies of Early Stages of Paste Hydration of Different Types of Portland Cements 268–73
55. P. de la Cierva and L. Arroyo: Study of Optical Glass Surfaces by Leaching with Nitric Acid: I, Polishing Lines 273–76
56. R. W. Taylor: Liquidus Temperatures in the System FeO–Fe_2O_3–TiO_2 276–79
57. J. F. Eichelberger, C. R. Hudgens, L. V. Jones, G. Pish, T. B. Rhinehammer, P. A. Tucker, and L. J. Wittenberg: Phase Equilibria for the Ternary Fused-Salt System NaF–BeF_2–UF_4 279–83
58. William D. Scott and Joseph A. Pask: Deformation and Fracture of Polycrystalline Lithium Fluoride 284–93

Discussions and Notes

William L. Baun and Neil T. McDevitt: Infrared Absorption Spectra of Rare-Earth Oxides in the Region 800 to 240 Cm^{-1} 294
V. Ern: Differential Thermal Analysis of a Cubic Modification of $BaTiO_3$ 295–96
J. A. Aboaf: Effects of Very High Pressures on Glass; Results Obtained Using a Tetrahedral Anvil Apparatus 296–97
T. Y. Tien and W. G. Carlson: Influence of Oxygen Partial Pressure on Properties of Semiconducting Barium Titanate 297–98
Henry P. Kirchner and Peter Knoll: Silicon Carbide Whiskers 299–300

July [No. 7], pp. 301–58

59. Robert Ruh: Reactions of Zirconia and Titanium at Elevated Temperatures 301–307
60. W. E. Elkington, G. Thomas, and J. Washburn: Damage Produced by Moving Dislocations in MgO 307–13
61. R. C. Doman, J. B. Barr, R. N. McNally, and A. M. Alper: Phase Equilibria in the System CaO–MgO 313–16
62. C. O. Hulse, S. M. Copley, and J. A. Pask: Effect of Crystal Orientation on Plastic Deformation of Magnesium Oxide 317–23
63. T. D. Chikalla: Melting Behavior in the System UO_2–PuO_2 323–28
64. M. L. Hammond and S. F. Ravitz: Influence of Environment on Brittle Fracture of Silica 329–32

65. G. R. Rigby, R. F. Hutton, and B. G. Hamilton: Reactions Occurring in Basic Brick 332–42
66. David L. Wilcox and Ralph L. Cook: Dielectric Behavior in the Systems $PbHfO_3$–$BaHfO_3$ and $PbHfO_3$–$SrHfO_3$ 343–48
67. Donald Bailey: Microscopy of Steam-Cured Asbestos Portland Cement Products 348–51

Discussions and Notes

L. H. Sjodahl and B. A. Chandler: Single-Crystal Elastic Constants of BeO from Polycrystalline Measurements 351–52
R. L. Coble and Y. H. Guerard: Creep of Polycrystalline Aluminum Oxide 353–54
S. J. Schneider: Discrepancy in Conversion of Early Melting-Point Temperatures 354–55
W. H. Grodkiewicz and L. G. Van Uitert: Synthesis of Forsterite, Diopside, Akermanite, and Wollastonite from Molten PbO 356
Mark J. Klein, Frank A. Rough, and Charles C. Simons: Structure and Annealing Behavior of Explosively Shocked Magnesia Single Crystals 356–58
Egil Aukrust and Arnulf Muan: The Stabilities of $CoO \cdot Al_2O_3$, $CoO \cdot Cr_2O_3$, and $2CoO \cdot SiO_2$ 358

August [No. 8], pp. 359–410

68. Patrick K. Gallagher, Frank Schrey, and Frank V. DiMarcello: Preparation of Semiconducting Titanates by Chemical Methods 359–65
69. Takeshi Takamori: Effects of Thermomechanical History on Properties of Glasses 366–70
70. Arthur S. Watts: Control of the Properties of Glazes by the Aid of Eutectics: Part IV, The Alkali–B_2O_3–SiO_2 Systems and Part V, The System PbO–B_2O_3–SiO_2 371–73
71. Edward A. Giess: Equations and Tables for Analyzing Solid-State Reaction Kinetics 374–76
72. F. P. Glasser and L. S. Dent Glasser: Crystal Chemistry of Some AB_2O_4 Compounds 377–80
73. T. H. Nielsen and M. H. Leipold: Thermal Expansion in Air of Ceramic Oxides to 2200°C 381–87
74. R. K. Datta and Rustum Roy: Phase Transitions in $LiAl_5O_8$ 388–90
75. W. D. Kingery, J. M. Woulbroun, and F. R. Charvat: Effects of Applied Pressure on Densification During Sintering in the Presence of a Liquid Phase 391–95
76. B. Blank, D. R. Rossington, and L. A. Weinland: Adsorption of Admixtures on Portland Cement 395–99
77. Walter S. Treffner and Robert M. Williams: Heat Evolution Tests with Calcium Aluminate Binders and Castables 399–406

Discussions and Notes

D. F. Carroll: Thermal Expansion of Plutonium Nitride 406
I. Amato, R. L. Colombo, and A. M. Protti: Influence of Stoichiometry on the Rate of Grain Growth of UO_2 407
Anthony J. Perrotta and I. Stewart McCallum: Germanate Spinels 408–409
Yoshihiro Matsuo and Hiromu Sasaki: PbO-Rich Side of the System PbO–TiO_2 409–10
Karl S. Vorres: Estimation of Phase Diagrams for Systems of Two Binary Compounds 410

September [No. 9], pp. 411–60

78. Walter M. Hirthe and John O. Brittain: High-Temperature Steady-State Creep in Rutile 411–17
79. G. M. Wolten: Diffusionless Phase Transformations in Zirconia and Hafnia 418–22
80. R. J. Stokes and C. H. Li: Dislocations and the Tensile Strength of Magnesium Oxide 423–34
81. D. P. H. Hasselman and W. B. Crandall: Thermal Shock Analysis of Spherical Shapes, II 434–37
82. R. L. Coble and J. S. Ellis: Hot-Pressing Alumina—Mechanisms of Material Transport 438–41
83. W. R. Buessem and S. R. Butler: Valence Changes of Iron and Manganese in Manganese Ferrite 442–46
84. W. L. Phillips, Jr., and J. E. Hanlon: Oxygen Penetration Into Single Crystals of Calcium Fluoride 447–49
85. L. F. Norris and G. Parravano: Sintering of Zinc Oxide 449–52
86. Dae-Hyun Chung, Joseph J. Swica, and William B. Crandall: Relation of Single-Crystal Elastic Constants to Polycrystalline Isotropic Elastic Moduli of MgO 452–57

Discussions and Notes

Leonard N. Grossman: On the Question of a Phase Change in Zirconium Monocarbide 457–58
W. C. Hansen: Comment on Paper, "Studies of Early Stages of Paste Hydration of Cement Compounds, II," by S. Chatterji and J. W. Jeffery 459
T. A. Voruz, R. P. Jewett, and O. E. Accountius: Direct Observation of Dislocations in Sapphire 459–60
A. E. Paladino and R. L. Coble: Correction: Effect of Grain Boundaries on Diffusion-Controlled Processes in Aluminum Oxide 460

October [No. 10], pp. 461–512

87. J. D. Mackenzie: High-Pressure Effects on Oxide Glasses: I, Densification in Rigid State 461–70
88. J. D. Mackenzie: High-Pressure Effects on Oxide Glasses: II, Subsequent Heat Treatment 470–76
89. F. P. H. Chen: Kinetic Studies of Crystallization of Synthetic Mica Glass 476–84
90. Robert C. Rau: Electron Microscopy of Sintered Beryllia 484–88
91. T. Y. Tien and E. C. Subbarao: Grain Growth in $Ca_{0.16}Zr_{0.84}O_{1.84}$ 489–92
92. T. Vasilos and R. M. Spriggs: Pressure Sintering: Mechanisms and Microstructures for Alumina and Magnesia 493–96
93. R. E. Gannon, R. C. Folweiler, and T. Vasilos: Pyrolytic Synthesis of Titanium Diboride 496–99
94. D. P. Hamblen, R. A. Weidel, and G. E. Blair: Preparation of Ceramic Semiconductors from High-Vanadium Glasses 499–504

Discussions and Notes

R. Douglas McBrayer, Hayne Palmour III, and Povindar Kumar Mehta: Chemical Etching of Defect Structures in Alumina-Rich Spinel Single Crystals 504–505
G. K. Layden: The System Al_2O_3–Nb_2O_5 506
D. R. Stiefbold, J. R. Boston, and R. A. Huggins: New Dislocation Etchant for Magnesium Oxide 507
R. M. Spriggs, L. A. Brissette, and T. Vasilos: Preparation of Magnesium Oxide of Submicron Grain Size and Very High Density 508–509
S. K. Misra and A. C. D. Chaklader: The System Copper Oxide–Alumina 509
John D. Buckley and H. H. Wilson: Destabilization of Zirconia by Cyclic Heating 510
Egil Aukrust and Arnulf Muan: Phase Relations in the System Cobalt Oxide–Manganese Oxide in Air 511
L. G. Van Uitert, J. J. Rubin, and W. A. Bonner: Preparation of Single Crystals of Tungstates and Molybdates of a Number of Divalent Metal Ions 512

November [No. 11], pp. 513–66

95. Robert K. Scott and Edwin Ruh: Design and Performance of a High-Temperature X-Ray Diffractometer Furnace . . 513–15
96. S. R. Hoh and F. E. Pirigyi: Barium Titanates with Improved Insulation Resistance and Time Constant 516–18
97. George K. Layden and G. W. Brindley: Kinetics of Vapor-Phase Hydration of Magnesium Oxide 518–22
98. W. F. Gabrysh, H. Eyring, Pan Lin-Sen, and A. F. Gabrysh: Rheological Factors for Bentonite Suspensions 523–29
99. M. Krishna Murthy and A. Mueller: Phosphate–Halide Systems: I, Constitution of $NaPO_3$-NaF Glasses 530–35
100. D. P. H. Hasselman: Elastic Energy at Fracture and Surface Energy as Design Criteria for Thermal Shock 535–40
101. D. Lynn Johnson and Ivan B. Cutler: Diffusion Sintering: I, Initial Stage Sintering Models and Their Application to Shrinkage of Powder Compacts 541–45
102. D. Lynn Johnson and Ivan B. Cutler: Diffusion Sintering: II, Initial Sintering Kinetics of Alumina 545–50
103. Buichi Kubota, Tomozo Nishikawa, Akira Yanase, Eiichi Hirota, Toshihiro Mihara, and Yoshio Iida: Modified Ferromagnetic Chromium Dioxide 550–56

Discussions and Notes

S. Block, J. Molin, and G. Piermarini: X-Ray Study of a Cadmium Borate Glass 557
M. Krishna Murthy: Phosphate–Halide Systems: II, Infrared Spectra of Glasses in the System $NaPO_3$–NaF 558–59
C. S. Morgan, L. L. Hall, and C. S. Yust: Sintering of Sodium Chloride 559–60
D. W. Budworth and Joseph A. Pask: Flow Stresses on the {100} and {110} Planes in LiF, and the Plasticity of Polycrystals 560–61
R. E. Mistler, G. L. Ploetz, and J. A. Smith: Thermal Expansion of Polycrystalline Lanthanum and Neodymium Sesquioxides 561–62
Michael Kestigian: Preparation of $Cd_2Nb_2O_7$ Single Crystals from a CdF_2 Melt 563–64
D. P. H. Hasselman: Relation Between Effects of Porosity on Strength and on Young's Modulus of Elasticity of Polycrystalline Materials 564–65
Deane K. Smith and Carl F. Cline: An X-Ray Investigation of Polymorphism in ZrC 566

December [No. 12], pp. 567–614

104. Patrick K. Gallagher and Frank Schrey: Thermal Decomposition of Some Substituted Barium Titanyl Oxalates and Its Effect on the Semiconducting Properties of the Doped Materials 567–73
105. E. Hal Bogardus and Rustum Roy: Residual Stresses in Two-Phase Systems as Determined by Changes in Transition Temperature 573–76
106. D. H. Speidel and Arnulf Muan: The System Manganese Oxide–Cr_2O_3 in Air 577–78
107. Bert Phillips, J. J. Hutta, and I. Warshaw: Phase Equilibria in the System NiO–Al_2O_3–SiO_2 579–83
108. Stanley A. Long and Thomas D. McGee: Effect of Grain Boundaries on Plastic Deformation of Sodium Chloride 583–87
109. A. R. Cooper, Jr., and R. C. Buchanan: Calculation of Temperature Distribution in Glass Tanks by Use of a Special-Purpose Electric Analog 588–92
110. Daniel R. Stewart and Guy E. Rindone: High-Temperature Energy Relations in Borates: Alkaline-Earth and Lead Borate Compounds and Their Glasses 593–96
111. Thomas W. Smoot and Joseph R. Ryan: Initial Temperatures of Zirconia Phase Changes and Solid-Solution Reactions 597–600
112. E. Gillam and J. P. Holden: Structure of Nickel Oxide Containing Alumina 601–604

Discussions and Notes

Gerhard Bayer: New Perovskite-Type Compounds A_2BTeO_6 604–605
Akos G. Revesz and Karl H. Zaininger: An Amorphous Modification of Gallium-Arsenic (V) Oxide 606
J. A. Christensen: Thermal Expansion and Change in Volume of Uranium Dioxide on Melting 607–608
Author Index to *The Journal* 609–11
Subject Index to *The Journal* 611–14

Instructions for Preparation of Papers and Notes . . . . . Back Cover, November Journal

CERAMIC ABSTRACTS

December 1963 *SECTION*

Compiled by the American Ceramic Society

AUTHOR INDEX FOR 1963

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates the position of the abstract on the page.

Aardt, J. H. P. van. Deterioration of cement products in aggressive media, B (5) 149*j*.
Abbott, L. S. See Blizard, E. P.
Abbott, R. E. Hard coated sheet, (3) 72*h*. Moving fiber optics, (2) 48*h*.
Abbott, W. F. Method for carbonizing fibers, P (1) 26*b*.
Abdrakhmanova, I. F., and Deryagin, B. V. Surface conductivity of quartz in the presence of adsorbed layers, (1) 30*h*.
Abe, E. See Inoue, Y.
Abe, Y. See Naruse, A.
Abendroth, H. J. See Fischer, W.
Abernathy, J. W. Infrared and radiant heat increase sign plant capacity, (8) 207*c*.
Abernethy, I. A. See Feichter, H. R.
Aboaf, J. A. Effects of very high pressures on glass—results obtained with a tetrahedral anvil apparatus, (8) 208*f*.
Aboaf, J. A., Hensler, J. R., et al. Irradiation damage to glass, (9) 240*g*.
Abraham, L. See Harman, C. G.
Abrecht, H. See Lukacs, J.
Abrosenkova, V. F., Logginov, G. I., and Rebinder, P. A. Binding of lime in calcium hydrosilicates under normal conditions, (2) 34*e*.
Accinno, D. J. See Schneider, J. F.
Accomazzo, M. A. See Sourirajan, S.
Accountius, O. E. See Voruz, T. A.
Ace Glass, Inc. Resistance coating for articles of glassware, etc., P (9) 242*b*. Stopcock for laboratory glassware, etc., P (9) 242*g*.
Acheson Industries, Inc. Heat resistant electrically conducting compositions, method of coating articles therewith, and articles produced thereby, P (11) 311*f*.
Acker, E. G., and Sanchez, M. G. Process for preparing fine size [20 to 250 $m\mu$] silica, P (7) 198*a*.
Ackerman, A. Apparatus for skiving abrasive bands for formation of abrasive belts therefrom, P (9) 236*a*.
Ackermann, H. Refractory magnesite linings for rotary cement kilns, P (3) 74*g*.
Acloque, P. H. Apparatus for the optical determination of stresses, P (7) 196*b*.
Acloque, P., and Guillemet, C. Course of fracture propagation in glass under varying strain, B (11) 321*b*.
Acme Steel Co. See Link-Belt Co.
Adamant Laboratories (Proprietary), Ltd. High-pressure die, P (3) 80*b*.
Adami, A., and Williams, L. S. Vacuum-assisted slip casting, (8) 221*i*.
Adami, L. H. See Mah, A. D.
Adams, A. See Brunner, G. M.
Adams, A. B., Farkas, E., Mardulier, F. J., and Shanklin, D. L. Cement grinding aid and pack set inhibitor, P (10) 268*e*.
Adams, C. A. Impact crusher [centrifugal], P (2) 55*j*.
Adams, E. L. Elimination of neck flash on blown plastic articles, P (7) 185*j*.
Adams, G. E., Gaines, W. M., Herz, J. H., and Romig, J. R. Use of process control computers in the cement industry, (5) 126*j*.
Adams, J. G. Determination of spectral emissivities, reflectivities, and absorptivities of materials and coatings, (8) 222*h*.
Adams, M. A., and Murray, G. T. Direct observations of grain-boundary sliding in bicrystals of sodium chloride and magnesia, (5) 142*h*.
Adams, M. C. Recent advances in ablation, (1) 8*e*.
Adams, R. V. Infrared absorption and the structure of glasses, (1) 7*b;* correction, (8) 209*b*. See Douglas, R. W.
Adams Engineering Co. Impact crusher [centrifugal], P (2) 55*j*. Impact crushing apparatus, P (5) 141*c*.
Adamsky, R. F. See Merz, K. M.
Addison, W. E. Structural Principles in Inorganic Compounds, B (5) 151*d*.
Adkins, F. E., Jr. Method for producing synthetic cryolite, P (6) 171*b*.
Adler, H. H., and Kerr, P. F. Infrared absorption frequency trends for anhydrous normal carbonates, (6) 173*i*.
Adomshick, G. J., and Quinn, R. G. Mounting for electrical resistance elements and method for preparing it, P (1) 16*h*.
Adsit, N. R. See Hirthe, W. M.
A. E. I.-John Thompson Nuclear Energy Co., Ltd. Temperature measurement apparatus for a nuclear reactor fuel element, P (8) 224*b*.
Aerofall Mills, Inc. Synthetic charge for material reduction mills, P (2) 51*h*.
Aerojet-General Corp. Cement composition, P (4) 96*f*.
Affsprung, H. E. See Christian, S. D.
Agafonova, Yu. A. See Lavrova, L. M.
Agarwala, R. P. Structure of cadmium rhodite, $CdRh_2O_4$, (4) 120*f*.
Agarwala, R. P., Naik, M. C., and Shankar, J. X-ray study of ZrO_2·2TeO formed by diffusion of Zr and Te in air, (4) 121*e*.
Aggarwala, B. D., and Saibel, E. Tempering stresses in an infinite glass plate, (1) 9*h*.
Aggregates Equipment, Inc. Screening device, P (4) 111*f*.
Aghajanian, H. A. Low flux density ferromagnetic material, P (3) 77*g*.
Agranovich, V. M., and Mikhlin, E. Ya. Theory of swelling in porous materials, B (8) 234*g*.
Agranovich, V. M., and Semenov, L. P. Theory of the effect of irradiation on some properties of graphite, B (8) 234*f*.
Agranovskaya, A. I. See Smolenskii, G. A.
Agte, C., Kohlermann, R., and Duebel, W. Wear-resistant cermets based on aluminum oxide and heavy-metal carbides, P (3) 75*b*.
Ahlstrom, E. R., and Schiel, E. J. Surface-barrier photocells, P (1) 21*j*.
Ahmed, F. R. See Bachmann, H. G.
Ahmed, N. See Fairbrother, F.
Ahn, Y. Studies on the formation and reduction of tungsten trioxide (I) thermal decomposition of ammonium paratungstate, (4) 120*h;* (II) reduction of tungsten trioxide, (4) 120*j*.
Ahrens, F. See Jaeger, G.
Aia, M. A. Process of preparing luminescent grade dibasic calcium phosphate, P (4) 106*a*.
Aihara, M. Construction and operation of the hearth, (11) 305*h*.
Aiken, W. S. Digital process control computers—capabilities and types, (5) 126*e*.
Air Products and Chemicals, Inc. Preparing alumina beta trihydrate, P (9) 254*e*.
Air Reduction Co., Inc. Electrode, P (3) 73*j*.
Airapetyants, S. V., and Bresler, M. S. Measurement of the anisotropy of electrical conductivity of semiconductors by the four-probe method, (7) 192*a*.
Aitken, A., and Taylor, H. F. W. Steam curing of cement and cement-quartz pastes, B (5) 149*j*.
Aitken, D. F. Blowing solids by hose, (3) 79*e*.
Ajax Magnethermic Corp. Control for electric furnace, P (1) 24*g*. Furnace, P (8) 224*g*.
Ajdacic, V., Kurepa, M., and Lalovic, B. Semiconductor measures fluxes in operating core, (3) 76*g*.
Akao, Y. See Moriya, T.
Akhtar, M. Gas analyzer, P (1) 24*j*.
Akimoto, S. See Ishikawa, Y.
Aktiebolaget Kanthal. Sintered electric resistance heating elements and methods of producing them, P (1) 17*c*.
Aktiebolaget Svenska Flaktfabriken. Transporting means [with reciprocating blade] for pulverous or granular materials, P (3) 80*b*.
Aktiebolaget Svenak Torvforadling. See Borsig Akt.-Ges.
Aktiengesellschaft Brown, Boveri & Cie. Method of contacting semiconductor devices, P (2) 49*a*.
Aladdin Industries, Inc. Ferrites having rectangular hysteresis loops and method for manufacture, P (5) 135*j*.
Albert, D. Pneumatic conveyor [with pressure vessel] for pulverant materials, P (11) 312*a*.
Albert Air Conveyor Corp. Pneumatic conveyor [with pressure vessel] for pulverant materials, P (11) 312*a*.
Alberti, K. Comparative investigations on the determination of the mixing proportions of mortars, (3) 64*e*.
Albertson, C. P., and Strittmatter, W. E. Method for testing fluids for particle contamination, P (10) 287*b*.
Albrecht, E. D. See Mulford, R. N. R.
Albrecht, F., Eppler, W., and Maucher, A. Low-silica glasses as hard materials, P (3) 69*c*.
Albrecht, W. Manufacture of a thermometer, (1) 7*f*.
Alcock, C. B. See Wolff, E. G.
Alderton, J. R. See Long, W. M.
Aldinger, R. Colored enamels, (10) 268*i*. Future of enameling, (8) 207*f*.
Aldred, F. H. Symposium on high-alumina refractories: Alumina ceramics, (11) 306*a*.
Aleixandre Ferrandis, V. Bodies, glazes, and processes in the wall tile industry (I, II), (6) 163*c*. Physical methods used in the study of clays, B (2) 61*a*. Refractories for the glass industry, (6) 160*f*.
Aleksandrov, B. S., Dobrokhotova, V. K., Naboikin, Yu. V., Spendiarov, N. N., and Uglanova, V. V. Zone purification of materials for use in monocrystal scintillators, B (9) 263*a*.
Aleksandrovich, E., Barteniu, M., Gus'kov, K., Zvonarev, A. V., and Klichkova, V. P. Investigation of the emf developed when a system of semiconductors containing uranium is irradiated in a reactor, (10) 280*g*.
Aleshin, E. See McKee, W. D., Jr.
Alexander, B. T., and Mathes, W. B. Preparation of white iron phosphate, P (4) 111*e*.
Alexander, D. L. See Scott, J. N., Jr.
Alexander, E. M. See Searight, C. E.
Alexander, G. B., and Pasfield, W. H. Iron group metals having submicron particles of refractory oxides uniformly dispersed therein, P (8) 216*i*.
Alexander, G. B., and Yates, P. C. Composition comprising particles of refractory oxide coated with an oxide of a transition metal, P (4) 102*d*. Process for dispersing a refractory metal oxide in another metal, P (8) 217*a*.
Alfille, L. Nuclear reactor duct structure, P (9) 245*b*.
Alford, H. E. Glass Microballoon particles for construction materials, (10) 270*j*. Method of acid treating hollow glass spheres, P (3) 69*g*.
Alford, H. E., and Veatch, F. Lightweight structural unit, P (8) 210*j*.
Alford, P. B. Statistical maintenance control, (3) 79*j*.
Alford, W. J., and Stephens, D. L. Chemical polishing and etching techniques for Al_2O_3 single crystals, (6) 167*h*.
Alfven, H. O. G. Generation of extremely high temperature, P (5) 140*e*.
Algatt, G. E., and Otto, W. G. Apparatus for finishing and mounting terminals on lamp bulbs, P (6) 157*d*.
Ali, A. See Rao, B. V. S. S.
Allegrini, A. P. Lightweight adsorbent clay product and method of making it, P (1) 25*j*. See Malone, T. S.
Allegrini, A. P., and Cecil, T. A. Method of drying attapulgite clay dispersions, P (1) 26*c*.

Allen, C. See Kuczynski, G. C.

Allen, C. C., Jr. Method [crystal growth] for fabricating transistors having desired current-transfer ratios, P (3) 78*b*.

Allen, E. M. Process for producing pigments, P (4) 111*d*.

Allen, F. M., Archer, F. C., and Shira, W. S. Rotary impact crusher [with overload release], P (10) 290*d*.

Allen, G. L. See Pyle, R. J.

Allen, R. G. Safety device for molding machines, P (3) 70*d*.

Allenbach, C. R. See Spendelow, H. R., Jr.

Alley, J. K., Johnson, R. C., Huggins, C., and Shell, H. R. Synthesis of fibrous silicon carbide by thermal reduction of silicates and silicon compounds, (9) 244*f*.

Allgeyer, G. H. Apparatus for handling [hot] glassware articles, P (3) 68*g*, P (5) 130*a*. Method for handling [hot deformable] glassware articles, P (3) 70*d*, P (10) 272*e*.

Allied Chemical Corp. Titanium compounds and processes of producing them, P (3) 85*a*.

Allis-Chalmers Mfg. Co. Apparatus for grinding and cooling solids, P (3) 83*d*. Automatic crusher [control circuit], P (6) 170*g*. Control system for automatically regulating cement kilns and auxiliary apparatus, P (5) 127*c*. Gyratory crusher, P (3) 83*i*. Seal for rotating cylinders such as kilns, etc., P (4) 108*j*. Shaft cooler [and crusher], P (8) 222*a*.

Allison, G. D. "Bitten by the bright gold bug," (2) 54*d*.

Allmanna Svenska Elektriska Aktiebolaget. Press stand [for hydraulic presses], P (3) 80*d*. High pressure vessel with punch, P (10) 285*f*. Magnetoelastic force measuring device, P (10) 282*j*.

Allnatt, A. R., and Jacobs, P. W. M. Conductance of potassium chloride in the solid state, (10) 294*d*.

Alloyd Corp. Method of making a pressure vessel by winding metallic-coated glass filaments, P (8) 211*f*. Process of coating vitreous filaments, P (7) 186*j*.

Alloyd Research Corp. Analytical process and apparatus, P (9) 252*d*. Bonding process and product thereof, P (6) 165*g*. Thermal insulating construction, P (8) 208*c*.

Almonte, J. B. See Dizon, G. D.

Alonso, J. J. Constitution and origin of clays, B (2) 61*j*.

Alper, A. M. See Doman, R. C.

Al'perovich, I. A., and Budnikov, P. P. Nature of dispersion of plastic clays, (4) 109*j*.

Alpine Akt.-Ges. Maschinenfabrik und Eisengiesserei. Flow apparatus for separating granular particles, P (9) 250*b*.

Altenburger Maschinen G.m.b.H. Apparatus for fine grinding, P (4) 106*i*.

Altieri, W. J. Means for controlling the effective resistance of piezoelectric quartz crystals, P (2) 49*h*.

Altman, G. See Saunderson, J. L.

Aluminium Laboratories, Ltd. Recovery of magnesium compounds from ores, P (8) 226*c*.

Aluminum Co. of America. Carbon anode [Fe stem, Al sheath], P (2) 45*i*. Electrochemical determination of fluorides, P (2) 60*a*. Production of low-soda alumina, P (9) 254*g*.

Alvarez de Toledo, F. Apparatus for forming mineral fibers, P (7) 185*g*.

Alvarez-Estrada, D. Dielectric properties of ceramic products, B (2) 61*a*. Formation and elimination of bubbles in ceramic glazes, (6) 163*c*. See Garcia Verduch, A.

Alviset, L., and Liger, C. Conditions of the movement of water in a clay during drying, B (10) 300*j*.

Amafuji, M., and Uno, T. Properties of minerals in cement clinker manufacture using calcined limestone, (7) 181*c*.

Amato, I., Colombo, R. L., and Protti, A. M. Influence of stoichiometry on the rate of grain growth of UO_2, (10) 294*b*.

Amberg, S., and Schrewelius, N. G. Sintered electric resistance heating elements and methods of producing them, P (1) 17*c*.

Amdur, E. J. Humidity sensors, (9) 251*c*.

Amelinckx, S. Dislocations in ionic crystals (I) geometry of dislocations; (II) electrical effects during cyclic straining of sodium chloride, B (3) 91*j*. See Delavignette, P.; Lierde, W. van.

Amelinckx, S., and Delavignette, P. Dislocations in layer structures, B (9) 262*a*. Electron microscopic observation of dislocations in silicate layer structures, B (3) 92*a*.

Amemiya, T., and Noguchi, H. Methods for estimating the mixing ratio of fine powders, (7) 181*b*.

American Air Filter Co., Inc. Automatic glass loader, P (10) 271*c*. Discharge electrode apparatus for electrostatic precipitators, P (2) 51*a*. Dust separator, P (5) 138*h*. Gas filter apparatus [washer], P (2) 51*c*. Gas filtering method and apparatus, P (1) 23*g*. Method and apparatus for making a condensed filamentous [glass] mat, P (9) 242*c*.

American Brake Shoe Co. Powder metallurgy, P (5) 133*e*.

American Cement Corp. Cement product, P (10) 268*f*.

American Cyanamid Co. Alumina of controlled density, P (8) 225*d*. Apparatus for combustion analysis, P (7) 196*a*. Automatic volumetric sampler and automatic material transfer, P (5) 139*d*. Calcium sulfate plasters containing [0.0007 to 1.5%] stearamidopropyldimethyl-beta-hydroxyethylammonium salts, P (5) 127*a*. Method of producing titanium monoxide or titanium carbide, P (6) 162*h*. Rock treatment, P (9) 254*h*. Shredder of rotating wires for filter cake, P (3) 80*a*. Titanium dioxide pigment and compositions containing it, P (3) 85*b*. Treatment of titanium dioxide pigment, P (8) 226*b*.

American Drill Bushing Co. Ceramic coated bushings and allied products, P (1) 4*i*.

American Instrument Co., Inc. Apparatus for measuring changes in weight of samples as a function of temperature, P (2) 53*a*. Spectrophosphorescence measuring instrument, P (9) 252*h*.

American Lava Corp. High hardness porcelain enamel composition, method of coating therewith, and article produced thereby, P (10) 269*b*. Metal-to-ceramic seals, P (3) 78*a*.

American Metal Climax, Inc. Molybdenum disulfide treating process, P (11) 315*d*.

American Metal Products Co. Method of joining carbon, P (11) 303*c*. Process of manufacturing nuclear fuel, P (9) 245*e*.

American Optical Co. Apparatus for drawing fibers, P (8) 210*e*. Bevel-edged lenses [4.5°], P (3) 69*d*. Light-conducting fibers, P (3) 69*b*. Method for analyzing microscopic particles, P (1) 24*c*. Method and apparatus for reclaiming particles from a mixture, P (1) 11*j*. Method and apparatus for supporting optical elements, P (3) 70*b*. Method for shaping a fiber optical device, P (1) 12*a*. Surfacing apparatus, P (10) 285*e*.

American Potash & Chemical Corp. Polishing composition and process of forming it, P (10) 265*g*.

American Radiator & Standard Sanitary Corp. Resistance thermometer probe, P (5) 140*a*.

American-Saint Gobain Corp. Electric heater with plate-clamping reflector, P (3) 69*g*. Method of attaching a metal channel to a glass plate, P (10) 272*b*.

American Society for Testing and Materials. ASTM Standards on Mineral Aggregates and Concrete (With Selected Highway Information)—C-9, D-4, B (10) 298*h*.

American Truck Body Co. Method and container for shipping brick [by rail], P (2) 44*d*.

American Vitrified Products Co. Bell and spigot tile and [tapered] seal joint therefor, P (5) 132*c*. Machine for cutting vitrified clay pipe, P (8) 212*a*.

Ames, L. L., Jr. Cation sieve properties of the open zeolites chabazite, mordenite, erionite, and clinoptilolite, (4) 112*b*. Characterization of a strontium-selective zeolite, (7) 198*j*. Effect of base cation on the cesium kinetics of clinoptilolite, (6) 172*c*. Kinetics of cesium reactions with some inorganic cation exchange materials, (7) 199*g*.

Amick, J. A., and Cullen, G. W. Semiconductor devices, P (10) 283*f*.

Amosov, N. I., and Savitskii, M. R. Classification of glassware, (7) 184*f*.

Ampex Corp. Lithium ferrites, P (9) 249*d*. Magnetically annealed ferrite material, P (2) 49*e*. Method of producing a ferrite body and product obtained, P (5) 136*f*.

Amphlett, C. B. Method for preparing granular gels, P (2) 55*a*.

Amsel, F. E., Sharav, W. B., and Stanchus, F. T. Magnetic flux-gas shielded metal arc welding, P (10) 269*d*.

Amsted Industries, Inc. Insert [refractory] core for slide shutoff device, P (9) 244*c*. Pouring spout and method of using, P (2) 46*g*. Process for producing a shaped graphite article, P (9) 245*j*.

Amstel, J. J. A. P. van. See Jochems, P. J. W.

Amy, J. A., and Haskins, J. F. Deformational mechanisms in ductile ceramics, (8) 226*i*.

Anaconda Co. Calcination of zinc sulfide concentrates, P (10) 289*e*.

Ananich, N. I. See Botvinkin, O. K.

Anchor Hocking Glass Corp. Method and means for inspecting containers, P (4) 100*e*. Rotary jar washer, P (10) 273*b*.

Anders, E. See Lipschutz, M. E.

Andersen, J. C. Fuel composition for nuclear reactors, P (11) 308*c*.

Anderson, C. W. Diamond cutoff wheel, P (3) 63*g*.

Anderson, E. E., Cunningham, J. R., Jr., et al. Polycrystalline ferrimagnetic garnets, (1) 19*c*.

Anderson, G. R. See Kirkpatrick, W. J.

Anderson, N. A. Process control, (2) 51*c*.

Anderson, N. G. Particle separation method, P (5) 138*d*.

Anderson, P. J., and Horlock, R. F. Thermal decomposition of magnesium hydroxide, (11) 319*i*.

Anderson, R. L., Marinace, J. C., and Silvey, G. A. Semiconductor body formation, P (5) 137*h*.

Anderson, W. K., and Dunning, D. N. Reactor control materials, (8) 214*c*.

Anderson, Y. R. Education Committee of Canadian Ceramic Society discusses certification of ceramic technicians, (6) 176*c*.

Ando, T. See Nobuoka, S.

Andreeva, A. B. See Keler, E. K.

Andreeva, E P. Segalova, E. E., and Volynets, E. E. Effect of calcium chloride on structure development in aqueous suspension of tricalcium aluminate, (11) 317*d*.

Andreeva, O. V. See Filonenko, N. E.

Andresen, W. V. Industrial hygiene design in raw materials handling systems, (9) 258*f*.

Andrews, A. I. See Forlano, R. J.

Andrews, R. S. L. Shell Process Foundry Practice, B (9) 259*g*.

Andrews, K. W. See Johnson, W.

Andrews, R., and Moore, F. M. Silicone-coated frit used in decorating glassware, P (11) 305*a*.

Andrievskii, A. I., Nabitovich, I. D., and Kotsyumakha, P. A. Structure of thin films of laboratory glasses, (2) 41*b*.

Andrievskii, A. I., Nabitovich, I. D., and Voloshchuk, Ya. V. Method of accounting for the background in electronographic studies of the structure of amorphous substances, (5) 144*e*.

Andryukhin, P. N. See Gurevich, I. E.

Angel, F. Deposits of magnesite and talc in Austria, (7) 197*e*.

Angelucci, L. J., Jr. Method of manufacturing electrical apparatus, P (2) 42*c*.

Angstroem, A. K., and Drummond, A. J. Basic concepts concerning cutoff glass filters used in radiation measurements, (2) 38*h*.

Annawerk Akt.-Ges. Highly refractory compound parts, P (3) 74*a*.

Anselmo, J. E. See Dizon, G. D.

Ansems, A. J. P. See Schoenmakers, H.

Anstalt fuer Technische Entwicklung und Verwertung. Casing for the production of a shrinkage funnel inhibitor coating in an ingot or like mold [hot top], P (10) 276*j*.

Antal, J. J., and Goland, A. N. Study of reactor-irradiated α-Al_2O_3, (3) 89*g*.

Antes, L. L. Process for making cadmium sulfide photoconducting articles, P (3) 78*g*.

Anthes, J. A. See Koontz, V. F.

Anthes, L. B. Synthetic abrasives industry in Canada, (3) 63*h*.

Anthony, B. F. Bottom rings for composite hot tops, P (3) 73*h*.

Anthony, C. E. Gravity actuated apparatus for weighing granular material, P (9) 250*c*.

Antill, J. E. See Peakall, K. A.

Antill, J. E., and Lloyd, H. Sintering long ceramic compacts in a movable, short furnace, P (2) 51*g*.

Antonevich, N. K., and Polyakova, T. P. Parameters for electrophoretic dewatering of slips for colored mosaic tile bodies, (7) 194*h*.

Antonov, G. I. See Khil'ko, M. M.

Antonov, G. I., and Berman, Sh. M. Rational parameters for regenerator checkers in glass furnaces, (8) 224*h*.

Antonsen, R. See Belknap, L. S.

Antonsen, R., Bradley, J. M., and Beattie, R. D. Process and apparatus for the production of finely divided pigments, P (4) 111*g*.

Antoszewski, W. J., and Kurtz, R. A. Apparatus for gaging glassware [diametrically], P (3) 68*g*.

Anufrieva, N. A. See Rutkovskii, M. L.

Anwyl, R. H. Deterioration of dried clay brick (warm weather storage), (1) 12*h*.

Ao, T., and Oyama, T. Study of the corrosion mechanism of refractories used in the zebra roof of a basic open-hearth furnace, (3) 73*i*.

Aoi, S., and Murata, N. Cathodes for electron tubes, P (4) 105*a*.

Aoki, S. See Nakahara, M.

Aoki, S., and Suzukawa, S. Five-year-test results on the neutralization of concrete containing fly ash, (8) 204*j*.

Aoki, Y. See Mito, S.

Aomine, S., and Wada, K. Differential weathering of volcanic ash and pumice, resulting in formation of hydrated halloysite, (6) 169*i*.

Aparicio-Arroyo, E. See Pedregal, J. D.; Terraza, J.

Apellaniz, J. A. See Morrison, A. R.

Apfelbeck, H. Mechanizing plate production, (4) 104*c*. Reply to comments on "A new method for the mechanical (pressing) shaping of plates," (3) 79*f*.

Appen, A. A., and Kayalova, S. S. Experimental basis for classification of oxides according to their influence on the surface tension of silicate melts, B (11) 321*a*.

Appleyard, A. H. Glass disk generates any low-frequency waveform, (2) 48*c*.

Arai, T. Study of the optical properties of conducting tin oxide films and their interpretation in terms of a tentative band scheme, (6) 175*g*. See Ishiguro, K.

Arai, Z., Hayashi, H., Nakamura, S., and Azuma, N. Synthesis of titanium nitride from titanium hydride powder and nitrogen or ammonia, (5) 146*i*.

Arakawa, M. See Bando, I.

Aramaki, S. Sillimanite and cordierite from volcanic xenoliths, (4) 110*f*.

Arapova, E. Ya. Luminescence of self-activated sublimed zinc sulfide phosphor, (6) 164*b*.

Arbeit, P. Method and furnace for making glass, P (8) 211*e*.

Arbiter, W. Dispersion hardening of uranium metal, P (5) 133*e*.

Arcement, L. M. Apparatus for handling particulate material, P (5) 138*g*.

Archambault, M. Lithium carbonate production, P (1) 26*a*.

Archer, F. C. See Allen, F. M.

Arents, J. W. M. See Wanmaker, W. L.

Argyle, J. F., and Hummel, F. A. Dilatometric and X-ray data for lead compounds (II), (3) 86*d*. Liquid immiscibility in the system BaO–SiO_2, B (11) 320*h*.

Ariizumi, A., Kondo, O., and Makida, M. Measurement of the neutralization of concrete with radioactive carbon dioxide, (8) 205*c*.

Ariizumi, A., and Oba, M. Reaction of allophane with solution containing calcium hydroxide and gypsum, (7) 181*f*.

Arimori, T., and Konishi, A. Investigation of the removal of iron content of Izumiyama pottery stone (I) relation between operating conditions of a hydraulic cyclone and the removal of iron, (8) 225*c*.

Arkharov, V. I. Problem of simulating the crystal boundaries, (2) 58*h*.

Arkless, K. Preparation of titanium dioxide, P (10) 289*i*. See Hughes, W.; Strain, F.

Arkless, K., and Whayman, E. Treatment of titanium dioxide, P (8) 226*a*.

Arlett, R. H. Behavior of chromium in the system $MgAl_2O_4$–Al_2O_3, (1) 26*f*.

Arlett, R. H., Di Vita, S., and Smoke, E. J. Ceramic materials and method for making them, P (7) 193*i*.

Armbruster, G. D. See Ninneman, E. O.

Armco International Corp. High-melting coatings on steel strip, P (6) 155*f*.

Armco Steel Corp. Abrasive grinding balls, P (3) 63*f*. Magnesia coatings on silicon steel, P (6) 155*f*.

Armeny, P. J. See Ogden, J.

Armour, W. H. See Haufman, W. F.

Armour and Co. Method for concentrating aluminum silicates and zircon from beach sand, P (10) 289*c*.

Armour Research Foundation of Illinois Institute of Technology. Method of applying an oxide coating onto a nonporous refractory substrate, P (7) 183*i*.

Armstrong, P. E. See Brown, H. L.

Armstrong, W. M., Chaklader, A. C. D., and Evans, D. G. Effect of oxygen on the ultraviolet optical absorption bands of MgO, (9) 256*d*.

Armstrong Cork Co. Flexible asbestos-cement products, P (2) 36*b*.

Armytage, F. W. Automatic contour superfinishing, (4) 98*a*.

Arnold, G. W., Jr. See Compton, W. D.

Arnold, K. H. Problem of enamel expansion, B (11) 322*h*.

Arnold, R. T. See Stanford, A. L., Jr.

Arntz, F. O., and Vliet, K. M. van. Secondary emission of thin self-supported films of MgO, (5) 145*h*.

Arrance, F. C. Method for disposing of radioactive waste and resultant product, P (9) 246*b*.

Arredondo y Verdu, F. Drying of clay products, B (2) 61*a*.

Arrington, T. B. See Rex, J. P., Jr.

Arroyo, E. A.-. See Aparicio-Arroyo, E.

Arroyo, L. See Cierva (Viudes), P. de la.

Artelt, P. See Kienow, S.

Artemis, E. C. Cement, P (5) 127*a*.

Arthur, P., Jr. Process for the production of fibrous alumina monohydrate, P (2) 46*b*.

Asanabe, S. See Sasaki, Y.

Asano, M. Effects of the fineness of clinker and slag on the drying shrinkage of portland blast-furnace slag cement mortar, (8) 204*g*. See Hori, M.

Asano, S. See Inoue, Y.

Asano, S., Ozu, M., Inoue, Y., and Hashizume, G. Hydration and carbonation of various types of cements and cement components, (8) 205*h*.

Ashbee, K. H. G., and Smallman, R. E. Stress-strain behavior of titanium dioxide (rutile) single crystals, (7) 200*g*.

Asher, D. R., Hansen, R. D., Seamster, A. H., Small, H., and Wheaton, R. M. Yttrium oxide of high purity, (11) 315*d*.

Ashley, M. See Waye, B. E.

Asprey, L. B. See Kruse, F. H.

Associated Electrical Industries, Ltd. Method for producing hollow glass articles, P (5) 131*a*. Production of high density sintered uranium oxide, P (3) 74*e*. Production of unipolar [monocrystal] transistors, P (5) 137*e*. Quartz-to-metal seals, P (11) 311*f*.

Associated Lead Manufacturers, Ltd. Pigments, P (1) 18*i*, P (3) 84*e*.

Astbury, N. F. Are ceramics in industry outdated? (1) 31*e*. "De Mensuris et Ponderibus"—testing of refractories, (1) 13*e*. Plasticity model, (11) 318*d*.

Astbury, N. F., and Moore, F. Contributions to the study of plasticity, B (10) 300*e*.

Astheimer, R. W., and Merlen, M. M. Infrared comparison micrometer, P (11) 320*d*.

Astwood, P., and Prutton, M. Influence of crucible material on the magnetic anisotropy of evaporated Permalloy films, (5) 132*h*.

Asunmaa, S. K. Electron microscopy and microheterogeneity of glasses, B (11) 320*f*.

Asunmaa, S. K., and Baak, T. Irradiation of glass films with a 100 kv electron beam, (2) 40*a*.

Atkinson, C. R. See West, H. W. H.

Atlantic Refining Co. Removal of ionic impurities from calcined alumina, P (5) 141*d*.

Atlas, L. M., Nagao, H., and Nakamura, H. H. Control of dielectric constant and loss in alumina ceramics—correction, (6) 163*j*.

Atlas, L. M., and Schell, D. C. Dolomitic refractory, P (5) 133*f*.

Aubert, M., Foglia, S., and Roche, R. System for supporting nuclear fuel in atomic reactors, P (11) 308*j*.

Aubrecht, V. Earthenware centrifugal pump, (5) 138*b*.

Audesse, E. G. Method for introducing iodine into a lamp envelope, P (3) 70*d*.

August Thyssen-Huette Akt.-Ges. Blast-furnace linings, P (4) 102*c*.

Aukrust, E., and Muan, A. Phase relations in the system cobalt oxide–manganese oxide in air, (11) 318*d*. Stabilities of $CoO \cdot Al_2O_3$, $CoO \cdot Cr_2O_3$, and $2CoO \cdot SiO_2$, (9) 257*g*.

Austerman, S. B. Growth of beryllia single crystals, (3) 87*c*.

Austerman, S. B., Berlincourt, D. A., and Krueger, H. H. A. Polar properties of BeO single crystals, (10) 281*g*.

Auzins, P. See Wertz, J. E.

Aveline, M. See Draignaud, P.

Aven, M., and Potter, R. M. Process for providing improved maintenance to electroluminescent [ZnS] phosphors, P (6) 166*f*.

Averbach, B. L. Process of coating vitreous filaments, P (7) 186*j*.

Aves, W. L., Jr. Metal-ceramic laminated coating and process for making it, P (2) 38*f*.

Avgustinik, A. I. Production of porcelain, (7) 190*d*. See Kachalova, L. P.; Petrova, V. Z.

Avgustinik, A. I., and Tsuranova, I. S. Study of bond development in silicate melt by infrared spectrometry method, B (11) 322*f*.

Avinor, M. Red luminescent material for cathode-ray tubes, P (1) 21*f*.

Aylmore, L. A. G., and Quirk, J. P. Structural status of clay systems, B (5) 150*d*.

Ayres, D. J. Mechanical rendering of surfaces and pointing of brickwork, P (6) 159*c*.

Ayres, R. J. Electric lamp base end structure, P (9) 241*i*.

Azarov, K. P. See Budnikov, P. P.

Azarov, K. P., and Balandina, V. V. Solubility of iron oxides in boron and boron-free silicate melts, (2) 37*b*.

Azarov, K. P., and Grechanova, S. B. Effect of iron oxide on the viscosity of boron and boron-free enamels, (1) 4*b*.

Azuma, N. See Arai, Z.

Baak, T. See Asunmaa, S. K.

Baarson, R. E., and Jonaitis, C. W. Method for concentrating aluminum silicates and zircon from beach sand, P (10) 289*c*.

Babadzhanyan, M. A. See Galdina, N. M.

Babcock, C. L. Articles bonded together by internally nucleated devitrified solder glasses and method of making them, P (3) 69*b*.

Babcock, E. W. See Sharp, D. E.

Babcock, R. S. See Humphries, J. J.

Babcock & Wilcox, Ltd. Apparatus for classifying air-dust mixture, P (6) 167*g*. Apparatus for forming a ceramic filament, P (3) 68*e*. Interlocking ceramic tile elements, P (2) 45*j*. Multiple nozzle gas burner, P (5) 140*e*. Pulverizer, P (9) 250*f*. Shaft kiln, P (11) 314*e*. Sintered refractory material, P (10) 278*b*.

Babin, V. N. See Novoselova, A. V.

Babushkin, V. I. See Mchedlov-Petrosyan, O. P.

Babushkin, V. I., and Mchedlov-Petrosyan, O. P. Thermodynamic study of solid-phase reactions in the system calcium oxide–alumina, (4) 121*a*.

Bachman, J. R. See Wade, W. S.

Bachman, W. S., and Porrata, L. R. Ceramic reproducer [transducer], P (2) 48*d*.

Bachmann, H. G., Ahmed, F. R., and Barnes, W. H. Crystal structure of vanadium pentoxide, (4) 113*g*.

Bachmann, L., and Cremer, E. Kinetics of the thermal decomposition of magnesium and calcium carbonate, (4) 115*f*.

Bacon, R., and Sprague, R. Decoration of dislocations and low angle grain boundaries in graphite single crystals, B (9) 262*b*.

Badger, A. E. See Meriwether, H. R., Jr.

Badische Anilin- & Soda-Fabrik Akt.-Ges. Process for the production of acicular gamma-iron(III) oxide, P (5) 141*b*.

Baenziger, N. C. See Eyring, L.

Baer, C. A., Clough, P. J., and Steeves, R. W. Process of coating a refractory body with boron nitride and then reacting with aluminum, P (7) 189*j*. Process of treating a boron nitride crucible with molten aluminum, P (3) 74*c*.

Baeumert, P. A. F. Process of producing fluorine compounds from fluorine-containing minerals, P (3) 84*i*.

Bagdasarov, Kh. S., Dobrzhanskii, G. F., and Il'in, N. P. Universal apparatus for growing monocrystals at high temperatures, B (9) 262*h*.

Bailey, D. Microscopy of steam-cured asbestos portland cement products, (9) 236*i*.

Bailey, G. W. See Brown, C. B.

Bailey, S. W. See Brown, B. E.

Bailey Meter Co. Resistance [probe type] thermometer, P (3) 81*f*.

Baillie, A. J. See Cunningham, K. G.

Baily, W. E., Danko, J. C., Ferrari, H. M., and Colombo, R. Steam sintering of uranium dioxide, (1) 15*j*.

Baird-Atomic, Inc. Spectroscopic apparatus, P (2) 53*d*, P (3) 90*a*. Spectroscopic apparatus with automatic correction of misalignment, P (7) 201*i*.

Baker, A. B. See McIlhenny, W. F.

Baker, A. R. Apparatus for detecting combustible gases having an electrically conductive member enveloped in a refractory material, P (9) 253*f*.

Baker, B. M. Compensated gravity measuring device, P (5) 139*d*.

Baker, D. V. Pottery Today, B (3) 92*g*.

Baker, G. S. See Gibbs, P.; Rogers, W. G.

Baker, H. D., Ryder, E. A., and Baker, N. H. Temperature Measurement in Engineering (Vol. II), B (2) 62*d*.

Baker, J., Edgington, J. H., and Fletcher, J. Mold cleaning, maintenance, and storage (a summary of three papers), (4) 98*g*.

Baker, N. H. See Baker, H. D.

Baker, R. E. See Li, J. C.

Baker, T. C. Volumetric measurement, P (3) 70*h*.

Baker, T. W. See Bellamy, B.

Bakian, J. P. Diamond grinding wheel and compositions therefor, P (8) 203*h*.

Bakker, C. See Wanmaker, W. L.

Bakker, M. A. M. See Duran, J. C.

Balachandra, J. See Gadiyar, H. S.

Balamuth, L. Ultrasonic rotary drive may open up many new applications for micro devices, (6) 165*a* See Kleesattel, C.

Balamuth, L., and Kuris, A. Ultrasonic lapping machines, P (10) 285*g*.

Balandina, V. V. See Azarov, K. P.

Balcar, O. Hot spray casting of ceramic products, (4) 104*a*.

Baldwin, R. C. Method of making holes in the earth, P (10) 289*d*.

Baldwin-Lima-Hamilton Corp. Sand or fines filtering device for [rotary drum] dryers, P (5) 140*g*.

Balgord, W. D. See Keller, W. D.

Balkanski, M., and Waldron, R. D. Internal photoeffect and exciton diffusion in cadmium and zinc sulfides, (4) 115*a*.

Ball, F. C. Celadon glazes for the stoneware potter, (7) 177*i*. Ceramic screens, (4) 95*i*. Clay bodies for salt glazing, (5) 126*a*. Color in salt glazing, (5) 126*a*. Engobes for color in salt glaze, (7) 177*j*. Glazing, decorating, and firing huge pots, (4) 95*f*. Huge pots, (4) 95*f*. Introduction to salt glaze, (5) 125*j*. Potter's basic glaze, (7) 178*a*. Preparing a salt-glaze body, (5) 126*a*. Salt-glazed stoneware, (5) 126*d*.

Ball, F. J. Mineral fiber mat formation, P (2) 42*h*.

Ball, R. J. See Kay, S. E.

Ball, W. L. Handling of volatile solvents, (1) 31*e*.

Ballard, J. W. High temperature pressure sensitive solid state material [Al_2O_3 and Mo] and [transducer] device, P (11) 311*g*.

Ballestra, M. Device for the measurement of the density of pulverulent or liquid materials, P (4) 108*e*.

Ballhausen, C. Method of and device for generating high pressures, P (8) 222*b*.

Ballman, A. A. Growth and properties of colored quartz, (4) 114*a*. New series of synthetic borates isostructural with the carbonate mineral huntite, (6) 170*f*. Yttrium and rare earth borates, P (2) 50*f*.

Baltzer, D. H. New near infrared spectrum filter media, P (1) 12*c*.

Baltzer, P. K. Mixed ferrospinels, P (2) 50*f*.

Balzer, C. G., and Dohrmann, H. C. Magnetic cleaning means for electrodes of electrostatic precipitator, P (4) 106*i*.

Bamford, C. R. Application of ligand field theory to glasses colored by the transition metals, B (11) 320*g*. Application of the ligand field theory to colored glasses, (7) 184*b*. Study of the magnetic properties of iron in relation to its coloring action in glass (III) iron in sodium silicate glasses and the sulfur-amber coloration, (1) 9*i*; (IV) iron in sodium phosphate glasses, (2) 41*d*.

Ban, P. van den. See Geldermans, P.

Bando, I., and Arakawa, M. Improvement of press process for spectacle lenses, (10) 271*a*.

Banerjee, B. K. Glass constitution, (9) 240*h*.

Banerjee, J. C., Banerjee, N. C., and Sircar, N. R. Study of natural sillimanite as a refractory material (II) superrefractories for glass tank furnaces, (6) 161*f*.

Banerjee, J. C., and Sircar, N. R. Study of natural sillimanite as a refractory material (I) tank blocks, (3) 73*j*.

Banerjee, N. C. See Banerjee, J. C.

Banks, E. See Mones, A. H.

Banks, J. H. Apparatus for making fibrous glass mats, P (1) 10*f*.

Banks, P. B. Television camera tubes, P (3) 70*e*.

Bansigir, K. G., and Schneider, E. E. Studies on the substructure of real crystals by optical and magnetic resonance methods, B (9) 260*i*.

Baradez, P. See Pruvot, E.

Baram, A. A. See Vasserman, I. M.

Baranovic, M. See Love, R. W.

Baratta, F. Pyrolytic graphite and its application, (4) 97*c*.

Barbaras, G. D. Film forming composition, P (2) 38*a*.

Barber, W. A. Method of producing titanium monoxide or titanium carbide, P (6) 162*h*.

Barber-Greene Co. Rotary impact crusher [with overload release], P (10) 290*d*.

Barcus, S. W., Jr. See Cornelison, B.

Bard, A. L., and Johnsen, A. M. Abrasive grinding balls, P (3) 63*f*.

Bares, R., and Rosenkranz, M. New method of indicating cracks in brittle materials, (2) 52*b*.

Bargezi, E. Sintered magnesia of uniform hardness, P (4) 103*d*.

Barghusen, J. J. See Jonke, A. A.

Barium and Chemicals, Inc. Preparation of pure titanates, P (3) 78*e*.

Barke, V. N., Blitstein, N. I., Griaznov, I. M., Livshits, A. L., Mechetner, B. K., Podiazov, S. S., and Yakhimovich, D. F. Ultrasonic [liquid] abrasive machining apparatus, P (10) 265*h*.

Barkemeyer, H. R., McAleer, W. J., and Poliak, P. I. Production of semiconductor films, P (3) 78*j*.

Barker, F. Phase relations in cordierite-garnet-bearing Kinsman quartz monzonite and the enclosing schist, Lovewell Mountain quadrangle, New Hampshire, (4) 117*j*.

Barkley, D. W. See Ogle, J. C., Jr.

Barkman, A., Fujimoto, M. S., and Orwig, B. R. Batch small-ball ball mill for dispersing pigments in liquid vehicles, P (2) 51*a*.

Barlogeanu, C. See Petri, I.; Solomon, L.

Barlow, D., and Beattie, I. R. Self-diffusion of sodium ions in analcite and anhydrous analcite, (11) 319*d*.

Barlow, O. M. See Van Sandt, W. A.

Barmore, W. L. See Vandervoort, R. R.

Barnaby, B. E. Ceramic receiving tube refinement program, (8) 218*h*.

Barnard, R. H. Method and apparatus for producing glass fibers, P (3) 70*a*.

Barnes, C. R., and Geesner, C. R. Electrical capacitor having a silicon nitride dielectric, P (10) 282*e*.

Barnes, E., Munro, W., Thackray, R. W., Williams, J., and Murray, P. Preparation, fabrication, and properties of uranium carbide and uranium/uranium carbide cermets, (8) 214*h*.

Barnes, H. L., and Ernst, W. G. Ideality and ionization in hydrothermal fluids—the system MgO–H_2O–NaOH, (6) 173*g*.

Barnes, M. W. See Ruthberg, S.

Barnes, R. G., Segel, S. L., and Jones, W. H., Jr. Nuclear quadrupole resonance and bonding in solid layer type metal halides, B (9) 259*e*.

Barnes, W. H. See Bachmann, H. G.

Barnes Engineering Co. Infrared comparison micrometer, P (11) 320*d*. Method of making thermistor bolometers, P (3) 78*g*. Two path infrared gas analyzer having one enclosed path, P (9) 253*b*.

Barnett, I., and Speil, S. Handleable heat insulation shapes, P (2) 45*g*.

Barogenics, Inc. Compact hydrostatic pressure apparatus, P (10) 285*c*. Hydrostatic press for an elongated object, P (9) 250*c*. Multianvil apparatus and test bodies therefor, P (7) 195*a*.

Barr, H. N., and Frank, L. Fissionable fuel capsules and method of manufacturing them, P (9) 244*h*.

Barr, J. B. See Doman, R. C.

Barre, R. M. See Hosbein, J. W.

Barrelet, J. Everyday glass (abstract), B (11) 321*c*.

Barrer, R. M. Some features of ion exchange in crystals, (4) 120*a*.

Barrer, R. M., and Baynham, J. W. Process for making crystalline zeolite K-G, P (3) 84*j*.

Barrer, R. M., and Saxon-Napier, E. A. Dielectric properties of basic sodalite and a silver nitrate-zeolite complex, (8) 218*i*. Dielectric properties of some ion-exchanged analcites, (8) 219*a*.

Barrer, R. M., and Wasilewski, S. Occlusion of iodine in some porous crystals (I) heat and energy relations, (10) 295*h*; (II) entropy and free-energy relations, (10) 296*a*.

Barrett, W. T., Sanchez, M. G., and Vanik, M. C. Stable silica-clad thoria sols and their preparation, P (10) 278*a*.

Barry, R. L., and Richardson, W. W. Production of potassium fluosilicate, P (7) 198*b*.

Barry, T. I., and Kiter, K. γ-irradiation of zinc oxide and its effect on adsorbed layers, (10) 293*g*.

Barshad, I. Thermodynamics of water adsorption and desorption on montmorillonite, B (3) 91*i*.

Barta, C., and Nigrinova, J. Verneuil's method applied to monocrystals of the alkaline-earth metaniobates, B (9) 263*e*.

Barta, J. See Briggs, G.

Barta, R. Chemistry and Technology of Cement, B (9) 261*j*.

Bartch, D. W. See Deal, S. B.

Bartels, P. Means for measuring the optical thickness and/or absorption of small specimens, P (3) 81*e*.

Bartelt, D. Apparatus for classifying particulate material, P (7) 197*g*.

Bartenev, G. M. Two processes of vitrification, (5) 130*h*. See Tsepkov, L. P.

Barteniu, M. See Aleksandrovich, E.

Barth, T. F. W. Composition of nepheline, (11) 314*i*.

Bartholomew, G. A., and Bartholomew, T. Method and apparatus for pelleting molten slag, P (2) 46*c*.

Bartholomew, T. See Bartholomew, G. A.

Bartlett, E. P. Thermal protection of rocket-motor structures, (10) 276*e*.

Barton, L. E. Thermometer, P (5) 140*a*, P (9) 253*a*.

Barton, R. Cast iron for glass container molds, (3) 65*j*.

Bartram, S. F. See Felten, E. J.

Bartuska, M. Use of specific surface measurements for controlling aluminum oxide fineness, (9) 252*j*.

Basic, Inc. Dolomitic refractory, P (5) 133*f*.

Baskey, R. H. Fiber reinforcement of metallic and nonmetallic composites (I) state of art and bibliography of fiber metallurgy, (8) 213*b*.

Baskin, Y., and Schell, D. C. Phase studies in the binary system MgO–Ta_2O_5, (6) 174*d*.

Bassett, W., Caughey, R., and Long, R. A. Development of exo-reactant inorganic adhesive system, (8) 206*i*.

Bassi, A. Metallographic technique for uranium dioxide, (11) 306*d*.

Bassi, A., and Camona, G. Chemical polishing of uranium dioxide, (11) 312*j*. Etchant for sintered alumina, (11) 313*a*.

Bassi, A., Camona, G., Dassu, G., and Piazzesi, G. Study of fracture surfaces of sintered uranium oxide, (11) 306*i*.

Bastian, R. R., and Ottoson, A. Development work on improved high modulus structural glass fiber, (9) 239*g*.

Bastin, J. A., and Mitchell, E. W. J. Light scattering from heat treated synthetic quartz (4) 115*g*.

Basumallick, S. Crystal-optic study of secondary overgrowth in quartz, (8) 226*f*.

Bas'yas, I. P., and Kosolapov, E. F. Phase changes during the forming and destruction of the working layer of open-hearth furnace bottoms with single-layer repairs, (1) 14*h*.

Bates, J. L., Christensen, J. A., and Roake, W. E. Fission products and plutonium migrate in uranium dioxide fuel, (4) 101*c*.

Bates, T. Ligand field theory and absorption spectra of transition-metal ions in glasses, B (9) 263*j*.

Bates, T. F. Halloysite and gibbsite formation in Hawaii, B (5) 150*f*. See Hinckley, D. N.

Bath Iron Works Corp. Dust prevention device for rotary [hammer] impactor, P (7) 195*a*.

Batha, H. D. Study of fundamental mechanical properties of ceramic single crystals, (8) 230*b*.

Battle, J. H., and Marino, A. J., Jr. Development of manufacturing process for high purity electronic ceramics, (8) 218*f*.

Battle, J. H., Marino, A. J., Jr., and Currier, E. W. Development of manufacturing process for high purity electronic ceramics, (8) 218*h*.

Baudran, A. Moisture expansion of earthenware, B (10) 300*c*. Present tendencies in the ceramic industry (I), (4) 122*b*; (II), (4) 122*c*. Standards and labels for quality of ceramic products, (9) 258*e*. See Jung, E.

Bauer, H. See Francais, J.

Bauer, R. M. Design and the production man, (1) 2*e*.

Bauer, W., and Singer, E. Sintered hard materials from alumina and zirconium nitride, P (3) 75*a*.

Bauer, W., Singer, E., and Weyl, D. Strength-determining factors in the manufacture of porcelain insulators, B (10) 300*c*.

Bauer, W. C. See Conroy, A. R.

Baughman, G. M., and Erhardt, J. E., Jr. Vacuum coating apparatus, P (2) 50*e*.

Baukrowitz, G. Firing of intermittent kilns in the stoneware pipe industry with industrial gas, (10) 287*g*.

Bauleke, M. P. What's new in volcanic ash for industry? (3) 83*b*.

Bauleke, M. P., and McDowell, K. O. System lead oxide–zinc oxide, (7) 201*b*.

Baum, M. See Schmidt, W.

Baum, W. See Haenlein, W.

Baun, W. L., and McDevitt, N. T. Infrared absorption spectra of rare earths in the region 800 to 240 cm^{-1}, (8) 228*g*.

Baur, W. H. Atomic distances and bond angles in brookite, TiO_2, (10) 290*f*. Refinement of the crystal-structure determination of some compounds of the rutile type (I) TiO_2, SnO_2, GeO_2, and MgF_2, (10) 296*h*; (II) difluorides of manganese, iron, cobalt, nickel, and zinc, (10) 296*h*; (III) lattice theory of the rutile type, (10) 296*h*.

Bausch & Lomb, Inc. Densification of glass, germanium oxide, silica, or boric acid, P (10) 271*f*. Interferometer using a diffraction grating, P (9) 252*f*. Method of making aspheric optical elements, P (3) 70*f*. Neutral colored glass composition, P (10) 272*h*. Ratio measuring spectrophotometer, P (4) 121*i*.

Baustelnwerk der Stadt Kassel G.m.b.H. Crystalline stone from slag, P (4) 96*g*.

Baut, E. R., and Baut, H. S. Art glass panel, P (3) 64*a*.

Baut, H. S. See Baut, E. R.

Bautista, E. N. Glass button analysis, (9) 251*c*.

Bautista, E. N., Pasiliao, E. V., Lozano, R. M., and Sison, C. R. Preliminary ceramic tests on clay from Bondolan, San Dionisio, Iloilo (Philippines), (3) 83*a*.

Baybarz, R. D., and Lloyd, M. H. Process for separating americium and curium from rare earth elements, P (6) 176*a*.

Bayer, G. Aluminum, chromium, and gallium tellurates, P (4) 104*j*. Cerium tellurite and method of preparation, P (1) 20*c*. Inorganic metal oxides, P (1) 11*f*. Manufacture of refractory oxide coatings, P (1) 16*g*. Method for making titanium, zirconium, and tin tellurites, P (1) 21*j*. Method of producing cerium tellurite, P (1) 21*c*. New chromium-tungsten oxide and preparation, P (4) 105*j*. Titanium, zirconium, and tin tellurites, P (1) 22*b*.

Bayliss, P., and Warne, S. St. J. Effects of the controllable variables on differential thermal analysis, (6) 167*j*.

Baynham, J. W. See Barrer, R. M.

Bazinet, W. P., Jr. See Hicks, J. W., Jr.

Beach, H. J., and Morgan, H. C. Cement composition, P (4) 96*f*.

Beale, J. R. A. Semiconductor devices, P (4) 106*b*.

Beals, M. D., and Giess, E. A. Frit for opaque white ceramic glazes, P (4) 104*b*.

Beard, E. H. See Wall, J. R. D.

Beard, R. B. Measuring apparatus, P (2) 53*b*.

Beard, W. C., Butterman, W. C., et al. Research on phase equilibria between boron oxides and refractory oxides, including silicon and aluminum oxides, (8) 229*f*.

Beasley, R. M. See Wainer, E.

Beasley, R. M., and Johns, H. L. Inorganic fibers and method of preparation, P (7) 189*c*.

Beattie, C. W. Critical grain growth of special low-carbon metals, (2) 36*f*.

Beattie, I. R. See Barlow, D.

Beattie, R. D. See Antonsen, R.

Beaty, A. Q. See Harvey, J. L.

Beaudoin, A. E. See Marzocchi, A.

Beaver, W. W. Technology of beryllium and beryllium oxide, (8) 215*d*.

Becher, H. J. Beryllium boride BeB_{12} with β-boron structure, (4) 112*h*. Formation and stability of aluminum diboride, (4) 114*i*. Preparation and structure of an aluminum beryllium boride, (5) 145*f*.

Becher, H. J., and Schaefer, A. Preparation and structure of the beryllium boride Be_4B, (5) 145*g*.

Beck, C. W. See Harvey, R. D.; Tettenhorst, R.

Beck, C. W., and Brunton, G. X-ray and infrared data on hectorite-guanidines and montmorillonite-guanidines, B (3) 91*h*.

Beck, P. W. See Brockman, F. G.

Becker, C. H., Cox, G. C., and McLennan, D. B. Quartz ultraviolet lasers, (7) 192*a*.

Becker, C. W. See Mod, W. A.

Becker, J. H., and Frederikse, H. P. R. Electrical properties of nonstoichiometric semiconductors, B (9) 260*g*.

Becker, N. V. Insulating material, P (10) 277*b*.

Beckman Instruments, Inc. Detector for gas chromatography, P (8) 223*f*. Glass electrode, P (4) 99*h*. Method of making thin layer semiconductor devices, P (7) 193*j*. Temperature regulator for chromatographs, P (3) 90*a*.

Beckner, R. Method and apparatus for making a condensed filamentous [glass] mat, P (9) 242*e*.

Becue, C. Process for manufacturing aluminum oxide, P (3) 84*a*.

Beer, E. J. Medieval Swiss stained glass—an artistic interplay that transcended frontiers, (6) 153*j*.

Beer, H. B. Electrolytic production of mixed metal oxides, P (5) 141*b*.

Beeson, E. J. G., Stanyon, H. E., and Capp, L. J. Quartz-to-metal seals, P (11) 311*f*.

Beggs, J. E. Miniature metal-ceramic tubes, (2) 48*g*.

Behr, H. Hydraulic suspension system for gyratory crusher shafts, P (2) 55*i*.

Behrens, R. Glazes for cone 010, (7) 177*j*. Naples yellow from raw glazes, (7) 177*i*. Red and yellow glazes from uranium, (7) 178*a*.

Beintema, C. D. See Yaggy, L. S.

Beke, B. Grinding process and its state of equilibrium, (1) 22*j*.

Bel, A. Sintering of plutonium/uranium oxides, B (8) 232*b*.

Belikova, G. S., and Belyaev, L. M. Mixed organic crystals for scintillation counters, B (9) 263*a*.

Belikova, T. P., Galanin, M. D., and Sviridenkov, E. A. Photoconductivity and luminescence kinetics of a ZnS:Cu crystal phosphor under pulse excitation, (6) 164*i*.

Belitz, R. K. Differential etching of $BaTiO_3$ by H_3PO_4, (2) 56*f*.

Belknap, L. S., Berstein, G., and Antonsen, R. Process for making titanium dioxide [pigment], P (6) 171*b*.

Bell, J. E. Effect of glass fiber geometry on composite material strength, (6) 156*g*.

Bell, K. E. Some aspects of the plastic and related properties of Queenston shales, (2) 51*e*.

Bell, T., Hetherington, G., and Jack, K. H. Water in vitreous silica (II) some aspects of hydrogen-water-silica equilibria, (3) 68*j*.

Bell, W. C. Method and apparatus for making briquets, P (9) 243*c*.

Bell Telephone Laboratories, Inc. Boron oxide-lead oxide etchant and etching process, P (3) 89*i*. Fabrication of *pn* junction devices, P (7) 193*b*. Fabrication of semiconductor devices, P (8) 220*g*. Ferrimagnetic crystals, P (8) 220*i*. Garnet gemstones, P (9) 249*b*. Growing and determining epitaxial layer thickness, P (11) 311*c*. Growth of single crystals of corundum and gallium oxide, P (5) 148*a*. Light gas detector using thin walled [0.2 to 10 mils] glass tubes for diffusion, P (11) 304*j*. Low resistance contact for semiconductors, P (4) 105*f*. Magneto-optical information storage unit, P (2) 49*f*. Manufacture of solid electrolytic capacitors, P (10) 283*b*. Method of bonding metallic members, P (1) 5*a*. Method of controlling liquid-solid interfaces by Peltier heat, P (8) 222*b*. Microwave ferrite devices, P (2) 50*d*. Mullite synthesis, P (5) 136*h*. Photosensitive gas phase etching of semiconductors by selective radiation, P (10) 283*c*. Piezoelectric devices utilizing aluminum nitride, P (9) 249*c*. Piezoelectric devices utilizing cadmium sulfide, P (9) 249*d*. Piezoelectric devices utilizing zinc oxide, P (9) 249*d*. Process for coating with silicon dioxide, P (9) 249*e*. Process for electropolishing semiconductor surfaces, P (5) 137*c*. Process of growing single crystals, P (6) 171*e*. Protective element for hermetically enclosed semiconductor devices, P (7) 194*b*. Semiconductor device contact, P (5) 137*a*. Single crystal garnets, P (1) 21*i*. Terbium and cerium activated calcium fluoride optical maser material, P (6) 166*g*. Treatment of gallium arsenide, P (4) 106*a*, P (8) 221*a*. Vapor-solid diffusion of semiconductive material, P (3) 79*c*. Yttrium and rare earth borates, P (2) 50*f*.

Bellamy, B., Baker, T. W., and Livey, D. T. Lattice parameters and density of beryllium oxide determined by precise X-ray methods, (1) 28*b*.

Belling, P. R. High-pressure thermocouple feed through, (2) 53*j*.

Beloit Iron Works. Apparatus and method for measurement of moisture content, P (6) 168*h*. Centrifugal [vortical] classifier and stock cleaner, P (3) 83*e*. Instrument for the measurement of moisture, etc., P (6) 168*i*.

Belous, V. M., and Golub, S. I. Effect of infrared light on the luminescence of pure and mixed silver halide phosphors, (5) 134*c*.

Belser, R. B., and Hicklin, W. H. Method of forming a stable aluminum plated quartz resonator, P (1) 21*f*.

Belyaev, A. D., Vasilevskaya, V. N., and Miselyuk, E. G. Factors affecting the dislocations in germanium monocrystals, B (9) 263*c*.

Belyaev, G. I. Action of enamel melts on steel, (2) 36*e*.

Belyaev, G. I., Belyi, Ya. I., and Smakota, N. F. Effects of clay on certain enamel properties, (7) 183*c*.

Belyaev, I. N. Production of barium titanate monocrystals under nearly isothermal conditions, B (9) 263*f*.

Belyaev, L. M. See Belikova, G. S.; Beznosikov, B. V.

Belyaev, L. M., Koshuashvili, M. V., Chernyshev, K. S., Gorshtein, G. I., and Nechaeva, V. S. Growth of crystals of lead fluoride and lead chloride, B (9) 263*b*.

Belyaev, L. M., and Perl'shtein, V. A. Use of radioactive tracers in studies on crystal growth, B (9) 263*a*.

Belyi, Ya. I. See Belyaev, G. I.

Belyustin, A. V., Kolina, A. V., and Stepanova, N. S. Crystallization of spheres in the presence of impurities, B (9) 262*c*.

Belz, F. W. Exothermic high refractory mixture, P (7) 189*j*.

Bendix Corp. Apparatus for presenting source particles to a mass spectrometer, P (5) 148*a*. Fastener construction and processes of mounting metal-ceramic [friction] compositions, P (3) 73*j*. High temperature antifriction seal, material, and method of making, P (2) 45*h*. Oxygen determination, P (8) 224*d*. Radially vibratile ceramic transducers, P (2) 50*a*.

Benecke, J. H., Firma. Flexible material for protection against atomic, bacterial, or chemical warfare, P (4) 99*f*.

Benedetto, B. di. See Waugh, J. S.

Benediktova, N. B., Zamyatin, S. R., Memnonova, T. V., and Solomonov, E. F. Experience with the preparation of tar-dolomite brick and its testing in service, (7) 187*h*.

Benesovsky, F. (editor). Powder Metallurgy in the Nuclear Age—Plansee Proceedings 1961, B (3) 92*j*.

Benjamin, B. M. See Kohn, H. W.

Benjamin, W. O. Prismatic light transmitting panel, P (4) 100*b*.

Benner, D. W. Contaminants in compressed air, (2) 50*j*. Cost of air and leaks, (4) 106*f*. Selecting your air compressor, (2) 51*d*.

Bennet, E. L. Apparatus for combustion analysis, P (2) 59*j*.

Bennett, A. I. Crystal growing process, P (2) 60*a*.

Bennett, A. L. Sudan's ceramic industries, (2) 60*g*.

Bennett, H., Eardley, R. P., Hawley, W. G., and Thwaites, I. Accurate analysis of ceramic materials—a new method, (3) 80*c*. Routing control analysis of high-silica and aluminosilicate materials—a spectrophotometric method based on the use of the Unicam SP-600 spectrophotometer, (3) 81*c*.

Bennett, H., and Hawley, W. G. Determination of small quantities of fluorine by pyrohydrolysis, (11) 312*j*.

Bennett, H., Hawley, W. G., and Eardley, R. P. Accurate volumetric determination of alumina in aluminosilicates, (5) 141*i*.

Bennett, H. E. Measurement of specular reflectance at normal incidence, B (3) 93*c*.

Bennett, J. M. Phase change on reflection as a parameter for the determination of optical constants, B (3) 93*d*.

Bennett, N. G. See Rogers, E. A.

Bennett, S. L., and Biermann, W. J. Solubility of beryllium oxide in aqueous beryllium sulfate solution, (3) 88*h*.

Bennett, W. H. Method and apparatus for producing electrically conducting coatings on vitreous substances, P (5) 131*f*.

Benning, C. J. Ball milling apparatus, P (2) 51*i*.

Benson, C. L., and Tingquist, S. C. Making refractory shell molds, P (1) 16*f*.

Benson, D. H. See Pratt, W. R.

Benson, G. C., Freeman, P. I., and Dempsey, E. Calculation of cohesive and surface energies of thorium and uranium dioxides, (3) 85*i*.

Benson, G. E., and Saunders, H. M. Apparatus for feeding a multifilament strand, P (4) 99*d*.

Benson, J. M. Thermal conductivity vacuum gages, (7) 196*a*.

Benson, J. M., and Horne, R. Surface temperature of thin sheets and filaments, (2) 52*h*.

Bentley, K. E., and Cole, L. G. Oxygen detection, P (8) 224*d*.

Bentley, R. A. See Bergman, I.

Benton, L. A. Continuous dry blender, P (9) 250*a*.

Berg, D. See Dakin, T. W.; Hirayama, C.

Berg, L. G. Introduction to Thermography, B (5) 151*b*.

Berg, P. W. Reduction of glazes containing copper and provision of the reducing atmosphere, B (4) 124*c*.

Berg, S. A. Examination and evaluation of cords in glass containers, (1) 6*f*.

Berge, P. See Dubois, M.

Bergeron, C. G., Russell, C. K., and Friedberg, A. L. Crystallization of the perovskite lead titanate from glasses, (9) 239*h*. Thermal analysis of lead borate glasses during crystallization, (7) 185*c*.

Berggren, L. See Dahle, O.

Bergin, J. A. See Feldman, C. L.

Bergman, I., Cartwright, J., and Bentley, R. A. Mechanism for the dissolution of ground quartz powders in dilute HF—an "easily soluble core" and its relation to the "easily soluble layer," (10) 295*g*.

Bergman, I., and Casswell, C. Disturbed layer on ground and shattered quartz powders of respirable size, (3) 86*i*.

Bergmann, A. E. H. Froth flotation of cryolite, P (7) 197*h*.

Bergseth, H. Comparison of the electrophoretic migration velocity of particles of a swelling and a nonswelling layer silicate, (3) 86*c*.

Bergstein, F. D., and Nerenberg, R. W. Method for casting clay coating, P (2) 51*e*.

Bergstein Packaging Trust. Method for casting clay coating, P (2) 51*e*.

Bergstrom, J. H. Bethlehem Limestone Co. launches sleek stone plant, (7) 178*f*. Lightweight aggregate operation with heavyweight capability, (6) 158*i*. Nytralite is newest contender in lightweight scramble, (6) 159*b*. Permanente doubles capacity at Cushenbury, (10) 267*g*. Space age technology highlights Ohio cement plant, (9) 237*e*.

Berkeyheiser, J. E., Jr. See Pankove, J. I.

Berkovich, T. M., Kheiker, D. M., Gracheva O. I., Zevin, L. S., and Kupreeva, N. I. Investigation of properties of calcium hydrosilicates, (1) 2*g*.

Berlincourt, D., and Jaffe, H. Elastic and piezoelectric coefficients of single-crystal barium titanate, (4) 113*c*.

Berlincourt, D. A. See Austerman, S. B.

Berman, H. A., and Newman, E. S. Heat of formation of calcium trisulfoaluminate at 25°C, B (5) 149*e*.

Berman, Sh. M. See Antonov, G. I.

Bermudez de Castro, M. H. See Hernaiz Bermudez de Castro, M.

Bernados, J. E. See Kelble, J. M.

Bernard, J. L., Gauthron, M., and Gautier, A. Methods and apparatus for the determination of thermal stresses, P (5) 139*h*.

Bernard, N. See Pierrot, A.

Berner, R. A. Pallet, P (6) 167*f*.

Bernhardi, T. G. Hydraulic classifier, P (4) 106*h*.

Bernoff, R. A., and Conroy, L. E. Lead tungstate bronzes, (4) 104*g*.

Bernsen, S. A., Hopkins, H. C., Jr., and Howard, R. C. Development of the semihomogeneous fuel element for a gas-cooled reactor, (4) 100*i*.

Bernstein, F. Distribution of water and electrolyte between homoionic clays and saturating NaCl solutions, B (3) 91*j*.

Berry, J. P. Strength and fracture properties of glassy polymers, B (9) 263*i*.

Berry, K. L. Fibrous aluminum borate and its preparation, P (6) 162*b*.

Berry, T. F. See Koch, W. J.

Bersohn, R. Solid-state perturbations of nuclear quadrupole coupling constants, B (9) 259*d*.

Berstein, G. See Belknap, L. S.

Bersudsky, S. Facets of design from the view of the designer, (1) 2*c*.

Bertaut, F., Forrat, F., and Fang, P. Rare earth and yttrium manganates—a new class of ferroelectrics, (9) 248*g*.

Berthier, R. M. Cements from slags containing fluorine compounds, P (3) 65*a*. Thermal treatment of blast-furnace slags, P (4) 96*i*.

Bertolacini, R. J., and Brennan, H. M. Method of controlling properties of porous metal oxides, P (10) 289*d*.

Bertozzi, G., Coceva, C., and Pizzini, S. Study on some scintillating glasses, (11) 304*j*.

Besborodov, M. A. See Bezbordov, M. A.

Bess, L. Radiationless recombination in phosphors, (4) 119*a*.

Best, E. F. See Swift, H. R.

Best, P., and Thorpe, T. Coherent boron powder bodies, P (2) 45*c*.

Beteiligungs- und Patentverwaltungsges.m.b.H. Arrangement for loading bulk material into compartments arranged alongside each other, P (1) 25*f*. Manganese-zinc ferrites, P (2) 49*h*.

Bethlehem Steel Co. Chrome silica brick, P (7) 189*i*. Hot top seal, P (9) 244*b*.

Better Industries, Inc. Apparatus for producing fibers from molten material, P (4) 99*g*.

Bettermann, G. A. See Hilgers, G.

Beutelspacher, H., and Marei, H. W. van der. Characteristics for the identification of kaolinite, "fireclay mineral," and halloysite and their distribution and formation, (4) 112*d*.

Bezborodov, M. A., and Kachan, I. S. Effect of zirconium and titanium on certain properties of silicate glasses, (2) 38*i*.

Bezborodov, M. A., and Khodskii, L. G. White enamel for aluminum, P (2) 38*f*.

Bezborodov, M. A., Mazo, E. E., and Mel'nik, M. T. Decolorizing of manganese glass, (6) 156*d*.

Bezborodov, M. A., and Zadneprovsky, J. A. Early stages of glassmaking in the USSR (abstract), B (11) 321*e*.

Beznosikov, B. V., Dobrzhanskii, G. F., Belyaev, L. M., and Chadaeva, V. V. Growth and pressure treatment of silver chloride crystals, B (9) 263*b*.

Bezruk, E. T. See Markovskii, L. Ya.

Bhatt, M. P. See Sapre, R. K.

Bhattacharya, H. See Droste, J. B.

Bhattacharya, N. Recent advances in clay mineralogy as applied to petroleum industry (I) fundamental generalizations, (3) 83*e*; (II) exploration and production, (6) 170*h*.

Bhide, V. G., and Dani, R. H. Electrical conductivity in oxides of manganese and related compounds, (7) 191*f*.

Bick, F. P., Rado, P., and Philpott, A. A. Symposium on nuclear ceramics: Fabrication of slip-cast urania ceramics, (11) 307*c*.

Bickerdike, R. L., and Hughes, G. Method of making carbon articles, P (8) 216*a*.

Bickerstaff, Inc. Apparatus for lifting a stack of building units, etc., P (3) 71*h*.

Bickley Furnaces, Inc. Burner assembly, P (2) 53*i*.

Bicknell, C. E. Machine for handling semiconductor material, P (6) 166*e*.

Biddulph, A. Architectural enameling, B (11) 322*g*.

Bieda, W., and Piatkowski, W. Alkali-bonded unfired refractories, P (2) 45*i*.

Bieda, W., Piatkowski, W., Piotrowski, Z., and Laurecka, H. Refractories for metal casting, P (2) 46*e*.

Biefeld, L. P., Philippe, T. E., and Collier, T. J. Glass fibers coated with an organosilicon polyol, P (7) 186*d*.

Bielanski, A., Deren, J., Haber, J., and Sloczynski, J. Physicochemical properties of alkali- and iron-doped nickel oxide, (8) 219*d*.

Bielenberg, W., Rodis, F., Ziegler, H. W., Dronsek, G., and Hinz, A. Process and apparatus for the drying and burning of pellets, P (11) 312*a*.

Bieling, C. R. See Elder, J. T.

Bielinski, G. D. See Bielinski, J. D.

Bielinski, J. D., and Bielinski, G. D. Bottle inspection and detecting method and apparatus, P (5) 130*d*.

Bierbrauer, G. Antimony compounds as raw materials for majolica colors and glazes, (4) 103*e*.

Biermann, W. J. See Bennett, S. L.

Bigelow, C. G., Jr. Burner, P (6) 169*c*.

Bigelow, J. E. X-ray analyzing apparatus wherein two comparative detector channels have different absorption versus frequency characteristics, P (11) 320*c*.

Bigge, H. C. Hot top seal, P (9) 244*b*.

Bigler, R. R., and Washburn, E. M. Crystal unit, P (5) 135*f*.

Billett, S. M. See Marzocchi, A.

Billian, C. J. Conducting solder glass compositions, P (6) 157*h*. Phosphorescent glasses and method of making them, P (6) 158*h*.

Billinger, W. F. Automotive glass cutting machines, P (1) 11*a*.

Billings, D. D. See Conroy, A. R.

Billmeyer, F. W., Jr. Systematic description of color, (8) 230*i*.

Billmeyer, J. G. Fastener construction and processes of mounting metal-ceramic [friction] compositions, P (3) 73*j*.

Billue, R. F. Fractured clay, P (2) 55*h*.

Bimson, M. See Werner, A. E.

Binns, D. B. Some physical properties of two-phase crystal-glass solids, B (4) 124*a*.

Birch, R. E. See King, D. F.

Birchall, J. See O'Riley, L.

Birdsboro Corp. Hydraulic [brick] press, P (6) 167*c*.

Birks, J. B., and Hart, J. (editors). Progress in Dielectrics (Vol. 4), B (9) 263*f*.

Birman, J. L. Theory of the piezoelectric effect in the zinc blende structure, (2) 59*f*.

Birss, F. W. See Thorvaldson, T.

Bischoff, D. F. See Bischoff, F. W.

Bischoff, F. New knowledge on dolomite, B (10) 300*g*.

Bischoff, F. W., and Bischoff, D. F. Apparatus for slaking lime, P (3) 64*h*.

Bishay, A. M. Anomalous gamma-ray-induced coloring of some glasses containing cerium, (1) 5*e*. Gamma radiation dosage measuring glasses and method of using, P (9) 241*j*. Glass composition and process of making, P (1) 11*j*.

Bishop, J. E., and Hanke, A. R. New phase in the lead chromate–lead molybdate system, (1) 28*g*.

Bishui, B. M., and Ghosh, D. K. Intensity of illumination of light from locomotive headlight fitted with metal reflector, (11) 304*d*.

Bisque, R. E. Clay polymerization in carbonate rocks: a silicification reaction defined, B (5) 150*g*.

Bitter, J. G. A. Study of erosion phenomena (I), (9) 236*a*.

Black, H. Lava glazes, (4) 95*i*.

Black, L. V. Apparatus for bending [nonuniformly curved] sheet glass, P (4) 99*c*.

Blackburn, W. S. Collapse of tubes of uranium and silicon carbide, (10) 274*c*.

Blackwood, G. W., and Shanklin, D. L. Cement pack set inhibitor, P (9) 237*c*.

Blade, L. V. See Milton, C.

Blaha, E. Apparatus for forming clay spheres, P (4) 106*e*. Manufacture of uniform cellular ceramic articles, P (2) 46*a*.

Blaies, H. O., Jr., and Froberger, C. F. Foundry process and molding mixture, P (4) 102*g*.

Blaine, R. L. Proton magnetic resonance in hydrated portland cements, B (5) 149*b*. See Evans, D. N.

Blair, G. E. See Hamblen, D. P.

Blake, L. R. Irradiation of uranium metal and uranium oxide fuel pins to high burnup at high temperatures, (10) 274*g*.

Blakeley, T. H. See White, A. E. S.

Blakemore, G. Simple chromatographic gas-analysis apparatus, (1) 23*i*.

Blakeslee, A. E. See Elder, J. T.

Blanc, G. See Dubois, M.

Blanco, D. M. See Martinez Blanco, D.

Blander, M., Braunstein, J., and Silverman, M. D. Heats of solution of solids in molten reciprocal salt systems, (10) 293*j*.

Blank, B., Rossington, D. R., and Weinland, L. A. Adsorption of admixtures on portland cement, (10) 266*c*.

Blank, H. Transmission electron microscopy of ceramic single crystals, (10) 286*g*.
Blasum, H. A., and Claus, D. Dust measurements in the ceramic industry, (3) 90*b*.
Blat Monzo, A. Clay tiles [of] ancient Paterna, P (9) 236*f*. Paterna ceramics, (6) 153*i*.
Blau, H. H., Jr., and Fischer, H. (editors). Radiative Transfer from Solid Materials—Proceedings of a Conference Sponsored by the Air Force Cambridge Research Laboratories and Arthur D. Little, Inc., Boston, Mass., December 1960, B (3) 92*j*.
Blau, R. E. Cement industry weathervanes, (10) 266*g*.
Blazek, R. J. Light-transmitting, electrically conducting element, P (5) 136*i*.
Bleaney, B. Electron spin resonance of point defects in CaF_2, B (9) 260*d*.
Bletzacker, R. W. Rheology of portland-cement concrete, (10) 267*c*.
Blickwede, D. J. See Frame, J. W.
Blin, C. Financial benefits of quality control of raw material, (9) 253*j*. Survey of the ceramic industries of Latin America, (6) 176*d*.
Blinov, V. A. See Kitaigorodskii, I. I.
Bliton, J. L., and Havell, R. Physical properties of flame-sprayed ceramic coatings (II) $BaTiO_3$, (1) 4*b*.
Bliton, J. L., Rechter, H. L., and Harada, Y. Flame sprayed zirconia films for fuel cell components, (2) 36*h*.
Blitstein, N. I. See Barke, V. N.
Blizard, E. P., and Abbott, L. S. (editors). Reactor Handbook (Vol. III, part B) Shielding, B (10) 299*j*.
Bliznakov, G. Kinetic theory of epitaxis, B (9) 262*b*.
Bloch, W. E. H. Ceramic bodies for dry pressing of electric heating elements, P (6) 165*i*.
Blocher, J. M., Jr. Chemical vapor deposition—a rediscovered tool for molecular engineering, (10) 284*b*.
Blocher, J. M., Jr., and Campbell, I. E. Carbide coatings for graphite, (10) 268*h*.
Block, A. Segment for rotary abrasive devices, P (1) 2*a*.
Block, S. See Engelhardt, H.; Piermarini, G. J.
Bloem, J. See Lemmens, H. J.
Bloembergen, N. Wave propagation in nonlinear electromagnetic media, (7) 193*b*.
Blokh, S. A. See Zakharikov, N. A.
Blondiau, L. Porosity, (1) 3*a*. Storage of supersulfated cement, (1) 3*d*.
Blood, G. See Watson, W. H.
Bloom, F. S. Internally cooled conveyor roll, P (2) 54*a*.
Bloom, H., and Welch, B. J. Molten salt mixtures (V) activity determinations from vapor-pressure measurements in molten salt systems, (10) 295*b*.
Bloom Engineering Co. Internally cooled conveyor roll, P (2) 54*a*.
Bloss, F. D. See Gibbs, G. V.
Blount, C. W. See Dickson, F. W.
Bloxam, T. W. Screened Eriochrome indicator for determining magnesium [in silicate rocks] with ethylenediaminetetraacetic acid, (3) 81*d*.
Boardman, G., and Whitmore, R. L. Behavior of a Bingham fluid in the cone-and-plate viscometer, (10) 278*c*.
Boatman, P. M. Oxygen determination, P (8) 224*d*.
Bobear, W. J. Method of bonding [glass fiber tape to silicone rubber material], P (1) 12*b*.
Bobovich, Ya. S. Investigation of the structure of glassy phosphates using Raman spectra, (6) 156*b*.
Bobovich, Ya. S., and Tolub, T. P. Raman spectra of alkali germanate glasses, (5) 129*c*.
Bockris, J. O'M. See Inman, D.
Boddye, E. T., and Elderfield, R. N. Bottom-making and relining practice in a VLN steel-plant, (6) 161*j*.
Bodenseewerk Perkin-Elmer & Co., G.m.b.H. Spectroscope, P (1) 24*f*.
Bodi, G. M., and Hauri, D. Apparatus for pressing glass sheet and plastic assemblies, P (4) 99*e*.
Bodine, A. G., Jr. Sonic apparatus for material separation, P (5) 141*e*. Sonic process for materials separation, P (5) 141*g*.
Bodine, E. G. Design with rate-sensitive ceramics, (10) 298*b*.
Bodman, G. B. See Watt, H. v. H. van der.
Bodrova, N. I. See Buzhinskii, I. M.
Boehm, H. See Schreiner, H.
Boehm, H. P. See Hofmann, U.
Boehme, G., Krupp, H., Rabenhorst, H., and Sandstede, G. Adhesion measurements involving small particles, (9) 250*j*.
Boerdlein, H. Light transmitting building tile, plate, block, or the like and method of making it, P (9) 242*c*.
Boettger, O., and Meister, W. Semiconducting properties of silver telluride (Ag_2Te), (4) 104*j*.
Boffe, M. See Plumat, E.
Boffe, M., and Letocart, G. Influence of the size of raw materials on the rate of melting of glass, (3) 66*e*.
Bogorodskaya, L. P. See Iskol'dskii, I. I.
Boguslavskii, I. A., and Sil'vestrovich, S. I. Strengthening of glass, P (2) 43*a*.
Bohmann, M. See Primak, W.
Bohmann, T. See Juza, R.
Boicey, J. H. See Marriott, J. G.
Boicey, J. H., and Henning, F. E. Apparatus for pressing glass-plastic sandwiches, P (11) 304*g*.
Boicey, J. H., and Williams, C. B., Jr. Apparatus for pressing curved laminated safety glass, P (2) 41*i*.
Boies, D. B., Bregman, J. I., and Newman, T. R. Corrosion inhibition with molecularly dehydrated phosphate glass, P (3) 69*e*.
Bokov, V. A. See Myl'nikova, I. E.
Boksha, S. S. High-pressure gas apparatus for use in crystal growing, B (9) 262*i*.
Boland, P. See Fleming, J. D.
Boles, S. J. Rare-earth compounds as high-temperature refractories—a bibliography, (1) 14*j*. Uses and properties of magnesia as a superrefractory for temperatures above 1500°C—a bibliography, (3) 73*e*.
Bolidens Gruvaktiebolag. Rock grinding system, P (10) 290*b*.
Bollin, E. M., and Kerr, P. F. Differential thermal pyrosynthesis, (4) 107*d*.
Bollmann, W. Dark field electron microscopy applied to radiation damage in graphite, B (8) 233*e*.
Bolton, H. C., Fawcett, W., and Gurney, I. D. C. Electric field in crystals—the refractivity of rutile, (5) 143*h*.
Bolz, H. M. Spectroscope, P (1) 24*f*.
Boncz, C., and Gink, K. Herend China, B (10) 299*b*.
Bond, F. C. Crushing and grinding calculations (I), (1) 22*f*.
Bondar, I. A. See Toropov, N. A.
Bondley, R. J. Method of making composite bodies, P (11) 311*h*. Window materials for high-power microwave tubes, (10) 282*b*.
Bondurant, J. E. See Nelson, E. W.
Bonner, W. A. See Van Uitert, L. G.
Bonsels, W. H. See Pohl, F. A.
Boose, C. Device for fractionating deposits of dust for particle size analysis, (2) 52*c*.
Booth, C., Hedley, C. S., and Gilpin, W. C. Refractory materials, P (3) 74*g*.
Booth, C. L., and Rindone, G. E. Surface nucleation of glass fibers, B (11) 320*i*.
Booth, H. See Davies, L. J.
Booth, I. M. William Billingsley and the Pinxton china factory—unpublished original factory records (I, II), (6) 153*h*.
Borasky, R., and Sorrell, C. A. Vacuum-firing and high-temperature replication of kaolinite, (7) 201*f*.
Borchardt, H. J. Yttrium-tungsten oxides, (7) 201*g*.
Borger, J. W. Container for pulverant material and method and apparatus for unloading it, P (4) 110*h*.
Borger, J. W., and Vander Linden, F. A. Apparatus for unloading bulk materials from hopper cars, P (4) 110*d*.
Borgman, V. A., and Chistoserdov, V. G. Absorption bands of latent image centers in photosensitive glasses, (5) 128*f*. Coloring of photosensitive glasses by X-radiation, (6) 156*a*.
Borisenko, A. I. Preparation of thin-layer silicate coatings from solutions, (4) 97*b*.
Borisov, B. I. See Solinov, F. G.
Borisov, K. I. Glass industry of the People's Republic of Bulgaria, (1) 7*a*.
Borisov, V. T. Temperature at the growth front of a mercury crystal, B (9) 262*f*.
Borrelli, N. F. See McSwain, B. D.; Su, G.-J.
Borrelli, N. F., McSwain, B. D., and Su, G.-J. Infrared spectra of vitreous boron oxide and sodium borate glasses, (8) 209*c*.
Borsig Akt.-Ges. and Aktiebolaget Svensk Torvforadling. Diaphragm filter press, P (10) 285*d*.
Borst, L. B. Temperature measuring method and apparatus, P (11) 313*j*.
Bortaud, M. See Halm, L.
Bortz, S. A., and Lund, H. H. Brittle ring test, B (3) 92*d*.
Bose, A. K. Assessing the quality of a refractory, (9) 243*d*.
Bosley, J. J., and Stephenson, R. L. Method for producing high-temperature cement in the blast furnace, P (1) 3*e*.
Bostock, J. H. Mold inspection techniques, (4) 98*h*.
Boston, J. R. See Stiefbold, D. R.
Bostroem, T. Treatment of "sick glasses," (1) 10*d*.
Boswell, D., and Miller, J. S. Electrical devices having hermetically sealed envelopes, P (3) 77*i*.
Bottger, G. See Dows, D. A.
Botvinkin, O. K., and Ananich, N. I. Orientational effect and shape birefringence in sodium borosilicate glasses, B (11) 321*b*.
Bouchard, G. H. Electroluminescent device, P (4) 105*j*.
Boulton, William, Ltd. See William Boulton, Ltd.
Bourdeau, R. G. Bonding process and product thereof, P (6) 165*g*. New pyrolytic materials, (2) 44*h*.
Bourdelais, C. H. See Kuck, J. A.
Bourgeaux, M. Apparatus for drawing uniform fibers of thermoplastic materials, P (2) 41*a*.
Bourgeaux, M., and Naudin, F. Articles made of a transparent material such as glass sheets, bricks, or blocks and having variable transparency or coloration, P (8) 210*i*. Sheets, bricks, blocks, etc., made of glass, P (8) 211*e*.
Boutry, M. Utilization of coal-washery shales in the heavy-clay industry, B (10) 300*j*.
Bovenkerk, H. P. Method for production of etched diamond, P (7) 177*g*. See Bundy, F. P.
Bowden, G. H. See Patrick, M. C.
Bowen, D. H. See Clarke, F. J. P.
Bowen, M. D. See Walton, J. D., Jr.
Bowen, S. W., and Marks, M. L. Chromatography, P (10) 287*b*.
Bowie, W. S. High temperature electrostatic precipitator and method of operation, P (2) 51*d*.
Bowles, R., and Sugarman, B. Strength and deflection characteristics of large rectangular glass panels under uniform pressure, (3) 68*b*.
Bowman, A. L. See Helms, S. B.
Boyarskaya, Yu. S., Val'kovskaya, M. I., and Savel'ev, N. T. Direct method for measuring the elastic recovery of indentation marks in microhardness measurements on transparent substances, (6) 167*i*.
Boyd, A. R. Glass fiber size comprising an aqueous dispersion of a film forming polymer, a coupling agent, and polyvinyl pyrrolidone, P (7) 186*d*.
Boyd, D. R., and Sihvonen, Y. T. Process of applying ohmic contacts to crystals, P (5) 137*b*.
Boyer, E. W. Method and apparatus for operating an analytical mass spectrometer with a getter-ion pump, P (2) 60*c*.
Boyer, E. W., Ford, H. T., and McKelvey, E. E. Method and apparatus for connecting a getter-ion pump to an analytical mass spectrometer, P (1) 31*c*.
Boyer, N. E. See Frank, J. M.
Boyer, W. H. See Van Dreser, M. L.
Boylan, D. R. See Wheelock, T. D.
Boyle, W. S. See Nelson, D. F.
Bozhenov, P. I., Kavalerova, V. I., Salnikova, V. S., and Suvorova, G. F. Influence of high pressure steam on the hardening of calcium and magnesium silicates and of cements of different compositions, B (5) 149*g*.
Brace, W. F., and Walsh, J. B. Direct measurements of the surface energy of quartz and orthoclase, (8) 227*g*.
Bradbury, B. T. Symposium on nuclear ceramics: Microstructural changes produced in uranium oxide during irradiation and under the influence of high temperature gradients, (11) 307*g*. See Robins, R. G.
Bradfield, G. See McKennell, R.
Bradley, A. A. See Talbot, J. H.
Bradley, J. M. See Antonsen, R.
Bradley, M. J., and Ferris, L. M. Hydrolysis of uranium carbides between 25° and 100° (I) uranium monocarbide, (1) 28*h*.
Bradley, R. S. Thermodynamic calculations on phase equilibria involving fused salts (I) general theory and application to equilibria involving calcium carbonate at high pressure, (2) 59*j*; (II) solid solutions and applications to the olivines, (2) 59*a*.
Bradley, W. F. See Grim, R. E.
Bradstreet, S. W. See Rechter, H. L.
Bradstreet, S. W., and Harada, Y. Synthesis of refractory mixed oxide with perovskite structure, (9) 257*i*.
Brady, J. G. Clays and clay products, (7) 202*a*. Effect of the mineralogical composition of Whitemud formation clays on their utilization, (10) 292*d*. Nature and properties of some western Canada clays, (2) 54*c*.
Brakel, L. H., and Jones, J. B., Jr. Antisegregation charge [multiple] feeder for shaft kilns, etc., P (4) 96*e*.
Branchereau, M., and Navez, M. Furnace adapted for use in dilatometry, P (8) 224*h*.
Brand, H. Use of mechanical presses in the refractories industry, (10) 276*g*.
Brand, H. R. Nuclear fuel element assembly and method of fabricating it, P (8) 216*i*.
Brandt, H. Shaking device for electric filters and a method for operating it, P (8) 222*a*.
Braniski, A. Refractory barium-aluminous cement and concrete, B (5) 150*d*.
Branwood, A., Hughes, O. H., Hurd, J. D., and Tredgold, R. H. Evidence for space charge conduction in barium titanate single crystals, (5) 143*b*.
Bratschun, W. R. Barium zirconate-lead titanate ferroelectric ceramics, (5) 134*d*. Sintering of doped and undoped barium titanate, (2) 58*f*.
Bratton, E. W. Sectional coated abrasive belt and process of making it, P (1) 2*b*.
Bratton, R. J., and Brindley, G. W. Structure-controlled reactions in kaolinite-diaspore-boehmite clays, (1) 30*f*.
Brauer, G. Nitrides, carbonitrides, and oxynitrides of niobium, B (7) 202*d*.
Brauer, G., and Esselborn, R. Nitride phases of niobium, (4) 117*a*. Oxonitrides of niobium, (4) 117*g*.
Brauer, G., and Morawietz, H. Investigations of the structure of niobium monoxide, NbO, (4) 115*h*.
Brauer, G., Muller, H., and Kuhner, G. Oxides of the low temperature oxidation of niobium and tantalum, (10) 296*e*.
Brauer, J. B. Microwave acoustic delay line, P (4) 105*i*.
Braun, Max, Firma. See Max Braun, Firma.
Braun, W. H. See Cliff, G. J.
Braunagel, M. V. Multiple thermocouple circuit, P (1) 24*c*.
Braune, R. See Brock, G. W.
Braunstein, J. See Blander, M.
Bray, P. J. See Kim, Y. W.; Lee, S.
Bray, P. J., Leventhal, M., and Hooper, H. O. Nuclear magnetic resonance investigations of the structure of lead borate glasses, (9) 241*a*.
Bray, P. J., and O'Keefe, J. G. Nuclear magnetic resonance investigations of the structure of alkali borate glasses, (9) 240*i*.
Brayman, J. See Gerard, G.
Brearley, W., Hastilow, P. A. P., and Holloway, D. G. Breaking strengths of some commercial glasses, (7) 184*d*.

Brearley, W., and Holloway, D. G. Effect of heat treatment on the breaking strength of glass, (10) 270*e*.

Brebrick, R. F. Statistical mechanics of dilute solid solutions, B (9) 260*d*.

Breck, D. W. Crystalline zeolite S, P (2) 55*f*.

Bredsdorff, P., Idorn, G. M., Kjaer, A., Plum, N. M., and Poulsen, E. Chemical reactions involving aggregate, B (5) 149*i*.

Breedlove, J. G. High hardness porcelain enamel composition, method of coating therewith, and article produced thereby, P (10) 269*b*.

Breen, S., and Mason, S. J. Method and apparatus for measuring capacitivity of materials, P (9) 252*h*.

Bregman, J. I. See Boies, D. B.

Brendel, O., Grantz, K., Hofstadt, K. E., and Franz, W. Method and apparatus for mass-producing small balls of plastic materials, P (1) 23*a*.

Brennan, H. M. See Bertolacini, R. J.

Brennan, J. H., and Scott, S. W. Process for producing molybdenum disilicide, P (2) 46*a*.

Bresler, M. S. See Airapetyants, S. V.

Brett, N. H., Harrison, J. D. L., and Russell, L. E. Production of PuO_2–UO_2 irradiation pellets, B (8) 231*j*.

Brett, N. H., and Russell, L. E. Symposium on nuclear ceramics: Sintering behavior and stability of $(PuU)O_2$ solid solutions, (11) 306*j*. Thermal expansion of PuO_2 and some other actinide oxides between room temperature and 1000°C, B (8) 231*f*.

Brewer, A. G. See Morrow, A. S.

Brezinski, J. P. Centrifugal [vortical] classifier and stock cleaner, P (3) 83*e*.

Brichard, E., Plumat, E., Meunier, G., and Deliere, E. Process and apparatus for obtaining electrically conductive coatings on the surface of objects consisting of glass or ceramic materials, P (8) 211*i*.

Brickwedde, F. G. (editor). Temperature—Its Measurement and Control in Science and Industry (Vol. III, part I) Basic Concepts, Standards and Methods, B (9) 259*h*.

Bridgewater, T. E. Breaker plate structure [for a crusher], P (9) 254*i*. Breaker plate structure for impact crusher and retaining means therefor, P (8) 221*f*. Impact crushing apparatus, P (5) 141*c*.

Bridwell, H. C. Obtaining unaltered core samples, P (3) 84*d*.

Briggs, G., Guha, J., Barta, J., and White, J. Symposium on nuclear ceramics: Systems of UC, UC_2, and UN with transition metals, (11) 307*f*.

Bright, J. E., and Ridge, M. J. Twinned crystals of precipitated gypsum, (9) 257*d*.

Bright, R. C. See Papike, J. J.

Bril, A., and Gelling, W. G. Conductivity induced by cathode rays in cadmium selenide layers, (5) 134*g*.

Bril, A., and Meurs-Hoekstra, W. van. Absolute efficiency measurements of infrared fluorescent zinc and cadmium sulfide activated with V,Ag and V,Cu, (5) 134*d*.

Bril, K. J. See Krumholz, P.

Bril, K. J., and Krumholz, P. Process for separating yttrium and rare earths, P (6) 176*b*.

Brill, R. H., and Moll, S. Electron beam probe microanalysis of ancient glass, B (11) 321*e*.

Brillhart, M. F. See Griss, C. H.

Brilliantov, N. A. See Grum-Grzhimailo, S. V.

Brindley, G. W. See Bratton, R. J.; De Kimpe, C.; Hoffmann, R. W.

Brindley, G. W., and Choe, J. O. Reaction series gibbsite → chi alumina → kappa alumina → corundum (I), (4) 119*g*.

Brindley, G. W., and De Kimpe, C. Identification of clay minerals by single crystal electron diffraction, (4) 107*h*.

Brindley, G. W., and Hoffmann, R. W. Orientation and packing of aliphatic chain molecules on montmorillonite, B (5) 150*j*.

Brindley, G. W., and Kurtossy, S. S. Quantitative determination of kaolinite by X-ray diffraction, (4) 107*d*; reply, (6) 168*g*.

Brindley, G. W., and Ougland, R. M. Quantitative studies of high temperature reactions of quartz-kaolinite-feldspar mixtures, (3) 75*g*.

Brindley, G. W., and Sandalaki, Z. Structure, composition, and genesis of some long-spacing mica-like minerals, (6) 170*a*.

Brisbin, P. H., and Heffernan, W. J. Method for the preparation of alumina fibers, P (10) 277*g*.

Brissette, L. A. See Spriggs, R. M.

Bristow, R. H. Forsterite-spinel ceramic bodies, P (2) 49*b*.

British Dielectric Research, Ltd. Ceramic dielectric materials and capacitors incorporating them, P (4) 105*b*.

British Industrial Sand, Ltd. Purification of sand containing color-imparting impurities, P (1) 26*d*. Removal of iron-containing materials from sand, P (3) 85*e*.

British Oxygen Co., Ltd. Method of and apparatus for oxygen determination, P (8) 224*c*.

British Periclase Co., Ltd. Refractory materials, P (3) 74*g*.

British Thomson-Houston Co., Ltd. Colored silicate coatings for glass, P (4) 99*a*.

British Titan Products Co., Ltd. Method of preparing metal oxides, P (4) 111*b*. Preparation of titanium dioxide, P (10) 289*i*. Process for reducing the acidity of oxides, P (2) 55*e*. Treatment of titanium dioxide, P (8) 226*a*.

Brittain, J. O. See Dahlberg, P.; Hirthe, W. M.

Brixner, L. H. Rare-earth arsenides, P (8) 220*j*.

Broch, O. A. Quick identification of potash feldspar, plagioclase, and quartz for quantitative thin section analysis, (4) 107*g*.

Brock, G. W., and Braune, R. Simple direct-stress fatigue machine for cumulative damage studies, (2) 52*e*.

Brockman, F. G., Beck, P. W., and Steneck, W. G. Magnetostrictive ferrites with small change in coupling coefficient from 0° to 20°C, (6) 164*d*.

Brockway, M. C. See Duckworth, W. H.

Brockway Glass Co., Inc. Apparatus for blow molding hollow articles, P (9) 241*e*.

Brode, W. R. Some problems associated with the growth of science, B (5) 148*c*.

Broder, D. L., Kondrashev, A. P., et al. Effect of boron-containing layers on the yield of secondary gamma rays, (10) 274*i*.

Broemer, H., and Meinert, N. Optical crown glasses, P (11) 305*c*.

Bron, W. E., and Nowick, A. S. Effect of fractional X-irradiation of NaCl crystals on F-center density, (4) 113*b*.

Bronaugh, H. J., and Kruesi, P. R. Concentration of rare earths, P (9) 254*j*.

Bronnes, R. L. Metal-to-ceramic seal and method of making it, P (2) 49*i*.

Bronson, R. D., Spain, J. M., and White, J. L. Potassium-depleted muscovite (I) preparation using filtration process for treatment with molten lithium nitrate, B (3) 91*h*.

Brookman, R. S. See Morris, L. D.

Brooks, D. H. See De Hart, H.

Brooks, E. Rotors for mixing, pulverizing, and like machines, P (5) 141*e*.

Brooks, F. A., Jr. Cementing composition, P (6) 154*i*.

Brooks, M. E. Apparatus for lifting a stack of building units, etc., P (3) 71*h*.

Brooks, S. H., Kiplin, R. A., and Ross, I. C. Sampling systems for waste gas analysis from open-hearth and Ajax furnaces, (8) 224*i*.

Brosset, C. Some aspects of the structure of glasses with high silica content, B (10) 300*f*. X-ray investigation of the distribution of heavy atoms in glass, (10) 271*i*.

Brosset, C., and Hagstedt, M. Electron microscope studies on glass surfaces, (1) 6*d*.

Brotzmann, K. See Knueppel, H.

Brough, R. See Davies, L. J.

Brown, B. E., and Bailey, S. W. Chlorite polytypism (I) regular and semirandom one-layer structures, (9) 255*i*.

Brown, C. B., Bailey, G. W., and White, J. L. Removal of reaction products from muscovite treated with molten lithium nitrate, (6) 170*i*.

Brown, C. F., Jr. Glass beads as blasting media, (9) 235*h*.

Brown, C. S. Recent developments in the growth of synthetic quartz, (9) 248*j*. See Hart, P. B.

Brown, D. J., and Stobo, J. J. Symposium on nuclear ceramics: Properties of uranium monocarbide, (11) 307*j*.

Brown, D. L. Lithium ferrites, P (9) 249*d*.

Brown, D. W. See White, A. E. S.

Brown, F., and Prichard, J. H. Rock treatment, P (9) 254*h*.

Brown, G. (editor). X-Ray Identification and Crystal Structure of Clay Minerals, B (7) 202*f*.

Brown, H. J. See Shapona, G.

Brown, H. L., and Armstrong, P. E. Young's modulus measurements above 2000°C, (10) 286*g*.

Brown, J. A. See De Long, H. K.

Brown, J. D., Thatcher, J. W., and Campbell, W. J. Design, construction, and evaluation of an electron probe X-ray spectrograph, (8) 222*j*.

Brown, J. T. See McHugh, J. P.

Brown, L. C. Progress in magnetic resonance spectroscopy, (8) 223*b*.

Brown, M. G. See Polanyi, M. L.

Brown, P. M. See Brown, S. P.

Brown, R. F., and McMahon, G. W. Material constants of ferroelectric ceramics at high pressure, (11) 310*j*.

Brown, R. L. Calculation of closed-circuit grinding, (1) 22*e*.

Brown, R. W. Role of beta alumina fused cast refractories in glass tank superstructures, (2) 40*h*.

Brown, R. W., and Jacobsen, G. W. Glass tank throats (I) throat design; (II) selection of throat refractories, (1) 7*b*; (III) how physical properties change in refractories, (3) 72*h*; (IV) how mechanical properties change refractories, (8) 208*i*.

Brown, S. P., and Brown, P. M. Method and apparatus for making briquets, P (9) 243*c*.

Brown, T. G. Examination by ultrasonics of bodies having a nonplanar surface, P (8) 223*i*.

Brown, W. R. See Kirchner, H. P.; Merz, K. M.

Browne, C. M. Light reflecting films and process for their production, P (8) 221*j*. Ultrathin films, P (2) 43*b*.

Brownell, W. E. Ceramic materials, (9) 258*b*. Reactions between alkaline-earth sulfates and cristobalite, (5) 145*i*. See Earl, W. A.

Browning, A. L. See Calhoun, F. L.

Browning, J. S., and McVay, T. L. Concentration of fine mica, (9) 253*j*.

Brownlow, J. M. Method of forming memory arrays, P (6) 166*i*.

Bruce, B. D. Advantages of lower temperature porcelain enameling on sheet steel, (2) 36*f*.

Bruce, I. B. See Trubey, P. W.

Bruch, C. A. Sintering kinetics for the high density alumina process, (1) 29*g*.

Bruche, E. Polishing of glass, (3) 67*c*.

Brueckner, E. Manufacture of plates by pressing, (10) 278*h*.

Brueckner, R. Thermal expansion behavior of silica glass as a function of thermal history, (6) 156*h*.

Bruere, G. M. Importance of mixing sequence when using set-retarding agents with portland cement, (10) 267*b*. Rearrangement of bubble sizes in air-entrained cement pastes during setting, (3) 64*i*.

Brumley, C. H. Ratio measuring spectrophotometer, P (4) 121*i*.

Brun, E., and Hafner, S. Quadrupole splitting of ^{27}Al in spinel $MgAl_2O_4$ and in corundum Al_2O_3 (I) nuclear resonance of ^{27}Al and cation distribution in spinel, (4) 119*c*; (II) ionic model for explanation of the measured quadrupole splitting, (4) 119*d*.

Brunauer, S. Tobermorite gel—the heart of concrete, (11) 302*c*.

Brunauer, S., and Greenberg, S. A. Hydration of tricalcium silicate and β-dicalcium silicate at room temperature, B (5) 149*b*.

Brunner, G. M., Hauck, W. V., and Adams, A. Method for the purification of potassium carbonate, P (6) 171*c*.

Brunson, R. D. Apparatus for testing heat responsive devices, P (4) 108*c*.

Brunton, G. See Beck, C. W.; Tettenhorst, R.

Brush Crystal Co., Ltd. Ferroelectric ceramic materials, P (4) 105*b*.

Brussaard, J. M., and Hekkert, J. W. Method of longitudinally prepolarizing bodies consisting of at least one layer of piezoelectric material, P (5) 136*e*.

Brustik, J. Standardization of cutting wheels in the glass industry, (5) 129*j*.

Bryan, A. No great changes in the future, (8) 218*c*.

Bryant, W. C. Protective backing for mirrors, P (4) 100*c*.

Bryatov, L. V., and Kuz'mina, I. P. Crystallization of the sulfides of lead and zinc from aqueous solutions of the chlorides, B (9) 263*e*.

Brydon, J. E. See Clark, J. S.; Turner, R. C.

Buchi, G. J. P. See Stewart, I. M.

Buck, I. E., Jr., and Pakutka, W. M. Electroluminescent device, P (5) 135*g*.

Buckley, E. D. See Teasel, R. C.

Buckley, J. D., and Wilson, H. H. Destabilization of zirconia by cyclic heating, (11) 305*i*.

Buckman, S. J., and Pera, J. D. Barium metaborate-silica particles and methods of preparing them, P (2) 55*b*.

Buckman, S. J., Pera, J. D., and Funderburk, G. R. Barium zirconium borate, pigments containing it, and processes for their production, P (8) 225*c*.

Buckman Laboratories, Inc. Barium metaborate-silica particles and methods of preparing them, P (2) 55*b*. Barium zirconium borate, pigments containing it, and processes for their production, P (8) 225*c*.

Budd, S. M. Mechanism of chemical reaction between silicate glass and attacking agents (I) electrophilic and nucleophilic mechanisms of attack, (4) 98*a*.

Budd, S. M., Exelby, V. H., and Kirwan, J. J. Formation of gas bubbles in glass at high temperature, (3) 66*c*.

Budd, S. M., and Frackiewicz, J. Mechanism of chemical reaction between silicate glass and attacking agents (II) chemical equilibria at glass-solution interfaces, (4) 98*b*; (III) equilibrium pH of some Na_2O–CaO–SiO_2 glasses and its relationship with chemical reactivity, (4) 98*c*.

Budnikov, P. P. Mullite-Carborundum and corundum-Carborundum refractories resistant to spalling, B (10) 300*g*. Problems in the slip casting of porcelain, (10) 278*j*. Role of gypsum in hardening of hydraulic cements, B (5) 149*a*. See Al'perovich, I. A.

Budnikov, P. P., Azarov, K. P., and Migonadjiev, A. S. Process of formation of enamel coatings on aluminum, B (11) 322*g*.

Budov, V. M., and Shaposhnikov, I. A. Improving the design of certain parts of a glass tank furnace, (1) 7*i*.

Buehler, G., and Feulner, H. Stable aqueous suspensions based on fused alumina, P (3) 90*a*.

Buehler, K., and Bues, W. Vibration spectra of fluorophosphate melts and crystals, (5) 147*b*.

Buell Engineering Co., Inc. Magnetic cleaning means for electrodes of electrostatic precipitator, P (4) 106*i*.

Buerger, M. J., and Wuensch, B. J. Distribution of atoms in high chalcocite, Cu_2S, (11) 317*a*.

Bues, W. See Buehler, K.

Buessem, W. R. Internal ruptures and recombinations in anisotropic ceramic materials, B (3) 92*a*.

Buessem, W. R., and Butler, S. R. Valence changes of iron and manganese in manganese ferrite, (10) 297*g*.

Buffalo China, Inc. Method for shaping appendages on ceramic articles, P (4) 104*b*.

Buffet, J., and Collinet, A. Use of glass in the hot extrusion of metals, (1) 10*i*.

Buhrer, C. F. Some properties of bismuth perovskites, (9) 257*f*.

Buhrow, J. See Witzmann, H.

Buie, B. F. See Robinson, G. C.

Bulis, Ya. Ya., and Ruzhanskii, S. D. Use of radioactive level indicator on lime shaft kiln, (7) 197*a*.

Bullard, George H., Co., Inc. See George H. Bullard Co., Inc.

Bullard, R. A. Abrasive wheel, P (7) 177*f*.

Bumm, H. Importance of oxides and carbides for nuclear reactor fuel elements, (10) 274*b*.

Bundy, F. P. Plural reaction chamber press for high pressures, P (5) 138*e*.

Bundy, F. P., Bovenkerk, H. P., Strong, H. M., and Wentorf, R. H., Jr. Diamond-graphite equilibrium line from growth and graphitization of diamond, (4) 113*i*.
Bundy, W. S. Preparation of pure titanates, P (3) 78*e*.
Bunge, H. J. See Wodtcke, F.
Bunk, W. Enameled aluminum in building construction, (10) 268*j*.
Burch, C. J. Hinged heat shield for metal teeming ladle bottoms, P (8) 216*i*.
Burger, W., and Luebbe, H. Process for the treatment of asbestos, P (3) 74*d*.
Burgess, D. Structure and propagation of turbulent Bunsen flames, (6) 169*a*.
Burgt, C. M. van der, and Put, E. Ferromagnetic material and method of making it, P (11) 311*c*.
Burian, R. J., Gates, J. E., and Dickerson, R. F. Radiation stability of compacts of aluminum and fuel-bearing glass fibers, (9) 241*f*.
Burian, R. J., Ritzman, R. L., et al. Evaluation of irradiated alumina-coated UO_2 particles dispersed in graphite spheres, (8) 213*j*.
Burk, M. Determination of thermal conductivity of beryllia rod by measuring axial temperature distribution, (11) 305*i*. Thermal conductivity of beryllia ceramics from −200° to 150°C, (5) 132*h*.
Burk, M. C. See Kindred, R. L.
Burk, W. See Fruehauf, K.
Burkart, E. H. See George, M. F., Jr.
Burke, J. E. (editor). Progress in Ceramic Science (Vol. II), B (8) 232*b*.
Burke, K. O., and Schafer, R. G. Flame treating apparatus, P (1) 11*g*.
Burkett, R. H. W. See Dummer, G. W. A.
Burkin, A. R., Meddings, B., and Sawyer, H. D. Treatment of columbite and related minerals, P (3) 85*c*.
Burkio, D. C. Brick quality at the press, (11) 311*i*. See Reynolds, C. B.
Burney, G. A. See Dukes, E. K.
Burnham, C. W., and Jahns, R. H. Method for determining the solubility of water in silicate melts, (5) 144*f*.
Burnham, J. B., Jr. Fuel element for nuclear reactors, P (8) 216*b*.
Burns, G., and Nathan, M. I. Quantum efficiency of ruby, (10) 281*e*.
Burns, R. P. See Grimley, R. T.
Burroughs Corp. Lamp and method of manufacture, P (6) 157*f*.
Burt, G. H. Manufacture of gypsum board, P (1) 3*e*.
Busby, T. S. Effect of fuel oil ash on glass tank refractories, (8) 213*e*. Flux line corrosion, (3) 72*d* Thermal conductivity of tank block materials, (1) 10*a*.
Busby, T. S., Corney, J. I. E., and Eccles, J. Zircon refractories, (7) 189*h*.
Busby, T. S., and Davies, M. W. Control rod materials, P (8) 215*j*.
Busby, T. S., and Eccles, J. Corrosion of corundum crystals by commercial glasses, (10) 274*d*. Reactions between refractory materials, (1) 14*j*. Relation between porosity, firing temperature, and corrosion resistance of slip-cast sillimanite, (1) 15*b*.
Busch, M. See Strasser, O.
Bush, D. R., Howarth, T. E., and Lawrence, R. Composition for and method of applying ceramic color, P (9) 239*d*.
Bush, J. E. Hydraulic [brick] press, P (6) 167*c*.
Bushmanov, B. N. Growth of large metal monocrystals of specified orientation and the mass-production of seed crystals, B (9) 263*d*.
Bushong, R. M. Graphite as an aerospace material, (10) 288*g*. See Ford, C. E.
Busker, J. W. See Neimeyer, W. F. F.
Buss, W. See Jebsen-Marwedel, H.
Bussy, P., and Zaceski, C. P. Comparison of different fuels destined for the Rapsodie fast reactor, B (8) 232*i*.
Buthala, D. A. See Matthews, J.
Butler, J. W. Method of making a neutron-absorbing calcium boride brick, P (9) 244*e*.
Butler, K. H. See Homer, H. H.
Butler, S. R. See Buessem, W. R.
Butt, Yu. M. See Yung, V. N.
Butt, Yu. M., and Timashev, V. V. Processes of clinker formation and limiting saturation of portland cement clinkers by lime, (7) 181*h*.
Butterman, W. C. See Beard, W. C.
Butters, R. B. Conveyor speed control by measuring material level, P (3) 80*b*.
Butterworth, B. See May, J. O.; Watson, A.
Butterworth, B., and Skeen, J. W. Experiments on the rain penetration of brickwork, (3) 71*c*.
Buttler, F. G. See Percival, A.
Buzuzov, V. P. See Chentsova, L. G.; Ikornikova, N. Yu.
Buyers, A. G. Ceramic-metal bonding stable in excess of 2248°K, (7) 183*c*.
Buzard, F. T. Augers, (2) 50*h*.
Bykhinskii, I. M., and Bodrova, N. I. Spectral study of CdS- and CdS,CdSe-colored glasses, (5) 129*f*.
Byteva, I. M. Effects of pH and crystal-holder speed on the growth of crystals of ammonium dihydrogen phosphate, B (9) 262*j*.
Byurganovskaya, G. V., and Orlov, N. F. Formation of color centers in sodium silicate and quartz glasses under the action of gamma radiation, (5) 129*e*.

Cable, M. Study of refining (II) mechanisms of refining—correction, (8) 209*j*; (III) function of arsenious oxide during melting and refining, (1) 9*c*.
Cabot Corp. Process and apparatus for the production of finely divided pigments, P (4) 111*g*. Process for making titanium dioxide [pigment], P (6) 171*b*. Production of silicon tetrachloride, P (10) 290*c*.
Cabrera, A. M., and West, T. S. New spectrophotometric reaction of beryllium, (9) 251*c*.
Caceres Hernandez, J. M. Principal methods used in dust concentration and the danger of dust in working places, (5) 148*d*.
Cach, F. J. Comments on "A new method for the mechanical (pressing) shaping of plates," (3) 79*e*. Development, future, and requirements in the porcelain industry, (4) 103*j*.
Cahill, J. A. See Kirshenbaum, A. D.
Caillat, R. See Pruvot, E.
Cain, F. M., Jr., and Eck, J. E. Dispersion element consisting of chromium coated UO_2 particles uniformly distributed in a Zircaloy matrix, P (8) 215*j*.
Caldecott, R. See Lee, J. D.
Caldwell, D. W. Glacial lake and glacial marine clays of the Farmington area, Maine—origin and possible use as lightweight aggregate, (4) 109*b*.
Caldwell, E. P. Microscope as controlling instrument in mineral dressing, (8) 225*e*.
Caley, E. R. Analyses of Ancient Glasses 1790–1957—A Comprehensive and Critical Survey, B (3) 90*h*.
Calhoun, F. L., and Browning, A. L. Inspection device, P (7) 186*c*.
Calhoun, W. A. See Powell, H. E.
Calhoun, W. A., and Hill, T. E., Jr. Metallurgical testing of Hawaiian ferruginous bauxites, (1) 25*i*.
California Institute Research Foundation. Transducer plate [with ribbed edge] for high acoustical-mechanical energy transfer to liquids, P (5) 137*h*.
California Portland Cement Co. Kiln automatic control method and apparatus, P (9) 237*h*. X-ray fluoroscopic analysis, P (5) 140*b*.
Calis, M. Ceramic dielectrics for high-tension capacitors, P (6) 165*i*. See Clement, R.
Calis, M., and Charpin, J. Formation of ultrafine-grained materials for ceramics or metallurgy by use of thixotropic layers, P (3) 83*g*.
Callcott, T. G., and Innes, J. A. Penetration plastometry: (A) Design and operation of plastometer; (B) Rank and coke quality correlations, (7) 196*i*.
Calleja, J. Hydraulic materials—physical chemistry and technology, (8) 205*j*.
Calstone Co. Equipment for manufacturing structural [concrete] blocks, P (2) 51*b*.
Calvert, W. L. See Miller, W. A.
Calvi, M. C., Tornati, M., and Scandellari, M. L. Historical and technological research on the ancient glass of Aquileia, B (11) 321*f*.
Camerman, C. See Solomon, L.
Cameron, A. E., and Wichers, E. Report of the International Commission on Atomic Weights, 1961, (5) 145*d*.
Cameron, N. M. Effect of annealing on the room temperature strength of glass fibers, (9) 239*j*.
Cameron and Jones, Inc. Antisegregation charge [multiple] feeder for shaft kilns, etc., P (4) 96*e*. Off-gas collector for shaft kilns, P (3) 82*a*.
Cammerer, W. F. Thermal conductivity measurements on boiler linings, (3) 73*b*.
Camona, G. See Bassi, A.
Camors, C. Photogeology, (8) 225*h*. Utilization of electrofiltration phenomena in the prospecting of ceramic raw materials, (3) 83*j*.
Campaigne, R. N., and Estabrooks, D. A. Machine coats films automatically, (9) 247*f*.
Campbell, I. E. See Blocher, J. M., Jr.
Campbell, J. Electrode, P (3) 73*j*.
Campbell, R. Solve clay screening problems, (8) 225*j*.
Campbell, R. A. Ceramic fiber products and method and apparatus for manufacture, P (6) 161*j*.
Campbell, W. J. Platinum expansion values for thermal calibration of high-temperature X-ray diffraction cameras and diffractometers, (3) 81*a*. See Brown, J. D.
Canadian Refractories, Ltd. Consolidating refractory materials, P (6) 162*a*. Low-iron, spalling-resistant periclase brick, P (6) 162*f*. Refractory masses, P (6) 162*h*. Thermoplastic refractories, P (6) 163*a*.
Canegallo, G. Method of making covered electrical resistors, P (2) 49*e*.
Cannon, M. C., Grimes, W. R., Ward, W. T., and Watson, G. M. Adsorption of xenon and argon on graphite, (4) 100*i*.
Cannon, P. Formation of diamond (I) demonstration of atomic processes involving carbon, (5) 143*f*. Synthetic zeolite for selective absorption of Freons, P (6) 171*e*.
Canrad Precision Industries. Device for rupturing glass [pipe] seals, P (1) 11*d*, P (8) 210*c*.
Cantrell, J. Abrasive articles and their manufacture, P (7) 177*g*.
Cap, M. Ultraviolet transmitting glass, (11) 304*d*.
Capellaro, D. F. See Kapany, N. S.
Capitol Products Corp. Method and apparatus for blending discrete materials, P (4) 106*i*.
Caporali, R. V., and Mould, R. E. Effect of heat treatment on the strength of pristine bulk glass, B (11) 320*h*.
Capp, L. J. See Beeson, E. J. G.
Capriz, G. Theoretical analysis of extrusion processes, (11) 312*b*.
Carbon Wool Corp. Method for carbonizing fibers, P (1) 26*b*.
Carbonic Development Corp. Combustion burner, P (10) 288*b*.
Carborundum Co. Abrasive articles and their manufacture, P (7) 177*g*. Antiweld additives for coated abrasive bonds, P (2) 33*h*. Ceramic fiber products and method and apparatus for manufacture, P (6) 161*j*. Heat resistant fibrous products containing ceramic fibers and method of making them, P (9) 244*i*. Method of making magnesium oxide, P (7) 189*i*. Method for making zirconium boride, P (4) 102*f*. Methods for making boron nitride materials, P (2) 46*c*. Molded bodies resistant to abrasion, P (6) 162*i*. Packaging of sheet abrasive disks, P (1) 1*j*. Process for adjusting the electrical characteristics of silicon carbide crystals, P (5) 137*a*. Sectional coated abrasive belt and process of making it, P (1) 2*b*. Silicon carbide resistance body and method of making it, P (10) 278*a*. Zirconium boride-silicide bodies and methods of making them, P (8) 217*b*.
Carb-Rite Co. Refractory composition and process of making it, P (8) 217*a*.
Cardon, F. Relation between polarization phenomenon and space-charge-limited currents in rutile single crystals (TiO_2), (5) 145*c*.
Carle, D. W. See Donner, W.
Carlson, C. E. See Del Grosso, E. J.
Carlson, C. W., and Carlson, C. W., Jr. Method for forming cased glassware, P (7) 186*c*.
Carlson, C. W., Jr. See Carlson, C. W.
Carlson, E. L. See Christensen, V. J.
Carlson, R. W. See Schluderberg, D. C.
Carlson, W. A., Sanford, E. A., and Crandall, W. B. Study of crystallization of glass coatings on metal by electron microscopy, (8) 207*j*.
Carlson, W. G. See Ichikawa, Y.; Tien, T. Y.
Carlstroem, B. I., and Rumberg, K. A. Method for manufacturing resin-bonded products made from inorganic fibers, P (1) 11*e*.
Carnahan, R. D. See Dahlberg, P.
Carnes, K. C. See Farmer, R. D.
Carniglia, S. C. Some thermal and mechanical properties of dense beryllium oxide, B (3) 92*c*.
Caroselli, R. F. Apparatus for treating fibrous glass, P (10) 271*b*.
Caroselli, R. F., and Gagnon, R. K. Method of producing dyed glass fiber yarn, P (4) 100*f*.
Caroselli, R. F., and Marzocchi, A. Sized glass fibers and composition, P (10) 273*c*.
Carpco Research & Engineering, Inc. Electrostatic separator, P (2) 51*a*.
Carpenter, H. W., and Johnson, P. D. Cadmium phosphate glass, P (7) 185*i*.
Carpenter, J. E. Structural model testing—compensation for time effect in plastics, (4) 107*i*.
Carpenter, J. H. Electrostatic separator, P (2) 51*a*.
Carpenter, V. W., and Jackson, J. M. High-melting coatings on steel strip, P (6) 155*f*. Magnesia coatings on silicon steel, P (6) 155*f*.
Carr, K. Experience with LDAC converter linings at Ebbw Vale, (6) 161*h*.
Carries, W. J., and Dean, J. A. Use of a light guide in flame spectrophotometry, (1) 23*j*.
Carrison, L. C. See Sclar, C. B.
Carroll, D. F. System PuO_2–ZrO_2, (6) 175*e*. Thermal expansion of plutonium nitride, (10) 297*c*.
Carroll, J. W. Cleaning prior to porcelain enameling, (2) 36*d*.
Carroll, P. E. Process for adjusting the electrical characteristics of silicon carbide crystals, P (5) 137*a*.
Carroll-Porczynski, C. Z. Advanced Materials—Refractory Fibers, Fibrous Metals, and Composites, B (5) 148*e*.
Carson, F. J. Glass bending mold, P (9) 242*a*.
Carson, F. J., and Leflet, H. A., Jr. Apparatus for bending glass sheets, P (8) 210*d*. Method and apparatus for feeding flat [triangular-shaped] sheets onto a moving conveyor, P (11) 304*j*.
Carson, F. J., and Stickel, A. Method and apparatus [sag mold] for bending glass sheets, P (4) 100*d*.
Carson, F. J., and Thayer, A. G. Apparatus for handling sheet material, P (4) 99*e*.
Carson, F. J., and White, G. Glass bending apparatus, P (9) 242*a*.
Carson, J. A., Mathieu, A. L., and Scheelar, M. D. Use of flooding solutions in the determination of metallic exchangeable cations, utilizing a Beckman DU flame spectrophotometer, (5) 139*f*.
Carson, R. W. How to control rust, (9) 238*b*, (11) 302*i*.
Carta, S. J. See Del Grosso, E. J.
Cartan, F. O., and Curtis, G. J. Apparatus for the determination of particle density of porous solids, (7) 195*d*.
Carter, F. H. N. Furnace lining, P (1) 16*b*.
Carter, G. J., Kelly, H. J., and Parsons, E. W. Industrial silica deposits of the Pacific Northwest, (6) 170*c*.
Carter, R. E. High density ferrites, P (5) 136*d*. Kinetic model for solid-state reactions, (2) 57*c*.
Cartwright, J. See Bergman, I.
Cartz, L. Moellenstedt, G., and Septier, A. Emission electron microscope studies of ceramic material, B (10) 300*f*.
Carver, R. L. Neutrons measure moisture in solids, (9) 251*a*.
Cary, H. H. See White, J. U.
Casswell, C. See Bergman, I.
Castillo Villaamil, J. R. Modern methods of forming refractory brick, (6) 160*a*.

Castro, M. H. B. de. See Hernaiz Bermudez de Castro, M.
Castro, P. L. See Hollander, L. E., Jr.
Cataphote Corp. Glass composition for beads, P (4) 99*g*. Method and apparatus for making glass beads, P (5) 131*d*.
Cates, J. C., Jr. See Myers, J. C.
Catron, W. M., and Kenyon, T. F. Method of making lenses, P (3) 70*g*.
Caughey, R. See Bassett, W.
Cavitron Corp. Acoustically vibrated material cutting and removing devices, P (5) 138*f*.
Cavitron Ultrasonics, Inc. Ultrasonic lapping machines, P (10) 285*g*.
Cazalas, A. L. Apparatus and method for the observation of flames, P (5) 139*c*.
Ceccaldi, J. C. Abrasives with synthetic resins as binders, P (3) 63*g*.
Cecil, T. A. See Allegrini, A. P.
Celotex Corp. Manufacture of gypsum board, P (1) 3*e*.
Cementation Co., Ltd. Mechanical rendering of surfaces and pointing of brickwork, P (6) 159*c*.
Centre National de la Recherche Scientifique. Calcium zirconate refractories, P (3) 73*i*. Treatment of zircon after fusion by concentrated solar rays, P (3) 75*c*.
Ceramic Combustion and Engineering Co. Pallet, P (6) 167*f*.
Cernoch, S., Tomco, S., and Spakovsky, E. New developments in the roasting of perlite, (2) 54*d*.
Cernohlavek, D. Trends in the development of electrotechnical and technical ceramics, (10) 298*f*.
Cersolsun Research Corp. Lamp base assembly, P (2) 42*a*.
Certa, A. J., and McMahon, J. F., Jr. Stem fabricating process, P (4) 100*d*.
Chadaeva, V. V. See Beznosikov, B. V.
Chain Belt Co. Device [vibratory screen] for separating fine from coarse materials, P (8) 221*k*. Method and apparatus for moving pulverulent materials [vibrating trough], P (2) 51*d*. Rotary conveyor [for granular material], P (3) 80*a*. Vibratory bin feeder, P (7) 195*c*.
Chaklader, A. C. D. Geometric model for quartz-cristobalite transformation, (6) 173*f*. X-ray study of quartz-cristobalite transformation, (4) 121*c*. See Armstrong, W. M.; Misra, S. K.
Chakrabarty, M. R. Crystal chemical studies of urania ceramics (I) dielectric and solid state studies of $BaTiO_3$–UO_3 ceramics, (10) 279*j*; (II) effect of varying firing temperature on the dielectric properties of $BaTiO_3$–UO_2 ceramics, (10) 280*a*. CURF uranium ceramics, (9) 239*i*.
Chakraborty, K. L. Mineralogical character of some Indian chromites, (8) 228*j*.
Chakravorty, S. K. See Roy, S. B.
Chambers, C. G. Tapping rod with lime coating, P (2) 46*h*.
Chambon, R. Evolution of the processes used for the hand-fashioning of window glass from the tenth century to the present, B (11) 321*b*.
Champion Spark Plug Co. Apparatus for measuring elevated temperatures, P (10) 286*j*.
Champlin, J. B. F. Rapid determination of permeability in porous rock, (6) 168*k*.
Chan, A. D. H., and Lambert, R. E. Tempered glass sheet or plate, P (7) 187*a*.
Chan, F. L. X-ray [powder diffraction] camera attachment, P (6) 176*d*.
Chandler, B. A. See Sjodahl, L. H.
Chang, H.-C. Producing diffused junctions in silicon carbide, P (7) 194*g*. Surface treatment [by electrolytic etching] of silicon carbide, P (6) 176*c*. See Le May, C. Z.
Chang, R. Elastic and anelastic properties of refractory materials for high-temperature applications, B (3) 92*b*.
Chang, W. S. C. Lasers and masers, (8) 228*b*.
Channell, J. K., and Hanna, R. J. Experience with light scattering particle counters, (8) 223*a*.
Chao, E. C. T. Natural coesite—an unexpected geological discovery, (7) 197*i*.
Chao, G. J., Priest, D. K., and Myers, J. R. Recent progress in protective coatings for molybdenum, B (7) 202*e*.
Chapelle, J. Use of slag sand and fly ash in concretes, (8) 206*a*.
Chapman, A. F., and Sutherland, R. A. Film-covered shaped objects, P (2) 42*e*.
Chapman, A. T. Phase studies in BeO–metal oxide systems using a porous-collector technique, (6) 174*b*.
Chapman, A. T., Jr., Foster, W. R., and Shevlin, T. S. Investigation of the Si–O–C system, (5) 144*j*.
Chapman, C. V. G. See Solt, G. S.
Chapman, L. See Moore, N. C.
Chapman, R. A. Lubrication of mold box liners, (4) 101*j*.
Chapman, R. L. Process stream analyzers, (1) 23*j*.
Chappell, C. H. Flexible high temperature thermoelectric device, P (3) 81*d*.
Chappell, T. T. See Wranau, G. von.
Chapus, E. E. See Condolios, E.
Chardoul, N. See Lundquist, R. V.
Charland, T. L., and Moss, R. H. Process for the preparation of thermoelectric elements, P (8) 220*i*.
Charles, R. J. Some structural and electrical properties of lithium silicate glasses, (7) 185*j*.
Charleston, R. J. Eighteenth century ingots of glass, B (11) 321*c*. Some tools of the glassmaker in medieval and Renaissance times, with special reference to the glassmaker's chair, (3) 64*b*.
Charman, H. B., and Dell, R. M. Fast neutron damage at the surface of metal oxides, (8) 227*j*.
Charpentier, M. See Levecque, M.
Charpentier, M., and Mabru, M. Apparatus for manufacturing fibers, P (6) 157*e*.
Charpin, J. See Calif, M.
Charters, M. See Sawaguchi, E.
Charvat, F. R. See Kingery, W. D.
Charvat, F. R., and Fentzke, A. D. Glass fiber composition, P (7) 186*c*.
Chase, A. B. See Lefever, R. A.
Chassevent, L. Determination of the Blaine specific surface area of gypsum, (5) 138*j*.
Chatterji, C. K. See Nag, B. R.
Chatterji, S., and Jeffery, J. W. Studies of early stages of paste hydration of cement compounds (I), (1) 3*e*; (II), (6) 154*c*. Studies of early stages of paste hydration of different types of portland cements, (8) 206*b*.
Chaumet, C. Development of extraction methods and related problems, (9) 253*k*.
Chave, K. E., Deffeyes, K. S., Weyl, P. K., Garrels, R. M., and Thompson, M. E. Observations on the solubility of skeletal carbonates in aqueous solutions, (10) 295*g*.
Cheban, A. G. See Perlin, Yu. E.
Chebotareva, T. E. See Vlasov, A. G.
Chegwidden, R. A. Microwave ferrite devices, P (2) 50*d*.
Chemetron Corp. Preparation of white iron phosphate, P (4) 111*e*.
Chemical Construction Corp. Sealing unit for rotary kiln, P (8) 225*a*.
Chemische Fabrik Kalk G.m.b.H. Material crushing apparatus, P (3) 84*a*.
Chen, D. Modulation of ruby laser output by absorption, (7) 192*c*.
Chen, F. P. H. Kinetic studies of crystallization of synthetic taica glass, (11) 317*j*.
Cheney, J. E. Diamond tool, P (11) 301*f*.
Chentsova, L. G., and Butuzov, V. P. Smoky color and thermoluminescence of X-rayed synthetic quartz containing traces of Li, Na, and Ge, B (9) 263*g*.
Cherdron, E. See Rueter, H.
Cherepanov, A. M. Monocrystals of $BaTiO_3$–$PbTiO_3$ and $BaTiO_3$–$BaSnO_3$ solid solutions, B (9) 263*f*.
Chernov, A. A. Effects of trace components on the growth rate of a crystal, B (9) 262*b*. Excess impurity trapping during crystal growth, B (9) 262*b*.
Chernyshev, K. S. See Belyaev, L. M.
Cheroff, G., and Keller, S. P. Optical transmission and photoconductive and photovoltaic effects in activated and unactivated single crystals of ZnS, (4) 117*f*.
Chessin, H., and Turkdogan, E. T. Crystallographic investigation of calcium diferrite, (2) 56*c*.
Chesters, J. H. Refractories for oxygen steelmaking: Introduction, (6) 160*g*. Research on research, (1) 15*e*. Steelplant Refractories—Testing, Research and Development (with Oxygen Addendum), B (10) 299*j*.
Chetty, B. V. See Narasimhan, M. D.
Chew, C., Sr. Controlling operation of a glass furnace, P (1) 11*b*.
Chew, R. T., III. How would you like to make brick like this? (11) 305*d*.
Chidley, B. E. See Grover, J. R.
Chikalla, T. D. Melting behavior in the system UO_2–PuO_2, (9) 243*g*. Studies on the oxides of plutonium, B (8) 232*d*.
Chikazumi, S. See Ishikawa, Y.
Childers, H. M. See Withers, J. C.
Childs, B. G. Release of stored energy from neutron-irradiated uranium oxides, (1) 29*c*.
Childs, B. G., and Ogilvie, A. Symposium on nuclear ceramics: Effects of irradiation on the electrical resistivity of cast uranium carbide, (11) 308*d*.
Chinner, G. A., and Schairer, J. F. Join $CaAl_2Si_2O_{13}$–$Mg_2Al_3Si_5O_{12}$ and its bearing on the system CaO–MgO–Al_2O_3–SiO_2 at atmospheric pressure, (2) 57*a*.
Chiola, V., and Vanderpool, C. D. Electrical insulating coating and method of producing it, P (8) 220*g*.
Chisholm, J. J. Interferometer using a diffraction grating, P (9) 252*f*.
Chisholm, R. S. See Thornhill, F. S.
Chismar, A. B., and Kmetz, E. W. Stencil screen coating comprising polyvinyl alcohol, polyvinyl acetate, and a light sensitizing agent, P (11) 312*e*.
Chistoserdov, V. G. Increasing the output of abrasive wheels used for cutting glassware, (7) 177*f*. See Borgman, V. A.
Chodos, A. A., and Engel, C. G. Fluorescent X-ray spectrographic analyses of amphibolite rocks, (4) 114*d*.
Choe, J. O. See Brindley, G. W.
Chojnacka, H. See Kamienska, Z.
Cholet, P. See Johannes, R.; Ramanathan, K.
Chopra, K. L. Current-controlled negative resistance in thin niobium oxide films, (10) 280*b*.
Choshi, I. See Kato, E.
Chourova, D. Surface covering glaze on Stealit, (11) 309*d*.
Chrest, R. W., Rummery, F. O., Richards, J. D., and Roseman, R. Inorganic blue to green pigments and processes for making them, P (6) 167*c*.
Christensen, A. N., and Rasmussen, S. E. Hydrothermal preparation of compounds of the type ABO_3 and AB_2O_4, (10) 294*a*.
Christensen, F. L. Abrasive [diamond] cutting devices, P (11) 301*g*. Abrasive cutting devices, P (1) 1*g*.
Christensen, J. A. See Bates, J. L.
Christensen, V. J., Egleson, G. C., and Carlson, E. L. Preparation of anhydrous magnesium chloride [by ammonia reaction], P (9) 254*d*.
Christensen Diamond Products Co. Abrasive cutting devices, P (1) 1*g*. Abrasive [diamond] cutting devices, P (11) 301*g*.
Christian, S. D., Affsprung, H. E., and Lin, C. Vapor density apparatus, (9) 252*a*.
Christie, G., and Williams, J. Effect of small additions of yttria on uranium oxides at 940°C, (1) 27*d*.
Chromium Mining & Smelting Corp., Ltd. Exothermic high refractory mixture, P (7) 189*j*.
Chromizing Corp. Protective coating of refractory metals, P (9) 239*c*.
Chrostowski, J. E. See McNeill, W.
Chrysler Corp. Glass bending mold [with movable sections], P (10) 271*j*.
Chu, G. P. K., and Helwig, W. C. Method of making enameled ductile iron, P (2) 38*a*.
Chubb, P. A. Treatment of lithium ores, P (5) 141*g*.
Chujo, K., and Hida, I. Effects of various conditions on the drying shrinkage of cement, (8) 204*i*.
Chung, D.-H. See Crandall, W. B.
Chung, D.-H., Swica, J. J., and Crandell, W. B. Relation of single-crystal elastic constants to polycrystalline isotropic elastic moduli of MgO, (10) 296*j*.
Churbakov, V. F. See Menkovskii, M. A.
Church, H. F. Dielectric properties of anodic aluminum oxide films, (9) 246*i*. Long-term stability of fixed resistors, (9) 247*c*.
Church, J. M., and Greenberg, W. H. High strength ceramic compositions and methods for preparing them, P (10) 272*d*.
Ciapetta, F. G. See Wilson, C. P., Jr.
Ciceri, C. See Murphy, N.
Cierva Viudes, P. de la. Effect of kiln atmosphere in ceramic firing, B (2) 61*b*.
Cierva (Viudes), P. de la, and Arroyo, L. Study of optical glass surfaces by leaching with nitric acid (I) polishing lines, (8) 209*i*.
Cimorelli, J. T. Nuvistor family—commercial and developmental status, (2) 48*j*.
Cioaca, E., Radu, A., Demetrescu, A., and Nicolescu, L. Spectrophotometric method for the analysis of ores, (3) 81*e*.
Clair, J. Method and composition for assembling together refractory bodies, P (9) 244*d*.
Clanton, A. R. See Clanton, R. W.
Clanton, H. L. See Clanton, R. W.
Clanton, R. W., Clanton, A. R., and Clanton, H. L. Apparatus for making shell brick, P (1) 13*c*.
Clark, A. E., and Strakna, R. E. Low-temperature excess specific heat of SiO_2 glass, (3) 67*e*.
Clark, C. B., and McDowell, J. S. Study of silica brick from the roof of copper refining furnaces, (8) 214*j*.
Clark, C. D., Kemmey, P. J., and Mitchell, E. W. J. Optical and electrical effects of radiation damage in diamond, (8) 229*c*.
Clark, C. D., Maycraft, G. W., and Mitchell, E. W. J. Polarization of luminescence, B (9) 260*h*.
Clark, C. D., and Mitchell, E. W. J. Electronic structure of defects—optical methods, B (8) 234*c*.
Clark, D. B. Rare earth pressure transducers, (6) 165*f*.
Clark, G. W. See Kopp, O. C.
Clark, J. S., Brydon, J. E., and Hortie, H. J. Clay minerals in some British Columbia subsoils, (5) 140*i*.
Clark, J. S., and Green, A. J. Pipetting assembly for the mechanical analysis of soils, (5) 139*d*.
Clark, R. B. Thermocouple, P (4) 108*e*.
Clarke, F. J. P., Bowen, D. H., and Wilks, R. S. Symposium on nuclear ceramics: Irradiation damage in some nonfissile ceramics, (11) 306*i*.
Clarke, F. J. P., Miles, G. D., and Sambell, R. A. J. Basic mechanisms leading to fracture by thermal shock, B (4) 124*b*.
Clarke, F. J. P., Sambell, R. A. J., and Tattersall, H. G. Cracking at grain boundaries due to dislocation pileup, (5) 142*h*.
Clarke, R. G., Groth, R. H., and Duzak, E. J. Coprecipitated adsorbent gels, (1) 27*b*.
Claus, D. See Blasum, H. A.
Claus, K. M. See Jordan, R. E., Jr.
Clausen, C. F. Underground nuclear explosions for mining, (1) 25*e*.
Clausen, H. H. New look for storage and loading, (4) 106*g*.
Clauson, W. E., and Zsoka, L. T. Cushion material [of fiber glass] and method of making it, P (2) 42*c*.
Claussen, G. E. See Jensen, W. L.
Clay, D. B. Open coil annealing, (2) 37*d*.
Claypoole, S. A. Method of separating devitrified glass seals, P (2) 42*f*.
Clayton, R. N. Oxygen isotope fractionation between calcium carbonate and water, (2) 58*e*.
Clemens, K. H. Measurement of the characteristics of enamel slips with the rotating cylinder viscometer, (8) 207*f*.
Clement, R., and Calis, M. Ceramic materials with high dielectric constants, P (6) 165*j*.
Clements, J. F. Specific heat of some refractory materials, (3) 73*d*.
Clemmons, B. H. See Feld, I. L.
Clendenning, T. G., and Durie, N. D. Properties and use of fly ash from a steam plant operating under variable load, (10) 267*h*.
Clerck, G. de. See Plumat, E.
Clevenger, T. R., Jr. Effect of Fe^{4+} in the system $SrFeO_3$–$SrTiO_3$, (7) 191*d*.

Clevite Corp. Apparatus for fabricating semiconductor devices, P (4) 104*j*. Dicing semiconductor crystals, P (7) 193*j*. Ferrite transducers, P (3) 77*a*. Hydrothermal synthesis of quartz, P (1) 25*i*. Method of growing silicon carbide crystals, P (1) 16*a*. Method of producing cellular ceramic electromechanical transducers, transducer materials, and elements, P (1) 21*b*.

Cliff, G. J., Parshall, B. B., Braun, W. H., Feldkamp, J. G., and Hager, R. E. Article stacking and strapping machine, P (10) 273*g*.

Clifton, D. F. See Hsi, H.-R.

Cline, D., and Kropschot, R. H. Thermal properties of powder insulators in the range 300° to 4°K, B (3) 93*b*.

Cline, R. A., and Tonjes, B. D. Sample splitter, P (5) 140*b*.

Clipson, S. Apparatus for exfoliating vermiculite, P (4) 110*c*.

Clorox Co. Hypochlorite bleach bottle, P (5) 131*b*.

Close, P. T., Watson, M. T., and Drummond, C. H. Analytical methods applicable to zirconium oxide and boron-silicon refractories, (8) 212*d*.

Cloud, W. H. Crystal structure and ferrimagnetism in $NiMnO_3$ and $CoMnO_3$, (4) 113*d*.

Clough, P. J. See Baer, C. A.

Cnudde, M. F. Effect and advantages of convection heated lehrs in glass annealing, (1) 6*c*.

Coast Metals, Inc. Surfacing torch with external powder feed, P (10) 269*h*.

Coble, R. L. See Kingery, W. D.; Paladino, A. E.

Coble, R. L., and Ellis, J. S. Hot-pressing alumina—mechanisms of material transport, (10) 293*d*.

Coble, R. L., and Guerard, Y. H. Creep of polycrystalline aluminum oxide, (9) 255*c*.

Coceva, C. See Bertozzi, G.

Cochardt, A. Modified strontium ferrite, a new permanent magnet material, (10) 281*d*.

Cochran, J. K. Twisted [glass fiber] yarn package, P (3) 70*h*.

Coen, J. K. See Morgan, W. L.

Coes, L., Jr. Electrically conductive organic bonded grinding wheel, P (3) 63*g*. Magnetic abrasive wheels, method of making them, and machine tools for using them, P (9) 236*d*.

Coffeen, W. W. (editor). Enamel Bibliography and Abstracts—1959 Supplement, B (1) 32*a*.

Cohen, A. J. Fossil glasses produced by impact of meteorites and asteroids with the planet Earth, B (11) 321*h*. Terrestrial origin of Libyan Desert silica glass, (1) 9*i*.

Cohen, A. J., and Smith, H. L. Variable transmission silicate glasses sensitive to sunlight, (2) 41*h*.

Cohen, J. Method of bonding materials, P (9) 249*h*.

Cohen, L. L. Dental device and method of making dental crowns, P (2) 47*d*.

Cohen, M. H. See Phillips, J. C.

Cohn, R. E. See Rosen, A. H.

Coiley, J. E. See Simms, D. L.

Colchagoff, R. D., and Trudeau, U. P. Glass forming machine, P (4) 99*i*.

Cole, H., and Procter, J. P. Processes of manufacturing glass, P (7) 187*a*.

Cole, L. G. See Bentley, K. E.

Cole, W. F. Moisture expansion of a ceramic body and its internal surface area, (10) 278*i*.

Cole, W. F., and Segnit, E. R. High-temperature phases developed in some kaolinite-mica-quartz clays, (11) 317*h*.

Coleman, J. R. See Sullivan, W. F.

Coleman, N. T. Decomposition of clays and the fate of aluminum, (5) 142*j*.

Coless, T. L. See Sharav, W. B.

Collet, A., Voisin, G. A., and Toullet, F. Production of antibodies by quartz and beryllium oxide, (2) 60*d*.

Collier, T. J. See Biefeld, L. P.

Collinet, A. See Buffet, J.

Collins, H. H. See Fuller, A. G.

Collins, R. J., and Thomas, D. G. Photoconduction and surface effects with zinc oxide crystals, (3) 88*i*.

Colman, R. Light beam controls potentiometers, (10) 280*j*.

Colnot, P., and Gallet, G. Glass and Ceramics in Vacuum Techniques, B (2) 61*b*.

Colombo, R. See Baily, W. E.

Colombo, R. L. See Amato, I.

Colombo, R. L., and Frigerio, G. Occurrence of uranium metal particles in fused UO_2, (1) 28*i*.

Colquhoun, W. P. Symposium on control of the quality of glassware: Reliability of the human element in a quality control system, (9) 241*a*.

Columbia Broadcasting System, Inc. Ceramic reproducer [transducer], P (2) 48*d*. Process for photographically forming color screens, P (6) 166*e*.

Columbia-National Corp. See Pittsburgh Plate Glass Co.

Columbian Carbon Co. Magnetic material, P (9) 249*e*.

Columbus McKinnon Corp. Loose material feeder, P (4) 106*h*.

Colwell, R. E. See Van Wazer, J. R.

Commanday, M. R., and Plambeck, P. J. Protective coating of refractory metals, P (9) 239*c*.

Commissariat a l'Energie Atomique. Apparatus for measuring the thickness of a deposit, P (2) 53*b*. Formation of ultrafine-grained materials for ceramics or metallurgy by use of thixotropic layers, P (3) 83*g*. Fuel arrangements for use in nuclear reactors having vertical channels, P (8) 216*b*. Methods and apparatus for the determination of thermal stresses, P (5) 139*h*. Methods and devices for performing spectrum analysis, in particular in the far ultraviolet region, P (1) 31*d*. Methods of obtaining sintered beryllium oxide, P (2) 46*e*. Nuclear reactor duct structure, P (9) 245*b*. Refractory materials from pure alumina, P (3) 74*i*. Systems for assembling together two pieces having anisotropic expansions, P (4) 121*i*. System for supporting nuclear fuel in atomic reactors, P (11) 308*j*.

Commonwealth Engineering Co. of Ohio. Metallizing siliceous inorganic fibers, P (6) 155*f*. Method and apparatus for generating electrical power from solar energy, P (4) 108*h*.

Compagnie pour la Fabrication des Compteurs et Materiel d'Usines a Gaz. Apparatus and method for the observation of flames, P (5) 139*c*.

Compagnie du Filage des Metaux et des Joints Curty. Extrusion lubrication, P (2) 42*d*.

Compagnie Francaise Thomson-Houston. Metallization of ceramics, P (2) 49*i*.

Compagnie Generale d'Electro-Ceramique. Suspension insulators provided with a core and an envelope, P (5) 137*c*.

Compagnie Generale de Telegraphie sans Fil. Ceramic dielectrics for high-tension capacitors, P (6) 165*i*. Ceramic materials with high dielectric constants, P (6) 165*j*. Ferrites for radio antennas, P (3) 77*c*.

Compagnie de Saint-Gobain. Apparatus for automatically loading and changing bobbins, P (5) 130*i*. Apparatus for drawing uniform fibers of thermoplastic materials, P (2) 41*a*. Apparatus for manufacturing fibers, P (6) 157*e*. Apparatus for the optical determination of stresses, P (7) 196*b*. Apparatus for producing fibers from thermoplastic material, P (8) 210*g*. Articles made of a transparent material such as glass sheets, bricks, or blocks and having variable transparency or coloration, P (8) 210*i*. Furnace adapted for use in dilatometry, P (8) 224*h*. Lubricants for the hot-working of titanium, P (3) 65*f*. Manufacture of fibers, particularly glass fibers, P (6) 157*h*, P (8) 211*b*. Method and apparatus for bending glass, P (6) 157*j*. Method and apparatus for the measurement of a flux of neutrons, P (3) 69*i*. Method and furnace for making glass, P (8) 211*e*. Objects with a metallic luster, P (3) 70*b*. Plastic coating of glass, objects, P (10) 272*i*. Process and apparatus for the manufacture of wicks or threads from glass, P (7) 186*h*. Process and apparatus for sorting balls, P (5) 131*f*. Production of fibers from thermoplastic material, particularly glass fibers, P (8) 211*c*. Sheets, bricks, blocks, or similar articles made of transparent material, especially glass, P (8) 211*e*. Tempered glass sheet or plate, P (7) 187*a*.

Compton, M. D. Method of producing a glazed ceramic article, P (8) 218*d*.

Compton, W. D., and Arnold, G. W., Jr. Radiation effects in fused silica and α-Al_2O_3, (8) 229*j*.

Conax Corp. Thermocouple unit, P (3) 81*h*.

Condolios, E., and Chapus, E. E. Transporting solid materials in pipelines, (10) 284*e*.

Cone, C. See Young, G. H.

Coney, J. J. Cementitious material and method of preparation, P (3) 64*j*.

Conley, R. F. New method gives particle size data quickly and accurately, (8) 223*b*. Rapid particle-size analysis of ceramic clays by packing-volume technique, (3) 83*c*.

Conn, J. B. Thermoelectric materials, P (2) 50*b*.

Conn, J. B., and Magee, J. V. Process for preparing heavy metal tellurides, P (3) 84*g*.

Connell, M. W. Thermocouple unit, P (3) 81*h*.

Connor, J. E., Jr. See Leum, L. N.

Conrose, C. W. Lenses cleaning apparatus, P (6) 157*f*. Protection and cleaning of lenses, P (6) 158*e*.

Conroy, A. R., Billings, D. D., Manring, W. H., and Bauer, W. C. Controlled atmosphere hot stage for microscopic observations of glass melting phenomena (II) experimental observations, (7) 184*h*.

Conroy, A. R., and Robertson, J. A. Controlled atmosphere hot stage for microscopic observations of glass melting phenomena (I) description of equipment, (7) 184*g*.

Conroy, L. E. See Bernoff, R. A.; McNeil, W.

Conry, W. T. See Roberts, R. W.

Consolidated Beryllium, Ltd. Method of making a porous shape of sintered refractory material, P (10) 277*e*.

Consolidated Electrodynamics Corp. Chromatography, P (10) 287*b*. Oxygen detection, P (8) 224*d*.

Continental Can Co., Inc. Glass jar unloader, P (5) 130*j*. Light source for photoelectric inspection of glassware, P (4) 100*b*. Photoelectric inspection of glassware, P (5) 131*d*.

Continental Oil Co. Method and apparatus for connecting a getter-ion pump to an analytical mass spectrometer, P (1) 31*c*. Method and apparatus for operating an analytical mass spectrometer with a getter-ion pump, P (2) 60*c*.

Continental Optical Co., Inc. Method of making lenses, P (3) 70*g*.

Controls Co. of America. Ceramic magnet mounting structure, P (9) 248*f*.

Conway, K. A. Coating materials, P (9) 237*d*.

Coobs, J. H. Materials development for Core I fuel assemblies for the experimental gas-cooled reactor, (4) 101*b*.

Cook, C. P. See Cook, M. D.

Cook, M. D., Cook, C. P., and King, D. F. Pneumatic placement of refractory castables (I), (10) 275*d*.

Cook, P. E. Continuous sampling for X-ray analysis, (5) 142*e*.

Cook, R. L. See Wilcox, D. L.

Cooke, C. C., and Hamilton, J. C. Method of forming glass articles, P (5) 131*h*.

Coon, D. D. See Roberts, S.

Coop, W. H., and Hammond, J. A. Phosphorescence of fused quartz and sapphire, (5) 145*b*.

Cooper, A. R., Jr. See Ritter, J. E., Jr.

Cooper, A. R., Jr., and Goodnow, W. H. Density distributions in dry-pressed compacts of ceramic powders examined by radiography of lead grids, (1) 22*h*.

Cooper, B. R. Magnetic anisotropy constant of yttrium iron garnet at 0°K, (3) 87*b*.

Cooper, T. D., and Srp, O. O. Refractory metals and their protection, (10) 269*f*.

Coors Porcelain Co. Method for disposing of radioactive waste and resultant product, P (9) 246*b*. Slurry diffusing machine, P (5) 138*g*.

Copeland, L. E., Kantro, D. L., and Verbeck, G. Chemistry of hydration of portland cement, B (5) 149*j*.

Copenhefer, J. E. Automatic glass loader, P (10) 271*c*.

Copley, S. M. See Hulse, C. O.

Coppola, P. P. Apparatus [stencil] for spraying cathodes, P (1) 10*j*.

Corbett, J. W. See Watkins, G. D.

Corbin, V. L., and Crain, A. M. Screen tensioning device, P (7) 195*c*.

Coren, G. Cooler electronic packages, (1) 19*d*.

Corliss, L. See Scatturin, V.

Cormier, F. S. de. See Kahan, G. J.

Cornelison, B. Strain gage [fused quartz], P (10) 287*f*.

Cornelison, B., Jones, M. E., Lineback, J. T., Wolff, E. A., Jr., Barcus, S. W., Jr., Horak, F. A., and Ince, N. S. Materials for and methods of manufacturing semiconductor devices, P (5) 136*a*.

Cornelison, B., and Wolff, E. A., Jr. Masking and fabrication technique [for semiconductor device], P (8) 220*a*.

Corney, J. D. Dish granulation in the chemical industry, (9) 250*a*.

Corney, J. I. E. See Busby, T. S.

Corning Glass Works. Electrical measuring and control apparatus and a glass press embodying it, P (5) 130*i*. Electrical metal oxide resistor having a glass enamel coating, P (4) 105*g*. Electroluminescent cell, P (1) 20*g*. Glass staining method and material, P (6) 157*d*. Image orthicon target, P (4) 100*a*. Laminated glass articles and method of making them, P (9) 242*b*. Method and apparatus for forming glass, P (10) 272*i*. Method of joining two glass bodies, P (11) 305*a*. Method of making an abraded neck ampoule, P (3) 70*e*. Method of making bifocal lenses, P (4) 100*d*. Method of making a sintered ceramic article, P (10) 277*f*. Method of separating devitrified glass seals, P (2) 42*f*. Opal 96% silica glass and method of production, P (2) 42*i*. Prismatic light transmitting panel, P (4) 100*b*. Production of sulfate opal glasses, P (6) 158*d*. Soft glasses having high electrical resistivity, P (6) 158*f*. Stopcock assembly, P (9) 242*f*. Ultrasonic delay line, P (1) 22*c*. Volumetric glassware and method of production, P (2) 43*c*.

Corsentino, J. Apparatus for producing fibers from molten material, P (4) 99*g*.

Corson, B. L. Shaft kiln with orifice controlled combustion, P (1) 3*j*.

Corson, G. & W. H., Inc. Compositions for building load supporting surfaces, P (5) 127*b*.

Cosma, M. Contributions to the study, with radioactive isotopes, of the wear of the refractory lining in converters operated by oxygen blast, (3) 72*b*.

Costa, D. P. Basic engineering charts for air heated enclosures, (4) 106*e*.

Cotter, P. G., and Potter, R. A. Method for producing zirconium diboride, P (8) 216*g*.

Cotton, F. A. (editor). Progress in Inorganic Chemistry (Vol. III), B (3) 92*a*.

Coughlin, J. M. See Rowan, H. D.

Council of Scientific & Industrial Research. Nonshrinking and low-expanding cement, P (9) 238*a*.

Counts, W. E. Permanent magnet, P (1) 21*c*.

Courbes, J. P. Combination of lime in calcareous earthenware bodies, (8) 217*g*.

Courtaulds, Ltd. Gas analyzer, P (1) 24*j*.

Cowan, C. T., and White, D. Adsorption by organo-clay complexes, B (5) 150*i*.

Cowan, R. D. Pulse method of measuring thermal diffusivity at high temperatures, (10) 286*b*.

Cowley, C. H. Apparatus for producing multiple sheet glazing units, P (1) 10*j*. See Davis, D. A.; Dunipace, D. W.

Cowley, C. H., Hubbell, J. W., and Durieux, M. E. Method of treating glass sheets or plates, P (4) 100*g*.

Cowley, W. E. Abrasive article, P (9) 236*e*.

Cox, F. G. See Miller, G. L.

Cox, G. C. See Becker, C. H.

Cox, M. C. See Sarakauskas, R. V.

Cox, N. L. Ferromagnetic chromium oxide and preparation, P (6) 166*c*. Process for producing ferromagnetic chromium oxide, P (5) 137*e*.

Cox, R. W. See Holmes, W. H.

Coyle, R. A. See Hickman, B. S.

Crafts, H. S. Components that learn and how to use them, (7) 191*b*.

Craig, B. G. How to develop porcelain enamels for corrosive environments, (11) 302*j*.
Craig, D. B. Benford plate, (4) 107*c*.
Craig, D. K. Differential thermal analysis of quartz, (2) 56*f*.
Craig, J. W. Low-iron, spalling-resistant periclase brick, P (6) 162*f*. Thermoplastic refractories, P (6) 163*a*.
Crain, A. M. See Corbin, V. L.
Cramer, S. Thermal transfer standard has memory, (7) 196*a*.
Crandall, W. B. See Carlson, W. A.; Chung, D.-H.; Hasselman, D. P. H.
Crandall, W. B., Chung, D.-H., and Gray, T. J. Mechanical properties of ultrafine hot-pressed alumina, B (3) 92*d*.
Crane, W. G. Method of inhibiting corrosion, P (1) 5*b*.
Crary, J. F., and Fryer, H. C. Factors affecting strength of field-fabricated concrete test beams, (2) 34*h*.
Crawford, J. H., Jr. Effect of neutron irradiation on crystalline and glassy inorganic solids, (10) 292*f*. See Curtis, O. L., Jr.
Crawley, G. E., Jr. See Pilloton, R. L.
Crawley, W. P. Heat resistant fibrous products containing ceramic fibers and method of making them, P (9) 244*i*.
Creager, J. S., and Sternberg, R. W. Comparative evaluation of three techniques of pipette analysis, (11) 312*j*.
Creamer, R. H. See Harrop, P. J.
Crede, C. E. See Harris, C. M.
Cremer, E. See Bachmann, L.
Cremer, E., and Nitsch, W. Kinetics of thermal decomposition of calcium carbonate, B (4) 124*a*.
Cremer, G. German tunnel kiln perfects zone control (I, II), (1) 24*h*.
Crimmins, D. H. Transient heat transfer from ceramic fuel pins, (4) 102*b*.
Crocker, W. G. Wave ring thermocouple, P (11) 314*a*.
Croessant, R. C., and Pascoe, W. R. Coating process, P (8) 208*b*.
Cronin, L. J. High-frequency energy absorbing material, P (10) 282*i*.
Crookston, J. A. See Frank, J. M.
Cropper, W. H. Radiation effects on the reactivity of solid surfaces, (2) 58*b*.
Cross, L. E. High permittivity relaxation dielectrics, (9) 247*i*.
Crossley Machine Co., Inc. Automatic thickness control means for flat products, P (6) 167*g*.
Crucible Steel Co. of America. Powder metallurgy processes and products, P (3) 74*i*.
Cullen, G. W. See Amick, J. A.
Cullis, J., Jr. Lamp and method of manufacture, P (6) 157*f*.
Cummings, W. V. See Holden, A. N.
Cunningham, A. See Wainer, E.
Cunningham, C. R., Weiss, M. D., and Schreffler, R. Z. Method and apparatus for forming and collecting filaments, P (9) 242*e*.
Cunningham, G. W. See Paprocki, S. J.
Cunningham, J. R., Jr. See Anderson, E. E.
Cunningham, K. G., and Baillie, A. J. Wall plasters and their preparation, P (2) 36*b*.
C.U.R.A. Patents, Ltd. Apparatus for the disintegration of solid particles, P (5) 140*j*.
Currier, E. L., Jr., and Nicklas, J. H. Nuclear reactor fuel-breeder fuel element, P (1) 16*j*.
Currier, E. W. See Battle, J. H.
Curtis, A. W. See Mentel, R. A.
Curtis, G. J. See Cartan, F. O.
Curtis, O. L., Jr., and Crawford, J. H., Jr. Carrier recombination and trapping processes in irradiated germanium, (8) 226*c*.
Curtiss-Wright Corp. Method of manufacture of homogeneous compositions, P (4) 102*g*. Molecular cermets and method of making them, P (3) 74*f*.
Cusano, D. A., and Sormberger, R. L. Method for making electrically conducting films and article, P (10) 283*f*.
Cushion, J. P. Ceramics for collector and potter (I) English medieval wares; (II) Staffordshire slipware; (III) English delftware; (IV) salt-glazed stoneware; (V) cream colored earthenware, (2) 33*i*. Modern potters: David Eeles, (2) 33*i*.
Cusick, P. Low-fire ceramic jewelry, (5) 126*a*.
Custers, J. F. H., Dyer, H. B., Senior, B. W., and Wedepohl, P. T. High-pressure die, P (3) 80*b*.
Cutler, I. B. See Herrmann, E. R.
Cutler, J. F. Clay masonry renaissance, (7) 187*b*.
Cuttitta, F. See Hickling, N.
Czaja, A. T. Problem of the effects of cement dust on plants, (4) 96*h*.
Czernin, W. A few unsolved problems of cement hydration, B (5) 149*i*.
Czerny, M., and Genzel, L. Calculation of the radiation flux in the glass bath of melting tanks, (11) 314*c*.

Dachille, F., and Roy, R. High-pressure region of the silica isotypes, (4) 114*b*. Use of infrared absorption and molar refractivities to check coordination, (5) 147*g*.
Dager, P. W. Ceramic engineering, (6) 176*d*.
Dahlberg, P., Carnahan, R. D., and Brittain, J. O. Dislocation damping in magnesium oxide crystals at low frequencies, (5) 134*j*.
Dahle, O., and Berggren, L. Magnetoelastic force measuring device, P (10) 282*j*.
Dahms, F. A. Glassware inspection apparatus, P (8) 210*h*.
Dahms, J. B. See Edmonds, B. P.
Dainton, A. D. Rheological properties of semicoke at high temperatures, (7) 196*i*.
Dakin, T. W., and Berg, D. Theory of gas breakdown, B (9) 263*j*.
Dale, A. E. Colored silicate coatings for glass, P (4) 99*a*.
Dalmazzo, M. See Grungo, G.
Dalton, E. T. Surfacing apparatus, P (10) 285*e*.
Daman, A. C. Apparatus for comminuting ores, etc., P (3) 83*c*.
Damm, J. Z., and Tompkins, F. C. Thermal bleaching of V and F centers in X-irradiated potassium chloride crystals, (11) 319*g*.
Damm, K. See Noll, W.
Dammers, A. Method and apparatus for bending glass, P (6) 157*j*.
Damodaran, V., Neuragaonkar, V. G., Sen, D. N., and Gupta, J. Chlorination of bauxite sludge, (11) 314*h*.
Damoth, D. C., and Saari, J. M. Apparatus for presenting source particles to a mass spectrometer, P (5) 148*a*.
Damrel, J. B. Quartz Bourdon gage, (6) 168*b*.
Dane, O. Financing industrial expansion in the ceramic industries, (6) 176*f*.
Danfoss VED ingenior Mads Clausen. Feeler element for a humidostat, P (2) 53*b*. Low pressure atomizer nozzle for oil burners, P (6) 169*e*.
Dani, R. H. See Bhide, V. G.
Daniel, W. A. Radially vibratile ceramic transducers, P (2) 50*a*.
Daniels, A. U., and Wadsworth, M. E. Equipment for sintering of thoria and thoria gels, (8) 227*i*.
Daniels, F. See Johnson, N. M.
Daniels, G. E. Radiation compensating thermoelectric device, P (1) 24*f*.
Danielson, G. C. See Ellerbeck, L. D.
Danielsson, U. Heat of hydration of cement as affected by water-cement ratio, B (5) 149*c*.
Danko, J. C. See Baily, W. E.
Dano, T. H., and Pedersen, H. E. O. Rotary kiln and method of burning material therein, P (5) 140*f*.
Dantro, H. F., Kalinowski, A. T., and Siuta, W. T. Method for producing titanium dioxide pigments, P (9) 254*b*.
Danyluke, O., and Fawcett, F. A. Dust prevention device for rotary [hammer] impactor, P (7) 195*a*.
Danzer, J. H. Optical mirrors, P (3) 70*b*.
D'Arcy-Smith, F. E. Bulk handling of powders in the chemical industry, (1) 22*d*.
Das, R. K. See Mahanta, P. C.
Das, S. C. See Ghosh, S. K.
Das Gupta, H. N., and Joshi, V. C. Formation of mullite crystals (I) mullitization of clays, (9) 256*f*.
Das Gupta, H. N., Sen, P., and Jaiswal, J. N. Application of differential thermal analysis technique to the study of glass systems (I), (9) 239*f*.
Dassu, G. See Bassi, A.
Datar, D. S. See Rao, B. V. S. S.
Datta, R. K., and Roy, R. Phase transitions in $LiAlO_2$, (10) 296*i*.
Dattan, W. See Streng, J.
Daum, M. Frontiers between industrial and craft production and the glass industry, B (11) 321*g*.
Daunt, J. E., and Grandey, M. F. Abradable material, P (1) 15*g*.
Dauphinee, T. McC., and Preston-Thomas, H. Direct reading resistance thermometer, P (8) 223*f*.
Davidson, C. R., Jr. Apparatus [tongs] for gripping and supporting glass sheets, P (9) 241*f*.
Davidson, C. R., Jr., and Mitchell, W. P. Handling rigid sheet articles [with glass tongs], P (8) 210*j*.
Davidson, D. T. See Mateos, M.
Davidson, D. T., Demirel, T., and Rosauer, E. A. Mechanism of stabilization of cohesive soils by treatment with organic cations, B (5) 151*a*.
Davidson, H. W., and Ryde, J. W. Methods of joining graphitic surfaces, P (10) 269*e*. Methods of protecting graphite surfaces, P (4) 103*a*.
Davidson, P. Hot top casing for casting molds, P (5) 133*i*. Ingot mold hot top structure [design], P (5) 133*a*.
Davies, B., and Renkey, A. L. Refractory compositions, P (5) 133*i*.
Davies, B., and Weaver, E. P. Refractory practices, P (4) 103*c*.
Davies, E. See Holmes, W. H.
Davies, L. J., and Booth, H. Hot strength apparatus and some preliminary results, (2) 52*i*.
Davies, L. J., and Brough, R. Physical properties of ceramic bodies at high temperatures (I) measurement of modulus of elasticity; (II) measurement of transverse strength, (11) 313*j*.
Davies, L. M., Simmonds, R. N., and Jones, T. Diamonds in atomic energy research (I) machining of sapphire, (9) 235*g*.
Davies, M. W. See Busby, T. S.
Davies, W. J. K., Thomas, A. G., Huffadine, J. B., and Moore, N. C. Symposium on nuclear ceramics: Zirconium carbide coated uranium oxide fuel particles, (11) 308*a*.
Davis, C. M., Jr. Magnetostrictive ferrite, P (6) 166*e*.
Davis, C. V. Zircon and refractory washes and cement, (5) 132*j*.
Davis, C. W. V. Magnetic separator [filter], P (3) 80*c*.
Davis, D. A., and Cowley, C. H. Apparatus for producing all-glass multiple sheet glazing units [with access opening], P (1) 10*i*.
Davis, E. K. Neutral colored glass composition, P (10) 272*h*.
Davis, G., Jr., and Grannemann, W. W. Point contact diodes utilizing single-crystal reduced rutile titanium dioxide, (10) 281*f*.
Davis, G. P. Alkali metal generators, P (10) 269*a*.
Davis, J. K. Electrical metal oxide resistor having a glass enamel coating, P (4) 105*g*.
Davis, L., Jr. Orientation of ferrites, P (3) 78*b*.
Davis, L. W. How to deposit metallic and nonmetallic coatings with the plasma arc torch, (9) 238*b*.
Davis, R. L., Williams, W. C., and Hanner, J. L. Multiple unitizer, P (5) 138*c*.
Davis, R. L., II. Measurement and control of constituent potentials, P (8) 221*j*.
Davis, W. L., Jr. Heat exchanger and method, P (5) 140*e*.
Davydov, K. N., Sidorenko, F. A., and Gel'd, P. V. Martensitic transformation in Mn_5Si, (2) 57*j*.
Day, C. E. See Mambourg, J. E.
Day, D. E., and Rindone, G. E. Properties of soda aluminosilicate glasses (III) coordination of aluminum ions, (2) 40*g*.
Day, G. V. See Huckstepp, L. D.
Day, R. K. Improved source for controlled thermal evaporation in a vacuum, (1) 19*j*.
De, K. See Haider, S. Z.
De, S. K. Adsorption of phosphate ion by hydrous ferric, chromic, and aluminum oxides (I) no organic material added; (II) organic material added, (3) 85*h*.
Deadmore, D. L., and Machin, J. S. Silica brick from northern Illinois silica sand, (8) 214*i*.
Deal, S. B., and Bartch, D. W. Resistive semiconductive coating, (2) 48*j*.
Dean, G. A. Titrimetric determination of vanadium in chromite, (1) 31*a*.
Dean, H. N. Method and apparatus for continuously gathering fiber, P (5) 131*c*. See Sharp, D. E.
Dean, H. N., and Olson, A. W. Apparatus for producing multiple glass sheet glazing units [by fusion bonding], P (10) 271*b*.
Dean, J. A. See Carries, W. J.
Deane, A. M. Infrared spectra and structures of some hydrated uranium trioxides and ammonium diuranates, (9) 256*a*.
Deans, T. See Wall, J. R. D.
Dear, E. J., and Staples, R. W. Ore pulverizer with centrifugal impact action, P (10) 289*i*.
Dear, P. S. Solid-state equilibria for the ternary system strontia–magnesia–silica, (10) 297*g*.
Dearing, A. G. Two stage centrifugal impact pulverizing apparatus with annular elastomeric concaves, P (3) 85*d*.
De Bartolomeis, R. Device for localizing rapid variations of temperature at predetermined points in tunnel type kilns for the firing of ceramic products, P (1) 24*h*.
Debras-Guedon, J. See Voinovitch, I. A.
Debras-Guedon, J., and Voinovitch, I. A. Analysis of silicates by flame photometry in an oxine medium, B (10) 300*f*.
Decken, A. von der. Expanded clay, P (4) 100*b*.
Decker, H., Maeder, H. J., and Wehren, P. Grinding mill of the swinging type with a plurality of grinder drums, P (7) 197*i*.
Decker, J. B., and Meder, H. Briquetting roller press [with roll adjustment] for compacting ore, coal, etc., P (5) 141*a*.
Deeg, E. W. General method for calculating temperature or concentration in laminated systems, (9) 251*b*. Survey on bending behavior of glasses in the arsenic–sulfur system, B (3) 92*e*.
Deely, M. H. Mason's lime fights to retain foothold, (2) 35*d*.
Deer, W. A., Howie, R. A., and Zussman, J. Rock-Forming Minerals (Vol. 1) Ortho- and Ring Silicates, B (5) 151*g*; (Vol. 2) Chain Silicates, B (9) 264*d*; (Vol. 3) Sheet Silicates, B (10) 299*d*.
Dees, J. W., and Sheppard, A. P. New millimeter components and techniques, (6) 164*h*.
Deevy, M. M. Method of making metal-to-ceramic seals, P (9) 249*a*.
Deffeyes, K. S. See Chave, K. E.
De Freyne, E. C. Thermometer manufacture, P (10) 273*a*.
Dega, R. L. High temperature bond and method of forming it, P (1) 16*d*. High temperature seal, P (4) 102*a*. Multilayered composite metal article, P (9) 245*a*.
Degelius, G. See Hedvall, J. A.
Degerfors Jarnverks AB. Process for producing hot tops, P (6) 162*h*.
De Hart, H., and Brooks, D. H. Supports for aerating particulate materials, P (11) 312*f*.
Deissmann, W. See Hund, F.
De Kimpe, C. See Brindley, G. W.
De Kimpe, C., Gastuche, M. C., and Brindley, G. W. Ionic coordination in aluminosilicic gels in relation to clay mineral formation, (4) 115*j*.
Dekker, P. Gloss measurement of enamels by the method of F. R. Meyer, (8) 207*f*.
Delachanal, M. Apparatus and process for sorting solid particle material in a fluidized liquid medium, P (5) 141*a*.
Delangre, M., Murdoch, A. W., and Vetten, W. C. Direct-on white enameling process, B (11) 322*h*.
DeLaRue, R. E. See Hiester, N. K.
Delavignette, P. See Amelinckx, S.
Delavignette, P., and Amelinckx, S. Dislocation patterns in graphite, (1) 27*i*.

Delbecq, C. J., Smaller, B., and Yuster, P. H. Optical absorption of Cl_2^- molecule ions in irradiated potassium chloride, (4) 117*b*.

Delfs, H. J. Apparatus for classifying air-dust mixture, P (6) 167*g*.

Del Grosso, E. J., Krutenat, R. C., Carlson, C. E., and Carta, S. J. Oxidation characteristics of niobium-1 zirconium alloy, (11) 302*j*.

Deliere, E. See Brichard, E.

Dell, R. M. See Charman, H. B.

Dell, R. M., and Wheeler, V. J. Chemical reactivity of uranium trioxide (I) conversion to U_3O_8, UO_2, and UF_4, (10) 290*i*.

Del Mar, R. Building material and manufacture thereof, P (10) 268*d*.

De Long, H. K. How to porcelain enamel magnesium, (5) 127*g*.

De Long, H. K., and Brown, J. A. Process for vitreous enameling of magnesium and its alloys, P (8) 208*b*.

Delott, R. B. Advantages of using ferric sulfate in the preparation of metal for cover coat direct-on steel enameling, (2) 36*g*. See Zander, J. M.

De Luca, F. J. See Jacobson, M. G.

Demaison, R. J. Method of spraying multiple coatings of refractory compositions for hot furnace repair, P (9) 244*i*. Open hearth furnace doors [design], P (7) 180*j*. Refractory insulating and sealing compound, P (9) 245*b*. Sprayable basic refractory composition for repairing the hot basic refractory linings of high temperature furnaces and method, P (9) 245*c*.

Demaison, R. J., and Dreyling, L. J. Heat resisting coating composition and method of applying it to the basic refractory surface of a furnace, P (9) 244*j*.

De Matteo, A. J. Multiple injection molding apparatus, P (11) 312*a*.

Dembinski, B. Diamond cutting and polishing device, P (10) 265*f*.

Demetrescu, A. See Cioaca, E.

Demirel, T. See Davidson, D. T.

Demishev, G. K., and Kolbasnikova, A. I. Polishing of glass with ultrasonics, (7) 185*e*.

Demkina, L. I., and Ivanov, M. F. Volatility of fluorine crowns, (1) 10*a*.

Demoulian, E. See Forest, J.

Dempsey, E. See Benson, G. C.

Denisova, L. L. See Ivoilov, A. S.

Dennis, J. S. See Wunnik, J. van.

Denniston, D. W. Combustion chamber burner for producing glass fibers, P (1) 11*a*. Method and apparatus for forming fibers, P (7) 186*i*. See Helbing, C. H.

Denny, A. D. See Kalousek, G. L.

Denovan, R. A. Gyrating [lateral] screen, P (11) 312*g*.

Denovan, Ltd. Gyrating [lateral] screen, P (11) 312*g*.

Dentists' Supply Co. of New York. Dental porcelains, P (4) 104*e*.

Denver Equipment Co. Apparatus for comminuting ores, etc., P (3) 83*c*.

De Poorter, G. L. See McNeilly, C. E.

Derbyshire, W. D., and Yearian, H. J. X-ray diffraction and magnetic measurements of the Fe-Cr spinels, (5) 147*g*.

Deren, J. See Bielanski, A.

Derevyankin, V. A. See Shabalina, O. K.

Deri, A. See Galdina, N. M.

Derlon, H. See Raub, K.

Deryagin, B. V. See Abdrakhmanova, I. F.

DeSantis, V. J. See Kibler, G. M.

Deshmukh, G. S., and Srivastava, J. P. Polarographic determination of titanium in the presence of iron-malonate complexes of titanium, (11) 313*c*.

Desmond, D. J. Symposium on control of the quality of glassware: Quality incentives in the container industry, (9) 241*a*.

Despres, J. Process and apparatus for the manufacture of fibers from fusible mineral materials, more particularly glass and its derivatives, P (7) 186*g*.

Dess, H. M. Foamed silicon carbide, P (11) 308*a*. Method of making foamed silicon nitride, P (8) 216*c*.

Detrick, M. H., Co. Roof or wall tile [interlocking], P (2) 46*g*.

Dettmer, F. Faulty brown glazes having a metallic luster effect, (10) 278*i*.

Dettre, R. H. See Gray, C. L., Jr.

D'Eustachio, D. Sound absorbers, P (9) 242*d*.

Deutsche Edelstahlwerke Akt.-Ges. Ceramic materials containing zirconium silicate for the manufacture of heat-resistant machine parts, P (4) 102*c*.

Deutsche Gold- und Silber-Scheideanstalt vorm. Roessler. Artificial gems, P (4) 121*h*. Burner for production of finely divided oxides, P (8) 224*f*. Fire-resistant nontoxic yellow ceramic glazes and enamels, P (6) 155*e*. Thin films with a negative temperature coefficient of electrical resistance on ceramics, P (4) 106*a*.

Deutsche Ton- und Steinzeugwerke Akt.-Ges. Electromagnetic removal of iron from ceramic powders in free fall, P (3) 83*g*.

Dever, C. D. See Wahl, W. W.

Devine, R. E. See Plesset, M. S.

Devoe & Raynolds Co., Inc. Cement base paints, etc., P (3) 64*i*.

DeVries, R. C. See Sears, G. W.

DeVries, R. C., and Sears, G. W. Step formation during the growth of $BaTiO_3$ crystals, (2) 58*j*.

Dewey, J. L. Refractory lining for alumina reduction cells, P (9) 245*d*.

DeWitt, V. R. See Glidewell, M. E.

De Woody, C. M. Stopcock for laboratory glassware, P (9) 242*g*.

De Woody, C. M., Pearce, R. L., Mueller, W., and Egizi, E. A. Resistance coating for articles of glassware, P (9) 242*b*.

Dezider'ev, G. P. See Vozdvizhenskii, G. S.

Dhar, R. N., Mandal, S. S., and Roy, S. B. Micanite and its properties, (3) 82*f*.

Diamond Tool Associates. Method of making a cutting apparatus, P (5) 125*g*.

Diaz, C. C. Deformations in ceramics—sources and remedies, B (2) 61*a*.

Dichter, J. Automatic machine for working the ends of long glass tubes, P (3) 69*c*. Glass tube feeding machine, P (4) 100*a*.

Dickerson, R. F. See Burian, R. J.

Dickey, W. S., Clay Mfg. Co. Coupling for ceramic pipe, P (2) 44*c*.

Dickson, F. W., Blount, C. W., and Tunell, G. Use of hydrothermal solution equipment to determine the solubility of anhydrite in water from 100°C to 275°C and from 1 bar to 1000 bars pressure, (5) 147*f*.

Didchenko, R., and Litz, L. M. Preparation of refractory sulfides, P (8) 216*i*.

Didier-Werke Akt.-Ges. Refractory magnesite linings for rotary cement kilns, P (3) 74*g*. Silicon carbide refractories, P (3) 75*a*. Sintering of fine-grained minerals, P (4) 111*f*.

Diehl, K. B. Effectiveness of CO_2 gas on portland cement slurry, (11) 302*a*.

Dietert, Harry W., Co. See Harry W. Dietert Co.

Dietert, H. W. Apparatus for measuring and controlling moisture content of materials, P (9) 250*d*. Moisture teller [for granular material], P (9) 252*h*.

Dietert, H. W., Dietert, R. L., Graham, A. L., and Kabel, M. R. Apparatus for electrical moisture measurement [during milling], P (9) 252*e*.

Dietert, R. L. See Dietert, H. W.

Dietrich, R. V. Virginia mineral localities, (10) 289*c*. Virginia minerals and rocks, (10) 289*c*.

Dietz, P. L., Jr. See Strain, F.

Dietz, U., and Schulle, W. Sintering of quartz and cristobalite, (10) 276*h*.

Dietzel, A. See Hinz, I.; Poch, W.

Dietzel, A., and Hinz, I. Melting of aluminum orthophosphate, (7) 183*h*.

Dietzel, A., Merker, L., and Haas, B. Highly acid- and alkali-resistant enamels containing cations of noninert gas structure, (8) 207*g*.

Dijck, W. J. D. van, and Koosterziel, H. Process for the preparation of carbon with high moderating properties and its use in nuclear reactors, P (1) 17*g*.

Dilliard, A. E., and Mifflin, E. L., Jr. Abrasive drilling apparatus, P (5) 138*f*.

Dilling, M. See Vratny, F.

Dillon, H. P., II. High temperature coatings, P (9) 239*a*.

Dillon, J. F., Jr. Ferrimagnetic resonance in yttrium iron garnet at liquid helium temperatures, (2) 57*c*.

Dillon, O. W. Bevel-edged lenses [4.5°], P (3) 69*d*.

Dills, R. L. Hydraulic thermostat protector, P (1) 25*a*.

Dilnot, S. Lightweight aerated concrete, P (3) 65*b*.

Dils, R. R., Martin, G. W., and Huggins, R. A. Chromium distribution in synthetic ruby crystals, (5) 142*c*.

DiMarcello, F. V. See Gallagher, P. K.; MacChesney, J. B.

Dinan, F. J. Method of making magnesium oxide, P (7) 180*i*.

Dinning, T. N. Guide to insulation costs for vessels, (8) 221*g*.

Dinsdale, A. Crystalline silica in whiteware bodies, (11) 309*b*.

Dinsdale, A., Moulson, A. J., and Wilkinson, W. T. Experiments on the impact testing of cylindrical ceramic rods, (9) 256*h*.

Di Vita, S. See Arlett, R. H.

Dixon, H. O. Method for preparing cellular cement, P (10) 268*a*.

Dixon, J. B., and Jackson, M. L. Mineralogical analysis of soil clays involving vermiculite-chlorite-kaolinite differentiation, B (3) 91*a*.

Dizon, G. D., Almonte, J. B., and Anselmo, J. E. Bagassosis and silicosis in the Philippines, (11) 320*d*.

Dmitrichenko, N. S. See Popov, V. S.

Dobbins, G. L. Method for removing complex sodium aluminum silicate scale, P (5) 138*b*.

Dobrokhotova, V. K. See Aleksandrov, B. S.; Naboikin, Yu. V.

Dobrzhanskii, G. F. See Bagdasarov, Kh. S.; Beznosikov, B. V.

Docherty, A. C. See Elmes, A. W.

Dodd, C. G. See Ham, W. E.

Dodd, C. G., and Ray, S. Semiquinone cation adsorption on montmorillonite as a function of surface acidity, B (3) 91*a*.

DODUCO-KG, Dr. Eugen Duerrwaechter. See Duerrwaechter, Dr. Eugen, DODUCO-KG.

Doedens, J. D., and Pletcher, D. E. Flame resistant compositions of inorganic fillers and polymeric products of halomethyl diphenyl oxides, P (7) 186*b*.

Doehler, R. W., and Young, W. A. Some conditions affecting the adsorption of quinoline by clay minerals in aqueous suspensions, B (5) 150*i*.

Doelp, L. C., Jr. Preparing alumina beta trihydrate, P (9) 254*e*.

Doetsch, E. Screw nipple connection for [carbon] electrodes, P (1) 17*c*.

Doetsch, E., and Klier, G. Method of interconnecting electrodes, especially carbon and graphite electrodes for electric furnaces, P (8) 224*j*.

Dohr, H., and Wiebke, G. Experiences with the crushing of silicon carbide in a boron carbide mortar, (10) 284*d*.

Dohrmann, H. C. See Balzer, C. G.

Doladugina, V. S. Apparatus and methods for testing quartz for homogeneity, B (9) 263*g*.

Dolloff, R. T. Method and apparatus for growing crystals, P (1) 16*h*. See Sara, R. V.

Dolph, J. L. Aluminum melting furnace refractory P (6) 161*i*.

Doman, R. C., Barr, J. B., McNally, R. N., and Alper, A. M. Phase equilibria in the system CaO–MgO, (9) 256*c*.

Domanski, S. M. Ceramic dielectric materials and capacitors incorporating them, P (4) 105*b*.

Domicone, J. J. Laminated glass articles and method of making them, P (9) 242*b*.

Domicone, J. J., and Smith, W. C. Method of joining two glass bodies, P (11) 305*a*.

Donahue, D. J. See Jordan, E. L.

Donald, M. B. See Roseman, B.

Donaldson, E. E., and Rabinowitz, M. Effects of glass contamination and electrode curvature on electrical breakdown in vacuum, (10) 280*h*.

Donaldson, I. G. Computed errors for a square guarded hotplate for the measurement of thermal conductivities of insulating materials, (3) 72*a*.

Donnay, J. D. H. See Ring, M. A.

Donner, W., and Carle, D. W. Temperature regulator for chromatographs, P (3) 90*a*.

Donohue, J. Relationship between atomic radii in close-packed and body-centered cubic structures, (11) 318*i*.

Doolittle, H. D. See Spurck, R. F.

Doorn, C. Z. van. Color centers in potassium chloride, (5) 142*e*.

Doremus, R. H. Diffusion in noncrystalline silicates, B (9) 263*i*. Structural information from transport measurements in glass, (3) 68*e*.

Dorril, D. T. See Williams, E. C.

Dorsey, M. M. Head and mantle assemblies for crushers, P (10) 289*j*.

Dortmund-Horder Huttenunion Akt.-Ges. Refractory nipple for dipping into molten metal, P (2) 46*g*.

Dotter, R. T. Blenders applied to batch mixing, (6) 167*b*.

Doughty, D. C., and White, E. A. D. Imperfections in yttrium iron garnet crystals, (10) 294*c*.

Douglas, R. W. Science and the glass industry, (5) 129*f*. See Mohyuddin, I.; Rana, M. A.

Douglas, R. W., and Adams, R. V. Comments on KBr briquette method for studying infrared spectra of anhydrous borates, (2) 57*b*.

Douglass, R. M. See Ogard, A. E.

Dow, F. W. Flexible electroluminescent strand, P (1) 21*b*.

Dow Chemical Co. Caustic beneficiation of titanium source materials, P (4) 110*e*. Chromate pigments, P (4) 110*f*. Composite anode, P (5) 135*e*. Flame resistant compositions of inorganic fillers and polymeric products of halomethyl diphenyloxides, P (7) 186*b*. Grinding and polishing compositions and method of making them, P (1) 1*g*. Low water-loss cement composition, P (8) 206*c*. Method of making lightweight aggregate, P (2) 44*a*. Method for making potable water and magnesium chloride from seawater, P (2) 55*a*. Preparation of anhydrous magnesium chloride [by ammonia reaction], P (9) 254*d*. Pressure leaching of titaniferous material, P (3) 84*h*. Process for preparation of titanium dioxide, P (3) 84*c*. Process for vitreous enameling of magnesium and its alloys, P (8) 208*b*. Production of $Mg(OH)_2$, P (6) 171*c*. Recovery of beryllium from acid leach solutions, P (2) 55*j*. Retardation of set time of aqueous gypsum compositions, P (2) 36*a*. Steel pipe having organic thermoplastic liner with glass fiber reinforcement, P (4) 100*c*. Water loss control of [pumpable] aqueous cement slurries by addition of quaternary ammonium polymers or sulfonium polymers, P (10) 268*e*.

Dow Corning Corp. Method of preparing ceramic-like articles, P (9) 246*d*.

Dowley, A. Apparatus adapted for use in affixing handles in the manufacture of ceramic ware, P (1) 18*c*.

Downs, C. D., and Martin, J. Magnetic material, P (9) 249*e*.

Dows, D. A., and Bottger, G. Infrared spectrum of crystalline BCl_3, (2) 57*j*.

Doyle, W. P. Absorption spectra of solids and chemical bonding (I) arsenic, antimony, and bismuth trioxides, (11) 315*j*.

Doyle, W. T. Method and apparatus for sizing solid particles [centrifugally], P (9) 250*c*. Optical absorption by F centers in alkali halides, (4) 117*c*.

Dragoman, I. See Solomon, L.

Draignaud, P. Control of technical potential in the works, (10) 298*c*. See Paquin, P.

Draignaud, P., and Aveline, M. Study of the uniformity of pressing of stoneware tiles—influence of the method of filling the molds, B (10) 300*j*.

Drakenfeld, B. F., & Co., Inc. Silicone-coated frit used in decorating glassware, P (11) 305*a*.

Drapak, I. T. See Vereshchagin, I. K.

Dravo Corp. Cooler for sinter, etc. [with vibratory conveyor], P (9) 253*g*.

Drefke, O. See Thiess, G. H.
Dreimanis, A. Quantitative gasometric determination of calcite and dolomite by using Chittick apparatus, (3) 81*b*.
Drennan, J. A. "Variable volume-decay rate" permeameter with restricted outflow, (3) 81*h*.
Drennan, J. G. Bottle handling apparatus, P (4) 99*j*.
Drexler, O., and Schat, B. R. Development of ceramic materials with a dielectric constant of 10,000 at room temperature, B (4) 123*i*.
Dreyfus, R. W., and Nowick, A. S. Energy and entropy of formation and motion of vacancies in NaCl and KCl crystals, B (9) 261*b*.
Dreyling, L. J. See Demaison, R. J.
Drickamer, H. G. See Tischer, R. E.
Driskell, L. R. How to select the best flowmeter, (7) 195*d*.
Dronsek, G. See Bielenberg, W.
Drost, W., Kebler, R. W., and Dutchess, E. E. Method of making synthetic unicrystalline bodies, P (6) 167*c*.
Droste, J. B. Clay minerals in the playa sediments of the Mojave Desert, Calif., (4) 109*a*. See Grim, R. E.
Droste, J. B., Bhattacharya, H., and Sunderman, J. A. Clay mineral alteration in some Indiana soils, B (5) 150*f*.
Drummond, A. J. See Angstroem, A. K.
Drummond, C. H. See Close, P. T.
Drury, D. V. Some contemporary stained glass—a letter from America, (10) 266*b*.
Drury, T., and Roberts, J. P. Diffusion in silica glass following reaction with tritiated water vapor, (10) 270*c*.
Drury, V. J., and Wilkinson, A. L. Conservation of stained glass, (10) 265*j*.
Drysdale, D. J., Lacy, E. D., and Tarney, J. "Water minus" (H_2O^-) in natural glasses, (7) 185*d*.
Drysdall, A. R., and Stillman, C. J. Optically negative variety of staurolite from Northern Rhodesia, (6) 170*f*.
Dubecky, P. Punch for forming perforations in coated asbestos-cement sheets, P (6) 167*g*.
Du Bois, E. See Saunderson, J. L.
Dubois, M., Berge, P., and Blanc, G. Influence of radiations on the electrical and optical properties of LiF, (10) 294*h*.
Dubrovo, S. K., Shmidt, Yu. A., Mozheiko, V. I., and Lileev, I. S. Chemically stable glass, P (2) 41*j*.
Ducati, A. C. Method of making glass fibers, P (11) 305*b*.
Duckworth, W. H., and Rudnick, A. Strength of ceramic materials, (7) 202*a*.
Duckworth, W. H., Smalley, A. K., and Brockway, M. C. Pelletizing to disperse nuclear fuel in fuel elements, (10) 275*a*.
Ducret, S. New and old information about the porcelain arcanist, Johann Benckgraff, (7) 177*j*.
Duebel, W. See Agte, C.
Dueker, G. W. See Woodcock, E. L.
Duerrwaechter, E., and Offner, T. Fluxing for metal coatings on ceramics, glass, or mica materials, P (3) 77*d*.
Duerrwaechter, Dr. Eugen, DODUCO-KG. Fluxing for metal coatings on ceramics, glass, or mica materials, P (3) 77*d*.
Duke, J. A. Temperature measuring apparatus, P (1) 24*g*.
Duke, J. B. Method for comminuting kaolin clay, P (10) 289*a*. See Greene, E. W.
Duke, J. B., and Greene, E. W. Attapulgite clay filter aid product and method of making it, P (6) 170*c*.
Dukes, E. K., and Burney, G. A. Solubility of neptunium(IV) peroxide, (7) 200*a*.
Dumesnil, M. E. Resistor and resistor composition, P (1) 21*h*.
Dumitrescu, T. See Petri, L.
Dummer, G. W. A., and Burkett, R. H. W. Recent developments in fixed and variable resistors, (9) 248*j*.
Dunbeck, J. T. Stopcock assembly, P (9) 242*f*.
Duncan, J. E., and Thomas, G. L. Glass composition, P (4) 99*g*.
Duncan, R. C., Jr. See Wittke, J. P.
Duncan, R. C., Kiss, Z. J., and Lewis, H. R. Sun-pumped continuous laser, (10) 282*j*.
Dundee Cement Co. Cement manufacture, P (9) 237*b*. Hot clinker conveying and cooling apparatus, P (9) 237*c*.
Dunegan, H. C. Notes on hardness measurements of polycrystalline materials, B (3) 92*e*.
Dungan, R. H., and Johnson, R. G. Method of making ceramic-metal seals, P (3) 78*e*.
Dunipace, D. W., and Cowley, C. H. Method and apparatus for fabricating all-glass multiple sheet glazing units, P (6) 158*a*.
Dun-Khua, T. See Tszyan, D. K.
Dunn, E. J., Jr. See Orsino, J. A.
Dunn, E. J., Jr., and Kushner, M. Antifouling pigment, P (11) 303*d*. Copper borate antifouling pigment, P (11) 303*a*.
Dunn, S. A., and Roth, W. P. High viscosity refractory fibers, (8) 214*c*.
Dunning, D. N. See Anderson, W. K.
Duperriez, C. Plastic coating of glass objects, P (10) 272*i*.
DuPlessis, J. J. See Palmour, H., III.
Du Pont de Nemours, E. I., and Co. Compaction process, P (8) 221*f*. Composition comprising particles of refractory oxide coated with an oxide of a transition metal, P (4) 102*d*. Ferromagnetic chromium oxides containing fluorine and their preparation, P (4) 105*c*. Ferromagnetic chromium oxide and preparation, P (6) 166*c*. Fibrous aluminum borate and its preparation, P (6) 162*b*. Film-covered shaped objects, P (2) 42*e*. Film forming composition, P (2) 38*a*. Free-flowing sodium silicate powder, P (1) 25*i*. Glass frit vehicle comprising normal butyl methacrylate polymer and monohydroxy aliphatic alcohol, P (7) 186*e*. Inorganic ceramic binders for metallizing piezoelectric transducers, P (6) 166*d*. Interlayers for safety glass, P (6) 157*e*. Iron group metals having submicron particles of refractory oxides uniformly dispersed therein, P (8) 216*i*. Preparation of recalcined zinc sulfide phosphors, P (1) 21*e*. Process for dispersing a refractory metal oxide in another metal, P (8) 217*a*. Process for increasing the scratch resistance of glass, P (1) 12*d*. Process for preparing aqueous silicate solutions, P (9) 254*f*. Process for preparing phosphor grade metal sulfides, P (2) 50*g*. Process for producing ferromagnetic chromium oxide, P (5) 137*e*. Process for the production of fibrous alumina monohydrate, P (2) 46*b*. Rare-earth arsenides, P (8) 220*j*. Resistor and resistor composition, P (1) 21*h*. Special forms of corundum, P (6) 171*d*. Thermofluid vehicles for preparation of ceramic coatings, P (6) 155*i*. Treatment of zinc sulfide phosphors, P (3) 79*a*. Vitreous enamel frit, P (3) 65*h*. Vitreous enamels, P (2) 38*e*.
Duquesnoy, A., and Marion, F. Electrical conductivity variations of CoO, NiO, and MnO as a function of the equilibrium partial pressure of oxygen at high temperatures, (9) 247*b*.
Duran, J. C., and Bakker, M. A. M. Vacuum-proof joints by fusion of silvered chromium-iron disks to glass, P (3) 79*b*.
Duran, P. L. Machine for sorting articles of different grades, P (10) 289*f*.
Durie, N. D. See Clendenning, T. G.
Durieux, M. E. See Cowley, C. H.
Duriez, M. J. J., and Lezy, R. E. A. Acceleration of the hardening of cements by introduction of crystallization nuclei, P (3) 64*k*.
Durig, J. R., Lord, R. C., Gardner, W. J., and Johnston, L. H. Infrared transmittance and reflectance of beryllium oxide, (4) 114*h*.
Duro-Test Corp. Constant lumen maintenance lamp, P (9) 241*g*. Method of producing crystal pattern and product, P (3) 70*i*. Multiple arc fluorescent lamp, P (7) 186*e*.
Durup, J., and Platzman, R. L. Role of the Auger effect in the displacement of atoms in solids by ionizing radiation, (11) 318*j*.
Dustex Corp. Dust collector, P (3) 83*g*. Dust collector [with continuous filter], P (7) 195*a*.
Dutchess, E. E. See Drost, W.
Dutz, H. See Lehmann, H.
Duval, L. E. Coated lamp, P (10) 271*d*.
Duwell, E. J., and McDonald, W. J. Some factors that affect the resistance of abrasive grits to wear, (5) 125*f*.
Duzak, E. J. See Clarke, R. G.
Dvorkind, M. M., Korshunov, V. S., Petrov, G. A., and Vydrina, Zh. A. Service conditions and nature of wear of refractories in a 15-ton rotary steel melting furnace, (7) 188*d*.
Dwight, K. See Menyuk, N.
Dyer, C. E. See McTaggart, G. D.
Dyer, H. B. See Custers, J. F. H.
Dynamics Corp. of America. Means for controlling the effective resistance of piezoelectric quartz crystals, P (2) 49*h*.
Dyurovich, S. Statistical model for the crystalline structure of mullite, (3) 89*a*.
Dzierzanowski, F. J. See Haden, W. L., Jr.
Dzierzanowski, F. J., and Haden, W. L., Jr. Method for making synthetic zeolitic material, P (10) 289*f*.
Dzyaloshinsky, I. Thermodynamic theory of "weak" ferromagnetism of antiferromagnetics, (11) 310*g*.

Eagle-Picher Co. Composite [glass] coated muffler and method of making it, P (9) 239*c*. Method and apparatus for molding, P (3) 80*d*. Porcelain enameling frit, P (10) 269*g*. Process for preparation of cadmium sulfide crystals, P (8) 226*a*. Process of preparing a ferrous surface for one-fire porcelain enameling, P (6) 155*h*.
Eardley, R. P. See Bennett, H.
Eargle, F. L. Proposed wage incentive plan for brick delivery, (8) 211*j*.
Earl, W. A., and Brownell, W. E. Composition of an ideal face brick, (3) 71*b*.
Earle, Francis, Laboratories, Inc. See Francis Earle Laboratories, Inc.
Early, R. L. Shape and height detection [photoelectric], P (9) 242*d*.
Eary, R. H. Glass scoring machine, P (2) 42*i*.
Easterling, K. E. High temperature resistance strain gages, (6) 159*f*.
Eastman, D. B. Method of forming gastight seal between vessel wall and refractory lining of a synthesis gas generator, P (1) 16*i*.
Eastman Kodak Co. Lenses cleaning apparatus, P (6) 157*f*. Protection and cleaning of lenses, P (6) 158*e*.
Eberhard, E. Miscibility and structural properties of synthetic cordierite in the systems (MnO, FeO, MgO, CaO)–Al_2O_3–SiO_2–H_2O at relatively low temperatures and low pressures, (4) 116*a*.
Eberspaecher, O. Substitution of antimony in barium titanate, (6) 165*i*.
Ebert, G. Dielectric resonance and dispersion phenomena in the system γ-alumina–water, (2) 56*e*.
Ebert, H., Ritter, F., Harmsen, E., and Grapentin, K. Process and apparatus for the manufacture of anhydrous magnesium chloride which is substantially free from magnesium oxide, P (3) 84*i*.
Eccles, J. See Busby, T. S.
Eck, J. E. See Cain, F. M., Jr.
Eckart, D. W. See Giardini, A. A.; Kohn, J. A.
Eckert, J. S. Saddles, P (3) 74*j*. Support plate, P (3) 76*a*.
Eckert, O. Ferrite containing neodymium, P (3) 77*a*.
Eckman, J. P., and Laudelout, H. Chemical stability of hydrogen-montmorillonite suspensions, (3) 86*a*.
Eckstein, J., and Jindra, J. Some new developments in techniques of growing crystals, B (9) 262*j*.
Eckstein, J., and Wachtl, Z. Growing single crystals from a molten mass with a linear isotherm, P (2) 60*b*.
Eclipse Fuel Engineering Co. Burner construction [radiant], P (3) 82*b*. Radiant gas burner, P (1) 25*c*.
Edgar, K. See Fairbrother, F.
Edgerly, C. R., Summers, W. J., and Gorski, A. Tray-loading apparatus, P (2) 51*i*.
Edgington, J. H. Surface treatment of molds, (4) 99*a*. See Baker, J.
Edmonds, B. P., Dahms, J. B., and Helvenston, E. P. Recovery of potassium chloride, P (10) 290*e*.
Ednell, D. F. Method for the production of refractory containers, P (3) 74*e*. Tightening device for hot tops, P (9) 245*g*.
Edwards, W. R., and Schwartzwalder, K. Method for making silicon nitride-bonded silicon carbide semiconductors and resulting bodies and articles using them, P (1) 16*c*.
Eeles, W. T., and Sutcliffe, J. M. Further studies of small angle X-ray scattering by pile-irradiated graphite, B (8) 233*j*.
E.F.S.I. Corrosion-inhibiting silicate cements, P (3) 65*a*.
Egizi, E. A. See De Woody, C. M.
Egleson, G. C. See Christensen, V. J.
Eguchi, I. See Soda, T.
Eguchi, K. See Mori, Y.
Ehrenreich, H. See Olechma, D. J.
Ehrlich, P., and Schmitt, R. Investigations on the systems LiCl–$TiCl_2$, RbCl–$TiCl_2$, and CsCl–$TiCl_2$, (4) 115*i*.
Eichelberger, J. F., Hudgens, C. R., Jones, L. V., Pish, G., Rhinehammer, T. B., Tucker, P. A., and Wittenberg, L. J. Phase equilibria for the ternary fused-salt system NaF–BeF_2–UF_4, (8) 229*e*.
Eidule, O. N. See Ivensen, V. A.
Eigen, H. Thermal physics of a rotary cement kiln with a gross heat consumption of 650 kcal/kg of clinker, (7) 182*h*.
Eiloart, T. M. B. Porous materials in the chemical industry, (3) 83*a*.
Eipeltauer, E. Topochemical hydration processe in the setting of gypsum, (5) 126*i*.
Eirich, G. See Eirich, W.
Eirich, W., and Eirich, G. Lime mortar, P (4) 96*g*.
Eitel-McCullough, Inc. Apparatus for applying a metallizing coating to ceramic parts, P (7) 193*h*. Ceramic metallizing mixture and method of compounding it, P (9) 239*b*.
Eklund, W. M. See Reynolds, C. B.
Eland, A. J. Etch pits on a zinc sulfide crystal, (5) 143*a*.
Elbeih, I. I. M., and Garba, G. G. Determination of zirconium with hafnium in zircon via paper chromatographic separation, (5) 142*f*.
Elder, J. T., Bieling, C. R., and Blakeslee, A. E. Photoconductive zinc oxide pigment, P (2) 55*d*.
Elderfield, R. N. See Boddye, E. T.
Elders, D. S. See Gerhold, R. A.
Eldred, J. W., and Legg, J. B. Decorating machine, P (10) 271*e*.
Eldred Co. Decorating machine, P (10) 271*e*.
Electric & Musical Industries, Ltd. Alkali metal generators, P (10) 269*a*.
Electro-Refractaire. Manufacture of electrically melted refractory products containing mineral oxides, P (6) 162*g*.
Electro Refractories & Abrasives Corp. Hard abrasive material and method of making, P (1) 1*i*.
Elek, J. W. See Riney, T. D.
Elektrokemisk A.-S. Process for producing electrode paste, P (3) 74*a*.
Elemelt, Ltd. Furnace for melting or refining glass electrically, P (10) 271*j*. Means for making fibers of vitreous material, P (10) 272*g*. Method and apparatus for heating glass preparatory to delivery, P (7) 186*j*.
Elettracarbonium S.p.A. Process of joining carbon bodies, P (2) 46*h*.
Elkington, W. E., Thomas, G., and Washburn, J. Damage produced by moving dislocations in MgO, (9) 255*g*.
Elkins, S. R. See Poulos, N. E.
Ellerbeck, L. D., Shanks, H. R., Sidles, P. H., and Danielson, G. C. Electrical resistivity of cubic sodium tungsten bronze, (3) 86*c*.
Ellert, H. G. See Gladrow, E. M.
Ellerton, H. South Australian building brick manufacture with special reference to the blending of raw materials and their extrusion characteristics, (5) 132*c*.
Ellies, C. Considerations on industrial esthetics in the ceramic industries, B (10) 300*c*. Niderviller pottery, (6) 153*h*.
Ellinger, F. H. See Mulford, R. N. R.
Elliott, J. H. Treating glass sheets, P (8) 211*i*.

Elliott, N. See Scatturin, V.
Elliott, W. L. Ware turning and handling machine, P (5) 134*b*.
Ellis, A. T., and Fourney, M. E. Application of a ruby laser to high-speed photography, (10) 279*f*.
Ellis, B. G., and Mortland, M. M. Comparison of two methods of determining heats of reaction by differential thermal analysis, (6) 167*i*.
Ellis, J. S. See Coble, R. L.
Ellis, R. B. Investigation of techniques and materials for the formation of high temperature (1500°F) inorganic fiber, (8) 214*e*.
Ellis, R. C., Jr. Vitreous phosphorus, (7) 201*f*.
Ellison, M. See Hunt, R.
Elmer, T. H. Opal 96% silica glass and method of production, P (2) 42*i*.
Elmer, T. H., and Nordberg, M. E. Thirsty glass, (6) 156*i*.
Elmes, A. W., and Docherty, A. C. Some uses of refractories in chemical processes, (3) 73*c*.
Elofsson, A. Method for the complexometric titration of alumina, (1) 28*g*.
Elston, J. W., Jr. See Wilson, C. P., Jr.
Eltysheva, A. A. See Tseitlin, L. A.
Elving, P. J. See Kolthoff, I. M.
Elyard, C. A. See Rawson, H.
Elyard, C. A., Gibbs, B. M., and Rawson, H. Symposium on nuclear ceramics: Effect on uranium oxide of controlling grain growth during sintering, (11) 307*d*.
Emblem, H. G., and Fothergill, E. W. Molds utilizing acid hydrolyzed isopropyl silicates as binders [for refractory material], P (4) 103*b*.
Emblem, H. G., Mountford, N. D. G., and Morley, C. W. Aqueous coating compositions for production of shell molds and process for preparing them, P (1) 15*g*.
Emeis, R. See Herlet, A.
Emerson, P. J. See Fuller, A. G.
Emery, L. D., Jr. Deposition and measurement of layer thickness, P (3) 77*f*.
Emhart Mfg. Co. Glassware inspection apparatus, P (8) 210*h*.
Emrich, E. W. Tremolitic talc—its modern role in ceramics, (2) 47*g*.
Emslie, A. G., and Strong, P. F. Passive temperature control in radiation environments, B (3) 93*d*.
Enders, A., Seirig, A. K., and Strunck, H. J. Dressing device for grinding spectacle glasses, P (1) 11*e*.
Enemark, A. F. Low pressure atomizer nozzle for oil burners, P (6) 169*e*.
Engel, C. G. See Chodos, A. A.
Engelbrecht, H. Modern oil-firing apparatus for heating continuous and periodic kilns and for dryers, (2) 53*f*, (10) 287*j*.
Engelhard Industries, Inc. Composite material of platinum alloy and glass, P (3) 77*d*. Composite material and thermocouple made therefrom, P (1) 24*a*. Furnace, P (5) 140*c*. Material for handling molten glass, P (3) 69*e*. Method of making an electrical resistance device, P (7) 183*j*. Spinnerette, P (1) 12*e*. Thermocouple, P (3) 81*g*, P (11) 314*a*.
Engelhardt, H., Block, S., and Schlenz, H. Gas analyzer, P (2) 53*c*.
Engineering Supervision Co. Multi-anvil force compensating pressure apparatus, P (1) 23*d*.
English Clays Lovering Pochin & Co., Ltd. Removal of impurities from fluxing materials for manufacture of ceramic or glass articles, P (2) 56*a*.
English Electric Co., Ltd. Electrically conductive glasses, P (9) 241*h*.
English Electric Valve Co., Ltd. Television camera tubes, P (3) 70*e*.
Enk, E., Jacob, H., and Nickl, J. Process for manufacturing indium phosphide and gallium arsenide of high purity, P (6) 166*c*.
Enomoto, S., Furuta, T., Mori, C., and Ishihara, Y. Industrial applications of beta-ray excited X rays (VIII) determination of sulfur in heavy oil by tritium bremsstrahlung absorption method, (4) 108*f*.
Enomoto, S., Mori, C., and Furuta, T. Industrial applications of beta-ray excited X rays (IX) rapid determination of the ash content of coal with the absorption method using tritium bremsstrahlung, (4) 108*g*.
Enz, U. Permeability, crystalline anisotropy, and magnetostriction of polycrystalline manganese-zinc-ferrous ferrite, (9) 247*j*. See Lotgering, F. K.
Epel'baum, M. B., and Gorbatyi, Yu. E. Internal strains and changes in the mechanical strength of glass, (1) 7*c*. Method of preparing glass samples for microhardness measurements, (6) 156*d*.
Epner, M., and Peckner, D. Heat treatable, machinable carbides, (6) 159*i*.
Eppler, R. A. Glass formation and recrystallization in the lithium metasilicate region of the system Li_2O–Al_2O_3–SiO_2, (4) 98*g*.
Eppler, W. See Albrecht, F.
Epstein, A. S. See Hill, D. E.
Epstein, A. S., and Kulifay, S. M. Thermoelectricity, P (10) 283*h*.
Erard, E. L. Apparatus for manufacturing mineral wool fibers, P (2) 41*c*.
Erben, E. See Lesser, R.
Erd, R. C., McAllister, J. F., and Vlisidis, A. C. Nobleite, another new hydrous calcium borate from the Death Valley region, Calif., (4) 110*c*.
Erdmann-Jesnitzer, F. See Petzold, A.
Erhardt, J. E., Jr. See Baughman, G. M.
Erickson, J. R. Cut-off wheel, P (4) 95*g*.
Erie Resistor Corp. Thermoelectric ceramic, P (5) 137*c*.
Ermakov, D. S. See Maleev, E. N.
Ern, V. Differential thermal analysis of a cubic modification of $BaTiO_3$, (8) 219*d*.
Ernst, W. G. See Barnes, H. L.
Ernst Leitz G.m.b.H. Means for measuring the optical thickness and/or absorption of small specimens, P (3) 81*e*. Optical borate glass, P (7) 186*e*. Optical crown glasses, P (11) 305*c*.
Erwin, L. R. Why we use "powdered ground coats" for water heater tanks, (4) 97*f*.
Esch, C. B. Tile ring, P (2) 44*c*.
Escher Wyss G.m.b.H. Electrostatic spraying of atomized material, P (1) 5*a*.
Eshaya, A. M. High-temperature [graphite-Rh] thermocouple, P (6) 168*i*. See Salzano, F. J.
Espe, W. Materials for High Vacuum Technique (Vol. III) Accessory Materials, B (2) 61*d*.
Espinosa, G. P. Crystal chemical study of the rare earth iron garnets, (9) 255*d*.
Esselborn, R. See Brauer, G.
Essen, U. v., and Klemm, W. Rare earth nitrides (cerium nitrides), (4) 119*b*.
Esso Research and Engineering Co. Chromatographic analysis, P (1) 31*a*. Temperature measuring instrument, P (11) 313*j*.
Estabrooks, D. A. See Campaigne, R. N.
Estrada, D. A.-. See Alvarez-Estrada, D.
Ettinghausen, R. Selected antique glass in the Freer collection (abstract), B (11) 321*g*.
Ettre, K. See Spurck, R. F.
Etzel, H. W., Gandy, H. W., and Ginther, R. J. Stimulated emission of infrared radiation from ytterbium activated silicate glass, (5) 130*a*.
Etzel, K. See Schaefer, H.
Eutectic Welding Alloys Corp. Coated welding rod, P (7) 183*h*.
Evander, H. S. Transistor's leads are its hermetic seals, (2) 48*c*.
Evans, C. C. See Gordon, J. E.
Evans, D. G. See Armstrong, W. M.
Evans, D. N., Blaine, R. L., and Workaman, P. Comparison of chemical resistance of supersulfate and special purpose cements, B (5) 149*f*.
Evans, J. L. Symposium on nuclear ceramics: Method for the determination of the bulk densities of granular materials, (11) 308*c*.
Evans, M. D. See Gabrysh, A. F.
Evans, R. B., III, Watson, G. M., and Truitt, J. Interdiffusion of gases in a low permeability graphite at uniform pressure, (1) 28*a*.
Evans, R. W., and Morris, J. M. Method and apparatus for moving pulverulent materials [vibrating trough], P (2) 51*d*.
Evans Research & Development Corp. Apparatus for use in determining particle size and distribution of particle size, P (10) 287*a*.
Even, U. See Oppenheim, U. P.
Everest, D. A., Mercer, R. A., Miller, R. P., and Milward, G. L. Chemical nature of sodium beryllate solutions, (7) 198*d*.
Everett, D. H. Thermodynamics of frost damage to porous solids, (8) 212*b*.
Evstrop'ev, K. S., and Ivanov, A. O. Physicochemical properties of germanium glasses, B (11) 321*a*.
Evtushenko, T. P. See Zil'bershtein, Kh. I.
Ewald, H. Spectrograph [with ionic separation], P (3) 81*g*.
Ewing, C. T. See Walker, B. E., Jr.
Ewing, C. T., Walker, B. E., Jr., Spann, J. R., Steinkuller, E. W., and Miller, R. R. Thermal conductivity of refractory materials, (1) 15*b*.
Exelby, V. H. See Budd, S. M.
Exley, D. Flame spectrophotometry, P (5) 139*f*.
Eynard, G. Control of manufacture in a ceramic sanitary ware plant, (10) 278*d*.
Eyring, H. See Gabrysh, A. F.
Eyring, L., and Baenziger, N. C. Structure and related properties of oxides of praseodymium, B (9) 260*e*.
Ezhik, I. I. Infrared luminescence of F centers in X-rayed fluorite crystals, (5) 135*d*.

Fabian, R. J. Engineer's guide to electronic materials, (4) 104*f*. Plated cermet coatings fight heat, wear, (6) 155*e*. Wear resistant materials and coatings—M/DE Manual No. 201, (6) 155*c*. What's new in coatings and finishes—M/DE Special Report No. 205, (9) 238*j*. See Seabright, L. H.
Fabricacion de Maquinas, S. A. Decorating apparatus for ceramic flatware, P (2) 47*c*.
Facaoaru, I. Study of mortar segregation by injection of ^{60}Co isotope, (10) 268*a*.
Faeth, P. A. See Rao, C. N. R.
Fagerholt, G. R. Method of grinding portland cement using a phenolic compound as a grinding aid, P (4) 96*i*.
Fahey, D. See Podmore, H. L.
Fahey, J. R. See McMahon, J. F., Jr.
Fahey, J. R., and Schnable, G. L. Miniature desiccator and production of units thereof, P (2) 50*e*.
Fahlstrom, A. H. H., Lundberg, H. L., and Holmberg, G. I. Rock grinding system, P (10) 290*b*.
Fahrig, R. H., and Medcalf, W. E. Process for preparation of cadmium sulfide crystals, P (8) 226*a*.
Fairbrother, F., Ahmed, N., Edgar, K., and Thompson, A. Complexes of niobium and tantalum hydroxides with dials, (10) 291*a*.
Falk, N. O. See Roetter, R. P.
Falladown, A. E. Symposium on economics in the enamel shop: Steel sheets, (2) 37*f*.
Fang, J. H. Comment on "Comment on Vegard's law . . . ," (7) 198*e*.
Fang, P. See Bertaut, F.
Farafonov, M. M. See Kargin, V. A.
Farbenfabriken Bayer Akt.-Ges. Building material compositions for the manufacture of water repellent masonry, P (10) 268*c*. Crystalline solid solutions with silicon dioxide structures as host components, P (9) 246*c*. Process for producing ferrites, P (7) 194*d*. Process for the production of isometric ferromagnetic gamma ferric oxide, P (7) 194*f*. Process for the production of sodium zeolite A, P (3) 84*j*.
Farenkopf, R. Hygrometer, P (2) 53*d*.
Faria, J. Lima-de-. See Lima-de-Faria, J.
Faria, S., and Goldberg, P. Process for producing electroluminescent phosphors, P (5) 137*c*.
Farkas, E. See Adams, A. B.
Farley, P. R. Symposium on economics in the enamel shop: Controlling and reducing cost in the enamel shop, (2) 37*f*.
Farmer, R. D., and Carnes, K. C. Recuperative firing systems, (2) 53*h*.
Farrah, G. H. Electrochemical determination of fluorides, P (2) 60*a*.
Farrel-Birmingham Co., Inc. Multiple injection molding apparatus, P (11) 312*a*.
Farrior, G. M. See Tyrrell, M. E.
Faul, J. C. Thermocouple performance in gas streams, (4) 108*a*.
Faulstich, M. See Geffcken, W.
Faust, J. W., Jr. See John, H. F.
Favre, J. A. Chromatographic analyzer [with dual columns], P (10) 287*b*.
Fawcett, F. A. See Danyluke, O.
Fawcett, J. A. Metallizing of glass machinery and molds, (4) 98*e*.
Fawcett, W. See Bolton, H. C.
Federal Screw Works. Diamond grinding wheel and compositions therefor, P (8) 203*h*.
Fedorov, N. F. See Toropov, N. A.
Feduska, W. See Lane, D. H.
Fedyushin, B. T. See Ryzhkov, V. A.
Fehn, H. Hardening of mica deposited by electrophoresis, P (4) 110*i*.
Feibelman, W. A. See Kanter, H.
Feichter, H. R., and Abernethy, I. A. Ceramic tile, P (8) 218*c*.
Feid, J. T. See Slayter, G.
Feigley, D. A., Jr., and Hawkins, W. M. Flexible asbestos-cement products, P (2) 36*b*.
Fein, A. E. See Gourary, B. S.
Feld, I. L., and Clemmons, B. H. Process for wet grinding solids to extreme fineness, P (5) 138*f*.
Felder, J. L. Method of producing vitreous clay products, P (1) 13*d*.
Feldkamp, J. G. See Cliff, G. J.
Feldman, C. L., Fields, A. C., and Bergin, J. A. Thermocouple reference junction, P (9) 253*a*.
Feldman, M. H., and Hosticka, H. E. Apparatus and process for forming high density compacts, P (9) 250*f*.
Feldman, O. Symposium on control of the quality of glassware: Statistical quality control in the container industry—its effect on production efficiency and customer goodwill, (9) 241*j*.
Felt, R. M. See Marriott, J. G.
Felten, E. J., Juenke, E. F., and Bartram, S. F. System Cr_2O_3–UO_2–O_2, (7) 201*i*.
Feltzin, J., and Schaeffler, O. S. Research on and development of high-temperature stable inorganic resins and elastomers, (8) 229*b*.
Fennell, A. A. Burner safety control, P (5) 140*g*.
Fenton, W. M. Present and prospective uses of lithia in porcelain enamels, B (11) 322*g*.
Fentzke, A. D. See Charvat, F. R.
Feofilov, P. P. Phototransfer of an electron in MeF_2:Eu,Sm monocrystals, (5) 145*d*.
Feofilov, P. P., and Tolstoi, M. N. Luminescence kinetics of divalent samarium in single crystals of strontium and barium fluorides, (6) 164*j*.
Ferguson, G. A., Jr., and Hass, M. Magnetic structure and vacancy distribution in γ-Fe_2O_3 by neutron diffraction, (3) 87*d*.
Ferguson, L. C., Mathews, A. W., and Hardinge, H. Method and means for segregating and recombining feed for grinding mill, P (6) 171*a*.
Ferrandis, V. A. See Aleixandre Ferrandis, V.
Ferranti, Ltd. Viscometers, P (3) 80*b*.
Ferrari, A. Concentration apparatus for quantitative analysis of a substance in a liquid, P (10) 287*c*.
Ferrari, H. M. See Baily, W. E.
Ferris, L. M. See Bradley, M. J.
Ferro Corp. Apparatus for making fibrous glass mats, P (1) 10*f*. Apparatus for shaping pressure-shapable materials, P (10) 284*j*. Composition for and method of applying ceramic color, P (9) 239*d*. Glass fiber size comprising an aqueous dispersion of a film forming polymer, a coupling agent, and polyvinyl pyrrolidone, P (7) 186*d*. Sanitary ware setter [with perforations], P (11) 308*j*.
Fetter, H., and Vela, D. L. Differential thermal analysis, (2) 52*e*.
Feuer, I. Device for rupturing glass [pipe] seals, P (1) 11*d*, P (8) 210*c*.
Feuerstein, S., and Parker, E. R. Effect of grain boundaries on the mechanical properties of ionic crystals, (8) 227*d*.
Feulner, H. See Buehler, G.
Fiedler, A. See Naeser, G.
Fiedler, W. S. Construction of an apparatus or drawing vitreous fibers, P (4) 99*b*.
Fields, A. C. See Feldman, C. L.
Filarska, B. Glass details in ancient architecture and furniture (abstract), B (11) 321*d*.
Filonenko, N. E., Lavrov, I. V., Andreeva, O. V., and Pevzner, R. L. Aluminous spinel AlO·Al_2O_3, (4) 112*a*.
Fine, M. E. See Greener, E. H.

Finnigan, G. Selection of diamond cutoff wheels, (9) 235*j*.
Finzer, G. F. Plant organization for quality control, (2) 60*d*.
Firestone, R. F. See Jones, A. L.
Firing, P. C. Apparatus for pulverizing material, P (2) 51*g*.
Firnhaber, M. S. Apparatus for manufacturing mineral wool fibers, etc., P (2) 41*d*. Rotors for use in apparatus for manufacturing mineral wool, P (1) 12*e*.
Firnhaber, M. S., Miller, J. R., and Kovach, M. J. Apparatus for manufacturing mineral wool fibers, P (1) 10*f*.
Fischer, H. See Blau, H. H., Jr.
Fischer, H. G., & Co. Spray gun for electrostatic coating, P (2) 38*e*.
Fischer, J. L. See Runyan, W. R.
Fischer, P. See Muschelknautz, E.
Fischer, W., and Abendroth, H. J. Phase diagram of the system NaCl–Na_2O, (4) 117*g*.
Fischer, W. A. Chromium oxide refractories, P (4) 102*d*.
Fischer-Colbrie, E. See Grinten, W. J. van der.
Fishburn, H. W. See Miller, J. A.
Fisher, D. J. Temperature control spindle stage, (6) 168*d*.
Fisher, G. F. Method and apparatus for drilling minute holes in small ceramic wafers, P (5) 138*b*.
Fisher Scientific Co. Apparatus for gas analysis, P (10) 286*i*.
Fishman, M. J. See Wahlberg, J. S.
Fishwick, J. H. Color of ceramics based on spodumene, (1) 17*h*. Manganese ore as a pigment in structural clay products, (1) 12*i*. Manufacture of foamed ceramics based on petalite and beta spodumene, (4) 101*a*.
Fitch, F. T., Sanchez, M. G., and Vanik, M. C. Hydrous oxide sols, P (9) 246*e*.
Fitzgerald, D. J. See Greener, E. H.
Fitzgerald, E. R. Mechanical resonance dispersion in quartz at audio frequencies, (3) 87*e*.
Fitzpatrick, R. L. See Kurnick, S. W.
Flammer Seifenwerke K.G. Process for the treatment of asbestos, P (3) 74*d*.
Flanagan, C. E. See Stephenson, C. V.
Fleeman, P. J. See Sauer, J. M.
Fleischer, J. Development of fused-cast glass tank blocks, (7) 187*h*.
Fleischer, K. Discussion of "'Pathology' in technology—concept and program as a section of applied science," (1) 8*f*.
Fleischer, R. L., Price, P. B., and Walker, R. M. Method of forming fine holes of near atomic dimensions, (11) 313*f*.
Fleming, J. D. See Morgan, W. L.
Fleming, J. D., Boland, P., and Harris, J. N. Porosity measurements by air displacement, (11) 313*d*.
Flemmert, G. L. Process for the production of hydrogen fluoride, P (8) 226*b*. Process for the production of hydrophilic silicon dioxide, P (1) 26*d*.
Fletcher, A. N. See Pecsok, R. L.
Fletcher, E. See Ward, W.
Fletcher, J. See Baker, J.
Fletcher, K. E. See Midgley, H. G.
Fletcher, W. W., Keir, E. S., Johnson, P. G., and Slingsby, B. Resistance of glass to some industrial detergents and detergent additives, (7) 185*h*.
Flick, F. B. Report of the Committee on Patents, (9) 258*c*.
Flintkote Co. Apparatus for handling particulate material, P (5) 138*g*. Flue covering process, P (9) 253*c*.
Flood, H., and Knapp, W. J. Acid-base equilibria in the system PbO–SiO_2, (4) 111*j*.
Florio, J. V. Retarding field technique for measuring sublimation from dispenser and oxide cathodes, (10) 281*g*.
Floyd, J. R. Effect of composition and crystal size of alumina ceramics on metal-to-ceramic bond strength, (3) 76*d*.
FMC Corp. Injection molding machine, P (1) 23*a*. Method of producing soda ash from crude trona, P (7) 198*a*.
Foerland, T. Acid-base reactions in silicate melts, (1) 26*f*.
Foex, M. See Trombe, F.
Fogelberg, T. Bottle glass industry in Sweden 1870–1920 (I–III), (1) 5*f*. Kosta Glassworks and the origin of the glass industry district of Smaland (I–III), (1) 7*e*. Location and structure of the Swedish handblown glass industry, 1870–1920 (I, II), (7) 184*h*. Swedish window glass industry 1927–1939, (1) 9*g*.
Foglia, S. See Aubert, M.
Fok, M. V. See Vinokurov, L. A.
Folk, F. M. Tile measuring machine, P (11) 312*f*.
Folk, R. L. Petrography and origin of the Silurian Rochester and McKenzie shales, Morgan County, W. Va., (3) 82*i*.
Folkman, R. L. See Spendelow, H. R., Jr.
Folweiler, R. C. See Gannon, R. E.
Fomenko, V. S. See Paderno, Yu. B.; Samsonov, G. V.
Fonderie de Precision. Core elements, P (10) 277*a*.
Foos, R. A. See Stambaugh, E. P.
Foos, R. A., and Ripley, R. L. Process for producing fluoride-free columbium [niobium] or tantalum pentoxide, P (5) 141*a*.
Foos, R. A., and Stambaugh, E. P. Process for preparing chromium oxide, P (3) 84*f*. Uranium oxide and thorium oxide recovery, P (10) 290*d*.
Ford, C. E., Bushong, R. M., and Stroup, R. C. New graphites—versatile engineering materials, (6) 160*b*.
Ford, H. T. See Boyer, E. W.
Ford, J. G. Magnetic stabilization-wound cores, P (5) 136*j*.
Ford, W. F. See Gadalla, A. M. M.
Ford Motor Co. Glass rolling apparatus, P (1) 11*c*. Resistor compositions and spark plugs having integral resistors, P (8) 221*a*. Vertical washer for flat glass, P (10) 273*c*.
Forest, J. Research on the lumping of cements, (1) 3*c*.
Forest, J., and Demoulian, E. Determination of alkalis with a flame photometer and filters, (8) 222*g*.
Forlano, R. J., and Andrews, A. I. Soluble constituents leached from titanium enamel frit, (6) 155*h*.
Forman, B. G. Means and method for forming electrical components, P (8) 220*a*.
Forne, R. M. See Mallol Forne, R.
Fornet, A. W. Dryer for removing moisture from analytical samples, P (8) 223*g*.
Forrat, F. See Bertaut, F.
Forshaw, I. P. Alumina for the ceramic industry, (2) 54*b*.
Forslund, H. B. See Hoehn, W. G.
Forte-Fairbairn, Inc. Method and apparatus for measuring capacitivity of materials, P (9) 252*h*.
Forten, J. See Johnson, E. R.
Forth, R. D. Status report on direct-on cover coat porcelain enameling, (7) 183*b*.
Fortin, E. G. See Sacco, J. J., Jr.
Fortuna-Werke Spezialmaschinenfabrik Akt.-Ges. Automatic balancing arrangement [static and dynamic] for grinding wheels, P (10) 265*f*.
Forty, A. J. Chemical decomposition of crystals of lead iodide by irradiation in an electron beam, (10) 290*g*.
Forwalt, H. J., Helbig, W. A., and Scheffler, G. H. Activated carbons for liquid-phase absorption, (11) 314*g*.
Foster, D. K. Apparatus for supporting [glass] sheets, P (2) 41*i*.
Foster, R. A. Detector for gas chromatography, P (8) 223*f*.
Foster, W. R. See Chapman, A. T., Jr.; Gentile, A. L.
Fothergill, E. W. See Emblem, H. G.
Foulon, A. Advances in the cementing of glasses, (1) 5*d*. Ceramic tile in industry, (8) 217*f*.
Fourney, M. E. See Ellis, A. T.
Fournier, R. O. See Morey, G. W.
Fournier, R. O., and Rowe, J. J. Solubility of cristobalite along the three-phase curve gas plus liquid plus cristobalite, (7) 200*i*.
Fouse, F. Z., and Kidwell, J. F. Method and means for inspecting containers, P (4) 100*e*.
Fowler, R. D. See Grison, E.
Fox, H. A. Fibrous mat and method of manufacture, P (7) 186*a*.
Fox, J. N. See Parker, W. S.
Fox, R. D. Slag-lined furnace tapping pots, P (3) 75*b*.
Foxboro Co. Split flow gas analysis detector, P (8) 224*b*.
Fraade, D. J. Measuring moisture in gases, (8) 223*e*. Measuring moisture in liquids, (7) 195*d*. Measuring moisture in solids, (6) 168*b*.
Fraas, F. Electrostatic separation of granular materials, (8) 221*e*.
Fracis, J. B. Fabricating a 3.5-in. ferrite sphere, (6) 164*b*.
Frackiewicz, J. See Budd, S. M.
Frame, J. W. See Rahn, H. N.
Frame, J. W., Whiteley, R. L., and Blickwede, D. J. Fundamentals of drawability of sheet steel for porcelain enameling, (4) 97*h*.
Francais, J., Bauer, H., and Vayssiere, P. Refractories used in the OLP process applied to high-phosphorus iron, (6) 161*i*.
Francis, R. Development of pyrolytic refractory materials for solid-fuel rocket motor applications, (8) 212*j*.
Francis Earle Laboratories, Inc. Nacreous material from titanium dioxide, P (4) 111*d*.
Frank, J. M., Boyer, N. E., and Crookston, J. A. Method of making refractory brick, P (11) 308*g*.
Frank, L. See Barr, H. N.
Frank, R. See Weiss, A.
Frank, R. C., Swets, D. E., and Lee, R. W. Diffusion of neon isotopes in fused quartz, (4) 113*j*.
Franke, E. A. Determination of the internal compressive strength of hollow glasses, (1) 6*g*. Determination of wall thickness and glass distribution in hollow glasses, (1) 6*h*.
Frankert, O. P. Tube mill trunnion, P (10) 285*e*.
Frank-Kamenetskii, V. A. Crystallochemical classification of simple and interstratified clay minerals, (11) 320*e*.
Frank-Kamenetskii, V. A., and Kamentsev, I. E. X-ray study of synthetic quartz, B (9) 263*g*.
Frankl, D. R. Electroluminescence of ZnS single crystals with cathode barriers, (2) 57*d*. Power and efficiency considerations in continuous laser operation, (10) 281*h*.
Franklin, R. W. Properties of insulating anodic oxide films, (9) 248*d*.
Franks, P. C. See Swineford, A.
Frantz, J. F. Design for fluidization (I, II), (1) 22*j*; (III), (2) 50*i*.
Franz, W. See Brendel, O.
Fraser, A. R. See Griggs, J. O.
Fraser, H. D. Press sealing process and apparatus, P (5) 131*e*.
Frazier, H. D., and Richey, P. W. Single station fusion machine for making semiconductor device, P (7) 194*c*.
Frederickson, A. F., and Reynolds, R. C., Jr. Geochemical method for determining paleosalinity, B (3) 91*j*.
Frederikse, H. P. R. See Becker, J. H.
Fredrick, R. E., and Fritts, R. W. Thermoelectric devices and thermoelements, P (1) 24*b*.
Fredriksen, O. See Torkar, K.
Free, J. L. Apparatus and [electrostatic] method for applying reflective coatings on unmasked portion of lamp envelope, P (10) 271*a*.
Free, J. M., Moffat, M. E. B., and Walker, G. B. Dielectric properties of titania ceramics at microwave frequencies, (10) 280*e*.
Freedman, B., and Mestdagh, J. J. Water sensitive molds and cores of fast collapsibility, P (1) 17*e*.
Freedman, J. F., and Robertson, W. D. Electrical resistivity of liquid sodium, liquid lithium, and dilute liquid sodium solutions, (2) 57*c*.
Freeman, D. C., Jr., and Sawdye, J. A. Method and apparatus for thermally working minerals and mineral-like materials, P (9) 254*a*.
Freeman, P. I. See Benson, G. C.
Freeman-Goodridge, Ltd. Method and apparatus for measurement of temperature, P (9) 252*g*.
Frei, E. H., Schieber, M., and Shtrikman, S. Ferrite material containing fluorine, P (9) 249*a*.
French, B. T., Nakaji, E. M., and Schneider, S. Method of making thin layer semiconductor devices, P (7) 193*j*.
Freyhold, H. V. Manufacture of water resistant laminates and silicate adhesive therefor, P (9) 246*f*.
Friauf, R. J. Correlation effects for diffusion in ionic crystals, B (9) 261*e*.
Fricke, H. See Gattow, G.
Frickert, P. J. Method of and apparatus for forming strands of filaments, P (4) 100*c*. Method and apparatus for processing heat-softenable materials, P (1) 11*i*. Method of producing a bulk strand product integrated at spaced zones, P (2) 42*d*.
Friedberg, A. L. See Bergeron, C. G.
Friedel, J. See Leman, G.
Friedman, G. E., and Nagy, A. W. Iron sapphire maser with no magnetic field, (7) 191*e*.
Friedman, H. A. See Thoma, R. E.
Friedman, R. Mobile standards laboratory, (9) 251*j*.
Friese, G. Process for producing hydraulic limes from oil shale, P (10) 290*b*.
Frieser, R. G., and Jordan, E. L. Boron nitride coatings and diffusion of boron into semiconductive wafers, (2) 36*i*.
Frieser, R. G., and Scardaville, P. A. Gold colored metallic pigments, P (3) 83*h*.
Frigerio, G. See Colombo, R.
Frikell, G. Manufacture of vitreous silica ware, (7) 184*i*.
Frilette, V. J., and Kerr, G. T. Process for making crystalline zeolites, P (4) 111*a*.
Frint, W. R., and Smith, W. D. Method of producing soda ash from crude trona, P (7) 198*a*.
Fripiat, J. J. See Gastuche, M. C.
Fritts, R. W. Development of thermoelectric power generators, (10) 280*e*. See Fredrick, R. E.
Fritts, R. W., and Richards, J. D. Bonding of lead based alloys to silicate based ceramic members, P (6) 165*f*.
Fritzer, H. P. See Torkar, K.
Froberger, C. F. See Blaies, H. O., Jr.
Froemel, J. G., Worden, E. C., et al. Synthetic mica crystal growth program, (1) 19*j*.
Froemel, J. G., Worden, E. C., and Hessinger, P. Synthetic mica crystal growth program, (3) 20*e*.
Frolov, A. P. Machine for continuous spreading of ceramic colors, (7) 190*f*.
Frondel, C. Dana's System of Mineralogy (Vol III) Silica Minerals, B (4) 122*h*.
Frorath, F. C. See Hoppe, R.
Frost, B. R. T. Symposium on nuclear ceramics: Irradiation behavior of monocarbide fuels, (11) 317*i*.
Frost, P. D. Extrusion lubrication, P (2) 42*d*.
Fruehauf, K., Burk, W., and Hofmann, U. Influence of exchangeable cations on the rheological properties and particle size distribution of kaolinite, (3) 87*e*.
Fruehauf, K., and Hofmann, U. Kaolinite and montmorillonite with exchangeable H ions, (4) 115*d*.
Fry, W. L., and Strzala, K. A. Gaging apparatus [for bottles], P (5) 130*i*.
Fry, W. L., and Uhlig, A. F. Glass container inspecting apparatus, P (11) 304*i*.
Fryer, H. C. See Crary, J. F.
Frysinger, G. R. Cation exchange behavior of vermiculite-biotite mixtures, B (3) 91*i*.
Fuchs, E. See Pfisterer, H.
Fuchs, R. Theory of the beta band in alkali halide crystals, (4) 121*h*.
Fuentes Guerra, R. Califal ceramics from Spain, (5) 125*j*.
Fuhr, W. See Schaefer, H.
Fuhrman, N., Hower, L. D., Jr., and Holden, R. B. Low-temperature sintering of uranium dioxide, (5) 132*j*.
Fujii, J. See Yamamoto, T.
Fujii, J. M., and Yoshida, T. Impact resistance and hardness of asbestos-cement sheets, (8) 205*a*.
Fujii, M. See Okada, K.

Fujimatsu, S. Effects of admixtures on the prevention of cracks in mortar, (7) 180*c*.
Fujimoto, M. S. See Barkman, A.
Fujioka, I. See Kubo, T.
Fujioka, N. Recent electric furnace steelmaking, (6) 160*e*.
Fujishiro, I. See Hukuo, N.
Fujishiro, S. Thermodynamic properties of transition metal carbides and their periodicity, (6) 175*i*.
Fujita, F. E., and Gonser, U. Small angle scattering of X rays by deuteron-irradiated germanium crystal, (7) 200*f*.
Fujita, S. See Mitsuishi, A.
Fukuda, N. Effect of calcium sulfate on the compound composition of portland cement clinker, (7) 179*b*. Effects of adding calcium sulfate to portland cement raw mix on properties of the resulting cements, (7) 180*a*.
Fukuda, T., Sugiyama, Y., Kobayashi, M., and Katsube, S. Spectral transmittance of optical glasses, (5) 129*h*.
Fukuhara, H. M. Split flowerpot, P (3) 64*c*.
Fuller, A. G., and Collins, H. H. Quality assessment—a graduation method for improved accuracy, (2) 51*c*.
Fuller, A. G., Emerson, P. J., and Rew, R. Sonic testing—a simple nondestructive test for verifying casting quality, (10) 269*h*.
Fuller, C. S. Treatment of gallium arsenide, P (8) 221*a*.
Fuller, C. S., and Whelan, J. M. Treatment of gallium arsenide, P (4) 106*a*.
Fuller, C. S., and Wolfstirn, K. B. Kinetics and equilibria involving copper and oxygen in germanium, B (9) 260*g*.
Fuller Co. Gas-material separator, P (10) 285*e*; [with reverse flush], P (10) 285*e*. Scoop feeder for rotary kiln, P (7) 197*b*.
Fuller's Earth Union, Ltd. Modifying natural silicate clays to produce organophilic substances, P (2) 55*d*.
Fulrath, R. M. Model polyphase ceramic systems and resultant stress systems, B (3) 92*e*. See Pask, J. A.; Rossi, R. C.
Fulton, J. W. See Hoehn, W. G.
Funabashi, W., and Terada, S. Melted media for barrel finishing, (1) 1*i*.
Funderburk, G. R. See Buckman, S. J.
Funk, H. Chemical investigations of silicates (XXVI) calcium silicate hydrates of the composition $CaO \cdot 2SiO_2 \cdot 0.5–2H_2O$ and the synthesis of reyerite (= truscottite), $CaO \cdot 2SiO_2 \cdot 5H_2O$, (4) 112*h*. Two different ways of hydration in the reaction of β-Ca_2SiO_4 with water at 25° to 120°C, B (5) 149*f*.
Funke, V. F., Panov, V. S., and Yudkovskii, S. I. Structure and physical and mechanical properties of TiC-WC-Co alloys, (2) 59*a*.
Funke, V. F., Usol'tseva, L. P., and Kalitin, P. P. Alumina-carbon compositions for cutting metals and alloys, P (2) 33*g*.
Funston, E. S. See Kirkpatrick, W. J.
Furcron, A. S. Kyanite, sillimanite, and andalusite in Georgia, (3) 82*e*.
Furczyk, A. A. Furnace conveyor roll, P (1) 24*i*.
Furnas, T. C., Jr. Diffraction apparatus and method of using it, P (4) 121*h*.
Furukawa, S. See Kumazawa, S.
Furumi, K. See Miyatake, K.
Furuoya, T. See Ishii, Z.
Furuoya, T., and Sasaki, Y. Dislocations in Si single crystals, (6) 172*b*.
Furuta, T. See Enomoto, S.
Fyfe, W. S. Relative stability of talc, anthophyllite, and enstatite, (2) 58*e*. See Weill, D. F.
Fyfe, W. S., and McKay, D. S. Hydroxyl ion catalysis of the crystallization of amorphous silica at 330°C and some observations on the hydrolysis of albite solutions, (7) 199*e*.

Gabor, C. D. See Snyder, R. P.
Gabor, J. D. See Mecham, W. J.
Gabriel, A. Chemical treatment of brick clays, (1) 12*h*.
Gabrysh, A. F., Eyring, H., LeFebre, V., and Evans, M. D. Thermoluminescence and the influence of γ-ray induced defects in single crystal α-Al_2O_3, (5) 147*b*.
Gachkovskii, V. F. Structure of magnesium phthalocyanine adsorbates on MgO, Al_2O_3, ZnO glass and their fluorescence, (5) 130*f*.
Gadalla, A. M. M., Ford, W. F., and White, J. Equilibrium relationships in the system CuO–Cu_2O–SiO_2, (11) 317*b*.
Gadiyar, H. S., and Balachandra, J. Sintering studies on molybdenum coated uranium dioxide particles, (11) 306*g*.
Gadsen, C. P. Anisotropy transformer, (9) 246*g*.
Gaertner, W. W. See Kunkel, B.
Gagin, L. V. See Labino, D.
Gagnon, R. E. See Caroselli, R. F.
Gaines, W. M. See Adams, G. E.
Galakhov, F. Ya. Phase diagrams and their application to the study of glass structure, (7) 185*c*. Study of the alumina region in ternary aluminosilicate systems (II) BeO–Al_2O_3–SiO_2 system; (III) system TiO_2–Al_2O_3–SiO_2, (3) 89*e*. Submicroliquefaction zones in the phase diagrams of silicate systems, (5) 146*d*. See Toropov, N. A.
Galanin, M. D. See Belikova, T. P.
Galdina, N. M., and Deri, A. Production and service of "korvishit" (fused corundum) refractory in Hungary, (7) 188*h*.
Galdina, N. M., Yanovskii, Yu. S., Kuznetsova, N. G., and Babadzhanyan, M. A. New highly resistant electrofused refractory, bakor-33, for glass furnaces, (1) 13*j*.
Galkin, L. N., and Kurbatov, L. N. Influence of oxygen on the photoluminescence of lead sulfide films, (5) 135*b*.
Gallagher, P. K. See MacChesney, J. B.
Gallagher, P. K., Schrey, F., and DiMarcello, F. V. Preparation of semiconducting titanates by chemical methods, (10) 281*b*.
Gallego, M. R. See Rodriguez Gallego, M.
Gallet, G. See Colnot, P.
Gallo, J. Flowerpot, P (5) 126*b*.
Gallup, J. L. Glass marking ink, P (10) 272*b*. Improved strain settings in glass button stems, (2) 39*g*.
Galy, A. Process for the manufacture of refractory materials and resultant product, P (6) 162*d*.
Gamain, C. H. A. Apparatus for producing artificial daylight, P (9) 252*f*.
Gandy, H. W. Cathodoluminescence of strontium oxide, barium-strontium oxide, and magnesium oxide, (4) 112*j*. See Etzel, H. W.
Gangoly, O. C. Indian Terracotta Art, B (10) 299*f*.
Gannon, R. E., Folweiler, R. C., and Vasilos, T. Pyrolytic synthesis of titanium diboride, (11) 306*e*.
Gans, F. F. Heterojunction transistor manufacturing process, P (2) 49*c*.
Garay, E., and Norwood, A. Dental impression compositions, P (7) 182*h*.
Garba, G. G. See Elbeih, I. I. M.
Garber, A. M. Pyrolytic materials for thermal protection systems, (10) 275*i*.
Garcia Verduch, A. Lightweight ceramic materials, (6) 158*j*. Reactions during the firing of clays, B (2) 61*a*. Scientific research in the present and the future of the ceramic industry, (5) 148*c*. Wollastonite ceramic bodies, (6) 163*d*.
Garcia Verduch, A., and Alvarez-Estrada, D. Formation of mullite from sericite and its mixtures with alumina and kaolin, B (4) 123*j*.
Garcia Vicente, J. X rays and ceramics, B (2) 61*b*.
Garcia Vicente, J., and Robredo, J. Cordierite obtained from sepiolite by solid-state reaction, B (4) 123*j*.
Gardner, A. R. Conductive coatings, (6) 155*c*. High speed testing, (3) 80*h*. New designs, new efficiency with superconductivity, (11) 310*c*. Pyrolytic graphite, (1) 25*j*.
Gardner, P. V. Glass collections and a special glass exhibit at the U. S. National Museum (abstract), B (11) 321*d*.
Gardner, W. J. See Durig, J. R.
Gardner, W. M., + Sons (Gloucester), Ltd. Double cone mixing machines, P (10) 285*d*.
Gardon, R. Emission of radiation by transparent materials, B (3) 93*b*.
Garino-Canina, V., and Priqueler, M. Diffusion of protons in SiO_2 + Al_2O_3 glass in an electrical field, (2) 38*h*.
Garner, H. Chinese and Japanese Cloisonné Enamels, B (11) 321*e*.
Garrels, R. M. See Chave, K. E.
Garrels, R. M., Sato, M., Thompson, M. E., and Truesdell, A. H. Glass electrodes sensitive to divalent cations, (9) 240*j*.
Garrett, A. B. (collector). Flash of genius: 17, The discovery of the transistor by W. Shockley, J. Bardeen, and W. Brattain, (9) 247*h*.
Garrett, C. G. B., and Kaiser, W. K. Terbium and cerium activated calcium fluoride optical maser material, P (6) 166*g*.
Garrett, W. G., and Walker, G. F. Cation-exchange capacity of hydrated halloysite and the formation of halloysite-salt complexes, (11) 316*b*. Swelling of some vermiculite-organic complexes in water, B (5) 151*a*.
Garton, A. F., Jr. Fabrication of semiconductor devices, P (3) 77*j*.
Gasiorowski, K. Peculiarities of fuel oils, (2) 53*g*.
Gaskins, F. H. See McKinney, C. D., Jr.
Gaspar Tebar, D. Plasticity of ceramic bodies B (2) 61*b*.
Gasquard, R. E. Refractory ceramic bodies, P (4) 103*c*.
Gastuche, M. C. See De Kimpe, C.
Gastuche, M. C., and Fripiat, J. J. Acid dissolution techniques applied to the determination of the structure of clay and controlled by physical methods, B (4) 124*e*.
Gates, J. E. See Burian, R. J.
Gatos, H. C. Crystalline structure and surface reactivity, (11) 316*d*.
Gatti, A. See Tragert, W. E.
Gattow, G. Enthalpy of formation of SeO_2 and heats of transformation of various Se modifications, (5) 143*i*. See Glemser, O.
Gattow, G., and Fricke, H. New bismuth oxide, Bi_2O_5, (5) 144*h*.
Gattow, G., and Glemser, O. Preparation and properties of manganese(IV) oxides (II) γ- and η-group of MnO_2; (III) ϵ-, β-, and α-group of manganese(IV) oxide, ramsdellite, and the transformations of MnO_2, (3) 88*a*.
Gaudin, A. M. See Ziegler, G. E.
Gaudin, A. M., Spedden, H. R., and Sullivan, J. H. Flotation procedures, P (10) 289*h*.
Gaukhman, E. L. See Shteinberg, Yu. G.
Gaule, G. K., Kedesdy, H. H., and Rouge, L. J. D. Apparatus for pulling single crystals in the form of long flat strips from a melt [by the crucible method], P (10) 284*j*.
Gauthron, M. See Bernard, J. L.
Gautier, A. See Bernard, J. L.
Gavrilova, I. V. Some aspects of the growth of crystals of sorbitol hexaacetate, B (9) 262*j*. See Koldobskaya, M. F.; Kuznetsova, L. I.; Nepomnyashchaya, V. N.
Gay, P. See Lima-de-Faria, J.
Gaynor, J. W., and Vienna, P. C. Glass grinding process employing a nonfoaming oiliness agent, P (3) 69*i*.
Gebauhr, W. See Geilmann, W.
Gee, L. J. Resistance thermometer probe, P (5) 140*a*.
Geesner, C. R. See Barnes, C. R.
Geffcken, W. Optical type glass compositions with high fluorine and titanium content, P (4) 100*a*. Some theoretical remarks about the diffusion processes governing the exchange of charged particles of different mobility, B (11) 320*j*.
Geffcken, W., and Faulstich, M. Optical glass, P (5) 131*c*, P (7) 186*g*. Optical glass free of thorium, P (6) 158*g*.
Gehlen, K. von. Oriented formation of mullite from Al-Si spinel in the transformation series kaolinite → mullite, (3) 72*c*.
Geilmann, W., Spang, A., and Gebauhr, W. Very pure uranium oxides, P (4) 111*g*.
Gelb, T. See Segnit, E. R.
Gel'd, P. V. See Davydov, K. N.
Geldermans, P., and Ban, P. van den. Ferrite bodies for magnet cores with nearly rectangular hysteresis loops, P (4) 105*b*.
Gell, P. A. M. Means for making fibers of vitreous material, P (10) 272*g*.
Gell, P. A. M., and Hann, D. G. Method and apparatus for heating glass preparatory to delivery, P (7) 186*j*.
Geller, S., and Gilleo, M. A. Crystal structure and ferrimagnetism of yttrium iron garnet, $Y_3Fe_5(FeO_4)_3$, (10) 291*j*.
Gelling, W. G. See Bril, A.
Gelsdorf, G., and Mueller-Hesse, H. Compounds with an andalusite structure in the system Al_2O_3–Fe_2O_3–GeO_2, (8) 226*g*.
Gel'tman, A. Z. Equipment for continuous dewatering of tile slips, (7) 194*h*.
Gemmer, E. Fluidized bed coating process for coating with thermosetting materials, P (9) 239*a*.
Gemmi, A. Process of joining carbon bodies, P (2) 46*h*.
Gemsa, J. Electrode for high-pressure electric discharge lamps, P (1) 20*f*.
General Dynamics Corp. Ceramic product and method of making it, P (2) 45*a*. Method for evaporating subliming materials, P (10) 285*a*. Method of treating an alumina ceramic article with lithium borate, P (1) 16*g*. Thermoelectric material, P (5) 137*e*.
General Electric Co. Abradable material, P (1) 15*g*. Apparatus for reshaping cylindrical glass tubes, P (3) 69*a*. Apparatus [stencil] for spraying cathodes, P (1) 10*j*. Basing cement, P (6) 154*i*. Bent end incandescent lamp, P (6) 157*h*. Ceramic material of high dielectric strength containing barium titanate and method of manufacturing, P (1) 20*a*. Ceramic product and method of making it, P (10) 279*a*. Coated electric lamp and method of manufacture, P (3) 69*e*. Coated metallic sheet material and method of making it, P (2) 37*h*. Diamond tool, P (11) 301*f*. Dielectric compositions, P (4) 105*c*. Electric lamp base end structure, P (9) 241*i*. Electric lamp mount making method, P (5) 130*h*. Electrical suspension insulator with improved pin, P (2) 47*e*. Encapsulated thermoelectric elements, P (2) 48*h*. Ferrites, P (6) 166*b*. Forsterite-spinel ceramic bodies, P (2) 49*b*. High density ferrites, P (5) 136*d*. High pressure, high temperature apparatus, P (8) 221*i*. Hydraulic thermostat protector, P (1) 25*a*. Light sources, P (1) 21*d*. Linings for miniature incandescent lamps, etc., P (6) 15"*g*. Magnesia-alumina spinel articles and process of preparing them, P (7) 189*c*. Method and alloy for bonding to nonmetallic refractory members, P (9) 249*g*. Method of bonding [glass fiber tape to silicone rubber material], P (1) 12*b*. Method of making a ceramic-to-metal seal, P (8) 220*e*. Method of making composite bodies, P (11) 311*h*. Method for making electrically conducting films and article, P (10) 283*f*. Method of making high purity substantially spherical discrete particles of beryllium hydroxide or oxide, P (11) 308*g*. Method of making a piezoelectric device, P (2) 49*f*. Method of making silicon carbide, P (8) 216*e*. Method for the preparation of alumina fibers, P (10) 277*g*. Method of preparing silicon nitride foam material, P (8) 216*f*. Method for production of etched diamond, P (7) 177*g*. Multilayer film heaters in strip form, P (9) 249*b*. Plural reaction chamber press for high pressures, P (5) 138*e*. Process for coating ferrous material and material coated, P (5) 128*b*. Process for making conducting cubic boron nitride and product therefrom, P (6) 162*d*. Process for producing carbides, P (6) 162*f*. Process for producing high density refractory bodies, P (1) 17*a*. Process for providing improved maintenance to electroluminescent [ZnS] phosphors, P (6) 166*f*. Quartz lamp sealing machine control, P (6) 158*e*. Sintered aluminum composition, P (6) 162*i*. Storage target electrode and method of manufacture, P (9) 249*i*. Synthetic zeolite for selective absorption of Freons, P (6) 171*a*. Temperature reference block, P (4) 108*c*. Thermocouple, P (4) 108*e*. Thermoelectric generator with encapsulated arms, P (4) 106*c*. Two-terminal end cap for high pressure, high temperature reaction vessels, P (8) 222*c*. X-ray analyzing apparatus wherein two comparative detector channels have different absorption versus frequency characteristics, P (11) 320*c*.

General Electric Co., Ltd. Control rod materials, P (8) 215*j*. Difficultly fusible bodies suitable as tank blocks for glassmelting furnaces, P (6) 162*b*. Electrical devices having hermetically sealed envelopes, P (3) 77*i*. Growing quartz crystals, P (6) 171*a*. Manufacture of apparatus including thin magnetic films, P (10) 283*a*. Methods of joining graphitic surfaces, P (10) 269*e*. Methods of protecting graphite surfaces, P (4) 103*a*.

General Motors Corp. Alumina base ceramic, P (8) 218*b*. Foundry process and molding mixture, P (4) 102*g*. Friction material, P (4) 95*h*. Fuel element for nuclear reactors, P (8) 216*b*. Heat-sensing device with protective sheath, P (2) 38*c*. High temperature bond and method of forming it, P (1) 16*d*. High temperature seal, P (4) 102*a*. Method for making electrodes, P (7) 193*g*. Method of making porous ceramic articles, P (9) 246*c*. Method for making silicon nitride-bonded silicon carbide semiconductors and resulting bodies and articles using them, P (1) 16*c*. Method and mechanism for forming annular grooves, P (4) 107*a*. Mold test apparatus, P (2) 46*f*. Multilayered composite metal article, P (9) 245*a*. Multiple thermocouple circuit, P (1) 24*d*. Parting agent for sprayed metal shells and method for making them, P (6) 162*a*. Permanent magnet, P (1) 21*c*. Process of applying ohmic contacts to crystals, P (5) 137*b*. Thermocouple, P (8) 224*d*.

General Precision, Inc. Interference goniometer, P (8) 224*b*.

General Refractories Co. Basic refractory [metal encased] brick and method, P (9) 244*g*. Brick package, P (3) 73*h*. Comolded magnesite-chromite tuyere, P (8) 215*h*. Furnace roof suspended by interconnected [metal encased] brick hanger extensions, P (5) 133*h*. Refractory brick and method of molding, P (1) 17*c*. Refractory roof [with suspended arch], P (3) 74*i*. Refractory [suspended] roof construction, P (9) 245*e*. Ribbed basic refractory roof, P (10) 277*h*.

General Telephone and Electronics Laboratories, Inc. Process for producing electroluminescent phosphors, P (5) 137*c*.

Gentile, A. L., and Foster, W. R. Calcium hexaluminate and its stability relations in the system $CaO–Al_2O_3–SiO_2$, (4) 112*i*.

Gentner, K. Pyrolytically decomposed resistor consisting of carbon, oxygen, and silicon, P (5) 137*f*.

Gentry, C. H. R., and Oldfield, R. C. Cathode ray tube with silica coated phosphor screen, P (11) 311*b*.

Genzel, L. See Czerny, M.

George H. Bullard Co., Inc. Abrasive wheel, P (7) 177*f*.

George, H. J. C. Optical pyrometers, P (6) 168*j*.

Geo. J. Meyer Mfg. Co. Inspection device, P (7) 186*e*.

George, M. F., Jr., Simon, E., and Burkart, E. H. High-dielectric constant material and method of making it, P (6) 166*c*.

Georgobiani, A. N. Effect of the bond type of crystal phosphors on their electroluminescent ability, (6) 163*j*.

Georgobiani, A. N., and Golubeva, N. P. Excitation of electroluminescence in alkali halides, (6) 163*j*.

Geppert, D. V. New negative-resistance device, (7) 192*f*.

Gerard, G., and Brayman, J. Compact hydrostatic pressure apparatus, P (10) 285*c*. Hydrostatic press for an elongated object, P (9) 250*c*. Multianvil apparatus and test bodies therefor, P (7) 195*a*. Multianvil force compensating pressure apparatus, P (1) 23*d*.

Gerhold, R. A., and Elders, D. S. Modules incorporate integrated circuits, (10) 281*e*.

Gerlach, H. G. Method of soldering molybdenum foil by molybdenum carbide, P (2) 50*b*.

German, W. L. Some impressions of the pottery industry in the U.S.A., (8) 218*d*. United States ceramics—education, training, and research, (9) 258*g*.

Gernes, D. C. Improvement in a process for producing synthetic cryolite, P (3) 83*i*.

Gernes, D. C., and King, W. R. Producing aluminum fluoride, P (2) 55*f*.

Gerrard Industries, Ltd. Method and machine for packaging bottles [with metal loops], P (5) 131*a*.

Gersbach, W. Dicing semiconductor crystals, P (7) 193*j*.

Gershkovich, V. I. See Solntsev, P. I.

Gerster, C. W., and Pearch, H. Apparatus for shaping pressure-shapable materials, P (10) 284*j*.

Gerthsen, P. New method of growing single crystals of materials with high melting points, (10) 288*e*.

Geschwind, S., and Remeika, J. P. Spin resonance of transition metal ions in corundum, B (9) 260*g*.

Ghose, A. C., and Su, G.-J. Viscosity, density, and electrical resistivity determinations of molten ternary lanthanum borates containing barium, tantalum, or tungsten oxide, B (11) 320*f*.

Ghose, S. Nature of Mg^{2+}-Fe^{2+} distribution in some ferromagnesian silicate minerals, (7) 199*j*.

Ghosh, D. K. See Bishui, B. M.

Ghosh, S. K., Das, S. C., and Mehta, S. C. Mineralogy of clays of red and lateritic soils, (3) 82*g*.

Ghosh, S. N., Guha, S. K., Sen, B. K., Gupta, Mrs. K. S., and Sen, S. Evaluation of plastic clays of India as substitutes for ball clays, (6) 169*j*.

Giardini, A. A., Kohn, J. A., Eckart, D. W., and Tydings, J. E. Formation of coesite and kyanite from pyrophyllite at very high pressures and high temperatures, (4) 114*f*.

Giardini, A. A., and Tydings, J. E. Diamond synthesis—observations on the mechanism of formation, (6) 169*h*. Pressure and temperature sensing device for high pressure apparatus, P (4) 108*a*.

Gibb, T. R. P., Jr. Primary solid hydrides, B (3) 92*c*.

Gibbs, B. M. See Elyard, C. A.

Gibbs, G. V., and Bloss, F. D. Indexed powder diffraction data for scapolite, (4) 114*f*.

Gibbs, G. V., Miller, J. L., and Shell, H. R. Synthetic fluor-magnesio-richterite, (7) 201*h*.

Gibbs, P. See Rogers, W. G.

Gibbs, P., Baker, G. S., et al. Surface and environmental effects on ceramic materials, (8) 230*c*.

Gibbs, T. W., and Theberge, C. L. Determining elastic moduli of materials by resonance, (7) 195*i*.

Gibby, W. F. See Vedder, W. O.

Gibson, B. See Waye, B. E.

Gibson, J. K. See Kreigh, J. R.

Gibson, W. M. See Madden, T. C.

Gibson Electric Co. Method for attaching silver-cadmium oxide bodies to a supporting member, P (6) 166*h*.

Gieskieng, D. H. Control system for automatically regulating cement kilns and auxiliary apparatus, P (5) 127*c*.

Giess, E. A. Equations and tables for analyzing solid-state reaction kinetics, (10) 292*c*. Growth of single-crystal $MgGa_2O_4$ spinel from molten PbO-PbF_2 solutions, (5) 144*b*. See Beals, M. D.; Lefever, R. A.

Gilbert, W. Background of ceramic raw materials (XII) influence of sulfur compounds, (1) 25*e*; (XIII) variations in clay deposits, (XIV) ceramic food for thought, (1) 25*f*; (XV) role of water in ceramics, (XVI) elements present in rocks in small concentrations, (1) 25*g*. Background of refractories technology, (10) 273*j*.

Gill, J. S. See Marshall, W. L.

Gill, R. M., and Spence, G. Self-bonded silicon nitride, (1) 15*g*.

Gilleo, M. A. See Geller, S.

Gillerman, H. M. Means and methods for electrically measuring the amount of oxygen in a gas, P (5) 139*h*.

Gilles, J.-M. F., and Van Cakenberghe, J. L. Process for the production of large semiconductor crystals, P (3) 78*i*.

Gilliland, H. E. See Schmunk, J. D.

Gilman, J. J. Strength of ceramic crystals, B (9) 259*f*.

Gilpin, W. C. See Booth, C.

Gilson Screen Co. Sample splitter, P (5) 140*b*.

Gink, K. See Boncz, C.

Ginsberg, H., Huettig, W., and Stiehl, H. Contribution to the system $H_2O–Al_2O_3$ (I) precipitation of aluminum hydroxides from aluminate solutions and from solutions of aluminum salts, (4) 112*g*; (II) formation of crystalline $Al(OH)_3$ and the transformation of bayerite into hydrargillite, (5) 142*f*.

Ginsling, A. A. See Rorden, R. J.

Ginther, R. J. Radiation sensitive glass, P (10) 273*a*. See Etzel, H. W.

Ginzburg, D. B. Improving the design of tunnel kilns, (7) 190*e*.

Gion, L. Process for producing sintered beryllium oxide and resultant products, P (3) 74*b*.

Giovannini, E. Ultrafine dust—its effective removal by suspension filters, (4) 108*b*.

Girela Vilchez, F. See Martin Vivaldi, J. L.

Gisondi, A. See Grungo, G.

Gitzen, W. H. Production of low-soda alumina, P (9) 254*g*.

Giulini, Gebrueder, G.m.b.H. Process for the decomposition of titanium ores, P (5) 141*h*.

Gjems, O. Some notes on clay minerals in podzol profiles in Fennoscandia, (11) 315*c*.

Gjertsen, P. R. Machine for testing hardness and wear characteristics of abrasive materials, P (4) 108*e*.

Glaceries de la Sambre, Soc. Anon. Glass polishing apparatus, P (5) 131*a*. Glass polishing tools, P (4) 99*j*. Process for the continuous manufacture of reinforced cast glass, P (8) 211*b*.

Glaces de Boussois. Method of manufacturing matching sheets of glass, P (1) 12*d*.

Gladding, McBean & Co. Method for continuous manufacture of ceramic sheathing, P (10) 285*g*. Method of producing a glazed ceramic article and the glazed article, P (8) 218*d*.

Gladrow, E. M., and Ellert, H. G. Preparation and surface properties of porous titania, (1) 29*g*.

Gladstone, M. T. Coated abrasives, P (9) 236*b*.

Glaister, R. M. Barrier-layer dielectrics, (10) 279*i*. See Planer, G. V.

Glaser, H. I. Method and apparatus for heat conditioning and feeding heat-softenable materials, P (2) 42*b*. Method and apparatus for melting and feeding heat-softenable materials, P (1) 11*h*.

Glaser, P. E. Heating of materials in imaging furnaces, B (10) 300*f*. (editor) Aerodynamically Heated Structures—Proceedings of a Conference Sponsored by Air Force Office of Scientific Research and Arthur D. Little, Inc., July 1961, Cambridge, Mass., B (2) 61*f*.

Glasner, A., and Steinberg, M. Thermal decomposition of the light rare earth oxalates, (9) 257*a*.

Glasrock Products, Inc. Ceramic body, P (2) 45*j*.

Glasser, F. P., and Glasser, L. S. D. Crystal chemistry of some AB_2O_4 compounds, (10) 291*g*. Crystallographic study of $Ca_3BaSi_2O_8$, (4) 113*h*.

Glasser, L. S. D. See Glasser, F. P.

Glaswerk Schuller G.m.b.H. Fibrous-glass laminates, P (4) 99*f*.

Glauser, A. Introduction to chemical calculations on the basis of equivalents in cement chemistry, (5) 126*j*.

Gleason Works. Magnetic separator, P (10) 289*a*.

Glemser, O. See Gattow, G.

Glemser, O., Gattow, G., and Meisiek, H. Preparation and properties of manganese(IV) oxides (I) δ group, (3) 88*a*.

Glenn, J. P. Manufacture of articles from powdered materials, P (5) 138*a*.

Glenn, R. C., Jackson, M. L., Hole, F. D., and Lee, G. B. Chemical weathering of layer silicate clays in loess-derived Tama silt loam of southwestern Wisconsin, B (3) 91*i*.

Glidden Co. Inorganic blue to green pigments and processes for making them, P (6) 167*c*. Rutile seed, P (4) 111*e*.

Glidewell, M. E., and DeWitt, V. R. Conveyor hanger doubles as paint mask, (3) 79*g*.

Gliemeroth, G. See Schmid, O.

Gliki, N. G. Growth of ice crystals from the vapor, B (9) 262*d*.

Globe-Union, Inc. Method of making porous metal bodies, P (4) 102*d*.

Glonti, N. Ya., and Sharabidze, M. I. Increasing the working capacity of tunnel kiln cars, (8) 224*g*.

Glover, J. H. Method of and apparatus for oxygen determination, P (8) 224*c*.

Glynn, T. W. Electric heater with plate-clamping reflector, P (3) 69*g*. Method of attaching a metal channel to a glass plate, P (10) 272*b*.

Godfrey, J., and Thurber, E. A. Protective element for hermetically enclosed semiconductor devices, P (7) 194*b*.

Godron, Y. G. Lubricants for the hot-working of titanium, P (3) 65*f*.

Goeddel, W. V. Ceramic product and method of making it, P (2) 45*a*.

Goeddel, W. V., and Simnad, M. T. Method of making fuel bodies, P (8) 216*d*.

Goeltz, P. H. Magnetic separator, P (10) 289*a*.

Goland, A. N. See Antal, J. J.

Golay, M. J. E. See Woodcock, E. L.

Gold, A. J. Automatic glass batching—key to modern glassmaking (I, II), (11) 303*e*.

Gold, L. Hot electron nonequilibrium carrier distribution in a many-valley semiconductor, (11) 310*g*.

Goldberg, P. See Faria, S.

Goldberg, P., and Solomon, A. L. Electroluminescent device, P (1) 20*f*.

Gol'denberg, L. G. Design and calculation of feeders with gas heating, (8) 224*e*.

Goldstein, M. Depolarized components of light scattered by glasses (III) scattering from general strain systems, with applications to neutron-damaged vitreous silica, (5) 128*i*.

Goldthwaite, V., and Schlacht, E. Machines for testing and sorting ferromagnetic cores, P (2) 49*e*.

Golightly, J. S. Glass bending method, P (8) 210*e*. Method of bending glass sheets [with a heat shield], P (4) 100*d*.

Golikova, E. V. See Mazurin, O. V.

Golob, H. R. See Ohlberg, S. M.

Golovanenko, I. M. Mining concerns in the [Russian] refractories industry during 1959–1961, (7) 197*h*.

Gol'tsman, B. M. Production of sheets, rods, and tubes by pulling from the melt, B (9) 263*d*.

Golub, S. I. See Belous, V. M.

Golubeva, N. P. See Georgobiani, A. N.

Gomes, G. S., and Levy, D. J. Gold plating with spray guns, (10) 278*j*.

Gompper, J. Apparatus for sampling granular or powdery material in bulk [in a closed container], P (3) 81*b*.

Goncharov, V. V. Chrome spinellids in a used arch magnesite-chromite refractory, (5) 132*e*.

Gonser, U. See Fujita, F. E.

Gonzalez, D. J. Discharge electrode apparatus for electrostatic precipitators, P (2) 51*a*.

Gonzalez, J. L. See Linares Gonzalez, J.

Gooch, F. P. See Payne, R. E.

Goodenough, R. D., and Stenger, V. A. Chromate pigments, P (4) 110*f*.

Goodman, G. Dielectric compositions, P (4) 105*c*. Electrical conduction anomaly in samarium-doped barium titanate, (3) 76*e*. Some varied dielectric properties of materials with tetragonal tungsten bronze crystal structure, (10) 282*h*.

Goodnow, W. H. See Cooper, A. R., Jr.

Goodrich, B. F., Co. Method and apparatus for making magnetically anisotropic elongated magnets, P (4) 105*g*. Method of making a particulate, solid silicon monoxide product, P (8) 225*g*.

Goodridge, H. C. Method and apparatus for measurement of temperature, P (9) 252*g*.

Goorissen, J. Method for treating [semiconductive] materials having a high surface tension in the molten state in a crucible, P (3) 78*a*.

Goorissen, J., and Manintveld, J. A. Method of producing electrode material for semiconducting devices, P (3) 78*j*.

Gorban, A. N., and Sokolov, V. A. Effect of an electric field on the radical-recombination luminescence of the phosphor ZnS,CdS:Cu, (5) 134*j*.

Gorbatyi, Yu. E. See Epel'baum, M. B.

Gorbauchuk, G. A. See Vozdvizhenskii, G. S.

Gordon, I. Method and apparatus for preparing magnetic cores, P (6) 166*g*.

Gordon, J. E., Evans, C. C., and Parratt, N. J. Process for the continuous production of thin elongated single crystals of zinc oxide and antimony trioxide, P (10) 285*c*.

Gordon, J. P. See Yariv, A.

Gordon & Piatt, Inc. Gas burner structure, P (5) 140*d*.

Gorgens, J. E., and Plavcan, E. J. Dial instrument [thermometer] with external calibration, P (10) 287*f*.

Gorina, Yu. I., and Maksimova, G. V. Verneuil's method and the growth of nonstoichiometric strontium titanate monocrystals, B (9) 263*f*.

Gorman, J. K. Shallow donor thermionic emitter, (5) 135*a*.

Gorshtein, G. I. See Belyaev, L. M.

Gorski, A. See Edgerly, C. R.

Gorskii, F. K., and Mikhlin, M. E. Effects of pressure on nucleation and linear growth rate for betol, B (9) 262*c*.

Gorter, E. W., Lotgering, F. K., Jonker, G. H., Wijn, H. P. J., and Kooy, C. Ferromagnetic body and method of making it, P (5) 136*b*.

Gorter, E. W., Schulkes, J. A., and Verweel, J. Ferromagnetic material, P (8) 220*j*.

Gorum, A. E. Mechanical properties of crystals, (10) 298*b*.

Gosa, C. L. Ceramic honeycomb, (3) 66*b*.

Goswami, K. N. See Patel, A. R.

Goto, K., Hanada, M., and Miyairi, H. Effect of chemical composition of slag on properties of portland blast-furnace slag cement, (7) 179*c*. Effects of chemical composition of clinker on properties of portland blast-furnace slag cement, (7) 180*d*.

Goto, Y., and Kitamura, T. Phase diagram of the Cr–O system at high pressure of oxygen and some properties of the coupound CrO_{2}, *x*, (4) 117*d*.

Goto, Y., Kitamura, T., Takada, T., and Kachi, S. Phase diagram of the system La_2O_3–Fe_2O_3, (6) 174*i*.

Goton, R. Utilization of physicochemical methods for studying fused oxides, B (10) 300*f*.

Goton, R. P. High temperature differential thermal analyzer, P (8) 224*a*.

Gottlieb, S. Vertical [cement] kilns allow remote control sintering, (10) 287*j*.

Gould, R. E. See Wahl, A. J.

Gourary, B. S., and Fein, A. E. Theory of localized electronic states at point imperfections, B (9) 259*j*.

Grabowski, B. See Pierrot, A.

Grace, W. R., & Co. Ball milling apparatus, P (2) 51*i*. Cement grinding aid and pack set inhibitor, P (10) 268*c*. Cement pack set inhibitor, P (9) 237*c*. Hydrous oxide sols, P (9) 246*e*. Method of preparing ferrimagnetic materials, P (3) 78*k*. Process for preparing alumina gels, P (3) 84*e*, P (4) 111*b*. Process for preparing fine size [20 to 250 mμ] silica, P (7) 198*a*. Process for preparing low surface area silica, P (4) 111*c*. Stable silica-clad thoria sols and their preparation, P (10) 278*a*.

Gracheva, O. I. See Berkovich, T. M.

Graf, R. B. See Wahl, F. M.

Graf, R. B., Wahl, F. M., and Grim, R. E. Phase transformations in silica-alumina-magnesia mixtures as examined by continuous X-ray diffraction (I) talc-kaolinite compositions, (6) 174*f*; (II) spinel-silica compositions, (7) 199*d*.

Graham, A. L. See Dietert, H. W.

Graham, P. N., and Krampf, M. B. Volumetric glassware and method of production, P (2) 43*c*.

Graham, R. A. Dielectric anomaly in quartz for high transient stress and field, (5) 142*g*.

Grandey, M. F. See Daunt, J. E.

Grandey, M. F., and Kulp, J. F. Method of preparing silicon nitride foam material, P (8) 216*f*.

Grandjean, B. L. Royal Danish porcelain and the C. L. David collection, (6) 153*j*.

Graner, W. R. Method for [radioactively] determining uniformity of finish on fibrous glass reinforcement, P (4) 100*f*.

Granger, T. L. See Marcyes, V. W.

Granholm, H. See Hedvall, J. A.

Grannemann, W. W. See Davis, G., Jr.

Granquist, W. T., and Pollack, S. S. Study of the synthesis of hectorite, B (3) 91*j*.

Grant, N. J. Ceramic coated metal bodies, P (3) 65*d*. Method of producing dispersion hardened titanium alloys, P (4) 103*a*.

Grant, N. J., and Zwilsky, K. M. Method for processing dispersion strengthened metals, P (4) 102*i*. Production of dispersion hardened metals, P (4) 103*e*. Production of dispersion strengthened metals, P (4) 103*b*.

Grantz, K. See Brendel, O.

Grapentin, K. See Ebert, H.

Grassmann, W., and Hannig, K. Method and apparatus for the continuous colorimetric determination of the individual components of a [liquid] mixture, P (2) 60*b*.

Graupner, W. Chronic shortness of breath and its treatment by aerosol therapy, (3) 90*c*.

Graves, S. See Morrow, S. A.; Tomlinson, L.

Graviner Mfg. Co., Ltd. Temperature sensitive devices, P (9) 252*j*.

Gravley, C. K. See Williams, A. L. W.

Gray, C. L., Jr., and Dettre, R. H. Process for increasing the scratch resistance of glass, P (1) 12*d*.

Gray, T. J. See Crandall, W. B.

Graziano, E. E. Oxidation-resistant refractory coatings for metals tested at 3000° to 6000°F—annotated bibliography, (8) 207*f*.

Great Lakes Carbon Corp. Mineral filter aids, P (6) 171*e*.

Grebenshchikov, R. G., and Toropov, N. A. New data on the phase diagram of the system barium oxide–silica, (3) 87*i*.

Grebski, J. Rapid method of boric oxide determination in glasses containing 0 to 18% B_2O_3 using a weak source of slow neutrons, B (11) 320*j*.

Grechanova, S. B. See Azarov, K. P.

Green, A. J. See Clark, J. S.

Green, A. P., Fire Brick Co. Method of making refractory brick, P (11) 308*g*.

Green, L., Jr. See Haufman, W. F.

Green, L., Jr., Stehsel, M. L., and Waller, C. E. High-temperature torsional shear properties of a molded graphite, B (3) 92*d*.

Green, W. Abrasives in the bearing industry, (2) 33*e*.

Greenberg, S. A. See Brunauer, S.; Ish-Shalom, M.

Greenberg, S. S. See Harrison, J. L.

Greenberg, W. H. See Church, J. M.

Greene, C. H. Dimensional analysis—its application to models of glass tanks, (7) 184*c*. Multiple break sources in laths of sheet glass, B (11) 320*i*.

Greene, C. H., and Weber, J. W. Interesting type of fracture, (2) 39*j*.

Greene, E. W. See Duke, J. B.

Greene, E. W., Duke, J. B., and Hunter, J. L. Method of brightening clay by froth flotation of sulfidized clay pulp, P (5) 141*e*.

Greene, K. T. Early hydration reactions of portland cement, B (5) 149*h*.

Greene, R. E., and Petit, G. S. High pressure fluorination of uranium oxides, (7) 199*d*.

Greene, T. G. See Kump, H. J.

Greene-Kelly, R. See Weir, A. H.

Greener, E. H., Fitzgerald, D. J., and Hirthe, W. M. Pulse currents in rutile, (10) 281*c*.

Greener, E. H., Whitmore, D. H., and Fine, M. E. Electrical conductivity of near-stoichiometric α-Nb_2O_5, (2) 56*i*.

Greenhouse, H. Ferrites having rectangular hysteresis loops and method for manufacture, P (5) 135*j*.

Greenhouse, H. M. See Vergara, W. C.

Greenland, D. J., Laby, R. H., and Quirk, J. P. Adsorption of glycine and its di-, tri-, and tetra-peptides by montmorillonite, (10) 290*f*.

Greenland, D. J., and Quirk, J. P. Adsorption of 1-*n*-alkyl-pyridinium bromides by montmorillonites, B (5) 150*j*.

Greenler, R. G. See Rothwell, W. S.

Grego, P., and Howell, R. G. Glass staining method and material, P (6) 157*d*.

Gregorius, J. S. Evolution of flat glass processes during the 20th century, (2) 39*c*.

Greiner, J. D., Shanks, H. R., and Wallace, D. C. Magnetic susceptibility of the cubic sodium tungsten bronzes, (9) 256*b*.

Greiser, W. Graf Sigvard Bernadotte, (10) 266*a*. Secret of mosaic, (7) 178*a*. Tapio Wirkkala of Finland, (10) 266*a*.

Gremigni, G. See Marchioli, G.

Gremmelmaier, R. Apparatus for pulling [semiconductor] crystals from molten compounds, P (5) 135*d*.

Griaznov, I. M. See Barke, V. N.

Grieb, W. E., and Woolf, D. O. Concrete containing fly ash as a replacement for portland blast-furnace slag cement, (1) 2*k*.

Griffin, W. F., and Miller, J. F. Method of and apparatus for spraying cathodes with emissive materials, P (7) 193*h*.

Griffith, C. F. See Vago, E.

Griffith, C. F., and Vago, E. Stirring test for the evaluation of the resistance of refractory materials to corrosion by molten glass, (2) 45*g*.

Griffiths, L. B. Symposium on nuclear ceramics: Irradiation damage in uranium monocarbide, (11) 307*c*.

Griffiths, R. Measuring particle size (I–V), (8) 223*f*.

Griggs, J. O., Ross, W. L., and Fraser, A. R. Refractory composition and process of making it, P (8) 217*a*.

Grigaby, C. E. Refractory [suspended] roof construction, P (9) 245*e*.

Grim, R. E. See Graf, R. B.; Wahl, F. M.

Grim, R. E., Droste, J. B., and Bradley, W. F. Mixed-layer clay mineral associated with an evaporite, B (3) 91*a*.

Grim, R. E., and Kulbicki, G. Montmorillonite—high temperature reactions and classification, (4) 116*c*.

Grimes, D. M. See Westrum, E. F., Jr.

Grimes, W. R. See Cannon, M. C.

Grimes, W. R., Shaffer, J. H., and Watson, G. M. Preparation of refractory oxide crystals, P (3) 74*j*.

Grimley, R. T., Burns, R. P., and Inghram, M. G. Thermodynamics of the vaporization of nickel oxide, (3) 89*f*.

Grimm, W. Fuel oil in the ceramic industry, (5) 140*c*.

Grindrod, J. Capacity doubled with new plant of French gypsum plaster producer, (6) 154*b*.

Grinten, W. J. van der, and Fischer-Colbrie, E. Thermoelectric generator with encapsulated arms, P (4) 106*c*.

Grinton, J. Low temperature enameling, (2) 37*d*.

Grison, E., Lord, W. B. H., and Fowler, R. D. (editors). Plutonium 1960—Proceedings of the Second International Conference on Plutonium Metallurgy, Grenoble, France, April, 1960, B (8) 231*b*.

Griss, C. H., and Brillhart, M. F. Method and apparatus for optical inspection of glass sheets, P (7) 186*a*.

Grjotheim, K., Krohn, C., and Toguri, J. M. Thermodynamic evaluation of activities in molten mixtures of reciprocal salt systems, (10) 297*d*.

Grodkiewicz, W. H., and Van Uitert, L. G. Synthesis of forsterite, diopside, akermanite, and wollastonite from molten PbO, (9) 257*h*.

Groenvold, F., and Westrum, E. F., Jr. Heat capacities and thermodynamic functions of iron disulfide (pyrite), iron diselenide, and nickel diselenide from 5° to 350°K—estimation of standard entropies of transition metal chalcogenides, (1) 27*j*.

Groessl, K. Higher zinc oxide content in mat glazes for Seger cone 05*a*, (10) 278*c*.

Grollier-Baron, T., and Gaudin, J. Manufacture of electrically melted refractory products containing mineral oxides, P (6) 162*g*.

Gromes, W. See Hofmann, U.

Gross, F. Photoluminescence of Ag-containing crystalline quartz, (6) 164*j*.

Gross, M. W. Method of making ceramic-to-metal composite stock, P (8) 208*c*.

Gross, P., Westrick, M. L., and McNerney, J. M. Glass dust—a study of its biologic effects, (2) 60*c*.

Grossman, L. N. High-temperature thermophysical properties of uranium monocarbide, (8) 228*e*. Question of a phase change in zirconium monocarbide, (10) 296*a*.

Groth, R. H. See Clarke, R. G.

Grover, J. R., and Chidley, B. E. Glasses suitable for the long-term storage of fission products, (10) 270*j*.

Groves, G. W., and Kelly, A. Climb of dislocations in magnesium oxide, B (9) 260*i*.

Gruber, B. A. Process for the production of metal borides, P (10) 277*g*.

Gruber, B. A., Ruehrwein, R. A., and Williams, F. V. Boron phosphide articles and coatings, P (9) 239*b*.

Gruber, J., and Wintersberger, K. Process for the production of acicular gamma-iron(III) oxide, P (5) 141*b*.

Gruber, W. M. Materials testing equipment, P (5) 139*g*.

Grudemo, A. Microstructure of hardened cement paste, B (5) 149*g*.

Gruen, G. Method and apparatus for mixing pulverulent or fine-grain material [by air jets], P (10) 285*g*.

Gruen, K. See Krebs, H.

Gruender, W. Dust technology, (3) 90*c*.

Gruenling, H. Microscopic investigations of Hirschau kaolinite, (4) 109*f*.

Grum-Grzhimailo, S. V., Brilliantov, N. A., Sviridova, R. K., Sukhanova, O. N., and Kapitonova, M. M. Absorption spectra of iron-colored beryls at temperatures from 290° to 1.7°K, (6) 171*f*.

Grumman Aircraft Engineering Corp. Method for testing fluids for particle contamination, P (10) 287*b*.

Grungo, G., and Dalmazzo, M. Technical features and behavior of the refractory materials used for lining passage kilns for the ceramic industry, B (10) 300*h*.

Grungo, G., Gisondi, A., and Rattazzi, M. Influence of CaO (free or combined) on the technological characteristics of siliceous refractories according to their firing temperature, B (10) 300*h*.

Gude, A. J., III, and Hathaway, J. C. Diffractometer mount for small samples, (4) 107*f*.

Gudz', P. N. See Mikhnevich, G. L.

Guentert, O. J. See Mozzi, R. L.

Guenther, G. G. J., and Rosengren, G. B. Method of producing a light-diffusing layer on glass surfaces, especially on the inside of electric lamp envelopes, P (2) 42*e*.

Guerard, Y. H. See Coble, R. L.

Guerra, A. See Taramasso, M.

Guerra, R. F. See Fuentes Guerra, R.

Guetter, E. Means for varying the picture brightness in an electron microscope, P (8) 230*d*.

Gugel, E. Combustion processes in the firing of lightweight brick containing combustible matter, (2) 53*e*.

Gugliotta, F. See Vratny, F.

Guha, J. See Briggs, G.

Guha, S. K. See Ghosh, S. N.

Guidi, A. See Lecis, P.

Guillaud, C. L. See Pierrot, A.

Guillemet, C. See Acloque, P.

Guinier, A. Twenty years of progress in X-ray diffraction techniques, B (2) 61*a*. See Yannaquis, N.

Gulevic, O. Zircon as opacifier in hard porcelain glazes, (10) 279*c*.

Gulf Oil Corp. Cement composition, P (4) 96*f*.

Gulf Research & Development Co. Catalyst coated thermocouple elements, P (4) 108*d*. Chromatographic method and apparatus, P (1) 31*a*. Method for preparing beta-alumina trihydrate, P (10) 289*f*.

Gul'ko, N. V. See Margulis, O. M.

Gullbring, B. Pharmaceutical glass from the consumer's viewpoint, (1) 8*g*.

Gulton Industries, Inc. Ceramic components and method of making them, P (1) 20*f*. Piezoelectric electromechanical transducer, P (9) 249*d*. Piezoelectric transducer, P (5) 136*i*. Piezoresistive transducer, P (8) 220*h*.
Gungle, W. C., and Ray, J. G. Fluorescent lamp, P (10) 271*h*.
Gungle, W. C., and Waymouth, J. F. Aperture fluorescent lamp, P (3) 68*c*. Helium-argon lamp, P (1) 11*e*.
Gunzelmann, R. N. Apparatus for handling stacks of bricks, P (9) 250*c*.
Gupta, J. See Damodaran, V.
Gupta, Mrs. K. S. See Ghosh, S. N.
Gupta, M. L., and Raychaudhuri, B. C. Guard-dome thermal conductivity apparatus—effect of small temperature unbalances on the conductivity values, (11) 313*c*.
Gupta, M. M., and Nandi, D. N. Silica refractories—a review, (6) 161*f*. Utilization of pure quartz in manufacturing silica brick, (6) 161*h*.
Gupta, P. K., and Kumar, S. Glasses in the systems $PbO–B_2O_3–SO_3$ and $ZnO–B_2O_3–SO_3$, (6) 156*j*.
Gurevich, I. E., Postemein, B. S., Khachaturov, S. Sh., Nikov, P. N., Kyazimov, A. A., Karakurchi, V. A., and Andryukhin, J. N. Tapping clay powder [dust collector], P (2) 51*h*.
Gurkovskii, E. V., and Kaminskaya, N. L. New gold-ruby glass composition, (7) 185*a*.
Gurney, I. D. C. See Bolton, H. C.
Gurvich, A. M. New luminophors—cadmium and zinc chlorides activated with sulfides, (5) 135*h*.
Gurynsky, D. H. See Schweitzer, D. G.
Guseva, I. N. Refractive indices and transparency of synthetic quartz crystals in the ultraviolet, B (9) 263*h*.
Gus'kov, K. See Aleksandrovich, E.
Gusman, I. J., and Horton, R. C. Fiber glass fabric filters for high temperature dust and fume control, (11) 303*i*.
Gutop, V. G., and Vil'nis, K. K. Glass-melting furnace, P (2) 42*j*.
Gutowsky, H. S. See Henderson, D. M.
Gutsche, H. See Schweickert, H.
Gutt, W. See Welch, J. H.
Guyer, G. W. See Shulver, W.
Gwirtsman, J. J. Abbreviations in Russian abstract journals covering chemistry and related fields, (5) 148*b*.
Gwyn, C. B., Jr., and Hoyer, N. S. Method for attaching silver-cadmium oxide bodies to a supporting member, P (6) 166*h*.
Gyulai, Z. Formation of KBr nuclei in aqueous solutions, B (9) 262*c*.

Haaijman, P. W., Janssen, G. H., and Linden, P. C. van der. Light-dispersing layers on glass surfaces, P (3) 69*c*. Light-scattering coatings for the inside of light bulbs, P (2) 60*i*.
Haake, C. H. Photopot optical potentiometer, (9) 251*d*. See Lehmann, W.
Haan, E. F. de. See Lemmens, H. J.
Haan, Y. M. de. See Newnham, R. E.
Haas, B. See Dietzel, A.
Haas, W. See Johannes, H.
Haba, V. Method and materials for obtaining low resistance bonds to bismuth telluride, P (6) 166*j*. Thermoelectric devices and methods of making them, P (5) 137*e*.
Haber, H. S. See McIntyre, G. H., Jr.
Haber, J. See Bielanski, A.
Haberey, W. Glass industry in the Roman Rhineland, B (11) 321*g*.
Hackett, W. S. Mold test apparatus, P (2) 46*f*.
Haden, W. L., Jr. See Dzierzanowski, F. J.; Robinson, A. J.
Haden, W. L., Jr., and Dzierzanowski, F. J. Method for producing synthetic crystalline zeolite aggregates, P (11) 315*c*. Synthetic crystalline zeolite produced from dehydrated aluminum silicate, P (3) 85*a*.
Hadley, D. W. Production of neck ring blanks on a Ward No. 7 turret lathe, (4) 98*i*.
Hadwiger, H. Consistency of enamel slip, (8) 206*h*. Ferric oxide as the colorant for red-brown enamels, (10) 269*b*.
Haefele, H. G. Optical constants of magnesium oxide in the infrared [region], (9) 256*d*.
Haeffner, H. Austrian regulations governing the solubility of lead from on-glaze decorated porcelain, (3) 90*b*.
Haenlein, W. Thin flexible glass coatings on wire, foil, etc., P (3) 65*g*.
Haenlein, W., and Baum, W. Electrically insulating glasslike ferromagnetic materials, (4) 105*i*.
Haese, U. Perlite—a many-sided raw material, (10) 288*j*.
Hafner, S. See Brun, E.
Hagedorn, E. C. Glass composition having high chemical durability, P (2) 42*g*.
Hagen, L. M., and Leverton, W. F. Preparation of high purity silicon by decomposition of silicon nitride powder having a graphite target buried therein, P (11) 311*e*.
Hager, R. E. See Cliff, G. J.
Hagerborg, J. G. Injection molding machine, P (1) 23*a*.
Hagglund, S. E. Diaphragm filter press, P (10) 285*d*.
Hagstedt, M. See Brosset, C.
Hagy, H. E. Experimental evaluation of beam-bending method of determining glass viscosities in the range 10^{13} to 10^{15} poises, (4) 98*d*.
Hahn, P. M. Evaluation of spring-loaded thermocouple probes under transient temperatures, (2) 52*e*.
Haider, S. Z., Khundkar, M. H., and De, K. Preparation and properties of chromyl borate, (7) 199*g*.
Haines, H. R. See Keig, G. A.
Halabi, A.-K. Systematic research on concrete tensile strength, (1) 3*i*.
Halden, F. A. Crystal growth in the system FeO–MgO–Fe_2O_3, (8) 226*e*. (editor) Crystals in your future, (10) 298*e*. Growth of single crystals, (10) 298*g*.
Halden F. A., and Sedlacek, R. Verneuil crystal growth in the arc-image furnace, (10) 284*g*.
Hale, D. Gamma radiation dosimeter, P (5) 136*c*.
Hale, R. M. See Stehsel, M. L.
Hale, R. W. Lithium—present and future and its meaning to the Canadian mining industry, (3) 82*e*.
Hales, B. See Waye, B. E.
Hall, H. L. Calcination means and method, P (1) 3*e*.
Hall, H. N. Tuyere block and reinforcing insert therefor, P (8) 217*b*. See Samuel, D. G.
Hall, J. L. Rotoscribe records "live" as kiln rotates, (9) 253*c*.
Hall, R. D. See Johnston, R. W.
Hall, R. T. Calcination means and method, P (1) 3*e*.
Haller, M. N., and Owen, C. J. Printed circuit on a ceramic base and method of making it, P (6) 166*b*.
Haller, W. K. Method and apparatus for making reconstituted synthetic mica sheet, P (8) 220*c*.
Halleu, I., and White, P. Simple high sensitivity microbalance for use in ultrahigh vacuum, (10) 286*c*.
Halliburton Co. Oil well cement compositions, P (1) 3*g*.
Hallikainen, K. E. Viscometry, (2) 52*j*.
Halm, L., Bortaud, M., and Lapoujade, P. Report on the activities of the French Ceramic Society Committee on Thermal Conductivity, (3) 72*h*.
Halstead, P. E., and Lawrence, C. D. Kinetics of reaction in the system $CaO–SiO_2–H_2O$, B (5) 149*g*.
Halva, C. Semimicroanalysis of silicate rocks for Ca, Fe, Mg, and Al employing EDTA, (3) 83*f*.
Halversen, R. A., and Russell, W. S. Method of pickling and coating with vitreous enamel, P (7) 184*a*.
Ham, W. E., Dodd, C. G., and Ray, S. Field trip to Wichita Mountain area, southwestern Oklahoma, B (3) 91*g*.
Hamano, K. Microstructure of porcelain bodies (XII) fusion of potash feldspar and the problem of leucite formation, (1) 18*h*.
Hamano, Y. Manufacture of superrefractories by hot-pressing (V) manufacture of ceramic packing by hot-pressing, (10) 275*d*. See Hashimoto, H.
Hamblen, D. P., Weidel, R. A., and Blair, G. E. Preparation of ceramic semiconductors from high-vanadium glasses, (11) 310*d*.
Hambleton, A. W. Carbonate-rock fabrics of three Missourian stratigraphic sections in Socorro County, New Mexico, (3) 82*b*.
Hamblin, W. K. X-ray radiography in the study of structures in homogenous sediments, (1) 31*d*.
Hamilton, B. G. See Rigby, G. R.
Hamilton, J. C. Apparatus for slicing semihardened materials, P (2) 51*h*. See Cooke, C. C.
Hamilton, J. P. Bell and spigot tile and [tapered] seal joint therefor, P (5) 132*c*.
Hamilton, J. R. Transfer and invert-revert mechanism for glass machines, P (3) 70*g*.
Hamilton, N. E. Apparatus for fabricating semiconductor devices, P (4) 104*j*.
Hamilton, P. M., and Kistiakowsky, G. B. Composition of metal oxides and carbon black, P (10) 289*f*.
Hamilton, R. See Tooley, F. V.
Hammond, J. A. See Coop, W. H.
Hammond, M. L., and Ravitz, S. F. Influence of environment on brittle fracture of silica, (9) 240*c*.
Hammond, R. Cement manufacture without dust, (3) 64*d*.
Hammond Lead Products, Inc. Corrosion inhibitive pigment and method of making it, P (6) 170*g*.
Hampe, R., and Winter, A. Potters in Crete, Messenia, and Cyprus, B (9) 263*b*.
Hampe, W. R. Fundamentals of fluoroscopy, (2) 52*g*.
Hanada, M. See Goto, K.
Hanada, M., and Miyairi, H. Effect of gypsum on properties of portland blast-furnace slag cement, (7) 179*f*.
Hancock Brick and Tile Co. Upender mechanism for tile machines, P (1) 13*c*.
Handelman, E. T. Fabrication of semiconductor devices, P (8) 220*g*.
Handl, E. Dry cementitious materials, P (2) 55*h*.
Handwerk, J. H., White, G. D., and Hill, D. C. Ceramic nuclear fuels in the system $UO_2–ZrO_2–CaO$, (3) 71*j*.
Haneda, S. See Oki, S.
Hanke, A. R. See Bishop, J. E.
Hanlon, J. E. See Phillips, W. L., Jr.
Hann, D. G. See Gell, P. A. M.
Hann, D. G., and Ramsay, R. F. Furnace for melting or refining glass electrically, P (10) 271*j*.
Hanna, R. Elastic moduli of polycrystalline magnesia alumina spinel, (4) 101*b*.
Hanna, R. J. See Channell, J. K.
Hanner, J. L. See Davis, R. L.
Hannes, G. J. Laminate and method of forming it, P (2) 42*j*.
Hannig, K. See Grassmann, W.
Hansen, A. L. Evaluation of low density high temperature (to 2000°F) thermal insulation, (8) 213*j*.
Hansen, M. Clays of North Dakota as a potential source of alumina, (3) 82*e*.
Hansen, R. C., and Thwaites, G. A. Equipment for transporting sheet materials, P (7) 157*j*.
Hansen, R. D. See Asher, D. R.
Hansen, T. C. Strength, elasticity, and creep as related to the internal structure of concrete, B (5) 149*h*.
Hansen, W. C. Comment on "Studies of early stages of paste hydration of cement compounds (II)," (10) 266*h*. False set in portland cement, B (5) 149*i*.
Hanson, J. A. Strength of structural lightweight concrete under combined stress, (4) 96*b*.
Happ, W. W. See Wagner, O. E.
Harada, Y. See Bliton, J. L.; Bradstreet, S. W.; Rechter, H. L.
Harbison-Walker Refractories Co. Alumina refractories, P (3) 73*f*. Aluminum melting furnace refractory, P (6) 161*i*. Apparatus for making tapered metal blanks for key brick cases, P (8) 215*c*. Brick hanger tab bending apparatus, P (1) 15*i*. Brick molding apparatus for incorporating metal inserts in refractory bricks, P (5) 133*b*. Cradle [zirconia setter], P (9) 244*g*. Furnace block with hanger socket, P (4) 102*f*. Furnace roof block, P (8) 216*e*. Metal cased refractory brick, P (5) 133*a*. Method of comolding a metal insert in a brick, P (7) 189*h*. Production of dead-burned grain, P (2) 46*c*. Production of dead-burned magnesia, P (2) 46*d*, P (9) 245*g*. Refractory castable, P (2) 46*f*. Refractory compositions, P (5) 133*i*. Refractory practices, P (4) 103*c*. Refractory silica brick for open-hearth furnaces, P (6) 162*i*. Tunnel kiln car top [with interlocking tile], P (10) 288*c*.
Harbke, W. See Moore, A.
Harder, P. B. Vermiculite—key to unusual insulating refractory shapes, (10) 276*h*.
Harding, W. E. See Rudge, W. E.
Hardinge, H. Autogenous grinding process and mill systems to perform it, P (6) 170*f*. Mill and process for autogenous grinding of friable material, P (6) 171*d*. See Ferguson, L. C.; Russell, R. J.
Hardinge Co., Inc. Means and methods of supplying heat to grinding mills, P (6) 171*a*. Method and means for segregating and recombining feed for grinding mill, P (6) 171*a*. Mill and process for autogenous grinding of friable material, P (6) 171*d*.
Hares, G. B., and Sheldon, J. L. Image orthicon target, P (4) 100*a*.
Haring, H. E., and Taylor, R. L. Manufacture of solid electrolytic capacitors, P (10) 283*b*.
Harkort, D., Honcia, G., and Kling, H. G. Physical properties of sintered urania bodies containing beryllia, (10) 275*c*.
Harman, C. G. Predicting and controlling loss factors of dielectrics, (6) 165*b*.
Harman, C. G., and Abraham, L. Polishing material, P (4) 95*g*.
Harman, G. G. Electroluminescence from the surface layers of $BaTiO_3$, $SrTiO_3$, and associated materials, (4) 113*e*.
Harmon, R. G. Vapor fraction analysis, P (4) 121*j*.
Harmsen, E. See Ebert, H.
Harper, T. J. Solubility of gases in glass—review, (3) 68*b*.
Harrell, W. C. See Kunkle, G. E.
Harrington, J. S. See Marasas, L. W.
Harris, C. M., and Crede, C. E. (editors). Shock and Vibration Handbook (Vol. I) Basic Theory and Measurements; (Vol. II) Data Analysis, Testing, and Methods of Control; (Vol. III) Engineering Design and Environmental Conditions, B (5) 151*c*.
Harris, D. M. See Henderson, C. M.
Harris, J. Dimensionless groups in viscoelastic flow through a tube, (10) 291*i*. Normal stress measurement in viscoelastic flow, (10) 295*f*.
Harris, J. N. See Fleming, J. D.
Harris, L. A. See Kopp, O. C.; Potter, R. A.
Harris, P. H. Cement product, P (10) 268*f*.
Harris, W. T. Circuit element transducer, P (9) 248*g*.
Harris Transducer Corp. Circuit element transducer, P (9) 248*g*.
Harrison, F. W., Hoselitz, K., and Knowles, J. N. Study of the magnetic properties of sintered ferrites, using single crystal data, (1) 19*i*.
Harrison, J. D. L. See Brett, N. H.
Harrison, J. L., and Greenberg, S. S. Dehydration of fully hydrated halloysite from Lawrence County, Indiana, B (5) 150*g*.
Harrison, L. G. Influence of dislocations on diffusion kinetics in solids with particular reference to the alkali halides, (10) 294*d*.
Harrisson, T. Japan and Borneo—some ceramic parallels, (9) 236*f*.
Harrop, P. J., and Creamer, R. H. High-temperature electrical conductivity of single-crystal alumina, (10) 280*d*.
Harry W. Dietert Co. Apparatus for electrical moisture measurement [during milling], P (9) 252*e*. Apparatus for measuring and controlling moisture content of materials, P (9) 250*d*. Moisture teller [for granular material], P (9) 252*h*.

Hart, J. See Birks, J. B.

Hart, P. B., and Brown, C. S. Synthesis of new calcium borate compounds by hydrothermal methods, (7) 201*g*.

Hart, P. B., and Steward, E. G. Compound formation in the system cadmium oxide–boric oxide, (7) 198*f*.

Hartmann & Braun Akt.-Ges. Gas analyzer, P (2) 53*c*. Gas analyzer based on the principle of thermal conductivity, P (8) 223*j*.

Hartog, J. J. See Perls, T. A.

Hartwig, F. J., and Norton, F. H. Apparatus for forming a ceramic filament, P (3) 68*e*.

Hartwig, J. Process for coating carbonaceous articles with silicon dioxide, P (10) 277*d*.

Hartwig, W. H. Novel test techniques measure Q in cryogenic resonant circuits, (7) 192*i*.

Hartzell, H. F., Jr. See Stirling, H. T.

Harvey, J. L., and Beaty, A. Q. Pulverizer, P (9) 250*f*

Harvey, J. P. See Steghart, F. L. F.

Harvey, R. D., and Beck, C. W. Hydrothermal regularly interstratified chlorite-vermiculite and tobermorite in alteration zones at Goldfield, Nevada, B (5) 150*f*.

Harvey Machine Co., Inc. Production of aluminum sulfate from clay, P (6) 171*b*.

Harwig, S. H. Article having electrically conductive coating and process of making, P (5) 130*c*. Method of making an electrically conductive [glass] article, P (3) 70*g*.

Haseman, J. F., and Reuss, J. L. Wet beneficiating of phosphate ores, P (8) 226*c*.

Hashimoto, H., and Hamano, Y. Kinetic studies on the transformation of quartz—mechanism of transformation from quartz to cristobalite, (5) 129*h*.

Hashizume, G. See Asano, S.

Haskins, J. F. See Amy, J. A.

Hass, M. See Ferguson, G. A., Jr.

Hasselman, D. P. H. Experimental and calculated Young's moduli of zirconium carbide containing a dispersed phase of graphite, (4) 101*b*. Thermal shock by radiation heating, (7) 189*d*.

Hasselman, D. P. H., and Crandall, W. B. Thermal shock analysis of spherical shapes (II), (10) 297*c*.

Hastilow, P. A. P. See Brearley, W.

Hastings, J. See Scatturin, V.

Hatfield, C. See Oakes, A. C.

Hathaway, A. J., III. Production of granular zirconia products, P (5) 133*f*.

Hathaway, J. C. See Gude, A. J., III.

Hathaway, J. C., and Schlanger, S. O. Norstrandite from Guam, (10) 288*g*.

Hatibarua, J. See Mahanta, P. C.

Hauck, W. V. See Brunner, G. M.

Haufman, W. F., Armour, W. H., and Green, L., Jr. Thermal protection of fluorine-hydrogen thrust chambers by carbonaceous materials, (4) 102*a*.

Haug, J. See Juza, R.

Haul, R., and Just, D. Dissorder and oxygen transport in cadmium oxide, B (9) 261*d*.

Haun, R. D., Jr. See Lin, F. C.

Haupin, W. E., and Maduk, E. A. Carbon anode [Fe stem, Al sheath], P (2) 45*i*.

Hauptman, Z., Katzer, J., and Hemperle, R. Growth of cobalt whiskers—some results from physical studies, B (9) 262*e*.

Hauri, D. See Bodi, G. M.

Hausner, H. H. Effect of porosity on the structure of sintered metals, (6) 172*i*. See Kingston, W. E.

Havell, R. See Bliton, J. L.

Haven, Y. See Kats, A.

Havens, R. Flotation process for concentration of phenacite and bertrandite, P (6) 170*h*.

Havighorst, C. R. Separating glass sand from clay, (10) 289*a*.

Hawker, T. G. Magnetic separators in the ceramic industry, (2) 50*i*.

Hawkes, W. H. Symposium on high-alumina refractories: Production of synthetic mullite, (11) 306*j*.

Hawkins, W. M. See Feigley, D. A., Jr.

Hawley, W. G. See Bennett, H.

Hawrylak, R. A. See Verba, J. W.

Hawthorn, A. N. Mica flakes, P (3) 84*d*.

Hay, W. J., Jr. Supporting glass sheets [by tongs], P (9) 242*h*.

Hayama, F. See Nobuoka, S.

Hayami, R., Kadota, M., and Tanaka, H. Ceramic coatings (I) coatings for high-temperature protection of cermets, (5) 127*d*.

Hayami, R., Ogura, T., and Tanaka, H. Fine grained crystalline glass-ceramics—crystallization of some glasses containing Cr_2O_3 (I) crystallization of some glasses in the system Li_2O–Al_2O_3–SiO_2, (5) 129*a*; (II) glass-ceramics having low thermal expansion in the system Li_2O–Al_2O_3–SiO_2–CaO, (5) 129*b*; (III) correlation between chemical composition of glass-ceramics having low thermal expansion in the system Li_2O–Al_2O_3–SiO_2–CaO and their properties, (5) 129*d*.

Hayashi, H. See Arai, Z.; Sudo, T.; Yonemochi, O.

Hayashi, M., and Ito, Y. Properties of cement paste containing expanding and dispersing agents, (7) 181*b*.

Hayashi, S. See Yamamoto, T.

Hayashi, T. Character of change in quality of coarse grain magnesia-chrome brick, (11) 305*f*. Mechanism of carbon deposition on fireclay brick in CO atmosphere (I) effects of iron oxide in mullite solid solution, (11) 306*c*. See Mori, S.

Hayes, C. I., Inc. Resistance heating element for vacuum furnaces, etc., P (2) 54*a*.

Hayes, J. C. Method of exfoliating vermiculite, P (3) 84*c*. See Ziegler, G. E.

Hayes, W. Effects of ionizing radiations on alkali halides containing divalent impurities, B (9) 259*i*.

Haynes, J. M. Gas adsorption method for rapid comparison of specific surface areas, (11) 313*b*.

Hazdra, J. J. Glass surfaces as a contributing factor to good labeling, (9) 240*c*.

Hazemag G.m.b.H. Impellers for comminutors [loose strikers], P (10) 289*j*.

Hazlett, T. H. Investigation of ductile ceramics, (8) 228*g*.

Healy, V. R. See McCorkel, F. M.

Heard, H. C. See Kennedy, G. C.

Heath, Hicks & Perken (Thermometers), Ltd. Thermometer manufacture, P (10) 273*a*.

Hebberling, F. Method and apparatus for traverse of strand material, P (10) 272*j*.

Heck, F. G. See Samuel, D. G.

Heck, I. A., and Humphrey, W. G. Apparatus for [rotary] brush polishing glassware, P (8) 210*h*.

Hedley, C. S. Open hearth furnace roof design, (1) 14*b*. See Booth, C.

Hedvall, J. A., with Degelius, G., and Granholm, H. Chemistry in the Service of Archeology, Building Technology, and Monument Preservation, B (8) 231*a*.

Heesen, L. B., Jr. See Heesen, L. B., Sr.

Heesen, L. B., Sr., Heesen, T. J., and Heesen, L. B., Jr. Mixing apparatus for powdered or granular substances, P (8) 222*d*.

Heesen, T. J. See Heesen, L. B., Sr.

Heffernan, W. J. See Brisbin, P. H.

Hegemann, F., Kostyra, H., and Pfab, B. Flame-spectrometric determination of Na and K with $BaCl_2$ as buffer, (11) 305*f*.

Hegemann, F., and Wilk, G. Photometric-complexometric determination of aluminum and iron in silicates, (3) 80*j*.

Heibel, J. D., and Shoot, L. E. Thermoelectric ceramic, P (5) 137*c*.

Heier, K. S. Estimation of chemical composition of rocks, (4) 107*g*.

Heilmann, T. Reactions of coal ash with portland cement clinker during the burning process, B (5) 148*i*.

Heimke, G. Study by magnetic measurements of the action of different types of grinding mills, (3) 76*i*.

Heimsoeth, W. Problems of porcelain enamel adhesion, B (11) 322*g*.

Heintges, F. Layout of working sequence from sorting to decorating [in the porcelain industry], (4) 104*c*.

Heinz, W. W., and Okwit, S. Note on low power level ferrite limiters, (7) 192*h*.

Heischman, F. E. Resistor compositions and spark plugs having integral resistors, P (8) 221*a*.

Hekkert, J. W. See Brussaard, J. M.

Helbig, W. A. See Forwalt, H. J.

Helbing, C. H., and Denniston, D. W. Method for forming glass fibers, P (6) 158*f*.

Held, H. E. Capacitor, P (8) 220*d*.

Helfferich, F. Ion exchange, B (3) 91*e*.

Heller, G. S., Stickler, J. J., Kern, S., and Wold, A. Antiferromagnetism in $NiTiO_3$, (10) 279*f*.

Heller, L. Thermal transformation of pyrophyllite to mullite, (7) 201*d*.

Heller, W. Black enamel for wet application of fritted ground coats and directly on cast iron, (8) 206*g*. Changes in ground coats for sheet metal in the last 30 years, (8) 206*h*. White and black sheet enamels for heavy duty, (8) 208*a*.

Hellwarth, R. W. See McClung, F. J.

Helming, P., and Schultz, G. Shaft cooler [and crusher], P (8) 222*a*.

Helming, B. H. Apparatus for heating cement powder or similar fine granular materials, P (1) 3*c*. Apparatus for preheating cement powder, P (7) 182*f*.

Helms, S. B., and Bowman, A. L. Extension of testing techniques for determining absorption of fine lightweight aggregate, (10) 286*g*.

Helmuth, R. A. Capillary size restrictions on ice formation in hardened portland cement pastes, B (5) 149*j*.

Helvenston, E. P. See Edmonds, B. P.

Helwig, W. C. See Chu, G. P. K.

Hemmenway, K. See Shankland, T. J.

Hemperle, R. See Hauptman, Z.

Hemstreet, H. S. Interference goniometer, P (8) 224*b*.

Henderson, C. M. Spark plug, P (3) 76*a*.

Henderson, C. M., and Harris, D. M. Thermoelectricity, P (7) 194*e*, P (8) 221*c*.

Henderson, C. M., and Stavrolakis, J. A. Method of sintering uranium dioxide, P (8) 216*h*.

Henderson, D. M., and Gutowsky, H. S. Nuclear magnetic resonance determination of the hydrogen positions in $Ca(OH)_2$, (7) 199*a*.

Hendrix, G. S. See Mulford, R. N. R.

Henley, P. E. Machine for cutting vitrified clay pipe, P (8) 212*a*.

Henneke, H. L. Indium antimonide transistor, P (11) 311*h*.

Hennicke, H. W. Experience with an oil-fired round kiln, (2) 53*g*. Torsional behavior of fine ceramic bodies at high temperature, (7) 196*b*.

Hennig, G. R. Review of radiation damage to graphite, (8) 214*g*.

Hennig, R. J. See Stanford, R. E. L.

Henning, F. E. See Boicey, J. H.

Henry, C. R. Water treatment, P (3) 80*c*.

Henry, W. E. Magnetization studies and possible magnetic structure of barium ferrate III, (4) 116*f*.

Hensel, W. C. Insulated chamber, P (6) 162*d*.

Hensler, J. R. Influence of excess oxygen in glass, B (11) 320*g*. See Aboaf, J. A.

Hensley, E. B. See Okumara, K.; Reiling, G. H.

Hentschel, E., Meyer, A. F., and Wichmann, D. Application of the Hall effect for the point-by-point measurement of magnetic fields, (9) 246*j*.

Herak, M. J., and Mirnik, M. Determination of ion adsorption by radioactive tracer technique (III) coagulating ion adsorption-desorption equilibria on negative AgI precipitates, (3) 86*d*.

Herbert, G. M. See Thoma, R. E.

Herbert Simpson Corp. Mulling and mixing apparatus, P (8) 222*e*.

Herbst, S. Further development of electrical tunnel kilns with heat recovery in the ceramic industry, (2) 53*k*, (10) 287*h*.

Hercules Powder Co. Mineral fiber [paper] products and method of preparing them, P (3) 70*a*.

Herdan, G. Statistical element in micromeritics, (5) 139*e*.

Herfeldt, B. Treatment of tuffaceous ash, P (3) 85*d*.

Herinckx, C., Offergeld, G. R., and Van Cakenberghe, J. L. Thermoelectric materials, P (5) 137*g*.

Herkart, P. G., Kestigian, M., and Yocum, P. N. Research on laser materials, (10) 281*f*.

Herlet, A., Spenke, E., and Emeis, R. Electric semiconductor device, P (4) 105*f*.

Hermann, C. E. Rock crusher, P (2) 56*a*.

Hermann, R. Strength of stoneware pipe, (8) 212*a*.

Hermans, M. E. A., and Plas, T. van der. Process for the preparation of granular uraniferous material of uniform particle size, P (10) 277*e*.

Hernaiz Bermudez de Castro, M. See Martin Vivaldi, J. L.

Hernandez, J. M. C. See Caceres Hernandez, J. M.

Herod, B. C. Lehigh's third-generation Indiana mill, (6) 154*h*. Medusa modernizes all phases at Dixon, (2) 35*e*. Ohio lime producer aims at a premium market, (10) 288*h*. Standard Lime and Cement Co.—Ohio plant takes place among industry leaders, (10) 289*a*.

Herrmann, E. R., and Cutler, I. B. Kinetics of slip casting, (5) 144*c*.

Herron, H. R. Tunnel kiln car top [with interlocking tile], P (10) 288*c*.

Herron, R. H., Vogan, J. W., and Scruggs, D. M. High temperature antifriction seal, material, and method of making, P (2) 45*h*.

Herz, J. H. Process sequence interlocking including motion switching and bin level detection, (5) 126*g*. See Adams, G. E.; Romig, J. R.

Herz, J. H., and Romig, J. R. Kiln automatic control method and apparatus, P (9) 237*h*.

Herzog, F. Polarization interferometric methods in incident-light microscopy, with special reference to material testing, (11) 313*b*.

Hesselbarth, H. See Lehmann, H. A.

Hesser, F., Maschinenfabrik Akt.-Ges. Apparatus for discharging bulk material in granular or powdery state, P (1) 23*e*.

Hessinger, P. S. See Froemel, J. G.

Hessinger, P. S., and Weber, T. W. Method of making synthetic mica, P (8) 220*f*, P (9) 249*b*.

Hetherington, G. See Bell, T.

Hetherington, G., and Jack, K. H. Water in vitreous silica (I) influence of "water" content on the properties of vitreous silica, (3) 68*i*.

Heuer, R. P. Basic refractory [metal encased] brick and method, P (9) 244*g*. Brick package, P (3) 73*h*. Refractory brick and method of molding, P (1) 17*c*. Refractory roof [with suspended arch], P (3) 74*i*. Ribbed basic refractory roof, P (10) 277*h*.

Heuschkel, H. Electrostatic spraying of atomized material, P (1) 5*a*.

Heynes, M. S. R. See Tuite, G.

Hicklin, W. H. See Belser, R. B.

Hickling, N., Cuttitta, F., and Meyrowitz, R. N,N-dimethylformamide, a new diluent for bromoform used as a heavy liquid, (4) 107*c*.

Hickman, B. S., Sabine, T. M., and Coyle, R. A. X-ray diffraction studies of irradiated beryllium oxide, (1) 31*b*.

Hicks, J. W., Jr. Light-conducting fibers, P (3) 69*b*.

Hicks, J. W., Jr., and Bazinet, W. P., Jr. Method for shaping a fiber optical device, P (1) 12*a*.

Hida, I. See Chujo, K.; Homma, E.

Hidalgo, H. Ablation of glassy material around blunt bodies of revolution, (1) 5*d*.

Hidalgo, H., and Kadanoff, L. P. Comparison between theory and flight ablation data, (6) 156*c*.

Hielscher, P. See Walther, H.

Hiester, N. K., and DeLaRue, R. E. Image furnace as a research tool, (1) 28*i*.

Higgins, J. V. Package construction for glassware, etc., P (3) 70*c*. Pattern for a designer, (9) 236*g*.

Highberg, C. W. Diamond grit performance, (6) 153*e*.

Hijikata, K., and Miyake, K. Sintering of alumina (I) effect of particle size and atmosphere on sintering, (7) 200*c*; (II) effect of magnesia as additive, (7) 200*e*.

Hijikata, K., and Tajima, Y. Some effects of atmosphere on the sintering process of iron-carbon compacts, (7) 200*b*.

Hiki, Y. Internal friction of quartz, (6) 173*j*.

Hildreth, C. L. Titanium compounds and processes of producing them, P (3) 85*a*.
Hilger and Watts, Ltd. X-ray beam intensity responsive sequential spectrometer, P (6) 176*c*.
Hilgers, G., and Bettermann, G. A. Oil gas for the ceramic industry, (9) 253*c*.
Hilker, H. W. Meters monitor rotary kilns, (2) 35*h*.
Hill, D. C. See Handwerk, J. H.
Hill, D. E., and Epstein, A. S. Thermoelectricity, P (6) 166*h*.
Hill, G. Quality control in the ceramic industries, (10) 298*d*.
Hill, J. S. Composite material of platinum alloy and glass, P (3) 77*d*. Composite material and thermocouple made therefrom, P (1) 24*a*. Material for handling molten glass, P (3) 69*e*. Method of making an electrical resistance device, P (7) 183*j*. Thermocouple, P (11) 314*a*.
Hill, R. A., and Stirling, A. W. Junction ceramic capacitor, (9) 247*j*.
Hill, T. E., Jr. See Calhoun, W. A.
Hill, U. T. Method and apparatus for automatic control of acid concentration in pickling system, P (5) 128*a*.
Hill, V. L. Thermocouple, P (8) 224*d*.
Hill, W. E., Jr. See Ives, W.
Hillig, W. B. Creation and stability of pyramidal hardness impressions on glass, B (11) 320*j*. Sources of weakness and the ultimate strength of brittle amorphous solids, B (9) 263*i*.
Himmelstein, P., Liebmann, B., and Schaefer, L. Manufacture and treatment of uranium monocarbide for fuel elements, (10) 275*f*.
Hinckley, A. T. Electrode structures and processes for utilizing them, P (5) 133*h*.
Hinckley, D. N. X-ray spectrographic method for measuring base exchange capacity, (6) 168*g*.
Hinckley, D. N., and Bates, T. F. Evaluation of the amount and distribution of montmorillonite in some Georgia and South Carolina kaolins, B (3) 91*g*.
Hind, S. R. Gel strength of glaze suspensions and the Bingham concept, (3) 75*h*.
Hines, D. P. Temperature reference block, P (4) 108*c*.
Hinkle, J. H., Jr. Aluminum and sodium aluminum fluorides, P (3) 83*c*.
Hinshaw, M. W. Method of making a cutting apparatus, P (5) 125*g*.
Hinson, A. L. Method and apparatus for cleaning small glass containers, P (4) 100*b*.
Hinz, A. See Bielenberg, W.
Hinz, I. See Dietzel, A.
Hinz, I., and Dietzel, A. Phase change of various samples of zirconia, (3) 88*c*.
Hiorns, F. J. Apparatus for the disintegration of solid particles, P (5) 140*j*.
Hirai, M. See Ishii, E.
Hirakawa, K. See Tsubota, H.
Hirano, S., and Sasuga, H. Quantitative determination of sodium and potassium in glasses and silicates by X-ray diffraction, (2) 40*i*.
Hiraoka, G., and Mori, M. Calcining temperature and reactivity of lime, (7) 178*j*.
Hirayama, C., and Berg, D. Dielectric properties of glasses in the system Nb_2O_5–Na_2O–SiO_2, (4) 98*a*. Dielectric properties of glasses in the system TiO_2–Na_2O–SiO_2, (1) 6*b*.
Hirayama, C., and Subbarao, E. C. Dielectric properties of bismuth borate glasses, (3) 66*f*.
Hirose, K., Mochizuki, M., and Nakashima, K. Relation between the content of sulfur in heavy oil and that of sulfur trioxide in cement clinker, (7) 181*i*.
Hirota, E., and Kubota, B. Magnetic property of Cr_2O_3, (4) 116*c*.
Hirota, M., Kitakaze, H., and Seki, K. Automatic recorder of particle size distribution determined by the sedimentation method, (8) 222*h*.
Hirsch, H. H. See Weber, C. E.
Hirthe, W. M. See Greener, E. H.
Hirthe, W. M., Adsit, N. R., and Brittain, J. O. Dislocations and plastic deformation in titanium oxide single crystals, B (9) 262*a*.
Hirthe, W. M., and Brittain, J. O. Dislocations in rutile as revealed by the etch-pit technique, (1) 27*a*. High-temperature steady-state creep in rutile, (10) 293*b*.
Hiyama, S. See Nagai, S.; Suzuki, K.
Hloch, J. Means of depositing metal compounds on glass for decoration purposes, P (10) 272*f*.
Ho, S.-M. See Lin, F. C.
Hobbs D. S. Particle counting [scanning] apparatus, P (8) 224*a*.
Hobin, J. L. Thermometer construction, P (5) 131*h*.
Hoch, M. Thermodynamic investigation of ceramic materials at elevated temperatures, (9) 257*c*. See Vardi, J.
Hoch, M., and Vardi, J. Thermal conductivity of TiC, (7) 189*d*.
Hochman, R. F. See Kuczynski, G. C.
Hockings, E. F. Thermoelectric compositions and devices utilizing them, P (3) 79*b*.
Hockings, E. F., and Mularz, W. L. Lead telluride-tin telluride thermoelectric compositions and devices, P (5) 136*h*.
Hodge, A. L. See Humphries, J. J.
Hodges, J. A. Influence of crucible material on the induced anisotropy of evaporated iron films, (10) 274*e*.
Hodgson, B. P. See McMillan, P. W.
Hodgson, J. F. See Tiller, K. G.
Hodgson, J. F., and Tiller, K. G. Location of bound cobalt on 2:1 layer silicates, B (5) 150*h*.
Hoeganaes Development Co., Ltd. Method for manufacturing resin-bonded products made from inorganic fibers, P (1) 12*e*.
Hoegberg, E. Investigations on adhesion [of mortar to wall tile], (3) 75*d*.
Hoehn, W. G., Forslund, H. B., and Fulton, J. W. Process for coating ferrous material and material coated, P (5) 128*b*.
Hoehne, M. Changing dipoles in silver halogenides with divalent anion impurities, (3) 85*j*. Simplest defect dipole in silver halogenides with divalent anion impurities, (3) 88*c*.
Hoekstra, A. H., and Wanmaker, W. L. Method of increasing the light output of alkaline earth halophosphates, P (2) 49*b*.
Hoenig, C. L. See Neimark, L. A.
Hofer, H. See Schmid, A.
Hoffer, A. Low quartz—geometry of its structure framework in terms of the directed bond, (4) 115*j*.
Hoffman, L. C. Glass frit vehicle comprising normal butyl methacrylate polymer and monohydroxy aliphatic alcohol, P (7) 186*e*. Precision glaze resistors, (10) 281*i*. Thermofluid vehicles for preparation of ceramic coatings, P (6) 155*i*. Vitreous enamel, P (2) 38*e*. Vitreous enamel frit, P (3) 65*h*.
Hoffman, M. S. Brockway's Rosemount, Minn., plant—automation with functional simplicity, (10) 269*j*. Glass or ceramic-to-metal seals—Glass-Tite Industries offers both, (10) 280*c*. Investing in research pays off for Pacific Clay Products, (10) 273*f*.
Hoffman, W. S., and Pastorius, J. W. X-ray analysis and control of a cement plant raw mix (I, II), (6) 154*g*.
Hoffman Electronics Corp. Semiconductor device and method of making it, P (3) 79*b*.
Hoffmann, E. Dictionary for the Glass Industry, B (8) 231*h*.
Hoffmann, R. W. See Brindley, G. W.
Hoffmann, R. W., and Brindley, G. W. Adsorption of ethylene glycol and glycerol by montmorillonite, (4) 107*b*.
Hofmann, C. F. See Westervelt, D. C.
Hofmann, C. F., Vondracek, C. H., and Westervelt, D. C. High temperature electrical insulating tape, P (7) 190*h*.
Hofmann, F., Kroll, H., Liebmann, B., and Neumann, O. Manufacture of urania fuel elements by vibration and swaging, (10) 275*g*.
Hofmann, U. Chemical basis of ancient Greek vase painting, (1) 2*c*. Chemistry of the surface of silica and silicosis, (3) 90*c*. See Fruehauf, K.
Hofmann, U., Boehm, H. P., and Gromes, W. Dimensions of crystals of clay minerals, (4) 113*a*.
Hofmann, U., Morcos, S., and Schembra, F. W. Halloysite, the most strange mineral, (3) 82*c*.
Hofstadt, K. E. See Brendel, O.
Hofstetter, G. W. Porcelain enameling cost practices, (3) 65*h*.
Hoh, S. R. Conversion of thermal to electrical energy with ferroelectric materials, (10) 279*i*.
Holden, A. F. Control system for luminous wall furnace, P (5) 140*c*.
Holden, A. N., Hoyt, E. W., Cummings, W. V., and Zimmerman, D. L. Radiation damage to boron-containing control materials, B (8) 234*d*.
Holden, R. B. See Fuhrman, N.
Holdridge, D. A., and Ryder, S. H. Norwegian nepheline syenite, B (10) 300*c*.
Hole, F. D. See Glenn, R. C.
Holland, C. Cut your coated abrasives cost, (3) 63*e*.
Holland, I. J. Method of making a porous shape of sintered refractory material, P (10) 277*e*.
Holland, M. G. Thermal conductivity of several optical maser materials, (1) 30*e*.
Holland, R. S. Process for preparing phosphor grade metal sulfides, P (2) 50*g*.
Hollander, L. E., Jr. Active solid-state devices using anisotropic single crystal rutile, P (11) 311*a*. Contact isolated potentiometer, P (3) 77*e*.
Hollander, L. E., Jr., and Castro, P. L. Dielectric properties of single-crystal nonstoichiometric rutile (TiO_2), (5) 134*i*.
Hollinger, D. L., and Plant, H. T. High strength glass fibers development program, (9) 240*c*.
Hollinger, D. L., Plant, H. T., and Jordan, T. J. High strength glass fibers development program, (9) 240*d*.
Hollman, C. Ceramic containers for electric melting furnaces, especially salt-bath furnaces, P (6) 169*e*.
Holloway, D. G. See Brearley, W.
Holmberg, G. I. See Fahlstrom, A. H. H.
Holmes, P. E. M. Looking around some modern German factories—a report on the recent T.B.E. visit, (10) 273*f*.
Holmes, R. J. Synthetic and other manmade gems, (7) 202*a*.
Holmes, S. T. Porous foamed silicate products, P (10) 277*c*.
Holmes, W. H., Cox, R. W., Davies, E., and Rowden, E. Pink centers and black cores, (3) 71*c*.
Holt, P. F., and Young, D. K. Dust-feed mechanism suitable for fibrous dust, (3) 90*d*.
Holt, R. D., and Shand, R. L. Influence of various clays on the set and bubble structure of porcelain enamel, (2) 37*a*.
Holtz, F. C. High-temperature oxidation protective coatings for vanadium-base alloys, (8) 207*i*. See Rausch, J. J.
Homer, H. H., and Butler, K. H. Method of making halophosphate phosphors, P (9) 249*j*.
Homer, H. H., and Taubner, F. R. Method of coating a fluorescent lamp tube [with amorphous silica and phosphor], P (10) 272*d*.
Homma, E. Thermal expansion of hardened cement paste, (7) 182*g*.
Homma E., and Hida, I. Volume change of cement paste at early period of hydration, (7) 182*c*.
Homonnay, E. See Louden, W. C.
Honcia, G. See Harkort, D.
Honda, T. See Tanabe, I.
Honig, R. E. Simple portable ultrahigh-vacuum system for lab experiments, (2) 52*g*. Vapor pressure data for the solid and liquid elements, (5) 147*j*.
Hooker, T. Apparatus and process for continuous proportioning of multicomponent mixtures, P (7) 194*j*.
Hooker Chemical Corp. Aluminum and sodium aluminum fluorides, P (3) 83*c*. Apparatus and process for continuous proportioning of multicomponent mixtures, P (7) 194*j*. Method of pickling and coating with vitreous enamel, P (7) 184*a*. Salt bath for electrolytic cleaning of metals, P (10) 269*g*.
Hooper, H. O. See Bray, P. J.
Hoover, H. L., and Van Dyke, N. D. Ultrasonic delay line, P (1) 22*c*.
Hopkins, B. J., and Marden, A. J. Coloration of activated calcium oxide coated cathodes, (10) 279*h*.
Hopkins, H. C., Jr. See Bernsen, S. A.
Hopkins, R. W. Method of preparing glass, P (3) 70*b*, P (10) 272*f*. See Tooley, F. V.
Hoppe, R. See Schnering, H. G.
Hoppe, R., Lindecke, W., and Frorath, F. C. NaInS$_2$ and NaInSe$_2$, (4) 116*e*.
Hopper, R. T. How to apply noble metals to ceramics, (11) 312*a*.
Horak, F. A. See Cornelison, B.
Hori, J. Observations of growth patterns on SiC single crystals, (8) 229*b*.
Hori, M. Statistical aspects of fracture in concrete (II) statistical relation between fracture and creep properties of portland cement mortar in bending, (9) 237*g*.
Hori, M., and Asano, M. Strength of mortar placed in various media, (8) 206*a*.
Horibe, T., and Kuwabara, S. Rate of lattice contraction of the corundum of the brown electrofused alumina abrasive grains on heating in air, (9) 235*f*.
Horizons, Inc. Fiber forming process, P (7) 189*a*. Inorganic fibers, P (7) 189*c*. Method of making inorganic fibers, P (10) 277*c*. Method for producing inorganic [oxide] fibers, P (7) 189*f*. Preparation of sapphire fibers, P (6) 162*b*. Stable colloidal dispersions and method of preparing them, P (7) 190*a*.
Horlock, R. F. See Anderson, P. J.
Horn, F. H. Barium titanate crystals grown from the melt, (5) 141*j*. Preparation of single-crystal cobalt ferrites from the melt, (1) 19*g*.
Hornblower, W. J. See Schmidt, J. E.
Horne, R. See Benson, J. M.
Horne, R. W., McMorris, M. N., and Ottewill, R. H. Electron microscope studies on some inorganic crystals, B (9) 262*a*.
Hornstein, N. See Narboni, M.
Hortie, H. J. See Clark, J. S.
Horton, P. V. Method of fabricating an array of magnetic cores, P (5) 136*d*.
Horton, R. C. See Gusman, I. J.
Hosbein, J. W., and Barre, R. M. Roof or wall tile [interlocking], P (2) 46*g*.
Hoselitz, K. See Harrison, F. W.
Hosterman, J. W. See Patterson, S. H.
Hostetler, P. B. Stability and surface energy of brucite in water at 25°C, (7) 200*g*.
Hosticka, H. E. See Feldman, M. H.
Hounam, R. F. See Stevens, D. C.
Hove, J. E. Low temperature irradiation and annealing effects in graphite, (10) 294*g*.
Hovi, V., Mantysalo, E., and Ketolainen, P. Gyulai-Hartly effect in single crystals of potassium iodide at 77° to 297°K, B (9) 261*g*.
Howard, B. T. Vapor-solid diffusion of semiconductive material, P (3) 79*c*.
Howard, R. C. See Bernsen, S. A.
Howard Grubb Parsons & Co., Ltd. Infrared spectrometer recorder wherein the spectra is recorded on a linear wave-number scale, P (11) 320*a*.
Howarth, T. E. See Bush, D. R.
Howatt, G. N. Ceramic components and method of making them, P (1) 20*j*.
Howden, James, & Co., Ltd. See James Howden & Co., Ltd.
Howe, E. E. Composite [glass] coated muffler and method of making it, P (9) 239*c*.
Howe, H. W. Electron-beam furnace with opposed-field magnetic beam guidance, P (8) 223*h*.
Howe Sound Co. Disposable pattern with lower melting external coating, P (3) 73*i*. Making refractory shell molds, P (1) 16*f*.
Howell, P. A. Process for producing molecular sieves, P (11) 315*e*. Refinement of the cation positions in synthetic zeolite, type A, (10) 296*f*.
Howell, R. G. See Grego, P.
Howell, S. N. Direct-reading [radiation type] pyrometer microscope, P (7) 196*b*.
Howell Instruments, Inc. Apparatus for testing heat responsive devices, P (4) 108*c*.
Hower, L. D., Jr. See Fuhrman, N.
Howerton, H. K. Spectro-phosphorescence measuring instrument, P (9) 252*h*.
Howie, R. A. See Deer, W. A.
Hoyer, N. S. See Gwyn, C. B., Jr

Hoyt, E. W. See Holden, A. N.
Hrabak, G. C. See Schweitzer, D. G.
Hrizo, J. See Subbarao, E. C.; Tien, T. Y.
Hrizo, J., and Subbarao, E. C. Sample holder for dielectric measurements up to 700°C, (10) 282*b*.
Hruby, J. Possibilities of using screen printing for dulling glass, (11) 304*e*.
Hsi, H.-R., and Clifton, D. F. Flocculation of selected clays by various electrolytes, B (5) 150*e*.
Hsu, P. H., and Rennie, D. A. Reactions of phosphate in aluminum systems (I) adsorption of phosphate by X-ray amorphous "aluminum hydroxide,"; (II) precipitation of phosphate by exchangeable aluminum on a cation exchange resins (5) 145*j*.
Huang, S. See Lewis, J.
Hub, W. See Kaufmann, W.
Hubbell, D. S., and Weaver, E. P. Porcelain enamel slip and method for preparing it, P (6) 155*e*.
Hubbell, J. W. See Cowley, C. H.
Hubble, D. H., and Powers, W. H. High-fired basic brick for open-hearth roofs, (8) 213*c*.
Huckstepp, L. D., and Day, G. V. Processing of enriched uranium oxide-paraffin wax mixtures, (1) 29*i*.
Hudgens, C. R. See Eichelberger, J. F.
Hudson, J. B. Nucleation of Zn on glass, (9) 241*c*.
Hueesker, M. See Schaefer, H.
Huettenwerk Rheinhausen Akt.-Ges. Hardening of blanks for smelter blocks containing glass-containing ground slag, P (3) 74*a*.
Huetter, L. J., and Stadelmaier, H. H. Ternary carbides of transition metals with aluminum and magnesium, (4) 101*h*.
Huettig, W. Surface preparation for aluminum alloys to be enameled, P (4) 97*j*. Technical hints on the enameling of aluminum and its alloys, (10) 269*i*. See Ginsberg, H.
Huffadine, J. B. See Davies, W. J. K.; Moore, N. C.
Huffine, C. See Sears, G. W.
Huggins, C. W. Electron micrographs of some unusual inorganic fibers, (3) 86*e*. See Alley, J. K.
Huggins, R. A. See Dils, R. R.; Stiefbold, D. R.
Hughan, R. R. Lubricant aids in the manufacture of silica and magnesia refractories, (1) 13*i*.
Hughes, G. See Bickerdike, R. L.
Hughes, J. E., and Ratcliffe, R. Metallographic technique for ferrites, (1) 19*b*.
Hughes, O. H. See Branwood, A.
Hughes, W. See Strain, F.
Hughes, W., and Arkless, K. Process for reducing the acidity of oxides, P (2) 55*e*.
Hughes, W. E., and Kremenek, C. R. 70-Gc maser, (10) 282*e*.
Hughes Aircraft Co. Flexible electroluminescent strand, P (1) 21*b*. Low loss, high Curie temperature ferrites for high power applications, P (1) 21*e*. Pyrometer [radiation], P (2) 53*c*. Storage target, P (8) 221*b*.
Hukki, R. T. Grinding at supercritical speeds, (1) 22*h*.
Hukuo, N., Kozuka, T., Fujishiro, I., and Yoshida, M. Measurement of temperature in solar furnace (I), (2) 52*a*.
Hulse, C. O., Copley, S. M., and Paak, J. A. Effect of crystal orientation on plastic deformation of magnesium oxide, (9) 256*a*.
Hume, L. N. Report from America on Tudor and early Stuart glasses found in London, (6) 153*j*.
Hummel, F. A. See Argyle, J. F.
Humphrey, W. G. See Heck, I. A.
Humphreys, J. Planned maintenance, (1) 31*f*.
Humphries, J. J., Hodge, A. L., Babcock, R. S., and Whitmore, B. C. Process for the manufacture of cement, P (5) 127*a*.
Humpola, H. Determination of free lime in clinker, (9) 236*g*. Nephelometric and turbidimetric determination of SO_3 content in silicates, (9) 237*a*.
Hund, F. Mixed-phase pigments with rutile structures, (1) 18*i*. Process for producing ferrites, P (7) 194*d*. Process for the production of isometric ferromagnetic gamma ferric oxide, P (7) 194*f*.
Hund, F., and Deissmann, W. Crystalline solid solutions with silicon dioxide structures as host components, P (9) 246*c*.
Hunt, C. M. Infrared absorption spectra of some compounds in the CaO–SiO_2–H_2O system, B (5) 149*f*.
Hunt, J. G., and Russell, R. B. Texture in hot extruded BeO, (1) 30*d*.
Hunt, R., and Ellison, M. New slow running personal dust sampler, (6) 168*e*.
Hunter, F. M. Heat resistant electrically conducting compositions, method of coating articles therewith, and articles produced, P (11) 311*f*.
Hunter, J. L. See Greene, E. W.
Hunter, R. S. Tests for the uniformity of 45° 0° reflectometers, (6) 168*f*.
Hunting Mhoglas, Ltd. Method of making non-metallic electric resistance elements, P (7) 193*i*.
Huntress, H. B. Powder metallurgy, P (5) 133*e*.
Hupp, A. G. Apparatus for breaking glass strands, P (3) 68*c*. Plastic glass breaker depositor, P (3) 70*c*.
Huppert, P. A. Modern enameling methods, B (11) 322*d*. New aspects in ceramic coatings, (1) 4*j*.
Hurd, E. G. Cathode bar for aluminum reduction cell, P (8) 215*f*.
Hurd, J. D. See Branwood, A.
Hurko, B. Multilayer film heaters in strip form, P (9) 249*b*.
Hurlbut, C. S., Jr. Tephroite from Franklin, New Jersey, (4) 110*i*.
Hurley, F. R. See MacCallum, R. B.
Hurst, E. Abrasive articles and methods of making them, P (1) 1*j*.
Hurst, G. P. Wire rope connector and kiln structure, P (10) 268*c*.
Hustinx, E. Glass manufacture from silicates, P (2) 42*i*. Manufacture of glass, P (3) 69*d*.
Husum, C. W. Conveyer, P (8) 221*g*.
Huta im. Lenina. Alkali-bonded unfired refractories, P (2) 45*i*. Refractories for metal casting, P (2) 46*c*.
Hutson, A. R. Piezoelectric devices utilizing aluminum nitride, P (9) 249*c*. Piezoelectric devices utilizing cadmium sulfide, P (9) 249*d*. Piezoelectric devices utilizing zinc oxide, P (9) 249*d*.
Hutter, J. F., Kelly, L., Mounce, G. R., and Leaver, E. W. Materials sorting apparatus, P (5) 141*d*. Quantitative photometric [ore] materials sorter, P (10) 290*e*.
Hutton, R. F. See Rigby, G. R.
Hutton, U. O. See Lloyd, E. C.
Hyodo, S. Possibility of supervelocity of glass fracture, (8) 209*i*.

Iacob, C. See Petri, L.
Ibuki, S. Crystal growth of cadmium sulfide, (6) 172*f*.
Ichiba, S. Use of radioactive fission product rare gases for the study of the phase change in fine particles—crystal structure change of γ-hematite to α-hematite, (6) 176*a*.
Ichikawa, Y., and Carlson, W. G. Yttrium-doped ferroelectric solid solutions with positive temperature coefficients of resistance, (6) 165*b*.
I.C.P.M. S.p.A. Industrie Chimiche Porto Marghera. See Industrie Chimiche Porto Marghera S.p.A.
Idorn, G. M. See Bredsdorff, P.
Iga, T. See Kato, S.
Ihlefeld, K. H. Expanded clay, P (4) 100*h*.
Iida, S. See Inoue, T.
Ijima, Y. See Murakami, K.
Ikeda, S. See Kusaka, Y.
Ikeda, T. Quaternary systems of perovskite type $A^{2+}B^{4+}O_3$ solid solutions, (6) 175*a*. Studies on the $(Ba,Pb)(Ti,Zr)O_3$ system, (7) 200*i*.
Ikenoue, T. See Ohba, H.
Ikornikova, N. Yu. Crystallization of carbonates from aqueous solutions of chlorides, B (9) 263*e*.
Ikornikova, N. Yu., and Butuzov, V. P. Hydrothermal synthesis of calcite, (5) 144*e*.
Il'in, N. P. See Bagdasarov, Kh. S.
Illing, A. M. Pressing defects in ceramic tile, (9) 245*j*.
Illinger, K. Dispersion and absorption of microwaves in gases and liquids, B (9) 263*h*.
Illinois Testing Laboratories, Inc. Pulsed resistance thermometers, P (5) 139*j*.
Imai, I. See Ishiguro, K.
Imamura, T. See Oki, S.
Imaoka, M., and Yamazaki, T. Optical properties of borate glass, (8) 209*f*. Refractive index and Abbe number of glass of the lanthanum borate system, (11) 304*f*.
Imarisio, G. Recent advances in the preparation of sinterable uranium dioxide, (5) 140*i*.
Imperial Chemical Industries, Ltd. Wall plasters and their preparation, P (2) 36*b*.
Ince, N. S. See Cornelison, B.
Indenbom, V. L. See Kitaigorodskii, I. I.
Indevco, Ltd. Supports for aerating particulate materials, P (11) 312*f*.
Indiana General Corp. Machines for testing and sorting ferromagnetic cores, P (2) 49*e*.
Indugas, Gesellschaft fuer Industrielle Gasverwendung m.b.H. Cooled furnace transport rollers, P (11) 314*e*.
Industrial Development Co. Establishment. Apparatus for producing fibers from mineral materials, P (3) 68*h*.
Industrial Nucleonics Corp. Conveyor speed control by measuring material level, P (3) 80*b*.
Industrial Powertronix, Inc. Flow measuring and dividing system, P (2) 51*b*. Supersonic vibrating drying system, P (8) 222*b*.
Industrie Chimiche Porto Marghera S.p.A. Process for preparation of artificial cryolite, P (1) 26*b*.
Ingenieurburo Kaswant. Modern process and installation for the refining of glass, (1) 8*b*.
Ingersoll-Rand Co. Method of making holes in the earth, P (10) 289*d*.
Ingham, H. S., Jr. Formation of semiconductor bodies, P (10) 282*g*.
Ingham, M. G. See Grimley, R. T.
Ingraham, J. N., and Swoboda, T. J. Ferromagnetic chromium oxides containing fluorine and their preparation, P (4) 105*c*.
Ingram, B. L. See Milton, C.
Ingram, J. W. Graph showing actual surface feet per minute, (9) 235*i*.
Ingri, N., and Lundgren, G. Crystal structure of $NaGe_9O_{20}$, (10) 291*c*.
Ingri, N., and Schorsch, G. Determination of the formation constants of $GeO_2(OH)_2^{2-}$ using a hydrogen electrode—measurements in 3 *M* Na(Cl) medium, (10) 291*e*.
Inland Steel Co. Method and apparatus for automatic control of acid concentration in pickling system, P (5) 128*a*. Method of inhibiting corrosion, P (1) 5*b*.
Inman, D., and Bockris, J. O'M. Complex ions in molten salts—a galvanostatic study, (10) 291*c*.
Innes, J. A. See Callcott, T. G.
Inomata, Y. See Uchikawa, H.
Inoue, K. Method of producing semiconductors and semiconductor elements utilizing electric spark discharge, P (3) 78*j*. See Okuda, S.
Inoue, N. See Moriya, T.
Inoue, T., and Iida, S. Specific heat of copper ferrite, (7) 200*e*.
Inoue, Y. See Asano, S.; Mori, H.
Inoue, Y., Asano, S., Abe, E., and Kinoshita, N. Percentage of voids in cement mortar, (7) 181*d*.
Inowaki, S. See Ishikawa, Y.
Insley, H. See Thoma, R. E.
Institut de Recherches de la Siderurgie Francaise. Porous refractory concrete element, P (1) 17*a*.
Interchemical Corp. Gold colored metallic pigments, P (3) 83*h*.
International Business Machines Corp. Compound semiconductor material control, P (3) 77*d*. Diffusion in semiconductor material, P (4) 105*d*. Evaporation method, P (2) 48*i*. Formation of semiconductor bodies, P (10) 282*g*. Formation of semiconductor devices, P (11) 311*d*. Low flux density ferromagnetic material, P (3) 77*g*. Method of fabricating an array of magnetic cores, P (5) 136*d*. Method of forming memory arrays, P (6) 166*i*. Method of producing ferrite bodies, P (7) 194*c*. Methods of etching a semiconductor device [electrolytically and ultrasonically], P (8) 220*h*. Semiconductor body formation, P (5) 137*h*. Semiconductor devices, P (3) 70*d*. Specimen identification apparatus and method, P (3) 89*j*. Square loop magnetic manganese ferrite material and manufacture thereof, P (2) 50*a*. Thin magnetic films, P (2) 50*c*. Vapor deposition of heavily doped semiconductor material, P (3) 79*c*.
International Harvester Co. Thickness gage for blast furnace wall, P (6) 169*e*.
International Minerals & Chemical Corp. Coarse screening dry particulate materials, P (5) 141*b*. Electrostatic separation in nonuniform field, P (2) 55*h*. Method for the purification of potassium carbonate, P (6) 171*c*. Process for beneficiating potash spar, P (5) 141*g*. Production of potassium fluosilicate, P (7) 198*b*. Wet beneficiating of phosphate ores, P (8) 226*c*.
International Radiant Corp. Gas-fueled infrared generator, P (8) 224*h*.
International Resistance Co. Pyrolytically decomposed resistor consisting of the elements carbon, oxygen, and silicon, P (5) 137*f*.
International Standard Electric Corp. Manganese ferrites, P (3) 77*i*.
International Telephone and Telegraph Corp. Dielectric materials and processes of manufacturing them, P (3) 77*h*. Method of joining a semiconductor to a conductor, P (3) 78*c*. Method and means for growing and treating crystals, P (8) 225*g*.
International Ytong-Stabalite Co., Ltd. Method for dividing bodies of lightweight concrete, P (3) 65*a*.
Interplanetary Research & Development Corp. Apparatus for the electrostatic coating of articles, P (1) 4*h*.
Inzigneri, M., and Peco, G. Influence of glaze under different stress degrees on the mechanical strength of vitrified ceramic bodies, B (10) 300*c*.
Ioffe, A. F. Two mechanisms for the motion of free charges, (7) 192*h*.
Iowa State College Research Foundation. Reductive decomposition of the calcium sulfate, P (8) 206*e*.
Ironman, R. Automatic vertical cement kiln—50 years later, (2) 34*d*.
Isakower, R. Graph simplifies calculation of laws of refraction, (4) 107*h*.
Isard, J. O. Symposium on control of the quality of glassware: Determination of composition from routine physical property measurements, (9) 241*j*. See Milnes, G. C.; Savage, J. A.
Ishida, K. Correlations for ternary liquid equilibria, (1) 27*c*.
Ishiguro, K., Sasaki T., Arai, T., and Imai, I. Optical and electrical properties of tin oxide films, (6) 174*e*.
Ishihara, Y. See Enomoto, S.
Ishii, E., Sugiura, M., Sano, S., and Hirai, M. Forsterite porcelain as a high frequency insulator (XI) quantitative analysis of the minerals existing in the process of the synthesis of forsterite, (1) 18*a*.
Ishii, S. See Tada, T.
Ishii, Z., Furuoya, T., Sasaki, Y., and Kohra, K. Observation of layer structure in dislocation-free silicon crystals by the use of X-ray anomalous transmission, (6) 174*b*.
Ishikawa, A., and Kawahito, T. Properties of cement mortar containing polyvinyl acetate emulsion, (8) 205*h*.
Ishikawa, T. See Matsushita, T.
Ishikawa, Y. Order-disorder transformation phenomenon in the $FeTiO_3$–Fe_2O_3 solid solution series, (6) 174*g*. See Shirane, G.
Ishikawa, Y., and Akimoto, S. Magnetic property and crystal chemistry of the ilmenite ($MeTiO_3$) and hematite (α-Fe_2O_3) system (I) crystal chemistry; (II) magnetic property, (6) 173*b*.
Ishikawa, Y., and Chikazumi, S. Design of high power electromagnets, (8) 218*j*.
Ishikawa, Y., Sasaki, Y., Seki, Y., and Inowaki, S. Rectifying action and electromotive force of films of Ta_2O_5 and SiO_2 at high temperatures, (10) 281*e*.

Ish-Shalom, M., and Greenberg, S. A. Rheology of fresh portland cement pastes, B (5) 149*i*.
Iskol'dskii, I. I., and Bogorodskaya, L. P. Possibility of preparing metalloceramic hard alloys based on the borides of chromium, titanium, and tungsten, (4) 118*c*.
Isomoto, M. See Tada, T.
Isupov, V. A. See Smolenskii, G. A.
Ito, Y. See Hayashi, M.; Terada, S.
Ivanov, A. O. See Evstrop'ev, K. S.
Ivanov, I. A. Influence of the gaseous phase on magnesite calcination (compositions with acid additions), (6) 159*j*.
Ivanov, M. F. See Demkina, L. I.
Ivanova, E. A. Colored glass, P (2) 41*j*.
Ivanova, N. I., and Zhukovskii, A. P. Luminescence centers of alkali halide phosphors doped with divalent metals, (5) 135*g*.
Ivantsov, G. P. Thermal and diffusion processes in crystal growth (II), B (9) 262*c*.
Ivensen, V. A., Koval'skii, A. E., Semenovskaya, S. V., and Eidule, O. N. Anisotropy of the elastic properties of the monocarbide of tungsten, (2) 56*d*.
Ives, W., and Hill, W. E., Jr. Occurrence and bleaching properties of some Kansas montmorillonite clays, (3) 82*h*.
Ives, W., and Runnels, R. T. Lime raw materials in the Kansas City area, (3) 64*h*.
Ivoilov, A. S., and Denisova, L. L. X-ray method for the determination of the quartz content of mineral mixtures, (9) 252*b*.
Iwai, T. Temperature dependence of the optical absorption edge of tungsten trioxide single crystal, (5) 146*f*.
Iwamoto, K. Measurements of UO_2 particle size distribution by radioactivation, (6) 173*f*.
Iwanaga, H. See Shibata, N.
Iwata, S. See Kobayashi, T.
Izui, K. Observations of lattice defects in graphite by moire patterns, (6) 174*c*.
Izumi, G., Kita, M., and Mitsuki, C. Aliphatic amines as molding aids for ceramic powders, (8) 217*d*.
Izumitani, T., and Moriya, Y. Devitrification of optical glasses, (11) 303*g*.
Izumitani, T., and Ogawa, H. Striae in new optical glasses (II) surface tension of striae, (5) 130*d*.
Izumitani, T., and Terai, R. Formation and growth of bubbles in the process of glass melting, (11) 303*h*.
Izumitani, T., Terai, R., and Ogawa, H. Striae in new optical glasses (I) densities and refractive indices of the striae, (5) 130*b*.

Jack, H. R. S., Jacquest, J. A. T., and Rothwell, G. Melting of glass batch, P (6) 157*i*.
Jack, K. H. See Bell, T.; Hetherington, G.
Jack, M. K., and Wierman, E. T. Low loss, high Curie temperature ferrites for high power applications, P (1) 21*e*.
Jackering, G. Apparatus for fine grinding, P (4) 106*i*.
Jackson, A. Refractories in the Ajax furnace, (6) 161*b*.
Jackson, C. E. Submerged melt welding process and composition, P (6) 155*i*.
Jackson, J. M. See Carpenter, V. W.
Jackson, M. L. Significance of kaolinite intersalation in clay mineral analysis, B (5) 150*i*. See Dixon, J. B.; Glenn, R. C.
Jacob, H. See Enk, E.
Jacob, P. See Traustel, S.
Jacob, P. J. See Lehmann, H.
Jacobs, C. W. F. New viewpoints on opacification with zirconium compounds, (9) 245*i*.
Jacobs, G., and Melcher, A. Source of radiation for infrared spectrophotometers, P (11) 320*b*.
Jacobs, P. W. M. See Allnatt, A. R.
Jacobsen, G. W. See Brown, R. W.
Jacobsen, K. Chinese porcelain in Danish collections, (6) 153*j*.
Jacobson, M. G., and De Luca, F. J. Electrochemical determination of components in gas mixtures, P(1) 24*b*.
Jacquest, J. A. T. See Jack, H. R. S.
Jadrnicek, V. Advantages and disadvantages of ceramic and plastic wall tile, (9) 245*h*.
Jaeger, G., and Ahrens, F. Artificial gems, P (4) 121*h*.
Jaerse, B. Thixotropy, (3) 89*a*.
Jaffe, H. See Berlincourt, D.
Jahns, R. H. See Burnham, C. W.
Jaiswal, J. N. See Das Gupta, H. N.
Jakobsen, K., and Semb, T. K. Method of excavating rock, ore, etc., by blasting and means for use in the method [charge holder], P (11) 315*h*.
Jakobsson, P. A. H., and Ohrn, K. G. Method for dividing bodies of lightweight concrete or similar material, P (3) 65*a*.
James, D. R. Machines for printing or decorating [back stamping] articles of ware, P (10) 279*c*.
James, G. See Waye, B. E.
James, G. R. See Koniewiez, P.
James Howden & Co., Ltd. Dust separators, P (7) 195*b*.
James, R. A., and Ward, C. R. Process for drawing glass sheet, P (10) 272*j*.
James, R. P., and Nolan, R. W. Glass electrode, P (4) 99.
Jamieson, H. D. Pigments, P (1) 18*i*.
Jamison, W. B. Method for drying finely divided materials, P (2) 51*e*.
Jamnik, F., and Pelzl, A. Apparatus for forming profiled glass sheets, P (6) 157*d*.
Janakirama Rao, B. V. See Rao, B. V. J.
Janes, M., and Taylor, S. A. Oxidation-resistant graphite article and method, P (3) 74*i*.
Janninck, R. F., and Whitmore, D. H. Electrical conduction in nonstoichiometric α-Nb_2O_5, (9) 256*f*.
Jansen, M. J. See Lemmens, H. J.
Janssen, G. H. See Haaijman, P. W.
Jantzen, O. Magnetic and dielectric properties in the transformation series $Fe_2O_3 \rightarrow \gamma$-$Fe_2O_3 \rightarrow \alpha$-$Fe_2O_3$, (9) 247*g*.
Janz, G. J., and Lorenz, M. R. Solid-liquid phase equilibria for mixtures of lithium, sodium, and potassium carbonates, (1) 30*c*.
Jarrett, H. S., and Waring, R. K. Ferrimagnetic resonance in $NiMnO_3$, (4) 114*c*.
Jaunarajs, K. L. See Meyer, J. W.
Jax, K. M. Ceramic balls for grinding mills, P (4) 106*h*.
Jebsen-Marwedel, H. "Pathology" in technology—concept and program as a section of applied science, (1) 8*f*. Reply to discussion of "'Pathology' in technology," (1) 8*g*.
Jebsen-Marwedel, H., and Buss, W. Smelting of glass from normal batch constituents as observed in the high temperature microscope, (8) 209*j*.
Jeffery, J. W. See Chatterji, S.
Jenaer Glaswerk Schott & Gen. Optical glass, P (5) 131*c*, P (7) 186*g*. Optical glass free of thorium, P (6) 158*g*. Optical type glass compositions with high fluorine and titanium content, P (4) 100*a*. Transparent conductive reflection-reducing coatings on nonconductive objects and method, P (10) 273*b*.
Jenckel, L. Combined mass spectrometer and gas chromatograph recording apparatus, P (7) 201*i*.
Jendrisak, J. E. Glass sheet bending mold, P (10) 272*b*.
Jenkins, G. M. Effect of irradiation on strain in graphite, B (8) 233*i*.
Jenkins, I. L., and Keen, N. J. Use of tantalum borides for the containment of molten uranium and calcium, (11) 308*i*.
Jensen, J. E. G. Feeler element for a humidostat, P (2) 53*b*.
Jensen, W. L., Phillips, R. P., and Claussen, G. E. Metal arc welding, composition, and process, P (1) 5*c*.
Jersey Production Research Co. Cementing composition, P (6) 154*i*. Obtaining unaltered core samples, P (3) 84*d*.
Jeschar, R. Investigation and evaluation of an electrically heated multipassage kiln, (2) 53*e*.
Jeschke, P., and Schwiete, H. E. Thermal conductivity of magnesite brick, (3) 73*a*.
Jewett, R. P. See Voruz, T. A.
Jindra, J. See Eckstein, J.
Jitea, E. See Petri, I.
Jochems, P. J. W., Amstel, J. J. A. P. van, and Rinia, H. Method of producing semiconductor electrode systems, P (5) 136*h*.
Jochmann, F. Analytically determined fluorine contents of opaque glasses made with cryolite, fluorspar, and sodium fluosilicate—constants for use in calculating the composition from the batch, (3) 65*j*. Glassmaking—the hollow-glass maker, (1) 7*f*. Glassworks practice with heat-resistant opal boric acid-phosphate illuminating glass, (8) 208*i*.
Joensuu, O. I., and Suhr, N. H. Spectrochemical analysis of rocks, minerals, and related materials, (1) 30*e*.
Johannes, R. See Ramanathan, K.
Johannes, R., Ramanathan, K., Cholet, P., and Haas, W. Role of avalanching in cold emission devices, (10) 281*h*.
Johanningmeier, C. E. Coarse screening dry particulate materials, P (5) 141*b*.
John, H. F., and Faust, J. W., Jr. Semiconductor dendritic crystals, P (9) 249*f*.
Johns, H. L. See Beasley, R. M.
Johnsen, A. M. See Bard, A. L.
Johns-Manville Corp. Apparatus for attenuating glass fibers, P (3) 68*d*. Asbestos fibers in mine roof coatings, P (2) 55*b*. Bonding agent for dry air setting mortars, P (8) 215*f*. Calcium silicate product and method of preparing it, P (1) 25*f*. Continuous dry blender, P (9) 250*a*. Glass composition, P (1) 11*j*. Handleable heat insulation shapes, P (2) 45*g*. Lightweight castable refractories, P (6) 162*e*. Method and apparatus for continuously gathering fiber, P (5) 131*c*. Method and apparatus for producing glass fibers, P (3) 70*a*. Method of preparing inorganic products, P (10) 277*h*. Method of producing a battery separator and product thereof, P (8) 211*f*. Method of producing shaped asbestos-cement articles [pipe], P (10) 268*a*. Mounting for electrical resistance elements and method for preparing it, P (1) 16*h*. Punch for forming perforations in coated asbestos-cement sheets, P (6) 167*g*.
Johns-Manville Fiber Glass, Inc. Apparatus for making mats of blown mineral fibers, P (5) 130*b*. Apparatus for packaging stranded material, P (1) 10*i*. Fibrous mat and method of manufacture, P (7) 186*a*. Gas burner, P (1) 11*h*. Glass composition, P (8) 210*f*. High temperature pipe insulation and method of making it, P (1) 16*e*. Laminate and method of forming it, P (2) 42*j*. Method and apparatus for forming and collecting fibers into an improved pipe covering, P (3) 74*c*. Method of forming color-patterned glass fiber panels, P (3) 70*c*. Method of forming multiple strands from a single bushing, P (5) 131*i*. Method for producing a gaseous blast and for producing glass fibers, P (8) 211*g*. Process for combining glass fibers with synthetic resin fibers and product thereof, P (9) 242*b*. Process of making essentially pure silica fiber bats, P (9) 245*d*.
Johns-Manville Perlite Corp. Insulating material, etc., P (10) 277*b*.
Johnson, C. P., Jr. Optical pyrometer with photoelectric detector, P (2) 53*c*.
Johnson, D. A., Mallory, K. B., Miller, R. H., Pantell, R. H., and Szente, P. A. Small signal characteristics of ferroelectric ceramics at millimeter wavelengths, (7) 192*c*.
Johnson, D. P. See Lloyd, E. C.
Johnson, E. F. See Matsen, J. M.
Johnson, E. R., and Forten, J. Radiation-induced decomposition of inorganic nitrates, (10) 296*a*.
Johnson, E. S. Process for calcination of gypsum, P (7) 182*i*.
Johnson, F. M. Studies of the ion emitter beta eucryptite, (2) 59*c*.
Johnson, G. H. (editor). Ceramic-Metal Systems and Enamel Bibliography and Abstracts—1960–1961, B (1) 32*b*; 1962, B (9) 259*c*.
Johnson, H. S., Jr. See Robinson, G. C.
Johnson, H. V., and Kirkhart, F. P. Electrode joint, P (1) 16*a*.
Johnson, J. R. Method and apparatus for controlling distribution of plastic coatings on [glass] articles, P (2) 42*a*. Positive assist for loading articles [bottles] to a chuck, P (4) 100*b*. Thermally resistant articles and method for their fabrication, P (6) 162*j*. Uranium dioxide, (8) 215*a*.
Johnson, J. R., and Rowe, W. E. Fuel element recovery process, P (8) 216*d*.
Johnson, J. R., Voss, E. B., and Wright, F. S. Oven for treating articles, P (9) 250*e*.
Johnson, L. W. Screen [vibratory] deck construction, P (11) 312*d*.
Johnson, N. Constructional faience—current trends and future possibilities, (6) 158*i*.
Johnson, N. M., and Daniels, F. Luminescence during annealing and phase change in crystals, (2) 48*e*.
Johnson, P. D. Light sources, P (1) 21*d*. See Carpenter, H. W.
Johnson, P. G. See Fletcher, W. W.
Johnson, P. W. See Peters, F. A.
Johnson, R. C. See Alley, J. K.; Miller, J. L.
Johnson, R. E., and Mehal, E. W. Method of producing gallium or aluminum arsenides and phosphides, P (10) 283*b*.
Johnson, R. G. See Dungan, R. H.
Johnson, R. G. R. See McHugh, J. P.
Johnson, R. L., and Wheildon, W. M. Faster plasma coating, (6) 155*c*.
Johnson, W., and Andrews, K. W. Symposium on high-alumina refractories: Quantitative X-ray examination of aluminosilicates, (11) 306*b*.
Johnson, W. R., and Oakes, D. T. Clay beneficiation, P (4) 110*g*.
Johnson, W. T. K. Extended application of a cobalt glass dosimeter, (9) 240*f*.
Johnston, H. L. See Wade, W. S.
Johnston, J. E. Method and apparatus for reclaiming particles from a mixture, P (1) 11*j*. See Polanyi, M. L.
Johnston, L. B. Acoustical panel, P (6) 156*j*. Apparatus for withdrawing mandrels from tubular bodies, P (3) 69*a*. Method of producing [decorative] panels of fibrous glass, P (2) 42*d*.
Johnston, L. H. See Durig, J. R.
Johnston, R. M. Pitfalls in color specifications, (8) 230*i*.
Johnston, R. W., and Hall, R. D. Pneumatic abrasive cutting tool, P (1) 23*d*.
Johnston, T. L. Fracture mechanisms in crystalline ceramics, B (9) 259*f*.
Johnston, W. G. Dislocation etch pits in nonmetallic crystals, B (8) 232*b*.
Johnstone, J. O. See Wilke, W. P., III.
Jona, F., and Shirane, G. Ferroelectric Crystals, B (4) 123*e*.
Jonaitis, C. W. See Baarson, R. E.
Jonas, B., and Seitz, G. Bonding of glass parts especially of cathode-ray tubes, P (3) 69*d*.
Jonas, E. C., and Thomas, G. L. Hydration properties of potassium deficient clay micas, B (3) 91*j*.
Jones, A. L., Strecker, H. A., and Firestone, R. F. Method of producing a permanently active catalyst utilizing neutron irradiation, P (9) 244*h*.
Jones, F. E. Hydration of calcium aluminates and ferrites, B (5) 149*d*. Hygrometer elements, P (2) 53*d*.
Jones, H. V. Apparatus facilitating accurate [photographic] reproduction of eyeglass lenses, P (7) 185*g*.
Jones, J. B., Jr. Off-gas collector for shaft kilns, etc., P (3) 82*a*. See Brakel, L. H.
Jones, L. E. Solar cell, P (6) 166*f*.
Jones, L. V. See Eichelberger, J. F.
Jones, M. E. See Cornelison, B.
Jones, M. E., and Mehal, E. W. Method of making degeneratively doped group III–V compound semiconductor material, P (9) 249*i*.
Jones, T. See Davies, L. M.
Jones, W. C., Jr. Chromatographic analysis, P (1) 31*a*.
Jones, W. H., Jr. See Barnes, R. G.
Jong, J. de. Mechanical strength of ceramic products, B (10) 300*c*.
Jonke, A. A., Barghusen, J. J., and Levitz, N. M. Process for dissolving binary uranium-zirconium or zirconium-base alloys, P (1) 17*e*.

Jonker, G. H. See Gorter, E. W.

Jonker, G. H., and Noorlander, W. Grain size of sintered barium titanate, B (4) 123*h*.

Jordan, E. L. See Frieser, R. G.

Jordan, E. L., and Donahue, D. J. Semiconductor devices and methods of making them, P (9) 249*h*.

Jordan, R. E., Jr., Mays, H. D., and Claus, K. M. Acoustical panel, P (8) 218*a*.

Jordan, T. J. See Hollinger, D. L.; Plant, H. T.

Josefsson, A. See Kalling, B.

Joseph Kaye & Co. Thermocouple reference junction, P (9) 253*a*.

Joshi, V. C. See Das Gupta, H. N.

Jost, J. M. Hydrothermal synthesis of quartz, P (1) 25*i*.

Jouquet, G., and Rappeneau, J. Mechanical properties of irradiated graphite—modification of the hardness after radiation and annealing, B (8) 234*h*.

Jourdain, A. Manufacture of magnesite brick (I), (2) 44*e*; (II), (4) 101*b*.

Joyce, T. A. See Robinson, A. E.

Juenke, E. F. See Felten, E. J.

Juerine, H. X-ray investigation of glazes containing zirconia, B (4) 124*b*.

Jung, E., and Baudran, A. Power supply for electrical high temperature kilns fitted with heating elements of high positive specific resistance, (5) 140*c*.

Juran, J. M. (editor). Quality Control Handbook, B (6) 176*i*.

Juretschke, H. J., and Steinitz, R. Hall effect and electrical conductivity of transition metal diborides, (11) 317*f*.

Just, D. See Haul, R.

Justi, E. Thermocouples, P (3) 81*h*.

Juvet, R. S., Jr., and Wachi, F. M. Gas chromatographic analysis of inorganic materials, P (1) 31*c*.

Juza, R., and Bohmann, T. Lithium-manganese phosphides and lithium-manganese arsenides, (4) 115*i*.

Juza, R., and Haug, J. Preparation and properties of ternary nitrides of chromium, molybdenum, and tungsten with the composition Li_3MeN_2, (4) 118*j*.

Kabel, M. R. See Dietert, H. W.

Kachalova, L. P., and Avgustinik, A. I. Study of the conditions of stabilization of ZrO_2 and the stability thereof, (4) 121*e*.

Kachan, I. S. See Bezborodov, M. A.

Kachi, S. See Goto, Y.; Watanabe, T.

Kacker, K. P. See Ramachandran, V. S.

Kadanoff, L. P. See Hidalgo, H.

Kadota, M. See Hayami, R.

Kaeser, R. S. Glassblower's safety manostat and system, P (1) 11*c*.

Kaestner, P. T. Method and apparatus for supporting optical elements, P (3) 70*b*.

Kafky, V. Method of decorating glass and ceramic objects, P (10) 272*d*.

Kahan, G. J., and Cormier, F. S. de. Evaporation method, P (2) 48*i*.

Kaibicheva, M. N., Pivnik, L. Ya., and Mar'evich, N. I. Service of concrete based on high-alumina cement in the roofs of electric furnaces, (7) 188*b*.

Kaiser, F. Flow apparatus for separating granular particles, P (9) 250*b*.

Kaiser, V. A. See Sauer, J. M.

Kaiser, W. K. See Garrett, C. G. B.

Kaiser Aluminum & Chemical Corp. Dolomite furnace lining with carbonaceous bond, P (2) 45*d*. Improvement in a process for producing synthetic cryolite, P (3) 83*i*. Method of adding a casing to a refractory article, P (7) 189*g*. Method for removing complex sodium aluminum silicate scale, P (5) 138*b*. Producing aluminum fluoride, P (2) 55*f*.

Kaiser Steel Corp. Apparatus for making shell brick, P (1) 13*c*.

Kalshev, R. Molecular-kinetic theory of crystal growth, B (9) 262*b*.

Kaji, K. Metastability of gypsum hemihydrate in mixed acids (H_3PO_4, H_2SO_4), (2) 35*f*.

Kajihara, H. See Nakayama, N.

Kajihara, H., Nakayama, N., Sakai, S., Yamada, K., and Mori, I. Ultra-high-speed cutting by cermet tool, (8) 203*f*.

Kakimoto, K. See Terada, K.

Kalabukhov, N. P., and Yurachkovskii, P. A. Ultraviolet absorption of X-rayed KCl crystals, (5) 147*e*.

Kalinina, A. M., and Porai-Koshits, E. A. Problem of the existence of metakaolinite and nature of exothermal effects of alumina, (10) 296*j*.

Kalinowski, A. T. See Dantro, H. F.

Kalitin, P. P. See Funke, V. F.

Kallen, D. See Krebs, H.

Kalliga, G. P., Kolbasova, V. A., and Poluboyarinov, D. N. Peculiarities of the technology of casting zircon products, (1) 14*c*.

Kalliga, G. P., and Tuzhilkin, I. M. Organic additives for the preparation of lightweight refractories, P (2) 46*g*.

Kalling, B., Josefsson, A., and Stroemstad, S. Lining performance in the Kaldo process, (6) 161*j*.

Kalous, J. Mechanization of technical porcelain production, (10) 281*b*.

Kalousek, G. L., and Denny, A. D. Thermal insulating product and method for making it, P (11) 308*f*.

Kalpers, H. Glass fiber reinforced plastics—new materials, (1) 7*a*.

Kalsing, H. Melting and production of crystal and lead-crystal glass, (1) 7*i*. Ring of crystal goblets, (1) 8*f*. Striae and other defects in crystal glass melting, (1) 9*b*. (editor) Sprechsaal Silikat Jahrbuch, B (5) 151*c*.

Kamao, H. See Miyazawa, K.

Kamb, W. B. Refraction corrections for universal stage measurements (I) uniaxial crystals, (9) 257*a*.

Kamentsev, I. E. See Frank-Kamenetskii, V. A.

Kamienska, Z., and Chojnacka, H. Use of researches made by a historian of material culture in the determination of the origin and artistic features of glass monuments (abstract), B (11) 321*f*.

Kaminow, I. P. See Rigrod, W. W.

Kaminskaya, N. L. See Gurkovskii, E. V.

Kaminski, J., Jr. See Vose, F. C.

Kamiya, Y., Nonoyama, M., and Uyeda, R. Electron microscopic observation of the superlattice in serpentine, (6) 173*b*.

Kamlet, J. Cyclic process for the beneficiation of titania ores and slags [using $(NH_4)_2SO_4$], P (2) 55*g*.

Kamlet Laboratories. Cyclic process for the beneficiation of titania ores and slags [using $(NH_4)_2SO_4$], P (2) 55*g*.

Kanamaru, F. See Okazaki, C.

Kanaya, M. See Sato, N.

Kaneko, K. See Suzuki, K.

Kano, J. See Teraoka, I.

Kanter, H., and Feibelman, W. A. Electron emission from thin Al-Al_2O_3-Au structures, (5) 134*g*.

Kantor, F. W. How ceramic benders control light rays, (10) 280*e*.

Kantro, D. L. See Copeland, L. E.

Kanzaki, H., Kido, K., and Ninomiya, T. Ionic conduction in zone-refined KCl, B (9) 261*c*.

Kapany, N. S., and Capellaro, D. F. Apparatus for drawing fibers, P (8) 210*e*.

Kapell, H. Wheel radius dressing (I, II), (9) 236*b*.

Kapernaros, E. L., and Ratterman, E. High efficiency approach to diamond carbide grinding (I) wet surface grinding, (11) 301*e*.

Kapitonova, M. M. See Grum-Grzhimailo, S. V.

Kaplan, R. See Kim, Y. W.

Kaplyanskii, A. A., and Moskvin, N. A. Piezospectroscopic effect in lithium fluoride crystals activated by hexavalent uranium, (6) 165*a*.

Kappelmeyer, R. Apparatus for drawing semiconductor bodies from a melt, P (6) 165*d*.

Kappmeyer, K. K., and Manning, R. H. Evaluating high-alumina brick, (8) 213*h*.

Karakurchi, V. A. See Gurevich, I. E.

Karamyshev, I. P., and Nedumov, N. A. Sintering powdered materials, P (2) 51*h*.

Karaulov, A. G. See Zhikharevich, S. A.

Kargin, V. A., Lastovskii, R. P., Matveeva, T. A., Ryabchikov, D. I., Zarinskii, V. A., and Farafonov, M. M. Purification of titanium dioxide and metatitanous acid by high-voltage electrodialysis, (7) 197*j*.

Karlson, K. Position of the foreman in the works, (1) 8*i*.

Karpenko, I. V. See Wolkenstein, T.

Karpinski, J. Y. Increase in corrosion resistence of microconcrete by limited substitution of limestone in siliceous aggregates, (8) 205*b*. Substitution of calcareous sand for siliceous sand, (1) 3*g*.

Karpuchin, V. I. See Pravdyuk, N. F.

Karsch, K.-H. Solidification range of the glass phase in ceramic bodies, (8) 229*h*.

Kartha, K. N., and Rao, H. V. B. Study of clay from Kumbalam (Kerala State), (6) 170*c*.

Kartluke, H. See Tarpley, W. B.

Kasai, J., and Nakahara, M. Large crystals of $CaSO_4 \cdot 2H_2O$ from $CaCl_2$ and Na_2SO_4, (5) 126*c*.

Kasai, J., Sakai, S., and Nakahara, M. Setting time of gypsum plaster in the presence of dolomite plaster, (10) 267*g*.

Kaspar, J. Stability of synthetic spinel monocrystals, B (9) 262*c*.

Kastenbein, E. L. Apparatus and method for making tile panels, P (4) 104*d*.

Kataoka, N., and Kawamoto, T. Low temperature glass (IV) measurements of adhesion, firing, and soldering temperature, (10) 271*c*.

Kataoka, N., Kawamoto, T., and Manabe, Y. Uses of low expansion ceramics (I) low temperature-low expansion heterogeneous frit, (5) 134*c*.

Kataoka, S. Magnetoresistance microwave wattmeter, (7) 191*j*.

Kataoka, Y. See Matsuo, C.

Kato, E. Ash glazes in ceramics, (9) 245*i*.

Kato, E., Morita, S., and Choshi, I. Iron glazes (I) influences of magnesia on iron glazes, (1) 18*d*.

Kato, E., Takashima, H., and Choshi, I. Softening and melting process of lime-zinc glazes, (11) 309*g*.

Kato, K. See Yamaguchi, G.; Yonemochi, O.

Kato, M. See Kubo, T.; Minowa, S.; Sato, S.; Takashima, S.

Kato, M., Mizuta, M., and Minowa, S. Reaction between molten steel and refractories (VIII) reduction of SiO_2 and Al_2O_3 by carbon in liquid iron, (1) 14*d*.

Kato, S. See Nishimura, Y.; Yamamoto, R.

Kato, S., Naito, R., Yamamoto, R., and Nishimura, Y. Effects of the particle size of raw materials in porcelain manufacturing (V) effect of comminution of feldspar and quartz [quartzite] on the packing of porcelain bodies, (8) 217*j*.

Kato, S., Okuda, H., Iga, T., and Okawara, S. Alumina porcelain as a high frequency insulator (II) effects of metal oxides, (1) 17*h*.

Katon, J. E. See Wildi, B. S.

Katona, G. P. Electroluminescent cell, P (1) 20*g*.

Kats, A. Hydrogen in alpha quartz, (5) 144*d*.

Kats, A., Haven, Y., and Stevels, J. M. Hydroxyl groups in α-quartz, (4) 114*d*.

Katsube, S. See Fukuda, T.

Katsura, T., and Kushiro, I. Titanomaghemite in igneous rocks, (4) 110*j*.

Katto, S. See Terada, S.

Katzer, J. See Hauptman, Z.

Kaufman, A. B. Bonded-wire temperature sensors, (9) 250*h*.

Kaufmann, W., and Hub, W. Screw nipple [expansion] joint for carbon electrodes, P (8) 225*a*.

Kautz, H. P. Crusher jaws [design], P (5) 138*h*. Ore crusher [with overload release], P (11) 315*e*.

Kavalerova, V. I. See Bozhenov, P. I.

Kavcic, J. Influence of the finest grain size fraction of the aggregate on the sulfate corrosion of cement mortars, (7) 180*c*.

Kawada, N. See Manabe, T.; Sawamura, M.

Kawahito, T. See Ishikawa, A.

Kawakita, K. See Nakamura, M.

Kawamoto, T. See Kataoka, N.

Kawamura, H., and Okubo, Y. ESR study of trapping of Mn ions along dislocation lines in NaCl, B (9) 260*g*.

Kawamura, S. See Yamaguchi, G.

Kawasaki, K., and Senzaki, K. Permeation of helium gas through glass, (8) 209*h*.

Kawashima, C., and Setaka, N. Microstructure and dielectric properties of barium titanate ceramics, (11) 310*b*.

Kay, S. E., and Ball, R. J. Depositing silver or copper from solutions on glass, P (6) 157*i*.

Kayalova, S. S. See Appen, A. A.

Kaye, Joseph, & Co. See Joseph Kaye & Co.

Kayser, A. J. Pump for imparting movement to dry pulverulent material, P (11) 312*c*.

Kayser, J. A. Effect of batch temperature and curing time on the tranverse strength of castable refractories, (11) 305*h*.

Kazabordskaya, G. V. See Malyshev, M. F.

Kazansky, V. B., Pariisky, G. B., and Voevodsky, V. V. Radiation-induced processes on the silica-gel surface, (10) 296*b*.

Keating, J. P., and Spielman, L. S. Burner construction [radiant], P (3) 82*b*.

Keattch, C. J., and Redfern, J. P. Preparation and properties of a hydrous ruthenium oxide, (11) 318*g*.

Kebler, R. W. See Drost, W.

Kedesdy, H. H. See Gaule, G. K.

Keeling, P. S. Common clay minerals as a continuous series, B (4) 124*e*. Kaolinite series, B (10) 300*f*.

Keely, W. M. See Pattison, J. N.

Keen, J. Symposium on control of the quality of glassware: Experiment for setting up a forming machine and the sampling plan for checking performance, (9) 241*a*.

Keen, N. J. See Jenkins, I. L.

Keesom, P. H., and Pearlman, N. Low-temperature heat capacity of pure and reduced rutile, (3) 87*i*.

Kegg, R. R. Glass-to-metal seals and method of fabricating them, P (3) 69*j*.

Kegg, R. R., La Brecque, R. E., and Warnke, R. C. Fenestration structure for control of daylighting, P (10) 271*g*.

Keib, H. See Schuller, W. H. W.

Keig, G. A., and Haines, H. R. Cathodic etching of plutonium ceramics, (11) 312*i*.

Keim, G. I., and Thompson, W. D. Mineral fiber [paper] products and method of preparing them, P (3) 70*a*.

Keir, E. S. See Fletcher, W. W.

Keitel, W. Furnace, P (5) 140*c*.

Kelble, J. M., and Bernados, J. E. High temperature nonmetallic materials, (10) 269*c*.

Keler, E. K., and Andreeva, A. B. Influence of ferric oxide on the sintering of zirconium bodies during stabilization of ZrO_2, (7) 188*b*. Study of the solid solution region in the system ZrO_2–SiO_2, (7) 201*a*.

Keler, E. K., and Kozlovskaya, E. I. Elastic properties of glass, (2) 39*c*.

Keler, E. K., and Kuznetsov, A. K. Formation and physicotechnical properties of yttrium orthosilicate—$Y_2O[SiO_4]$, (4) 114*g*.

Kell, R. C. Properties of niobate high-temperature piezoelectric ceramics, (9) 248*f*.

Kelleher, D. Comminution theory and practice (I, II), (2) 50*i*.

Keller, C. Fluorite phase in the system CdO–UO_2–O_2, (5) 143*e*. Ternary oxides of niobium and tantalum of the ABO_4 type, (4) 121*g*.

Keller, S. P. See Cheroff, G.

Keller, S. P., and Pettit, G. D. Quenching, stimulation, and exhaustion studies on some infrared stimulable phosphors, (2) 58*a*.

Keller, W. Apparatus for orientation of the crystal nucleus during the growth of single crystals, P (4) 121*g*.

Keller, W. D. See Ponder, H.

Keller, W. D., Balgord, W. D., and Reesman, A. L. Dissolved products of artificially pulverized silicate minerals and rocks (I), (11) 316*f*.

Keller, W. D., and Reesman, A. L. Dissolved products of artificially pulverized silicate minerals and rocks (II), (11) 316*i*.

Kelley, C. M. Crystals in electronics, (10) 298*a*.

Kelley, D. T. Method for making semiconductor device, P (3) 78*g*.

Kelley, R. H. See Kulp, B. A.

Kelly, A. See Groves, G. W.

Kelly, G. D. How to calibrate optical pyrometers, (1) 23*i*.

Kelly, H. J. See Carter, G. J.

Kelly, L. See Hutter, J. F.
Kelly, T. M., and Mielenz, R. C. Hydraulic cement additives and cement compositions containing them, P (9) 237*g*. Mortar additives, P (9) 237*j*.
Kelmers, A. D. Preparation of ammonium metavanadate, P (3) 84*g*. Production of low sulfate uranium oxide, P (11) 315*e*.
Kemeny, G. See Walsh, P.
Kemmey, P. J. See Clark, C. D.
Kemmler, S. See Ruedorff, W.
Kemp, A. J. Method of making nonmetallic electric resistance elements, P (7) 193*i*.
Kempcke, E. Neuburg (Bavaria) earthenware and stoneware from the 17th century to 1853, (7) 177*j*.
Kempf, R. Homogeneous batch for the mechanical production of sheet glass, (8) 209*a*.
Kempis, E. B. See Talbot, J. H.
Kempter, C. P. Hydrolysis properties of uranium monocarbide and dicarbide, (10) 293*j*.
Kempthorne, J. L. Process for making concrete for application by spray gun, P (10) 277*e*.
Kenan, W. M. Control of reversible thermal expansion of pyrophyllite refractories by talc additions, (4) 100*j*. See Tanner, J. T.
Kendall, T. A. See McGrain, P.
Kendrick, R. W. See Snow, H. J.
Kenington, H. W. See Neville, A. M.
Kennedy, D. P., and Murley, P. C. Impurity atom diffusion into finite slices of semiconductor material, (7) 191*c*.
Kennedy, G. C., Wasserburg, G. J., Heard, H. C., and Newton, R. C. Upper three-phase region in the system SiO_2–H_2O, (2) 59*f*.
Kennedy Van Saun Mfg. & Eng. Corp. Hydraulic suspension system for gyratory crusher shafts, P (2) 55*i*.
Kennicott, W. L. Use of hard metal carbides in ceramic fabrication, (4) 106*g*.
Kenshol, K. W. Molten material spray gun with laterally deflecting air cap, P (8) 208*a*.
Kenworthy, L. A. Rutile seed, P (4) 111*e*.
Kenyon, T. F. See Catron, W. M.
Keon, E. F. Anisotropic heat-controlling body and method for manufacture, P (10) 276*i*.
Kern, S. See Heller, G. S.
Kerr, G. T. See Frilette, V. J.
Kerr, P. F. See Adler, H. H.; Bollin, E. M.
Kerr, R. E., and Saviers, G. B. Method and apparatus for metering slurry, P (3) 80*c*.
Kershaw, P. L. See Steghart, F. L. F.
Kerstan, W. Fire-resistant, nontoxic yellow ceramic glazes and enamels, P (6) 155*e*.
Kerstetter, D. R. Thermal emissivity device, P (4) 108*c*.
Kersting, A. See Reuschel, K.
Kervin, W. D. Combustion burner, P (10) 288*b*.
Kessler, H. Hardening of blanks for smelter blocks containing glass-containing ground slag, P (3) 74*a*.
Kestigian, M. See Herkart, P. G.
Ketolainen, P. See Hovi, V.
Khachaturov, S. Sh. See Gurevich, I. E.
Khaibullin, I. Kh. See Styrikovich, M. A.
Khashkovskaya, A. P. See Konovalov, P. F.
Kheiker, D. M. See Berkovich, T. M.
K. & H. Equipment, Ltd. Materials sorting apparatus, P (5) 141*d*. Quantitative photometric [ore] materials sorter, P (10) 290*e*.
Khil'ko, M. M., and Antonov, G. I. Experience with the use of forsterite checkers in high-load open-hearth furnaces working with oxygen, (7) 187*j*.
Khlapova, A. N. Phase transformations in the system sodium sulfate–sodium carbonate, (1) 29*c*.
Khodakov, A. L. See Sholokhovich, M. L.
Khodskii, L. G. See Bezborodov, M. A.
Kholin, I. I., and Royak, S. M. Blast-furnace cement in the USSR, B (5) 150*d*.
Khundkar, M. H. See Haider, S. Z.
Kibler, G. M., Lyon, T. F., and DeSantis, V. J. Carbonization of plastics and refractory materials reasearch program (II) refractory materials research, (8) 212*f*.
Kida, K., and Nishigaki, S. Extraction of beryllium oxide from beryl ore, (2) 54*f*.
Kido, K. See Kanzaki, H.
Kidwell, J. F. See Fouse, F. Z.
Kieffer, E. Surface treatment of glazed ceramics, P (4) 104*e*.
Kiehl, J. P. Refractories of high mullite content, P (3) 74*f*.
Kienow, S., Artelt, P., Naefe, H., and Steinhoff, E. Vaporization of refractory materials, (7) 189*e*.
Kienow, S., and Steinhoff, E. Corrosion of checkerbrick in regenerators of open-hearth furnaces, (8) 212*j*.
Kiessewetter, F. Statistical evaluation of test data within the refractories industry, B (10) 300*h*.
Kihlstedt, P. G. Relation between particle size distribution and specific surface in comminution, (9) 237*c*.
Kikuchi, M. Negative resistance in the forward direction of semiconductor point contact diodes, (8) 219*d*.
Kikuchi, M., and Sato, M. Possible evidence for the light induced plasticity in germanium, (6) 174*h*.
Kilby, J. S. Semiconductor structure fabrication, P (5) 137*b*.
Kilby, J. S., and Williamsen, E. J. Method of making porous metal bodies, P (4) 102*d*.
Kilgore, C. R. Engineered composite coatings, (8) 207*d*.
Kilian, G., and Mainz, F. Apparatus for producing double sheet glazing units, P (11) 304*h*.
Killam, E. R. Foreign trade in ceramic products, (1) 31*e*.
Kim, K. Y. See Van Wazer, J. R.
Kim, P. H. See Namba, S.
Kim, Y. W., Kaplan, R., and Bray, P. J. V-type center resonance of neutron-irradiated LiF at room temperature, (2) 59*i*.
Kimble Glass Co. Apparatus for extruding glass, P (6) 157*a*. Apparatus for producing glass rod and tubing [by drawing], P (3) 68*i*. Apparatus for shaping mouth portions of glass articles [vials], P (1) 10*j*. Glass-to-metal seals and method of fabricating them, P (3) 69*j*. Method and apparatus for cleaning small glass containers, P (4) 100*b*. Plunger for forming glass articles, P (2) 42*j*, P (6) 158*a*.
Kimpel, R. F. Cement composition, P (4) 96*f*.
Kimura, I. Rheological study of plastic cement, (8) 205*j*.
Kimura, S. See Suzuki, H.
Kimura, Y. Expansion and shrinkage characteristics of ferrites in the firing process, (3) 76*h*. Formation of zinc ferrite by explosive compression, (11) 310*d*. Properties of metallic oxides formed by explosives, (6) 174*i*.
Kindred, R. L., and Burk, M. C. Programmer-integrator for chromatographic analyzer, P (1) 24*e*.
King, A. G. Influence of microstructure on the mechanical properties of dense polycrystalline alumina, B (3) 92*c*. See Whittemore, O. J., Jr.
King, D. F. See Cook, M. D.
King, D. F., Birch, R. E., and Thompson, C. L. Refractory silica bricks for open-hearth furnaces, P (6) 162*i*.
King, E. G. Low temperature heat capacities and entropies at 298.15°K of crystalline lead metasilicate, lead orthosilicate, and cadmium metasilicate, (2) 57*g*.
King, J. C. Electrolysis of synthetic quartz—effect upon resonator performance, (9) 247*c*.
King, P. Protecting refractory metals with diffusion coatings, (1) 4*d*.
King, R. C. Dielectric ceramic and method of preparing it, P (9) 248*i*.
King, W. R. See Gernes, D. C.
Kingery, W. D. (editor) Ice and Snow—Properties, Processes, and Applications, B (11) 321*h*. Thermal conductivity of ceramic dielectrics, B (8) 233*e*.
Kingery, W. D., and Coble, R. L. Review of the effect of microstructure on mechanical behavior of polycrystalline ceramics, B (9) 259*g*.
Kingery, W. D., Sidhwa, A. P., and Waugh, A. Structure and properties of vitrified bonded abrasives, (6) 153*g*.
Kingery, W. D., Woulbroun, J. M., and Charvat, F. R. Effects of applied pressure on densification during sintering in the presence of a liquid phase, (10) 292*i*.
Kingery, W. D., Woulbroun, J. M., and Coble, R. L. Glasses formed by vapor deposition, B (11) 320*g*.
Kingston, W. E., Kopelman, B., and Hausner, H. H. Nuclear reactor fuel elements and method of preparation, P (10) 277*b*.
Kinker, C. C. See Olson, R. H.
Kinney, K. Glass Craft: Designing, Forming, and Decorating, B (2) 61*c*. Kiln-formed glass: designing with wire, (5) 126*a*; firing glass over clay forms, (5) 126*a*; firing glass on metals, (5) 126*a*; firing glass—a review and some new evaluations, (7) 177*i*.
Kinoshita, N. See Inoue, Y.
Kinoshita, T. Trends and present state of converter steelmaking at the Japan Steel & Tube Co., Ltd., (6) 161*h*.
Kiplin, R. A. See Brooks, S. H.
Kirby, P. L., and Walton, B. Recent developments in resistors for use at high voltages, (9) 248*a*.
Kirby, R. C. See Peters, F. A.
Kirby, R. E. Glass manufacture, P (1) 11*a*.
Kirchner, H. P. See Merz, K. M.
Kirchner, H. P., and Knoll, P. Silicon carbide whiskers, (8) 229*g*.
Kirchner, H. P., Merz, K. M., and Brown, W. R. Thermal expansion of uranium pyrophosphate and of ceramic bodies in the system UO_2–UP_2O_7, (5) 132*h*.
Kirkhart, F. P. See Johnson, H. V.
Kirkpatrick, W. J., Anderson, G. R., and Funston, E. S. Basic Materials studies sinterable high purity BeO, (8) 226*e*.
Kirkpatrick, W. J., and Funston, E. S. Method of making high purity substantially spherical discrete particles of beryllium hydroxide or oxide, P (11) 308*g*.
Kirshenbaum, A. D., and Cahill, J. A. Liquid density of yttrium and some rare-earth fluorides from the melting points to approx 2500°K, (1) 28*c*.
Kirwan, J. J. See Budd, S. M.
Kishii, T. Surface leakage resistance of glass, (11) 304*a*.
Kiss, Z. J. See Duncan, R. C.; Wittke, J. P.
Kistiakowsky, G. B. See Hamilton, P. M.
Kita, M. See Izumi, G.
Kitaigorodskii, I. I., and Blinov, V. A. Heat resistant "pireksil" glasses, (1) 7*f*. Preparation of superthin film glass and its field of application, (1) 8*i*.
Kitaigorodskii, I. I., and Indenbom, V. L. Internal stresses in quenched glasses, (10) 271*b*.
Kitaigorodskii, I. I., and Sil'vestrovich, S. I. Problem of increasing the hardness and thermal stability of glass, (7) 185*e*.
Kitakaze, H. See Hirota, M.
Kitamura, S. Effect of heat treatment on sintered cadmium sulfide photoconductive films, (5) 143*a*.
Kitamura, T. See Goto, Y.
Kitamura, Y. Results with burned basic brick for the front wall, (11) 306*f*. Wear and tear of mold top brick and quality of its component refractories, (11) 308*a*.
Kittanning Brick Co. Extruded ribbon of fireclay, P (10) 277*a*.
Kittel, J. H. See Neimark, L. A.
Kitzrow, H. Heat exchangers in furnaces for the sintering of magnesite, dolomite, or cement, P (4) 108*g*. Supply apparatus for shaft furnaces, etc., P (6) 155*a*.
Kjaer, A. See Bredsdorff, P.
Kjennerue, A. Behavior of hydrated cement minerals toward aggressive waters with reference to concrete corrosion, (1) 2*f*.
Klamt, H. A. Defects in glass melting pots and their avoidance, (1) 6*g*.
Klanke, G. Prestressed ceramics, (3) 71*f*.
Klasse, F. Silicon carbide refractories, P (3) 75*a*.
Kleber, W., and Witzke, H. D. Growth and morphology of AlN single crystals, (4) 114*j*.
Kleesattel, C., Balamuth, L., and Kuris, A. Acoustically vibrated material cutting and removing devices, P (5) 138*f*.
Klein, A. Ceramics of Iran, (3) 63*i*. Cordoba Cathedral, the Alhambra, and Spanish-Moorish faience, (10) 265*j*. European faience as an artistic form in the past and present, (10) 265*j*. Exhibition of German faience in the Hetjens Museum, (3) 63*i*. History and problems of old and new Japanese ceramics, (7) 177*h*. Importance of German faience in European ceramics, (3) 63*j*. Tea ceramics, (3) 64*c*. Work of Otto and Albrecht Hohlt, (3) 64*c*.
Klein, M. J., Rough, F. A., and Simons, C. C. Structure and annealing behavior of explosively shocked magnesia single crystals, (9) 257*g*.
Kleinkauf, H. Statistical quality control—some case histories in ceramics, (4) 122*e*.
Kleinteich, R. History of the glass apparatus and instrument industry, (4) 98*i*. Properties of glasses for technical ware and for sealing to metals, (7) 185*h*.
Klement, R., and Kresse, P. Polymorphism of phosphates, arsenates, and vanadates containing alkali and alkaline earth metals, (4) 118*f*.
Klemm, W. See Essen, U. v.
Klepsch, H. Consistent quality control as an effective means of reducing production costs in the ceramic industry, (4) 122*b*.
Klichkova, V. P. See Aleksandrovich, E.
Klieger, P. Extensions to the long-time study of cement performance in concrete, (4) 96*c*.
Klier, G. See Doetsch, E.
Klier, K. See Barry, T. I.
Klimenskii, R. Ya. Metal-ceramic joints, P (2) 38*e*.
Kling, H. G. See Harkort, D.
Kloeckner-Humboldt-Deutz Akt.-Ges. Briquetting roller press [with roll adjustment] for compacting ore, coal, etc., P (5) 141*a*. Froth flotation of cryolite, P (7) 197*h*. Grinding mill of the swinging type with a plurality of grinder drums, P (7) 197*i*.
Kloosterziel, H. See Dijck, W. J. D. van.
Klopp, W. D. Summary of the Fifth Meeting of the Refractory Composites Working Group (1961), (9) 238*e*.
Klopp, W. D., Powell, C. F., et al. Development of protective coatings for tantalum-base alloys, (8) 206*g*.
Klyachko, V. A. See Shemyakina, O. N.
Kmetz, E. W. See Chismar, A. B.
Knapic, D. D. Crystal growing furnace, P (2) 53*j*.
Knapic Electro-Physics, Inc. Crystal growing furnace, P (2) 53*j*.
Knapp, O. Illuminating Glass, B (11) 322*h*. Manufacture of television tubes, (1) 7*f*. Silicate glasses—crystallization and composition, (9) 241*h*.
Knapp, W. J. Method of treating an alumina ceramic article with lithium borate, P (1) 16*g*. See Flood, H.
Knapp, W. J., and Shanley, F. R. Process for making laminated material, P (9) 250*f*.
Knapsack-Griesheim Akt.-Ges. Fluidized bed coating process for coating with thermosetting materials, P (9) 239*a*. Process and apparatus for the drying and burning of pellets, P (11) 312*a*. Process and apparatus for the manufacture of anhydrous magnesium chloride which is substantially free from magnesium oxide, P (3) 84*i*.
Knauf, A. N. Process for producing construction elements of any shape, P (1) 3*i*.
Knauf, N. W. Process for producing construction elements of any shape, P (1) 3*i*.
Knaust, H. Apparatus for cooling ore sinter and [cement clinker], P (1) 3*a*.
Knights, H. C., and Munn, P. N. Graphite moderator structures for nuclear reactors, P (8) 216*f*.
Knipper, C. E. Dryers for porcelain enameling, (8) 207*c*.
Knisely, R. C. Apparatus for producing glass rod and tubing [by drawing], P (3) 68*i*.
Kniveton, J. Method of producing a combined radiant heat fuel burner block and refractory cup, P (1) 16*f*.
Knizek, I. Some aspects of crystallization in the system α-alumina–silica (II), (4) 120*i*.
Knoblauch, H. Investigation of the liquid phase of blast-furnace cement pastes and of the slags used in their preparation, (7) 180*f*.
Knoll, P. See Kirchner, H. P.
Knowles, J. N. See Harrison, F. W.
Knueppel, H., and Brotzmann, K. Refractory nipple for dipping into molten metal, P (2) 46*g*.

Kobayashi, M. See Fukuda, T.
Kobayashi, S. Energy band structure of the SiC crystal, (6) 173*b*.
Kobayashi, T., Tanaka, H., and Iwata, S. Cracks appearing on the surface of glass bottles steeped in soakers, (8) 208*i*.
Kobozev, N. I. See Krylova, I. V.
Koch, A. Process and apparatus for the production of cement clinker, more especially for white cement, P (8) 206*d*.
Koch, W. J., and Berry, T. F. Electron tubes (I) properties of ceramic parts in electron tubes, (11) 310*b*.
Kocher, F. W., and Rinne, O. H. Sheet handling apparatus, P (10) 273*b*.
Kocher, G. K. Apparatus for comminuting materials, P (2) 55*a*.
Kocsis, G., Somogyi, A., and Locsei, B. Additional data for the corrosion mechanism of enamels (I) solution rate of enamels, (10) 268*g*.
Koda, N. J. See Yaggy, L. S.
Koehegyi, J. N. Process of making basic refractory and basic refractory composition, P (2) 46*j*.
Koehler, E. K. See Konopicky, K.
Koelmans, H., and Verhagen, C. M. C. Titanium-activated calcium germanate, P (2) 50*d*.
Koenig, C. J. Fusion characteristics and ranges of Lakefield nepheline syenite as influenced by grain size and iron oxide, (2) 54*b*. See Wilson, R. C.
Koenig, J. H. See Smoke, E. J.
Koerner, M. P., and Warner, L. L. Glass flake electrical insulation, P (3) 69*h*.
Koester, H. M. Grain size analysis of kaolins by the pipet method, (3) 80*g*.
Koffskey, J. M., Jr. See Pelton, J. F.
Kofstad, P. Studies of electrical conductivity of Nb_2O_5 as a function of oxygen pressure at 600° to 1200°C, (8) 229*j*. Thermogravimetric studies of the defect structure of rutile (TiO_2), (8) 230*a*. See Oesthagen, K.
Koglin, W. Construction, operation, and characteristics of dust collectors in the silicate and metallurgical industries (III) electrostatic filter, (5) 138*a*.
Kohanowski, F. I. Grate-kiln systems for the production of lime, (10) 288*g*.
Kohlermann, R. See Agte, C.
Kohlswa Jernverks Aktiebolag. Method and device for pulverizing and/or decomposing solid materials, P (4) 110*j*.
Kohn, H. W., and Benjamin, B. M. Radiation coloration of silica minerals, (4) 119*f*.
Kohn, J. A. See Giardini, A. A.
Kohn, J. A., and Eckart, D. W. Twinning study of cubic (β) silicon carbide, (7) 201*d*.
Kohn, L. L. Produce larger profits by stretching working capital, (5) 148*c*.
Kohn, W., III. Grinding disk, P (4) 95*f*.
Kohra, K. See Ishii, Z.
Kohring, W. M. Process for making resistors [with glass-silicone seal], P (1) 21*f*.
Koide, K. See Sakaino, T.
Koide, S. Studies on aluminous cement (V) hydraulicity of aluminous cement—prediction of the mechanical strength of long-aged mortars, (11) 302*c*.
Koide, Y. See Sanada, Y.
Koike, H. See Yamaguchi, G.
Koizumi, M. See Kusaka, Y.
Kojonen, E. Compatibility in glass forming systems, (1) 5*h*.
Kokorish, E. Yu., and Myakinenkova, E. V. Chemical etching and the dislocation density of a germanium monocrystal, B (9) 263*c*.
Kokorish, E. Yu., and Sheftal', N. N. Growth of dislocation-free germanium monocrystals, B (9) 263*d*.
Kokorish, N. P. Deposition of monocrystalline films of germanium from the vapor, B (9) 263*c*. See Sheftal', N. N.
Kokorish, N. P., and Sheftal', N. N. Morphology of polycrystalline films of silicon, B (9) 263*c*.
Kolaian, J. H., and Low, P. F. Thermodynamic properties of water in suspensions of montmorillonite, B (5) 150*c*.
Kolbasnikova, A. I. See Demishev, G. K.
Kolbasova, V. A. See Kalliga, G. P.
Koldobskaya, M. F., and Gavrilova, I. V. Growth of large regular crystals of triglycine sulfate under laboratory conditions, B (9) 262*i*.
Kolina, A. V. See Belyustin, A. V.
Kolomiets, B. T. See Vashko, A.
Koltermann, M. Thermal conductivity of ceramic materials, (4) 121*i*. Torsional testing of ceramic materials at high temperatures, (3) 81*h*. See Lehmann, H.
Koltermann, M., and Mueller, K. H. Differential thermal analysis (with and without vacuum) of olivine, fayalite, and bronzite, (10) 291*f*.
Kolthoff, I. M., and Elving, P. J. (editors) **with Sandell, E. B.** Treatise on Analytical Chemistry (Part II, Vol. 8) Analytical Chemistry of the Elements, B (10) 300*d*.
Komnik, Yu. F. See Palatnik, L. S.
Komskaya, M. S., and Nichiporenko, S. P. Use of physicochemical mechanical methods for analyzing the work of equipment in porcelain factories, (1) 18*b*.
Kondo, M. Factors affecting the drying shrinkage of hardened cement paste, (8) 204*c*. Factors affecting the formation of cracks in hardened mortar, (8) 204*e*.
Kondo, O. See Ariizumi, A.
Kondo, R. Chemical resistivities of various types of cements, B (5) 149*j*. Effects of various factors on mineralogical composition, structure, and strength of hydrothermal reaction products in the system lime–silica, (8) 204*j*. Reaction velocity in portland cement clinker formation, B (5) 148*i*.
Kondrashev, A. P. See Broder, D. L.
Kondrashev, F. V. Vacuum treatment of ceramic powders during pressing, (4) 106*g*.
Kondrashina, A. I. See Vasilevskaya, L. S.
Koniewiez, P., and James, G. R. Sealing unit for rotary kiln, P (8) 225*a*.
Konishi, A. See Arimori, T.
Kono, H. Thermodynamical consideration on the ferromagnetic phase formation in $MnAl_2$, (8) 220*c*.
Konopicky, K. See Schmidt, W.
Konopicky, K., and Koehler, E. K. Variation of ceramic-technological properties and mineral composition of selected clays on firing, (7) 197*e*.
Konopicky, K., Koehler, E. K., and Lohre, W. Preparation and properties of sewer pipe—influence of raw material and limitations of manufacture, (7) 187*c*.
Konopicky, K., and Patzak, I. Density of the zones of used silica brick, (8) 212*h*.
Konovalov, P. F. See Petrova, V. Z.
Konovalov, P. F., Volkonskii, B. V., and Khashkovskaya, A. P. Atlas of Microstructures of Cement Clinkers, Refractories, and Slags, B (11) 321*a*.
Konovalova, E. P. See Petrova, V. Z.
Konrad, H. E. Bonding agent for dry air setting mortars, P (8) 215*f*.
Konrad, H. E., and Stafford, W. L. Lightweight castable refractories, P (6) 162*e*.
Konuma, E. Effect of alcohol vapor on determinations of the fineness of cement and cement raw materials by the air elutriation method, (7) 179*j*.
Koonce, S. E. See Williams, J. C.
Koontz, V. F., and Anthes, J. A. Cooler for sinter, etc. [with vibratory conveyor], P (9) 253*g*.
Kooy, C. Anisotropic exaggerated grain growth and sintering in $MnFe_2O_4$ and $Y_3Fe_5O_{12}$, B (4) 123*h*. See Gorter, E. W.
Kopeikin, A. A. Production of face tile—modern techniques, (7) 190*c*.
Kopelman, B. See Kingston, W. E.
Kopp, O. C., Harris, L. A., and Clark, G. W. Hydrothermal conversion of muscovite to kalsilite and an iron-rich mica, (4) 114*c*.
Koppers Co., Inc. Continuous radiant furnace sintering machine, P (7) 197*c*. Method and apparatus for moistening dust, P (9) 250*d*. Nuclear reactor safety device, P (4) 103*c*.
Koptev, G. S. See Tatevskii, V. M.
Kora, Y. Problems of recent refractories engineering, (5) 132*g*.
Korach, M. "Sandwich" method of rapid firing and the efficiency of the tunnel kiln, (7) 196*j*.
Korach, M., and Thomas, J. K., III. Method of separating silica from zirconium sulfate solutions, P (10) 289*h*.
Korchak, E. I. See Mickley, H. S.
Korchevoi, Yu. P. See Morgulis, N. D.
Korger, M. New trends in the drying of ceramics, (10) 287*f*.
Korinth, J., and Royen, P. Contributions to the reduction of metal salts (I) reactions in the system Fe_2O_3–$FePO_4$, (4) 113*b*.
Korshunov, V. S. See Dvorkind, M. M.
Kosaka, M. See Minowa, S.
Kosevich, V. M. See Palatnik, L. S.
Koshuashvili, M. V. See Belyaev, L. M.
Koski, W. S. See Ring, M. A.
Kosolapov, E. F. See Bas'yas, I. P.
Kostelec, J. See Kunkel, B.
Kostyra, H. See Hegemann, F.
Kostyuchenko, V. P. See Ovsienko, D. E.
Kothe, E. Slurry diffusing machine, P (5) 138*g*.
Kotowski, J. See Pulfrich, H.
Kotsyumakha, P. A. See Andrievskii, A. I.
Kovach, M. J. See Firnhaber, M. S.
Koval'chenko, M. S. See Samsonov, G. V.
Kovalev, A. I. Measurement of the moduli of elasticity of refractory materials at high temperatures under vacuum, (9) 243*e*.
Koval'skii, A. E. See Ivensen, V. A.
Kowalski, A. See Mockrin, I.
Kozak, J., and Soubier, L. D. Apparatus for extruding glass, P (6) 157*a*.
Kozlovskaya, E. I. See Keler, E. K.
Kozlovskii, M. I. Spiral growth and dissolution of crystals, B (9) 262*d*.
Kozuka, T. See Hukuo, N.
Kraemer, W. Method of preparing wire for wired glass, P (1) 12*a*.
Kramarov, O. P. Production of monocrystals of ferroelectrics by zone recrystallization, B (9) 263*f*.
Kramarsky, B. Method of preparing magnetic garnet crystals, P (1) 21*a*.
Kramer, B. E. Method of making jet turbine buckets, P (4) 97*h*.
Kramer, W. Blast-furnace slags and slag cements, B (5) 150*b*.
Krames, E. Effect of various additives on the behavior of porcelain bodies during firing, (10) 278*h*.
Kramm, D. E., and Stone, I. C. Characterization of granular solids by quantitative attrition, (7) 195*h*.
Krampf, M. B. See Graham, P. N.
Krasnaya, A. R., Nosenko, B. M., Revzin, L. S., and Yaskolko, V. Ya. Exoelectronic emission of the phosphors $CaSO_4$, $CaSO_4$:Mn, and $CaSO_4$: Sm, (5) 134*j*.
Kratz, H. R. Method of fabricating a graphite-moderated reactor, P (8) 216*j*.
Kraus, J. Dielectric constant of ADP as a function of temperature, B (9) 263*h*.
Krause, A. Low-temperature synthesis of ferromagnetic ferrites, (9) 247*f*.
Krause, R. Viscosity studies on glass with the parallel-plate plastometer, (1) 10*j*.
Krautwurst, H. See Wuhrer, J.
Kravchuk, L. V. See Tret'yachenko, G. N.
Krebs, H., Gruen, K., and Kallen, D. Structure and properties of semimetallic elements (XIV) solid solutions in systems between semiconducting chalcogenides of group IV, (4) 120*g*.
Krebs, H., Gruen, K., Kallen, D., and Lippert, W. Structure and properties of semimetallic elements (XIII) formation of solid solutions between arsenic and antimony and the semiconducting chalcogenides of group IV, (3) 89*c*.
Krebs, R. D., Thomas, G. W., and Moore, J. E. Anion influence on some soil physical properties, B (5) 150*e*.
Kreigh, J. R., and Gibson, J. K. Metal-aggregate product, P (2) 46*b*.
Kremenek, C. R. See Hughes, W. E.
Kresse, P. See Klement, R.
Kriegel, W. W. See Palmour, H., III.
Kriegel, W. W., and Palmour, H., III (editors). Mechanical Properties of Engineering Ceramics—Proceedings of a Conference Conducted by The School of Engineering and the College Extension Division, North Carolina State College, in Cooperation with the Office of Ordnance Research, U. S. Army, Raleigh, N. C., March 1960, B (3) 91*g*.
Krier, C. A. Coatings for the protection of refractory metals from oxidation, (3) 65*d*.
Krinov, S. Method of preparing glass bath ingredients, P (7) 186*d*. Sampling device and method for analysis of [condensed] furnace gases, P (4) 108*i*.
Krischner, H., and Torkar, K. Microcrystalline active corundum, B (4) 123*i*.
Krishna, N. D. See Narasimhan, M. D.
Krishna, P., and Verma, A. R. X-ray diffraction study of silicon carbide structure types[(33)$_n$-34]R, (5) 147*j*.
Kristofel, N. N. See Zavt, G. S.
Krisztinkovich, B. Habaner Fayencen, B (3) 91*b*.
Krivoglaz, M. A. Theory of the scattering of X rays by crystals containing defects, (2) 59*g*.
Krogh-Moe, J. Crystal structure of cesium triborate, $Cs_2O{\cdot}3B_2O_3$, (10) 291*b*. Energy and length of the boron-oxygen bond, (10) 292*b*. KBr briquette method for studying infrared spectra of anhydrous borates, (2) 57*b*. New evidence on the boron coordination in alkali borate glasses, (2) 40*b*. Structural interpretation of melting point depression in the sodium borate system, (4) 120*f*. Transition point depression of cesium chloride by rubidium chloride, (2) 59*d*. X-ray study of barium borate glasses, (7) 185*e*.
Krogstad, R. S., and Moss, R. W. Ultrasonic study of the cubic-tetragonal phase change and the Curie temperature of single crystal $SrTiO_3$, (9) 257*f*.
Krohn, C. See Grjotheim, K.
Kroll, H. See Hofmann, F.
Kronberg, M. L. See Lommell, J. M.
Kronberg, M. L., Westbrook, J. H., and May, J. E. Deformation of refractory crystals, (8) 227*c*.
Kropschot, R. H. See Cline, D.
Kroyer, K. K. Road construction materials, P (5) 131*f*.
Krstanovic, I., and Radosevic, S. Monoclinic kaolinite from Kocevje Mine, Yugoslavia, (4) 109*j*.
Krueger, G., and Thilo, E. Chemical investigations of silicates (XXV) the solubility product of barium silicate hydrate, $BaO{\cdot}SiO_2{\cdot}6H_2O$, and the electrolytic dissociation of barium hydroxide, (4) 112*g*.
Krueger, H. E., and Schmahl, H. Flexible material for protection against atomic, bacterial, or chemical warfare, P (4) 99*f*.
Krueger, H. H. A. See Austerman, S. B.
Kruesi, P. R. Concentration of rare earths, P (9) 254*j*. See Bronaugh, H. J.
Kruger, O. L. Phase studies on arc-melted plutonium-carbon alloys near the monocarbide composition, (4) 117*j*.
Kruithof, A. M. See Schoenmakers, H.
Krumhansl, J. A. Lattice vibrations in solids, B (9) 259*g*.
Krumholz, P. Process for precipitating readily filterable rare earth hydroxides, P (1) 26*a*. See Bril, K. J.
Krumholz, P., and Bril, K. J. Process for separating rare earths and yttrium by ion exchange [resin], P (2) 60*a*.
Kruml, F., and Rigan, J. Creep of common and light concretes, (6) 154*b*.
Krupp, H. See Boehme, G.
Kruse, F. H., and Asprey, L. B. Crystalline fluoride complex of tetravalent americium, (1) 27*e*.
Krusemeyer, H. J., and Thomas, D. G. Adsorption and charge transfer on semiconductor surfaces, (11) 309*h*.
Kruszewski, S. Effects of furnace operation on quality and quantity of glass, (3) 66*b*.
Krutenat, R. C. See Del Grosso, E. J.
Krylova, I. V., Shashkov, A. S., and Kobozev, N. I. Investigation of ZnS:Cu phosphors by the exoelectron emission method, (5) 135*e*.
Krylow, K. E., Perry, J. T., Jr., and Reimer, W. A. Semipermanent memory—latest use for twistors, (7) 192*b*.
Ksendzovskii, V. R. Automatic control and regulation of the performance of rotary grog calcining kilns, (7) 194*h*.
Kubli, R. A., and Sharav, W. B. Submerged-melt welding and composition therefor, P (11) 303*d*.
Kubo, I. See Shibata, N.

Kubo, T., and Kato, M. High temperature attachment to X-ray diffractometer for the investigation of solid state reaction and its applications, (2) 52*h*.
Kubo, T., Shinriki, K., Fujioka, I., and Kato, M. Synthesis of uranium carbide, (5) 146*a*.
Kubo, T., Taniguchi, M., and Shirasaki, S. Study on the physicochemical properties of ferric oxide particles prepared by roasting of ferric sulfate crystals, (6) 175*i*.
Kubota, B. Preparation of ferromagnetic chromium dioxide, (4) 118*g*. See Hirota, E.
Kuck, J. A., and Bourdelais, C. H. Apparatus for combustion analysis, P (7) 196*a*.
Kuczynski, G. C., Hochman, R. F., and Allen, C. Effect of light on plasticity of semiconductors, B (3) 92*e*.
Kuehl, G. W. Glass with variable transparency, (1) 7*e*.
Kuehne, K. Medieval glasses, (1) 7*g*.
Kuehnert, A. Melting capacity of glass tank furnaces in Germany and abroad, (1) 7*i*.
Kugler, A. E. Parting agent for sprayed metal shells and method for making them, P (6) 162*a*.
Kuhary, E. E. See Operhall, T.
Kuhner, G. See Brauer, G.
Kuhrt, F., and Maaz, K. Magnetically responsive resistance device, particularly Hall generator, P (7) 193*d*.
Kukolev, G. V. Role of ion exchange and surface-active materials in slip casting and other methods of forming ceramic articles, (7) 190*f*. See Kuznichenko, A. N.
Kukolev, G. V., and Mel'nik, M. T. Stabilization of dicalcium silicate, (5) 146*b*.
Kulbicki, G. See Grim, R. E.
Kul'chitskaya, I. B., and Kuznetsova, N. B. Resistance of steel casting plugs, (7) 188*a*.
Kulifay, S. M. Method for the preparation of inorganic selenides and tellurides, P (2) 49*i*. See Epstein, A. S.
Kulik, I. O., and Zil'berman, G. E. Impurity segregation during the growth of a crystal from a melt, B (9) 262*c*.
Kullerud, G., and Yund, R. A. Ni–S system and related minerals, (4) 116*h*.
Kulp, B. A., and Kelley, R. H. Electron processing of semiconducting material, P (7) 193*a*.
Kulp, J. F. See Grandey, M. F.
Kumai, H. Effect of increase in height of the open-hearth furnace roof, (11) 305*i*.
Kumar, S. See Gupta, P. K.
Kumar, S., and Nag, B. B. Effects of fluxing ingredients on the properties of magnesium-calcium-aluminosilicate glasses, (6) 156*h*.
Kumazawa, S., Maeda, T., Nishimura, T., Furukawa, S., and Oota, U. Drainage by refining of ceramic raw materials, (1) 31*e*.
Kumnick, M. C., and Watson, F. K. Interlayers for safety glass, P (6) 157*e*.
Kump, H. J., and Greene, T. G. Magnetization of uniaxial cylindrical thin films, (9) 247*h*.
Kumpera, F. Rationalization of the manufacture of spectacle glass blanks, (1) 8*d*.
Kunkel, B., Kostelec, J., and Gaertner, W. W. Glass-to-silicon seals for components, (2) 148*d*.
Kunkle, G. E., and Harrell, W. C. Manufacture of [contour polished] glass, P (3) 69*d*.
Kunugi, M., Takahashi, K., and Sawai, I. Experimental formulas on the flow of molten glass in a tank furnace, (8) 208*g*. Studies on the flow of molten glass in a glass tank by model techniques, (1) 9*h*.
Kunze, I. Absorption of silver bromide doped with divalent anions, (3) 85*h*.
Kuong, J. F. Flow of granular solids through orifices, (11) 313*a*.
Kupreeva, N. I. See Berkovich, T. M.
Kurbatov, L. N. See Galkin, L. N.
Kurczyk, H. G., and Schwiete, H. E. Hydration products of $3CaO \cdot SiO_2$ and β-$2CaO \cdot SiO_2$, B (5) 149*h*.
Kure, F. Factors affecting glaze fit, (4) 103*j*.
Kurepa, M. See Ajdacic, V.
Kuris, A. See Balamuth, L.; Kleesattel, C.
Kurkjian, C. R. Relaxation of torsional stress in the transformation range, B (11) 320*h*.
Kurnick, S. W., La Grange, L. D., Fitzpatrick, R. L., and Merriam, M. F. Thermoelectric material, P (5) 137*e*.
Kurokawa, M. Method of preparing a magnetic recorder powder, P (7) 194*b*.
Kurosawa, T. Vacancy pairs and dislocations in ionic crystals, B (9) 259*h*.
Kursatsova, V. M. See Rodin, A. M.
Kurtossy, S. S. See Brindley, G. W.
Kurtz, R. A. See Antoszewski, W. J.
Kusaka, Y., Koizumi, M., Saito, H., and Ikeda, S. Growing of mullite from clay minerals, (5) 143*j*.
Kushiro, I. See Katsura, T.
Kushner, M. See Dunn, E. J., Jr.
Kuwabara, S. See Horibe, T.
Kuwata, T., and Sugawara, Y. Artificial gypsum, P (2) 36*a*.
Kuz'mina, I. P. See Bryatov, L. V.
Kuznetsov, A. K. Interaction between calcium zirconate and B_2O_3, (4) 114*i*. See Keler, E. K.
Kuznetsov, A. M. See Yung, V. N.
Kuznetsov, S. I. See Shabalina, O. K.
Kuznetsov, V. N. See Pravdyuk, N. F.
Kuznetsov, V. V. See Zakharikov, N. A.
Kuznetsova, L. I., and Gavrilova, I. V. Laboratory method of growing crystals of pentaerythritol, B (9) 262*i*.
Kuznetsova, N. B. See Kul'chitskaya, I. B.
Kuznetsova, N. G. See Galdina, N. M.
Kuznichenko, A. N., Kukolev, G. V., and Kuznichenko, A. P. Grinding ceramic materials in ball mills, P (2) 51*c*.
Kuznichenko, A. P. See Kuznichenko, A. N.
Kvapil, J. See Smid, I.
Kyazimov, A. A. See Gurevich, I. E.
Kyoden, H. See Mori, S.
Labino, D. Apparatus for attenuating glass fibers, P (3) 68*d*. Apparatus for making mats of blown mineral fibers, P (5) 130*b*. Gas burner, P (1) 11*k*. Glass composition, P (1) 11*j*. High temperature pipe insulation and method of making it, P (1) 16*e*. Method and apparatus for forming and collecting fibers into an improved pipe covering, P (3) 74*c*. Method of producing a battery separator and product thereof, P (8) 211*f*. Method for producing a gaseous blast and for producing glass fibers, P (8) 211*g*. Process of making essentially pure silica fiber bats, P (9) 245*d*.
Labino, D., and Gagin, L. V. Glass composition, P (8) 210*f*. Glass for glass fibers, P (6) 157*c*.
Laboratori Riuniti Studi e Ricerche S.p.A. Microsyringe for gas chromatography, P (11) 320*b*.
Laboratory Equipment Corp. Apparatus for combustion analysis, P (2) 59*j*. Miniature ceramic crucibles for burning metal samples, and ceramic material, P (11) 308*i*.
La Brecque, R. E. See Kegg, R. R.
Laby, R. H. See Greenland, D. J.
Lach, V. Seven fundamental principles of ceramics from the standpoint of research, (11) 320*e*.
Lachmann, G. B. Liquefied gas for industrial use, (5) 140*d*.
Lachut, F. See Marzocchi, A.
Lacroix, M. M. Sintering of calcium fluoride, (3) 88*f*.
Lacy, E. D. See Drysdale, D. J.
Ladell, J., and Spielberg, N. X-ray spectral analysis, P (5) 148*a*.
Ladisch, R. K. Polarographic method and apparatus, P (5) 139*i*.
Lafferty, J. M., and Vanderslice, T. A. Vacuum measurement by ionization, (7) 196*d*.
La Grange, L. D. See Kurnick, S. W.
Lahiri, D. See Samaddar, B.
Lai, T. M., and Mortland, M. M. Self-diffusion of exchangeable cations in bentonite, B (5) 150*e*.
Laird, R. T., and Swallow, H. T. S. Practical measures to prevent lime blowing in the products of a large brickworks, B (10) 300*a*.
Lajarte, S. de. Spheroidal glass particles which contain fissionable material, P (6) 158*g*.
Lakin, J. R. See Mackenzie, J.
Lalovic, B. See Ajdacic, V.
Lam, D. G., Jr. See Wachtman, J. B., Jr.
Lamar, L. E. See Mulford, R. N. R.
Lamarche, D. Porcelain enameling of aluminum alloys, (2) 37*f*.
Lamb, E. F., and Tompkins, F. C. Semiconductivity and thermoelectric power of cadmium oxide, (8) 219*g*.
Lamb, H. W. Automatic thickness control means for flat products, P (6) 167*g*.
Lamb, K. Surfacing torch with external powder feed, P (10) 269*h*.
Lamb, R. J. See Wranau, G. von.
Lamb, V. A., and Salmon, H. I. Electrophoretic deposits of barium titanate, (1) 19*f*.
Lambert, B. See Lecrivain, L.
Lambert, J. D. B. Symposium on nuclear ceramics: Irradiation stability of dispersion fuels, (11) 307*h*.
Lambert, R. E. See Chan, A. D. H.
Lamberty, M. Lubrication method for hot-extrusion press, P (10) 269*c*.
La Mer, V. K., and Smellie, R. H., Jr. Theory of flocculation, subsidence, and refiltration rates of colloidal dispersions flocculated by polyelectrolytes, B (5) 150*f*.
Lamorte, M. F. See Murray, L. A.
Lampman, C. M., Jr. How to avoid glaze defects caused by improper automatic spray application, (11) 309*c*.
Lampman, J. Selection and performance of abrasion-resistant materials in the mining and quarrying industries, (9) 254*h*.
Land, T. Advances in glass temperature measurement, (9) 239*e*.
Lander, J. J., and Morrison, J. Process for coating with silicon dioxide, P (9) 249*c*.
Landis, A. L. See Topol, L. E.
Lane, D. H., and Feduska, W. Thermoelectric elements, P (7) 194*c*.
Lane, J. W. Ousting human error, computers boost kiln output, decrease costs, (6) 154*i*.
Lang, D. L. Apparatus for determining thermal conductivity of materials, P (5) 139*a*.
Lange, R. Quickest method for analyzing alkalis and alkaline earths, (8) 223*c*.
Langford, F. F. Epoxy resin for oil immersion and heavy mineral studies, (6) 167*j*.
Langier-Kuzniarowa, A. Importance of the deflocculant in particle size analysis, (10) 286*c*.
Langley, R. Inorganic films for solar energy absorption, (10) 269*d*.
Langrod, K. Method for producing high density [stoichiometric] uranium oxide, P (10) 277*i*.
Langton, N. H. Statistical distribution, (10) 298*c*.
Lanina, E. N. See Rodin, A. M.
Laning, S. H. X-ray study of glass, (9) 241*d*.
Lapham, D. M. New data on deweylite, (4) 110*a*.
Lapidus, M. E. See Tolstoi, N. A.
Laporte Chemicals, Ltd. Production of barium oxide, P (2) 55*g*.
Laporte Titanium, Ltd. Manufacture of titanium dioxide, P (3) 84*a*. Manufacture of titanium dioxide [with 0.5 to 5% (wt) Al_2O_3], P (5) 141*d*. Process for the manufacture of titanium dioxide, P (10) 290*c*.
Lapoujade, P. See Halm, L.
Lappe, F. Some physical properties of sputtered PbO_2 films, (8) 219*f*.
LaQue, F. L. See Seabright, L. H.
Larson, E. D., and Roden, G. B. Air-sweep [partial vacuum] classifier, P (2) 54*j*.
Larson, K. R. Dimensionally stable expanded perlite and method for making it, P (3) 83*f*.
Lasser, K. See Torkar, K.
Lastovskii, R. P. See Kargin, V. A.
Laswick, J. A. Preparation of γ-(Al,Cr)OOH and of H(Cr,Al)O_2 by homogeneous hydrolysis at elevated temperatures, (7) 199*h*.
Lathe, F. E. Consolidating refractory materials, P (6) 162*a*. Refractory masses, P (6) 162*h*.
Latta, E. Ceramic magnet mounting structure, P (9) 248*f*.
Latva, J. D. Selection and fabrication of ceramics and intermetallics, (6) 161*c*. Selection and fabrication of nonmetallics—oxides, beryllides, and silicides, (6) 161*d*. See Ramke, W. G.
Lauchner, J. H. Mechanical behavior of ceramic composites, B (3) 92*f*.
Lauck, A. G. Mold assembly with controlled cooling, P (10) 272*g*.
Laudelout, H. See Eckman, J. P.
Laudise, R. A. Growing oxide crystals, (3) 86*j*. Hydrothermal synthesis of single crystals, B (3) 92*b*. Kinetics of hydrothermal quartz crystallization, (2) 57*d*.
Laufer, B. Chinese Pottery of the Han Dynasty, B (5) 150*d*.
Laurecka, H. See Bieda, W.
Laverdisse, E. Glass polishing apparatus, P (5) 131*a*. Glass polishing tools, P (4) 99*j*.
Lavino, E. J., and Co. Magnesium oxide pellets and process of producing them for burning, P (11) 308*f*. Refractory [metal encased] unit for furnace-lining construction, P (8) 217*a*. Tuyere block and reinforcing insert therefor, P (8) 217*b*.
Lavrov, I. V. See Filonenko, N. E.
Lavrova, L. M., Vizir, L. A., and Agafonova, Yu. A. Silicate enamel, P (2) 38*b*.
Law, M. Turbo mill, P (9) 254*j*.
Lawhorne, E. R. See Sheehan, G. M.
Lawrance, J. J., and O'Connor, D. J. Hydrolysis of thorium carbide, (1) 28*f*.
Lawrence, C. D. See Halstead, P. E.
Lawrence, R. See Bush, D. R.
Lawson, A. W. Defect structures and transport of matter in AgBr, B (9) 261*a*.
Lawson, D. C. See Sahinen, U. M.
Lawthers, D. D., and Sama, L. High temperature oxidation resistant coatings for tantalum base alloys, (8) 207*a*.
Layden, G. K. System Al_2O_3–Nb_2O_5, (11) 319*c*.
Layer, H., Miller, M. G., and Slifkin, L. Effects of quenching and annealing on ionic conductivity and on dislocation decorability in silver chloride, B (9) 261*c*.
Layne, F. A. Ceramic ware setter, P (2) 45*b*.
Lazarev, A. N. Vibrational spectra of silicates (IV) interpretation of the spectra of silicates and germanates with ring anions, (5) 147*f*.
Lazarev, A. N., and Tenisheva, T. F. Vibrational spectra of mixed crystals in the Li_2SiO_3–Li_2GeO_3 system, (6) 176*c*. Vibrational spectra of silicates (III) infrared spectra of the pyroxenoids and other chain metasilicates, (5) 147*e*; (V) silicates with anions in ribbon form, (5) 147*g*.
Lazaro, L. M. Extrusion, B (2) 61*a*.
Lazeeva, G. S. See Zaidel, A. N.
Lea, F. M. Cement research—retrospect and prospect, B (5) 148*e*. Development in building materials—prospect for the future, (4) 122*c*.
Leach, T. C. Increasing life of molds and mold equipment, (4) 98*i*.
Leary, J. A. See Ogard, A. E.
Leary, J. K. See Wilson, A.
Leatham, E. See Snyder, R. P.
Leatham, E., and Pack, A. H. Production of dead-burned grain, P (2) 46*c*. Production of dead-burned magnesia, P (9) 245*g*.
Leaver, E. W. See Hutter, J. F.
Leavitt, F. W. See Mays, R. L.
Leaycraft, E. C. Square loop magnetic manganese ferrite material and manufacture thereof, P (2) 50*a*.
Leaycraft, E. C., and Morris, G. H., Jr. Method of producing ferrite bodies, P (7) 194*c*.
Le Baron, I. M. Electrostatic separation in nonuniform field, P (2) 55*h*.
Lechler, Paul, Firma. See Paul Lechler, Firma.
Lecis, P., and Guidi, A. Process for production of alumina from bauxite and other aluminous materials, by pyrogenic attack, in agglomeration plants, under either suction or pressure, P (3) 84*j*.
Le Clerc, P. G. Method and apparatus for the measurement of a flux of neutrons, P (3) 69*i*.
Lecrivain, L. Effect of particle size of chamotte on the properties of sanitary ware, (1) 17*i*. Various aspects of the mechanical strength of refractory products, B (10) 300*i*.
Lecrivain, L., Lambert, B., and Risse, M. Study of the mechanism of the formation of spalling cracks in refractories, (9) 244*d*.
Leddy, J. J. See Schechter, D. L.
Leddy, J. J., and Schechter, D. L. Pressure leaching of titaniferous material, P (3) 84*h*.
Lederer, E. A. Device for converting thermal energy into electrical energy, P (9) 248*h*.
Lederer, J. Method of increasing the chemical resistance of glass articles, P (11) 305*a*.
Lee, C. A., and White, H. G. Fabrication of *pn* junction devices, P (7) 193*b*.
Lee, G. B. See Glenn, R. C.
Lee, H. C. Dead-burned dolomite—its manufacture and its use in steel refining furnaces, (1) 13*f*.

Lee, J. D., and Caldecott, R. Experiments with hypersonic plasmas, (8) 227*i*.
Lee, R. W. See Frank, R. C.
Lee, S., and Bray, P. J. Electron-spin paramagnetic resonance studies of irradiated aluminosilicate glasses, (2) 39*i*.
Leeds and Northrup Co. Immersion pyrometer with expendable plug-in temperature sensing unit, P (1) 24*b*. Measurement and control of constituent potentials, P (8) 224*j*. Quick disconnecting means for expendable thermocouples, P (2) 53*c*.
Leeper, W. S. Brick hanger tab bending apparatus, P (1) 15*i*.
Leers, K.-J. See Lehmann, H.
LeFebre, V. See Gabrysh, A. F.
Lefever, R. A., Chase, A. B., and Sobon, L. E. Synthetic emerald, (6) 170*d*.
Lefever, R. A., and Giess, E. A. Suggested mechanism for formation of hopper crystals in flux systems, (5) 135*c*.
Leff, J. Methods of etching a semiconductor device [electrolytically and ultrasonically], P (8) 220*h*.
Leflet, H. A., Jr. Apparatus for bending glass sheets, P (8) 210*d*. Apparatus for cleaning glass sheets, P (5) 130*j*. See Carson, F. J.
Legg, J. B. See Eldred, J. W.
Leggett, H., and Urode, R. J. Development of refractory composite materials systems for solid-propellant rocket motors, (8) 206*i*.
Lehmann, H., and Dutz, H. Infrared spectroscopy studies on the hydration of clinker minerals and cements, B (5) 149*b*.
Lehmann, H., and Koltermann, M. Measurement of specific surface with the Blaine apparatus, (4) 116*h*.
Lehmann, H., and Leers, K.-J. Reactions in the setting of aluminous cement, (10) 267*a*.
Lehmann, H., and Lorenz, W. pH measurements of suspensions of clay mineral containing raw materials (4) 117*j*.
Lehmann, H., and Mields, A. Ettringite-like phase of some cements under the influence of large additions of calcium sulfate (10) 266*d*.
Lehmann, H., and Mueller, K. H. Ceramic radiation absorbing materials containing rare earths, (10) 273*j*.
Lehmann, H., Mueller, K. H., and Wermbter, H. Influence of mineralogical constitution of barium cements on their hydraulic properties, (7) 180*d*.
Lehmann, H., and Thormann, P. Investigation of raw materials by combined thermal expansion and differential thermal analysis, (7) 180*h*.
Lehmann, H., Traustel, S., and Jacob, P. J. Determination of the regularity of the structure of alite, (3) 64*f*.
Lehmann, H. A., and Hesselbarth, H. Lithium aluminates (I) new modification of $LiAlO_2$, (4) 115*g*.
Lehmann, W. Electroluminescent cell and method, P (1) 20*h*. Electroluminescent system, electrically nonlinear element, and method, P (5) 135*j*. Method of improving electroluminescent phosphor and electroluminescent lamp, P (2) 49*a*, P (5) 136*d*.
Lehmann, W., and Haake, C. H. Electroluminescent [breakdown protected] cell, P (1) 20*g*.
Lehovec, K., and Shirn, G. A. Ceramic bodies, P (3) 77*b*.
Lehrer, N. H., and Solivan, R. A. Storage target, P (8) 221*b*.
Leibowitz, D. What you must know to use ferrites at low frequencies, (7) 193*d*.
Leifield, R. F. See Piper, R. D.
Leighton, J. See Wigginton, R. J.
Leineweber, J. P. See Vander Linden, C. R.
Leipold, M. H. See Nielsen, T. H.
Leisenberg, M. Electromagnetic removal of iron from ceramic powders in free fall, P (3) 83*g*.
Leite, R. C. C., and Porto, S. P. S. Simple method for calibration of ruby laser output, (9) 251*g*.
Leitz, Ernst, G.m.b.H. See Ernst Leitz G.m.b.H.
Lejsek, L. Utilization of fine dust from cement kilns, (11) 302*f*.
Lelak, J. W. Furnace roof block, P (8) 216*e*.
Lele, R. V. Sanitary-ware manufacture at the Stroifiansa plant, Kirov, U.S.S.R., (6) 163*c*.
Lell, E. Radiation effects in doped fused silica, (4) 119*h*.
Lellep, O. G. Apparatus for grinding and cooling solids, P (3) 83*d*.
Lemaire, H. New techniques for ferrite nanosecond memories, (2) 48*i*.
Leman, G., and Friedel, J. Description of covalent bonds in diamond lattice structures by a simplified tight-binding approximation, B (9) 259*c*.
Le May, C. Z., and Chang, H. C. Preparation of junctions in silicon carbide members, P (3) 78*d*.
Lemieux, P. F. Direct-reading semiquantitative spectrochemical analysis of nonmetallics, (1) 27*h*.
Lemmens, H. J., Bloem, J., Haan, E. F. de, and Jansen, M. J. Method of manufacturing oxide cathodes and cathodes manufactured by such methods, P (8) 220*g*.
Lemmens, H. J., Venema, A., and Zalm, P. Method of manufacturing oxide cathodes and cathodes manufactured by such methods, P (11) 311*b*.
Lenne, H.-U. Dehydration of boehmite, investigated with a new X-ray heating camera, (5) 142*c*.
Leo, J. Thermal expansion apparatus used for process control, (3) 81*g*.
Leonard, R. J. Patching plaster compositions, P (11) 302*g*.
Leonov, Yu. S. Effect of grinding on the luminescent properties of tungstate luminophors, (5) 134*d*.
Leppla, P. W. Mineral filter aids, P (6) 171*e*.
Leroy, P., and Simon, R. Porous refractory concrete element, P (1) 17*a*.
Lescroel, Y. See Pierrot, A.
Leshchinskii, M. Yu. Influence of surface-active agent on hardness of concrete, (1) 2*f*.
esser, R., and Erben, E. Purification of silicon by means of transport reactions, (4) 119*b*.
Lessing, P. See Reynolds, R. C., Jr.
Lester, M. See Richardson, H. M.
Lester, R. H. Ceramic product and method of making it, P (10) 279*a*.
Letocart, G. See Boffe, M.
Leum, L. N., Connor, J. E., Jr., Rothrock, J. J., and Shipley, C. S. Removal of ionic impurities from calcined alumina, P (5) 141*d*.
Leusden, C. O. P. Plastic properties of clay and their effect on some features of die design, B (10) 300*a*.
Leutner, H. See Ruedorff, W.
Lev, A. Hardened wall tile, (9) 245*j*.
Levand, V. A. See Noel, E. B.
Levecque, M. See Peyches, I.
Levecque, M., and Charpentier, M. Manufacture of fibers from thermoplastic material, particularly glass fibers, P (8) 211*bc*.
Levecque, M., and Mabru, M. Apparatus for producing fibers from thermoplastic material, P (8) 210*g*.
Leventhal, M. See Bray, P. J.
Leverton, W. F. See Hagen, L. M.
Levett, P. D. Factors affecting lead zirconate-lead titanate ceramics, (7) 191*h*.
Levey, R. P., Jr., and Smith, A. E. Preparation of spherical uranium dioxide particles, P (8) 216*j*.
Levin, A. I. See Sokolov, N. V.
Levin, E. M., and Mauer, F. A. Improved sample holder for X-ray diffractometer furnace, (3) 80*j*.
Levin, E. M., Roth, R. S., and Martin, J. B. Polymorphism of ABO_3 type rare earth borates, (4) 118*j*.
Levine, H. H. See Ruetman, S. H.
Levine, S. Lime recovery and production increased by new kiln at St. Marys Kraft Corp., (2) 35*b*. Medusa modernizes all phases at Dixon, (2) 35*c*. Process instrumentation and control computers in the cement industry, (5) 126*g*. Recalcining of bauxite for brick manufacturing, (4) 101*f*. See Protze, H. G.
Levinson, S. Dielectric ceramic composition, P (4) 105*b*.
Levitas, A. D. Preparation of multiple *pn* junction semiconductor crystals, P (3) 78*e*.
Levitskii, V. K. See Zakharikov, N. A.
Levitz, N. M. See Jonke, A. A.
Levshin, V. L., and Pipinis, P. A. Exoelectron emission method for investigating trapping levels in crystal phosphors and its application to the study of trapping levels in CaS and SrS phosphors, (5) 134*h*.
Levshin, V. L., and Ryzhikov, B. D. Causes of the decrease in luminescence intensity caused by the mechanical crushing of zinc sulfide phosphors (II), (5) 134*f*.
Levy, D. J. See Gomes, G. S.
Levy, H. Resistor structure, P (4) 106*b*.
Levy, M. Evaluation of flame-sprayed coatings for Army weapons applications, (10) 268*j*.
Levy, P. W., and Weeks, R. A. Review of 1962 Conference on Radiation Effects, B (11) 320*j*.
Lewin, S. Z. Apparatus for use in determining particle size and distribution of particle size, P (10) 287*a*.
Lewis, H. R. Laser—an introduction, (10) 280*i*. See Duncan, R. C.; Sabisky, E. S.
Lewis, J., and Huang, S. High temperature furnace with a sharp temperature gradient, (11) 314*f*.
Lewis, J. G., and Ohlgren, H. A. Method of joining carbon, P (11) 303*c*. Process of manufacturing nuclear fuel, P (9) 245*e*.
Lewis, W. B. See Pretzel, F. E.
Lezy, R. E. A. See Duriez, M. J. J.
L'Hermite, R. G. Volume changes of concrete, B (5) 149*h*.
Lhopitallier, P. Calcium aluminates and high-alumina cements, B (5) 150*c*.
Li, C. H. See Sartell, J. A.; Stokes, R. J.
Li, J. C., and Baker, R. E. Recovery of earth acids from slag, P (11) 315*f*.
Libbey-Owens-Ford Glass Co. Apparatus for bending glass sheets, P (3) 68*d*, P (8) 210*d*. Apparatus for cleaning glass sheets, P (5) 130*j*. Apparatus for feeding glass batch materials, P (6) 157*c*. Apparatus for gaging the curvature of sheet material, P (1) 10*d*. Apparatus for handling sheet material, P (4) 99*e*. Apparatus for pressing [curved] glass-plastic assemblies, P (9) 241*f*. Apparatus for pressing curved laminated safety glass, P (2) 41*i*. Apparatus for pressing glass-plastic sandwiches, P (11) 304*g*. Apparatus for pressing glass sheet and plastic assemblies, P (4) 99*e*. Apparatus for producing all-glass multiple sheet glazing units [with access opening], P (1) 10*i*. Apparatus for producing double sheet glazing units, P (1) 10*d*. Apparatus for producing multiple sheet glazing units, P (1) 10*j*; [by fusion bonding], P (10) 271*b*. Apparatus for supporting [glass] sheets, P (2) 41*i*. Article having electrically conductive coating and process of making, P (5) 130*c*. Bedding glass plates for grinding and polishing, P (6) 157*g*. Electrically conducting films on glass, P (6) 157*i*. Electrically conducting glasses for aircraft windshields, P (6) 157*j*. Electrically conductive multilayer transparent article and method for making it, P (1) 11*e*. Equipment for transporting sheet materials, P (6) 157*j*. Glass bending apparatus, P (9) 242*a*. Glass bending mold, P (9) 242*a*. Glass sheet bending mold, P (10) 272*b*. Handling equipment for [glass] sheet materials, P (8) 210*i*. Hydrophobation of shaped glass parts, P (6) 157*d*. Laminated safety glass, P (3) 69*b*. Light reflecting films and process for their production, P (8) 221*j*. Method and apparatus for fabricating all-glass multiple sheet glazing units, P (6) 158*a*. Method and apparatus for feeding flat [triangular-shaped] sheets onto a moving conveyor, P (11) 304*j*. Method of and apparatus for feeding glass batch materials, P (5) 131*c*. Method and apparatus for inspecting [the dew point of] multiple sheet glazing units, P (3) 69*h*. Method and apparatus for optical inspection of glass sheets, P (7) 186*a*. Method and apparatus [sag mold] for bending glass sheets, P (4) 100*d*. Method and apparatus for producing multiple glass sheet glazing units, P (8) 211*d*. Method and apparatus for treating glass, P (10) 272*a*. Method of making an electrically conductive [glass] article, P (3) 70*g*. Method of treating glass sheets or plates, P (4) 100*g*. Polishing compositions, P (6) 153*g*. Process and apparatus for forming multiple sheet glazing units, P (6) 158*b*. Sonic treating apparatus, P (11) 312*d*. Ultrathin film, P (2) 43*b*.
Libby, W. F. Heat resistant structure, P (10) 272*c*.
Libensky, S. History of Czechoslovakian glass and its development from 1945 to the present (abstract), B (11) 321*c*.
Liberthson, L., and Zara, M. H. Portland cement concrete adjuvant, P (1) 3*h*.
Libowitz, G. G. Nonstoichiometry and lattice defects in transition metal hydrides, B (9) 260*a*.
Licencia Talalmanyokat Ertekesito Vallalat. Improvement of the rheological properties of alkaline earth bentonites, P (4) 110*i*.
Licentia Patent-Verwaltungs-G.m.b.H. Permanent oxide-base magnets, P (4) 105*j*. Process for producing boron- and phosphorus-free high purity silicon dioxide, P (3) 84*h*.
Lichtenstein, V. See Smith, H. L., Jr.
Lidiard, A. B. Reactions among point defects in alkali halides, B (9) 260*b*.
Lieb, A. Electrically conducting transparent layers on glass objects, P (4) 99*e*.
Liebau, F. See Wodtcke, F.
Liebmann, B. See Himmelstein, P.; Hofmann, F.
Liebreich, O. P. Method and mechanism for forming annular grooves, P (4) 107*a*.
Liederbach, W. H. See Scheffer, H. G.
Liehn, W. Batch feeder as sintering chamber in glass tank furnaces, (1) 5*d*.
Liehr, A. D. Coupling of vibrational and electronic motions in degenerate electronic states, B (3) 92*b*.
Lierde, W. van, Strumane, R., Smets, E., and Amelinckx, S. Preparation of uranium oxide single crystals by sublimation, (1) 29*h*.
Liesk, W. See Pfisterer, H.
Ligenza, J. R. Photosensitive gas phase etching of semiconductors by selective radiation, P (10) 283*c*.
Liger, C. See Alviset, L.
Lignes Telegraphiques et Telephoniques. Ferromagnetic materials, P (3) 77*c*.
Ligon, E. R. Coupling for ceramic pipe, P (2) 44*c*.
Lileev, I. S. See Dubrovo, S. K.
Lima-de-Faria, J., and Gay, P. Disordered structural states in the dehydration of goethite and diaspore, (8) 227*c*.
Lin, C. See Christian, S. D.
Lin, F. C. Infrared transmission of several nonsilicate glass systems, (7) 184*g*.
Lin, F. C., Haun, R. D., Jr., and Ohlmann, R. C. Absorption and emission characteristics of glasses containing rare earth ions, B (11) 320*f*.
Lin, F. C., and Ho, S.-M. Chemical durability of arsenic-sulfur-iodine glasses, (3) 66*b*.
Linares, R. C. Growth of refractory oxide single crystals, (5) 144*a*.
Linares Gonzalez, J. See Martin Vivaldi, J. L.
Lincoln, R. L. Gas-material separator, P (10) 285*e*.
Lindbloom, H. E. Method and machine for cutting tile pipe, P (1) 13*c*.
Lindecke, W. See Hoppe, R.
Lindeken, C. L., and Meadors, O. L. Control of beryllium hazards, (3) 90*f*.
Linden, F. A. V. See Vander Linden, F. A.
Linden, P. C. van der. See Haaijman, P. W.
Lindquist, C. A., Jr. Latest fundamentals of piezoelectric ceramics, (9) 247*b*.
Lindsay, G. C. Don't throw away dust, (2) 34*c*. See Trauffer, W. E.
Lineback, J. T. See Cornelison, B.
Linhart, O. C. See Van Dolah, H. J.
Link, V. V. See Prentice, W. H.
Link-Belt Co. and Acme Steel Co. Article stacking and strapping machine, P (10) 273*g*.
Lins, S. J., and Oberg, P. E. Latest thing in thin films—automatic deposition control, (7) 191*g*
Lionnel, L. J. See Wilson, A. D.
Lippert, W. See Krebs, H.
Lippincott, E. R. See Weir, C. E.

Lipschutz, M. E., and Anders, E. Mechanism of diamond formation, (1) 28*e*.
Lisle, A. L. de. Production of improved synthetic stone bodies with controlled properties, P (6) 154*j*.
Lissac, G. Machine for shaping the edges of spectacle glasses, P (8) 211*a*.
Lister, R. D. Safety glass for vehicle windscreens, (1) 8*g*.
Little, H. J. Glass bending mold [with movable sections], P (10) 271*j*.
Littler, D. J. (editor). Properties of Reactor Materials and the Effects of Radiation Damage—Proceedings of the International Conference held at Berkeley Castle, Gloucestershire, England, May-June 1961, B (8) 233*b*.
Litvakovskii, A. A. Fused Cast Refractories, B (4) 123*e*.
Litz, L. M. See Didchenko, R.
Litzow, K. Works control in the ceramic industry and its value, (9) 258*k*.
Liversidge, R. M. See Segnit, E. R.
Livey, D. T. Symposium on nuclear ceramics: Fabrication, properties, and irradiation stability of dispersion-type fuels, (11) 307*d*. See Bellamy, B.; Murray, P.
Livey, D. T., and Williams, J. Aspects of the technology of [beryllium and] beryllia, (10) 273*h*.
Livshits, A. L. See Barke, V. N.
Lloyd, E. C., Hutton, U. O., Johnson, D. P., and Zoranski, H. J. Multiple-anvil high pressure apparatus, P (8) 222*e*.
Lloyd, E. C., Johnson, D. P., and Hutton, U. O. Dual-wedge high-pressure apparatus, P (11) 312*g*.
Lloyd, H. See Antill, J. E.
Lloyd, H. E., and Owens, J. L. Apparatus for making electrical resistors, P (3) 77*a*.
Lloyd, M. H. See Baybarz, R. D.
Lloyd, T. W. See Platt, R. O.
Locher, F. W. Hydraulic properties and hydration of glasses of the system $CaO–Al_2O_3–SiO_2$, B (5) 149*e*. Solid solution of alumina and magnesia in tricalcium silicate, B (5) 148*i*.
Lockheed Aircraft Corp. Active solid-state devices using anisotropic single crystal rutile, P (11) 311*a*. Contact isolated potentiometer, P (3) 77*e*. Cushion material [of fiber glass] and method of making it, P (2) 42*c*. High-dielectric constant material and method of making it, P (6) 166*c*. Pyroelectric squaring element, P (8) 220*j*.
Lockwood, P. A. Metal and fiber composite materials and methods of producing, P (10) 272*h*.
Locsei, B. Formation of an amorphous metaphase in the reaction of kaolinite with aluminum fluoride and its importance in mullite formation, (10) 292*g*. Increase of the Al_2O_3 content or the quantity of mullite in acid refractory materials, (10) 274*d*. Kinetics of phase transformations in the production of fused-cast refractories, (10) 274*i*. New evidence of the existence of the metakaolinite phase, (10) 295*d*. See Kocsis, G.
Lodding, W. Gibbsite vermiforms in the Pensauken formation of New Jersey, (4) 109*j*.
Loeb, L. B. Static electrification (I), B (9) 264*b*.
Loecsei, B. See Locsei, B.
Loeffler, J. Heterogeneities in glass and methods of determining their composition, (1) 7*h*.
Loesche, E. G. Fifty years of the automatic vertical kiln, (10) 266*i*.
Loevenstein, H. Production of aluminum sulfate from clay, P (6) 171*b*.
Loewenstein, K. L. Effect of various cations on the Young modulus of a soda-lime-silica glass, (2) 38*j*. Glass compositions, P (2) 42*g*. Studies in the composition and structure of glasses possessing high Young's moduli (I) composition of high Young's modulus glasses and the function of individual ions in the glass structure, (1) 9*c*; (II) effect of changes in the configuration temperature, (1) 9*f*.
L. O. F. Glass Fibers Co. Glass for glass fibers, P (6) 157*c*.
Logan, J. C. See Whittemore, O. J., Jr.
Logginov, G. I. See Abrosenkova, V. F.
Lohre, W. See Konopicky, K.
Lomakin, G. A. Apparatus for the classification of diamond fines or for the extraction of diamonds, P (2) 51*g*.
Lommell, J. M., and Kronberg, M. L. X-ray diffraction micrography of aluminum oxide single crystals, B (9) 262*b*.
London, H. Glass-lined chemical plant—manufacture and technology, (1) 4*k*.
Long, A. X-ray beam intensity responsive sequential spectrometer, P (6) 176*c*.
Long, J. C., and Milton, C. B. Apparatus for the oxidation of metal powders, P (8) 221*e*.
Long, J. J. Protection from glass, (11) 304*f*.
Long, L. D. Apparatus for making precast cored building blocks, P (9) 250*d*.
Long, R. A. See Bassett, W.; Reeder, R. K., Jr.
Long, R. S., Olson, R. S., and Suris, J. P., Jr. Process for preparation of titanium dioxide, P (3) 84*c*.
Long, W. M. Radial pressures in powder compaction, (1) 23*a*.
Long, W. M., and Alderton, J. R. Displacement of gas from powders during compaction, (1) 22*j*.
Long Meg Plaster & Mineral Co., Ltd. Loading and transport of minerals in mines and quarries, P (2) 55*i*.
Longo, J. See Sleight, A. W.; Ward, R.
Longuet, P. Behavior of tetracalcium aluminoferrite in an atmosphere of hydrogen, B (5) 149*a*.
Loodin, O. Toughened glass, (1) 10*c*.
Loomis, C. A. Packaging of sheet abrasive disks, P (1) 1*j*.
Lopker, E. B. Rotary dryer, P (10) 285*d*.
Lord, J. B. Piezoelectric crystal holder, P (1) 21*d*.
Lord, R. C. See Durig, J. R.
Lord, W. B. H. See Grison, E.
Lordi, A. C. Selecting geared drives for cement plants, (2) 35*i*.
Lorenz, M. R. See Janz, G. J.
Lorenz, W. See Lehmann, H.
Loring, D. H. See Nicholls, G. D.
Loshkarev, B. A. Sintering in the system $ZnO–TiO_2$, (1) 29*i*.
Lotgering, F. K. See Gorter, E. W.
Lotgering, F. K., Enz, U., and Smit, J. Influence of Co^{2+} ions on the magnetic anisotropy of ferrimagnetic oxides having hexagonal crystal structures, (5) 144*g*.
Lotz, F. G. See Penn, W. H.
Louckes, F. L., Jr. See Stiller, B.
Louden, W. C., and Homonnay, E. Method of making a ceramic-to-metal seal, P (8) 220*c*.
Love, R. W., and Baranovic, M. Apparatus for reshaping cylindrical glass tubes, P (3) 69*a*.
Lovejoy, D. R. Detection limits in radiation and optical pyrometry, (5) 138*i*.
Lovering, T. S., and Shepard, A. O. Hydrothermal argillic alteration on the Helen claim, East Tintic district, Utah, B (3) 91*j*.
Low, P. F. Influence of adsorbed water on exchangeable ion movement, B (5) 150*e*. Viscosity of water in clay systems, B (3) 91*j*. See Kolaian, J. H.
Lowdin, P.-O. Band theory, valence bond, and tight-binding calculations, B (9) 259*b*.
Lowell, C. E. See Sara, R. V.
Lowrie, R. Research on physical and chemical principles affecting high temperature materials for rocket nozzles, (8) 214*e*.
Lowther, D. R., and Wright, H. R. Round disk with noncircular backup pad, P (2) 33*g*.
Lozano, R. M. See Bautista, E. N.
Lozier, W. W. See Null, M. R.
Lozier, W. W., and Manofsky, M. B. Properties and performance of pyrolytic graphite, B (3) 92*d*.
Lubell, M. S. See McHugh, J. P.
Lubey, J. Highly refractory magnesite-chromite molded bodies, P (4) 102*b*.
Lucero, D. P. High dielectric material, P (10) 282*i*.
Lucia, L. V. Electrical resistance element, P (4) 105*h*.
Ludowici-Celadon Co. Tile measuring machine, P (11) 312*f*.
Ludwig, U., and Schwiete, H. E. Researches on hydration of trass cements, B (5) 150*d*.
Luebbe, H. See Burger, W.
Luertzing, P. R., and Luertzing, W. O. Joints for use in scientific glass apparatus, P (6) 157*e*.
Luertzing, W. O. See Luertzing, P. R.
Luff, D. See Robinson, A. E.
Lukacs, J., and Abrecht, H. Influence of several gas atmospheres on SiC refractory materials, B (10) 300*i*.
Lukantsever, Yu. L. See Sidlyarenko, V. I.
Luks, D. W., and Magee, J. H. Hollow sphere method for determining tensile strength of ceramics, (1) 23*h*.
Luk'yanova, O. I., Segalova, E. E., and Rebinder, P. A. Nature of the induction period in the hydration of portland cement with additions of hydrophilic plasticizer, (5) 126*e*.
Lumalampan Aktiebolag. Method of producing a light diffusing layer on glass surfaces, especially on the inside of electric lamp envelopes, P (2) 42*e*.
Lund, H. H. See Bortz, S. A.
Lundberg, H. L. See Fahlstrom, A. H. H.
Lundblad, E. High pressure vessel with punch, P (10) 285*f*.
Lundgren, G. See Ingri, N.
Lundin, C. E. See Nachman, J. F.
Lundquist, R. V., and Chardoul, N. Desilication of caustic leach liquors containing alumina, (6) 154*d*.
Lungu, S. N. See Popescu-Has, D.
Lurex Mfg. Co. Joints for use in scientific glass apparatus, P (6) 157*e*.
Lusher, K. G. Article handling apparatus, P (7) 185*i*.
Luttinger, J. M. Theory of the Hall effect in ferromagnetic substances, (3) 89*j*.
Lutz-Dettinger, E. Abrasives having mineral binders for wet grinding of steel and iron, P (4) 95*g*.
Lux, J. F. See Wahl, A. J.
Luzhnova, M. A. See Raikhbaum, Ya. D.
L'vov, S. N. See Verkhoglyadova, T. S.
Lynch, C. T., Vahldiek, F. W., et al. Investigation of single-crystal and polycrystalline titanium diboride—metallographic procedures and findings, (8) 228*i*.
Lynch Corp. Transfer and invert-revert mechanism for glass machines, P (3) 70*g*.
Lyon, T. F. See Kibler, G. M.
Lyons, E. H., Jr. Energy conversion process and apparatus, P (11) 303*a*.
Lyons, J. H. K. Customer-oriented product development, (4) 97*c*.
Lyons, J. W. See Min, H. S.; Van Wazer, J. R.
Lyons, J. W., Mins, H. S., Parisot, P. E., and Paul, J. F. Experimentation with a wet-process rotary cement kiln via the analog computer, (11) 302*a*.
Lyons, S. C. See Murray, H. H.
Lyons, V. J. Compound semiconductor material control, P (3) 77*d*. Diffusion in semiconductor material, P (4) 105*d*.
Lytle, W. O. Method and apparatus for producing filmed bent glass sheets, P (6) 158*d*.
Lyubov, B. Ya., Roitburd, A. L., and Temkin, D. E. Mathematical analysis of crystallization for bodies of simple shape, B (9) 262*b*.
Lyubov, B. Ya., and Temkin, D. E. Partition of soluble impurities during crystallization, B (9) 262*b*.

Maaz, K. See Kuhrt, F.
Mabru, M. See Charpentier, M.; Levecque, M.
Mabru, M., and Piot, P. Process and apparatus for the manufacture of wicks or threads from thermoplastic materials such as glass, P (7) 186*h*.
McAfee, K. B., Jr. Light gas detector using thin walled [0.2 to 10 mils] glass tubes for diffusion, P (11) 304*j*.
McAleer, W. J. See Barkemeyer, H. R.
McAllister, J. F. See Erd, R. C.
McAtee, J. L., Jr. Cation exchange of organic compounds on montmorillonite in organic media, B (5) 150*i*.
McAuley, J. W. Sonic treating apparatus, P (11) 312*d*.
McBrayer, R. D., Palmour, H., III, and Mehta, P. K. Chemical etching of defect structures in alumina-rich spinel single crystals, (11) 316*a*.
McCaleb, S. B. Hydrothermal products formed from montmorillonite clay systems, B (5) 150*f*.
McCallum, I. S. See Perrotta, A. J.
MacCallum, R. B., and Hurley, F. R. Method of preparing ferrimagnetic materials, P (3) 78*h*.
McCammont, R. G. Loading and transport of minerals in mines and quarries, P (2) 55*j*.
MacChesney, J. B., Gallagher, P. K., and DiMarcello, F. V. Stabilized barium titanate ceramics for capacitor dielectrics, (7) 192*f*.
MacChesney, J. B., and Muan, A. Phase equilibria at liquidus temperatures in the system iron oxide–titanium oxide at low oxygen pressures, (4) 117*h*.
Macchine Industria Doiciaria Carle & Montanari S. A. Installation for the automatic operation of hydraulic [filter] presses in a predetermined and continuous succession of working cycles, P (6) 167*d*.
McCleary, R. E. See Page, J.
McClellan, R. S. New storage method improves talc uniformity by 50%, (8) 225*h*.
McClelland, J. D. See Zehms, E. H.
McClelland, J. D., and Zehms, E. H. End-point density of hot-pressed alumina, (4) 113*f*.
McClung, F. J., and Hellwarth, R. W. Characteristics of giant optical pulsations from ruby, (7) 190*j*.
McClure, D. S. See Weakliem, H. A.
McClure, J. W. Analysis of multicarrier galvanomagnetic data for graphite, (3) 85*j*.
McCombie, C. W., Matthew, J. A. D., and Murray, A. M. Modification of lattice vibrations by an imperfection, B (9) 260*e*.
McConnell, D., and Murdoch, J. Crystal chemistry of ettringite, (8) 226*i*.
McConnell, D. P. Crushing apparatus [with vibrating jaw], P (6) 170*h*.
McConville, J. H. Semiconductor device contact, P (5) 137*a*.
McCord, J. Is our industry losing to competition through default? (6) 176*f*.
McCorkel, F. M., and Healy, V. R. Screening device, P (4) 111*f*.
McCormick, J. J. See Wittke, J. P.
McCormick, L. Ceramics solve metal casting problem, (8) 212*i*.
McCullen, H. L. Wet blasting, (3) 79*j*.
McCullough, J. D. Castable refractories for tunnel kiln car tops, (3) 71*i*. Interlocking ceramic tile elements, P (2) 45*j*.
McCurdy, K. G. See Thorvaldson, T.
McDermott, L. C. Comminution device, P (11) 315*f*.
McDevitt, N. T. See Baun, W. L.
McDonald, B. T. See Ruckwardt, K. F.
McDonald, R. A., and Stull, D. R. Heat content and heat capacity of crystalline boron from 298° to 1700° K, (1) 28*b*.
McDonald, W. J. See Duwell, E. J.
McDowell, J. S. See Clark, C. B.
McDowell, K. O. See Bauleke, M. P.
Macenauer, A. Rotational viscosimeter—concentric cylinder method, (6) 168*i*.
MacEwan, D. M. C. Interlamellar reactions of clays and other substances, B (5) 150*i*. See Martin Vivaldi, J. L.; Sutherland, H. H.
Macey, H. H. Moisture movement in plastic clay, (11) 305*f*. Probability screen, (10) 284*b*.
McFadden, C. A. See Remmey, G. B.
McGeary, R. K., and Winslow, F. R. Fuel element for a neutronic reactor, P (11) 308*c*.
McGill, A. Brick molding apparatus for incorporating metal inserts in refractory bricks, P (5) 133*b*.
McGowan, J. P. Glass shaping tools coated with nickel phosphorus alloy, P (4) 99*j*.
McGrain, P., Kendall, T. A., and Teater, T. C. Miscellaneous clay and shale analyses for 1957–1959, (8) 225*g*.
McGrath, H. E. Inflatable dunnage, (8) 230*h*.
Mach, O. See Ondracek, M.
McHenry, T. F. Two path infrared gas analyzer having one enclosed path, P (9) 253*b*.
Machin, J. S. See Deadmore, D. L.
McHugh, J. P., Lubell, M. S., Johnson, R. G. R., and Brown, J. T. Thermoelectric material, P (5) 137*f*.
McIlhenny, W. F., and Baker, A. B. Method for making potable water and magnesium chloride from seawater, P (2) 55*a*.

McIlvaine, R. L. Mulling and mixing apparatus, P (8) 222*e*.
McIntosh, R. See Valcin, A. S.
McIntyre, A. A. Method and apparatus for blending discrete materials, P (4) 106*i*.
McIntyre, G. H., Jr., Sprouse, N. T., and Haber, H. S. Production of boron trihalides, P (10) 290*d*.
McKay, D. S. See Fyfe, W. S.
McKee, R. L. Basics of surface grinding, (3) 79*d*.
McKee, W. D., Jr. See McMullen, J. C.
McKee, W. D., Jr., and Aleshin, E. Aluminum oxide-titanium oxide solid solution, (3) 85*i*.
McKelvey, E. E. See Boyer, E. W.
McKelvey, H. E. Molds [with movable sections] for bending glass sheets, P (9) 242*a*.
McKelvey, J. G., and Milne, I. H. Flow of salt solutions through compacted clay, B (5) 150*e*.
McKenna, F. E. Graphic symbols for glass systems, (5) 139*c*.
McKennell, R., and Bradfield, G. Viscometers, P (3) 80*b*.
Mackenzie, J. Symposium on high-alumina refractories: Use of high-alumina refractories in ironmaking, (11) 306*g*.
Mackenzie, J., and Lakin, J. R. Refractories for Ajax furnace roofs, (6) 161*b*.
Mackenzie, J. D. High-pressure effect on oxide glasses (I) densification in rigid state; (II) subsequent heat treatment, (11) 303*i*. (editor) Modern Aspects of the Vitreous State (Vol. 2), B (9) 263*h*. Refractory behavior of vanadia-silica glass, (2) 40*g*. Semiconducting oxide glasses—principle of preparation and typical examples, B (11) 320*j*.
Mackenzie, R. C. (compiler). Scifax Differential Thermal Analysis Data Index, B (2) 62*h*.
Mackenzie, R. C., and Mitchell, B. D. Differential thermal analysis, (5) 142*h*.
Mackey, J. H. Paramagnetic color centers and ionic mobility in germanium-doped quartz, B (11) 320*i*.
Mackey, R. J. Ceramic metalizing mixture and method of compounding it, P (9) 239*b*.
McKibbon, J. H. Developments in dust collection equipment, (3) 79*j*.
McKinley, A. H., and Underwood, D. T., Jr. Apparatus for slaking lime, P (3) 64*h*.
McKinney, C. D., Jr., Tarpley, W. B., and Gaskins, F. H. Applications of ultrasonic energy—ultrasonic casting of ceramic and cermet slips, (8) 221*d*.
McKulla, G. W., Jr. See Stalter, T. L.
Mackus, T. J. See McNeill, W.
McLachlan, D., Jr. Geometry of crystals, (10) 298*f*.
MacLean, A. J. Fixation of potassium in some Canadian soils, (5) 140*j*.
McLean, D. A. American developments in miniature capacitors, (9) 246*g*.
McLennan, D. B. See Becker, C. H.
McMahon, G. W. See Brown, R. F.
McMahon, J. F., Jr. See Certa, A. J.
McMahon, J. F., Jr., and Fahey, J. R. Method of making glass to metal seal, P (8) 208*d*.
McMaster, H. A. See Nitschke, N. C.
McMillan, P. W., and Hodgson, B. P. Electrically conductive glasses, P (9) 241*h*.
McMorris, M. N. See Horne, R. W.
McMullen, J. C., and McKee, W. D., Jr. Method for making zirconium boride, P (4) 102*f*.
McNabb, G. C. Split flow gas analysis detector, P (8) 224*b*.
McNally, H. L. Method of making lightweight aggregate, P (2) 44*a*.
McNally, R. N. See Doman, R. C.
McNamara, J. E. See Robertson, H. M.
McNeil, W., and Conroy, L. E. Electric properties of some dilute sodium tungsten bronzes, (9) 256*g*.
McNeill, W., and Chrostowski, J. E. Means for reducing thermal gradients in the hot-pressing of synthetic mica, P (11) 313*i*.
McNeill, W., Chrostowski, J. E., and Mackus, T. J. Method of making lamellar sheets of fluorphlogopite mica, P (11) 315*h*.
McNeilly, C. E., and De Poorter, G. L. Deformation of a structural clay body at high temperatures, (2) 43*h*.
McNerney, J. M. See Gross, P.
McQuade, J. M. Coated metallic sheet material and method of making it, P (2) 37*h*.
Macrae, J. C., and Murthi, K. S. Apparent variation in fluidity of a coking coal at a constant temperature below its active decomposition point, (7) 196*e*.
Macrosonic Process Corp. Methods and means for producing physical, chemical, and physicochemical effects by large-amplitude sound waves, P (8) 222*c*.
McSwain, B. D. See Borrelli, N. F.; Su, G.-J.
McSwain, B. D., Borrelli, N. F., and Su, G.-J. Effect of composition and temperature on the ultraviolet absorption of glass, (8) 208*j*.
McTaggart, G. D., and Dyer, C. E. Testing glass furnace refractories, (4) 101*i*.
McVay, T. L. See Browning, J. S.
Maddalon, G. See Occella, E.
Madden, T. C., and Gibson, W. M. Silicon dioxide passivation of *pn* junction particle detectors, (10) 282*e*.
Maddock, A. G., and Mohanty, S. R. Annealing of radiolytic damage in some nitrates (I) lead nitrate, (10) 290*e*.
Mader, H. Process for the recovery of cryolite from waste gases and from the carbon bottom of an aluminum electrolytic furnace, P (3) 85*b*.
Madera, J. See Tschudi, W. J.
Madge, J. G. Vertical washer for flat glass, P (10) 273*c*.
Madge, J. G., and Walker, A. D. Glass rolling apparatus, P (1) 11*c*.
Madison, R. E. Cement base paints, etc., P (3) 64*i*.
Madsen, W. M. Sand or fines filtering device for [rotary drum] dryers, P (5) 140*g*.
Maduk, E. A. See Haupin, W. E.
Maeda, M. Improvement of the method of laying brick in checker chambers, (11) 306*a*. See Yonemochi, O.
Maeda, T. See Kumazawa, S.
Maeder, H. J. See Decker, H.
Maekawa, A. See Soda, T.
Maekawa, S. Erosive effects of molten steel on pouring-pit refractories, (11) 305*j*. Snapping of roof brick hangers, (11) 306*h*.
Maekawa, S., and Yoneyama, Y. Rapid determination of sulfur in basic slag by combustion method, (6) 154*j*.
Maerker, R. "Fish scales"—a defect in the enameling of sheet steel, (8) 207*e*.
Maerz Ofenbau Akt.-Ges. Wall [expansion joint] construction and mounting thereof for industrial furnaces, P (8) 225*b*.
Maestas, T. E. Electrostatic separator [for ores], P (10) 289*g*.
Magee, J. H. See Luks, D. W.
Magee, J. V. See Conn, J. B.
Mager, L. Method of making a pressure vessel by winding metallic-coated glass filaments, P (8) 211*f*.
Magill, P. J. Compound barriers in thin film TiO_2 diodes, (7) 191*c*.
Magnaflux Corp. Visible indicator for sonic thickness measuring apparatus, P (3) 81*i*.
Magneto-Chemie, N. V. Electrolytic production of mixed metal oxides, P (5) 141*b*.
Magnusson, J. Technologist and his position in a glassworks for handmade ware, (7) 185*c*.
Mah, A. D., and Adami, L. H. Heats and free energies of formation of germanium dioxide, (1) 28*c*.
Mahanta, P. C., Hatibarua, J., and Das, R. K. Thermal expansion of cerium dioxide by X-ray diffraction method, (6) 175*h*.
Mahoney, J. F. See Ruckwardt, K. F.
Mainz, F. Method and apparatus for producing multiple glass sheet glazing units, P (8) 211*d*. See Kilian, G.
Maki, A. G. Thermal radiation standards and measurements of the Radiometry Section at the National Bureau of Standards, B (3) 93*c*.
Maki, I. See Watanabe, K.
Maki, T. See Tashiro, M.
Makida, M. See Ariizumi, A.
Makino, H. See Takemoto, K.
Makiuchi, T. See Oki, S.
Maksimova, G. V. See Gorina, Yu. I.
Maleev, E. N., and Ermakov, D. S. Single beam two-frequency pyrometer for measuring flame temperatures, (6) 168*b*.
Malhotra, H. L. Fire tests on V-brick, (1) 12*g*.
Malinowski, R. F. See Vodicka, V.
Malitson, I. H. Refraction and dispersion of synthetic sapphire, (5) 145*b*.
Malley, T. J., Schindler, H. D., and Pennell, J. D., Jr. Alumina of controlled density, P (8) 225*d*.
Mallol Forne, R. Effect of heat on concrete—refractory and insulating concretes, (8) 204*e*.
Mallory, K. B. See Johnson, D. A.
Malm, R. N., and Vodicka, V. Linings for miniature incandescent lamps, etc., P (6) 157*g*.
Malone, T. S., and Allegrini, A. P. Gel-forming attapulgite clay and method for preparing it, P (6) 170*j*.
Malquori, G. Portland-pozzolan cement, B (5) 150*b*.
Mal'tsev, A. A. See Tatevskii, V. M.
Malyshev, M. F., and Kazabrodskaya, G. V. Role of sodium ferrite in the extraction of aluminate sinters, (4) 120*f*.
Mambourg, J. E., Sporer, A. G., and Day, C. E. Method of and apparatus for feeding glass batch materials, P (5) 131*c*.
Mamen, C. I.M.C. potash plant in production, (10) 288*i*.
Mamykin, P. S., and Zlatkin, S. G. Calcium oxide crucibles, (5) 132*d*.
Mamzic, C. L. Peak seeking optimizers, (2) 51*b*.
Manabe, T. How time and temperature affect gypsum transformation, (6) 154*f*. See Soda, T.
Manabe, T., Kawada, N., and Nishiyama, M. Calcium carboaluminate, (7) 178*b*.
Manabe, Y. See Kataoka, N.
Mandal, S. S. See Dhar, R. N.
Mandarino, J. A. Some optical and stress-optical properties of synthetic ruby, (2) 58*g*.
Mandelkorn, J. Method of making a gallium sulfide dioxide, P (4) 105*h*.
Mandell, H. C., Jr. Flame photometry, P (8) 223*i*.
Manelis, R. M. Measurement of the strength of bonds between ceramics and metals, (9) 238*d*.
Manintveld, J. A. See Goorissen, J.
Mann, W. Crushing resistance of synthetic abrasives—experiment in relative measurement, (10) 265*f*, B (10) 300*g*.
Mannesmann Akt.-Ges. Apparatus for classifying particulate material, P (7) 197*g*. Lubrication method for hot-extrusion press, P (10) 269*c*.
Manney, C. J. See Schreyer, K. D.
Manning, R. H. See Kappmeyer, K. K.
Manning, Maxwell & Moore, Inc. Dial instrument [thermometer] with external calibration, P (10) 287*f*.
Manofsky, M. B. See Lozier, W. W.
Manring, W. H. See Conroy, A. R.
Mansfield, R. L. Fire tube furnace and method for baking [carbon] articles, P (1) 16*b*.
Mantysalo, E. See Hovi, V.
Maraman, W. J. See Ogard, A. E.
Marasas, L. W., and Harrington, J. S. Some oxidative and hydroxylative actions of quartz—their possible relation to the development of silicosis, (2) 60*f*.
Marboe, E. C. See Weyl, W. A.
Marburg, E. Hot tops with exothermic inserts, P (3) 74*b*.
Marchant, C. Future of construction products from industrial minerals, (3) 82*j*.
Marchioli, G., and Gremigni, G. Apparatus for shaping and compressing sheets of asbestos cement into particles of complex configuration, P (11) 312*f*.
Marcic, B. See Zincke, A.
Marciniak, S. Cobalt glass for safety goggles, P (2) 41*j*.
Marcot, G. C. See Nelson, E. W.
Marcyes, V. W., and Granger, T. L. Sound actuated control system for ball mill, P (1) 23*g*.
Marden, A. J. See Hopkins, B. J.
Mardulier, F. J. See Adams, A. B.
Marel, H. W. van der. Quantitative determination of kaolinite by X-ray diffraction, (6) 168*g*. See Beutelspacher, H.
Mar'evich, N. I. See Kaibicheva, M. N.
Margolis, D. P., and Walsh, E. G. Method of bonding metallic members, P (1) 5*a*.
Margrave, J. L. Chemistry at high temperatures, (9) 258*c*.
Margulis, O. M., and Gul'ko, N. V. Destabilization of cubic form of zirconium dioxide, (1) 27*g*.
Marinace, J. C. Vapor deposition of heavily doped semiconductor material, P (3) 79*c*. See Anderson, R. L.
Marinace, J. C., and Rutz, R. F. Formation of semiconductor devices, P (11) 311*d*.
Marinder, B.-O. Crystal structure of niobium dioxide, (5) 142*i*.
Marino, A. J., Jr. Method of joining a semiconductor to a conductor, P (3) 78*c*. See Battle, J. H.
Marino, A. J., Jr., and Seeley, D. C. Method and means for growing and treating crystals, P (8) 225*g*.
Marion, F. See Duquesnoy, A.
Mark, A. Process for producing single crystal silicon surface layers, P (10) 283*d*.
Mark, S. D. See Shaffer, P. T. B.
Markali, J. Observations on Nb_2O_5 whiskers and their strength properties, B (3) 92*a*.
Markevich, G. S. See Markovskii, L. Ya.
Markle, H. A., Jr. Cement plant arrangements most suitable for automation, (5) 126*c*.
Markovskii, L. Ya., and Bezruk, E. T. Chemical resistance of certain transition metal borides, (5) 141*j*.
Markovskii, L. Ya., and Markevich, G. S. Determination of softening temperatures for the system beryllium–boron in the beryllium-rich range, (5) 142*e*.
Markovskii, L. Ya., and Vekshina, N. V. Preparation of alkaline-earth borides by reduction of the respective oxides with carbon, (4) 118*e*.
Marks, M. L. See Bowen, S. W.
Marks, W. H. See Plant, H. T.
Marly, G. Continuous coating of mirrors with silver, P (4) 99*c*.
Maron, R. See Otto, H.
Marquez, J. M. S. See Serratosa Marquez, J. M.
Marriott, J. G., Felt, R. M., Boicey, J. H., and Ryan, J. D. Electrically conducting glasses for aircraft windshields, P (6) 157*j*.
Marsh, T. Folk potters of Mashiko, (7) 177*j*.
Marshale, C. E. Reaction of feldspars and micas, (4) 119*c*.
Marshall, W. L., and Gill, J. S. Aqueous systems at high temperature (III) investigations on the system UO_3–CuO–NiO–SO_3–H_2O at 300°C, (9) 255*a*.
Marshall, W. R., Jr. Spray drying apparatus, P (1) 23*g*.
Martens, F. H. See Spinrad, B. I.
Martin, A. E. Infrared spectrometer recorder wherein the spectra is recorded on a linear wave-number scale, P (11) 320*a*. Spectrometers [with rotating diffraction grating], P (6) 176*b*.
Martin, G. W. See Dils, R. R.
Martin, J. See Downs, C. D.
Martin, J. B. See Levin, E. M.
Martin, J. K. Decorating apparatus for ceramic flatware, P (2) 47*c*.
Martin, P. J., and Moehl, A. H. Open-hearth furnace [design], P (3) 74*h*.
Martin, R. Fuel arrangements for use in nuclear reactors having vertical channels, P (8) 216*b*.
Martin, R. L., and West, J. B. Solubility of magnesium oxide in molten salts, (9) 257*e*.
Martin, R. T. Adsorbed water on clay—a review, B (5) 150*c*. Water vapor sorption on kaolinite: Entropy of adsorption, B (3) 91*i*.
Martin, S. Method of doping crystals, P (6) 166*h*.
Martin, T. R., and Whatley, H. F. Method and machine for packaging bottles [with metal loops], P (5) 131*a*.
Martin, W. S. Optical constants and spectral emissivities at high temperatures, B (3) 93*c*.
Martinelli, P. P. Apparatus for measuring the thickness of a deposit, P (2) 53*b*.
Martinengo, F. Vinovo porcelain, (2) 33*j*.
Martinet, J. R. Dolomite furnace lining with carbonaceous bond, P (2) 45*d*.
Martinez, E. Effect of particle size on the thermal properties of serpentine minerals, (5) 143*c*.
Martinez Blanco, D. Brushes for ceramic decoration, (6) 153*i*.
Martini, R. W. See Wilcox, R. J.

Martin-Marietta Corp. Fissionable fuel capsules and method of manufacturing them, P (9) 244*h*. Hydraulic cement additives and cement compositions containing them, P (9) 237*g*. Method and machine for cutting tile pipe, P (1) 13*c*. Mortar additives, P (9) 237*j*.
Martin Vivaldi, J. L., Girela Vilchez, F., Hernaiz Bermudez de Castro, M., and Rodriguez Gallego, M. Thermal decomposition of NH_4 montmorillonites (1), (11) 320*a*.
Martin Vivaldi, J. L., Girela Vilchez, F., and MacEwan, D. M. C. Modifications to standard Philips powder cameras for clay mineral work, (11) 313*i*.
Martin Vivaldi, J. L., and Linares Gonzalez, J. Random intergrowth of sepiolite and attapulgite, B (5) 151*a*.
Martin Vivaldi, J. L., and MacEwan, D. M. C. Corrensite and swelling chlorite, (11) 314*j*.
Martirosov, S. M. See Men, E. M.
Marzocchi, A. Method for cleaning and coating fibrous glass, P (3) 70*b*. See Caroselli, R. F.
Marzocchi, A., and Billett, S. M. Metalized flattened glass strand and method of manufacturing, P (9) 242*d*.
Marzocchi, A., Lachut, F., and Willis, W. H., Jr. Glass fibers and their use as filter media, (2) 39*f*.
Marzocchi, A., Waugh, J. A., and Beaudoin, A. E. Glass reinforced gypsum, P (3) 65*b*.
Mash, D. H. Electroluminescent lamps, P (1) 21*a*.
Mash, D. R. (editor). Materials Science and Technology for Advanced Applications, B (3) 92*g*.
Masing, L., and Young, L. Kinetics of formation of anodic oxide films on bismuth, (3) 87*h*.
Mason, S. J. See Breen, S.
Massey, A. G. Uses of electrical discharges in preparative inorganic chemistry, (9) 252*i*.
Masson, R. Contribution to the question of microstress in porcelain bodies, B (10) 300*d*.
Masterson, F. H. Semiconductor devices, P (3) 70*d*.
Mateos, M., and Davidson, D. T. Steam curing and X-ray studies of fly ashes, (10) 267*j*.
Materiali Refrattari Societa per Azioni. Refractory compositions containing silica and silicon carbide, P (2) 46*g*.
Mathes, W. B. See Alexander, B. T.
Mathews, A. L. See Schmidt, J. E.
Mathews, A. W. See Ferguson, L. C.
Mathews, F. S. See Watt, A. D.
Mathias, B. B. Apparatus for acoustically measuring volume, P (5) 130*i*.
Mathieson, Olin, Chemical Corp. See Olin Mathieson Chemical Corp.
Mathieu, A. L. See Carson, J. A.
Matisoff, B. Cool electronic packages, (3) 76*c*.
Matouschek, F. How the chromate content of cement clinker is affected by magnesite brick containing chromium, (3) 72*i*.
Matsen, J. M., and Johnson, E. F. Extension of the Andrade equation for viscosity at the normal melting point, (1) 27*g*.
Matson, F. R., and Rindone, G. E. (editors). Advances in Glass Technology (Part 2) History Papers and Discussions of the Technical Papers of the Sixth International Congress on Glass, July 1962, Washington, D.C., B (11) 320*f*.
Matsuno, Y. See Terada, S.
Matsuo, C., and Kataoka, Y. Clinker brick for use in rotary cement kiln, (7) 178*i*.
Matsuo, Y., and Sasaki, H. PbO-rich side of the system PbO–TiO_2, (10) 296*g*.
Matsushiro, A. Some problems in repairing an open-hearth furnace where a large quantity of oxygen was used, (11) 306*h*.
Matsushita, T., and Ishikawa, T. Measurement of dielectric constant and dielectric loss by the powder method—application to synthetic mica, (8) 223*d*.
Mattes, B. L. Secondary piezoresistivity in oxygen deficient $BaTiO_3$ single crystals, (10) 282*c*. See Perls, T. A.
Matthew, J. A. D. See McCombie, C. W.
Matthews, J., and Buthala, D. A. Carbon films for electron microscopy, (11) 312*h*.
Matthews, S. Production of electronic ceramics, (6) 165*c*.
Mattison, A. C. Tradition vs. profit squeeze—the coming shakeout in machining, (5) 125*h*.
Mattock, A. H. Structural model testing—theory and applications, (7) 195*h*.
Mattock, G. Properties of two highly selective sodium ion-responsive electrode glasses, (5) 129*j*.
Mattock, G., and Uncles, R. Response of a sodium-sensitive electrode glass to silver, lithium, and thallous ions, (5) 129*e*.
Matveeva, T. A. See Kargin, V. A.
Matya, S. J. See O'Connor, J. A.
Maucher, A. See Albrecht, F.
Mauer, F. A. See Levin, E. M.
Maurer, K. Possibility of drying ceramic materials with electrical current, (4) 108*j*.
Maurer, R. D. See Stookey, S. D.
Max Braun, Firma. Ferromagnetic layers, P (4) 105*e*.
Maxon Premix Burner Co. Air-heating gas burner, P (1) 24*j*.
Max-Planck-Institut fuer Eisenforschung. Chromium oxide refractories, P (4) 102*d*.
Maxwell, E. L. See Watt, A. D.
Maxwell, J. A. Laser as a source in emission spectroscopy, (8) 223*c*.
Maxwell, L. H. Antimony-doped titanium oxide capacitors, (9) 246*h*.
Maxwell, W. J. Shipping container [for curved glass], P (3) 70*e*.
May, J. E. See Kronberg, M. L.
May, J. O. See Watson, A.
May, J. O., and Butterworth, B. Studies of pore-size distribution (III) effect of firing temperature, B (4) 124*d*.
May, M. Ceramics from Israel—exhibition in Munich, (10) 265*j*. Contemporary form developed from the traditional—work of Hans Meyer, (10) 265*i*. Otto Hufnagel, ceramist and art teacher, (7) 178*a*. Outstanding ceramic art achievements—five gold medals at the International Handicrafts Exhibition in Munich, 1962, (3) 63*j*.
Maycraft, G. W. See Clark, C. D.
Maydl, P. Structural composition material and process for making it, P (10) 268*b*.
Mayer, E. F. See Wainer, E.
Mayer, E. F., and Straughan, V. E. Method for producing inorganic [oxide] fibers, P (7) 189*f*.
Mayer, E. H. See Rahn, H. N.
Mayhe—, R. W., and Vogelpohl, R. L. Cathode ray tube envelope, P (4) 99*j*.
Maynard, N. See Smakula, A.
Maynor, H. W. See Pattison, J. N.
Mayo, G. J. J., Shepherd, W. H., and Thomas, A. G. Oxidation behavior of niobium-chromium alloys, B (7) 202*g*.
Mays, H. D. See Jordan, R. E., Jr.
Mays, R. L., Rhodes, H. B., and Leavitt, F. W. Reactivation of molecular [zeolitic] sieves, P (4) 104*d*.
Mazo, E. E. See Bezborodov, M. A.
Mazurin, O. V., Golikova, E. V., and Shtolitser, N. V. Effect of calcium oxide on electrical conductivity of glass containing two alkali oxides, (7) 184*d*.
Mchedlov-Petrosyan, O. P. See Babushkin, V. I.
Mchedlov-Petrosyan, O. P., and Babushkin, V. I. Thermochemistry and thermodynamics of the anhydrous and hydrated cement minerals, (7) 182*i*. Thermodynamics of the hardening processes of cement, B (5) 149*c*.
Meadors, O. L. See Lindeken, C. L.
Meanor, H. C. See Wranau, G. von.
Mecham, W. J., and Gabor, J. D. Fluorination of oxidic nuclear fuel, P (10) 289*i*.
Mechetner, B. K. See Barke, V. N.
Medcalf, W. E. See Fahrig, R. H.
Meddings, B. See Burkin, A. R.
Meder, H. See Decker, J. B.
Medlin, W. L. Thermoluminescence in dolomite (2) 48*c*.
Mee, C. H. B. Photoelectric emission from cathodes coated with strontium oxide, (5) 135*i*.
Meehanite Metal Corp. Method of improving foundry molds, P (1) 16*c*.
Megumi, N. Slag wool refining method and apparatus, P (2) 43*b*.
Mehal, E. W. See Johnson, R. E.; Jones, M. E.
Mehdi, S. See Rao, B. V. S. S.
Mehmel, M. Investigation of the surface of a glaze by light interference, (10) 278*f*.
Mehta, P. K. Slagging failure of refractories in cement rotary kilns, (2) 45*e*. See McBrayer, R. D.
Mehta, S. C. See Ghosh, S. K.
Meier, H. K. Corrosion-resistant cementitious mineral building materials and method of producing them, P (8) 206*b*.
Meier-Grolman, F. W. Corrosion-resistant cementitious mineral building materials and method of producing them, P (8) 206*b*.
Meigh, E. Vision screening in industry, (10) 271*h*.
Meinert, N. See Broemer, H.
Meisiek, H. See Glemser, O.
Meister, W. See Boettger, O.
Mekjean, M. Salt bath for electrolytic cleaning of metals, P (10) 269*g*.
Melcher, A. See Jacobs, G.
Melcher, R. E. See Wallace, B. P.
Mele, J. J. Ceramic coated bushings and allied products, P (1) 4*i*.
Mel'nik, M. T. See Bezborodov, M. A.; Kukolev, G. V.
Melsert, H. Method of manufacturing nickel supports for oxide cathodes and cathodes provided with them, P (2) 49*h*.
Memnonova, T. V. See Benediktova, N. B.
Men, E. M., and Martirosov, S. M. Mechanized production of mosaics, (1) 18*g*.
Menkovskii, M. A., and Churbakov, V. F. Simplified X-ray method for the quantitative determination of free silica in rocks, (9) 251*i*.
Mennitt, J. L. Apparatus for supporting and cutting semiplastic bodies, P (8) 221*c*.
Mentel, R. A., and Curtis, A. W. Gas-fueled infrared generator, P (8) 224*h*.
Menyuk, N., and Dwight, K. Low-temperature transition of magnetic anisotropy in nickel-iron ferrite, (3) 87*j*.
Mercer, O. H. Method and means for drying plaster molds, P (1) 23*c*.
Mercer, R. A. See Everest, D. A.
Merchant, H. D. Influence of metal roughness on surface texture of glass, (3) 66*d*.
Mercier, H. See Soudan, P.
Mercier, J. High-purity corundum, P (3) 83*i*.
Merck & Co., Inc. Process for preparing heavy metal tellurides, P (3) 84*g*. Production of semiconductor films, P (3) 78*j*. Thermoelectric materials, P (2) 50*b*.
Meriwether, H. R., Jr., Mewbourne, C. A., Warren, R. E., and Badger, A. E. Method and apparatus for treating glass, P (10) 272*a*.
Merkens, J. C. Gas meter for low rates of flow, (5) 139*c*.
Merker, L. See Dietzel, A.
Merker, L., and Wondratschek, H. Oxypyromorphite, $Pb_{10}(PO_4)_6O$, and the region $Pb_4P_2O_9$–$Pb_3(PO_4)_2$ of the system PbO–P_2O_5, (4) 117*i*.
Merlen, M. M. See Astheimer, R. W.
Merlub-Sobel, M. Molecular cermets and method of making them, P (3) 74*f*.
Merriam, M. F. See Kurnick, S. W.
Merry, J. D., and Vondracek, C. H. Three uses for flame sprayed alumina, (7) 183*c*.
Mertz, F. A. See Walker, R. S.
Merz, K. M. See Kirchner, H. P.
Merz, K. M., and Adamsky, R. F. Synthesis of the wurtzite torm of silicon carbide, (2) 59*e*.
Merz, K. M., Brown, W. R., and Kirchner, H. P. Thermal-expansion anisotropy of oxide solid solutions, (1) 30*g*.
Merz, W. J. Ferroelectricity, B (9) 263*i*.
Mestdagh, J. J. See Freedman, B.
Metal Box Co., Ltd. Manufacture of hollow articles, P (8) 211*b*.
Metallgesellschaft Akt.-Ges. Firing and sintering of alkaline earth carbonates, P (3) 76*a*. Process for producing hydraulic limes from oil shale, P (10) 290*b*. Titanium boride coatings on metals, P (2) 38*c*.
Metallizing Co. of America, Inc. Molten material spray gun with laterally deflecting air cap, P (8) 208*a*.
Metropolitan Brick, Inc. Tile punching apparatus, P (2) 44*b*.
Metz, A. Application of the hot-stage microscope to technical problems, (3) 80*g*. Dilatometer and its use in ceramic problems, (10) 286*b*.
Metzel, H. Firing of porcelain in tunnel kilns with liquefied gas, (7) 196*g*.
Metzel, H., and Olschewski, K. H. C_4 hydrocarbons as gaseous fuels for the firing of porcelain, (3) 81*j*.
Meunier, G. See Brichard, E.
Meurs-Hoekstra, W. van. See Bril, A.
Mewbourne, C. A. See Meriwether, H. R., Jr.
Meyer, A. F. See Hentschel, E.
Meyer, Geo. J., Mfg. Co. See Geo. J. Meyer Mfg. Co.
Meyer, H. W. Solubility of lead in molten silicates, (3) 64*d*.
Meyer, J. W., and Jaunarajs, K. L. Synthesis and chemical chemistry of gyrolite and reyerite, (5) 146*f*.
Meyer, J. W., and Yang, J. C.-S. Some observations in the system MgO–H_2O, (5) 146*a*.
Meyer, K., and Rausch, H. Firing and sintering of alkaline earth carbonates, P (3) 76*a*.
Meyer, L. J. Impellers for comminutors [loose strikers], P (10) 289*j*.
Meyer, R. W. Method of forming color-patterned glass fiber panels, P (3) 70*c*.
Meyerhofer, D. Transition to the ferroelectric state in barium titanate, (3) 89*b*.
Meyers, D. B. Enamel shop practices, (2) 36*h*.
Meyrowitz, R. Semimicroprocedure for the determination of ferrous iron in nonrefractory silicate minerals, (11) 313*g*. See Hickling, N.
Meyrowitz, R., and Westley, H. Stability of the arsenic tribromide immersion liquids during storage, (4) 107*i*.
Mezard, R. See Zarzycki, J.
Micanite and Insulators Co., Ltd. Mica flakes, P (3) 84*d*.
Michel, H. See Perraut, J. M.
Michel, V. E. See Vargin, V. V.
Mick, W. F. Steel pipe having organic thermoplastic liner with glass fiber reinforcement, P (4) 100*c*.
Mickley, H. S., and Korchak, E. I. Graphical method easily determines multistage exchanger performance, (2) 53*j*. How to find optimum economic size for multistage heat exchangers, (3) 81*j*.
Micks, W. R. Novel structural composite material, P (10) 277*j*.
Microcell, Ltd. Glass compositions, P (2) 42*g*.
Midgley, C. M. See Midgley, H. G.
Midgley, H. G. Mineralogical examination of set portland cement, B (5) 149*a*.
Midgley, H. G., and Midgley, C. M. Mineralogy of some commercial vermiculites, (11) 314*k*.
Midgley, H. G., and Rosaman, D. Composition of ettringite in set portland cement, B (5) 149*e*.
Midgley, H. G., Rosaman, D., and Fletcher, K. E. X-ray diffraction examination of portland cement clinker, B (5) 148*g*.
Midland Mfg. Co., Inc. Method and apparatus for drilling minute holes in small ceramic wafers, etc., P (5) 138*b*.
Midland-Ross Corp. Furnace roller, P (4) 108*g*.
Midori, Y. See Nakayama, T.
Midwest Pressure Casting Co., Inc. Method and means for drying plaster molds, P (1) 23*c*.
Mields, A. See Lehmann, H.
Mielenz, R. C. See Kelly, T. M.
Mifflin, E. L., Jr. See Dilliard, A. E.
Migonadjiev, A. S. See Budnikov, P. P.
Mihailovic, Z. Apparatus for the measurement of the thermal conductivity of nuclear ceramics, (3) 71*i*.
Mikhailov, V. V. Stressing cement and the mechanism of self-stressing concrete regulation, B (5) 150*a*.
Mikhlin, E. Ya. See Agranovich, V. M.
Mikhlin, M. E. See Gorskii, F. K.
Mikhnevich, G. L., and Gudz', P. N. Nucleation and crystal size distribution for supersaturated solutions of sucrose, B (9) 262*d*.
Mikhnevich, G. L., and Stepula, E. V. Kinetics of crystallization around impurity particles, B (9) 262*d*.
Mikhnevich, G. L., and Yanchuk, R. A. Crystallization of sucrose solutions during the latent period, B (9) 262*d*.

Miksits, R. Impregnated paper to serve as a dielectric, especially in condensers to improve their critical performance, P (9) 249*c*.
Mildh, G. Transporting means [with reciprocating blade] for pulverous or granular materials, P (3) 80*b*.
Miles, G. D. See Clarke, F. J. P.
Mileski, S. E., and Raeuber, A. E. Development of heat-resistant paints for metals, (9) 238*c*.
Millar, N. S. C. Metal preparation for direct-on enamel application, B (11) 322*h*.
Miller, A. R. See Su, G.-J.
Miller, C. K. See Powell, H. E.
Miller, E. B. See Rosin, S.
Miller, E. D., Jr. Alumina refractories, P (3) 73*f*.
Miller, G. E., and Voss, W. G. Corrosion testing of enamel coatings for hot water heaters, (2) 36*e*.
Miller, G. L., and Cox, F. G. Development of oxidation resistance of some refractory metals, B (7) 202*i*.
Miller, H. A. Nacreous material from titanium dioxide, P (4) 111*d*.
Miller, H. B. Ferrite transducers, P (3) 77*a*.
Miller, J. A., Fishburn, H. W., and Montague, H. Mortar staining in some brick walls, (11) 305*e*.
Miller, J. F. See Griffin, W. F.
Miller, J. L. See Gibbs, G. V.
Miller, J. L., and Johnson, R. C. Synthesis and properties of a fluormica intermediate between fluortaeniolite and fluorhectorite, (7) 201*e*.
Miller, J. L., Jr., Turner, I. L., and Shell, H. R. Lead and barium disilic fluormicas, (9) 247*b*.
Miller, J. R. See Firnhaber, M. S.
Miller, J. S. See Boswell, D.
Miller, M. G. See Layer, H.
Miller, R. C. Some experiments on the motion of 180° domain walls in $BaTiO_3$, (4) 120*j*.
Miller, R. C., and Savage, A. Velocity of sidewise 180° domain-wall motion in $BaTiO_3$ as a function of the applied electric field, (3) 89*e*.
Miller, R. E. Cleaning, surface treating small parts automatically, (6) 155*b*.
Miller, R. H. See Johnson, D. A.
Miller, R. L. Terra sigillata glazes, (7) 178*a*.
Miller, R. P. See Everest, D. A.
Miller, R. R. See Ewing, C. T.; Walker, B. E.
Miller, W. See Scheffer, H. G.
Miller, W. A., and Calvert, W. L. Viscosimeter, P (1) 24*d*.
Millington, R. J., and Quirk, J. P. Permeability of porous solids, (10) 290*g*.
Milne, I. H. See McKelvey, J. G.
Milnes, G. C., and Isard, J. O. Mechanism of electrical conduction in lead silicate glasses and its dependence on "water" content, (3) 67*h*.
Milton, C., Ingram, B. L., and Blade, L. V. Kimzeyite, a zirconium garnet from Magnet Cove, Arkansas, (4) 109*c*.
Milton, C. B. See Long, J. C.
Milton, R. M. Synthetic crystalline zeolites, P (6) 171*e*.
Milward, G. L. See Everest, D. A.
Min, H. S., Parisot, P. E., Paul, J. F., and Lyons, J. W. Computer simulation of wet process cement kiln operation, (5) 126*d*.
Minakawa, Z., and Obata, M. False set of cement, (8) 204*f*.
Minar, S., and Myska, L. Stable high-refractive-index coatings for glass, P (2) 43*a*.
Mine Safety Appliances Co. Electrochemical determination of components in gas mixtures, P (1) 24*b*.
Mine and Smelter Supply Co. Crusher jaws [design], P (5) 138*k*. Ore crusher [with overload release], P (11) 315*e*.
Mineralchemie Werner & Co. Shaped bodies consisting of minerals and a binder, P (4) 104*d*.
Minerals & Chemicals Philipp Corp. Attapulgite clay filter aid product and method of making it, P (6) 170*e*. Gel-forming attapulgite clay and method for preparing it, P (6) 170*j*. Lightweight adsorbent clay product and method of making it, P (1) 25*j*. Method of brightening clay by froth flotation of sulfidized clay pulp, P (5) 141*e*. Method for comminuting kaolin clay, P (10) 289*a*. Method of drying attapulgite clay dispersions, P (1) 26*c*. Method for making synthetic zeolitic material, P (10) 289*f*. Method for preparing aqueous dispersions of clay coated with polymers of ethylenically unsaturated monomers and aqueous film forming compositions produced, P (4) 111*a*. Method for producing rounded contact masses, P (6) 171*b*. Method for producing synthetic crystalline zeolite aggregates, P (11) 315*c*. Synthetic crystalline zeolite produced from dehydrated aluminum silicate, P (3) 85*a*.
Mining Research Corp. Crushing apparatus [with vibrating jaw], P (6) 170*h*.
Ministere des Richesses Naturelles (Canada). Lithium carbonate production, P (1) 26*a*.
Ministry of Petroleum and Chemical Industry of Romania. Conversion of fused glass to porcelain by crystallization after shaping and solidification, P (2) 42*b*.
Minneapolis-Honeywell Regulator Co. Measuring apparatus, P (2) 53*b*. Method of making ceramic-metal seals, P (3) 78*e*. Temperature measuring apparatus, P (1) 24*g*.
Minnesota Mining and Mfg. Co. Apparatus for determining molecular weight, P (8) 230*c*. Bonding of lead based alloys to silicate based ceramic members, P (6) 165*f*. Fuel element recovery process, P (8) 216*d*. Reaction milieu and afterburner incorporating it, P (8) 224*j*. Thermally resistant articles and method for their fabrication, P (6) 162*j*. Thermoelectric devices and thermoelements, P (1) 24*b*. Ultrathin glass sheet, P (9) 242*h*.
Minnick, L. J. Compositions for building load supporting surfaces, P (5) 127*b*.
Minowa, S. See Kato, M.
Minowa, S., Kato, M., and Mizuta, M. Reaction between molten steel and refractories (VII) rate of reaction between molten high carbon iron and silica or alumina crucible, (1) 14*a*; (IX) effect of elements in molten iron on the reduction of SiO_2, (1) 14*f*.
Minowa, S., Kosaka, M., Kato, M., and Mizuta, M. Reaction of steel with silica sand, (9) 243*f*.
Mins, H. S. See Lyons, J. W.
Mirnik, M. See Herak, M. J.
Misawa, T. "Oscillator" phenomena in extrinsic semiconductors, (4) 117*g*.
Miselyuk, E. G. See Belyaev, A. D.
Miserocchi, H. F. Method of making thermistor bolometers, P (3) 78*g*.
Misra, M. L. Refractory materials from Bansi and Emlo (their properties and mineralogical nature), (2) 54*f*.
Misra, S. K., and Chaklader, A. C. D. System copper oxide–alumina, (11) 319*c*.
Mitchell, B. D. See Mackenzie, R. C.
Mitchell, E. W. J. See Bastin, J. A.; Clark, C. D.
Mitchell, E. W. J., and Townsend, P. D. Luminescence from ruby excited by fast electrons, (6) 164*a*.
Mitchell, J. J. Process of making mixed oxide films, P (3) 65*f*.
Mitchell, J. K. Components of pore water pressure and their engineering significance, B (5) 150*d*.
Mitchell, J. W. Equilibration of lattice defects in real crystals, B (9) 260*b*.
Mitchell, W. P. See Davidson, C. R., Jr.
Mito, S., and Aoki, Y. Electroluminescence of ZnS:CuAl excited at high frequencies (I), (10) 292*a*.
Mitoff, S. P. Electrical conductivity and thermodynamic equilibrium in nickel oxide, (3) 76*g*. Electronic and ionic conductivity in single crystals of MgO, (9) 247*f*.
Mitronovas, F. See Olson, R. S.
Mitsuishi, A., Yoshinaga, H., and Fujita, S. Far infrared absorption of ferrites, (6) 173*e*.
Mitsuishi, A., Yoshinaga, H., Fujita, S., and Suemoto, Y. Vibrational spectra of ruby and hematite in the infrared region, (5) 147*c*.
Mitsuki, C. See Izumi, G.
Mittenbuehler, A. Measurement of thermal conductivity of refractories by the hot-wire method, (3) 72*a*.
Mitusch, H. Properties and use of refractory concrete made from alumina cement, (3) 72*d*.
Miyahara, S. See Ohnishi, H.
Miyairi, H. See Goto, K.; Hanada, M.
Miyakawa, T. See Nakahara, M.
Miyakawa, T., Takakusa, Y., and Nakahara, M. Plasticity figure of slaked lime for use as plaster, (1) 2*j*.
Miyake, K. See Hijikata, K.
Miyamoto, H. See Rokunohe, M.
Miyano, K. See Sawamura, M.
Miyatake, K., and Furumi, K. Effect of atmosphere on properties of magnesia-chrome brick, (11) 305*f*. Examination of unburned chrome-magnesia brick for the roof of an open-hearth furnace, (11) 306*a*.
Miyatani, S. See Yokota, I.
Miyazawa, K. High-magnesia cement, (8) 205*f*. Magnesia in portland cement, (7) 180*i*.
Miyazawa, K., and Kamao, H. Masonry cement, (8) 205*d*.
Miyazawa, K., Kamao, H., and Tazawa, M. Masonry cement made with low-grade limestone, (7) 181*a*.
Mizetskaya, I. B. See Vitrikhovskii, N. I.
Mizuno, S. See Rokunohe, M.
Mizuta, M. See Kato, M.; Minowa, S.
Mochizuki, M. See Hirose, K.
Mockrin, I., and Kowalski, A. Fluoaluminate composition as dielectric material, P (10) 282*f*.
Mod, W. A., and Becker, C. W. Recovery of beryllium from acid leach solutions, P (2) 55*j*.
Modelle, P. A. Apparatus for shaping mouth portions of glass articles [vials], P (1) 10*j*.
Moe, L. A. Ingredient content determination, P (7) 193*c*.
Moehl, A. H. See Martin, P. J.
Moehling, W., and Thiel, H. True structure of CdS crystals, (3) 89*d*.
Moellenstedt, G. See Cartz, L.
Moeller, C. E. Special surface thermocouples, (9) 252*a*.
Moeller, C. W. See Patterson, F. K.
Moeller, W. See Witzmann, H.
Moffat, M. E. B. See Free, J. M.
Moffitt, R. B. Drain tile—two for the price of one, (9) 243*a*. This. . .not this, (11) 305*f*.
Mohanty, S. R. See Maddock, A. G.
Mohler, N. Automation fights off rising costs, (4) 100*k*. Machine lays 900 brick per hour, (8) 211*j*. New strides in rail shipments, (8) 230*i*. Soft-mud brick, (8) 211*j*.
Mohyuddin, I., and Douglas, R. W. Some observations of the anelasticity of glasses—correction, (8) 209*c*.
Moldovan, A. Pallet for brick cubes and means for handling it, P (8) 212*a*.
Molesworth, T. V. Glass for chemical plant, (1) 6*j*.
Moll, S. See Brill, R. H.
Mols, A. Process for the continuous manufacture of reinforced cast glass, P (8) 211*b*.
Momoki, K. Dilution method for fluorescent X-ray spectrometry of powder sample, (2) 56*h*.
Monath, A. Abrasive materials, P (4) 95*g*.
Monath, H. Abrasive materials, P (4) 95*g*.
Mones, A. H., and Banks, E. Cation substitution in $BaFe_{12}O_{19}$, (11) 316*d*.
Moneta, F. Enamel in household appliances, B (11) 322*g*.
Monfore, G. E. Direct current strain bridge, (3) 80*i*.
Monlux, C. R. Furnace roof suspended by interconnected [metal encased] brick hanger extensions, P (5) 133*h*.
Monolith Portland Cement Co. Apparatus and method for conveying slurry, P (9) 250*e*.
Monro, H. Glass engraving, (2) 33*j*.
Monroe, E. A. Reactions between fireclay ladle bricks and basic slags, (8) 214*a*.
Monsanto Chemical Co. Boron phosphide articles and coatings, P (9) 239*b*. Clay beneficiation, P (4) 110*g*. Composition of metal oxides and carbon black, P (10) 289*f*. Crystallization of boron phosphide, P (6) 176*a*. Method for the preparation of inorganic selenides and tellurides, P (2) 49*i*. New near infrared spectrum filter media, P (1) 12*c*. Process of decreasing the salt content of an acidic silica hydroorganosol, P (1) 26*a*. Process for preparing boron phosphide, P (10) 277*g*. Process for the production of metal borides, P (10) 277*g*. Production of single crystal boron phosphide, P (5) 133*h*. Spark plug, P (3) 76*a*. Thermoelectric device, P (2) 50*a*. Thermoelectricity, P (6) 166*h*, P (7) 194*e*, P (8) 221*c*, P (10) 283*h*. Tunnel diode, P (4) 106*c*. Water sensitive molds and cores of fast collapsibility, P (1) 17*e*.
Montague, H. See Miller, J. A.
Montecatini-Societa Generale per l'Industria Mineraria e Chimica. Aqueous dispersions of high molecular weight fibrils of amorphous silicates, P (4) 104*e*. Glass fibers from aqueous compositions, P (2) 42*h*. Process for production of alumina from bauxite and other aluminous materials, by pyrogenic attack, in agglomeration plants, under either suction or pressure, P (3) 84*j*.
Montgomery, E. C. See Sharp, D. E.
Montgomery, R. S., and Tobey, H. M. Retardation of set time of aqueous gypsum compositions, P (2) 36*a*.
Monzo, A. B. See Blat Monzo, A.
Moody, B. E. Symposium on control of the quality of glassware: Theoretical and practical aspects of sampling schemes, (9) 241*a*.
Mooney, C. F. Method of making aspheric optical elements, P (3) 70*f*.
Mooney, R. W. Tin-activated calcium silicate phosphor, P (3) 79*c*.
Moore, A., and Harbke, W. An Old World pottery, (4) 95*i*.
Moore, E. E. See Saunders, J. A.
Moore, F. See Astbury, N. F.
Moore, F. C. Destructible reinforced sand core for metal casting, P (4) 102*e*.
Moore, F. M. See Andrews, R.
Moore, J. E. See Krebs, R. D.
Moore, N. C. See Davies, W. J. K.
Moore, N. C., Huffadine, J. B., and Chapman, L. Heat-resistant bodies of sintered molybdenum silicide-aluminum oxide mixture, P (6) 162*d*.
Moore, R. E. Method of making ceramoplastic material, P (2) 49*c*.
Moore, R. H. Fused-salt process for recovery of values from used nuclear-reactor fuels, P (6) 167*b*.
Moore, R. L. High-speed servo positioner bonds mesa transitors, (7) 191*a*.
Moore, W. H. Method of improving foundry molds, P (1) 16*c*.
Moore, W. J. See O'Keeffe, M.
Moosbrunner Glasfabrik, A. G. Apparatus for forming profiled glass sheets, P (6) 157*d*.
Moran, R. Chemical pretreatment in enameling, (3) 65*d*.
Moran, V. J. Structure in the fracture surface of silicate glass, (4) 99*a*.
Moraru, D., and Risnoveanu, A. Studies on building materials used in Roman buildings with mosaic work, (10) 266*b*.
Morawietz, H. See Brauer, G.
Morawski, J. Cyclone separator, P (3) 83*f*.
Morcos, S. See Hofmann, U.
Moreland, S. T., and Tyner, R. E. Glass jar unloader, P (5) 130*j*. Photoelectric inspection of glassware, P (5) 131*d*.
Morelock, C. R., and Sears, G. W. Growth of whiskers by chemical reactions, (2) 57*i*.
Morey, G. W. Action of water on calcite, magnesite, and dolomite, (6) 169*f*. Alkali aluminate crystals and potassium ferrite, (6) 169*h*.
Morey, G. W., and Fournier, R. O. Decomposition of microcline, albite, and nepheline in hot water, (5) 142*a*.
Morgan, H. C. See Beach, H. J.
Morgan, H. W., and Staats, P. A. Infrared spectra of dilute solid solutions, B (9) 260*f*.
Morgan, J. G., Osborne, M. F., and Sisman, O. Irradiation effects in the EGCR fuel, (4) 101*g*.
Morgan, P. (editor). Glass Reinforced Plastics, B (1) 32*c*.
Morgan, W. L. Production of [vapor] coated fibers, P (5) 131*f*. See Russell, R. G.; Slayter, G.
Morgan, W. L., Coen, J. K., and Fleming, J. D. Fibrous glass reinforcement, P (7) 186*a*.
Morgan, W. L., Morrison, A. R., and Shannon, R. F. Fibrous glass product and method of manufacture, P (3) 69*h*.

Morgan Crucible Co. Molybdenum-alumina cermets, P (6) 162*j*.
Morgenshtern, Z. L. See Vasil'eva, N. N.
Morgenstern, J. C. See Skinner, B. J.
Morgulis, N. D., and Korchevoi, Yu. P. Application of thorium carbide to the thermionic conversion of heat into electrical energy, (10) 279*g*.
Mori, C. See Enomoto, S.
Mori, H. See Sudoh, G.
Mori, H., and Inoue, Y. Color of portland cement and hardened mortar, (7) 178*j*.
Mori, I. See Kajihara, H.
Mori, K. See Narita, K.
Mori, M. See Fujii, J.; Hiraoka, G.
Mori, S. See Okazaki, C.
Mori, S., Hayashi, T., and Kyoden, H. Tests of Belgian rammed ladle refractory, Ladelit, (11) 308*h*.
Mori, Y., Eguchi, K., and Noda, A. Borosilicate glasses (II) change in the linear expansion of borosilicate glasses with time in the transformation range, (5) 128*g*.
Mori, Y., Eguchi, K., Noda, A., and Uetsuki, T. Borosilicate glasses (I) change in density and refractive index on thermal treatment, (5) 128*h*. Changes in infrared absorption spectra on crystallization of some glasses, (5) 128*h*.
Morinaga, K. Oxygen process for iron and steel making (I, II), (6) 160*j*.
Morio, A. See Sakurai, S.
Morita, S. See Kato, E.
Moriya, T. See Sakaino, T.
Moriya, T., Sakaino, T., Akao, Y., and Inoue, N. Study on the strength of glass plates used for the portholes of an undersea observation vessel, "Kuroshio," (1) 9*f*.
Moriya, Y. Quartz glass, P (2) 43*b*. See Izumitani, T.
Morley, C. W. See Emblem, H. G.
Morlock, H. A. Comolded magnesite-chromite tuyere, P (8) 215*h*.
Morozov, V. N., Tyurin, V. V., and Snezhinskii, N. S. Service of refractories in direct-heated tank furnaces, (1) 8*i*.
Morrill, V. Apparatus for shrinking tubular glass blank, P (9) 241*f*.
Morrill, V., Jr. Method for shaping a glass tube preform, P (9) 242*g*.
Morris, G. H., Jr. See Leaycraft, E. C.
Morris, J. M. See Evans, R. W.
Morris, L. D., and Brookman, R. S. Dust collector, P (3) 83*g*. Dust collector [with continuous filter], P (7) 195*a*.
Morris, T. J. See Osborne, R. W.
Morrison, A. R. See Morgan, W. L.; Slayter, G.
Morrison, A. R., and Apellaniz, J. A. Heat setting of binder of fibrous masses, P (10) 272*d*.
Morrison, I. R., and Wilson, A. L. Absorptiometric determination of silicon in water (I) formation, stability, and reduction of α- and β-molybdosilicic acids, (9) 250*g*; (II) method for determining "reactive" silicon in power-station waters, (9) 250*h*; (III) method for determining the total silicon content, (10) 285*i*.
Morrison, J. See Lander, J. J.
Morrow, A. S., Brewer, A. G., and Torbin, M. A. Glass mold lubricant, P (1) 11*b*.
Morrow, S. A. See Tomlinson, L.
Morrow, S. A., Graves, S., and Tomlinson, L. Hydrogen reduction of low-surface area uranium trioxide, (10) 293*f*.
Morsanyi, A. V. Effect of vanadium compounds on silica refractories, (8) 213*g*.
Morse, L. E. Catalytic recombination of radiolytic gases in thorium oxide slurries, P (1) 15*i*.
Mortensen, J. L. Adsorption of hydrolyzed polyacrylonitrile on kaolinite, B (5) 150*j*.
Mortland, M. M. See Ellis, B. G.; Lai, T. M.
Mosaic Tile Co. Acoustical panel, P (8) 218*a*.
Moser, F. Equilibrium properties of solid solutions of copper ions in large AgCl crystals, B (9) 260*b*.
Moskvin, N. A. See Kaplyanskii, A. A.
Moss, R. H. See Charland, T. L.
Moss, R. W. See Krogstad, R. S.
Motorola, Inc. Method for making semiconductor device, P (3) 78*g*.
Motz, J. Properties and manufacture of massive bodies of zirconium hydride produced by powder metallurgical methods, (10) 275*g*.
Motz, J. C. Mantle structure for gyratory crusher, P (5) 141*c*.
Mould, R. E. See Caporali, R. V.
Moulson, A. J. See Dinsdale, A.
Moulson, A. J., and Roberts, J. P. Water in silica glass, (8) 210*a*.
Moulton, A. K. Vibrating [rotary anvil] crushers, P (8) 222*d*.
Mouly, R. J. Electrical measuring and control apparatus and a glass press embodying it, P (5) 130*i*.
Mounce, G. R. See Hutter, J. F.
Mountford, N. D. G. See Emblem, H. G.
Mountvala, A. J. Hot-pressing piezoelectric and ferroelectric materials, (4) 104*g*.
Moussou, J. Suspension insulators provided with a core and an envelope, P (5) 137*c*.
Mozheiko, V. I. See Dubrovo, S. K.
Mozzi, R. L., and Guentert, O. J. X-ray study of phase transformations in some rare-earth oxide systems, (9) 257*h*.
Muan, A. Silver-palladium alloys as crucible material in studies of low-melting iron silicates, (7) 200*b*. See Aukrust, E.; MacChesney, J. B.; Phillips, B.; Riboud, P. V.
Muan, A., and Somiya, S. System iron oxide—manganese oxide in air, (5) 146*d*.
Mucon Corp. Ceramic dielectric compositions and method of making them, P (6) 165*h*.
Mueller, C. Radioactive isotopes in bin and level indication of granular materials and liquids, (5) 138*d*.
Mueller, F. Filtration in the structural clay and ceramic whiteware industries, (3) 79*d*.
Mueller, J. A. Grinding wheel potential today, (8) 203*e*.
Mueller, K. H. See Koltermann, M.; Lehmann, H.
Mueller, N. Sintering of urania, (10) 276*i*.
Mueller, R. F. Theory of homologous sublattices and intracrystalline equilibria, (11) 319*f*.
Mueller, W. See De Woody, C. M.
Mueller, W. M. (editor). Advances in X-Ray Analysis (Vol. 5) Proceedings of the Tenth Annual Conference on Applications of X-Ray Analysis, August 1961, B (2) 60*j*.
Mueller-Buschbaum, H. K. See Witzmann, H.
Mueller-Hesse, H. See Gelsdorf, G.; Planz, J. E.
Muetterties, E. L. Chemistry of the difluorides of germanium and tin, (1) 26*i*.
Mularz, W. L. See Hockings, E. F.
Muldawer, L. Temperature responsive resistance control elements, P (8) 224*c*.
Mulford, R. N. R., Ellinger, F. H., Hendrix, G. S., and Albrecht, E. D. Plutonium–carbon system, B (8) 231*d*.
Mulford, R. N. R., and Lamar, L. E. Volatility of plutonium oxide, B (8) 231*h*.
Mulisch, E. Vibratory mills and the milling of refractory raw materials, (10) 284*h*.
Muller, H. See Brauer, G.
Muller, R. H. Applications of automatic weighing, (7) 195*f*.
Munch, R. H., and Pierron, E. D. Practical method of powder sample preparation for X-ray diffraction, (9) 251*e*.
Mundinger, K. P., G.m.b.H. Hygrometer, P (2) 53*d*.
Munekata, E., and Sagawa, H. Water-quenched slags suitable as additives for concrete, P (4) 96*j*.
Munn, P. N. See Knights, H. C.
Munro, M. Errors in the measurement of $2V$ with the universal stage, (11) 317*j*.
Munro, W. See Barnes, E.
Murakami, K. See Sugiura, T.
Murakami, K., Ijima, Y., Saito, K., Sano, K., and Shindo, K. Effect of fluorine on the growth of gypsum crystal and its prevention, (5) 126*f*.
Murakami, K., and Tanaka, H. Quality test of by-product gypsum from phosphoric acid manufacture, (2) 35*d*.
Murakami, T. See Seto, K.
Murata, N. See Aoi, S.
Murdock, A. W. See Delangre, M.
Murdoch, J. See McConnell, D.
Murdock, J. B., and Stein, H. A. Furnace for expanding perlite, etc., P (10) 288*b*.
Murley, E. M., Jr. Inhibiting false signals [line voltage variation] in electronic gaging, P (1) 11*f*.
Murley, P. C. See Kennedy, D. P.
Murphy, N., and Ciceri, C. Method of manufacturing matching sheets of glass, P (1) 12*d*.
Murray, A. M. See McCombie, C. W.
Murray, G. T. See Adams, M. A.
Murray, H. H., and Lyons, S. C. Further correlations of kaolinite crystallinity with chemical and physical properties, B (3) 91*g*.
Murray, H. L. Polystyrene-silica replica technique for relocating selected areas for examination in the electron microscope, (10) 286*a*.
Murray, J. A., and Sifford, L. L., Sr. Automatic volumetric sampler and automatic material transfer, P (5) 139*d*.
Murray, L. A., Lamorte, M. F., and Vogel, F. L. Development of effective lasers, (10) 280*c*.
Murray, P. Metal ceramic mixtures, (1) 28*f*. Symposium on nuclear ceramics: Introduction, (11) 306*h*. See Barnes, E.
Murray, P., and Livey, D. T. Technology of urania and thoria, (8) 215*f*.
Murray Curvex Printing, Ltd. Machines for printing or decorating [back stamping] articles of ware, P (10) 279*c*.
Murthi, K. S. See Macrae, J. C.
Murthy, M. K. Thermal-expansion properties of $BaTiGe_2O_6$, (1) 30*i*. Thermal-expansion properties of vitreous and crystalline germania, (2) 59*i*.
Murton, C. B. Stopper for a ladle or similar receptacle, P (9) 245*f*.
Muschelknautz, E., and Fischer, P. Sticking of dust to walls (during blowing), (4) 122*f*.
Musschoot, A. Rotary conveyor [for granular material], P (3) 80*a*. Vibratory bin feeder, P (7) 195*c*.
Musschoot, A., and Wilson, L. B. Device [vibratory screen] for separating fine from coarse materials, P (8) 221*h*.
Muster, J. Pure synthetic minerals produced in the solar furnace, (5) 140*h*.
Mutter, W. E. See Rudge, W. E.
Myakinenkova, E. V. See Kokorish, E. Yu.
Mycalex Corp. of America. Method and apparatus for making reconstituted synthetic mica sheet, P (8) 220*c*. Method of making ceramoplastic material, P (2) 49*c*. Method of making synthetic mica, P (8) 220*f*, P (9) 249*b*.
Myers, E. B. Selective color filter, P (5) 131*g*.
Myers, J. C., and Cates, J. C., Jr. Composite anode, P (5) 135*e*.
Myers, J. R. See Chao, G. J.
Myers, R. L. Special steels for porcelain enameling, (2) 37*d*.
Myers, W. H., and Schob, F. O. Method of comolding a metal insert in a brick, P (7) 189*h*.
Myl, J. See Smid, I.
Myl'nikova, I. E., and Bokov, V. A. Growth and electrical properties of monocrystals of $Pb_2NiNb_2O_6$ and $Pb_2MgNb_2O_6$, B (9) 263*e*.
Myska, L. See Minar, S.
Myuller, R. L. Problem of interconnection between electroconductivity and the ductility of glasses, (7) 185*f*.

Nabitovich, I. D. See Andrievskii, A. I.
Naboikin, Yu. V. See Aleksandrov, B. S.
Naboikin, Yu. V., Dobrokhotova, V. K., Uglanova, V. V., and Solfer, L. M. Optical parameters of organic monocrystals grown in the presence of additives, B (9) 263*a*.
Nachman, J. F., and Lundin, C. E. (editors). Rare Earth Research—Proceedings of the Second Conference, Glenwood Springs, Colorado, 1961, B (5) 151*f*.
Nack, H. R. Metallizing siliceous inorganic fibers, P (6) 155*f*.
Naefe, H. See Kienow, S.
Naeser, G., Scholz, W., and Fiedler, A. Mechanical activation and passivation—influence of the grinding method and the grinding medium on the sintering of ceramic oxides, (3) 79*f*.
Nag, B. B. See Kumar, S.
Nag, B. R., Roy, S. K., and Chatterji, C. K. Microwave measurement of conductivity and dielectric constant of semiconductors, (10) 286*j*.
Nagai, S. Special masonry cement having a high slag content, B (5) 150*c*. See Suzuki, K.; Yamada, T.
Nagai, S., and Hiyama, S. Studies on special basic seawater magnesia-dolomite refractories for L.D converters, (6) 161*g*.
Nagami, K. Trial results of high magnesia (89.5% MgO) roof brick, (11) 308*h*.
Nagano, R. Entrapped air in cement mortar, (8) 204*b*
Nagano, R., and Wada, H. Hydration of dicalcium silicate, (7) 180*i*.
Nagao, H. See Atlas, L. M.
Nagaoka, M. History of the glass industry in Japan (abstract), B (11) 321*b*.
Nagasaki, S., Watanabe, A., Yoshizaki, K., and Umeya, K. Relations between thermal expansion and packing of particles of refractory clay bodies, (3) 72*g*.
Nagasaki, S., Yoshizaki, K., and Watanabe, A. Relations between the apparent porosity, Shore hardness, and abrasion resistance of alumina silica refractories, (1) 15*d*.
Nagato, H. Method of quantifying Fe^{2+} and Mn^{2+} in sintered Mn-Zn ferrites, (6) 164*f*.
Nagy, A. W. See Friedman, G. E.
Naidenov, V. V. See Zakharikov, N. A.
Naik, M. C. See Agarwala, R. P.
Naito, R. See Kato, S.; Nishimura, Y.; Yamamoto, R.
Naka, S., and Noda, T. Reaction products in the system fluorphlogopite–KF, (4) 119*d*.
Nakahara, C. Jet type apparatus for classifying, dewatering, and recovering slack or other fine ore [stationary sifter], P (2) 55*j*.
Nakahara, M. See Kasai, J.; Miyakawa, T.
Nakahara, M., and Aoki, S. Change in composition of efflorescence, (7) 178*g*.
Nakahara, M., Miyakawa, T., and Suga, K. Effect of adding gypsum anhydrite and potassium sulfate on properties of portland cement, (7) 179*i*.
Nakai, Y. See Yokota, R.
Nakaji, E. M. See French, B. T.
Nakamura, A., and Sugiura, Y. Magnetostriction of yttrium iron garnet, (4) 116*h*.
Nakamura, H. H. See Atlas, L. M.
Nakamura, M., Kawakita, K., and Sakurai, T. Frit compositions for cast-iron chemical ware enamels, (5) 127*h*.
Nakamura, S. See Arai, Z.
Nakashima, K. See Hirose, K.
Nakata, M. M. See Taylor, R. E.
Nakaya, E. Electrostatic coating [deposition control] device, P (2) 38*a*.
Nakayama, N. See Kajihara, H.; Yamada, J.
Nakayama, N., Yamada, K., Naoki, K., Kajihara, H., and Sakai, S. Machinability study of ceramic tools (X) hardness of ceramic tools at high temperature and temperature distribution near the tool point, (1) 1*f*.
Nakayama, T., and Midori, Y. Simple three-terminal ceramic oscillator, (7) 192*c*.
Nalco Chemical Co. Corrosion inhibition with molecularly dehydrated phosphate glass, P (3) 69*e*. Process of concentrating aqueous silica sols, P (3) 84*f*.
Namba, S., and Kim, P. H. Stimulated emission from Nd^{3+} glass, (8) 209*e*.
Nameshi, N. See Toyoda, I.
Nanba, J. See Terada, K.
Nancollas, G. H., and Purdie, N. Crystallization of magnesium oxalate in aqueous solution, (8) 212*f*.
Nandi, D. N. See Gupta, M. M.
Naoki, K. See Nakayama, N.
Naples, P. V. Solid differential expansion temperature sensor, P (3) 81*f*.
Narasimhan, M. D., Krishna, N. D., and Chetty, B. V. Sintering studies on the talc–kaolin and forsterite–kaolin systems, (5) 145*j*.
Narboni, M., and Hornstein, M. Grinding of glass [with diamond], (6) 156*b*.

Narita, K., and Mori, K. Application of a supplementary low-velocity electron gun to electron-diffraction reflection, (7) 195*e*. Investigation of nonmetallic inclusions constituting sand marks by electron-diffraction reflection method, (6) 159*h*. Study of nonmetallic inclusions in iron and steel with an electron microscope (I) titanium carbide, (6) 155*j*.
Naruse, A., and Abe, Y. Striking effect due to iron oxide in certain phosphate glass, B (11) 320*h*.
Nassau, K. Crystals for optical masers, (9) 255*e*.
Nathan, M. L. See Burns, G.
National Distillers and Chemical Corp. Process for preparing chromium oxide, P (3) 84*f*. Uranium oxide and thorium oxide recovery, P (10) 290*d*. Zirconium dioxide recovery, P (9) 254*j*.
National Lead Co. Antifouling pigment, P (11) 303*d*. Apparatus for pulverizing material, P (2) 51*g*. Composite lead oxide-silica particles, P (1) 25*h*. Copper borate antifouling pigment, P (11) 303*a*. Method for producing titanium dioxide pigments, P (9) 254*b*. Production of granular zirconia products, P (5) 133*f*.
National Limestone Institute. Percentage depletion for limestone producers, (10) 288*j*.
National Physical Laboratory. Report for 1962, B (8) 231*a*.
National Research Corp. Electrical device for induction furnaces, P (4) 108*g*. Process of coating a refractory body with boron nitride and then reacting with aluminum, P (7) 189*j*.
National Research Council (Canada). Direct reading resistance thermometer, P (8) 223*f*.
National Research Development Corp. Apparatus for detecting combustible gases having an electrically conductive member enveloped in a refractory material, P (9) 253*f*. Flame spectrophotometry, P (5) 139*f*. Intergranular barrier layer dielectric ceramic compositions and the method of production, P (5) 136*f*. Treatment of columbite and related minerals, P (3) 85*c*.
National Resistance Corp. Means and method for forming electrical components, P (8) 220*a*.
National Spectrographic Laboratories, Inc. Method and apparatus for analysis of [toxic] particles in a gaseous stream, P (8) 224*c*.
National Steel Corp. Process of treating a boron nitride crucible with molten aluminum, P (3) 74*c*.
Naudin, F. See Bourgeaux, M.
Naumov, M. M. Relations between drying rate of ceramics and their relative elongation during tension, (1) 23*b*.
Navez, M. See Branchereau, M.
Navias, L. Magnesia-alumina spinel articles and process of preparing them, P (7) 189*c*. Preparation and properties of spinel made by vapor transport and diffusion in the system MgO–Al_2O_3 (II) in hydrogen and argon at medium pr ssures and in vacuum, (1) 29*e*; (III) effect of time and intermittent cooling on diffusion pattern, (5) 145*e*.
Nayudu, Y. R. Rapid methods for studying silt-size sediments and heavy minerals by liquid immersion, (1) 29*j*.
Nebel, R. See Sliscko, N. M.
Nechaeva, V. S. See Belyaev, L. M.
Nedopil, E. Method for producing high-purity graphite, P (9) 244*f*.
Nedumov, N. A. See Karamyshev, I. P.
Needham, B. A. Curtain wall, P (2) 37*j*.
Negishi, H. See Sekiya, M.
Neil, H. G. Apparatus for determining physical [permeability] properties of porous material, P (3) 81*a*.
Neimark, L. A., Kittel, J. H., and Hoenig, C. L. Irradiation of metal-fiber-reinforced thoria-urania, (7) 188*d*.
Neimeyer, W. F. F., and Busker, J. W. Granulated abrasive, P (2) 33*f*.
Neitzel, M. Flux coating of granular or briquetted refractory materials, P (4) 102*g*.
Nekrashevich, G. A. Electrical separation of pegmatites, (7) 197*f*.
Nelson, D. F., and Boyle, W. S. Continuously operating ruby optical maser, (5) 134*h*.
Nelson, D. H. See Sullivan, J. D.
Nelson, E. W., Bondurant, J. E., and Marcot, G. C. Titanium dioxide pigment and compositions containing it, P (3) 85*b*.
Nelson, F. W. See Sullivan, J. D.
Nelson, F. W., and Stearns, W. E. Glass lining requirements for domestic water heaters, (5) 127*j*.
Nelson, G. C. Scandinavian potters, (5) 126*a*.
Nelson, M. D. Designing ball check valves, (4) 106*f*.
Nelson, R. C. Electronic conduction in glass, (10) 280*i*. Gel-time meters, (4) 107*g*. Magnetic core and film stores, (4) 104*i*. Manual force viscometers, (9) 251*f*. Manual time-measuring viscometers, (4) 107*j*.
Nemchenko, V. F. See Verkhoglyadova, T. S.
Nemetschek, T., and Pollmann, S. Influence of milling, ion exchange, and removal of quartz on a shale, (3) 82*c*.
Nepomnyashchava, V. N., Shternberg, A. A., and Gavrilova, I. V. Laboratory method of growing large regular crystals and oriented blocks of lithium sulfate, B (9) 262*j*.
Nerenberg, R. W. See Bergstein, F. D.
Nerenst, P. Frost action in concrete, B (5) 149*i*.
Nerwin, H. N., Jr., and Robinson, B. H., Jr. Visible indicator for sonic thickness measuring apparatus, P (3) 81*i*.
Netsch, Gebrueder, Maschinenfabrik. Vacuum gypsum mixers, P (10) 268*c*.
Neuerburg, G. J. Method of mineral separation using hydrofluoric acid, (4) 107*b*.
Neumann, O. See Hofmann, F.
Neumayer, J. J. Apparatus for determining molecular weight, P (8) 230*c*.
Neuragaonkar, V. G. See Damodaran, V.
Neville, A. M., and Kenington, H. W. Creep of aluminous cement concrete, B (5) 149*h*.
Neville, J. R. Oxygen sensor [electrolytic], P (4) 121*i*.
New, T. C. T. Method and apparatus for the fabrication of alloyed transistors, P (5) 136*d*.
New England Materials Laboratory, Inc. Method for processing dispersion strengthened metals, P (4) 102*i*.
New Jersey Zinc Co. Photoconductive zinc oxide pigment, P (2) 55*d*.
Newburg, C. F. Screening process for vibratory screens, P (1) 23*e*.
Newby, B. J. Precipitation of zirconium and fluoride ions from solutions, P (9) 254*c*.
Newhall, D. H. Manganin high-pressure sensors, (2) 52*a*.
Newkirk, J. B., and Wernick, J. H. (editors). Direct Observation of Imperfections in Crystals—Proceedings of Technical Conference Held in St. Louis, March 1961, B (9) 261*c*.
Newman, E. S. See Berman, H. A.
Newman, K. W. Process for removal of radioactive contaminants from surfaces, P (6) 176*f*.
Newman, R. C., Wakefield, J., and Rouse, R. L. Production of unipolar [monocrystal] transistors, P (5) 137*e*.
Newman, T. R. See Boies, D. B.
Newnham, R. E., and Haan, Y. M. de. Refinement of the α-Al_2O_3, Ti_2O_3, V_2O_3, and Cr_2O_3 structures, (4) 120*d*.
Newnham, R. E., Redman, M. J., and Santoro, R. P. Crystal structure of yttrium and other rare-earth borates, (8) 226*h*.
Newton, R. C. See Kennedy, G. C.
Newton, R. G. Symposium on control of the quality of glassware: To what quality do we control, (9) 241*j*; Report of the discussion on the symposium, (9) 241*b*.
Ni, L. P. See Sazhin, V. S.
Nichiporenko, S. P. Significance of rheological curves of ceramic bodies in ceramic technology, (1) 29*e*. See Komskaya, M. S.
Nicholas, N. C. See Vergara, W. C.
Nicholls, G. D. Environmental studies in sedimentary geochemistry, (4) 109*d*. Scheme for recalculating the chemical analyses of argillaceous rocks for comparative purposes, (6) 170*i*.
Nicholls, G. D., and Loring, D. H. Some chemical data on British carboniferous sediments and their relationship to the clay mineralogy of these rocks, (11) 314*j*.
Nickerson, J. D. Furnace lining brick, P (7) 189*b*.
Nickl, J. See Enk, E.
Nicklas, J. H. See Currier, E. L., Jr.
Nicolescu, L. See Cioaca, E.
Nie, L. H. de. See Nijman, J.
Nielsen, J. W. Garnet gemstones, P (9) 249*b*. Single crystal garnets, P (1) 21*i*.
Nielsen, T. H., and Leipold, M. H. Thermal expansion in air of ceramic oxides to 2200°C, (10) 276*c*.
Nielson, J. P. See Shell, J. S.
Nigrinova, J. See Barta, C.
Nijman, J. Contributions to the crushing and grinding literature in 1960, (1) 22*f*. Particle size reduction 1961–62, (9) 250*b*.
Nijman, J., and Nie, L. H. de. Grinding in ball mills (I), (10) 288*h*.
Nikitichev, P. I., Saburenkov, E. M., and Nozdrina, V. G. Corundum single crystals, P (2) 55*f*.
Nikitina, O. N. See Zil'bershtein, Kh. I.
Nikolaenko, V. A. See Pravdyuk, N. F.
Nikov, P. N. See Gurevich, I. E.
Ninneman, E. O., and Armbruster, G. D. Container handling apparatus [spacing conveyor], P (5) 130*h*.
Ninomiya, T. See Kanzaki, H.
Nippon Electric Co., Ltd. Manufacturing method of magnetic focusing equipment, P (7) 193*f*. Method of machining semiconductors, P (3) 78*d*.
Nippon Telegraph & Telephone Public Corp. Method of manufacturing bubble insulated wire, P (4) 97*i*.
Nishigaki, S. See Kida, K.
Nishikawa, Y. See Ohba, H.
Nishimura, T. See Kumazawa, S.
Nishimura, Y. See Kato, S.; Yamamoto, R.
Nishimura, Y., Naito, R., Yamamoto, R., and Kato, S. Effects of the particle size of raw materials in porcelain manufacturing (VI) effect of the comminution of feldspar and quartz on the behavior of porcelain bodies during firing, (8) 217*f*.
Nishioka, A., Sekikawa, K., and Owaki, M. Effect of Fe_2O_3 on the properties of barium titanate single crystals, (6) 172*e*.
Nishiyama, M. See Manabe, T.
Nitsch, W. See Cremer, E.
Nitschke, N. C., and McMaster, H. A. Automatic glass bending and tempering furnace, P (8) 210*j*.
Niwa, S. Fundamental studies on the relation between the structure and the properties of electrically fused dunite (VI) radioisotope study on the resistance of dunite refractories to corrosion by molten slag, (1) 13*j*. Trial of unburned spinel ($MgO \cdot Al_2O_3$) brick for roofs of open-hearth furnaces, (11) 308*i*.
Nixon, H. L. See Weir, A. H.
Nobel, D. de. Alloying jig for alloying contacts to semiconductor bodies, P (7) 193*f*.
Nobuoka, S., Ando, T., and Hayama, F. Method of preparing a magnetic recorder powder, P (7) 194*b*.
Noda, A. See Mori, Y.
Noda, T. See Naka, S.
Noddack, W., and Oertel, G. Separation of rare earths by means of ion exchangers, (5) 145*i*.
Noel, E. B., and Levand, V. A. Bent end incandescent lamp, P (6) 157*h*.
Noel, R. W. Shop experience with special low carbon steels in two coat system, (6) 155*g*.
Noguchi, C. See Yonemochi, O.
Noguchi, H. See Amemiya, T.
Nolan, R. W. See James, R. P.
Noll, W., Damm, K., and Weissbach, H. Building material compositions for the manufacture of water repellent masonry, P (10) 268*c*.
Nomm, O. Wet clay preparation and its problems, (2) 44*b*.
Nomura, S. See Yoshida, I.
Nonoyama, M. See Kamiya, Y.
Noorlander, W. See Jonker, G. H.
Nordberg, M. E. See Elmer, T. H.
Nordberg Mfg. Co. Mantle structure for gyratory crusher, P (5) 141*c*.
Nordin, A. W. Practical aspects of the chlorination of ilmenite, (7) 197*j*.
Nordyke, J. S. See Wilke, W. P., III.
Norreys, J. J., and Wheeler, M. J. Symposium on nuclear ceramics: Compressive creep and some physical properties of uranium monocarbide, (11) 307*b*.
Norris, L. F., and Parravano, G. Sintering of zinc oxide, (10) 297*d*.
Norrish, K. See Radoslovich, E. W.
North, J. W. Ceramic body, P (2) 45*j*.
North American Aviation, Inc. Measuring and comparing device of the [optical] pyrometer type, P (4) 108*e*.
North American Philips Co., Inc. Alloying jig for alloying contacts to semiconductor bodies, P (7) 193*f*. Cathode ray tube with silica coated phosphor screen, P (11) 311*b*. Device for X-ray spectrochemical analysis by means of fluorescent radiation, P (2) 60*a*. Electric gas discharge lamp comprising a luminescent layer, P (2) 42*c*. Ferromagnetic body and method of making it, P (5) 136*b*. Ferromagnetic material, P (8) 220*j*. Ferromagnetic material and method of making it, P (11) 311*c*. Glass for dielectric uses, P (5) 130*i*. Magnetic separator [filter], P (3) 80*c*. Metal-to-ceramic seal and method of making it, P (2) 49*i*. Method of flame sealing of glass tube, P (6) 158*e*. Method of increasing the light output of alkaline earth halophosphates, P (2) 49*b*. Method of longitudinally prepolarizing bodies consisting of at least one layer of piezoelectric material, P (5) 136*e*. Method of making Tl_2Te_3, P (10) 283*a*. Method of manufacturing nickel supports for oxide cathodes and cathodes provided with them, P (2) 49*h*. Method of manufacturing oxide cathodes and cathodes manufactured by such methods, P (8) 220*g*, P (11) 311*b*. Method of producing electrode material for semiconducting devices, P (3) 78*j*. Method of producing semiconductive devices, more particularly transistors, P (5) 136*g*. Method of producing semiconductor electrode systems, P (5) 136*h*. Method of producing a stable coagel of an alkaline earth fluoride, P (1) 26*d*. Method of soldering molybdenum foil by means of molybdenum carbide, P (2) 50*b*. Method for treating [semiconductive] materials having a high surface tension in the molten state in a crucible, P (3) 78*a*. Particle counting [scanning] apparatus, P (8) 224*a*. Red luminescent material for cathode-ray tubes, P (1) 21*f*. Semiconductor devices, P (4) 106*b*. Semiconductor Tl_2Te_3 and its method of preparation, P (10) 283*g*. Temperature measuring method and apparatus, P (11) 313*j*. Titanium-activated calcium germanate, P (2) 50*d*. X-ray spectral analysis, P (5) 148*a*.
Norton, C. L., Jr. Shaft kiln, P (11) 314*e*.
Norton, D. A., and Ohrt, J. M. Provisional method of eliminating the effects of film shrinkage and improper camera diameter in Debye patterns, (6) 168*g*.
Norton, F. H. See Hartwig, F. J.
Norton, H. N. Piezoelectric pressure transducers, (6) 165*a*. Strain-gage pressure transducers, (7) 195*g*.
Norton Co. Abrasive grain, P (6) 153*f*. Cathode bar for aluminum reduction cell, P (8) 215*f*. Coated abrasives, P (9) 236*b*. Cut-off wheel, P (4) 95*g*. Diamond cut-off wheel, P (3) 63*g*. Electrically conductive organic bonded grinding wheel, P (3) 63*g*. Grinding wheel, P (5) 125*f*. Grinding wheels having unsaturated organic polymeric bonds, etc., P (10) 265*g*. Magnetic abrasive wheels, method of making them, and machine tools for using them, P (9) 236*d*. Molded alumina articles and process of making them, P (9) 244*j*. Process of making a nuclear fuel element, P (7) 190*a*. Round disk with noncircular backup pad, P (2) 33*g*.
Norton Grinding Wheel, Co., Ltd. Coating articles with alumina by flame-spraying, P (2) 37*i*.
Norwood, A. See Garay, E.
Norwood, A. S. Modifying natural silicate clays to produce organophilic substances, P (2) 55*d*.
Nosenko, B. M. See Krasnaya, A. R.
Nottingham, R. B. Telltale indicator [colored wax or resin] for heat processes and method of using it, P (8) 224*b*.
Novak, I. J. Production of asbestos slurries, P (3) 85*d*.
Novaky, G. Open blisters in the Fourcault process, (1) 8*d*.

Novikov, D. S. Experience in operating an oil-fired glass furnace, (1) 6*f*.
Novo Industrial Corp. Screening process for vibratory screens, P (1) 23*e*.
Novoselova, A. V., Babin, V. N., and Sobolev, B. P. Synthesis of monocrystals of the luminophors Zn_2SiO_4/Mn and $(Zn,Be)_2SiO_4$/Mn, (4) 104*g*.
Novosel'skii, I. M. New method of making large crystals of aluminum and anode dissolution of crystals, B (9) 263*d*.
Novotny, G. V. Fiber optics for electronics engineers, (3) 76*j*.
Nowick, A. S. Effect of plastic deformation on the γ-ray coloration of NaCl crystals, (5) 143*g*. See Bron, W. E.; Dreyfus, R. W.
Nowotny, H. Crystal structure and stability of refractory phases, B (2) 61*b*.
Noyce, R. H. See Ruthberg, S.
Nozdrina, V. G. See Nikitichev, P. I.
Nuclear Corp. of America. Method for preparing ferromagnetic oxides, P (6) 166*a*.
Null, M. R., and Lozier, W. W. Carbon-arc radiation standard, (9) 250*i*.
Nurmagambetov, Kh. N. See Sazhin, V. S.
Nurse, R. W. Phase equilibria and constitution of portland cement clinker, B (5) 148*c*.
Nuvar'eva, V. V. See Ramazanov, P. E.
N. V. de Bataafsche Petroleum Maatschappij. Treatment of zeolitic molecular sieves to inhibit polymerization of olefins, P (2) 60*b*.
N. V. Philips' Gloeilampenfabrieken. Bonding of glass parts especially of cathode-ray tubes, P (3) 69*d*. Ferrite bodies for magnet cores with nearly rectangular hysteresis loops, P (4) 105*b*. Light-dispersing layers on glass surfaces, P (3) 69*c*. Light-scattering coatings for the inside of light bulbs, P (2) 60*i*. Vacuum proof joints by fusion of silvered chromium-iron disks to glass, P (3) 79*b*.

Oakes, A. C., Oakes, W. W., and Hatfield, C. Glass [sheet] snapping apparatus, P (5) 131*a*.
Oakes, D. T. Solids concentration effects in bentonite drilling fluids, B (3) 91*a*. See Johnson, W. R.
Oakes, W. W. See Oakes, A. C.
Oaks, A. Clay testing and processing, (4) 95*i*.
Oba, M. See Ariizumi, A.
Obata, M. See Minakawa, Z.
Obenauer, K. Gas pores as structural constituent of blast-furnace slags and matrix, (10) 267*a*.
Oberg, P. E. See Lins, S. J.
Oblival'nyi, F. A. See Pronin, B. G.
Occella, E., and Maddalon, G. Methods of preparation of silica-containing dusts for use in biological research, (2) 60*g*.
O'Connor, D. J. See Lawrance, J. J.
O'Connor, J. A., and Matys, S. J. Silicon carbide resistance body and method of making it, P (10) 278*a*.
Oel, H. J. Ceramic materials for breeders, moderators, reflectors, control rods, shielding, and construction elements and for thermoelectric power generation, (10) 273*i*.
Oertel, G. See Noddack, W.
Oesterreichisch-Amerikanische Magnesit Akt.-Ges. Sintered magnesia of uniform hardness, P (4) 103*d*.
Oesthagen, K., and Kofstad, P. Reaction between tantalum and nitrogen at 800° to 1300°C, (11) 318*f*.
Offergeld, G. R. See Herinckx, C.
Offner, T. See Duerrwaechter, E.
Ofner, F. R. Flow measuring and dividing system, P (2) 51*b*. Supersonic vibrating drying system, P (8) 222*b*.
Ogard, A. E., Leary, J. A., and Maraman, W. J. Method for preparing uranium monocarbide-plutonium monocarbide solid solution, P (7) 189*d*.
Ogard, A. E., Prichard, W. C., Douglass, R. M., and Leary, J. A. Preparation of uranium monocarbide-plutonium monocarbide solid solutions, plutonium sesquicarbide, and plutonium monocarbide, (9) 256*h*.
Ogawa, H. See Izumitani, T.
Ogden, G. W., Jr. Spectroscopic apparatus, P (2) 53*d*.
Ogden, J., and Armeny, P. J. Spinnerette, P (1) 12*e*.
Ogilvie, A. See Childs, B. G.
Ogle, J. C., Jr., and Barkley, D. W. Electrically conductive multilayer transparent article and method for making it, P (1) 11*e*.
Ogura, T. See Hayami, R.; Tanigawa, H.
Ohba, H. Loss of hearth in the basic open-hearth furnace—comparison of hearths made of brick and ramming materials, (11) 306*a*.
Ohba, H., Ikenoue, T., and Nishikawa, Y. Refractories for LD converters at the Yawata works, Japan, (6) 161*e*.
Ohio Kilns, Inc. Kilns, P (9) 253*e*.
Ohlberg, S. M., Sperry, L. L., Parsons, J. M., and Golob, H. R. Experimental study of Griffith flaws produced by impact, B (11) 320*g*.
Ohlgren, H. A. See Lewis, J. G.
Ohlmann, R. C. See Lin, F. C.
Ohmite Mfg. Co. Resistor structure, P (4) 106*b*.
Ohnemueller, W., and Struchtrup, H. H. Testing of brittle materials with high frequency ultrasonics, (7) 195*j*.
Ohnishi, H., Teranishi, T., and Miyahara, S. Transition temperature of copper ferrite, (6) 175*j*.
Ohrn, K. G. See Jakobsson, P. A. H.
Ohrt, J. M. See Norton, D. A.
Ohta, K. Time decrease of magnetic permeability in some mixed ferrites, (11) 310*h*.
Okada, K., Fujii, M., Yamada, M., and Shinchi, R. Effect of curing under pressure on compressive strength of concrete, (8) 204*b*.
Okamoto, S. See Sekiya, M.
Okamoto, Y. Phenomenological study of liquid phase sintering (I) sintering of Cu-Ag; (II) effects of liquid solubility and wettability on microstructure and densification in several systems; (III) liquid formation and division of particles in the initial stage of liquid phase sintering, (4) 118*d*.
Okawara, S. See Kato, S.
Okazaki, C., Mori, S., and Kanamaru, F. Magnetic and crystallographical properties of hexagonal barium monoferrite, $BaO \cdot Fe_2O_3$, (11) 310*g*.
Okazaki, K., and Yoshioka, T. Firing process and electrical properties of barium titanate ceramics, (11) 310*c*. See Yoshioka, T.
O'Keefe, J. G. See Bray, P. J.
O'Keeffe, M., and Moore, W. J. Electrical conductivity of monocrystalline cuprous oxide, (3) 86*a*.
Oketani, T. See Rokunohe, M.
Oki, S., Imamura, T., and Haneda, S. Measurement of the viscosity of slurry in the systems cement–water and asbestos–cement–water, (8) 205*g*.
Oki, S., Imamura, T., and Makiuchi, T. Filterability in the system asbestos–cement–water, (8) 204*h*.
Oki, S., Imamura, T., and Yamada, H. Determination of chrysotile in asbestos-cement sheets with X-ray diffractometer, (7) 179*d*.
Oki Electric Industry Co., Ltd. Cathodes for electron tubes, P (4) 105*a*.
Okubo, D. Carburization of tungsten powder by carburizing gases (II), (6) 171*g*.
Okubo, T. See Yonemochi, O.
Okubo, Y. See Kawamura, H.
Okuda, H. See Kato, S.
Okuda, J., and Suzuki, T. α trapping centers in *n*-type silicon, (4) 111*j*.
Okuda, K. Precision of air permeability methods in particle size determination, (6) 174*h*. See Tanabe, I.
Okuda, S., Inoue, K., and Uei, I. Determination of surface area of several oxides and clay minerals by the heat of immersion method, (6) 172*j*.
Okumura, K., and Hensley, E. B. Drift and diffusion of activation in oxide-coated cathodes, (10) 280*g*.
Okwit, S. See Heinz, W. W.
Olave, J. R. Clay minerals, B (2) 61*a*.
Olby, J. K. Pigments, P (3) 84*e*.
Olczak, J. Problems of research on Polish glass in the early middle ages (abstract), B (11) 321*c*.
Oldekop, W. Protective glass sheaths for fission-able fuel elements of nuclear reactors, P (3) 70*c*. Theoretical considerations on the viscosity of glasses, (11) 304*b*.
Oldfield, L. F., and Wright, R. D. Volatilization of constituents from borosilicate glass at elevated temperatures, (2) 41*j*;—correction, (8) 209*j*.
Oldfield, R. C. See Gentry, C. H. R.
Olechna, D. J., and Ehrenreich, H. Mobility and thermoelectric power in many-valley polar semiconductors, (8) 219*b*.
Olgebay Norton Co. Bottom rings for composite hot tops, P (3) 73*h*.
Olin Mathieson Chemical Corp. Rotary dryer, P (10) 285*d*.
Oliver, B. M. Sparkling spots and random diffraction, (7) 192*e*.
Oliver, J. Modeling by machines, (3) 79*h*.
Olphen, H. van. Ion adsorption on clays—a review, B (3) 91*i*.
Olschewski, K. H. See Metzel, H.
Olsen, E. J. Six-layer orthohexagonal serpentine from the Labrador trough, (4) 110*g*.
Olsen, H. W. Hydraulic flow through saturated clays, B (5) 150*d*.
Olsen, Tinius, Testing Machine Co. See Tinius Olsen Testing Machine Co.
Olson, A. W. See Dean, H. N.
Olson, O. H., and Weigandt, A. Total emittance measuring techniques, B (3) 93*b*.
Olson, R. E., and Mitronovas, F. Shear strength and consolidation characteristics of calcium and magnesium illite, B (5) 150*d*.
Olson, R. H. Method of controlling the wall thickness of blown glass articles, P (1) 12*b*.
Olson, R. H., and Kinker, C. C. Apparatus for controlling formation of blown glass articles, P (6) 157*a*.
Olson, R. S. See Long, R. S.
Olt, R. D. Crystals for microwave and optical masers, (2) 47*k*.
Olt, R. D., and Rudness, R. G. Single crystals as engineering materials, (9) 258*d*.
O'Malley, J. B. Machine for processing mineral material, P (3) 83*j*.
Ondracek, M., and Mach, O. Apparatus for detecting streaks and other latent defects in glass objects, (9) 239*f*.
O'Neil, J. R. Development of resins in coated abrasives, (2) 33*f*.
Ono, M. Studies on the pot used for melting optical glasses (V) effects of the firing temperature of the grog and green body of the pot for melting optical glasses on their physical properties; (VI) relation between the flow property of clay-chamotte mixtures, the properties of green and fired bodies made by slip casting, and the particle size distribution of the chamotte—relation between gap grading and continuous grading, (3) 73*e*.
Ono, Y. See Yamaguchi, G.
Ontario Research Foundation. X-ray spectrometer, P (1) 24*e*.
Oota, U. See Kumazawa, S.
Operhall, T., and Kuhary, E. E. Disposable pattern with lower melting external coating, P (3) 73*i*.
Oppenheim, M. J. Spindle stage—a modification utilizing a hypodermic syringe, (6) 168*c*.
Oppenheim, U. P., and Even, U. Infrared properties of sapphire at elevated temperatures, (4) 114*g*.
Orbach, H. K. Ceramic uses of plasma jet, (3) 81*j*.
Ordway, F. Crystal structures of clinker constituents, B (5) 148*g*.
Orel, M. Some physicochemical properties of lime, (5) 126*h*.
Orem, T. H. Method for the growth of preferentially oriented single crystals of metals, P (2) 60*a*.
O'Riley, L., Birchall, J., and Tolmie, R. Gamma ray glass gage, (2) 39*c*.
Orlov, N. F. See Byurganovskaya, G. V.
Orlova, G. V. See Sharafiev, M. Sh.
Ormsby, R. G., and Trementozzi, F. J. Method and apparatus for forming glass, P (10) 272*i*.
O'Rourke, D. C. See White, G. D.
Orsino, J. A., and Dunn, E. J., Jr. Composite lead oxide-silica particles, P (1) 25*h*.
Orton, J. W. See Wertz, J. E.
Orville Simpson Co. Screen tensioning device, P (7) 195*c*.
Orwig, B. R. See Barkman, A.
Osawa, S. Flow behavior of plastering cement, (8) 205*c*.
Osborn, E. F. Chrome silica brick, P (7) 189*i*. Reaction series for subalkaline igneous rocks based on different oxygen pressure conditions, (7) 199*i*.
Osborne, M. F. See Morgan, J. G.
Osborne, R. W., and Morris, T. J. Cathode-ceramic assembly for electron guns and method of making, P (8) 220*f*.
Oshima, T., and Uyemura, Y. Coating composition, P (12) 303*d*.
Osiko, V. V. Intracrystalline reactions in crystalline phosphors and the structure of luminescence centers, (5) 144*i*.
Osipova, Z. G. See Podushko, E. V.
Ossenbrink, W. Material crushing apparatus, P (3) 84*a*.
Ostantowski, J. See Walker, W. C.
Ostapchenko, E. P., and Zhmud, E. S. Pressed barium tungstate cathodes, P (2) 50*g*.
Ostberg, W. Cement manufacture, P (9) 237*b*. Hot clinker conveying and cooling apparatus, P (9) 237*e*.
Oswald, D. R. See Riney, T. D.
Ota, E., Yamada, K., Sakai, S., and Uchida, S. Performance test of internal grinding wheels (I) measurement of normal component of grinding force and determination of most suitable grinding conditions, (8) 203*f*.
Ota, M. Clay used for roofing tile, (3) 71*a*.
Ota, Z. Comparative tests of magnesite clinker and seawater magnesia clinker for basic open-hearth furnace brick (II) tests of brick after service, (11) 305*g*.
Ottar, B., and Ruigh, W. L. Structure of boric oxide and borate glasses—preliminary communication, (3) 68*f*.
Ottewill, R. H. See Horne, R. W.
Otto, H., and Maron, R. Histology of iron deposits in silicosis among porcelain workers, (2) 60*e*.
Otto, W. G. See Algatt, G. E.
Otto, W. H. Properties of glass fibers at elevated temperatures, (9) 241*e*. See Whitehurst, H. B.
Ottoson, A. See Bastian, R. R.
Ougland, R. M. See Brindley, G. W.
Overhauser, A. W., and Ruechardt, H. Inversion symmetry of M and R centers, (4) 115*a*.
Ovsienko, D. E., and Kostyuchenko, V. P. Effects of oxides on nucleation in supercooled iron alloys, B (9) 262*c*.
Owaki, M. See Nishioka, A.
Owen, A. E. Comments on "Volume conductivity of borosilicate glass," (10) 270*a*. Properties of glasses in the system $CaO–B_2O_3–Al_2O_3$ (I) dc conductivity and structure of calcium boroaluminate glasses, (1) 8*j*; (II) dielectric properties in relation to structure, (1) 8*b*; (III) thermal expansion in the cabal glasses and its correlation with structure and electrical properties, (3) 67*f*.
Owen, C. J. See Haller, M. N.
Owen, D. H. Manganese ferrites, P (3) 77*i*.
Owen, J. Spin resonance of ion pairs in crystal lattices, B (9) 260*d*.
Owens, E. B. Emission spectrographic analysis of fused aluminum oxide and fused tin oxide crystals, (1) 27*f*.
Owens, J. L. See Lloyd, H. E.
Owens-Corning Fiberglas Corp. Acoustical panel, P (6) 156*j*. Apparatus for determining thermal conductivity of materials, P (5) 139*a*. Apparatus for feeding a multifilament strand, P (4) 99*d*. Apparatus for forming mineral fibers, P (7) 185*g*. Apparatus for measuring the viscosity of glass at high temperatures, P (2) 41*f*. Apparatus for production of glass fibers, P (4) 99*k*. Apparatus for treating fibrous glass, P (10) 271*b*. Apparatus for withdrawing mandrels from tubular bodies, P (3) 69*a*. Bearings with journal supporting elements of glass, P (5) 130*d*. Composite fibers, P (5) 130*g*. Control of crystal growth in mica materials, P (2) 55*e*. Crystalline fibers, P (3) 69*f*. Fiber production, P (6) 157*a*. Fibrous glass product and method of manufacture, P (1) 11*f*, P (3) 69*k*. Fibrous glass re-

inforcement, P (7) 186*a*. Gass fibers coated with an organosilicon polyol, P (7) 186*d*. Glass flake electrical insulation, P (3) 69*h*. Glass-reinforced article, P (6) 157*c*. Glass reinforced gypsum, P (3) 65*b*. Heat setting of binder of fibrous masses, P (10) 272*d*. Liquid fuel burner for forming glass fibers, P (5) 131*b*. Manufacture and stabilization of colloidal silicic acid, P (7) 186*f*. Metal and fiber composite materials and methods of producing, P (10) 272*h*. Metallized flattened glass strand and method of manufacturing, P (9) 242*d*. Metallized glass fibers and method, P (3) 69*f*. Method and apparatus for forming and collecting filaments, P (9) 242*e*. Method and apparatus for forming fibers, P (1) 11*g*. Method and apparatus for forming and processing fibers, P (6) 158*c*. Method of and apparatus for forming strands of filaments, P (4) 100*c*. Method and apparatus for heat conditioning and feeding heat-softenable materials, P (2) 42*b*. Method and apparatus for melting and feeding heat-softenable materials, P (1) 11*h*. Method and apparatus for metal coating glass filaments, P (5) 131*e*. Method and apparatus for processing heat-softenable materials, P (1) 11*i*. Method and apparatus for producing filaments of heat-softenable materials, P (3) 69*j*. Method and apparatus for reconstituting fibrous material, P (2) 42*c*. Method and apparatus for traverse of strand material, P (10) 272*j*. Method for cleaning and coating fibrous glass, P (3) 70*b*. Method of forming a substantially rigid laminated fibrous board, P (7) 186*d*. Method for optical measurement of fiber diameters, P (4) 100*e*. Method of precoating and coating glass fibers [with polyethylene derivative] and article produced thereby, P (9) 242*g*. Method of producing a bulk strand product integrated at spaced zones, P (2) 42*d*. Method of producing [decorative] panels of fibrous glass, P (2) 42*d*. Method of producing dyed glass fiber yarn, P (4) 100*f*. Method for producing glass roving, P (3) 70*j*. Production of reinforced articles, P (2) 43*a*. Production of [vapor] coated fibers, P (5) 131*f*. Sized glass fibers and composition, P (10) 273*c*. Sound absorbing fibrous board with plastic film covering, P (9) 242*e*. Surface treated glass and similar fibers, P (2) 43*a*. Thermal insulating product and method for making it, P (11) 308*j*. Treatment for glass bodies, P (3) 70*g*. Treatment for glass bodies in filament forming operation, P (1) 12*f*.

Owens-Illinois Glass Co. Aluminum, chromium, and gallium tellurates, P (4) 104*j*. Analyzing stresses in transparent articles, P (1) 10*c*. Apparatus for acoustically measuring volume, P (5) 130*i*. Apparatus for [rotary] brush polishing glassware, P (8) 210*h*. Apparatus for controlling formation of blown glass articles, P (6) 157*a*. Apparatus for detecting imperfections in glass containers, P (4) 99*c*. Apparatus for gaging glassware [diametrically], P (3) 68*g*. Apparatus for handling glassware articles, P (5) 130*a*. Apparatus for handling [hot] glassware articles, P (3) 68*g*. Apparatus for mixing colorant in glass furnace forehearth, P (2) 41*g*. Apparatus for producing charges of molten glass, P (4) 99*f*. Apparatus for slicing semihardened materials, P (2) 51*h*. Apparatus for supporting and cutting semiplastic bodies, P (8) 221*e*. Article handling apparatus, P (7) 185*i*. Articles bonded together by internally nucleated devitrified solder glasses and method of making them, P (3) 69*b*. Bonded glass surfaces and method therefor, P (4) 99*i*. Bottle handling apparatus, P (4) 99*j*. Carbon to metal bonded assembly and method of making it, P (5) 130*e*. Catadioptric electroluminescent glass block, P (8) 210*b*. Cathode ray tube envelope, P (4) 99*j*. Cerium tellurite and method of preparation, P (1) 20*c*. Clamping mechanism for glass mold, P (4) 99*a*. Conducting solder glass compositions, P (6) 157*h*. Container handling apparatus [spacing conveyor], P (5) 130*h*. Controlling operation of a glass furnace, P (1) 11*b*. Conveyer, P (8) 221*g*. Decorating method and apparatus, P (8) 210*b*. Elimination of neck flash on blown plastic articles, P (7) 185*j*. Fenestration structure for control of daylighting, P (10) 271*g*. Flame treating apparatus, P (1) 11*g*. Gaging apparatus [for bottles], P (5) 130*i*. Glass composition having high chemical durability, P (2) 42*g*. Glass container inspecting apparatus, P (11) 304*i*. Glass forming machine, P (4) 99*i*. Glass rod and tube cutter, P (8) 210*g*. Glass shaping tools coated with nickel phosphorus alloy, P (4) 99*j*. Inhibiting false signals [line voltage variation] in electronic gaging, P (1) 11*f*. Inorganic metal oxides, P (1) 11*f*. Manufacture of refractory oxide coatings, P (1) 16*g*. Method of adhering metal to a glass base, P (5) 136*c*. Method and apparatus for controlling distribution of plastic coatings on [glass] articles, P (2) 42*a*. Method of blow molding hollow articles, P (8) 211*e*. Method of controlling the wall thickness of blown glass articles, P (1) 12*b*. Method of forming glass articles, P (5) 131*h*. Method for handling glassware articles, P (10) 272*e*. Method for handling [hot deformable] glassware articles, P (3) 70*d*. Method for making titanium, zirconium, and tin tellurites, P (1) 21*j*. Method of producing cerium tellurite, P (1) 21*c*. Method for producing silicon, P (2) 49*j*. Mold assembly with controlled cooling, P (10) 272*g*. Multiply bag, P (2) 51*g*. New chromium-tungsten oxide and preparation, P (4) 105*j*. Oven for treating articles, P (9) 250*e*. Package construction for glassware, etc., P (3) 70*c*. Phosphorescent glasses and method of making them, P (6) 158*h*. Positive assist for loading articles [bottles] to a chuck, P (4) 100*b*. Safety device for molding machines, P (3) 70*d*. Sealing glass, P (8) 211*e*. Shape and height detection [photoelectric], P (9) 242*d*. Stencil screen coating comprising polyvinyl alcohol, polyvinyl acetate, and a light sensitizing agent, P (11) 312*e*. Thermally devitrifiable sealing glasses, P (8) 211*g*. Titanium, zirconium, and tin tellurites, P (1) 22*b*. Universal automatic ware loading machine, P (11) 305*b*. Volumetric measurement, P (3) 70*h*.

Oyama, T. See Ao, T.

Ozawa, U., and Yamada, T. Erosion resistance of fireclay brick to high calcareous slag (I) effects of porosity of brick and flow rate of molten slag on erosion, (1) 13*g*.

Ozu, M. See Asano, S.

Pacific Semiconductors, Inc. Method of bonding materials, P (9) 249*h*. Method of doping crystals, P (6) 166*h*. Single station fusion machine for making semiconductor device, P (7) 194*c*.

Pack, A. H. See Leatham, E.; Snyder, R. P.

Paderno, Yu. B. See Samsonov, G. V.

Paderno, Yu. B., Fomenko, V. S., and Samsonov, G. V. Synthesis and properties of pure neodymium hexaboride, (11) 319*j*.

Paetsch, D. Cracking of once-fired wall tile caused by cristobalite in the intermediate layer, (3) 75*e*.

Page, J., and McCleary, R. E. Board-forming machine, P (7) 182*g*.

Pakutka, W. M. See Buck, I. E., Jr.

Paladino, A. E. See Waugh, J. S.

Paladino, A. E., and Coble, R. L. Effect of grain boundaries on diffusion-controlled processes in aluminum oxide, (5) 142*i*; correction, (10) 292*d*.

Palatnik, L. S., and Komnik, Yu. F. Mechanism of the vacuum condensation of metals, B (9) 262*f*.

Palatnik, L. S., and Kosevich, V. M. Mechanism of the growth of spherulites in amorphous films of antimony, B (9) 262*e*.

Palenik, G. J., and Warf, J. C. Hydrolysis of lanthanum and cerium carbides, (1) 28*c*.

Palit, S. R. Waterproofing of sand-cement plaster of buildings and R. C. roofs, (9) 243*b*.

Palm, B. E. Rotary screening apparatus for separating different kinds of materials in mixtures, P (3) 85*c*.

Palmer, K. E. Applications of the vacuum X-ray spectrometer to cement plant operations, (2) 34*c*.

Palmer, W. (editor). Magnetic Materials Digest, 1961, B (3) 91*f*.

Palmeri, V. R. Physicochemical properties of ceramic-metal systems, (5) 127*f*.

Palmour, H., III. Metal-to-ceramic seals, P (3) 78*a*. See Kriegel, W. W.; McBrayer, R. D.

Palmour, H., III, Kriegel, W. W., and DuPlessis, J. J. Microbrittleness anisotropy in thermally etched sapphire, B (3) 92*c*.

Panda, J. See Traustel, S.

Pangborn Corp. Sonic cleaning of dust filters, P (1) 23*e*.

Pani, P., and Sharma, K. D. Care, cleaning, and maintenance of glass molds, (6) 156*a*.

Panish, M. B. Vaporization of several rare earth oxides, (2) 59*h*.

Pankove, J. I., and Berkeyheiser, J. E., Jr. Method of depositing films of silicon carbide, (2) 48*f*.

Panov, V. S. See Funke, V. F.

Panteleev, A. S. Cements with microfillers, (7) 178*f*.

Pantell, R. H. See Johnson, D. A.

Papadakis, M. Automatic device for measuring the specific surface of powders, (8) 222*g*.

Papike, J. J., Bright, R. C., and Zoltai, T. Crystal sphere orienter, (10) 285*j*.

Pappis, J. Mechanical properties of pyrographite, B (3) 92*d*.

Pappis, J., and Stapleton, R. E. Micromolecular resistor, P (2) 50*c*.

Paprocki, A., Walento, S., and Stepien, K. High-strength autoclaved cellular concrete, P (2) 36*c*.

Paprocki, S. J., and Cunningham, G. W. Ductile chromium, P (5) 133*g*.

Paquin, P., and Draignaud, P. Ceramic industry in the developing countries, (10) 298*a*.

Paracheva, G. T. See Zelikin, Ya. M.

Pardon, L. Microscopy of clinker minerals, (7) 181*c*.

Pariisky, G. B. See Kazansky, V. B.

Paris, R. A., and Perieres, R. Process of making aluminum nitride, P (9) 245*c*.

Parisot, P. E. See Lyons, J. W.; Min, H. S.

Park, R. H. Apparatus for blow molding hollow articles, P (9) 241*e*.

Parker, E. R. Ductility of magnesium oxide, B (3) 91*j*. Future prospects for structural ceramics, B (3) 91*j*. Plastic flow and fracture of crystalline solids, B (9) 259*f*. See Feuerstein, S.

Parker, K. B., Jr. Immersion pyrometer with expendable plug-in temperature sensing unit, P (1) 24*b*.

Parker, R. B. Rapid determination of the approximate composition of amphiboles and pyroxenes, (4) 107*g*.

Parker, W. S., and Fox, J. N. Weighing apparatus [for cement clinker], P (9) 238*a*.

Parkhill, S. M. Inclined drilling—current production at Gibsonburg, (9) 254*e*.

Parks, T. D. Hypochlorite bleach bottle, P (5) 131*b*.

Parks, W. J. Pedestal supports for vibrating screening equipment, P (7) 195*b*.

Parnham, H. Dolomite refractories—a review of applications, (10) 274*g*. New approach to portland cement kiln refractory problems, (1) 2*h*. New approach to solve cement and lime kiln hot zone problems, (2) 35*i*. Some important refractory problems in oxygen steelmaking units—a review, (6) 160*i*.

Parratt, N. J. See Gordon, J. E.

Parravano, G. Reactions in the solid state, (1) 29*a*. See Norris, L. F.

Parshall, B. B. See Cliff, G. J.

Parsons, C. A., & Co., Ltd. Spectrometers [with rotating diffraction grating], P (6) 176*b*.

Parsons, E. W. See Carter, G. J.

Parsons, Howard Grubb, & Co., Ltd. See Howard Grubb Parsons & Co., Ltd.

Parsons, J. M. See Ohlberg, S. M.

Pascoe, W. R. See Croessant, R. C.

Pasfield, W. H. See Alexander, G. B.

Pasiliao, E. V. See Bautista, E. N.

Pask, J. A. Impact of materials science and materials engineering on ceramic engineering, (2) 60*g*. See Hulse, C. O.; Scott, W. D.

Pask, J. A., and Fulrath, R. M. Fundamentals of glass-to-metal bonding (VIII) nature of wetting and adherence, (2) 57*f*.

Passmore, M. E. See Ward, D.

Pastorius, J. W. See Hoffman, W. S.

Patel, A. R., and Goswami, K. N. New method for the study of dislocation etch pits, (4) 116*g*.

Patel, A. R., and Ramanathan, S. Etching of synthetic fluorphlogopite, (7) 199*c*.

Patent-Treuhand-Gesellschaft fuer Elektrische Gluehlampen m.b.H. Electrically heated furnace for melting quartz or quartz glasses, P (4) 99*f*. Electrode for high-pressure electric discharge lamps, P (1) 20*f*.

Paton, E. N. Machine for the electrostatic deposition of powders on heated surfaces, P (2) 38*d*.

Patrick, M. C., and Bowden, G. H. Use of boric oxide in container glass—factory trials, (2) 41*g*.

Patterson, F. K., Moeller, C. W., and Ward, R. Magnetic oxides of molybdenum(V) and tungsten(V) with the ordered perovskite structure, (7) 191*h*.

Patterson, M. M. Unique machine grinds green ceramic insulators, (10) 265*g*.

Patterson, S. H., and Hosterman, J. W. Geology and refractory clay deposits of the Haldeman and Wrigley quadrangles, Kentucky, (6) 170*a*.

Patterson, W. R. Automatic crusher [control circuit], P (6) 170*g*.

Pattison, J. N., Keely, W. M., and Maynor, H. W. Solid state reaction study of hydrated and α-aluminas with the nitrates of nickel and cobalt, (1) 30*b*.

Patwardhan, N. K. See Ramachandran, V. S.

Patzak, I. See Konopicky, K.

Paul, J. F. See Lyons, J. W.; Min, H. S.

Paul Lechler, Firma. Cement addition agent, P (4) 96*e*.

Paulson, W. T. Antiweld additives for coated abrasive bonds, P (2) 33*h*.

Pavlik, A. Several conclusions from concrete mixture rheology and the device measuring mixture mobility, (6) 154*b*.

Pavlov, B. V. See Vashko, A.

Pavlov, V. S. See Stepanenko, M. G.

Pavlova, E. N. See Vlasenko, N. A.

Pawiek, F. Permanent oxide-base magnets, P (4) 105*j*.

Payne, R. E., and Gooch, F. P. Centrifugal dust separator, P (10) 285*b*.

Peakall, K. A., and Antill, J. E. Oxidation of uranium monocarbide, (10) 296*c*.

Pearce, R. L. See De Woody, C. M.

Pearch, H. See Gerster, C. W.

Pearlman, N. See Keesom, P. H.

Peavey, F. H., & Co. Ingredient content determination, P (7) 193*c*.

Pechiney, Compagnie de Produits Chimiques et Electrometallurgiques. Apparatus for the continuous digestion of bauxite [in a series of autoclaves], P (10) 289*e*. High-purity corundum, P (3) 83*i*. Method and composition for assembling together refractory bodies, P (9) 244*d*. Process of making aluminum nitride, P (9) 245*c*. Process for manufacturing aluminum oxide, P (3) 84*a*. Process for the manufacture of refractory materials and resultant product, P (6) 162*d*. Process for producing sintered beryllium oxide and resultant products, P (3) 74*b*.

Pechmann, H. Fire resistance of prestressed ceramic building elements, B (10) 300*a*.

Peck, W. H. Walking beam mechanism, P (9) 253*f*.

Peckham, H. G. Comminution device, P (11) 315*f*.

Peckner, D. See Epner, M.

Peco, G. See Inzigneri, M.

Pecriaux, G. See Plumat, E.

Pecsok, R. L., and Fletcher, A. N. Hydrolysis of titanium (III), (1) 28*g*.

Pedersen, H. E. O. See Dano, T. H.

Pedregal, J. D., and Aparicio-Arroyo, E. Fluoride-based ceramics, B (4) 124*g*.

Peek, V. G. Microscope micro hot stage, (11) 313*h*.

Peikarski, L. T. Ferrites, P (6) 166*b*.

Peklenik, J. Testing the toughness of abrasive particles, (3) 63*h*.

Pellegrino, D. J. See Rex, J. P., Jr.

Pels Leusden, C. O. Plastic properties of clays and their influence on the design of extrusion nozzles, (3) 71*d*.

Peltola, V. K. Pulsed resistance thermometers, P (5) 139*j*.
Pelton, J. F., and Koffskey, J. M., Jr. Process of flame spraying a tungsten carbide-chromium carbide-nickel coating and article produced thereby, P (4) 103*d*.
Pelzer, H. See Reiff, W.
Pelzl, A. See Jamnik, F.
Penberthy, H. L. Apparatus and method of homogenizing glass, P (1) 10*g*.
Penland, R. B. Method for [electrolytically] producing sodium borates of lowered iron content, P (3) 84*b*.
Penn, W. H., and Lotz, F. G. Gas analyzer based on the principle of thermal conductivity, P (8) 223*j*.
Pennell, J. D., Jr. See Malley, T. J.
Pennsalt Chemicals Corp. Flame photometry, P (8) 223*i*. Fluoaluminate composition as dielectric material, P (10) 282*f*.
Penta Laboratories, Inc. Ceramic metalizing process, P (1) 20*b*.
Pera, J. D. See Buckman, S. J.
Percival, A., Buttler, F. G., and Taylor, H. F. W. Precipitation of $CaO{\cdot}Al_2O_3{\cdot}10H_2O$ from supersaturated calcium aluminate solutions at 21°C, B (5) 149*f*.
Peria, W. T. Optical absorption and photoconductivity in magnesium oxide crystals, (3) 88*a*.
Periard, J. N. See Waldron, G. W.
Perieres, R. See Paris, R. A.
Perkin-Elmer Corp. Radiation pyrometer, P (10) 287*c*.
Perkins, W. W. Particle size reduction (I) ball and pebble milling, (10) 269*e*.
Perlin, Yu. E., and Cheban, A. G. Capture of polarons by F centers, (b) 141*j*.
Perls, T. A., Hartog, J. J., and Mattes, B. L. Pyroelectric squaring element, P (8) 220*j*.
Perl'shtein, V. A. See Belyaev, L. M.
Permadent Mfg. Corp. Porcelain covered metal-reinforced teeth, P (1) 18*j*.
Permaglass, Inc. Automatic glass bending and tempering furnace, P (8) 210*j*.
Perraut, J. M., and Michel, H. Apparatus for automatically loading and changing bobbins, P (5) 130*i*.
Perrot, P. N. International cooperation in glass studies—some problems, B (11) 321*g*.
Perrotta, A. J., and McCallum, I. S. Germanate spinels, (10) 293*i*.
Perry, J. T., Jr. See Krylow, K. E.
Perry, L. R., and Rowe, W. E. Process for photographically forming color screens, P (6) 166*e*.
Perry, W. R. Cathode ray screen structure, P (1) 20*i*.
Persson, R. Chemical surface resistance of container glass, (1) 5*g*. Improvement of the chemical durability of soda-lime-silica glass bottles by treating with various agents, (2) 39*g*.
Perthen, J. F., and Steudel, H. K. Linear dimension gage [circuit], P (8) 224*b*.
Pertierra, J. M. Rapid methods of silicate analysis, (5) 145*h*.
Pesatova, Z. Bohemian glass, its history and world contribution, (7) 177*h*.
Pesce, L. Bleaching of diatomaceous earth, P (4) 110*e*.
Pescheck, C. Double [divided] dishes of clay from the early iron age, (7) 177*i*.
Peselnick, L., and Robie, R. A. Elastic constants of calcite, (1) 27*e*.
Peter, K. Electron microscopic investigation of thin glass films, B (11) 320*j*. Simple schlieren-optical instrument for the study of glass surfaces, (1) 9*a*.
Peters, D. L. See Scott, J. N., Jr.
Peters, F. A., Johnson, P. W., and Kirby, R. C. Methods for producing alumina from clay—an evaluation of five hydrochloric acid processes, (6) 170*c*; an evaluation of three sulfuric acid processes, (9) 254*e*.
Peters, F. G. See Sinclair, W. R.
Peterson, D. T., and Rexer, J. Ternary compounds between thorium monocarbide and thorium dihydride, (7) 201*b*.
Peterson, M. N. A. Expandable chloritic clay minerals from upper Mississippian carbonate rocks of the Cumberland Plateau in Tennessee, (4) 109*h*.
Peterson, M. W. See Rackley, J. M.
Petit, G. S. See Greene, R. E.
Petrea, J. C. Vibratory feeder, P (8) 222*d*.
Petri, I., Veiser, I., Jitea, E., and Barlogeanu, C. Semiacid refractories for casting ladles, (3) 72*h*.
Petri, L., Dumitrescu, T., and Iacob, C. Influence of technological factors on the properties of silicoaluminous refractories, (3) 72*j*.
Petrov, G. A. See Dvorkind, M. M.
Petrov, T. G. Growth of potassium nitrate crystals and the formation of inclusions, B (9) 262*e*.
Petrova, V. Z., and Avgustinik, A. I. Relation between the stressed state of porcelain and the damping of vibrations excited in it, (4) 120*e*.
Petrova, V. Z., Avgustinik, A. I., Konovalov, P. F., and Konovalova, E. P. Solution of quartz in feldspar melts, (4) 120*h*.
Pettit, G. D. See Keller, S. P.
Petzold, A., and Erdmann-Jesnitzer, F. Fish scales as influenced by some properties and pretreatments of ferrous metal, B (11) 322*g*.
Pevzner, R. L. See Filonenko, N. E.
Peyches, I., and Levecque, M. Manufacture of fibers, particularly glass fibers, P (6) 157*h*.
Pfab, B. See Hegemann, F.
Pfaender, L. V. Carbon to metal bonded assembly and method of making it, P (5) 130*e*.
Pfann, W. G. Method of controlling liquid-solid interfaces by Peltier heat, P (8) 222*b*.
Pfaudler Permutit, Inc. Chemical processing equipment, P (3) 65*e*. Corrosion resistant coated equipment and methods of making, P (1) 4*j*. Method of making enameled ductile iron, P (2) 38*a*.
Pfeiffer, Gebrueder, Barbarossawerke Akt.-Ges. Grinding mill [with rollers and grinding disk], P (7) 195*a*.
Pfisterer, H., Fuchs, E., and Liesk, W. Electron microscopic evidence of ferroelectric domains in thin $BaTiO_3$ single crystal films, (6) 163*i*.
Pflaum, H. Automatic weighing units for batch preparation in the metallurgical industry, (8) 225*c*.
Pfuhl, H. Vacuum de-airing of plaster for molds in the ceramic industry, (3) 64*g*.
Pheasant, R. See Tarpley, W. B.
Phelps, G. W. See Wunnik, J. van.
Philadelphia Quartz Co. Manufacture of water resistant laminates and silicate adhesive therefor, P (9) 246*f*. Molds utilizing acid hydrolyzed isopropyl silicates as binders [for refractory material], P (4) 103*b*. Water treatment, P (3) 80*c*.
Philco Corp. Fabrication of semiconductor devices, P (3) 77*j*. Method of making glass to metal seal, P (8) 208*d*. Method of manufacturing electrical apparatus, P (2) 42*c*. Method of manufacturing semiconductive device [by jet electrolytic etching], P (10) 283*b*. Miniature desiccator and production of units thereof, P (2) 50*e*. Stem fabricating process, P (4) 100*d*.
Philibert, G. Process and apparatus for sorting balls, P (5) 131*f*.
Philip Morris, Inc. Apparatus and method for measuring the volume and density of solid material, P (3) 81*a*.
Philipp, H. R. Intrinsic optical absorption in single-crystal silicon carbide, (4) 115*d*.
Philippe, J. Archeological criteria for the dating of ancient glass, B (11) 321*f*.
Philipps, T. E. See Biefeld, L. P.
Phillips, B., and Muan, A. Phase equilibria in the system MgO–FeO–Fe_2O_3 in temperature range 1400° to 1800°C, (2) 58*f*.
Phillips, C. E. Machine for mixing particulate materials, P (8) 222*a*.
Phillips, C. J. See Wranau, G. von.
Phillips, J. C., and Cohen, M. H. New approach to ionic character in solids, B (9) 259*e*.
Phillips, R. P. See Jensen, W. L.
Phillips, W. L., Jr., and Hanlon, J. E. Oxygen penetration into single crystals of calcium fluoride, (10) 296*f*.
Phillips Petroleum Co. Blow molding apparatus, P (9) 250*a*. Chromatographic analyzer [with dual columns], P (10) 287*b*. Method for preparing cellular cement, P (10) 268*a*. Programmer-integrator for chromatographic analyzer, P (1) 24*e*.
Philpott, A. A. See Bick, F. P.
Phoenix Gems, Inc. Production of improved synthetic stone bodies with controlled properties, P (6) 154*j*.
Piatkowski, W. See Bieda, W.
Piazzesi, G. See Bassi, A.
Pickart, S. J. See Shirane, G.
Picker X-Ray Corp., Waite Mfg. Div., Inc. Diffraction apparatus and method of using it, P (4) 121*h*.
Piece, R. Simultaneous differential thermal and thermogravimetric analyses of gypsum and its dehydration products, (11) 302*b*.
Piermarini, G. J., and Block, S. Radial distribution study of vitreous barium borosilicate, (6) 156*f*, B (11) 320*i*.
Pierron, E. D. See Munch, R. H.
Pierrot, A., Lescroel, Y., and Bernard, N. Dielectric materials and processes of manufacturing them, P (3) 77*h*.
Pierrot, A., Lescroel, Y. C. E., Grabowski, B., and Guillaud, C. L. Ferromagnetic materials, P (3) 77*c*.
Pike, E. Canadian Guild of Potters workshop, (2) 33*h*.
Pikor, A. J. See Scheffer, H. G.
Pilkington, L. A. B. Manufacture of flat glass, P (7) 186*f*.
Pilkington, L. H. A. Symposium on control of the quality of glassware: Importance of the National Productivity Year, (9) 241*j*.
Pilkington Brothers, Ltd. Depositing silver or copper from solutions on glass, P (6) 157*i*. Manufacture of flat glass, P (7) 186*f*. Manufacture of flat glass in continuous ribbon form, P (7) 186*g*. Melting of glass batch, P (6) 157*i*. Processes of manufacturing glass, P (7) 187*a*.
Pilloton, R. L. Production of hafnium-free zirconium compounds, P (2) 55*h*.
Pilloton, R. L., and Crawley, G. E., Jr. Process of separating tantalum and columbium values, P (3) 89*f*.
Pilpel, N. Dust control in the cement industry, (1) 2*i*.
Pinck, L. A. Adsorption of proteins, enzymes, and antibiotics by montmorillonite, B (5) 150*j*.
Pinto, J., Jr. Inclined drilling—laboratory studies and field developments, (9) 254*c*.
Piolenc, G. de, and Stalego, C. J. Liquid fuel burner for forming glass fibers, P (5) 131*b*.
Piot, P. See Mabru, M.
Piotrowski, Z. See Bieda, W.
Piper, R. D., and Leifield, R. F. Double-baked self-channeling electrode, P (7) 197*a*.
Pipinis, P. A. See Levshin, V. L.
Pirooz, P. P. Sealing glass, P (8) 211*c*. Thermally devitrifiable sealing glasses, P (8) 211*g*.
Piryutko, M. N. See Zil'bershtein, Kh. I.
Pish, G. See Eichelberger, J. F.
Pistorius, C. W. F. T. Lattice constants of synthetic lawsonite, (4) 115*g*. Thermal decomposition of portlandite and xonotlite at high pressures and temperatures, (5) 147*a*.
Pitak, N. V., and Strelets, V. M. Service of nozzles for continuous pouring of steel, (1) 15*g*.
Pitt, E. E. H. Flame photometric determination of sodium, potassium, and calcium in nickel-alumina catalysts, (10) 286*d*.
Pitts, J. W. Ultrasounds induce flaking of ceramics from metals, (2) 37*g*.
Pittsburgh Corning Corp. Sound absorbers, P (9) 242*d*.
Pittsburgh Plate Glass Co. Apparatus for bending [nonuniformly curved] sheet glass, P (4) 99*c*. Apparatus [tongs] for gripping and supporting glass sheets, P (9) 241*f*. Combustion chamber burner for producing glass fibers, P (1) 11*a*. Destructible reinforced sand core for metal casting, P (4) 102*e*. Glass bending lehr, P (8) 210*d*. Glass bending method, P (8) 210*e*. Glass composition, P (4) 99*g*. Glass manufacture, P (1) 11*a*. Glass [sheet] snapping apparatus, P (5) 131*a*. Handling rigid sheet articles [with glass tongs], P (8) 210*j*. Manufacture of [contour polished] glass, P (3) 69*d*. Method and apparatus for forming fibers, P (7) 186*i*. Method and apparatus for producing filmed bent glass sheets, P (6) 158*d*. Method of bending glass sheets [with a heat shield], P (4) 100*d*. Method for forming glass fibers, P (6) 158*f*. Method of preparing glass, P (3) 70*h*, P (10) 272*f*. Method of preparing glass bath ingredients, P (7) 186*d*. Method of preparing metal oxides, P (4) 111*b*, P (4) 111*c*. Method for treating [laminated curved] glass sheets, P (9) 242*j*. Molds [with movable sections] for bending glass sheets, P (9) 242*a*. Preparation of siliceous pigment, P (8) 225*i*. Process for drawing glass sheet, P (10) 272*j*. Process for producing pigments, P (4) 111*d*. Recovery of potassium chloride, P (10) 290*e*. Safety glass glazing unit, P (7) 187*a*. Sampling device and method for analysis of [condensed] furnace gases, P (4) 108*i*. Sheet handling apparatus, P (10) 273*b*. Shipping container [for curved glass], P (3) 70*e*. Supporting glass sheets [by tongs], P (9) 242*h*. Treating glass sheets, P (4) 100*f*, P (8) 211*i*. Treatment of sodium carbonate, P (7) 198*a*. Twisted [glass fiber] yarn package, P (3) 70*h*.
Pittsburgh Plate Glass Co. and Columbia-National Corp. Method of separating silica from zirconium sulfate solutions, P (10) 289*h*.
Pittwell, L. R. Color of fusion melts of the elements, (4) 112*j*.
Pivnik, L. Ya. See Kaibicheva, M. N.
Pizzini, S. See Bertozzi, G.
Plambeck, P. J. See Commanday, M. R.
Planck, Max, Institut fuer Eisenforschung. See Max-Planck-Institut fuer Eisenforschung.
Planer, G. V., and Glaister, R. M. Intergranular barrier layer dielectric ceramic composition and the method of production, P (5) 136*f*.
Planiol, R. Centrifugal grinding mills and vacuum, (1) 22*e*.
Plant, H. T. See Hollinger, D. L.
Plant, H. T., Marks, W. H., and Jordan, T. J. Research on binder techniques for high temperature radome structures, (9) 241*f*.
Planz, J. E., and Mueller-Hesse, H. Existence of metakaolin, (10) 292*f*. Solid state reactions in the system BaO–Al_2O_3–SiO_2 (II) formation of celsian, (10) 297*h*.
Plas, T. van der. See Hermans, M. E. A.
Plasmadyne Corp. Method of making glass fibers, P (11) 305*b*.
Platen, B. von. Press stand [for hydraulic presses], P (3) 80*d*.
Platt, R. O., and Lloyd, T. W. Apparatus for making tapered metal blanks for key brick cases, P (8) 215*e*.
Platzman, R. L. See Durup, J.
Plavcan, E. J. See Gorgens, J. E.
Plesnivy, F. Determination of some impurities in titanium dioxide, (5) 138*i*.
Plesset, M. S., and Devine, R. E. Transducer plate [with ribbed edge] for high acoustical-mechanical energy transfer to liquids, P (5) 137*h*.
Plessey Co., Ltd. Heat-resistant bodies of sintered molybdenum silicide-aluminum oxide mixture, P (6) 162*d*.
Pletcher, D. E. See Doedens, J. D.
Pliquett, F. Measurements on long-time magnetic aftereffects of the remanence of ferrites, (3) 87*e*.
Plorer, J. Coloring glass, P (4) 99*b*.
Pluchery, M. Contribution of crystallographic analysis using X rays to the study of irradiation defects in graphite, B (8) 234*e*.
Plum, N. M. See Bredsdorff, P.
Plumat, E. See Brichard, E.
Plumat, E., Boffe, M., Pecriaux, G., and Clerck, G. de. Method of studying the degree of homogenization of molten glass, (8) 209*d*.
Plummer, D. E. Perlite panorama, (6) 170*g*.
Plummer, H. C. Brick and Tile Engineering, B (10) 298*h*.
Plust, H. G., and Weisshaar, E. Method of contacting semiconductor devices, P (2) 49*a*.
Plyavin, I. K., and Trinkler, M. F. Kinetics of intracenter luminescence in the region of temperature quenching of the activator, (5) 135*f*.
Poch, W., and Dietzel, A. Formation of silicon carbide from silica and carbon, (3) 72*f*.
Podlazov, S. S. See Barke, V. N.
Podmore, H. L. Vibratory grinding, P (8) 222*e*.
Podmore, H. L., and Fahey, D. Vibration mills P (11) 315*h*.

Podmore, W., and Sons, Ltd., and William Boulton, Ltd. Vibration mills, P (11) 315*h*.
Podushko, E. V., and Osipova, Z. G. Clarifying glass, P (2) 41*j*. Glass-melting crucible, P (2) 42*j*.
Pohl, F. A., and Bonsels, W. H. Process for producing boron- and phosphorus-free high purity silicon dioxide, P (3) 84*h*.
Pohl, H. A. Semiconduction in polymers, B (9) 263*i*.
Pohm, A. V. Process and apparatus for producing magnetic material and resulting article, P (3) 78*f*.
Point, M. A. R. Electrostatic spraying or atomizing heads for liquids or pulverulent solids, P (7) 195*b*. Gun for atomization and electrostatic spraying of materials, P (5) 138*h*. Spray guns having a fixed electrostatic head, P (8) 222*b*.
Pointud, R. See Pruvot, E.
Pokrovskii, N. L., and Smirnova, T. G. Effects of impurities on the growth of grains of tin during selective recrystallization, B (9) 262*g*.
Pokrovskii, N. L., and Tissen, D. S. Effects of soluble and insoluble impurities on the crystallization of tin, B (9) 262*g*.
Polanyi, M. L., Johnston, J. E., and Brown, M. G. Method for analyzing microscopic particles, etc., P (1) 24*c*.
Poli, A. A., Jr. See Taylor, B. W.
Poli, F. Lighting and architecture, B (11) 321*g*.
Pollack, S. S. See Granquist, W. T.
Pollak, P. I. See Barkemeyer, H. R.
Pollak, R. J. Gyratory crusher, P (3) 83*i*.
Pollmann, S. See Nemetschek, T.
Polson, J. B. Ganister quarrying, engineered for quality plus economy, (11) 314*h*.
Poluboyarinov, D. N. See Kalliga, G. P.
Poluboyarinov, D. N., Popil'skii, R. Ya., and Tsyvin, D. K. Influence of certain additions on the sintering and properties of highly refractory periclase ceramics, (7) 187*h*.
Polyakova, T. P. See Antonevich, N. K.
Polymer Processes, Inc. Coating process, P (8) 208*b*.
Polysius G.m.b.H. Apparatus for heating cement powder or similar fine granular materials, P (1) 3*c*. Flux coating of granular or briquetted refractory materials, P (4) 102*g*.
Poncelet, R. F. Fracture and flow (II), (9) 240*h*.
Ponder, H., and Keller, W. D. Geology, mineralogy, and genesis of selected fireclays from Latah County, Idaho, B (3) 91*h*.
Ponomarev, V. D. See Sazhin, V. S.
Popescu-Hias, D., and Lungu, S. N. Conversion of fused glass to porcelain by crystallization after shaping and solidification, P (2) 42*b*.
Popil'skii, R. Ya. See Poluboyarinov, D. N.
Popov, S. S. See Smolenskii, G. A.
Popov, V. S., and Dmitrichenko, N. S. Strength of press-mold plates used for pressing magnesia and fireclay refractories, (7) 189*a*.
Popp, E. Heating of glass-melting furnaces, (8) 208*j*.
Popper, P., and Ruddlesden, S. N. Double oxides with layer structures related to perovskite (II) titanate structures, (11) 317*b*.
Porai-Koshits, E. A. See Kalinina, A. M.
Porcelain Enamel Institute, Inc. Cupric sulfate test for color retention—PEI: T–22 (tentative), (9) 238*b*. Specification for architectural porcelain enamel on steel for exterior use—PEI: S-100(62) (tentative), (7) 183*b*. Test for acid resistance of porcelain enamels (citric acid spot test) PEI: T–21, (9) 238*j*.
Porrata, L. R. See Bachman, W. S.
Porter, D. W. Visit of the Building Materials Section to France, April 1961, (1) 31*g*.
Porter, H. K., Co., Inc. Electrical insulator constructions, P (10) 279*c*. Refractory bricks, P (8) 217*c*.
Porter, M. A. New developments in the use of ammonium nitrate products in underground limestone mines, (10) 288*d*.
Porter, R. F. Stabilities of gaseous molecules in the Pb–Se and Pb–Te systems, (2) 58*h*.
Portland Zementwerke Heidelberg Akt.-Ges. Process and apparatus for the production of cement clinker, more especially for white cement, P (8) 206*d*.
Porto, S. P. S. See Leite, R. C. C.
Porzellanfabrik Weiden Gebr. Bauscher, Zweigniederlassung der Lorenz Hutschenreuther Akt.-Ges. Selb. Surface treatment of glazed ceramics, P (4) 104*e*.
Pospisil, Z. Exact viscosity measurement of ceramic suspensions by means of capillary viscosimeters, (6) 168*a*.
Postemein, B. S. See Gurevich, I. E.
Potash Co. of America. Method and means for filtration of slurries, P (3) 84*c*.
Potter, R. A. See Cotter, P. G.
Potter, R. A., and Harris, L. A. Stability of $CaBeO_3$ in the system BeO–CaO, (2) 58*i*.
Potter, R. M. See Aven, M.
Poulos, N. E. See Walton, J. D., Jr.
Poulos, N. E., Elkins, S. R., et al. High temperature ceramic structures, (8) 213*f*.
Poulos, N. E., Elkins, S. R., and Walton, J. D., Jr. High temperature ceramic structure, (8) 213*h*.
Poulos, N. E., Walton, J. D., Jr., and Elkins, S. R. Fused silica-hydrated cements for thermal protection systems, (1) 4*f*.
Poulsen, E. See Bredsdorff, P.
Powell, C. F. See Klopp, W. D.
Powell, D. A. Calcium sulfate hemihydrate prepared in sodium chloride solution, (7) 198*e*.
Powell, D. A., and Way, S. J. Transformation of calcium sulfate hemihydrate to insoluble anhydrite, (5) 147*d*.
Powell, H. E. Analyzing stresses in transparent articles, P (1) 10*c*.
Powell, H. E., Calhoun, W. A., and Miller, C. K. Beneficiation of refractory clay, (6) 169*f*.
Power, W. H. Process of decreasing the salt content of an acidic silica hydroorganosol, P (1) 26*a*.
Powers, D. J. Thermal and mechanical testing of foam alumina and foam zirconia, (8) 215*i*.
Powers, T. C. Physical properties of cement paste, B (5) 149*f*.
Powers, W. H. See Hubble, D. H.
Prasad, J. Comparative studies of optical path difference measurement with Michelson and polarization interferometers, (10) 270*b*.
Prasad, K. See Prasad, S. S.
Prasad, S. S., and Prasad, K. Franck-Condon factors and γ-centroids for the B-X systems of MgO, (5) 143*h*.
Prasad, T. V., and Radovanovich, S. Studies on sintering of some natural magnesites and crystal growth of periclase at high temperatures, (3) 73*h*.
Pratt, P. L. Microstructure and mechanical properties of silicon nitride, B (3) 92*e*.
Pratt, W. R., and Benson, D. H. Abrasive cut-off disks, P (4) 95*f*.
Pravdyuk, N. F., Nikolaenko, V. A., Karpuchin, V. I., and Kuznetsov, V. N. Investigation of diamond and silicon carbide as indicators of irradiation conditions, B (8) 233*d*.
Prener, J. S. Method of making silicon carbide, P (8) 216*e*. Physical chemistry of compound semiconductors, B (9) 260*f*.
Prentice, W. H., and Link, V. V. Method and apparatus for reconstituting fibrous material, P (2) 42*c*.
Prerovske strojirny. Apparatus for preheating finely divided material, P (4) 110*c*.
Preston, F. W. Discussion of "Investigation of the factors likely to affect the strength and properties of glass fibers," (2) 38*i*.
Preston, J. A. Dental stone, P (7) 190*b*.
Preston-Thomas, H. See Dauphinee, T. McC.
Pretzel, F. E., Lewis, W. B., Szklarz, E. G., and Vier, D. T. Properties of lithium hydride (V) vacancy formation, cavitation, and lithium precipitation in irradiated lithium hydride, B (9) 261*h*.
Price, N. E. Process and apparatus for shaping and polishing gemstone particles, P (10) 285*b*.
Price, P. B. See Fleischer, R. L.
Prichard, J. H. See Brown, F.
Prichard, W. C. See Ogard, A. E.
Priest, D. K. See Chao, G. J.
Primak, W., and Bohmann, M. Radiation damage, B (8) 232*j*.
Prince, L. A. See Sharav, W. B.
Priqueler, M. See Garino-Canina, V.
Process Engineers, Inc. Machine for processing mineral material, P (3) 83*j*.
Prochazka, S. Technical and economical considerations of ultrafine grinding, (10) 284*d*.
Procter, J. P. See Cole, H.
Proctor, B. Effects of hydrofluoric acid etching on the strength of glasses, (2) 39*a*.
Proctor, B. A. See Wilkinson, B.
Proctor & Schwartz, Inc. Spray drying apparatus, P (1) 23*g*.
Prod'homme, M. Specific heat of glass (I) historical; (II) differential thermal analysis, (10) 271*g*.
Prokopova, G. See Vashko, A.
Pronin, B. G., Oblival'nyi, F. A., and Vainshtein, A. L. Technology for producing highly tridymitized glass Dinas brick, (7) 189*b*.
Prosser, R. A. Blending apparatus for particulate materials, P (3) 80*a*.
Protti, A. M. See Amato, I.
Protze, H. G., and Levine, S. Lightweight aggregate for structural concrete and products, (11) 302*h*.
Proux, J. L. Process for coating brickwork, masonry, concrete, and wood and compositions therefor, P (1) 13*a*.
Prutton, M. See Astwood, P.
Pruvot, E., Baradez, P., Caillat, R., and Pointud, R. Methods of obtaining sintered beryllium oxide, P (2) 46*e*.
Pryanishnikov, V. P. See Vasserman, I. M.
Pryce, M. H. L. Electronic structure of point defects in crystals, B (9) 260*j*.
Przemeck, E. See Scheffer, F.
Przybylska, M., Reddoch, A. H., and Ritter, G. J. Preparation and structure of lutetium diboride, scandium dodecaboride, and lutetium antimonide, (11) 318*b*.
Puckett, J. P. Instrumentation and automatic control techniques as applied to rotary kilns, (5) 126*j*.
Pulfrich, H. Metal-to-ceramic joint and method of forming, P (2) 38*g*.
Pulfrich, H., and Kotowski, J. Present state of development of ceramic-to-metal sealing, (3) 79*h*.
Pulliam, G. R. Decorated dislocations in magnesia crystals, (7) 198*h*.
Pullman, Inc. Container for pulverant material and method and apparatus for unloading it, P (4) 110*h*.
Purdie, N. See Nancollas, G. H.
Purex Corp., Ltd. Process for removal of radioactive contaminants from surfaces, P (6) 176*f*.
Pushkina, I. K. Hygiene characteristics of mica dust, (2) 60*f*.
Put, E. See Burgt, C. M. van der.
Puustusmaa, J. Enamel frits with a titania base, P (2) 38*a*.
Pye, Ltd. Machine for handling semiconductor material, P (6) 166*e*.
Pyke, M. Science is an attitude of mind, (8) 230*g*.
Pyle, R. J., and Allen, G. L. Coated carbon element for use in nuclear reactors and process of making it, P (5) 133*c*.

Quaas, J. F. See Wasserman, R. D.
Quarrell, A. G. (editor). Niobium, Tantalum, Molybdenum, and Tungsten—Reports of a Conference held in the University of Sheffield, September 1960, B (7) 202*c*.
Quartz & Silice Soc. Anon. Optical pyrometers, P (6) 168*j*.
Quetier, M., and Rappeneau, J. Energy stored by irradiated graphite—variation of the energy as a function of successive annealings, B (8) 234*a*.
Quigley Co., Inc. Heat resisting coating composition and method of applying it to the basic refractory surface of a furnace, P (9) 244*j*. Method of spraying multiple coatings of refractory compositions for hot furnace repair, P (9) 244*i*. Open hearth furnace doors [design], P (7) 189*j*. Refractory insulating and sealing compound, P (9) 245*b*. Sprayable basic refractory composition for repairing the hot basic refractory linings of high temperature furnaces and method, P (9) 245*c*.
Quinn, R. G. Method of preparing inorganic products, P (10) 277*h*. See Adomshick, G. J.
Quirk, J. P. See Aylmore, L. A. G.; Greenland, D. J.; Millington, R. J.
Quirk, R. F. Methods of coating fluorescent lamps, P (2) 42*g*.

Raal, F. A. Orientation of diamonds for tools, (9) 235*j*.
Rabenau, A. K. H. T. Method of making Tl_2Te_3, P (10) 283*a*. Semiconductor Tl_2Te_3 and its method of preparation, P (10) 283*g*. Silicon nitride, a ceramic for high temperatures, (10) 276*g*.
Rabenhorst, H. See Boehme, G.
Rabinovich, A. E., and Rybakov, A. N. Lining tunnel kiln cars with heat-resistant blocks, (7) 196*h*.
Rabinovich, S. A. Effect of the size of grinding balls on ball-mill output, (1) 22*e*.
Rabinowitz, M. See Donaldson, E. E.
Rabotkin, V. L. Electroluminescence of ZnS: Cu,Pb microcrystals, (6) 163*g*.
Rabson, S. R. Vermiculite in the absorption of gases, vapors, and fumes, (2) 54*h*.
Rackley, J. M., and Peterson, M. W. Multiple nozzle gas burner, P (5) 140*e*.
Radczewski, O. E. Examination of ceramic raw materials, B (4) 124*d*. Mineral components of some ball clays, (8) 225*e*.
Radin, A. Ya. See Yung, V. N.
Radio Corp. of America. Cathode-ceramic assembly for electron guns and method of making, P (8) 220*f*. Crystal unit, P (5) 135*f*. Electroluminescent screen, P (4) 105*a*. Glass marking ink, P (10) 272*b*. High power electron discharge device, P (1) 21*c*. Lead telluride-tin telluride thermoelectric compositions and devices, P (5) 136*h*. Magnetic cores, P (3) 77*h*. Method and apparatus for preparing magnetic cores, P (6) 166*g*. Method of and apparatus for spraying cathodes with emissive materials, P (7) 193*h*. Method of making metal-to-ceramic seals, P (9) 249*a*. Method and materials for obtaining low resistance bonds to bismuth telluride, P (6) 166*j*. Mixed ferrospinels, P (2) 50*f*. Semiconductor devices, P (10) 283*f*. Semiconductor devices and methods of making them, P (9) 249*h*. Solid capacitors, P (11) 311*g*. Thermoelectric compositions and devices utilizing them, P (3) 79*b*. Thermoelectric devices and methods of making them, P (5) 137*e*. Thermoelectric elements having graded energy gap, P (1) 22*a*. Thermometer, P (5) 140*a*. Thermometers, P (9) 253*a*.
Rado, P. Manufacture and properties of slip-cast crucibles of calcium fluoride and their use in the smelting of uranium, (10) 275*b*. See Bick, F. P.
Radosevic, S. See Krstanovic, I.
Radoslovich, E. W. Cell dimensions and symmetry of layer-lattice silicates (II) regression relations, (7) 198*h*; (IV) interatomic forces, (9) 255*f*; (V) composition limits; (VI) serpentine and kaolin morphology, (11) 316*e*. Structure of muscovite, $KAl_2(Si_3Al)O_{10}(OH)_2$, (11) 319*h*. See Veitch, L. G.
Radoslovich, E. W., and Norrish, K. Cell dimensions and symmetry of layer-lattice silicates (I) some structural considerations, (7) 198*f*.
Radovanovich, S. See Prasad, T. V.
Radu, A. See Cioaca, E.
Raekers, E. Modern raw material processing in Germany, (2) 50*j*.
Raeuber, A. E. See Mileski, S. E.
Ragan, R. C. Method for continuous manufacture of ceramic sheathing, P (10) 285*g*.
Ragone, D. V., and Zumwalt, L. R. Gaseous corrosion of graphite, B (8) 234*a*.
Rahn, H. N., Mayer, E. H., and Frame, J. W. Relation between base metal composition, surface composition, pickling rate, and direct-on [enamel] adherence, (2) 37*j*.
Raikhbaum, Ya. D., and Luzhnova, M. A. Quantitative spectral analysis of minerals by introducing the sample in the arc with an air stream, (4) 119*e*.

Rakowski, A. J. Method of adjusting the resistance of [metallic oxide] thermistor elements, P (6) 166*f*.
Ramachandran, V. S., Kacker, K. P., and Patwardhan, N. K. Adsorption of dyes by clay minerals, (6) 169*h*. Differential thermal studies of dye-clay complexes, B (10) 300*a*.
Ramana, Y. V., and Subrahmanyam, Y. Effect of texture on ultrasonic wave velocities in sandstones, (11) 317*f*.
Ramanathan, K. See Johannes, R.
Ramanathan, K., Johannes, R., and Cholet, P. Noise characteristics of cold cathodes, (7) 192*g*.
Ramanathan, S. See Patel, A. R.
Ramazanov, P. E., and Nuvar'eva, V. V. Light sums stored in the ZnS:Cu,Al luminophor, (5) 135*f*.
Ramberg, H. Artificial and natural photoelastic effects in quartz and feldspars, (4) 112*g*.
Ramke, W. G., and Latva, J. D. Refractory ceramics and intermetallic compounds, (10) 276*b*.
Ramp, L. Chromite in southern Oregon, (4) 109*a*.
Ramsay, R. F. See Hann, D. G.
Ram Verma, A. See Verma, A. R.
Rana, M. A., and Douglas, R. W. Reaction between glass and water (I) experimental methods and observations; (II) discussion of the results, (2) 40*a*.
Ranby, P. W., and Turner, D. W. Electric lamps embodying reflectors, P (4) 99*d*.
Rand Corp. Novel structural composite material, P (10) 277*j*. Process for making laminated material, P (9) 250*f*.
Randolph, D. W. Method of making impregnated glass fiber articles [tanks], P (1) 12*d*.
Ransom & Randolph Co. Dental stone, P (7) 190*h*.
Rao, A. B. Differential thermal analysis of Brazilian minerals (I) altered spodumenes; (II) some zeolites, (3) 82*i*.
Rao, B. V. J. Dielectric properties of glasses in the systems Bi_2O_3–CdO–SiO_2, Bi_2O_3–CdO–B_2O_3, and Bi_2O_3–CdO–GeO_2 and their relation to the structure of glass, (1) 6*i*. Dual role of titanium in the system K_2O–SiO_2–TiO_2, (9) 255*j*. Influence of TiO_2 on properties of glasses in the system K_2O–PbO–SiO_2–TiO_2 and its relation to structure, (5) 129*f*.
Rao, B. V. S. S., Mehdi, S., Datar, D. S., and Ali, A. Formation of tricalcium silicate by the interaction of calcium carbonate and silica at 840°C, (3) 86*f*.
Rao, C. N. R. Mechanism of crystal structure transformation (I) kinetics and thermodynamics of the crystal structure transformation of spectroscopically pure anatase to rutile, (11) 318*b*. See Vratny, F.; Yoganarasimhan, S. R.
Rao, C. N. R., Yoganarasimhan, S. R., and Faeth, P. A. Mechanism of crystal structure transformations (II) studies on the brookite-rutile transformation, (10) 295*a*.
Rao, H. V. B. See Kartha, K. N.; Sen, P. C.
Rao, M. R. See Sen, P. C.
Rao, M. R. K. Mineralogy and liquidus determination of some low-shaft furnace slags by hot stage microscopy, (2) 44*f*.
Rappeneau, J. See Jouquet, G.; Quetier, M.
Rasch, R. Lightweight [refractory] construction in ceramic kilns, (7) 196*h*.
Raschig, Dr. F., G.m.b.H. Highly swellable clays for foundry molds, P (4) 102*c*.
Rasmussen, S. E. See Christensen, A. N.
Ratcliffe, R. See Hughes, J. E.
Ratcliffe, T. W. Sintered refractory material, P (10) 278*b*.
Rath, W. Ceramic materials containing zirconium silicate for the manufacture of heat-resistant machine parts, P (4) 102*c*.
Ratinov, V. B. See Rozenberg, T. I.
Rattazzi, M. See Grungo, G.
Ratterman, E. See Kapernaros, E. L.
Rau, R. C. Electron microscopy of sintered beryllia, (11) 317*i*.
Rauh, K., and Derlon, H. Highly swellable clays for foundry molds, P (4) 102*c*.
Rausch, H. See Meyer, K.
Rausch, J. J., and Holtz, F. C. High-temperature oxidation protective coatings for vanadium-base alloys, (9) 238*h*.
Ravitz, S. F. See Hammond, M. L.
Rawson, H. See Elyard, C. A.; Tuite, G.
Rawson, H., and Elyard, C. A. Production of high density sintered uranium oxide, P (3) 74*e*.
Rawstron, G. O. Apparatus for and method of polishing aspheric surfaces, P (1) 10*h*.
Ray, E. H., and Sullivan, R. M. Effect of combustion gases on ceramic colors, (2) 47*a*.
Ray, J. G. Fluorescent lamp, P (3) 77*d*. See Gungle, W. C.
Ray, S. See Dodd, C. G.; Ham, W. E.
Raybestos-Manhattan, Inc. Production of asbestos slurries, P (3) 85*d*.
Raychaudhuri, B. C. See Gupta, M. L.
Raymond, M. L. Nondrip, nonslip, nontip cup and saucer, P (4) 95*j*.
Raytheon Co. Anisotropic heat-controlling body and method for manufacture, P (10) 276*i*. Ferrite isolator utilizing aligned crystals with a specific anisotropy constant, P (11) 311*c*. Orientation of ferrites, P (3) 78*b*. Orientation of ferromagnetic particles, P (3) 78*c*.
Rebane, K. S. K. Steady-state luminescence of ZnS phosphors (I); (II) electroluminescence and infrared quenching, (5) 135*a*; (III), (6) 165*i*.
Rebhan, A. Highly refractory compound parts, P (3) 74*a*.
Rebinder, P. A. See Abrosenkova, V. F.; Luk'yanova, O. I.
Rechter, H. L. See Bliton, J. L.
Rechter, H. L., and Bradstreet, S. W. Development of high-temperature strain-gage bonding materials curable at low temperatures (IV), (9) 238*e*.
Rechter, H. L., and Harada, Y. Development of high-temperature strain-gage bonding materials curable at low temperatures (V), (9) 238*g*.
Reddoch, A. H. See Przybylska, M.
Redfern, J. P. See Keattch, C. J.
Redman, M. J. See Newnham, R. E.
Reed, A. E. What's your recipe for screen cloth? (9) 250*b*.
Reed, T. F. Method and apparatus for controlling feed to shaft furnace, P (1) 25*a*.
Reeder, R. K., Jr., and Long, R. A. Ceramic adhesive bonding of refractory metals—a preliminary investigation, (7) 183*a*.
Rees, V. C. Apparatus for packaging stranded material, P (1) 10*i*. Process for combining glass fibers with synthetic resin fibers and product thereof, P (9) 242*b*.
Rees, W. M. See Slayter, G.
Reesman, A. L. See Keller, W. D.
Reeve, K. D. Nonuniform shrinkage in sintering, (9) 243*i*.
Refractory Products Co. Refractory-forming products, P (9) 245*a*.
Reggia, F. Magnetically tunable microwave bandpass filter, (7) 191*j*.
Reid-Jones, R. C. See Williams, E. C.
Reiff, W., and Pelzer, H. Arrangement for loading bulk material into compartments arranged alongside each other, P (1) 25*f*.
Reiling, G. H., and Hensley, E. B. Fundamental optical absorption in magnesium oxide, (3) 86*g*.
Reimer, W. A. See Krylow, K. E.
Reimers, H. Method of producing a binder, P (3) 65*b*.
Reinhold, J. Core elements, P (10) 277*a*.
Reiselt, W. J. Multiply bag, P (2) 51*g*.
Reiss, K. H. Electrically conducting oxide surface layers on nonglazed ceramic parts, P (3) 77*i*.
Reithof, T. R. High-temperature spectral emissivity studies, B (3) 93*b*.
Remeika, J. P. Boron oxide-lead oxide etchant and etching process, P (3) 89*i*. Growth of single crystals of corundum and gallium oxide, P (5) 148*a*. Process of growing single crystals, P (6) 171*e*. See Geschwind, S.
Remmey, G. B., and McFadden, C. A. Burner assembly, P (2) 53*i*.
Renault, P. Diagram for establishing the optimum formula for casting (I, II), (4) 103*h*.
Renkert, D. H., and Schreiber, J. H. Tile punching apparatus, P (2) 44*b*.
Renkey, A. L. Refractory castable, P (2) 46*f*. See Davies, B.; Ruh, E.
Rennie, D. A. See Hsu, P. H.
Repucci, A. See Smakula, A.
Reumann, O. Composition and properties of porcelain glazes, (7) 190*d*.
Reusche, L., & Co. Decorating ceramic surfaces, P (10) 279*b*.
Reuschel, K. See Schweickert, H.
Reuschel, K., and Kersting, A. Method of producing hyperpure silicon, silicon carbide, and germanium, P (11) 311*b*.
Reuss, J. L. See Haseman, J. F.
Reuter, G. Butt joint for unweldable vibratory bodies, P (10) 282*c*.
Reuter, R., and Tozydlo, A. J. Process of concentrating aqueous silica sols, P (3) 84*j*.
Revzin, L. S. See Krasnaya, A. R.
Rew, R. See Fuller, A. G.
Rex, J. P., Jr., Arrington, T. B., and Pellegrino, D. J. Furnace combustion chamber, P (11) 308*e*.
Rex Roto Corp. Furnace combustion chamber, P (11) 308*e*.
Rexall Drug Co. Abrasive articles and methods of making them, P (1) 1*j*.
Rexer, J. See Peterson, D. T.
Reynolds, A. O. Plant grower assembly, P (2) 33*j*.
Reynolds, C. B., Eklund, W. M., and Burklo, D. C. Method of adding a casing to a refractory article, P (7) 189*g*.
Reynolds, R. C., Jr. See Frederickson, A. F.
Reynolds, R. C., Jr., and Lessing, P. Determination of dioctahedral mica and potassium feldspar in submicroscopic grain sizes, (6) 167*j*.
Reynolds Metals Co. Method for producing synthetic cryolite, P (6) 171*b*. Refractory lining for alumina reduction cells, P (9) 245*d*.
Reznikov, M. I. See Voskovoinikov, G. I.
Rheinisch-Westfaelische Isolatoren-Werke G.m.b.H. Device for the sponging of wet-shaped insulators and for cleaning the sponge, P (4) 104*a*.
Rheinische Kalksteinwerke, G.m.b.H. Heat exchangers in furnaces for the sintering of magnesite, dolomite, or cement, P (4) 108*g*.
Rheostatic Co., Ltd. Burner control means, P (7) 197*c*.
Rhinehammer, T. B. See Eichelberger, J. F.
Rhodes, H. B. See Mays, R. L.
Rhodes, L. A. How do you select a crusher? (9) 254*c*.
Riboud, P. V., and Muan, A. Melting relations of CaO-manganese oxide and MgO-manganese oxide mixtures in air, (3) 87*g*.
Rich, S. R. Method of separating differentially heated particles, P (10) 289*h*.
Richard, M. High pressure investigation of barium titanate ceramics, (3) 87*d*.
Richards, J. D. See Chrest, R. W.; Fritts, R. W.
Richardson, H. M., and Lester, M. Symposium on high-alumina refractories: Laboratory experiments on high-alumina refractories, (11) 306*e*.
Richardson, M. E. Method for evaporating subliming materials, P (10) 285*a*.
Richardson, R. D. Gas analyzing apparatus, P (3) 89*i*.
Richardson, R. E. Glass bending lehr, P (8) 210*d*.
Richardson, W. O., and Swanson, N. Instrument maintenance for centrally controlled cement plants, (10) 267*d*.
Richardson, W. W. See Barry, R. L.
Richey, P. W. See Frazier, H. D.
Richman, P. Peak ac to dc comparator, (7) 195*f*.
Richmond, J. C. Physical standards of emittance and reflectance, B (3) 93*c*.
Richmond, J. L., and Wells, C. E. Neutron source, P (5) 133*c*.
Richmond, W. E. Method of accurately machining semiconductor bodies, P (10) 283*e*.
Richter, H. Panel freezing test—determination of frost resistance, (3) 71*i*.
Richter, W. Manufacture of black porcelain, (8) 218*a*.
Rider, D. Review of international trade, (1) 31*g*.
Ridge, M. J. See Bright, J. E.
Ridout, R. A. Fabricating the aluminum alloys (I, II), (4) 97*g*.
Riebling, E. F. Improved counterbalanced sphere viscometer for use to 1750°C, (11) 313*d*.
Riegert, R. P. Method of making multiple layer condensers by vapor deposition and product thereof, P (10) 283*h*.
Ries, H. B. Preparation of fine-ceramic pressing powders by granulation, (10) 284*j*. Trends in the development of batch preparation methods in the heavy clay industry, (10) 284*f*.
Riesbeck, L. J. Electrically heated screening apparatus, P (6) 167*a*. Particle size reduction (II) vibratory mills, (10) 269*e*.
Riesz, C. H., and Weber, H. S. Mechanism of wear of nonmetallic materials, (8) 228*c*.
Rigaku Denki Co., Ltd. X-ray diffraction system, P (1) 24*d*.
Rigan, J. See Kruml, F.
Rigby, G. R. Evaluation of testing methods with particular application to basic refractories, B (10) 300*i*. Refractories paradox, (3) 72*e*.
Rigby, G. R., Hutton, R. F., and Hamilton, B. G. Reactions occurring in basic brick, (9) 243*j*.
Rigrod, W. W., and Kaminow, I. P. Wide-band microwave light modulation, (7) 193*d*.
Riley, M. W. Carbon and graphite—M/DE Manual No. 199, (6) 159*f*.
Rimer, K. W. See Shrubsall, A. E.
Rindone, G. E. See Booth, C. L.; Day, D. E.; Matson, F. R.
Rinesch, R. F. See Weitzer, H. P.
Riney, T. D., and Elek, J. W. Thermoelastic stresses in balanced and unbalanced seals, (1) 20*h*.
Riney, T. D., and Oswald, D. R. Stress-temperature hysteresis as related to plastic deformation in a copper-glass seal, B (3) 92*b*.
Ring, M. A., Donnay, J. D. H., and Koski, W. S. Crystal structure of boron triiodide, (1) 27*e*.
Rings, Inc. Tile ring, P (2) 44*c*.
Ringwood, A. E., and Seabrook, M. System $MgSiO_3$–Ni_2GeO_4 at 600°C and 0 to 90 kilobars, (11) 319*c*.
Rinia, H. See Jochems, P. J. W.
Rinne, O. H. See Kocher, F. W.
Rio, A. See Turriziani, R.
Ripley, R. L. Preparation and properties of some transition phosphides, (11) 318*i*. See Foos, R. A.
Riseman, J. See Sankuer, R. F.
Risnoveanu, A. See Moraru, D.
Risse, M. See Lecrivain, L.
Ritchie, D. Practical test methods for the porcelain enamel industry, (2) 37*g*.
Ritchie, T. Research on brick masonry by the Division of Building Research, National Research Council, (2) 43*h*.
Ritter, F. See Ebert, H.
Ritter, G. J. See Przybylska, M.
Ritter, J. E., Jr., and Cooper, A. R., Jr. Fracture strength of commercial soda-lime-silica glass from −100° to 700°C, (10) 270*h*.
Ritzman, R. L. See Burian, R. J.
Riva, A. Vitreous enameled signs, B (11) 322*h*.
Riverside Plastics Corp. High strength ceramic compositions and methods for preparing them, P (10) 272*d*.
Rivette, E. J. Ceramic mud dispenser, P (11) 309*g*.
Rizzo, H. F. See Weber, B. C.
Roach, G. H. Method of making a high temperature thermocouple, P (4) 108*a*.
Roach, S. A. See Wolff, H. S.
Roake, W. E. See Bates, J. L.
Robb, W. E. Gas burner structure, P (5) 140*d*.
Robb, W. L. Process for producing carbides, P (6) 162*f*.
Robbins, W. P. High temperature bonds with new ceramic adhesives, (1) 4*i*.
Roberts, E. Some observation of gas bubble formation in irradiated boron steels, B (8) 234*e*.
Roberts, J. P. See Drury, T.; Moulson, A. J.
Roberts, R. W., and Conry, W. T. Temperature indicating device, P (4) 108*b*.
Roberts, S. Method of making a piezoelectric device, P (2) 49*f*.
Roberts, S., and Coon, D. D. Far-infrared properties of quartz and sapphire, (4) 114*b*.
Robertson, D., and Ross, R. W. Quick disconnecting means for expendable thermocouples, P (2) 53*c*.
Robertson, H. H., Co. Porcelain enamel slip and method for preparing it, P (6) 155*g*.
Robertson, H. M., McNamara, J. E., and Warner, R. M., Jr. Silicon oxide film thickness measurement, (1) 29*f*.
Robertson, J. A. See Conroy, A. R.

Robertson, R. H. S. Survey of ceramic raw materials, B (4) 124*c*.
Robertson, W. D. See Freedman, J. F.
Robie, N. P. Hard abrasive material and method of making, P (1) 1*i*.
Robie, R. A. See Peselnick, L.
Robins, R. G. Twinning, slip, and cleavage in U_3O_8, (1) 31*a*.
Robins, R. G., Wilks, R. S., and Bradbury, B. T. Crystal habit of uranium dioxide, (1) 27*d*.
Robins, R. H. Electromechanical transducers, P (2) 48*g*.
Robinson, A. E., and Joyce, T. A. Preparation of lead-zirconate-titanate compositions (I) determination of unreacted constituents, (1) 19*d*.
Robinson, A. E., and Luff, D. Preparation of lead-zirconate-titanate compositions (II) effect of excess lead oxide and zirconium oxide, (1) 19*f*.
Robinson, A. J., and Haden, W. L. Method for producing rounded contact masses, P (6) 171*b*.
Robinson, B. H., Jr. See Nerwin, H. N., Jr.
Robinson, G. C., Buie, B. F., and Johnson, H. S., Jr. Common clays of the coastal plain of South Carolina and their use in structural clay products, (3) 82*f*.
Robinson, J. A. Temperature measurement apparatus for a nuclear reactor fuel element, P (8) 224*b*.
Robinson, P. Inductor materials, P (3) 77*e*.
Robinson, T. L. Transfer process avoids p-c open circuits, (6) 165*a*.
Roblee, L. H. S., Jr. Temperature measuring instrument, P (11) 313*j*.
Robredo, J. See Garcia-Vicente, J.
Roche, R. Systems for assembling together two pieces having anisotropic expansions, P (4) 121*i*. See Aubert, M.
Rocktaeschel, G. See Weiss, A.
Rocktaeschel, G., and Weiss, A. Strontium silicides, (4) 120*c*.
Rodeffer, E. O. Material and method for coloring portland cement concretes, P (4) 96*h*.
Roden, G. B. See Larson, E. D.
Rodin, A. M., Rodina, A. A., Lanina, E. N., and Kursatsova, V. M. Conducting layers on titanium dioxide ceramics, P (2) 48*e*.
Rodina, A. A. See Rodin, A. M.
Rodis, F. See Bielenberg, W.
Rodriguez Gallego, M. See Martin Vivaldi, J. L.
Roetter, R. P. Apparatus for gaging the curvature of sheet material, P (1) 10*d*.
Roetter, R. P., and Falk, N. O. Method and apparatus for inspecting [the dew point of] multiple sheet glazing units, P (3) 69*h*.
Rofusa, N. V. Method of producing a binder, P (3) 65*b*.
Roger, M. Market and ceramic industry in Brazil and the Argentine Republic, (9) 258*i*.
Rogers, E. A., and Bennett, N. G. Temperature sensitive devices, P (9) 252*j*.
Rogers, W. G., Baker, G. S., and Gibbs, P. Creep in aluminum oxide, B (3) 92*c*.
Rohrer, K. L. New black emissivity coating, (2) 48*h*.
Roitburd, A. L. See Lyubov, B. Ya.
Rokunohe, M., Yoshida, Z., Miyamoto, H., Mizuno, S., and Oketani, T. Method of manufacturing bubble insulated wire, P (4) 97*i*.
Rolls-Royce, Ltd. Aqueous coating compositions for production of shell molds and process for preparing them, P (1) 15*g*. Barrelling chips, P (9) 236*a*.
Romig, J. R. See Adams, G. E.; Herz, J. H.
Romig, J. R., and Herz, J. H. Kiln control method and apparatus, P (9) 237*h*.
Rooksby, H. P. See Turner, W. E. S.
Rooymans, C. J. M. Crystal structure of $LiScO_2$, (4) 113*c*.
Ropp, R. C. Process for preparation of titanium activated barium pyrophosphate phosphor, P (3) 78*h*.
Rorden, R. J., and Ginsling, A. A. Thermocouple measuring circuit, P (5) 140*a*.
Rosaman, D. See Midgley, H. G.
Rosauer, E. A. See Davidson, D. T.
Rose, D. A. Water movement in porous materials (I) isothermal vapor transfer, (11) 320*b*.
Rose, H. E., and Sullivan, R. M. E. Experimental investigation of vibration milling, (1) 22*g*.
Rosell, B. O. See Tikkanen, M. H.
Roseman, B., and Donald, M. B. Effects of varying the operating conditions of a horizontal drum mixer, (3) 79*j*.
Roseman, R. See Chrest, R. W.
Rosen, A. H., Sellew, W. W., and Cohn, R. E. Method of separating differentially heated particles, P (10) 289*h*.
Rosenberg, P. E. See Warshaw, C. M.
Rosengren, G. B. See Guenther, G. G. J.
Rosenkranda, B., and Simmingskoeld, B. Observations on the reactions in a red lead-potash-sand batch during melting, (2) 40*e*.
Rosenkranz, M. See Bares, R.
Rosenqvist, I. T. Influence of physicochemical factors upon the mechanical properties of clays, B (5) 150*c*.
Rosenthal, G. Freezing behavior of water in brick, (3) 71*e*. Study of the plasticity of mono-ionic clays, B (4) 124*f*.
Rosenthal-Porzellan Akt.-Ges. Porcelain compositions, P (4) 104*c*.
Roshal, J. See Sherr, A. E.
Rosi, F. D. Thermoelectric elements having graded energy gap, P (1) 22*a*.
Rosin, S., and Miller, E. B. Flow cells, P (7) 196*d*.
Ross, B. Semiconductor device and method of making it, P (3) 79*b*.
Ross, C. S. Microlites in glassy volcanic rocks, (6) 170*e*.
Ross, C. W. Effect of thermal neutron irradiation on thermocouples and resistance thermometers, (5) 139*a*.
Ross, I. C. See Brooks, S. H.
Ross, J. Crystallizing carbon of hardness equal to diamond out of solution, P (6) 176*a*.
Ross, J. W. Oxygen for combustion and heating flames in the glass industry, (2) 40*f*. See Runyan, W. R.
Ross, R. W. See Robertson, D.
Ross, W. H. Apparatus for making semiconductor units, P (6) 165*e*.
Ross, W. L. See Griggs, J. O.
Rossetti, M. See Spriggs, R. M.
Rossi, N. Clay from Quetrequile, (6) 169*g*.
Rossi, R. C., and Fulrath, R. M. Epitaxial growth of spinel by reaction in the solid state, (5) 143*j*.
Rossington, D. R. See Blank, B.
Rossmann, H. Vacuum gypsum mixers, P (10) 268*c*.
Roth, H. H. Grinding and polishing compositions and method of making them, P (1) 1*g*.
Roth, R. S. See Levin, E. M.
Roth, W. P. See Dunn, S. A.
Rothrock, J. J. See Leum, L. N.
Rothwell, E. High temperature substoichiometry in uranium dioxide, (1) 28*d*.
Rothwell, G. See Jack, H. R. S.
Rothwell, W. S., and Greenler, R. G. Mechanical behavior of sodium chloride single crystals in flexure, (2) 58*b*.
Roubal, A. J. Seal for rotating cylinders such as kilns, etc., P (4) 108*j*.
Roudabush, N. W. Refractory bricks, P (8) 217*c*.
Rouge, L. J. D. See Gaule, G. K.
Rough, F. A. See Klein, M. J.
Rough, R. R., and Swain, A. B., Jr. Apparatus for mixing colorant in glass furnace forehearth, P (2) 41*g*.
Rouse, R. L. See Newman, R. C.
Roussos, G. Casing for the production of a shrinkage funnel inhibitor coating in an ingot or like mold [hot top], P (10) 276*j*.
Rowan, H. D., and Coughlin, J. M. Electric lamp mount making method, P (5) 130*h*.
Rowden, E. See Holmes, W. H.
Rowe, J. G., III. See Streib, W. C.
Rowe, J. J. See Fournier, R. O.
Rowe, W. E. See Johnson, J. R.; Perry, L. R.
Rowland, C. A. Preparing cement clinker for finish grinding, (2) 35*c*.
Rowse, R. A. Grinding wheels having unsaturated organic polymeric bonds, etc., P (10) 265*g*.
Roy, D. M., and Roy, R. Crystalline solubility and zeolitic behavior in garnet phases in the system $CaO–Al_2O_3–SiO_2–H_2O$, B (5) 149*g*.
Roy, R. Densification of glass, germanium oxide, silica, or boric acid, P (10) 271*f*. See Dachille, F.; Datta, R. K.; Roy, D. M.; Stubican, V.; Warshaw, C. M.
Roy, S. B. See Dhar, R. N.
Roy, S. B., and Chakravorty, S. K. Studies on Indian vermiculite, (11) 319*i*.
Roy, S. B., and Som, S. K. Factors affecting the properties of heat insulating mica brick (I), (3) 72*c*.
Roy, S. K. See Nag, B. R.
Royak, S. M. Sealing cements, (7) 182*c*. See Kholin, I. I.
Royen, P. See Korinth, J.
Rozenberg, T. I., Rubinina, N. M., and Ratinov, V. B. Control of gypsum hardening by means of multicomponent admixtures, (10) 266*i*.
Rozsa, J. T., Uguccini, O. W., and Zeeb, L. E. Method and apparatus for analysis of [toxic] particles in a gaseous stream, P (8) 224*c*.
Rubens, G. J. Tiltable bowl, P (11) 301*i*.
Rubin, G. A. Aluminum-resistant refractory material, P (3) 73*g*. Determination of the thermal conductivity of ceramic materials by temperature cycling, (10) 285*j*. Determination of the thermal shock resistance of ceramic materials, (10) 274*f*.
Rubin, J. J. See Van Uitert, L. G.
Rubinina, N. M. See Rozenberg, T. I.
Rubissow, G. A. Apparatus for producing fibers from mineral materials, P (3) 68*h*.
Ruckelshaus, J. G. Mass production of resistors, P (10) 283*c*.
Ruckwardt, K. F., McDonald, B. T., and Mahoney, J. F. Calcination of zinc sulfide concentrates, P (10) 289*c*.
Ruddlesden, S. N. Application of the electron microscope to ceramics, B (4) 124*e*. See Popper, P.
Rudge, W. E., Harding, W. E., and Mutter, W. E. Fly's-eye lens technique for generating semiconductor device fabrication masks, (9) 247*h*.
Rudness, R. G. See Olt, R. D.
Rudnick, A. See Duckworth, W. H.
Rudy, E., and Stecher, P. Constitution of the hafnium-oxygen system, (11) 316*b*.
Rueb, F. Vacuum equipment and dust removal in the ceramic industry, (5) 138*d*.
Ruechardt, H. See Overhauser, A. W.
Ruedorff, W., Kemmler, S., and Leutner, H. Ternary uranium(V) oxides (I), (1) 30*c*.
Ruehrwein, R. A. Tunnel diode, P (4) 106*c*. See Gruber, B. A.; Stone, B. D.
Ruehrwein, R. A., and Williams, F. V. Crystallization of boron phosphide, P (6) 176*a*.
Ruemmel, T. Crucible for melting silicon of highest purity and method of making it, P (1) 20*d*.
Rueter, H., Weingaertner, F., and Cherdron, E. Process for the decomposition of titanium ores, P (5) 141*h*.
Ruetman, S. H., and Levine, H. H. Research and development of high temperature structural adhesives, (8) 207*h*.
Ruh, E., and Renkey, A. L. Thermal conductivity of refractory castables, (4) 101*j*.
Ruh, E., and Wallace, R. W. Thermal expansion of refractory brick, (3) 73*d*.
Ruh, R. Reactions of zirconia and titanium at elevated temperatures, (9) 256*i*.
Ruhrchemie Akt.-Ges. Process for the treatment of divided materials, P (5) 141*b*.
Ruigh, W. L. See Ottar, B.
Rumberg, K. A. See Carlstroem, B. I.
Rumble, R. P. See Van Sandt, W. A.
Rummel, T. Lining of crucibles for melting silicon and other semiconducting materials, P (4) 102*c*.
Rummery, F. O. See Chrest, R. W.
Runco, J. C. Rotary jar washer, P (10) 273*b*.
Runnels, R. T. Cement raw materials in Kansas, (3) 64*e*. See Ives, W.
Runyan, W. R., Ross, J. W., and Fischer, J. L. Method for recovery and reuse of quartz containers [for melting Si], P (9) 244*i*.
Rusche, H., and Wilmanns, F. Washing of limestone and similar kinds of rock, (10) 289*d*.
Rush, J. Symposium on economics in the enamel shop: Economics in the pickle room, (2) 37*f*.
Russell, C. K. See Bergeron, C. G.
Russell, G. F. Impregnation [of cellular material] by implosion, P (9) 250*d*.
Russell, L. E. See Brett, N. H.
Russell, R. B. See Hunt, J. G.
Russell, R. G. Apparatus for production of glass fibers, P (4) 99*h*.
Russell, R. G., Morgan, W. L., and Scheffler, L. F. Crystalline fibers, P (3) 69*f*.
Russell, R. J., and Hardinge, H. Means and methods of supplying heat to grinding mills, P (6) 171*a*.
Russell, V. A. Ceramic material of high dielectric strength containing barium titanate and method of manufacturing, P (1) 20*a*.
Russell, V. P. Equipment for manufacturing structural [concrete] blocks, P (2) 51*b*.
Russell, W. S. See Halversen, R. A.
Rustom, M. Syrian clays, (10) 289*b*.
Ruthberg, S., Barnes, M. W., and Noyce, R. H. Alteration of the muscovite absorption spectrum of KBr pellet preparation, (6) 171*g*.
Rutherford, S. L. Vacuum techniques, (6) 168*f*.
Rutkovskii, M. L., Anufrieva, N. A., et al. Kinetics of the gas boronizing of nickel, (2) 37*b*. Reasons for the linear time dependence of the depth of a boronized layer on nickel, (2) 37*h*.
Rutz, R. F. See Marinace, J. C.
Ruzhanskii, S. D. See Bulis, Ya. Ya.
Ryabchikov, D. I. See Kargin, V. A.
Ryan, F. J. Cryogenic hose, (9) 250*f*.
Ryan, J. D. Laminated safety glass, P (3) 69*b*. See Marriott, J. G.
Ryan, R. F. See Wahl, W. W.
Rybakov, A. N. See Rabinovich, A. E.
Ryde, J. W. See Davidson, H. W.
Ryder, E. A. See Baker, H. D.
Ryder, S. H. See Holdridge, D. A.
Ryshkewitch, E. Oxide Ceramics—Physical Chemistry and Technology, B (2) 61*i*. Sintered beryllia, (3) 72*j*.
Ryzhikov, B. D. See Levshin, V. L.
Ryzhkov, V. A., and Fedyushin, B. T. Temperature dependence of the electroluminescence of ZnS:Cu,Cl single crystals, (6) 165*j*.

Saalfeld, H. Modification of Al_2O_3 with sillimanite structure, B (10) 300*g*.
Saari, J. M. See Damoth, D. C.
Sabine, T. M. See Hickman, B. S.
Sabins, R. C. Electrolytic method, P (7) 197*j*.
Sabisky, E. S., and Lewis, H. R. Holmium doped calcium fluoride as a maser material, (7) 191*b*.
Sable, A. Process for the conversion of dolomite, P (1) 17*b*.
Sabroff, A. M. Lubricants for high-temperature metalworking processes, (7) 183*f*.
Saburenkov, E. M. See Nikitichev, P. I.
Sacco, J. J., Jr., and Fortin, E. G. Magnetic cores, P (3) 77*h*.
Sacco, R. M. Grinding wheel, P (5) 125*f*.
Sachse, H. B. Measurement of low temperatures with semiconductor resistance thermometers, (10) 281*a*.
Sadanaga, R., and Takeuchi, Y. Polysynthetic twinning of mica, (4) 118*b*.
Sadler, A. G. Mineral constitution of some Ordovician shales of eastern and southern Ontario, (10) 295*a*.
Safar, J. Dry process production of cement clinker in rotary cement kiln with a shaft counterflow heat exchanger, (11) 301*j*. Vibrating cement cooler, (9) 237*j*.
Saffir, J. A. Dental porcelains, P (4) 104*e*.
Sagawa, H. See Munekata, E.
Saha, P. System $NaAlSiO_4$(nepheline)–$NaAlSi_3O_8$(albite)–H_2O, (5) 146*e*.
Sahinen, U. M., Smith, R. I., and Lawson, D. C. Progress report on clays and shales of Montana 1960–1961, (3) 83*b*.
Sahores, J. Study of mechanical phenomena accompanying the hydration of anhydrite, (8) 206*d*.
Saibel, E. See Aggarwala, B. D.
Saiki, Y. See Takemoto, K.
Saito, H. See Kusaka, Y.
Saito, K. See Murakami, K.
Saito, M. See Sato, T.
Saito, Y. See Yamasaki, K.
Sakai, S. See Kajihara, H.; Kasai, J.; Nakayama, N.; Ota, E.

Sakaino, T. See Moriva, T.
Sakaino, T., and Moriya, T. Color of chromium containing glass, (8) 208*g*. Color of glasses containing silver and titanium, (8) 208*h*.
Sakaino, T., Moriya, T., and Koide, K. Coloration of glass containing titanium, (11) 303*f*.
Sakarov, I. E., and Shishakov, N. A. Mechanism of interaction between calcium hydroxide and quartz under normal conditions, (5) 144*d*.
Sakata, K. See Sakata, T.
Sakata, T., and Sakata, K. Change of oxygen concentration with temperature of nickel and cobalt oxide solid solutions, (6) 171*i*.
Sakharnova, I. L. See Zil'bershtein, Kh. I.
Sakka, S. See Soga, N.
Sakurai, S., Watabe, S., and Morio, A. Capacitor of titanium dioxide film produced by thermal decomposition of organic titanium compounds, (8) 218*f*.
Sakurai, T. See Nakamura, M.
Salge, H. Solubility of sulfur in furnace slags (system $CaO–Al_2O_3–SiO_2$), (7) 182*d*.
Salman, T., and Sirois, L. L. Density, viscosity, and surface area relationships in grinding, (3) 79*h*.
Salmon, H. I. See Lamb, V. A.
Salnikova, V. S. See Bozhenov, P. I.
Salotti, C. A. Anthophyllite within the albite-epidote hornfels facies, Fremont County, Colorado, (6) 169*h*.
Saltzman, M. Colored organic pigments: Why so many? Why so few?, (8) 230*f*.
Salzano, F. J., and Eshaya, A. M. Sorption of xenon in high density graphite at high temperatures, (4) 101*g*.
Sama, L. See Lawthers, D. D.
Samaddar, B., and Lahiri, D. Investigations on the activation of slags of $CaO–Al_2O_3–SiO_2$ system by DTA, (6) 154*g*.
Sambell, R. A. J. See Clarke, F. J. P.
Samis, C. S. See Toop, G. W.
Sampson, F. W. Friction material, P (4) 95*h*.
Samsonov, G. V. See Paderno, Yu. B.; T'ai, S.; Verkhoglyadova, T. S.
Samsonov, G. V., Fomenko, V. S., and Paderno, Yu. B. Radiation coefficients of refractory compounds, (1) 14*i*.
Samsonov, G. V., Koval'chenko, M. S., and Sleptsov, V. M. Boron nitride, P (2) 55*d*.
Samsonov, G. V., Koval'chenko, M. S., and Solonnikova, L. A. Diamond substitute for truing grinding wheels, P (2) 33*f*.
Samsonov, G V., Vereikina, L. I., and Titkov, Yu. B. Preparation of gallium phosphide, (4) 118*k*. New methods of obtaining phosphides by reduction of oxides by phosphine, (7) 192*e*.
Samuel, D. G., Heck, F. G., and Hall, H. N. Refractory [metal encased] unit for furnace-lining construction, P (8) 217*a*.
Samuel, L. W. Western Australia Government Chemical Laboratories Report for the Year 1961—extract from the report of the Department of Mines, B (11) 322*i*.
Sanada, Y., and Koide, Y. Japan's cement quadruples in a decade, (9) 236*j*.
Sanchez, M. G. See Acker, E. G.; Barrett, W. T.; Fitch, F. T.
Sandalaki, Z. See Brindley, G. W.
Sandberg, O. H. Process for producing electrode paste, P (3) 74*a*.
Sandell, E. B. See Kolthoff, I. M.
Sanderson, H. S. Gravity actuated apparatus for weighing granular material, etc., P (9) 250*c*.
Sanderson, L. Magnesite, (3) 82*f*.
Sandmeier, H. A. See Spinrad, B. I.
Sandstede, G. See Boehme, G.
Sandvikens Jernverks Aktiebolag. Hot top casing for casting molds, P (5) 133*i*. Ingot mold hot top structure [design], P (5) 133*a*. Tightening device for hot tops, P (9) 245*g*.
Sanford, E. A. See Carlson, W. A.
Sanford, E. A., and Su, G.-J. Chemical processing equipment, P (3) 65*e*.
Sanford, E. A., and Warren, G. Corrosion resistant coated equipment and methods of making, P (1) 4*j*.
Sankuer, R. F., and Riseman, J. Thin magnetic films, P (2) 50*c*.
Sano, K. See Murakami, K.
Sano, S. See Ishii, E.
Santhany, L. W. Sanitary ware setter [with perforations], P (11) 308*j*.
Santisi, H. C. See Williams, J. R.
Santomassino, V. C. See Van Sandt, W. A.
Santoro, R. P. See Newnham, R. E.
Sanz, M. C. Sample holder for photometric analyzing apparatus, P (1) 31*d*.
Sapotnitskii, S. A., and Vasil'ev, N. P. Organic compositions as additives for ceramic steatite bodies, P (2) 47*g*.
Sapre, R. K., and Bhatt, M. P. Production of B.P.C. grade plaster of Paris, (9) 237*b*.
Sara, R. V., Lowell, C. E., and Dolloff, R. T. Research study to determine the phase equilibrium relations of selected metal carbides at high temperatures, (10) 276*e*.
Saraikauskas, R. V., Cox, M. C., and Thielke, N. R. Ferrimagnetic spinel bodies, P (10) 282*f*.
Sarian, S. Pressure-differential type apparatus useful in density and volume measurements [of solids], P (8) 224*a*.
Sarin, D. D. Cyclic sedimentation of primary dolomite and limestone, (3) 82*g*.
Sartell, J. A., and Li, C. H. Twinning in nickel oxide platelets, B (3) 92*a*.
Sarver, J. F. Comment on "Vegard's law and the system alumina–chromia," (3) 86*b*. Thermal-expansion data for rutile-type GeO_2, (6) 175*i*.
Sasaki, H. See Matsuo, Y.
Sasaki, T. See Ishiguro, K.; Suzukawa, Y.; Watanabe, K.
Sasaki, T., and Suzukawa, Y. Effect of ferrous oxide on the β-γ inversion temperature of dicalcium silicate, (7) 179*e*.
Sasaki, Y. See Furuoya, T.; Ishii, Z.; Ishikawa, Y.
Sasaki, Y., Asanabe, S., and Shinoda, D. Thermoelectric generator, P (5) 137*e*.
Sasuga, H. See Hirano, S.
Satkiewicz, F. G. Experiments on plasticity of magnesium oxide and calcium oxide under compression, B (3) 91*j*.
Sato, A. Method of machining semiconductors, P (3) 78*d*.
Sato, M. See Garrels, R. M.; Kikuchi, M.
Sato, N., and Kanaya, M. Determination of the content of various forms of gypsum in portland cement by differential thermal analysis, (7) 179*e*.
Sato, S., and Tagai, H. Formula for estimating the heat of hydration and mortar strength of rapid-hardening portland cement, (8) 205*d*.
Sato, S., Takashima, S., and Kato, M. Composition of ferrite phase in portland cement, (7) 179*a*.
Sato, T., Sugihara, M., and Saito, M. Formation of ultrafine spinel ferrite, (8) 219*i*.
Sattler, F. A., and Tierney, P. A. Electrical insulating coating composition, method, and coated article, P (9) 248*j*.
Sauer, H. A., and Turner, D. R. Low resistance contact for semiconductors, P (4) 105*f*.
Sauer, J. M., Weeks, L. W., Fleeman, P. J., and Kaiser, V. A. Riverside puts kiln under closed-loop computer control, (2) 35*g*.
Sauerwald, F. Possibilities for forming, especially of metal ceramics, (11) 312*a*.
Sauman, Z. Study of possibility of synthesis of clinker minerals and X-ray diffraction determination in industrial clinkers, (7) 182*e*.
Saunders, A. C. Refractory laminates—a step forward in refractory technology and engineering, (10) 276*c*.
Saunders, H. M. See Benson, G. E.
Saunders, J. A., and Moore, E. E. Radiant gas burner, P (1) 25*c*.
Saunderson, J. L. Spectroscopic apparatus with automatic correction of misalignment, P (7) 201*i*.
Saunderson, J. L., and Altman, G. Spectroscopic apparatus, P (2) 53*d*.
Saunderson, J. L., and Du Bois, E. Spectroscopic apparatus, P (3) 90*a*.
Savage, A. See Miller, R. C.
Savage, J. A., and Isard, J. O. Investigation of the electrode properties of some cation sensitive glasses, (3) 67*a*.
Savel'ev, N. T. See Boyarskaya, Yu. S.
Saviers, G. B. See Kerr, R. E.
Savitskii, M. R. See Amosov, N. I.
Savvina, Yu. A. See Serb-Serbina, N. N.
Sawada, S. See Yoshida, I.
Sawaguchi, E., and Charters, M. (I) Aging of ferroelectrics; (II) symmetry of the low temperature phase of barium titanate, (1) 19*b*. Growth and investigation of ferroelectric and antiferroelectric crystals, (3) 76*j*.
Sawai, I. Glass technology in Japan, (1) 7*c*. See Kunugi, M.
Sawamoto, K. See Yamaka, E.
Sawamura, K. Activity of lime in blast-furnace slag (I) activity of CaO in the binary system $CaO–SiO_2$, (7) 178*b*.
Sawamura, M., Kawada, N., and Miyano, K. Effect of curing water on the strength of mortar, (8) 204*d*.
Sawdye, J. A. See Freeman, D. C., Jr.
Sawicki, A. Factors pertaining to the adherence properties and durability of enamels, B (11) 322*f*.
Sawyer, C. B. Method of controlling deposition of crystalline material from solution on a seed by use of a temperature profile curve, P (11) 320*a*.
Sawyer, G. C. Shredder of rotating wires for filter cake, P (3) 80*a*.
Sawyer, H. D. See Burkin, A. R.
Sawyer Research Products, Inc. Method of controlling deposition of crystalline material from solution on a seed by use of a temperature profile curve, P (11) 320*a*.
Saxon-Napier, E. A. See Barrer, R. M.
Sayers, J. B. Symposium on nuclear ceramics: Irradiation effects in uranium and plutonium ceramics, (11) 307*f*.
Sayers, J. E. Dust separators, P (7) 195*b*.
Sayre, E. V. Intentional use of antimony and manganese in ancient glasses, B (11) 321*d*.
Sazhin, V. S., Ponomarev, V. D., Nurmagambetov, Kh. N., and Ni, L. P. Recovery of alumina from nepheline concentrates, P (2) 55*j*.
Scala, S. M. Hypersonic environment—heat transfer in multicomponent gases, (10) 294*b*.
Scandellari, M. L. See Calvi, M. C.
Scarborough Associates, Inc. Selective color filter, P (5) 131*g*.
Scardaville, P. A. See Frieser, R. G.
Scatturin, V., Corliss, L., Elliott, N., and Hastings, J. Magnetic structures of 3*d* transition metal double fluorides, $KMeF_3$, (10) 294*i*.
Schade, O. H., Sr. High power electron discharge device, P (1) 21*c*.
Schaedel, J. Structure and physicochemical properties of feldspars, (4) 110*g*.
Schaefer, A. See Becher, H. J.
Schaefer, H. Chemical transport reactions (VII) chemical transport reactions and their uses, (5) 142*c*.
Schaefer, H., and Etzel, K. Chemical transport reactions (V) migration of copper(I) oxide and copper in temperature gradients; (VI) transport of metallic iron and nickel by the reaction $M + 2HCl \rightleftharpoons MCl_{2(gas)} + H_2$—stability of the gaseous subchlorides FeCl and NiCl, (5) 142*b*.
Schaefer, H., and Fuhr, W. Chemical transport reactions (IX) transport of TiN by means of HCl in a molybdenum tube, (6) 172*d*.
Schaefer, H., and Hueesker, M. Chemical transport reactions (VIII) (Contributions to the chemistry of the elements niobium and tantalum: XXX) preparation of niobium oxides and their transport in a temperature gradient, (6) 172*c*.
Schaefer, L. See Himmelstein, P.
Schaefer, W. See Steinhauer, O.
Schaefer, Z. Melting of quality utility glasses in pot furnaces, (7) 184*i*.
Schaeffler, O. S. See Feltzin, J.
Schafer, R. G. See Burke, K. O.
Schaffer, S. A. Treating glass sheets, P (4) 100*f*.
Schairer, J. F. See Chinner, G. A.; Schreyer, W.
Schat, B. R. See Drexler, O.
Schatz, E. A. Isomorphous substitution for silicon in fluorphlogopite, (4) 115*b*.
Schaub, F., and Schleper, B. Process for the treatment of divided materials, P (5) 141*b*.
Schauer, S. Grinding mill [with rollers and grinding disk], P (7) 195*a*.
Schawlow, A. L. Crystals and light, (10) 298*a*. Fine-line spectra of chromium ions in crystals, B (9) 260*j*.
Schechter, D. L. See Leddy, J. J.
Schechter, D. L., and Leddy, J. J. Caustic beneficiation of titanium source materials, P (4) 110*e*.
Schechter, W. Twin kilns toil for Norlite, (9) 243*a*.
Scheelar, M. D. See Carson, J. A.
Scheetz, H. Investigation of the theoretical and practical aspects of the thermal expansion of ceramic materials, (8) 228*j*.
Scheffer, F., Przemeck, E., and Wilms, W. Effect of cement kiln dust on soil and plants, (2) 34*d*.
Scheffer, H. G., Liederbach, W. H., Pikor, A. J., and Miller, W. Ultrasonic sealing of hermetic ceramic transistor packages, (3) 76*j*.
Scheffler, G. H. See Forwalt, H. J.
Scheffler, L. F. See Russell, R. G.
Scheibe, H. Preparation of sintered urania materials, (7) 188*h*.
Schell, D. C. See Atlas, L. M.; Baskin, Y.
Schembra, F. W. See Hofmann, U.
Schepers, G. W. H. Pathogenicity of glass reinforced plastics—experimental inquiries by injection or external application techniques, (2) 60*h*.
Schetky, L. M. Thermal insulating construction, P (8) 208*c*.
Scheuermann, E. A., and Voggel, K. Membrane filter—its use in ceramics, (7) 194*i*.
Scheutz, C. I. Swedish glass industry, 1962, (1) 9*g*.
Schieber, M. See Frei, E. H.
Schiel, E. J. See Ahlstrom, E. R.
Schiessl, H. A. Colored structural glass, P (5) 130*f*.
Schiff, D. Pyrolytic materials for reentry applications, (10) 275*h*.
Schifferle, C. J. Cementitious material and method of preparation, P (3) 64*j*.
Schill, F. Foamed Glass, B (8) 231*i*.
Schimitschek, E. J., Schwarz, E. G. K., and Turnbull, W. G. Four-level K_α-band maser, (7) 191*j*.
Schindler, H. D. See Malley, T. J.
Schirm, H. T. Clamping mechanism for glass mold, P (4) 99*a*.
Schlacht, K. See Goldthwaite, V.
Schlanger, S. O. See Hathaway, J. C.
Schlegel, H. Installation of cloth type air filters in the ceramic industry, (3) 79*f*.
Schlenz, H. See Engelhardt, H.
Schleper, B. See Schaub, F.
Schloemann, E. F. R. A. Ferrite isolator utilizing aligned crystals with a specific anisotropy constant, P (11) 311*c*.
Schloemann, E. F. R. A., and Sirvetz, M. H. Orientation of ferromagnetic particles, P (3) 78*c*.
Schlosser & Co., G.m.b.H. Manufacture of crystalline porous stones, P (7) 187*c*.
Schluderberg, D. C., Whitelaw, R. L., and Carlson, R. W. Gaseous suspensions—new reactor coolant, (4) 101*e*.
Schmahl, H. See Krueger, H. E.
Schmid, A., and Hofer, H. Method for carrying out endothermic processes in a [dual] shaft furnace, P (5) 127*a*.
Schmid, H. See Schwab, G.-M.
Schmid, O., and Gliemeroth, G. Slagging tests on checker-brick at various temperatures in a furnace with a rotating specimen holder, (7) 188*f*.
Schmidt, J. E., Mathews, A. L., and Hornblower, W. J. Bond Teflon with epoxies, (9) 258*a*.
Schmidt, J. H. Flue covering process, P (9) 253*c*.
Schmidt, K. G. Types of asbestos, their study by optical methods, and their pathogenic action, (2) 60*g*.
Schmidt, M. Package, in particular for hollow bodies sensitive to pressure such as Christmas tree balls, P (9) 242*a*.
Schmidt, T. Cooled furnace transport rollers, P (11) 314*e*.
Schmidt, W., Konopicky, K., and Baum, M. Flame spectrometric determination of Fe_2O_3, CaO, MgO, and K_2O in aluminosilicates, (10) 286*e*.

Schmied, W. Observations and experiments on the incidence of the cracking and chipping of floor and wall tile due to temperature changes, (7) 190*g*.
Schmitt, R. See Ehrlich, P.
Schmitz, G. K. Exploration and evaluation of new glasses in fiber form, (9) 240*d*.
Schmunk, J. D., and Gilliland, H. E. Upender mechanism for tile machines, P (1) 13*c*.
Schnable, G. L. See Fahey, J. R.
Schneider, A., and Zintl, G. Enthalpy of formation of tellurium dioxide, (4) 113*h*.
Schneider, E. E. Role of impurities in radiation effects in ionic solids, (11) 319*b*. See Bansigir, K. G.
Schneider, F. Tonnage oxygen for the glass industry, (2) 41*f*.
Schneider, J. Calcination of rocks containing organic substances in ceramic kilns, especially annular kilns, P (3) 83*e*.
Schneider, J. F., and Accinno, D. J. Thermocouple, P (3) 81*g*.
Schneider, S. See French, B. T.
Schneider, S. J. Discrepancy in conversion of early melting-point temperatures, (9) 255*i*.
Schnering, H. G., and Hoppe, R. Crystal structure of $SrZnO_3$, (4) 113*f*.
Schob, F. O. See Myers, W. H.
Schocken, K. Emission and reflection of radiation by metals, B (3) 93*b*.
Schoder, W. P. Preparation of high purity vanadium pentoxide from oxidic vanadium materials, P (8) 225*h*.
Schodowski, S. S. See Vonbun, F. O.
Schoefer, R. Study of reactions in ceramic solids by infrared spectroscopy exemplified by barium titanate, (3) 89*f*.
Schoen, R. Semiquantitative analysis of chlorites by X-ray diffraction, (6) 168*j*.
Schoenmakers, H., Kruithof, A. M., and Ansems, A. J. P. Method of flame sealing of glass tube, P (6) 158*e*.
Scholder, R. Recent investigations on oxometallates and double oxides, (1) 29*b*.
Scholder, R., and Suchy, H. Alkaline earth chromates(V), (4) 111*i*.
Scholes, A. B. Lamp base assembly, P (2) 42*a*.
Scholes, S. R. Calculating transmissions of glasses of various thicknesses, (7) 184*e*.
Scholl, F. Determination of surface area and surface quality of solids by gas chromatographic methods, B (10) 300*g*.
Scholz, A. Absorption and photochemistry of AgCl crystals doped with divalent cations and anions, (3) 85*f*.
Scholz, W. See Naeser, G.
Schoonover, P. L. Apparatus and method for conveying slurry, P (9) 250*e*.
Schornstheimer, R. E. Method and apparatus for making magnetically anisotropic elongated magnets, P (4) 105*g*.
Schorsch, G. See Ingri, N.
Schramke, E. Austrian deposits of ceramic raw materials, (7) 197*d*.
Schratt, F. S. Thermometer and method of making and calibrating it, P (3) 70*f*.
Schreck, A. E. Lithium, (7) 197*g*. Lithium—a materials survey, (10) 288*j*.
Schreffler, R. Z. See Cunningham, C. R.
Schreiber, C. W. Universal automatic ware loading machine, P (11) 305*b*.
Schreiber, J. H. See Renkert, D. H.
Schreiner, H., and Boehm, H. Method for producing sintered semiconductor bodies, P (2) 50*a*.
Schreiter, H. See Witzmann, H.
Schrewelius, N. G. See Amberg, S.
Schrey, F. See Gallagher, P. K.
Schreyer, K. D., and Manney, C. J. Loose material feeder, P (4) 106*h*.
Schreyer, W., and Schairer, J. F. Compositions and structural states of anhydrous Mg cordierites—a reinvestigation of the central part of the system $MgO–Al_2O_3–SiO_2$, (2) 56*f*. Metastable osumilite- and petalite-type phases in the system $MgO–Al_2O_3–SiO_2$, (6) 173*h*.
Schriner, J. E. Method and apparatus for molding, P (3) 80*d*.
Schroeder, H. Transparent conductive reflection-reducing coatings on nonconductive objects and methods, P (10) 273*b*.
Schroeder, H. S. Molded bodies resistant to abrasion, P (6) 162*i*.
Schroeder, J. Apparatus for determining the thermal conductivity of solids in the temperature range 20° to 200°C, (10) 285*j*.
Schroeder, K. Automatic glass grinding machines (I) practices and considerations in the manufacture of machines for the decorative grinding of hollow glasses, (8) 208*e*; (II) technical problems in the machine grinding of decorative designs on hollow glasses, P (8) 208*f*.
Schueller, K. Effect of quartz on the texture of porcelain, (3) 75*f*.
Schuetz, H. Clean air in ceramic factories, (3) 90*d*.
Schuler, F. Ancient glassmaking techniques—Egyptian fused miniature mosaics (abstract), B (11) 321*c*. Ancient glassmaking—the evolution of techniques, B (11) 321*h*; methodology for attacking the Assyrian glassmaking texts, B (11) 321*h*.
Schulkes, J. A. See Gorter, E. W.
Schulle, W. See Dietz, U.
Schuller, W. H. W. Spinning of glass or other thermoplastic masses from rods, P (2) 43*d*.
Schuller, W. H. W., and Keib, H. Continuous spinning of glass or like thermoplastic masses from rods, P (2) 42*a*.
Schultheis, P. Clear primer for enameling cast iron, P (6) 155*d*. Fusion of enamels, glazes, and glass, P (6) 155*e*.
Schultheis & Sohne. Clear primer for enameling cast iron, P (6) 155*d*. Fusion of enamels, glazes, and glass, P (6) 155*e*.
Schultz, C. E. Variable strength permanent magnets, P (6) 166*i*.
Schultz, G. See Helming, B.
Schultz, W. H. Ceramic coated tuyeres, etc., P (4) 97*g*. Tuyere with preformed refractory nose and sleeve, P (3) 75*a*.
Schumacher, C. P. Thinning slurries for fatter profits, (11) 302*e*.
Schumacher, W. W. B. X-ray spectrometer, P (1) 24*e*.
Schumann, H. Ceramic structural materials for the absorption of gamma radiation and neutrons, (10) 274*a*.
Schuster, H. Automatic shaping of flowerpots, bowls, etc., from plastic clay, (10) 284*a*. Hot body preparation and hot forming (II) heating and moistening by the Perio-Kontinu process, (3) 79*e*.
Schuster, H. K. New special type of paper for the ceramic industry, (9) 254*g*.
Schwab, G.-M., and Schmid, H. Effect of added oxides on *p*-conducting nickel oxide, B (9) 260*e*.
Schwartz, A. B. Method for preparing siliceous aerogels, P (2) 55*b*.
Schwartz, C. M. See Sclar, C. B.
Schwartz, D. L. Process for producing high density refractory bodies, P (1) 17*a*.
Schwartz, D. S. Piezoelectric transducer, P (5) 136*i*.
Schwartz, K. E. Film for recording the reactions in the diamond wheel structure, (3) 63*f*.
Schwartzwalder, K. Heat-sensing device with protective sheath, P (2) 38*c*. See Edwards, W. R.; Schwyn, R. E.
Schwartzwalder, K., and Somers, A. V. Method of making porous ceramic articles, P (9) 246*c*.
Schwarz, E. G. K. See Schimitschek, B. J.
Schweickert, H., Reusechl, K., and Gutsche, H. Method of production of high-purity semiconductor materials for electrical purposes, P (11) 311*d*.
Schweinsberg, E. S. zu. Contributions to the sociology of glass—an attempt, B (11) 321*d*.
Schweitzer, D. G., Hrabak, G. C., Singer, R. M., and Gurynsky, D. H. Oxidation and heat transfer studies in graphite channels (I) effect of air flow rate on the C–O_2 and CO–O_2 reaction; (II) thermal changes with time and distance in air-cooled graphite channels; (III) chemical reactivity of BNL graphite and its effect on the length of channel cooled by air; (IV) combined effects of temperature, flow rate, diameter, and chemical reactivity on the length of channel cooled by air, (6) 160*d*.
Schweitzer, H. V., and Verba, R. J. Electrostatic spray heads, P (8) 221*h*.
Schweitzer Electrostatic Co. Electrostatic spray heads, P (8) 221*h*.
Schwiete, H. E. Contribution to development of methods of testing refractory materials for resistance to thermal shock, B (10) 300*i*. See Jeschke, P.; Kurczyk, H. G.; Ludwig, U.
Schwiete, H. E., and Tik-Ien, A. T. Contribution to the determination of heat of hydration of clinker minerals, B (5) 149*c*.
Schwing, R. L. Method of making electrically insulated heating units, P (1) 18*h*.
Schwob, C. R. Determination of shielding factors of complex structures for the energy range of 0.1 to 4.0 Mev [translucent model], P (10) 287*e*.
Schwyn, R. E., and Schwartzwalder, K. Method for making electrodes, P (7) 193*g*.
Sclar, C. B., Carrison, L. C., and Schwartz, C. M. Optical crystallography of coesite, (7) 199*b*. Relation of infrared spectra to coordination in quartz and two high-pressure polymorphs of SiO_2, (2) 58*c*.
Scott, A. B. Energy structure of crystals, (10) 298*f*.
Scott, J. N., Jr., Alexander, D. L., and Peters, D. L. Blow molding apparatus, P (9) 250*a*.
Scott, S. W. See Brennan, J. H.
Scott, W. D. Purification, growth of single crystals, and selected properties of MgF_2, (2) 58*j*.
Scott, W. D., and Pask, J. A. Deformation and fracture of polycrystalline lithium fluoride, (8) 226*j*.
Screen Heating Transformers, Inc. Electrically heated screening apparatus, P (6) 167*a*.
Scruggs, D. M. See Herron, R. H.
Seabright, L. H., Fabian, R. J., and LaQue, F. L. Corrosion—M/DE Special Report No. 202, (10) 298*d*.
Seabrook, M. See Ringwood, A. E.
Seager, A. F., and Sunagawa, I. Movement of screw dislocations in hematite, (8) 229*a*.
Seailles, J. C. Calcium aluminates from slags, P (3) 64*h*.
Seal, M. Growth history of diamonds as revealed in etched cross sections, (10) 293*j*.
Sealtite Insulation Mfg. Corp. Apparatus for manufacturing mineral wool fibers, P (1) 10*f*. Rotors for use in apparatus for manufacturing mineral wool, P (1) 12*e*.
Seamster, A. H. See Asher, D. R.
Seanor, J. G. Laminations (I) what causes them in clay products; (II) relation of clay particles to bonding, (9) 243*b*; (III) causes in clay; (IV) causes in clay performance, (11) 305*e*.
Searcy, A. W. High-temperature inorganic chemistry, B (3) 92*b*.
Searight, C. E. Method and apparatus for making glass beads, P (5) 131*d*.
Searight, C. E., and Alexander, E. M. Glass composition for beads, P (4) 99*g*.
Sears, G. W. Ultimate strength of crystals, (9) 257*e*. See DeVries, R. C.; Morelock, C. R.
Sears, G. W., DeVries, R. C., and Huffine, C. Twist in alumina whiskers, (2) 59*e*.
S.E.C.I. See Societa Elettrotecnica Chimica Italiana S.p.A.
Secord, R. N., and Wendell, C. B. Production of silicon tetrachloride, P (10) 290*e*.
Sedlacek, R. See Halden, F. A.
Sedlacsik, J., and Sedlacsik, J., Jr. Apparatus for the electrostatic coating of articles, P (1) 4*h*.
Sedlacsik, J., Jr. See Sedlacsik, J.
Seeley, D. C. See Marino, A. J., Jr.
Segalova, E. E. See Andreeva, E. P.; Luk'yanova, O. I.
Segel, S. L. See Barnes, R. G.
Segnit, E. R. Three planes in the quaternary system $CaO–ZnO–Al_2O_3–SiO_2$, (2) 59*b*. See Cole, W. F.
Segnit, E. R., Liversidge, R. M., and Gelb, T. Mechanism of corrosion of firebrick by ash of borax-impregnated timber, (10) 275*i*.
Segrove, H. D. Purification of sand containing color-imparting impurities, P (1) 26*l*. Removal of iron-containing materials from sand, P (3) 85*c*.
Seidel, J. Inorganic binders for C cores, (8) 207*c*.
Seidle, R. E. Method and container for shipping brick [by rail], P (2) 44*d*.
Seirig, A. K. See Enders, A.
Seitz, G. See Jonas, B.
Seitz, J. P. Control for electric furnace, P (1) 24*g*.
Sejbl, J., and Sejblova, S. Harmful properties of fluorine and its compounds, (8) 230*g*. Health damage by use of ammonia, (7) 202*b*.
Sejblova, S. See Sejbl, J.
Seki, K. See Hirota, M.
Seki, Y. See Ishikawa, Y.
Sekikawa, K. See Nishioka, A.
Sekiya, M. Transition after dehydration of calcium sulfate hemihydrate, (9) 237*h*.
Sekiya, M., Setoyama, K., and Nezishi, H. Kinetic transition in liquid phase between calcium sulfate dihydrate and hemihydrate, (9) 236*h*.
Sekiya, M., and Sugiyama, Y. Effects of crystal state on the dehydration of calcium sulfate dihydrate, (1) 2*j*.
Sekiya, M., Sugiyama, Y., and Okamoto, S. Effects of some inorganic salts on the dehydration of calcium sulfate dihydrate, (2) 34*e*.
Selas Corp. of America. Apparatus for forming clay spheres, P (4) 106*e*. Burner, P (6) 169*c*. Furnace conveyor roll, P (1) 24*i*. Manufacture of uniform cellular ceramic articles, P (2) 46*a*. Method of producing a combined radiant heat fuel burner block and refractory cup, P (1) 16*f*. Radiant cup gas burner, P (5) 140*f*, P (7) 197*a*. Walking beam mechanism, P (9) 253*f*.
Sellers, T. (editor). Ceramic Projects, B (11) 321*c*.
Sellew, W. W. See Rosen, A. H.
Seltmann, H. Mold for shaping ceramic material, P (5) 133*b*.
Semb, T. K. See Jakobsen, K.
Semenov, L. P. See Agranovich, V. M.
Semenovskaya, S. V. See Ivensen, V. A.
Semicon of California, Inc. High-frequency energy absorbing material, P (10) 282*i*.
Semrau, K. Construction, operation, and characteristics of dust collectors in the silicate and metallurgical industries (II) wet dust collector, (5) 137*j*.
Sen, B. K. See Ghosh, S. N.
Sen, D. N. See Damodaran, V.
Sen, P. See Das Gupta, H. N.
Sen, P. C., Rao, M. R., and Rao, H. V. B. Refractory properties of Indian seawater magnesia, (6) 170*h*.
Sen, R. Safe limit of fluoride content for direct silica determination, (5) 145*c*.
Sen, S. Changes in the physical properties of kaolinite clay on heating and their structural implications, (3) 82*d*. See Ghosh, S. N.
Senior, B. W. See Custers, J. F. H.
Senior, F. C. Furnace refractory structures, P (6) 162*c*.
Sentyurin, G. G. Structure of glass and its thermal history, (7) 185*b*.
Senzaki, K. See Kawasaki, K.
Septier, A. See Cartz, L.
Serb-Serbina, N. N., Savvina, Yu. A., and Zhurina, V. S. Formation of calcium hydrochloraluminates and their influence on the structure of cement stone, (5) 126*h*.
Sergeant, G. A. See Wilson, A. D.
Serratosa, J. M. Dehydration and rehydration studies of clay minerals by infrared absorption spectra, B (5) 150*h*.
Serratosa Marquez, J. M. Physical chemistry of clay suspensions, B (2) 61*a*.
Service (Engineers), Ltd. Apparatus adapted for use in affixing handles in the manufacture of articles of ceramic ware, P (1) 18*e*.
Servo Corp. of America. Direct-reading [radiation type] pyrometer microscope, P (7) 196*b*.
Servomechanisms, Inc. Method of making multiple layer condensers by vapor deposition and product thereof, P (10) 283*h*.
Serwatzky, G. Preparation of clays for electron microscope examination, (5) 138*c*. Preparation of mullite for the electron-optical study of ceramic raw materials and fired bodies, (8) 229*h*.

Setaka, N. See Kawashima, C.
Seth, S. Prospects of ceramic industry in Uttar-Pradesh, (9) 254*g*.
Seto, K., and Murakami, T. Building materials made with granulated slag and sand, (8) 203*j*.
Setoyama, K. See Sekiya, M.
Severin, H. State of development of ferrites and their applications, (8) 220*a*.
Seyferth, D. Vinyl compounds of metals, B (3) 92*b*.
Sfucko, N. M., Nebel, R., and Van Derbeek, W. L. Method of producing shaped asbestos-cement articles [pipe], P (10) 268*a*.
Shabalina, O. K., Derevyankin, V. A., and Kuznetsov, S. I. Experience with the examination of aluminum oxides and hydroxides under the electron microscope, (4) 113*i*.
Shafer, H. J., Jr. Decorating method and apparatus, P (8) 210*b*.
Shaffer, J. H. See Grimes, W. R.
Shaffer, P. T. B. Evidence for high-temperature forms of zirconium and tantalum monocarbides, (6) 159*g*. Zirconium boride-silicide bodies and methods of making them, P (8) 217*b*.
Shaffer, P. T. B., and Mark, S. D. Inert-atmosphere dilatometer for use to 2000°C, (4) 107*j*.
Shaikh, Z. S. Ball clays, (9) 253*j*.
Shalek, P. D. Preparation and properties of uranium and thorium monosulfides, (6) 160*d*.
Shamovskii, L. M. General rules for producing crystals of spectrometric grade by the Stockbarger method, B (9) 262*j*.
Shampaine Industries, Inc. Means and methods for electrically measuring the amount of oxygen in a gas, P (5) 139*h*.
Shand, E. B., and Stanton, C. C. Method of making an abraded neck ampoule, P (3) 70*e*.
Shand, R. L. See Holt, R. D.
Shankar, J. See Agarwala, R. P.
Shanklaud, T. J., and Hemmenway, K. Synthesis of forsterite crystals, (6) 175*d*.
Shanklin, D. L. See Adams, A. B.; Blackwood, G. W.
Shanks, H. R. See Ellerbeck, L. D.; Greiner, J. D.
Shanley, F. R. See Knapp, W. J.
Shannon, R. F. Manufacture and stabilization of colloidal silicic acid, P (7) 186*f*. Production of reinforced articles, P (2) 43*a*. See Morgan, W. L.; Slayter, G.
Shapona, G., and Brown, H. J. Basic open hearth roof construction [with metal-cased brick], P (9) 244*g*.
Shaposhnikov, I. A. See Budov, V. M.
Sharabidze, M. I. See Glonti, N. Ya.
Sharafiev, M. Sh., and Orlova, G. V. Periclase chrome-magnesite lining for a rotary kiln used to calcine cement clinker, (7) 188*g*.
Sharav, W. B. See Amsel, F. E.; Kubli, R. A.
Sharav, W. B., Coiess, T. L., and Prince, L. A. Submerged-melt arc welding composition and process, P (5) 128*c*.
Sharbaugh, A. H., and Watson, P. K. Conduction and breakdown in liquid dielectrics, B (9) 264*a*.
Sharma, K. D. See Pani, P.
Sharma, T. N. The term "porcelain"—its scope and its limitations, (9) 246*b*.
Sharon Steel Corp. Basic open hearth roof construction [with metal-cased] brick, P (9) 244*g*.
Sharp, D. E., Dean, H. N., Babcock, E. W., and Montgomery, E. C. Process and apparatus for forming multiple sheet glazing units, P (6) 158*b*.
Sharples, T. D. Particle classification [vortical], P (1) 23*d*.
Sharples Corp. Centrifugal dust separator, P (10) 285*b*. Particle classification [vortical], P (1) 23*d*.
Shashkov, A. S. See Krylova, I. V.
Shaw, C. Electric arc furnaces, P (2) 45*e*. Method of manufacturing composite refractory objects, P (3) 74*c*.
Shaw, F. See Thorpe, C.
Shaw, J. H. Radiation environment of interplanetary space, B (3) 93*d*.
Shaw, J. L. Electrical hygrometers, P (7) 196*c*.
Shaw, K. Ceramic Colours and Pottery Decoration, B (6) 176*h*. Color technology and the decoration of ceramics (XV) organic materials used in decoration, (4) 109*b*. Slip banding machinery has automatic controls, (10) 284*d*.
Shaw, R. P. Methods and means for producing physical, chemical, and physicochemical effects by large-amplitude sound waves, P (8) 222*c*.
Shaw, R. R. Rapid orientation of sapphire monocrystals, (6) 175*e*.
Shearman, W. E. See Tama, M.
Sheehan, G. M., and Lawhorne, E. R. Treatment of titanium dioxide pigment, P (8) 226*b*.
Sheftal', N. N. Formation of real crystals (II) B (9) 262*a*. See Kokorish, N. P.; Shubnikov, A. V.; Stepanov, I. V.
Sheftal', N. N., and Kokorish, N. P. Mutual overgrowth of crystals of silicon and germanium, B (9) 263*c*.
Sheinbaum, M. Comparative concentration of silica in parent material and in airborne particulate matter, (3) 90*d*.
Sheldon, J. L. See Hares, G. B.
Shell, H. R. Fluormica-fluoramphibole ceramics and processes of making them, P (2) 49*a*. See Alley, J. K.; Gibbs, G. V.; Miller, J. L., Jr.
Shell, H. R., and Warwick, W. Synthetic mica from low cost raw materials, (8) 225*j*.
Shell, J. S., and Nielson, J. P. Study of the bond between gold alloys and porcelains, (7) 183*d*.
Shell Oil Co. Glass mold lubricant, P (1) 11*b*. Process for the preparation of carbon with high moderating properties and its use in nuclear reactors, P (1) 17*g*.
Shelley, D. P. Electric Top Hat pottery kilns, (11) 314*e*.
Shelton, G. L., Jr. Specimen identification apparatus and method, P (3) 80*j*.
Shemyakina, O. N., and Klyachko, V. A. Porous magnesia sorbent for removal of silicates from water, P (3) 84*g*.
Shepard, A. O. See Lovering, T. S.
Shepherd, W. H. See Mayo, G. J. J.
Sheppard, A. P. See Dees, J. W.
Sheridan, J. Microwave spectroscopy of gases, B (9) 264*g*.
Sherman, E. J. Solid capacitors, P (11) 311*g*.
Sherning, O. D. Method of making a high temperature thermocouple, P (4) 108*a*.
Sherr, A. E., and Roshal, J. Calcium sulfate plasters containing [0.0007 to 1.5%] stearamidopropyldi - methyl - beta - hydroxyethylammonium salts, P (5) 127*a*.
Sherrill, F. A. See Wittels, M. C.
Sherwin-Williams Co. Batch small-ball ball mill for dispersing pigments in liquid vehicles, P (2) 51*a*.
Sherwood, R. C., and Williams, H. J. Magneto-optical information storage unit, P (2) 49*f*.
Shestoperov, S. V. Durability of concrete and reinforced concrete and its connection with the composition of cement, concrete, and construction methods, B (5) 149*j*.
Shevlin, T. S. Strong, tough cermets, B (3) 92*f*. See Chapman, A. T., Jr.
Shibata, C. Electron emission from oxide coated cathode subject to strong electric field, (11) 310*a*.
Shibata, N., Kubo, I., and Iwanaga, H. Simple method of obtaining replicas of selected areas in electron microscopic study, (9) 251*h*.
Shibaura Electric Co., Ltd. Quartz glass, P (2) 43*b*.
Shields, W. H. Tapping rod with lime coating, P (2) 46*h*.
Shifrina, G. G. See Vasilevskaya, L. S.
Shilo, V. P. See Vashko, A.
Shimizu, S. See Terada, K.
Shimoda, S. See Sudo, T.
Shimosato, T. See Yamada, T.
Shimula, Y., and Uchida, H. Automatic recording system of X-ray diffraction patterns, P (1) 23*j*. X-ray diffraction system, P (1) 24*d*.
Shinchi, R. See Okada, K.
Shindo, K. See Murakami, K.
Shinoda, D. See Sasaki, Y.
Shinriki, K. See Kubo, T.
Shipley, C. S. See Leum, L. N.
Shira, W. S. See Allen, F. M.
Shirane, G. See Jona, F.
Shirane, G., Pickart, S. J., and Ishikawa, Y. Neutron diffraction study of antiferromagnetic $MnTiO_3$ and $NiTiO_3$, (6) 173*j*.
Shirasaki, S. See Kubo, T.
Shirn, G. A. See Lehovec, K.
Shishakov, N. A. See Sakarov, I. E.
Shmidt, Yu. A. See Dubrovo, S. K.
Shockley, W. Method of growing silicon carbide crystals, P (1) 16*a*. Method of making thin slices of semiconductive material [by preferential etching], P (10) 283*i*.
Shoemaker, F. O. Controlled coolant resistance widens resinoid use, (5) 125*f*.
Shoji, T. See Takemoto, K.
Sholokhovich, M. L., and Khodakov, A. L. Production and properties of monocrystals of $PbTiO_3$ and of $BaTiO_3$–$BaSnO_3$ solid solutions, B (9) 263*g*.
Shonkwiler, F. P. Metal cased refractory brick, P (5) 133*a*.
Shono, S. See Tominago, A.
Shook, W. B. New horizons in lightweight aggregate, (8) 211*j*.
Shoot, L. E. See Heibel, J. D.
Shore, B. Ceramic circuits, (2) 47*h*. Lasers—new power from light, (2) 48*d*.
Shorr, N. Safety glass glazing unit, P (7) 187*a*.
Shrubsall, A. E., and Rimer, K. W. Free-peeling submerged arc welding composition, P (4) 102*g*.
Shteinberg, Yu. G., and Gaukhman, E. L. Strontium crackle glaze, (1) 2*d*.
Shternberg, A. A. Growth of crystals in response to heat removal, B (9) 262*h*. See Nepomnyashchaya, V. N.
Shtolitser, N. V. See Mazurin, O. V.
Shtrikman, S. See Frei, E. H.
Shubnikov, A. V., and Sheftal', N. N. (editors). Growth of Crystals: Vol. 3—Reports of Second All-Union Conference on Crystal Growth, Moscow, March–April 1959, B (9) 262*c*.
Shull, H. Concept of partial ionic character, B (9) 259*d*.
Shulman, W. Better control of particle sizes, (1) 25*h*.
Shulver, W., and Guyer, G. W. Method of precoating and coating glass fibers [with polyethylene derivative] and article produced thereby, P (9) 242*g*.
Shumitskaya, L. F. Determination of the resistance of glass to alkali metal vapors, P (2) 38*a*.
Shun-Fu, L. See Tolstoi, N. A.
Shurgan, J. Constant lumen maintenance lamp, P (9) 241*g*.
Shvartsman, M. Z. Automating the heating schedule of tunnel driers, (6) 167*a*.
Shwayder, W. M. Process for applying tungsten carbide particles to a workpiece surface, P (1) 2*a*.
Sidhwa, A. P. See Kingery, W. D.
Sidles, P. H. See Ellerbeck, L. D.
Sidlyarenko, V. I., Zaitov, F. N., and Lukantsever, Yu. L. Existence of F centers with different thermal stability in alkali halide phosphors, (6) 164*a*.
Sidorenko, F. A. See Davydov, K. N.
Siebel, K. Highly refractory stabilized dolomite blocks, P (3) 74*b*.
Siebert, H. Use of praseodymium compounds for light filters for Raman spectroscopy, (5) 147*i*.
Siebertz, K. Method and device for the successive zone melting and resolidifying of extremely pure substances, P (8) 220*d*.
Sieger, E. W. Apparatus for handling and wetting dust, P (8) 221*d*.
Siemens & Halske Akt.-Ges. Apparatus for drawing semiconductor bodies from a melt, P (6) 165*d*. Crucible for melting silicon of highest purity and method of making it, P (1) 20*d*. Lining of crucibles for melting silicon and other semiconducting materials, P (4) 102*c*. Method and device for the successive zone melting and resolidifying of extremely pure substances, P (8) 220*d*.
Siemens-Planiawerke Akt.-Ges. fuer Kohlefabrikate. Method for producing high-purity graphite, P (9) 244*f*. Screw nipple [expansion] joint for carbon electrodes, P (8) 225*a*.
Siemens-Reiniger-Werke Akt.-Ges. Electrically conducting oxide surface layers on nonglazed ceramic parts, P (3) 77*i*.
Siemens-Schuckertwerke Akt.-Ges. Apparatus for orientation of the crystal nucleus during the growth of single crystals, P (4) 121*g*. Apparatus for pulling [semiconductor] crystals from molten compounds, P (5) 135*d*. Ceramic containers for electric melting furnaces, especially salt-bath furnaces, P (6) 169*e*. Electrically insulating, glasslike, ferromagnetic materials, P (4) 105*i*. Electric semiconductor device, P (4) 105*f*. Hardening of mica deposited by electrophoresis, P (4) 110*i*. Magnetically responsive resistance device, particularly Hall generator, P (7) 193*d*. Method of producing hyperpure silicon, silicon carbide, and germanium, P (11) 311*b*. Method for producing sintered semiconductor bodies, P (2) 50*a*. Method for production of high-purity semiconductor materials for electrical purposes, P (11) 311*d*. Protective glass sheaths for fissionable fuel elements of nuclear reactors, P (3) 70*c*. Sintered hard materials from alumina and zirconium nitride, P (3) 75*a*. Thermocouples, P (3) 81*h*. Thin, flexible glass coatings on wire, foil, and the like, P (3) 65*g*. Very pure uranium oxides, P (4) 111*g*.
Sienko, M. J., and Weller, P. F. Carrier characteristics in copper-doped WO_3 from conductivity, Hall voltage, and thermal emf studies, (1) 26*i*.
Sifford, L. L., Sr. See Murray, J. A.
Sihvonen, Y. T. See Boyd, D. R.
Silard, B. A. Recorder for densitometer, P (11) 320*b*.
Silika- und Schamotte-Fabriken Martin & Pagenstecher Akt.-Ges. Nonporous carbon bricks, especially for cellulose digesters, P (4) 103*b*.
Silverman, A. Fiber glass—modern history and prognosis (abstract), B (11) 321*g*.
Silverman, J. H. Now you can use nonreciprocal devices at low frequencies, (7) 192*j*.
Silverman, L. Reference junctions, (9) 251*f*.
Silverman, M. D. See Blander, M.
Silvernail, W. L. Polishing composition and process of forming it, P (10) 265*g*.
Sil'vestrovich, S. I. See Boguslavskii, I. A.; Kitaigorodskii, I. I.
Silvey, G. A. See Anderson, R. L.
Simmingakold, B. Cleaning art and crystal glass ultrasonically, (7) 184*g*. See Rosenkrands, B.
Simmonds, R. N. See Davies, L. M.
Simms, D. L., and Coiley, J. E. Some radiation characteristics of a gas-fired panel, (10) 287*i*.
Simnad, M. T. See Goeddel, W. V.
Simon, E. See George, M. F., Jr.
Simon, I. Method for optical measurement of fiber diameters, P (4) 100*e*.
Simon, R. See Leroy, P.
Simonds Abrasive Co. Grinding disk, P (4) 95*f*.
Simons, C. C. See Klein, M. J.
Simons, E. L. Modified flotation method of density determination for small solid samples, (7) 195*e*.
Simpson, Herbert, Corp. See Herbert Simpson Corp.
Simpson, Orville, Co. See Orville Simpson Co.
Sinclair, W. R. See Williams, J. C.
Sinclair, W. R., and Peters, F. G. Preparation of oxide glass films by reactive sputtering, (3) 67*d*.
Sinclair, W. R., and Williams, J. C. Mullite synthesis, P (5) 136*h*.
Singer, E. See Bauer, W.
Singer, R. M. See Schweitzer, D. G.
Sinha, V. T. Nomograph gives equivalent lengths of orifices, (2) 51*a*.
Sinke, G. C. See Stull, D. R.
Sinta, T. See Wolff, F.
Sip, V., and Vanicek, V. New items of equipment for the production of monocrystals, B (9) 262*i*.
Sircar, N. R. See Banerjee, J. C.
Sirois, L. L. See Salman, T.
Sirota, N. N. Some major topics in the theory of crystal nucleation and growth, B (9) 262*g*.
Sirvetz, M. H. See Schloemann, E. F. R. A.
Sisman, O. See Morgan, J. G.
Sison, C. R. See Bautista, E. N.
Sissons, T. Recent developments in the manufacture of sewer pipe, (6) 159*c*.
Siuta, W. T. See Dantro, H. F.
Sjodahl, L. H., and Chandler, B. A. Single-crystal elastic constants of BeO from polycrystalline measurements, (9) 257*e*.
Skeen, J. W. See Butterworth, B.

Skegga, L. T. Chromatography analysis apparatus and method, P (10) 287*c*. Fluid processing system with continuous filter apparatus, P (10) 287*a*.
Skellern, V. Color in clay, (3) 63*j*.
Skinner, B. J., Stewart, D. B., and Morgenstern, J. C. New heating stage for the X-ray diffractometer, (6) 168*d*.
Skinner, K. G. Effect of mineralogical composition, crystal phases, particle size, and particle-size distribution on the physical properties of barium titanate, (8) 219*f*.
Sklarew, S. Reinforced refractory ceramic coatings for ramjet and supersonic aircraft applications, B (3) 92*b*.
Skomal, E. N. High power ferrite isolator having ferrite materials of differing Curie temperature, P (5) 136*e*.
Skoning, J. H. S. Inorganic binder for refractory materials, P (2) 45*i*.
Skow, M. L. Mica—a materials survey, (8) 225*d*.
Skramtaev, B. G. High strength rapid hardening concrete, B (5) 150*d*.
Skreta, F. Decal decoration line for household china, (9) 245*i*.
Sladkov, A. S. Removing iron from glass sands in a mill with abrasive action, (1) 25*c*.
Slavin, R. H. Japanese-American relations—dilemma for glassware producers, (2) 40*a*.
Slayter, G. Control of crystal growth in mica materials, P (2) 55*c*. Glass-reinforced article, P (6) 157*c*. Method for producing glass roving, P (3) 70*j*.
Slayter, G., Morgan, W. L., Morrison, A. R., and Shannon, R. F. Fibrous glass product and method of manufacture, P (1) 11*f*.
Slayter, G., Rees, W. M., and Feid, J. T. Sound absorbing fibrous board with plastic film covering, P (9) 242*e*.
Sleight, A. W., Longo, J., and Ward, R. Compounds of osmium and rhenium with the ordered perovskite structure, (1) 26*j*.
Sleight, A. W., and Ward, R. Compounds of hexavalent and pentavalent uranium with the ordered perovskite structure, (7) 198*g*.
Sleptsov, V. M. See Samsonov, G. V.
Slesaczek, A. Wall [expansion joint] construction and mounting thereof for industrial furnaces, P (8) 225*b*.
Slifkin, L. See Layer, H.
Slingsby, B. See Fletcher, W. W.
Sloczynski, J. See Bielanski, A.
Smagin, A. G. Role of internal friction in piezoelectric quartz crystals, (10) 282*b*.
Smakota, N. F. See Belyaev, G. I.
Smakula, A., Maynard, N., and Repucci, A. Defects in mixed crystals of KCl-KBr, B (9) 260*h*.
Small, H. See Asher, D. R.
Smalley, B. See Delbecq, C. J.
Smalley, A. K. See Duckworth, W. H.
Smalley, W. Double cone mixing machines, P (10) 285*d*.
Smallman, R. E. See Ashbee, K. H. G.
Smellie, R. H., Jr. See La Mer V. K.
Smets, E. See Lierde, W. van.
Smid, I., Kvapil, J., Myl, J., and Solz, S. Effects of supersaturation on the production of parasitic crystals, B (9) 262*i*.
Smidth, F. L., & Co. Method of grinding portland cement using a phenolic compound as a grinding aid, P (4) 96*i*. Rotary kiln and method of burning material therein, P (5) 140*f*. Tube mill trunnion, P (10) 285*c*.
Smirnova, G. P. See Vargin, V. V.
Smirnova, T. G. See Pokrovskii, N. I.
Smit, J. See Lotgering, F. K.
Smith, A. E. See Levey, R. P., Jr.
Smith, A. L. See Stepanski, B.
Smith, A. O., Corp. Vitreous enamel-coated ferrous article and method of making it, P (10) 269*f*.
Smith, B. R. Method of making metallized ceramic bodies, P (5) 136*e*.
Smith, D. K. Techniques of high-temperature X-ray diffraction using metal ribbon furnaces, (9) 252*c*.
Smith, D. S. Hard-to-analyze minerals yield to thermal analysis, (5) 144*c*.
Smith, F. G. Physical Geochemistry, B (10) 229*j*.
Smith, G. R. Reaction milieu and after-burner incorporating it, P (8) 224*j*.
Smith, G. S. Preparation of ammonium metavanadate, P (3) 84*g*.
Smith, H. J. Care and use of mill additivies, (2) 36*j*.
Smith, H. L. See Cohen, A. J.
Smith, H. L., Jr., and Lichtenstein, V. Apparatus and method for measuring the volume and density of solid material, P (3) 81*a*.
Smith, I. N. Method of forming a substantially rigid laminated fibrous board, P (7) 186*d*.
Smith, J. V. Explanation of strain and orientation effects in perthites, (4) 114*b*.
Smith, R. E. Method and means for filtration of slurries, P (3) 84*c*.
Smith, R. I. See Sahinen, U. M.
Smith, R. M. Bonded glass surfaces and method therefor, P (4) 99*i*.
Smith, R. W. Archeological evaluation of analyses of ancient glass, B (11) 321*e*.
Smith, S., & Sons (England), Ltd. Examination by ultrasonics of bodies having a nonplanar surface, P (8) 223*i*.
Smith, T. A. Organic binders and other additives for glazes and engobes, (3) 75*e*.
Smith, T. R. Gas filter apparatus [washer], P (2) 51*c*. Gas filtering method and apparatus, P (1) 23*g*.
Smith, W. C. See Domicone, J. J.
Smith, W. D. See Frint, W. R.
Smith, W. W. Some interstratified clay minerals from basic igneous rocks, (11) 315*b*.
Smithells, C. J. Metals Reference Book, B (3) 92*f*.
Smith-Gorman, R. J. Barrelling chips, P (9) 236*a*.
Smoke, E. J. See Arlett, R. H.
Smoke, E. J., and Koenig, J. H. Development of refractory ceramics that can be processed at temperatures considerably lower than their maximum use temperature, (8) 213*b*.
Smolenskii, G. A., Agranovskaya, A. I., and Popov, S. N. Mechanism of polarization in the solid solutions of $Pb_2NiNb_2O_9$ and $Pb_2MgNb_2O_9$, (7) 192*b*.
Smolenskii, G. A., Isupov, V. A., and Agranovskaya, A. I. New group of ferroelectrics (with layered structure), (7) 192*d*.
Smoluchowski, R., and Wiegand, D. A. Formation of interstitials and vacancies in alkali halides, (10) 293*d*.
Smoot, T. W., and Stock, D. F. Cradle [zirconia setter], P (9) 244*g*.
Snell, R. G. Electrical properties and uses of glass, (9) 240*a*.
Snezhinskii, N. S. See Morozov, V. N.
Snitzer, E. See Woodcock, R. F.
Snow, H. J., and Kendrick, R. W. Method and apparatus for forming and processing fibers, P (6) 158*c*.
Snow, R. E. Process for beneficiating potash spar, P (5) 141*g*.
Snyder, M. J. Toward a science of clays, (10) 297*g*.
Snyder, R. P., Leatham, E., Gabor, C. D., and Pack, A. H. Production of dead-burned magnesia, P (2) 46*d*.
Snyder, S. W. Treatment of sodium carbonate, P (7) 198*a*.
Sobolev, B. P. See Novoselova, A. V.
Sobon, L. E. See Lefever, R. A.
Sobotka, Z. Rheological laws of the long-time deformation of concrete, (7) 182*a*.
Sochevanova, M. M. Use of complexometric methods in the analysis of silicate rocks, (9) 252*h*.
Societa per Azioni Del Monte Amiata Farine Fossili d'Italia. Bleaching of diatomaceous earth, P (4) 110*e*.
Societa per Azioni Forni ed Impianti Industriali Ingg. De Bartolomeis. Device for localizing rapid variations of temperature at predetermined points in tunnel type kilns for the firing of ceramic products, P (1) 24*h*.
Societa per Azioni Macchine per l'Industria Dolciaria Carle & Montanari. Hydraulic horizontal press with two series of multiple chambers for pressing with filter plates for very high production, P (5) 138*a*.
Societa Elettrotecnica Chimica Italiana S.p.A. Method of making covered electrical resistors, P (2) 49*e*.
Societe Anon. des Etablissements Parra-Mantois & Cie. Optical glass containing silica and boric anhydride and lanthanum oxide and alkaline earth as modifiers, P (3) 70*b*.
Societe Anon. de Machines Electrostatiques. Electrostatic spraying or atomizing heads for liquids or pulverulent solids, P (7) 195*b*. Gun for atomization and electrostatic spraying of materials, P (5) 138*h*. Spray guns having a fixed electrostatic head, P (8) 222*b*.
Societe Anon. des Manufactures des Glaces & Produits Chimiques de Saint-Gobain, Chauny et Cirey. Glass compositions for use as wire-drawing lubricants, P (6) 157*b*. Spheroidal glass particles which contain fissionable material, P (6) 158*g*.
Societe d'Electro-Chimie, d'Electro-Metallurgie et des Acieries Electriques d'Ugine. Process for the conversion of dolomite, P (1) 17*b*.
Societe des Electrodes et Refractaires Savoie. Refractories of high mullite content, P (3) 74*f*.
Societe d'Etudes de Coordination et d'Orientation des Societes du Groupe Gabriel Marly (S.E.-C.O.). Continuous coating of mirrors with silver, P (4) 99*c*.
Societe Grenobloise d'Etudes et d'Applications Hydrauliques. Apparatus and process for sorting solid particle material in a fluidized liquid medium, P (5) 141*a*.
Societe Intercontinentale de Realisation et d'Exploitation d'Inventions. Luminescent and phosphorescent glass, P (3) 69*d*.
Societe Nouvelle de l'Outillage, R.B.V. et de la Radio-Industrie. Ceramic oxide bases for cadmium sulfide photoresistance cells, P (3) 77*c*.
Societe de Technique Industrielle. Refractory materials for air heaters for blast furnaces, P (3) 74*h*.
Society for Analytical Chemistry, Analytical Methods Committee, Particle Size Analysis Sub-Committee. Classification of methods for determining particle size—a review, (7) 195*i*.
Society of Glass Technology, Chemical Analysis Committee. Chemical analysis of a fluoride-opal glass described as Standard Glass No. 4, (2) 38*j*.
Society of Glass Technolog , Furnace Committee. Instrumentation of regenerative furnaces in the British glass industry, (3) 66*h*.
Society of Glass Technology, Physical Properties Committee. Assessment of heterogeneity in glass, (1) 5*j*.
Society of Glass Technology, Refractories Committee. Application of vitreous silica in tank furnaces, (7) 187*d*. Corrosion tests for evaluating the solution of tank block materials by molten glass, (1) 6*a*.
Socony Mobil Oil Co., Inc. Method for preparing siliceous aerogels, P (2) 55*b*. Process for making crystalline zeolites, P (4) 111*a*.
Soda, T., and Maekawa, A. Effects of entrained air on properties of mortar, (7) 180*f*.
Soda, T., Manabe, T., Eguchi, I., and Yanakawa, S. Relation between the false set of cement and the consistency of concrete at a low temperature, (7) 181*j*.
Soffer, B. H. Studies of the optical and infrared absorption spectra of rutile single crystals, (4) 121*b*.
Soga, N., Sakka, S., and Tashiro, M. Chemically machinable photosensitive glasses of the Li_2O–K_2O–ZnO–SiO_2 system, B (11) 320*h*.
Soga, N., and Tashiro, M. Role of cerium ion in preventing the γ-ray induced coloration of glass, (11) 304*h*.
Sogawa, S. Scattering coefficient, reflectivity, and covering power of recrystallized opaque glazes, (3) 75*i*.
Sogn, L. T. Quartz piezoelectric element, P (5) 137*g*, P (10) 283*f*.
Soifer, L. M. See Naboikin, Yu. V.
Sokolov, A. A. Calculating the basic convection stream of glass in tank furnaces, (1) 5*f*.
Sokolov, N. V., and Levin, A. I. Electrolytic treatment of metalloceramic drawplates, (4) 97*f*.
Sokolov, V. A. See Gorban, A. N.
Solbach, W. Construction, operation, and characteristics of dust collectors in the silicate and metallurgical industries (I) centrifugal dust collector, (5) 137*j*.
Solc, I. Highway reflection glasses, (9) 240*e*.
Soldatov, G. A. See Zakharikov, N. A.
Solinov, F. G., Borisov, B. I., and Terman, V. B. Design of submachine chambers for drawing sheet glass without a debiteuse, (7) 184*h*.
Solivan, R. A. See Lehrer, N. H.
Solntsev, P. I., and Gershkovich, V. I. Strength of press-mold plates used for pressing fireclay products, (7) 188*j*.
Solomon, A. L. See Goldberg, P.
Solomon, L., Dragoman, I., Barlogeanu, C., and Camerman, C. Sintering process of chemically prepared magnesia, (3) 72*j*.
Solomonov, E. F. See Benediktova, N. B.
Solonnikova, L. A. See Samsonov, G. V.
Solow, G. Partially atuomatic equipment for the production of glass tubes, (1) 8*e*. See Wihsmann, F. G.
Solt, G. S., Wegelin, E., and Chapman, C. V. G. Electrodialysis as a unit operation, (10) 284*c*.
Solvason, K. R. See Wilson, A. G.
Solz, S. See Smid, I.
Som, S. K. See Roy, S. B.
Somers, A. V. Alumina base ceramic, P (8) 218*b*. See Schwartzwalder, K.
Somiya, S. See Muan, A.
Sommer, H. E. Process and apparatus for the manufacture of fibers from fusible mineral materials, more particularly glass and its derivatives, P (7) 186*g*.
Somogyi, A. See Kocsis, G.
Somorjai, G. A. Surface energy effect on diffusion-controlled particle growth, (3) 89*i*.
Sondy, D. Ceramic kiln, P (10) 288*a*.
Sonneborn Chemical and Refining Corp. Portland cement concrete adjuvant, P (1) 3*h*.
Sonntag, A. Significance of surface finish on friction, wear, and lubrication, (3) 90*g*.
Soper, R. J. See Weir, C. C.
Sormberger, R. L. See Cusano, D. A.
Sorrell, C. A. See Borasky, R.
Sorrell, J. See Wilkinson, W. T.
Soubier, L. D. Apparatus for producing charges of molten glass, P (4) 99*f*. See Kozak, J.
Soudan, P., and Mercier, H. Apparatus for the continuous digestion of bauxite [in a series of autoclaves], P (10) 289*e*.
Soule, D. E. Analysis of galvanomagnetic de Haas-van Alphen type oscillations in graphite, (4) 112*c*. Magnetic field dependence of the Hall effect and magnetoresistance in graphite single crystals, (4) 115*j*.
Sourirajan, S., and Accomazzo, M. A. Application of the copper oxide-alumina catalyst for air pollution control, (3) 79*d*.
Spacil, H. S. Analytical process and apparatus P (9) 252*d*.
Spain, J. M. See Bronson, R. D.
Spakovsky, E. See Cernoch, S.
Spang, A. See Geilmann, W.
Spann, J. R. See Ewing, C. T.
Specialties Development Corp. Method of adjusting the resistance of [metallic oxide] thermistor elements, P (6) 166*f*.
Specialties, Inc. Colorimeter and [photoelectric] color sorting apparatus, P (3) 81*c*.
Spedden, H. R. See Gaudin, A. M.
Speed, D. B. Free-flowing sodium silicate powder P (1) 25*i*.
Speil, S. See Barnett, I.
Spektor, M. P. See Zakharikov, N. A.
Spence, G. See Gill, R. M.
Spendelow, H. R., Jr., Folkman, R. L., and Allenbach, C. R. Electrodes for melting refractory metals, P (2) 45*f*.
Spendiarov, N. N. See Aleksandrov, B. S.
Spenke, E. See Heriet, A.
Sperry, L. L. See Ohlberg, S. M.
Sperry Rand Corp. Process and apparatus for producing magnetic material and resulting article, P (3) 78*f*. Vibratory feeder, P (8) 222*d*.
Spetzler, E. Life of refractory linings in the Rotor process, (6) 161*a*.

Spiegelglaswerke Germania Akt.-Ges. Zweigniederlassung der Glaceries de Saint Roch Soc. Anon. Process for the preparation of multipane insulating glass, P (10) 272*j*.
Spielberg, N. See Ladell, J.
Spielman, L. S. See Keating, J. P.
Spinks, C. N. Early Thai pottery, (9) 236*f*.
Spinrad, B. I., Sandmeier, H. A., and Martens, F. H. Fuel assay reactor, P (4) 102*i*.
Spitzer, W. G., and Tanenbaum, M. Growing and determining epitaxial layer thickness, P (11) 311*e*.
Spooner, R. B. Nuclear reactor safety device, P (4) 103*c*.
Sporer, A. G. Bedding glass plates for grinding and polishing, P (6) 157*g*. See Mambourg J. E.
Sprague, R. See Bacon, R.
Sprague Electric Co. Ceramic bodies, P (3) 77*b*. Inductor materials, P (3) 77*e*. Preparation of multiple *pn* junction semiconductor crystals, P (3) 78*e*.
Spriggs, R. M. See Vasilos, T.
Spriggs, R. M., Brissette, L. A., Rossetti, M., and Vasilos, T. Hot-pressing ceramics in alumina dies, (10) 284*h*.
Spriggs, R. M., Brissette, L. A., and Vasilos, T. Preparation of magnesium oxide of submicron grain size and very high density, (11) 318*g*.
Spriggs, R. M., and Vasilos, T. Effect of grain size on transverse bend strength of alumina and magnesia, (7) 198*j*.
Sprigings, D. G. Electrical insulator constructions, P (10) 279*c*.
Springfield Greene Industries, Inc. Thermometer construction, P (5) 131*h*.
Sproule, W. A. See Wranau, G. von.
Sprouse, N. T. See McIntyre, G. H., Jr.
Spurck, R. F., Doolittle, H. D., Ettre, K., and Varadi, P. F. Metallizing tape for high quality ceramic-metal seals, (1) 19*j*.
Spurlin, W. V. Dual eccentric weight vibratory generator for circular feeder, P (1) 23*g*.
Srivastava, J. P. See Deshmukh, G. S.
Srp, O. O. See Cooper, T. D.
Staats, P. A. See Morgan, H. W.
Stackhouse, R. D. Coated graphite bodies, P (8) 215*h*.
Stadelmaier, H. H. See Huetter, L. J.
Stafford, W. L. See Konrad, H. E.
Stahl, E. (editor). Thin-Layer Chromatography—A Laboratory Handbook, B (8) 234*j*.
Staiego, C. J. Method and apparatus for forming fibers, P (1) 11*g*. See Piolenc, G. de.
Staley, W. W. Oneida perlite deposit, (4) 110*d*.
Stalter, T. L., and McKulla, G. W., Jr. Effective pickling (I) direct to steel enameling methods, (1) 4*e*; (II) single coat nitrate process speeds and economizes pickling, (3) 65*f*. See Foos, R. A.
Stambaugh, E. P., and Foos, R. A. Zirconium dioxide recovery, P (9) 254*j*.
Stambera, A. Apparatus for discharging bulk material in granular or powdery state, P (1) 23*e*.
Stamberger, P. Method for preparing aqueous dispersions of clay coated with polymers of ethylenically unsaturated monomers and aqueous film forming compositions produced, P (4) 111*a*.
Stanavage, J. P. Electroluminescent screen, P (4) 105*a*.
Stanchus, F. T. See Amsel, F. E.
Standard Elektrik Lorenz Akt.-Ges. Electrically conducting transparent layers on glass objects, P (4) 99*e*.
Standard Oil Co. Glass grinding process employing a nonfoaming oiliness agent, P (3) 69*i*. Lightweight structural unit, P (8) 210*j*. Method of acid treating hollow glass spheres, P (3) 69*g*. Method of controlling properties of porous metal oxides, P (10) 289*d*. Method of producing a permanently active catalyst utilizing neutron irradiation, P (9) 244*h*.
Stanford, A. L., Jr., and Arnold, R. T. Ferroelectric microwave switch, (7) 191*j*.
Stanford, R. E. L., and Hennig, R. J. Plutonium fuel systems for the next large fast breeder power reactors, B (8) 232*j*.
Stangl, J. M. Decorated ceramic ware, P (3) 64*a*.
Stanton, C. C. See Shand, E. B.
Stanworth, J. E. Science and technology in the glass and electrical industries, (9) 258*c*.
Stanyon, H. E. See Beeson, E. J. G.
Staples, B. G. Bolt torques and gaskets for glassed-steel equipment, (9) 238*b*.
Staples, R. W. See Dear, E. J.
Stapleton, R. E. See Pappis, J.
Starr, C. Nuclear reactor, P (5) 133*d*.
Stauffer, K. W. Quantitative petrographic study of Paleozoic carbonate rocks, Caballo Mountains, New Mexico, (4) 110*d*.
Stauffer Chemical Co. Electron-beam furnace with opposed-field magnetic beam guidance, P (8) 223*h*.
Stavrolakis, J. A. See Henderson, C. M.
Stearn, E. W. Accurate weights—with electronic continuous belt weighing systems, (10) 284*a*.
Stearns, W. E. See Nelson, F. W.
Steatit-Magnesia Akt.-Ges. Ceramic balls for grinding mills, P (4) 106*h*. Ferrite containing neodymium, P (3) 77*a*.
Stecher, P. See Rudy, E.
Stedham, M. E. C. Improved method of moisture control for ceramic products, (3) 71*g*. Rapid measurement of water absorption of building bricks, B (10) 300*b*.
Steel Technology Joint Research Society, Special Steel Division. Pouring pit refractories, (6) 160*c*.
Steeves, R. W. See Baer, C. A.
Steg, L. Materials for reentry heat protection of satellites, (1) 7*g*.
Steghart, F. L. F., Kershaw, P. L., and Harvey, J. P. Burner control means, P (7) 197*c*.
Stehle, H. Grain growth of UO_2, (10) 293*i*.
Stehsel, M. L. See Green, L., Jr.
Stehsel, M. L., Hale, R. M., and Waller, C. E. Modulus of rupture measurements on beryllium oxide at elevated temperatures, B (3) 92*c*.
Steierman, B. L. Glass rod and tube cutter, P (8) 210*g*.
Steijn, R. P. Sliding and wear in ionic crystals, (10) 297*f*.
Steimke, F. C. New refractories for the glass industry, (10) 275*j*.
Stein, H. A. See Murdock, J. B.
Steinberg, M. See Glasner, A.
Steinbrucker, C. Chimu ceramics from the northern coast of Peru, (10) 265*j*. Nymphenburg porcelain, (10) 266*a*.
Steinfink, H. Crystal structure of a trioctahedral mica—phlogopite, (8) 226*f*.
Steinhauer, O., and Schaefer, W. Use of dolomite in the production of basic pig iron and its effect on the applicability of basic pig iron slag to road construction, (10) 268*b*.
Steinhoff, E. See Kienow, S.
Steinitz, R. See Juretschke, H. J.
Steinkuller, E. W. See Ewing, C. T.
Steneck, W. G. See Brockman, F. G.
Stenger, V. A. See Goodenough, R. D.
Steopoe, A. Two occurrences of rapid destruction of steel in concrete, (8) 206*f*.
Stepanenko, M. G., and Pavlov, V. S. Method of calculating tank furnaces with developed working installations, (1) 8*a*.
Stepanov, I. V., and Vasil'eva, M. A. Temperature control during the production of optical-grade monocrystals, B (9) 262*g*.
Stepanov, I. V., Vasil'eva, M. A., and Sheftal', N. N. Effects of the temperature gradient at the contact between crystal and melt on the growth of a monocrystal, B (9) 262*h*.
Stepanova, N. S. See Belyustin, A. V.
Stepanski, B., Smith, A. L., and Werthwine, J. Method of delaminating cemented glass optics or lenses, P (1) 12*c*.
Stephens, D. L. See Alford, W. J.
Stephenson, C. V., and Flanagan, C. E. Electrical conduction in polycrystalline lead zirconate-titanate, (2) 47*h*.
Stephenson, R. L. See Bosley, J. J.
Stepien, K. See Paprocki, A.
Stepula, E. V. See Mikhnevich, G. L.
Sterk, E., Tardos, M., and Szanto, V. Method for electron microscopic study of ceramic surfaces, (9) 251*j*.
Sterk, E., and Veszelei, J. Micromorphological investigations of manganese zinc ferrites, (10) 295*i*.
Sternberg, R. W. See Creager, J. S.
Sterry, J. P. New refractory fibers for ablation and thermal insulation, (6) 160*c*.
Steudel, H. K. See Perthen, J. F.
Steuler-Industriewerke G.m.b.H. Highly refractory stabilized dolomite blocks, P (3) 74*b*.
Stevels, J. M. Dielectric losses of quartz crystals in relation to their imperfections, B (11) 320*j*. See Kats, A.; Trap, H. J. L.
Stevels, J. M., and Volger, J. Further experimental investigations on the dielectric losses of quartz crystals in relation to their imperfections, (5) 143*k*.
Stevens, D. Establishment of the potential of flake reinforced composites as engineering structural materials, (9) 240*b*.
Stevens, D. C., and Hounam, R. F. Fine glass fiber paper for air sampling, (3) 90*e*.
Stevens, D. S. Method of a means for determining the average size o particles, P (8) 224*d*.
Stevens, R. J. Resistance [probe type] thermometer, P (3) 81*f*.
Stevenson, F. D., and Wicks, C. E. Metal diaphragm apparatus for measuring vapor pressures—vapor pressure of arsenic(III) oxide, (9) 251*h*.
Steward, E. G. See Hart, P. B.
Stewart, D. B. See Skinner, B. J.
Stewart, F. Symposium on economics in the enamel shop: Equipment, (2) 37*f*.
Stewart, G. H. (editor). Science of Ceramics: Vol. I—Proceedings of a Conference Held at Oxford, June 1961, Under Auspices of the British Ceramic Society and the Nederlandse Keramische Vereniging, B (4) 123*f*.
Stewart, G. W. Preliminary report—lightweight aggregate raw materials in New Hampshire, (8) 225*j*.
Stewart, I. M., and Buchi, G. J. P. Phase relationships in the system Li_2O–ZnO–SiO_2, (3) 88*h*.
Stewart, M. M. Method for preparing beta-alumina trihydrate, P (10) 289*f*.
Stichting Reactor Centrum Nederland. Process for the preparation of granular uraniferous material of uniform particle size, P (10) 277*e*.
Stickel, A. Apparatus for bending glass sheets P (3) 68*d*. See Carson, F. J.
Stickler, J. J. See Heller, G. S.
Stiefbold, D. R., Boston, J. R., and Huggins, R. A. New dislocation etchant for magnesium oxide, (11) 318*c*.
Stiegler, J. O. See Wittels, M. C.
Stiehl, H. See Ginsberg, H.
Stiller, B., and Louckes, F. I., Jr. Multifilar measuring device, P (10) 287*b*.
Stillman, C. J. See Drysdall, A. R.
Stirling, A. W. See Hill, R. A.
Stirling, H. T. Continuous radiant furnace sintering machine, P (7) 197*c*.
Stirling, H. T., and Hartzell, H. F., Jr. Method and apparatus for moistening dust, P (9) 250*d*.
Stobo, J. J. See Brown, D. J.
Stock, D. F. See Smoot, T. W.
Stoddard, M. Tunnel kilns, (6) 169*b*.
Stokes, R. J. Dislocation sources and the strength of magnesium oxide single crystals, (8) 227*h*.
Stokes, R. J., and Li, C. H. Dislocations and the strength of polycrystalline ceramics, (8) 227*j*. Dislocations and tensile strength of magnesium oxide, (10) 291*j*.
Stolterfoht, H. Automatic apparatus for measuring the particle size distribution of dispersed phases, (7) 195*g*.
Stone, B. D., and Ruehrwein, R. A. Production of single crystal boron phosphide, P (5) 133*h*.
Stone, I. C. See Kramm, D. E.
Stookey, S. D., and Maurer, R. D. Catalyzed crystallization of glass—theory and practice, B (8) 232*e*.
Storey, C. Oxygen application to fixed basic open-hearth furnaces and its effect on refractories consumption, (6) 161*a*.
Stout, R. K. Brick veneer construction material, P (6) 159*b*.
Stover, E. R. See Westbrook, J. H.
Strain, F., Wilson, W. L., Dietz, P. L., Jr., Hughes, W., and Arkless, K. Method of preparing metal oxides, P (4) 111*b*.
Strakna, R. E. See Clark, A. E.
Strasser, O., and Busch, M. Porcelain compositions, P (4) 104*c*.
Strategic Material Corp. Electrode structures and processes for utilizing them, P (5) 133*h*. Furnace refractory structures, P (6) 162*c*. Sealer-cooler structure for furnace electrodes, P (2) 46*h*.
Straubel, R. Generation of magnetic anisotropy in ferrites by thermomechanical treatment, (3) 86*i*.
Straughan, V. E. See Mayer, E. F.
Strauss, E. L. Structural and heat transfer characteristics of resin-impregnated porous ceramics, (9) 243*i*.
Strauss, J. Lauenstein glasses—notes for the connoisseur, B (11) 321*d*.
Strecker, H. A. See Jones, A. L.
Streib, W. C., and Rowe, J. G., III. Asbestos fibers in mine roof coatings, P (2) 55*b*.
Strelets, V. M. See Pitak, N. V.
Streng, J., and Dattan, W. Semiconducting ceramic glazes for insulating bodies, P (3) 79*a*.
Strepp, N. See Wiemer, H.
Strittmatter, W. E. See Albertson, C. P.
Strivens, M. A. Injection molding of ceramic insulating materials, (2) 47*d*.
Stroemstad, S. See Kalling, B.
Strong, H. M. Two-terminal end cap for high pressure, high temperature reaction vessels, P (8) 222*c*. See Bundy, F. P.
Strong, P. F. See Emslie, A. G.
Stroud, J. S. Photoionization of Ce^{3+} in glass, (3) 67*b*.
Stroup, R. C. See Ford, C. E.
Strub, R. Bearing comprising polytetrafluoroethylene and phosphate glass, P (3) 69*c*.
Struchtrup, H. H. See Ohnemueller, W.
Struckmann, H. Spiraling brick arch construction for rotary kiln, P (2) 46*h*.
Structural Fibers, Inc. Method of making impregnated glass fiber articles [tanks], P (1) 12*d*.
Strumane, R. See Lierde, W. van.
Strunck, H. J. See Enders, A.
Strzala, K. A. Apparatus for detecting imperfections in glass containers, P (4) 99*c*. See Fry, W. L.
Stubbs, F. J. Symposium on nuclear ceramics: diffusion studies in dispersion-type fuels, (11) 307*j*.
Stubican, V., and Roy, R. Boron substitution in synthetic micas and clays, (7) 198*c*.
Stuchbery, A. L. Manufacture of hollow articles, P (8) 211*b*.
Stuckey, N. Cutting crystal glass with diamond, (6) 156*d*.
Studier, W. Quartz pressure sensors, (4) 104*j*.
Stuermer, C. M. Defects with tin glazes, (4) 103*g*.
Stull, D. R. See McDonald, R. A.
Stull, D. R., and Sinke, G. C. Thermodynamic properties of the elements, B (4) 122*j*.
Sturm, B. J. Method for preparation of sinterable beryllium oxide, P (11) 315*b*. Phase equilibria in the system chromium(II) fluoride–chromium(III) fluoride, (1) 28*j*.
Sturtevant Mill Co. Method and apparatus for sizing solid particles [centrifugally], P (9) 250*e*.
Stutterheim, N. Risk of unsoundness due to periclase in high-magnesia blast-furnace slags, B (5) 150*c*.
Styrikovich, M. A., and Khaibullin, I. Kh. Phase equilibrium diagrams of the systems NaCl–H_2O, Na_2SO_4–H_2O, $CaSO_4$–H_2O, and SiO_2 (quartz)–H_2O, (5) 144*i*.
Su, G.-J. See Borrelli, N. F.; Ghose, A. C.; McSwain, B. D.; Sanford, E. A.
Su, G.-J., Borrelli, N. F., and McSwain, B. D. Comparison of the experimental techniques employed in the measurement of infrared spectra of borate glasses, (3) 66*d*.
Su, G.-J., Borrelli, N. F., and Miller, A. R. Interpretation of the infrared spectra of silicate glasses, (3) 66*j*, B (11) 320*i*.

Subbarao, E. C. Ferroelectricity in mixed bismuth oxides with layer-type structure, (2) 48*b*. Polymorphism and dielectric properties of $Bi_2Ti_4O_{11}$, (1) 29*d*. See Hirayama, C.; Hrizo, J.; Tien, T. Y.

Subbarao, E. C., and Hrizo, J. Solid solutions based on ferroelectric $PbNb_2O_6$, (1) 30*a*.

Subrahmanyam, Y. See Ramana, Y. V.

Suchy, H. See Scholder, R.

Sucov, E. W. Diffusion of oxygen in vitreous silica, (3) 66*g*. Elastic stresses produced by indentation of plane surface of a semi-infinite elastic solid by an elastic spherical punch, (2) 39*e*. Phonon scattering and glass inhomogeneity, (5) 129*f*.

Sudo, T. See Ueda, S.

Sudo, T., Hayashi, H., and Shimoda, S. Mineralogical problems of intermediate clay minerals, B (5) 150*g*.

Sudoh, G. Reaction in the system $CaO–SiO_2$ gel–H_2O at 110°C and the products, (4) 119*i*. See Yoshii, T.

Sudoh, G., and Mori, H. Effects of mixing water content and alkalis on the hydration of tricalcium silicate, (7) 180*g*. Influence of KOH solution on the formation of tobermorite phase at room temperature, (4) 114*f*.

Suemoto, Y. See Mitsuishi, A.

Sueptitz, P. Distribution of impurities dissolved during growth from the melt of AgCl and AgBr single crystals, (3) 86*g*.

Suga, K. See Nakahara, M.

Sugano, S. Recent progress of crystal field theory, B (9) 259*f*. See Tsujikawa, I.

Sugarman, B. See Bowles, R.; Symmers, C.

Sugawara, A., and Yoshizawa, Y. Experimental investigation on the thermal conductivity of consolidated porous materials, (2) 44*g*.

Sugawara, Y. See Kuwata, T.

Sugden, J. A. Ferroelectric ceramic materials, P (4) 105*b*.

Sugihara, M. See Sato, T.

Sugiura, M. See Ishii, E.

Sugiura, T., Murakami, K., and Tanaka, H. Influence of gamma-ray irradiation on the electrical conductivity of glass, (8) 209*a*.

Sugiura, Y. See Nakamura, A.

Sugiyama, Y. See Fukuda, T.; Sekiya, M.

Suhr, N. H. See Joensuu, O. I.

Sukeji, K. Study on the powders of thorium and its oxide, (6) 175*b*.

Sukhanoa, O. N. See Grum-Grzhimailo, S. V.

Sulikowski, J. P. Influence of false setting on some properties of hardening cement paste and mortar, B (5) 149*c*.

Sullivan, D. F. Thermocouple, P (1) 24*b*.

Sullivan, J. D. Vitreous enamel-coated ferrous article and method of making it, P (10) 269*k*.

Sullivan, J. D., Nelson, D. H., and Nelson, F. W. Effect of moisture in furnace atmosphere on hydrogen defect in glass-coated steel, (1) 4*c*.

Sullivan, J. H. See Gaudin, A. M.

Sullivan, K. M. Reducing stack emissions from intermittent downdrafts (I), (6) 169*c*; (II) application of forced secondary air in hand-fired kilns, (6) 169*e*.

Sullivan, M. V. Process for electropolishing semiconductor surfaces, P (5) 137*c*.

Sullivan, R. M. See Ray, E. H.

Sullivan, R. M. E. See Rose, H. E.

Sullivan, W. F., and Coleman, J. R. Effect of sulfur trioxide on the anatase-rutile transformation, (7) 199*a*.

Sulzer Freres, S. A. Bearing comprising polytetrafluoroethylene and phosphate glass, P (3) 69*c*.

Summers, W. J. See Edgerly, C. R.

Sun, M.-S. Tridymite (low form) in some opal of New Mexico, (6) 170*d*.

Sunagawa, I. See Seager, A. F.; Tolansky, S.

Sunderman, J. A. See Droste, J. B.

Sunrod Mfg. Corp. Furnace lining, P (1) 16*b*.

Suris, J. P., Jr. See Long, R. S.

Sutcliffe, J. M. See Eeles, W. T.

Sutherland, F. R. Multilayer shell mold, P (6) 162*j*.

Sutherland, H. H., and MacEwan, D. M. C. Swelling chlorite mineral, B (5) 150*i*.

Sutherland, J. P. Spherical agglomeration, (1) 23*d*.

Sutherland, R. A. See Chapman, A. F.

Sutton, W. H. Development of composite structural materials for space vehicle applications, (4) 97*e*.

Suvorova, G. F. See Bozhenov, P. I.

Suzukawa, S. See Aoki, S.

Suzukawa, Y., and Sasaki, T. Influence of reducing atmosphere on the constitution of clinker, B (5) 148*b*. See Sasaki, T.

Suzuki, H. See Tsubota, H.

Suzuki, H., Kimura, S., Yamada, H., and Yamauchi, T. Studies on refractories of the system $Na_2O–Al_2O_3–ZrO_2$ (II) systems $Na_2ZrO_3–Al_2O_3$ and β-$Al_2O_3–ZrO_2$, (4) 121*c*.

Suzuki, K., Kaneko, K., Hiyama, S., and Nagai, S. Contraction of portland blast-furnace slag and slag-lime cements, (7) 179*b*.

Suzuki, K., and Tsujita, M. Function of components substituted for SiO_2 in an oxidizing atmosphere (I) influence of minute quantity of impurities on the transformation of dicalcium silicates, (1) 27*i*.

Suzuki, T. See Okuda, J.

Svec, J. J., et al. Properties—uses—current—future for electronic ceramic products, (11) 310*f*.

Svec, J. J., and Taylor, R. B. Hot extrusion—advancement toward automation, (9) 243*a*.

Sviridenkov, E. A. See Belikova, T. P.

Sviridova, R. K. See Grum-Grzhimailo, S. V.

Swain, A. B., Jr. See Rough, R. R.

Swalin, R. A. Thermodynamics of Solids, B (4) 124*e*.

Swallow, H. T. S. See Laird, R. T.

Swann, R. T. Composite thermal protection systems for manned reentry vehicles, (4) 97*a*.

Swanson, C. E. Method of producing crystal pattern and product, P (3) 70*i*. Multiple arc fluorescent lamp, P (7) 186*e*.

Swanson, N. See Richardson, W. O.

Swartz, J. C. Direct-on cover coat experiences, (2) 36*g*.

Swartz, P. C. Apparatus for applying a metallizing coating to ceramic parts, P (7) 193*h*.

Swed, J. P. Compaction process, P (8) 221*f*.

Swets, D. E. See Frank, R. C.

Swica, J. J. See Chung, D.-H.

Swift, H. R., and Best, E. F. Polishing compositions, P (6) 153*g*.

Swindler, R. L. Apparatus for pressing [curved] glass-plastic assemblies, P (9) 241*f*.

Swineford, A., and Franks, P. C. (editors). Clays and Clay Minerals—Proceedings of the Eighth National Conference, Norman, Oklahoma, October, 1959, B (3) 90*j*; Ninth National Conference, Lafayette, Indiana, October, 1960, B (5) 150*h*.

Swoboda, T. J. See Ingraham, J. N.

Sylvania Electric Products, Inc. Aperture fluorescent lamp, P (3) 68*c*. Coated lamp, P (10) 271*d*. Electrical insulating coating and method of producing it, P (8) 220*g*. Electroluminescent device, P (1) 20*j*, P (2) 48*e*, P (4) 105*j*. Fluorescent lamp, P (3) 77*d*, P (10) 271*h*. Helium-argon lamp, P (1) 11*e*. High power ferrite isolator having ferrite materials of differing Curie temperature, P (5) 136*e*. Method of accurately machining semiconductor bodies, P (10) 283*e*. Method of coating a fluorescent lamp tube [with amorphous silica and phosphor], P (10) 272*d*. Method for introducing iodine into a lamp envelope, P (3) 70*d*. Method of making halophosphate phosphors, P (9) 249*j*. Method for producing high density [stoichiometric] uranium oxide, P (10) 277*i*. Methods of coating fluorescent lamps, P (2) 42*g*. Nuclear fuel element assembly and method of fabricating it, P (8) 216*i*. Pneumatic abrasive cutting tool, P (1) 23*d*. Process for preparation of titanium activated barium pyrophosphate phosphor, P (3) 78*k*. Process of preparing luminescent grade dibasic calcium phosphate, P (4) 106*a*. Resistor, P (1) 21*g*. Thermal emissivity device, P (4) 108*c*. Tin-activated calcium silicate phosphor, P (3) 79*c*.

Syme, A. W. Symposium on control of the quality of glassware: What level of quality provides the best economic return, (9) 241*a*.

Symmers, C., Ward, J. B., and Sugarman, B. Studies of the mechanical strength of glass, (3) 68*f*.

Syntron Co. Dual eccentric weight vibratory generator for circular feeder, P (1) 23*g*.

Syska, Z. Increasing the green mechanical strength of porcelain bodies, (10) 278*e*.

Systems Research Laboratories, Inc. High temperature pressure sensitive solid state material [Al_2O_3 and Mo] and [transducer] device, P (11) 311*g*.

Szanto, V. See Sterk, E.

Szente, P. A. See Johnson, D. A.

Szepesi, K. Improvement of the rheological properties of alkaline earth bentonites, P (4) 110*i*.

Szklarz, E. G. See Pretzel, F. E.

Tabikh, A. A. X-ray fluoroscopic analysis, P (5) 140*b*.

Tada, T., Ishii, S., and Isomoto, M. Sillimanite brick used for slag chamber and checker chamber, (11) 306*g*.

Tagai, H. See Sato, S.

T'ai, S., Yasins'kaya, G. A., and Samsonov, G. V. Interaction of chromium boride with molybdenum, (10) 294*b*.

Tait, H. James Rogers—a leading porcelain painter at Worcester ca. 1755–65, (6) 153*j*.

Tajima, Y. See Hijikata, K.

Takabayashi, M. Epitaxial vapor growth of single crystal Ge, (4) 113*i*.

Takada, T. See Goto, Y.; Watanabe, T.

Takagi, R. Growth of oxide whiskers on metals at high temperature, (6) 173*f*.

Takagi, S. See Yamaguchi, G.

Takahashi, H. See Takemoto, K.

Takahashi, K. See Kunugi, M.

Takakusa, Y. See Miyakawa, T.

Takamori, T. Effects of thermomechanical history on properties of glasses, (10) 270*g*.

Takano, Y. X-ray study of autunite, (5) 148*a*.

Takashima, H. See Kato, E.

Takashima, S. See Sato, S.

Takashima, S., and Kato, M. Preparation of standard sample of alite, (7) 181*f*.

Takemoto, K. See Yamaguchi, G.

Takemoto, K., and Saiki, Y. Infrared absorption spectra of calcium sulfate dihydrate, hemihydrate, and soluble and insoluble anhydrites, (2) 34*j*.

Takemoto, K., Takahashi, H., Shoji, T., and Makino, H. Effect of sodium and magnesium oxides on the strength of cement, (7) 179*h*.

Takeuchi, Y. See Sadanaga, R.

Talbot, J. H., Bradley, A. A., and Kempis, E. B. Disturbed layer on ground quartz powders of respirable size, (10) 292*b*.

Tama, M., and Shearman, W. E. Furnace, P (8) 224*g*.

Tanabe, I., Okuda, K., and Honda, T. Production of chromium boride by thermite process, (9) 243*i*.

Tanaka, H. See Hayami, R.; Kobayashi, T.; Murakami, K.; Sugiura, T.; Tanigawa, H.

Tanaka, S., and Tanaka, T. Effects of deutron bombardment on CdS single crystals, (6) 173*a*.

Tanaka, T. See Tanaka, S.

Tanenbaum, M. Ferrimagnetic crystals, P (8) 220*i*. See Spitzer, W. G.

Tangerman, E. J. Who selects materials, (3) 90*k*.

Tanigawa, H., Ogura, T., and Tanaka, H. Ceramic coatings (II) frit of system $SiO_2–BaO–TiO_2–Cr_2O_3$, (10) 268*j*.

Taniguchi, M. See Kubo, T.

Tanisaki, S. Crystal structure of monoclinic tungsten trioxide at room temperature, (6) 172*g*.

Tanner, J. T., and Kenan, W. M. Use of fly ash as a pozzolan in dense and lightweight concrete, (4) 96*d*.

Tanzilli, R. Development of a stable "white" coating system, (8) 207*b*.

Taplin, J. H. Temperature coefficient of the rate of hydration of β-dicalcium silicate, B (5) 149*e*.

Taramasso, M., and Guerra, A. Microsyringe for gas chromatography, P (11) 320*b*.

Tarbes, P. Ceramic oxide bases for cadmium sulfide photoresistance cells, P (3) 77*c*.

Tardos, M. See Sterk, E.

Tarjan, I. Hungarian work on crystal growth, B (9) 262*a*.

Tarney, J. See Drysdale, D. J.

Tarpley, W. B. See McKinney, C. D., Jr.

Tarpley, W. B., and Kartluke, H. Application of ultrasonic vibration to cold pressing of ceramic pellets, (8) 221*d*.

Tarpley, W. B., Yocom, K. H., and Pheasant, R. Ultrasonic extrusion—reduction in vehicle and plasticizer requirements for nonclay ceramics, (8) 221*i*.

Tashiro, M. See Soga, N.

Tashiro, M., and Maki, T. Studies on the thermal shock resisting ceramics of the $Li_2O–Al_2O_3–SiO_2$ system (I) effects of addition of lithia containing glass on the properties of lithia ceramics, (8) 209*g*.

Tashiro, M., and Wada, M. Glass-ceramics catalyzed with zirconia, B (11) 320*g*.

Tatarinova, L. See Vitkovskii, B.

Tatevskii, V. M., Koptev, G. S., and Mal'tsev, A. A. Vibrational spectra of the B_2O_3 and B_2S_3 molecules, (5) 147*a*.

Tatnall, R. F. Automatic pugging in America, (10) 273*d*.

Tattersall, H. G. See Clarke, F. J. P.

Taubner, F. R. See Homer, H. H.

Tauch, E. J. Process for preparing aqueous silicate solutions, P (9) 254*f*.

Taylor, B. W., Poli, A. A., Jr. Apparatus for gas analysis, P (10) 286*i*.

Taylor, H. D. Microscopy technique for alumina ceramics, (4) 101*e*.

Taylor, H. F. W. Dehydration of hemimorphite, (8) 227*e*. Hydrothermal reactions in the system $CaO–SiO_2–H_2O$ and the steam curing of cement and cement-silica products, B (5) 149*c*. See Aitken, A.; Percival, A.

Taylor, K. M. Methods for making boron nitride materials, P (2) 46*c*.

Taylor, R. B. See Svec, J. J.

Taylor, R. E., and Nakata, M. M. Study of thermal properties of refractories, (8) 215*b*.

Taylor, R. L. See Haring, H. E.

Taylor, R. W. Liquidus temperatures in the system $FeO–Fe_2O_3–TiO_2$, (8) 228*c*.

Taylor, S. A. See Janes, M.

Taylor, Smith & Taylor Co. Ware turning and handling machine, P (5) 134*b*.

Tazawa, M. See Miyazawa, K.

Tcheichvili, L., and Weyl, W. A. Synthesis of ceramic pigments in the light of modern high-temperature crystal chemistry (I); (II) rate phenomena in high-temperature crystal chemistry; (III) classification of inorganic chromophors; (IV), Conclusion, (9) 238*g*.

Teasel, R. C., and Buckley, E. D. Apparatus for measuring elevated temperatures, P (10) 286*j*.

Teater, T. C. See McGrain, P.

Tebar, D. G. See Gaspar Tebar, D.

Technical Association of Refractories (Japan). Tentative plan for standardization of the shape and dimensions of sleeve brick, (11) 308*h*.

Technicon Instruments Corp. Chromatography analysis apparatus and method, P (10) 287*c*. Concentration apparatus for quantitative analysis of a substance in a liquid, P (10) 287*c*. Flow cells, P (7) 196*d*. Fluid processing system with continuous filter apparatus, P (10) 287*a*.

Tefft, W. E. See Wachtman, J. B., Jr.

Teja, J. D. Aqueous dispersions of high molecular weight fibrils of amorphous silicates, P (4) 104*e*.

Telefunken G.m.b.H. Butt joint for unweldable vibratory bodies, P (10) 282*c*. Metal-to-ceramic joint and method of forming, P (2) 38*g*.

Telfer, A. L. Improving fire travel in a Hoffmann, (1) 24*h*.

Temkin, D. E. See Lyubov, B. Ya.

Ten Eyck, R. R. Piezoelectric electromechanical transducer, P (9) 249*d*.

Tenisheva, T. F. See Lazarev, A. N.

Terada, K., Shimizu, S., Kakimoto, K., and Nanba, J. Fundamental studies on lime shaft kilns (III) resistance to flow of gas through preheating zone, (8) 205*e*.

Terada, S. See Fundabashi, W.

Terada, S., Ito, Y., Katto, S., Matsuno, Y., and Yamada, H. Vitrified grinding wheels prepared by using bonds composed of Aotsuchi, feldspar, and Toseki, (9) 236*b*.
Terai, R. See Izumitani, T.
Teranishi, T. See Ohnishi, H.
Teraoka, I., and Kano, J. Mechanism of the hydration of gypsum plaster (III), (10) 267*e*.
Terman, V. B. See Solinov, F. G.
Ternisien, J. A. Refractory bodies suitable as combustion catalysts, P (3) 74*f*.
Terraza, J., and Aparicio-Arroyo, E. Technical application of soft porcelains, B (4) 124*g*.
Terrier, P. Liding of rotary kilns, (1) 24*i*.
Tervakoski Osakeyhtio. Impregnated paper to serve as a dielectric, especially in condensers to improve their critical performance, P (9) 249*c*.
Tettenhorst, R. Cation migration in montmorillonites, (7) 198*f*. Clay-organic complexes, (8) 225*c*.
Tettenhorst, R., Beck, C. W., and Brunton, G. Montmorillonite-polyalcohol complexes, B (5) 150*j*.
Texaco, Inc. Method of forming gastight seal between vessel wall and refractory lining of a synthesis gas generator, P (1) 16*i*.
Texas Instruments, Inc. Apparatus for making semiconductor units, P (6) 165*e*. Compensated gravity measuring device, P (5) 139*d*. Indium antimonide transistor, P (11) 311*h*. Masking and fabrication technique [for semiconductor device], P (8) 220*a*. Materials for and methods of manufacturing semiconductor devices, P (5) 136*a*. Method [crystal growth] for fabricating transistors having desired current-transfer ratios, P (3) 78*b*. Method of making ceramic-to-metal composite stock, P (8) 208*c*. Method of making degeneratively doped group III-V compound semiconductor material, P (9) 249*i*. Method of producing gallium or aluminum arsenides and phosphides, P (10) 283*b*. Method for recovery and reuse of quartz containers [for melting Si], P (9) 244*i*. Semiconductor structure fabrication, P (5) 137*b*. Solar cell, P (6) 166*f*. Strain gage [fused quartz], P (10) 287*f*.
Thackray, R. W. See Barnes, E.
Thaden, H. V. Apparatus for forming products from resin-impregnated long [glass] fiber filaments, P (8) 210*f*.
Thamerus, G. See Weiss, A.
Thatcher, J. W. See Brown, J. D.
Thayer, A. G. See Carson, F. J.
Theberge, C. L. See Gibbs, T. W.
Thermal Mfg. Co. Method of making electrically insulated heating units, P (1) 18*h*.
Thermway Industries, Inc. Curtain wall, P (2) 37*j*.
Thiel, H. See Moehling, W.
Thiele Kaolin Co. Fractured clay, P (2) 55*h*.
Thielfoldt, H. W. Method of blow molding hollow articles, P (8) 211*e*.
Thielke, N. R. See Sarakauskas, R. V.
Thiess, G. H. Wrenn, J., and Drefke, O. Ferromagnetic resonance-tuned microwave oscillator, (10) 280*a*.
Thilo, E. See Krueger, G.
Thoma, R. E. Cation size effects in complex fluoride compound formation, (1) 26*g*.
Thoma, R. E., Insley, H., Herbert, G. M., Friedman, H. A., and Weaver, C. F. Phase equilibria in the system NaF–ThF_4–UF_4, (3) 88*d*.
Thomas, A. G. See Davies, W. J. K.; Mayo, G. J. J.
Thomas, D. G. See Collins, R. J.; Krusemeyer, H. J.
Thomas, D. W. Preparation and application of engobes to brick, (6) 159*c*.
Thomas, G. See Elkington, W. E.
Thomas, G. L. See Duncan, J. E.; Jonas, E. C.
Thomas, G. W. See Krebs, R. D.
Thomas, J. K., III. See Korach, M.
Thomas, L. D. Electrically conducting films on glass, P (6) 157*i*. Electrically conducting glasses for aircraft windshields, P (6) 157*j*.
Thomas, W. Reply to Discussion of "Investigation of the factors likely to affect the strength and properties of glass fibers," (2) 38*i*.
Thomasson, C. V. See Wilburn, F. W.
Thome, P. Methods and devices for performing spectrum analysis, in particular in the far ultraviolet region, P (1) 31*d*.
Thompson, A. See Fairbrother, F.
Thompson, C. L. See King, D. F.
Thompson, J. J. Forming thin ceramics, (10) 284*g*.
Thompson, M. E. See Chave, K. E.; Garrels, R. M.
Thompson, N. Symposium on control of the quality of glassware: Scheme for the selection and training of sorters, (9) 241*j*.
Thompson, W. D. See Keim, G. I.
Thompson, W. R. Reducing thermal upsets in fluid measuring cells, P (10) 287*e*.
Thormann, P. Experiences with differential thermal analysis and expansion/contraction apparatus, (4) 113*j*. See Lehmann, H.
Thorn Electrical Industries, Ltd. Electric lamps embodying reflectors, P (4) 99*d*. Electroluminescent lamps, P (1) 21*a*.
Thornhill, F. S., and Chisholm, R. S. Preparation of siliceous pigment, P (8) 225*i*.
Thornton, W. A., Jr. Electroluminescent phosphor, method of improving electroluminescent phosphor and electroluminescent lamp, P (5) 135*i*. Method of improving electroluminescent phosphor, P (7) 193*i*. Method for improving electroluminescent phosphor and electroluminescent lamp, P (7) 193*g*.
Thorp, J. Pharmaceutical glass from the consumer's viewpoint, (1) 8*g*.
Thorpe, C., and Shaw, F. Effect of small additions of sodium sulfate on the refining of glass, (3) 66*j*.
Thorpe, T. See Best, P.
Thorvaldson, T., Birss, F. W., and McCurdy, K. G. Calcium exchange in systems of $xCaO{\cdot}SiO_2{\cdot}yH_2O$–$Ca(OH)_2$–$H_2O$, B (5) 149*g*.
Thuemmler, F. Less-known uranium compounds as possible nuclear fuels, (10) 275*a*.
Thurber, E. A. See Godfrey, J.
Thurnauer, H. Ceramic insulation—state of art review, (3) 76*b*. See Tierney, H. J.
Thwaites, G. A. See Hansen, R. C.
Thwaites, I. See Bennett, H.
Thyssen-Huette, August, Akt.-Ges. See August Thyssen-Huette Akt.-Ges.
Tichane, R. M. Cleaning processes for borosilicate glass, (9) 239*g*.
Ticino, J. Machine for grinding and polishing facets of precious stones, P (5) 125*g*.
Tiede, R. L. Apparatus for measuring the viscosity of glass at high temperatures, P (2) 41*f*. Composite fibers, P (5) 130*g*. Glass composition, P (7) 186*b*. Treatment for glass bodies in filament forming operation, P (1) 12*f*.
Tien, T. Y., and Carlson, W. G. Effect of additives on properties of lead titanate, (2) 47*i*. Influence of oxygen partial pressure on properties of semiconducting barium titanate, (8) 219*j*.
Tien, T. Y., and Subbarao, E. C. Grain growth in $Ca_{0.15}Zr_{0.85}O_{1.85}$, (11) 317*d*.
Tien, T. Y., Subbarao, E. C., and Hrizo, J. Ferroelectric phase transitions in the system PbTiO$_3$–KNbO$_3$, (2) 47*j*.
Tierney, H. J., and Thurnauer, H. Ultrathin glass sheet, P (9) 242*h*.
Tierney, P. A. Ceramic potting composition and method of encapsulating an electrical article therewith, P (6) 165*j*. See Sattler, F. A.
Tigerschiold, B. M. Process for producing hot tops, P (6) 162*h*.
T. I. (Group Services), Ltd. Process for the continuous production of thin elongated single crystals of zinc oxide and antimony trioxide, P (10) 285*c*.
Tik-Ien, A. T. See Schwiete, H. E.
Tikkanen, M. H. Aspects of the use of metallic materials in the glass industry, (1) 5*j*.
Tikkanen, M. H., Rosell, B. O., and Wiberg, O. Hydrogen reduction of solid NiO–CoO–MgO solutions, (10) 293*h*. Influence of magnesium oxide on the reduction of cobalt and nickel oxides, (10) 294*g*.
Tile Council of America. Apparatus and method for making tile panels, P (4) 104*d*.
Tiller, K. G. See Hodgson, J. F.
Tiller, K. G., and Hodgson, J. F. Specific sorption of cobalt and zinc by layer silicates, B (5) 150*h*.
Timashev, V. V. See Butt, Yu. M.
Timashov, V. V. See Yung, V. N.
Timmermans, O. E. B. South African ceramic industries, (8) 230*h*.
Ting-chaun, C. China's famous pottery ware, (9) 236*f*.
Tinguist, S. C. See Benson, C. L.
Tinius Olsen Testing Machine Co. Materials testing equipment, P (5) 139*g*.
Tinker, C. D. Kiln, P (9) 253*d*. Kilns, P (9) 253*e*.
Tischer, R. E., and Drickamer, H. G. Use of pressure to investigate local symmetry and compressibility in glass, (9) 241*b*.
Tissen, D. S. See Pokrovskii, N. L.
Titaan, N. V. Barium titanate monocrystals, P (2) 55*d*.
Titangesellschaft m.b.H. Frit for opaque white ceramic glazes, P (4) 104*b*.
Titkov, Yu. B. See Samsonov, G. V.
Titova, A. G. Monocrystals of yttrium ferrite with the garnet structure, B (9) 263*e*.
Tobey, H. M. See Montgomery, R. S.
Tobi, A. C. Recognition of plagioclase twins in sections normal to the composition plane, (4) 120*a*.
Toguri, J. M. See Grjotheim, K.
Tolansky, S., and Sunagawa, I. Interferometric studies on synthetic diamonds, (3) 87*b*. Some growth characteristics of synthetic diamonds—a distinction between natural and synthetic diamond, (3) 88*j*.
Toledo, F. A. de. See Alvarez de Toledo, F.
Tolmie, R. See O'Riley, L.
Tolstoi, M. N. See Feofilov, P. P.
Tolstoi, N. A., and Shun-Fu, L. Luminescence kinetics of chromium luminophors (I) gallium oxide—methods; temperature and concentration dependence of luminescence spectra; (II) gallium oxide—relaxation spectra and reabsorption; (IV) ruby—interpretation of the relaxation spectrum; temperature variation of the relaxation time and the intensity of the luminescence, (6) 164*e*. Relaxation luminescence spectra of uranium activated alkali and alkaline earth metal fluorides, (6) 165*g*.
Tolstoi, N. A., Shun-Fu, L., and Lapidus, M. E. Luminescence kinetics of chromium luminophors (III) ruby, (6) 164*h*.
Tolub, T. P. See Bobovich, Ya. S.
Tomanek, V. New criteria for evaluation of refractory clays and schistous clays, B (10) 300*j*. Recent knowledge of the properties of some refractory schistose clays and clays of central Europe, (4) 110*e*. Refractory Schistous Clays and the Technology of Their Processing, 2d ed. B (8) 234*i*. Test for the homogeneity of refractory clays and other ceramic testing methods, (10) 286*d*.
Tomco, S. See Cernoch, S.
Tominaga, A., Yatsuzuka, T., and Shono, S. Measurement of the wear of blast-furnace brickwork with the radioactive isotope (I), (6) 159*j*.
Tomita, T. Crystal structure of silicon carbide of 174 layers, (6) 172*i*.
Tomlinson, L. See Morrow, S. A.
Tomlinson, L., Morrow, S. A., and Graves, S. Kinetics of the hydrofluorination of uranium dioxide, (10) 294*d*.
Tompkins, E. H. Method of applying an oxide coating onto a nonporous refractory substrate, P (7) 183*i*.
Tompkins, F. C. See Damm, J. Z.; Lamb, E. F.
Tonjes, B. D. See Cline, R. A.
Tonkin, R. J. See Windle, W.
Tooker, E. W. Clay minerals in rocks of the lower part of the Oquirrh formation, Utah, B (5) 150*g*.
Tooley, F. V., Hopkins, R. W., and Hamilton, R. Gypsum in glass, (7) 184*f*.
Toop, G. W., and Samis, C. S. Some new ionic concepts of silicate slags, (10) 297*a*.
Topol, L. E., and Landis, A. L. Cadmium–cadmium halide systems, (2) 56*e*.
Torbin, M. A. See Morrow, A. S.
Torkar, K. See Krischner, H.
Torkar, K., and Fredriksen, O. Effect of grain size on saturation magnetization of barium ferrite powders, (1) 19*e*.
Torkar, K., Lasser, K., and Fritzer, H. P. Method of combining dynamic differential calorimetry with simultaneous calibration and thermogravimetry, (8) 228*f*.
Tornati, M. See Calvi, M. C.
Torok, J. J. Plunger for forming glass articles, P (2) 42*j*; P (6) 158*a*.
Toronto Brick Co., Ltd. Pallet for brick cubes and means for handling it, P (8) 212*a*.
Toropov, N. A. Solid solutions of the minerals of portland cement clinkers, B (5) 148*j*. See Grebenshchikov, R. G.
Toropov, N. A., Bondar, I. A., and Galakhov, F. Ya. High-temperature solid solutions of silicates of the rare-earth elements, B (10) 300*g*.
Toropov, N. A., and Fedorov, N. F. Binding properties of the different modifications of dicalcium silicate, (7) 178*h*.
Totti, A. Italian ceramists (XIII) Bruno Capacci, (3) 63*j*.
Tottle, C. R. Thermal cycling of graphite, B (8) 234*c*.
Toullet, F. See Collet, A.
Toulmin, H. A., Jr. Apparatus for making metallized porous refractory material, P (5) 133*a*. Method and apparatus for gas plating of metal on glass fibers, P (10) 272*i*. Method and apparatus for generating electrical power from solar energy, P (4) 108*h*.
Tove, P. A. Method and device for pulverizing and/or decomposing solid materials, P (4) 110*f*.
Towe, K. M. Electronoscopic studies of acid-treated kaolinite, (7) 199*c*.
Townsend, P. D. See Mitchell, E. W. J.
Toyoda, I., and Nameshi, N. Effect of size of coarse magnesia grains in basic open-hearth furnace roof brick, (11) 305*j*.
Toyozawa, Y. Self-trapping and drift motion of an electron, B (9) 260*a*.
Tozydlo, A. J. See Reuter, R.
Tracht, J. H. Catalyst coated thermocouple elements, P (4) 108*f*. Chromatographic method and apparatus, P (1) 31*a*.
Tracy, B. B. English pottery in the collection of the Newark Museum, (3) 63*j*.
Tragert, W. E., and Gatti, A. Sintered aluminum composition, P (6) 162*i*.
Traite, M. See Welkowitz, W.
Trap, H. J. L. Glass for dielectric uses, P (5) 130*i*.
Trap, H. J. L., and Stevels, J. M. New types of glasses showing electronic conductivity, B (11) 321*a*.
Trauffer, W. E. Cement, (7) 178*e*. High-feldspar-iron sand being processed for glass wool manufacture, (9) 254*b*. Lone Star builds new plant beside old operation at Norfolk, (2) 35*c*. Penn-Dixie's Georgia plant expansion, (2) 35*j*.
Trauffer, W. E., and Lindsay G. C. Florida's new 200-tpd lime plant, (10) 288*e*.
Traustel, S. See Lehmann, H.
Traustel, S., Panda, J., and Jacob, P. Application of the electrical analogy to the investigation of the thermal conductivity of mixtures of components with different conductivities, (4) 112*e*.
Trawinski, H. F. Elutriation of kaolin in centrifugal classifiers, (10) 288*c*.
Tredgold, R. H. See Branwood, A.
Treffner, W. S., and Williams, R. M. Heat evolution tests with calcium aluminate binders and castables, (10) 274*j*.
Trehan, Y. N. Reduction of copper oxides by molecular hydrogen, (4) 120*b*.
Trementozzi, F. J. See Ormsby, R. G.
Tress, H. J. Ruby and related glasses from the standpoint of the chemical potential of oxygen in glass (I) chemical potential of oxygen in glass, (2) 40*j*; correction, (4) 98*j*; (II) gold and copper glasses, (3) 67*i*; (III) cadmium sulfoselenide glass, (3) 67*j*.
Tret'yachenko, G. N., and Kravchuk, L. V. Method of determining the thermophysical constants of materials at high temperatures, (8) 223*j*.
Trifileman, B. H. Method of manufacture of homogeneous compositions, P (4) 102*g*.
Trifonov, I. A. Mechanism of the high-temperature phase transition in barium titanate, B (9) 262*f*.
Trinkler, M. F. See Plyavin, I. K.
Trionics Corp. Micromolecular resistor, P (2) 50*c*.
Troelstra, S. A. Method of producing a stable coagel of an alkaline earth fluoride, P (1) 26*d*.
Trombe, F., and Foex, M. Calcium zirconate refractories, P (3) 73*i*. Treatment of zircon after fusion by means of concentrated solar rays, P (3) 75*c*.

Trostel, L. J., Jr. Strength and structure of refractories as a function of pore content, (1) 15*a*.
Trubey, P. W., and Bruce, I. B. Recovery of magnesium compounds from ores, P (8) 226*c*.
Trudeau, U. P. See Colchagoff, R. D.
Truesdell, A. H. See Garrels, R. M.
Truitt, J. See Evans, R. B., III.
Trupiano, R., and Zanon, D. Process for preparation of artificial cryolite, P (1) 26*b*.
Tscheischwili, L. See Tcheichvili, L.
Tschudi, W. J., and Madera, J. Molybdenum disulfide treating process, P (11) 315*d*.
Tseitlin, L. A., and Eitysheva, A. A. High alumina ramming nonshrinking bodies, (1) 13*f*.
Tsepkov, L. P., and Bartenev, G. M. Determination of the elasticity constant of glass by means of resistance strain gages, (9) 239*f*.
Tsilosani, Z. N. Physicochemical interaction of the medium with hardened cement block, structural mortars, and concretes, (1) 2*i*.
Tsubota, H., Suzuki, H., and Hirakawa, K. Mechanism of electrical conduction in CdSe, (4) 116*j*.
Tsuchiya, M. See Yamamoto, K.
Tsuji, Y. Sorption of water vapor on glass surface in vacuum apparatus, (8) 209*d*.
Tsujikawa, I., and Sugano, S. Anomalous *g* shifts of excited states of Cr^{3+} in ruby, (6) 171*h*.
Tsujita, M. See Suzuki, K.
Tsuranova, I. S. See Avgustinik, A. I.
Tsvetkova, N. A. Coloring glass, P (2) 42*a*.
Tszyan, D. K. See Poluboyarinov, D. N.
Tucker, P. A. See Eichelberger, J. F.
Tuite, G., Rawson, H., and Heynes, M. S. R. Symposium on nuclear ceramics: High-melting point glasses containing U oxide, (11) 308*f*.
Tumanov, N. S. New machines for the porcelain-earthenware industry, (1) 18*a*.
Tummers, L. J. Method of producing semiconductive devices, more particularly transistors, P (5) 136*g*.
Tunell, G. See Dickson, F. W.
Turbett, P. E. Effect of moisture on modulus of rupture of some typical ball clays, (2) 54*f*.
Turek, M. Lithium ceramics—ceramic bodies with negative heat expansion, (4) 101*j*.
Turkdogan, E. T. See Chessin, H.
Turnbull, W. G. See Schimitschek, E. J.
Turner, A. F. Reflectance properties of thin films and multilayers, B (3) 93*b*.
Turner, D. R. See Sauer, H. A.
Turner, D. W. See Ranby, P. W.
Turner, I. L. See Miller, J. L., Jr.
Turner, R. Synthetic charge for material reduction mills, P (2) 51*h*.
Turner, R. C., and Brydon, J. E. Formation of double hydroxides and the titration of clays, (10) 293*a*.
Turner, W. E. S. Notable British seventeenth-century contribution to the literature of glass-making, (7) 185*a*. Precision attainable in the chemical analysis of ancient glasses, B (11) 321*h*. Tercentenary of Neri-Merrett's *The Art of Glass*, B (11) 321*c*.
Turner, W. E. S., and Rooksby, H. P. Study of the opalizing agents in ancient glasses throughout 3400 years (II) (abstract), B (11) 321*e*.
Turner Mfg. Co. Protective backing for mirrors, P (4) 100*c*.
Turriziani, R., and Rio, A. High chemical resistance pozzolanic cements, B (5) 150*d*.
Tuttle, O. F. See Wyllie, P. J.
Tuzhilkin, I. M. See Kalliga, G. P
Twigg, E. Work study and management, (7) 202*b*.
Tydings, J. E. See Giardini, A. A.
Tyler, W. S., Co. Pedestal supports for vibrating screening equipment, P (7) 195*b*.
Tyner, R. E. See Moreland, S. T.
Tyrrell, J. L. See Watson, D. L.
Tyrrell, M. E. Experimental production of light-weight basic refractories, (1) 13*i*.
Tyrrell, M. E., and Farrior, G. M. Cemented tungsten carbide with titanium diboride additions, (8) 212*i*.
Tyurin, V. V. See Morozov, V. N.

Uchida, H. See Shimula, Y.
Uchida, I. Impedance changes induced by photoconductive effect in ZnS:Cu, Cl phosphors, (1) 19*h*.
Uchida, S. See Ota, E.
Uchikawa, H. See Yamaguchi, G.
Uchikawa, H., and Inomata, Y. Fluorescent X-ray spectrometric determination of the six major components in portland cement, (9) 236*h*.
Udy, M. J. Sealer-cooler structure for furnace electrodes, P (2) 46*h*.
Ueda, S., and Sudo, T. Artificial crystallization of volcanic glass to carnegieite, nepheline, and albite at room pressure, (11) 315*j*.
Uei, I. See Okuda, S.
Ueltz, H. F. G. Abrasive grain, P (6) 153*f*.
Ueno, T. Glass fiber treatment (II) making of silica fiber from sodium silicate glass, (10) 270*b*.
Ueno, T., and Urano, N. Glass fiber treatment (III) transformation of porous glass fiber by heat treatment; (IV) rate of solution of glass fiber in hydrochloric acid; (VI) adsorption of water vapor on porous glass fiber; (VII) solution of glass fiber in acid, (10) 270*d*.
Uetsuki, T. See Mori, Y.
Uglanova, V. V. See Aleksandrov, B. S.; Naboikin, Yu. V.
Uguccini, O. W. See Rozsa, J. T.
Uhlig, A. F. See Fry, W. L.
Umberger, J. Q., and Wahlig, C. F. Treatment of zinc sulfide phosphors, P (3) 79*a*.
Umblia, E. Safety glass for cars and airplanes, (7) 185*j*.
Umeya, K. See Nagasaki, S.
Uncles, R. See Mattock, G.
Underwood, D. T., Jr. See McKinley, A. H.
Underwood, G. W. Use of glass in high-speed aircraft, (1) 10*f*.
Ungemach, O. See Weissenberg, G.
Union Carbide Corp. Aluminum-resistant refractory material, P (3) 73*g*. Apparatus for making metallized porous refractory material, P (5) 133*a*. Apparatus for the oxidation of metal powders, P (8) 221*e*. Blending apparatus for particulate materials, P (3) 80*a*. Coated graphite bodies, P (8) 215*h*. Crystalline zeolite S, P (2) 55*f*. Electrode joint, P (1) 16*a*. Electrodes for melting refractory metals, P (2) 45*f*. Ferrimagnetic spinel bodies, P (10) 282*f*. Fire tube furnace and method for baking [carbon] articles, P (1) 16*b*. Flexible high temperature thermoelectric device, P (3) 81*d*. Flotation procedures, P (10) 289*h*. Foamed silicon carbide, P (11) 308*a*. Free-peeling submerged arc welding composition, P (4) 102*g*. Furnace lining brick, P (7) 189*b*. Glass fiber composition, P (7) 186*c*. High temperature coatings, P (9) 239*a*. High temperature differential thermal analyzer, P (8) 224*a*. Magnetic flux-gas shielded metal arc welding, P (10) 269*d*. Metal arc welding, composition, and process, P (1) 5*c*. Method and apparatus for gas plating of metal on glass fibers, P (10) 272*i*. Method and apparatus for growing crystals, P (1) 16*h*. Method and apparatus for thermally working minerals and mineral-like materials, P (9) 254*a*. Method of making foamed silicon nitride, P (8) 216*c*. Method of makirg synthetic unicrystalline bodies, P (6) 167*e*. Multilayer shell mold, P (6) 162*j*. Oxidation-resistant graphite article and method, P (3) 74*i*. Preparation of ammonium metavanadate, P (3) 84*g*. Preparation of high purity vanadium pentoxide from oxidic vanadium materials, P (8) 225*h*. Preparation of refractory sulfides, P (8) 216*i*. Pressure-differential type apparatus useful in density and volume measurement [of solids], P (8) 224*a*. Process for coating carbonaceous articles with silicon dioxide, P (10) 277*d*. Process of flame spraying a tungsten carbide-chromium carbide-nickel coating and article produced thereby, P (4) 103*d*. Process for making crystalline zeolite K-G, P (3) 84*j*. Process for the manufacture of cement, P (5) 127*a*. Process for producing fluoride-free columbium [niobium] or tantalum pentoxide, P (5) 141*a*. Process for producing molecular sieves, P (11) 315*e*. Process for producing molybdenum disilicide, P (2) 46*a*. Process for the production of large semiconductor crystals, P (3) 78*i*. Process of separating tantalum and columbium values, P (3) 89*j*. Production of hafnium-free zirconium compounds, P (2) 55*h*. Production of low sulfate uranium oxide, P (11) 315*e*. Reactivation of molecular [zeolitic] sieves, P (4) 104*d*. Reducing thermal upsets in fluid measuring cells, P (10) 287*e*. Slag-lined furnace tapping pots, P (3) 75*b*. Submerged-melt arc welding composition and process, P (5) 128*c*. Submerged-melt welding and composition therefor, P (11) 303*d*. Submerged melt welding process and composition, P (6) 155*i*. Synthetic crystalline zeolites, P (6) 171*e*. Thermoelectric materials, P (5) 137*g*. Vapor fraction analysis, P (4) 121*j*. Viscosimeter, P (1) 24*d*. Wave ring thermocouple, P (11) 314*a*.
Union des Verreries Mecaniques Belges, Soc. Anon. Process and apparatus for obtaining electrically conductive coatings on the surface of objects consisting of glass or ceramic materials, P (8) 211*i*.
United Aircraft Corp. Solid differential expansion temperature sensor, P (3) 81*f*. Thermocouple, P (1) 24*b*.
United Carbon Co., Inc. Multiple unitizer, P (5) 138*c*.
United Insulator Co., Ltd. Electromechanical transducers, P (2) 48*g*.
United Kingdom Atomic Energy Authority. Coherent boron powder bodies, P (2) 45*c*. Graphite moderator structures for nuclear reactors, P (8) 216*f*. Method for preparing granular gels, P (2) 55*a*. Sintering long ceramic compacts in a movable, short furnace, P (2) 51*g*.
United Kingdom of Great Britain and Northern Ireland, Minister of Aviation in Her Majesty's Government. Method of making carbon articles, P (8) 216*a*.
United States of America, Secretary of the Air Force. Crucible and refractory material therefor, P (1) 15*j*. Electrical capacitor having a silicon nitride dielectric, P (10) 282*e*. Electron processing of semiconducting material, P (7) 193*a*. Method of making jet turbine buckets, P (4) 97*k*. Microwave acoustic delay line, P (4) 105*i*. Printed circuit on a ceramic base and method of making it, P (6) 166*b*. Process for making cadmium sulfide photoconducting articles, P (3) 78*g*. Silicon-boron-oxygen refractory material, P (10) 277*j*.
United States of America, Secretary of the Army. Abrasive drilling apparatus, P (5) 138*f*. Apparatus for pulling single crystals in the form of long flat strips from a melt [by the crucible method], P (10) 284*j*. Ceramic materials and method for making them, P (7) 193*i*. Heat sinks for [quartz] crystal oscillators, P (4) 105*e*. Means for reducing thermal gradients in the hot-pressing of synthetic mica, P (11) 313*i*. Method of delaminating cemented glass optics or lenses, P (1) 12*c*. Method of forming a stable aluminum plated quartz resonator, P (1) 21*f*. Method of making ferromagnetic barium ferrites, P (1) 21*h*. Method of making a gallium sulfide dioxide, P (4) 105*h*. Method of making lamellar sheets of fluorphlogopite mica, P (11) 315*h*. Method of making magnetic ferrite films, P (10) 283*g*. Pressure and temperature sensing device for high pressure apparatus, P (4) 108*a*. Process of making mixed oxide films, P (3) 65*f*. Process for producing single crystal silicon surface layers, P (10) 283*d*. Radiation compensating thermoelectric device, P (1) 24*e*. Surface-barrier photocells, P (1) 21*j*. Temperature responsive resistance control elements, P (8) 224*c*.
United States of America, Secretary of Commerce. Dual-wedge high-pressure apparatus, P (11) 312*g*. Glassblower's safety manostat and system, P (1) 11*c*. High-pressure optical cell, P (6) 168*h*. Method for the growth of preferentially oriented single crystals of metals, P (2) 60*a*. Multiple-anvil high pressure apparatus, P (8) 222*e*.
United States of America, Secretary of the Interior. Flotation process for concentration of phenacite and bertrandite, P (6) 170*h*. Fluormica-fluoramphibole ceramics and processes of making them, P (2) 49*a*. High temperature electrostatic precipitator and method of operation, P (2) 51*d*. Method for producing zirconium diboride, P (8) 216*g*. Process for wet grinding solids to extreme fineness, P (5) 138*f*.
United States of America, Secretary of the Navy. Hygrometer elements, P (2) 53*d*. Magnetostrictive ferrite, P (6) 166*e*. Metal-ceramic laminated coating and process for making it, P (2) 38*f*. Multifilar measuring device, P (10) 287*b*. Preparation of high purity silicon by decomposition of silicon nitride powder having a graphite target buried therein, P (11) 311*e*.
United States of America, U. S. Atomic Energy Commission. Cadmium phosphate glass, P (7) 185*i*. Catalytic recombination of radiolytic gases in thorium oxide slurries, P (1) 15*i*. Coated carbon element for use in nuclear reactors and process of making it, P (5) 133*c*. Continuous rotation scattering chamber [for nuclear reaction], P (11) 320*c*. Dispersion element consisting of chromium coated UO_2 particles uniformly distributed in a Zircaloy matrix, P (8) 215*j*. Dispersion hardening of uranium metal, P (5) 133*e*. Double-baked self-channeling electrode, P (7) 197*a*. Ductile chromium, P (5) 133*g*. Fluorination of oxidic nuclear fuel, P (10) 289*i*. Fuel assay reactor, P (4) 102*i*. Fuel composition for nuclear reactors, P (11) 308*c*. Fuel element for a neutronic reactor, P (11) 308*c*. Fused-salt process for recovery of values from used nuclear-reactor fuels, P (6) 167*b*. Gamma radiation dosage-measuring glasses and method of using, P (9) 241*j*. Glass composition, P (7) 186*b*. Glass composition and process of making, P (1) 11*j*. High-temperature [graphite-Rh] thermocouple, P (6) 168*i*. Method of fabricating a graphite-moderated reactor, P (8) 216*j*. Method of making fuel bodies, P (8) 216*d*. Method of making spherical actinide carbide, P (4) 102*e*. Method for preparation of sinterable beryllium oxide, P (11) 315*b*. Method for preparing uranium monocarbide-plutonium monocarbide solid solution, P (7) 189*d*. Method of sintering uranium dioxide, P (8) 216*h*. Neutron source, P (5) 133*c*. Nuclear reactor, P (5) 133*d*. Nuclear reactor fuel-breeder fuel element, P (1) 16*j*. Nuclear reactor fuel elements and method of preparation, P (10) 277*b*. Particle separation method, P (5) 138*d*. Precipitation of zirconium and fluoride ions from solutions, P (9) 254*c*. Preparation of refractory oxide crystals, P (3) 74*j*. Preparation of spherical ranium dioxide particles, P (8) 216*j*. Process for dissolving binary uranium-zirconium or zirconium-base alloys, P (1) 17*e*. Process for separating americium and curium from rare earth elements, P (6) 176*a*.
United States Borax & Chemical Corp. Method for [electrolytically] producing sodium borates of lowered iron content, P (3) 84*b*. Production of boron trihalides, P (10) 290*d*.
United States Ceramic Tile Co. Ceramic tile, P (8) 218*c*.
United States Gypsum Co. Board-forming machine, P (7) 182*g*. Dimensionally stable expanded perlite and method for making it, P (3) 83*f*. Process for calcination of gypsum, P (7) 182*i*.
United States Steel Corp. Air-sweep [partial vacuum] classifier, P (2) 54*j*. Apparatus for handling and wetting dust, P (8) 221*d*. Ceramic coated tuyeres, etc., P (4) 97*g*. Heat exchanger and method, P (5) 140*c*. Hinged heat shield for metal teeming ladle bottoms, P (8) 216*i*. Method and apparatus for controlling feed to shaft furnace, P (1) 25*a*. Method for producing high-temperature cement in the blast furnace, P (1) 3*e*. Open-hearth furnace [design], P (3) 74*h*. Tuyere with preformed refractory nose and sleeve, P (3) 75*a*.
United States Stoneware Co. Saddles, P (3) 74*j*. Support plate, P (3) 76*a*.
Universal Oil Products Co. Insulated chamber, P (6) 162*d*.
University of Tennessee Research Corp. Apparatus for determining physical [permeability] properties of porous material, P (3) 81*a*.

Univis Lens Co. Polishing material, P (4) 95*g*.
Uno, T. See Amafuji, M.
Unwin, J. T. Production of barium oxide, P (2) 55*g*.
Urano, N. See Ueno, T.
Urode, R. J. See Leggett, H.
Usol'tseva, L. P. See Funke, V. F.
Utley, H. F. Asbestos boom in California, (6) 169*i*. California cement producers, (7) 178*e*. Crestlite's new expanded shale aggregate plant, (6) 158*f*.
Uyeda, R. See Kamiya, Y.
Uyemura, Y. See Oshima, T.

Vadilo, P. S. Formation of hollow-needle crystals, B (9) 262*e*.
Vago, E. See Griffith, C. F.
Vago, E., and Griffith, C. F. Corrosion of refractories by molten glass, (1) 5*j*. Corrosion of zircon refractories by molten glasses (I) effect of the porosity of zircon refractories on their resistance to corrosion by a calcium aluminoborosilicate glass; (II) effect of the concentration of zirconium silicate dissolved in a calcium aluminoborosilicate glass and in a soda-lime silicate sheet glass on the relative rate of corrosion of zircon refractories in these glasses, (1) 6*b*.
Vahldiek, F. W. See Lynch, C. T.
Vail, C. R. Molecular behavior of composite electrical insulation, (3) 76*d*.
Vainshtein, A. L. See Pronin, B. G.
Vainshtein, E. E., Verkhoglyadova, T. S., and Zhurakovskii, E. A. Microstructure of the X-ray K-absorption spectra of the metal in the range of homogeneity of titanium nitride, (2) 58*c*.
Vaintraub, Yu. Ya. Glass laminates, P (2) 42*i*.
Valenta, L. Errors in the manufacture of porcelain, (5) 133*j*. Structure and calculation of glazes for china, (5) 134*b*.
Valery, A. L. Asia Cement Corp.'s new operation boosts Formosa cement output, (7) 178*e*.
Val'kovskaya, M. I. See Boyarskaya, Yu. S.
Vallings, H. G. Process and handling in making Pyrex glass, (7) 194*i*.
Van Antwerp, A. E. Method of making a particulate, solid silicon monoxide product, P (8) 225*g*.
Van Cakenberghe, J. L. See Gilles, J.-M. F.; Herinckx, C.
Vance, J. A. Polysynthetic twinning in plagioclase, (4) 118*c*.
Van Cott, H. C. Method of making a sintered ceramic article, P (10) 277*f*.
Vand, V. Meteoritic craters of Ries Kessel and Steinheim Basin (Germany) and their relation to tektites, (4) 109*c*.
Vander, F. Batch calculation of china clay, (11) 309*b*.
Van Der Beck, R. R. Spodumene-based castable refractory, (9) 243*h*.
Van Derbeek, W. L. See Sfiscko, N. M.
Vander Linden, C. R., and Leineweber, J. P. Calcium silicate product and method of preparing it, P (1) 25*f*.
Vander Linden, F. A. See Borger, J. W.
Vanderpool, C. D. See Chiola, V.
Vanderslice, T. A. See Lafferty, J. M.
Vandervoort, R. R., and Barmore, W. L. Compressive creep of polycrystalline beryllium oxide, (6) 172*e*.
Van Dolah, H. J., and Linhart, O. C. Porcelain enameling frit, P (10) 269*g*.
Van Dreser, M. L., and Boyer, W. H. High-temperature firing of basic refractories, (8) 214*a*.
Van Dyke, N. D. See Hoover, H. L.
Vanguard Abrasive Corp. Abrasive cut-off disks, P (4) 95*f*.
Van Hook, H. J. Influence of oxygen pressure on incongruent melting temperature of yttrium iron garnet, (7) 199*f*. Phase relations in the garnet region of the system Y_2O_3–Fe_2O_3–FeO–Al_2O_3, (5) 144*i*.
Vanicek, V. See Sip, V.
Vanik, M. C. See Barrett, W. T.; Fitch, F. T.
Van Riper, J. W. Plastic material extrusion apparatus, P (7) 195*b*.
Van Sandt, W. A., Santomassino, V. C., Rumble, R. P., and Barlow, O. M. Direct reading beryllium spectrograph, (5) 138*j*.
Van Saun, Kennedy, Mfg. & Eng. Corp. See Kennedy Van Saun Mfg. & Eng. Corp.
Van Uitert, L. G. See Grodkiewicz, W. H.
Van Uitert, L. G., Rubin, J. J., and Bonner, W. A. Preparation of single crystals of tungstates and molybdates of a number of divalent metal ions, (1) 318*a*.
Van Valkenburg, A. See Weir, C. E.
Van Wazer, J. R., Lyons, J. W., Kim, K. Y., and Colwell, R. E. Viscosity and Flow Measurement—A Laboratory Handbook of Rheology, B (10) 300*e*.
Varadi, P. F. See Spurck, R. F.
Vardi, J. See Hoch, M.
Vardi, J., and Hoch, M. Thermal conductivity of anisotropic solids at high temperatures—thermal conductivity of molded and pyrolytic graphites, (5) 146*j*.
Vargin, V. V. Enamels for the coating of metals, (7) 183*f*. Nickel ion as an indicator of the structure of sodium aluminosilicate glasses, (3) 67*j*.
Vargin, V. V., and Michel, V. E. Antimony enamels, B (11) 322*h*.
Vargin, V. V., and Smirnova, G. P. Titanium enamels with low TiO_2 contents, (7) 183*f*.
Varian Associates. Thermocouple measuring circuit, P (5) 140*a*.
Vashko, A., Prokopova, G., Kolomiets, B. T., Pavlov, B. V., and Shilo, V. P. Absorption spectra of glasses of the system As_2S_3–As_2Se_3, (5) 128*g*.
Vasil'ev, N. P. See Sapotnitskii, S. A.
Vasil'eva, M. A. See Stepanov, I. V.
Vasil'eva, N. N., and Morgenshtern, Z. L. Gamma and photoluminescence of alkali iodides, (5) 135*a*.
Vasilevskaya, L. S., Kondrashina, A. I., and Shifrina, G. G. Spectrochemical method for determining the boron concentration in silicon and its compounds, (9) 252*a*.
Vasilevskaya, V. N. See Belyaev, A. D.
Vasilos, T. See Gannon, R. E.; Spriggs, R. M.
Vasilos, T., and Spriggs, R. M. Pressure sintering—mechanisms and microstructures for alumina and magnesia, (11) 318*c*.
Vasserman, I. M., Baram, A. A., and Pryanishnikov, V. P. Silicon dioxide by electrolysis of silicates, P (2) 56*a*.
Vassiliev, A. Ferrites for radio antennas, P (3) 77*c*.
Vatterodt, K. Electrically heated furnace for melting quartz or quartz glasses, P (4) 99*f*.
Vaughan, C. D., Jr., and Vetter, R. H. Magnesium oxide pellets and process of producing them for burning, P (11) 308*f*.
Vaughan, J. T. Electrical device for induction furnaces, P (4) 108*g*.
Vawter, D. D. Measuring and comparing device of the [optical] pyrometer type, P (4) 108*e*.
Vayssiere, P. See Francais, J.
Veatch, F. See Alford, H. E.
Veazie, F. M. Treatment for glass bodies, P (3) 70*g*.
VEB Keramische Werke Hermsdorf. Hydrothermal synthesis of steatite, P (4) 110*i*.
Vedder, W. O., and Gibby, W. F. Sonic cleaning of dust filters, P (1) 23*e*.
Veilleux, E. D. Gray iron under impact, (4) 97*j*.
Veiser, I. See Petri, I.
Veitch, L. G., and Radoslovich, E. W. Cell dimensions and symmetry of layer-lattice silicates (III) octahedral ordering, (9) 255*d*.
Veitscher Magnesitwerke Akt.-Ges. Highly refractory magnesite-chromite molded bodies, P (4) 102*b*.
Vekshina, N. V. See Markovskii, L. Ya.
Vela, D. L. See Fetter, H.
Venema, A. See Lemmens, H. J.
Venuat, M. Composition and structure of the hydration products of calcium silicates of cements, (1) 2*g*. Use of test specimens of 2 x 2 x 16 cm for hydraulic binders, (1) 3*j*.
Verba, J. W., and Hawrylak, R. A. Continuous rotation scattering chamber [for nuclear reaction], P (11) 320*c*.
Verba, R. J. See Schweitzer, H. V.
Verbeck, G. See Copeland, L. E.
Verbitskaya, T. N. Investigation of electrostriction of Seignette ceramics, (10) 280*f*.
Verdu, F. A. y. See Arrendondo y Verdu, F.
Verduch, A. G. See Garcia Verduch, A.
Vereikina, L. L. See Samsonov, G. V.
Vereinigte Metallwerke Ranshofen-Berndorf. Process for the recovery of cryolite from waste gases and from the carbon bottom of an aluminum electrolytic furnace, P (3) 85*b*. Surface preparation for aluminum alloys to be enameled, P (4) 97*j*.
Veres, F. Catadioptric electroluminescent glass block, P (8) 210*b*. Method of adhering metal to a glass base, P (5) 136*c*. Method for producing silicon, P (2) 49*j*.
Vereshchagin, I. K. Electroluminescence of ZnS phosphors under excitation by square pulses of different duration, (6) 163*h*.
Vereshchagin, I. K., and Dra ak, I. T. Electroluminescence of ZnO single crystals, (5) 134*f*.
Vergara, W. C., Greenhouse, H. M., and Nicholas, N. C. Evaporant sources for the deposition of pinhole free films, (11) 311*j*.
Vergunas, F. I., and Yashin, E. M. Certain regularities of the optical flash in ZnS:Cu,Pb phosphors, (6) 163*f*.
Verhagen, C. M. C. See Koelmans, H.
Verkhoglyadova, T. S. See Vainshtein, E. E.
Verkhoglyadova, T. S., L'vov, S. N., Nemchenko, V. F., and Samsonov, G. V. Electrical and galvanomagnetic properties of chromium nitrides, (2) 57*a*.
Verma, A. R. See Krishna, P.
Verma, S. S. Effects of minor constituents of sheet iron on its enameling quality—a review, (3) 65*g*. Progress of vitreous enameling industry and research in India, (11) 303*b*.
Vermont American Corp. Abrasive article, P (9) 236*e*.
Vernon, R. C. Extinction coefficient of single-crystal hematite in the region 3600 to 7000 A, (5) 143*d*.
Vernon, R. H. Magnetic susceptibility as a measure of total iron plus manganese in some ferromagnesian silicate minerals, (4) 116*e*.
Verweel, J. Permeability and ferromagnetic resonance line width of some ferrites with garnet structure, (9) 248*b*. See Gorter, E. W.
Vest, R. W. Electrical behavior of refractory oxides, (8) 219*h*.
Vesuvius Crucible Co. Stopper for a ladle or similar receptacle, P (9) 245*f*.
Veszelei, J. See Sterk, E.
Veth, G. J. Optical soldering promotes automated packaging, (7) 192*a*.
Vetten, W. C. See Delangre, M.
Vetter, R. H. See Vaughan, C. D., Jr.
Vicary, J. W. Plant layout changeable for efficiency, (9) 238*d*. Sales—production—design, the eternal triangle, (2) 33*j*.
Vicente, J. G. See Garcia Vicente, J.
Vickers-Armstrongs (Engineers), Ltd. Weighing apparatus [for cement clinker], P (9) 238*a*.
Vickery, R. C. Method for preparing ferromagnetic oxides, P (6) 166*a*.
Vienna, P. C. See Gaynor, J. W.
Vier, D. T. See Pretzel, F. E.
Vilchez, F. G. See Girela Vilchez, F.
Vilensky, M. B. Method of producing a ferrite body and product obtained, P (5) 136*f*.
Villaamil, J. R. C. See Castillo Villaamil, J. R.
Villalobos, H. F. Diamond cutting tool having an edge thickness of 0.001 to 0.01 μ, P (3) 81*c*.
Vil'nis, K. K. See Gutop, V. G.
Vincent, G. L. American Lava Corp., (6) 163*b*. Automation upgrades production facilities, (3) 75*e*. Ford produces plate in world's largest integrated glass plant, (4) 98*f*. Frigidaire expands porcelain enameled refrigerator line for 63, (6) 155*d*. Haeger Potteries, Inc., (6) 163*c*. How Fortune Industries manufactures ceramic whiteware abrasive products, (1) 1*f*. Owens-Illinois Glass Co.—New Orleans plant, (6) 156*f*.
Vingas, G. See Wolke, R.
Vinkeloe, R. Concrete as a reactor material, (10) 266*h*.
Vinogradov, B. N. Intensification of the lime burning process with the aid of mineralizers, (11) 302*f*.
Vinokurov, L. A., and Fok, M. V. Final stages of the buildup of the blue and green luminescence bands of a ZnS·Cu,Cl phosphor, (6) 164*c*.
Vitali, A. Hydraulic horizontal press with two series of multiple chambers for pressing with filter plates for very high production, P (5) 138*a*. Installation for the automatic operation of hydraulic [filter] presses in a predetermined and continuous succession of working cycles, P (6) 167*d*.
Vitkovskii, B., and Tatarinova, L. Crystallization of nominally pure materials, B (9) 262*h*.
Vitramon, Inc. Dielectric ceramic composition, P (4) 105*b*.
Vitrikhovskii, N. I., and Mitzetskaya, I. B. Characteristics of CdS·CdSe and CdS·CdTe crystals grown from the vapor state, B (9) 263*b*.
Vitro Corp. of America. Concentration of rare earths, P (9) 254*j*. Piezoelectric crystal holder, P (1) 21*d*.
Viudes, P. de la C. See Cierva Viudes, P. de la.
Vivaldi, J. L. M. See Martin Vivaldi, J. L.
Vivian, H. E. Some chemical additions and admixtures in cement paste and concrete, B (5) 150*a*.
Vizir, L. A. See Lavrova, L. M.
Vlachovsky, O. Faults occurring during the manufacture of electrotechnical porcelain—causes and prevention, (9) 247*g*.
Valsenko, N. A., and Pavlova, E. N. Role of additional impurities in the formation of luminescence centers in the phosphor ZnS:Cu, (6) 165*g*.
Vlasov, A. G., and Chebotareva, T. E. Determination of the quantitative relationship between the ordered and disordered phases in a glass with a composition of 33.3% Na_2O and 66.6% SiO_2, (6) 156*f*.
Vliet, K. M. van. See Arntz, F. O.
Vlisidis, A. C. See Erd, R. C.
Vodicka, V. Basing cement, P (6) 154*i*. See Malm, R. N.
Vodicka, V., and Malinowski, R. F. Coated electric lamp and method of manufacture, P (3) 69*e*.
Voeller, R. Automatic balancing arrangement [static and dynamic] for grinding wheels, P (10) 265*f*.
Voevodsky, V. V. See Kazansky, V. B.
Vogan, J. W. See Herron, R. H.
Vogel, F. L. See Murray, L. A.
Vogelpohl, R. L. See Mayhew, R. W.
Voggel, K. See Scheuermann, E. A.
Voigt, F. Dispersion of the complex permeability of lithium ferrites, (3) 86*f*.
Voinovitch, I. A. See Debras-Guedon, J.
Voinovitch, I. A., and Debras-Guedon, J. Analysis of soluble salts in clays, (2) 56*b*.
Voishville, N. A. Spectrophotometric and photometric characteristics of the opal glass MSI4, (5) 129*f*.
Voisin, G. A. See Collet, A.
Voiger, J. See Stevels, J. M.
Volkonskii, B. V. See Konovalov, P. F.
Voloshchuk, Va. V. See Andrievskii, A. I.
Volynets, E. E. See Andreeva, E. P.
Vonbun, F. O., and Schodowski, S. S. Heat sinks for [quartz] crystal oscillators, P (4) 105*e*.
Vondracek, C. H. See Hofmann, C. F.; Merry, J. D.; Westervelt, D. C.
Von Mickwitz, A. W. Magnesia composition and method of making it, P (9) 244*c*.
Von Saldern, A. Sassanian "luxury" glass (abstract), B (11) 321*f*.
Vordahl, M. B. Powder metallurgy processes and products, P (3) 74*i*.
Vorob'ev, V. G. Solution for treating glass for mirrors, P (2) 43*d*.
Vorres, K. S. Estimation of phase diagrams for systems of two binary compounds, (10) 292*e*.
Voruz, T. A., Jewett, R. P., and Accountius, O. E. Direct observation of dislocations in sapphire, (10) 291*i*.
Vose, F. C., and Kaminski, J., Jr. Electrical suspension insulator with improved pin, P (2) 47*e*.
Voskoboinikov, G. I., and Reznikov, M. I. Improving the manufacture of enameled glass facing tile, (1) 7*j*.
Voss, E. B. See Johnson, J. R.
Voss, W. G. See Miller, G. E.

Vosskuehler, H. Composite mold for continuous casting, P (2) 45*c*.

Vozdvizhenskii, G. S., Gorbauchuk, G. A., and Dezider'ev, G. P. Electron-microscope study of the dissolution of a metal at an anode, B (9) 262*f*.

Vratny, F., Dilling, M., Gugliotta, F., and Rao, C. N. R. Infrared spectra of metallic oxides, phosphates, and chromates, (5) 144*i*.

Vukovich, M., Jr. Wollastonite in melted ceramic systems, (2) 47*b*.

Vydrina, Zh. A. See Dvorkind, M. M.

Vyrodov, I. P. Indexing of X-ray [diffraction] diagrams and determination of the lattice parameters from X-ray diagrams of polycrystalline substances, (5) 144*g*.

Waanders, J. Fluorspar admixes strengthen cement, (6) 154*e*.

Wachi, F. M. See Juvet, R. S., Jr.

Wachtl, Z. See Eckstein, J.

Wachtman, J. B., Jr., Tefft, W. E., and Lam, D. G., Jr. Elastic constants of rutile (TiO_2), (3) 86*j*. Young's modulus of single crystal corundum from 77° to 850°K, B (3) 92*b*.

Wacker-Chemi G.m.b.H. Process for manufacturing indium phosphide and gallium arsenide of high purity, P (6) 166*c*.

Wada, H. See Nagano, R.

Wada, K. See Aomine, S.

Wada, M. See Tashiro, M.

Wade, W. L., Jr. Method of making ferromagnetic barium ferrites, P (1) 21*h*. Method of making magnetic ferrite films, P (10) 283*g*.

Wade, W. S., Johnston, H. L., and Bachman, J. R. Measurement of stress in furnace arches, (8) 214*g*.

Wadsworth, M. E. See Daniels, A. U.

Wagner, E. Burner for production of finely divided oxides, P (8) 224*f*.

Wagner, H. A. Hermetically sealed [ceramic] semiconductor devices, P (4) 105*e*.

Wagner, H. C. Miniature ceramic crucibles for burning metal samples, and ceramic material, P (11) 308*i*

Wagner, O. E, and Happ, W. W. Field emmission in rutile diodes, (10) 280*b*.

Wagner, R. Angular dependency of the anisotropy of Fe-Ni ferrite single crystals induced by a magnetic field, (3) 85*h*.

Wah Chang Corp. Recovery of earth acids from slag, P (11) 315*f*.

Wahl, A. J., Lux, J. F., and Gould, R. E. Method for shaping appendages on ceramic articles, P (4) 104*b*.

Wahl, F. M. See Graf, R. B.

Wahl, F. M., Grim, R. E., and Graf, R. B. Phase transformations in silica-alumina mixtures as examined by continuous X-ray diffraction, (4) 118*b*.

Wahl, W. W., and Dever, C. D. Water loss control of [pumpable] aqueous cement slurries by addition of quaternary ammonium polymers or sulfonium polymers, P (10) 268*e*.

Wahl, W. W., Dever, C. D., and Ryan, R. F. Low water-loss cement composition, P (8) 206*c*.

Wahlberg, J. S., and Fishman, M. J. Adsorption of cesium on clay minerals, (6) 169*g*.

Wahlig, C. F. See Umberger, J. Q.

Waid, D. E. See Yeo, R. H.

Wainer, E. Stable colloidal dispersions and method of preparing them, P (7) 190*a*.

Wainer, E., and Beasley, R. M. Fiber forming process, P (7) 189*a*.

Wainer, E., and Cunningham, A. Preparation of fibers, P (6) 162*b*.

Wainer, E., and Mayer, E. F. Method of making inorganic fibers, P (10) 277*c*.

Waite, J. M. Rapid change rotating sample holder for X-ray diffraction of powders, (11) 313*f*.

Waitkus, J. Recover waste heat to reduce glass tank operating cost, (3) 67*h*.

Wakamatsu, S. Study on chemical analysis of basic slag (I) determination of SiO_2, total Fe, Al_2O_3, MnO, CaO, and MgO in basic slag; (II) determination of FeO, Fe_2O_3, and TiO_2 in basic slag; (III) determination of sulfur in basic slag, (5) 139*f*.

Wakefield, J. See Newman, R. C.

Walberg, A. C. Spray gun for electrostatic coating, P (2) 38*e*.

Wald, D. Measuring temperature in strong fields, (9) 251*g*.

Waldner, W. F. Accurate determination of minerals with the phase contrast microscope (in combating dust and silicosis), (4) 111*h*.

Waldron, G. W., and Periard, J. N. Production of $Mg(OH)_2$, P (6) 171*c*.

Waldron, R. D. See Balkanski, M.

Walento, S. See Paprocki, A.

Walker, A. D. See Madge, J. G.

Walker, B. E., Jr. See Ewing, C. T.

Walker, B. E., Jr., Ewing, C. T., and Miller, R. R. Thermoelectric instability of some noble metal thermocouples at high temperatures, (5) 139*h*.

Walker, C. W. E. Apparatus and method for measurement of moisture content, P (6) 168*h*. Instrument for the measurement of moisture, etc., P (6) 168*i*.

Walker, G. B. See Free, J. M.

Walker, G. F. See Garrett, W. G.

Walker, P. L., Jr. Carbon—an old but new material, (11) 314*h*.

Walker, R. M. See Fleischer, R. L.

Walker, R. S., and Mertz, F. A. Scoop feeder for rotary kiln, P (7) 197*b*.

Walker, W. A. Oil well cement compositions, P (1) 3*g*.

Walker, W. C., and Ostantowski, J. Reflection spectrum of cubic zinc sulfide in the interband transition region, (6) 175*f*.

Wall, J. R. D., Wolfenden, E. B., Beard, E. H., and Deans, T. Norstrandite in soil from West Sarawak, Borneo, (10) 288*h*.

Wallace, B. P., and Melcher, R. E. Cellulosic additive materials for green sand molding, P (8) 215*g*. Green molding sand additive [starch], P (8) 216*h*. Methyl cellulose additive for green molding sand, P (10) 277*j*.

Wallace, D. C. See Greiner, J. D.

Wallace, R. W. See Ruh, E.

Waller, C. E. See Green, L., Jr.; Stehsel, M. L.

Wallhaus, R. A. Statistical study of factors influencing the strength of glass fibers, (9) 241*h*.

Walsh, E. G. See Margolis, D. P.

Walsh, J. B. See Brace, W. F.

Walsh, P., and Kemeny, G. Laser operation without spikes in a ruby ring, (10) 280*j*.

Walt, J. P. Furnace block with hanger socket, P (4) 102*j*.

Walter, P. Thin films with a negative temperature coefficient of electrical resistance on ceramics, P (4) 106*a*.

Walters, E. L. Handling equipment for [glass] sheet materials, P (8) 210*i*.

Walther, H., and Hielscher, P. Foam silicate structural elements for rural and housing construction, (1) 6*h*.

Walton, B. See Kirby, P. L.

Walton, J. D., Jr. See Poulos, N. E.

Walton, J. D., Jr., and Bowen, M. D. Evaluation of ceramic materials under thermal shock conditions, B (3) 92*a*.

Walton, J. D., Jr., and Poulos, N. E. Fused silica refractories, B (10) 300*j*. Slip-cast metal fiber reinforced ceramics, (1) 4*e*.

Wangsness, R. K. Introduction to Theoretical Physics—Classical Mechanics and Electrodynamics, B (10) 299*j*.

Wanmaker, W. L. See Hoekstra, A. H.

Wanmaker, W. L., Bakker, C., and Arents, J. W. M. Electric gas discharge lamp comprising a luminescent layer, P (2) 42*c*.

Wantman, R. See Waugh, J. S.

Warburton, R. S., and Wilburn, F. W. Application of differential thermal analysis and thermogravimetric analysis to the study of reactions between glassmaking materials (IV) calcium carbonate–silica–alumina system, (10) 269*j*.

Ward, C. R. See James, R. A.

Ward, D., and Passmore, M. E. Nose cones—study in grinding technique, (3) 63*g*.

Ward, J. B. Design management—an executive function, (9) 236*g*. See Symmers, C.

Ward, J. W. Colorimeter and [photoelectric] color sorting apparatus, P (3) 81*c*.

Ward, R. See Patterson, F. K.; Sleight, A. W.

Ward, R., and Longo, J. Magnetite phases of the perovskite type, (2) 57*h*.

Ward, W., and Fletcher, E. Methods for the analysis of ream knots in glass, (8) 209*e*.

Ward, W. T. See Cannon, M. C.

Warf, J. C. See Palenik, G. J.

Waring, C. L. Microspectrochemical analysis of minerals (II), (6) 168*c*.

Waring, C. L., Worthing, H. W., and Weeks, A. D. Microspectrochemical analysis of minerals, (4) 107*c*.

Waring, R. K. See Jarrett, H. S.

Warkentin, B. P., and Young, R. N. Shear strength of montmorillonite and kaolinite related to interparticle forces, B (5) 150*d*.

Warne, S. St. J. See Bayliss, P.

Warner, L. L. See Koerner, M. P.

Warner, R. M. Epitaxial growth and devices, (2) 47*i*.

Warner, R. M., Jr. See Robertson, H. M.

Warnke, R. C. See Kegg, R. R.

Warren, G. See Sanford, E. A.

Warren, I. H. Uranium compounds as thermoelectric materials, (10) 282*a*.

Warren, R. E. See Meriwether, H. R., Jr.

Warshaw, C. M., Rosenberg, P. E., and Roy, R. Changes effected in layer silicates by heating below 550°C, (11) 316*j*.

Wartenberg, E. W. Method of coating glass, P (9) 242*f*.

Warthen, W. P. Method and apparatus for producing filaments of heat-softenable materials, P (3) 69*j*. See Whitehurst, H. B.

Warwick, W. See Shell, H. R.

Washburn, E. M. See Bigler, R. R.

Washburn, J. See Elkington, W. E.

Washburn, M. E. Superrefractory products of oxynitride bonded silicon carbide, (10) 276*b*.

Wasilewski, S. See Barrer, R. M.

Wasserburg, G. J. See Kennedy, G. C.

Wasserman, M. Electroluminescent device, P (2) 48*e*. Resistor, P (1) 21*g*.

Wasserman, R. D., and Quaas, J. F. Coated welding rod, P (7) 183*h*.

Watabe, S. See Sakurai, S.

Watanabe, A. See Nagasaki, S.

Watanabe, H. Energy loss of electrons passing through a graphite single crystal at different incident angles, (6) 173*c*.

Watanabe, K., and Sasaki, T. Nuclear magnetic resonance study on hardened cement paste, B (5) 149*a*.

Watanabe, K., Sasaki, T., and Maki, I. Dielectric study on the hydration of cement paste, (7) 179*g*.

Watanabe, T., Takada, T., and Kachi, S. Study on the morphological properties of uranium dioxide, (7) 201*b*.

Waters, P. L. Rheological properties of coal during the early stage of thermal softening, (7) 196*g*.

Watkins, G. D., and Corbett, J. W. Electron paramagnetic resonance of defects in irradiated silicon, (8) 227*g*.

Watson, A., May, J. O., and Butterworth, B. Studies of pore-size distribution (II) apparatus for measurement of coarse pores, B (4) 124*d*.

Watson, D. L., and Tyrell, J. L. Apparatus for measuring changes in weight of samples as a function of temperature, P (2) 53*a*.

Watson, F. K. See Kumnick, M. C.

Watson, G. M. See Cannon, M. C.; Evans, R. B., III.; Grimes, W. R.

Watson, M. T. See Close, P. T.

Watson, P. K. See Sharbaugh, A. H.

Watson, W. H., and Blood, G. Method for producing hollow glass articles, P (5) 131*a*.

Watt, A. D., Mathews, F. S., and Maxwell, E. L. Some electrical characteristics of the earth's crust, (10) 282*g*.

Watt, H. v. H. van der, and Bodman, G. B. Viscosimetric constants of suspensions of clay-polymer complexes, B (5) 151*a*.

Watts, A. S. Control of the properties of glazes by the aid of eutectics—study of fusion behavior and other properties of ceramic mixtures in the eutectic areas (IV) alkali–B_2O_3–SiO_2 systems; (V) system PbO–B_2O_3–SiO_2, (10) 278*g*.

Waugh, A. See Kingery, W. D.

Waugh, J. A. See Marzocchi, A.

Waugh, J. S., Paladino, A. E., diBenedetto, B., and Wantman, R. Effect of dislocations on oxidation and reduction of single-crystal $SrTiO_3$, (3) 86*j*.

Way, S. J. See Powell, D. A.

Waye, B. E. Further consideration of shaping methods, (7) 190*d*.

Waye, B. E., Ashley, M., Gibson, B., Hales, B., and James, G. Vitrification and fired properties of an electrical porcelain body, (11) 309*e*.

Waymouth, J. F. See Gungle, W. C.

Wayrynen, R. E. Preparation of recalcined zinc sulfide phosphors, P (1) 21*e*.

Weakliem, H. A., and McClure, D. S. Symmetry of transition metal impurity sites in crystals as inferred from optical spectra, B (9) 260*c*.

Weaa Engineering Co., Inc. Vacuum coating apparatus, P (2) 50*e*.

Weatherley, E. G. Diffusion of metals in relation to glass mold equipment, (4) 98*b*.

Weaver, C. E. Possible uses of clay minerals in the search for oil, B (3) 91*a*.

Weaver, C. F. See Thoma, R. E.

Weaver, E. P. See Davies, B.; Hubbell, D. S.

Weaver, L. G. Thickness gage for blast furnace wall, P (6) 169*e*.

Webber, J. J. Secondary regeneration and combustion control techniques, (10) 287*g*.

Weber, B. C. Crucible and refractory material therefor, P (1) 15*j*. Inconsistencies in zirconia literature, (2) 57*j*. Luminescence phenomena and zirconia research, (10) 280*h*.

Weber, B. C., and Rizzo, H. F. Silicon-boron-oxygen refractory material, P (10) 277*j*.

Weber, C. E. Progress on dispersion elements, (10) 275*f*.

Weber, C. E., and Hirsch, H. H. Dispersion type fuel elements, (8) 213*d*.

Weber, D. Spectral emissivity measurements near room temperature, B (3) 93*c*.

Weber, H. Process for the production of sodium zeolite A, P (3) 84*j*.

Weber, H. S. See Riesz, C. H.

Weber, J. W. See Greene, C. H.

Weber, T. W. See Hessinger, P. S.

Weber-Klein, P. Glass level control—problems and methods, (8) 208*h*.

Wecht, P. Use of high-forsterite brick in the open-hearth furnace, (8) 215*c*.

Wedepohl, P. T. See Custers, J. F. H.

Weeks, A. D. See Waring, C. L.

Weeks, L. W. See Sauer, J. M.

Weeks, R. A. See Levy, P. W.

Wegelin, E. See Solt, G. S.

Wehren, P. See Decker, H.

Weidel, R. A. See Hamblen, D. P.

Weigandt, A. See Olson, O. H.

Weill, D. F., and Fyfe, W. S. Preliminary note on the relative stability of andalusite, kyanite, and sillimanite, (4) 118*e*.

Weilner, C. Use of cristobalite to prevent crazing in glazes, (8) 218*c*.

Weimer, P. K. TFT—a new thin-film transistor, (2) 48*b*.

Weingaertner, F. See Rueter, H.

Weinland, L. A. See Blank, B.

Weinstein, M. Fused porcelain-to-metal teeth, P (1) 18*g*. Porcelain covered metal-reinforced teeth, P (1) 18*j*.

Weir, A. H., and Greene-Kelly, R. Beidellite, (6) 169*i*.

Weir, A. H., Nixon, H. L., and Woods, R. D. Measurement of thickness of dispersed clay flakes with the electron microscope, B (5) 150*h*.

Weir, C. C., and Soper, R. J. Adsorption and exchange studies of phosphorus in some Manitoba soils, (5) 140*h*.

Weir, C. E., Van Valkenburg, A., and Lippincott, E. R. High-pressure optical cell, P (6) 168*h*.

Weisner, I. Apparatus for determining the hardness of glazes, (3) 75*d*.

Weiss, A. See Rocktaeschel, G.

Weiss, A., and Frank, R. Significance of exchangeable ions for the formation of the skeleton of thixotropic gels, (3) 88*c*.

Weiss, A., and Rocktaeschel, G. Thiosilicates, (4) 121*b*.

Weiss, A., and Thamerus, G. Substitution of exchangeable cations in micalike layer silicates by Al^{3+} and Si^{4+}, (5) 146*e*.
Weiss, M. D. See Cunningham, C. R.
Weissbach, H. See Noll, W.
Weissenberg, G., and Ungemach, O. Optical borate glass, P (7) 186*e*.
Weissenberger, E. S. Metal sheathed thermocouples, (9) 251*i*.
Weisshaar, E. See Plust, H. G.
Weissmann, H. Treatment of discontinuous operations in automation of processes and mechanical manufacture, (8) 221*h*.
Weisz, R. S. Magnetically annealed ferrite material, P (2) 49*e*.
Weitzer, H. P., and Rinesch, R. F. Experience with refractory linings for LD furnaces at VOEST, Austria, (6) 161*c*.
Weizmann Institute of Science. Ferrite material containing fluorine, P (9) 249*a*.
Welch, B. J. See Bloom, H.
Welch, J. H., and Gutt, W. Effect of minor components on the hydraulicity of the calcium silicates, B (5) 148*g*.
Welkowitz, W., and Traite, M. Piezoresistive transducer, P (8) 220*h*.
Weller, L. G. Gas-material separator [with reverse flush], P (10) 285*c*.
Weller, P. F. See Sienko, M. J.
Wellinger, R. P. Storage target electrode and method of manufacture, P (9) 249*i*.
Wellman, S. K., Co. Friction composition and method of making, P (4) 102*h*.
Wells, C. E. See Richmond, J. L.
Welty, J. R., and Wicks, C. E. Ice calorimeter for precise measurement of heat content from 0° to 1500°K, (1) 23*i*.
Wendell, C. B. See Secord, R. N.
Wentorf, R. H., Jr. High pressure, high temperature apparatus, P (8) 221*i*. Process for making conducting cubic boron nitride and product therefrom, P (6) 162*d*. Synthesis of the cubic form of boron nitride, (2) 54*g*. See Bundy, F. P.
Werff, W. van der. Rotary fil ers [assembly], P (3) 85*e*.
Werkspoor N. V. Rotary filters [assembly], P (3) 85*e*.
Wermbter, H. See Lehmann, H.
Werner, A. E., and Bimson, M. Some opacifying agents in oriental glass, B (11) 321*e*.
Wernick, J. H. See Newkirk, J. B.
Wernicke & Co., K. G. Dressing device for grinding spectacle glasses, P (1) 11*e*.
Wertheim, G. Radiation effects in semiconductors (3) 76*e*.
Werthwine, J. See Stepanski, B.
Wertz, J. E., Orton, J. W., and Auzins, P. Spin resonance of point defects in magnesium oxide, B (9) 259*h*.
West, H. W. H., and Atkinson, C. R. Effect of the relative expansions and contractions of body and coating on the durability of roofing tile engobe, B (10) 300*b*.
West, J. B. See Martin, R. L.
West, R. Coloration of brick manufactured from limey clays, (2) 43*f*.
West, T. S. See Cabrera, A. M.
West Virginia Pulp and Paper Co. Mineral fiber mat formation, P (2) 42*h*.
Westbrook, J. H. See Kronberg, M. L.
Westbrook, J. H., and Stover, E. R. Method and alloy for bonding to nonmetallic refractory members, P (9) 249*g*.
Westeren, H. W. Resistance heating element for vacuum furnaces, etc., P (2) 54*a*.
Western Electric Co., Inc. Apparatus for finishing and mounting terminals on lamp bulbs, P (6) 157*d*. Apparatus for making electrical resistors, P (3) 77*a*. Deposition and measurement of layer thickness, P (3) 77*f*. Potassium-sodium niobate ceramics for transducers, P (6) 166*b*.
Westervelt, D. C. See Hofmann, C. F.
Westervelt, D. C., Vondracek, C. H., and Hofmann, C. F. Solid inorganic insulation for metallic conductors, P (2) 38*c*.
Westinghouse Electric Corp. Apparatus and [electrostatic] method for applying reflective coatings on unmasked portion of lamp envelope, P (10) 271*a*. Apparatus and process for forming high density compacts, P (9) 250*f*. Ceramic potting composition and method of encapsulating an electrical article therewith, P (6) 165*j*. Crystal growing process, P (2) 60*a*. Device for converting thermal energy into electrical energy, P (9) 248*h*. Electrical insulating coating composition, method, and coated article, P (9) 248*j*. Electroluminescent [breakdown protected] cell, P (1) 20*g*. Electroluminescent cell and method, P (1) 20*h*. Electroluminescent device, P (5) 135*g*. Electroluminescent phosphor, method of improving electroluminescent phosphor and electroluminescent lamp, P (5) 135*i*. Electroluminescent system, electrically nonlinear element, and method, P (5) 135*j*. Hermetically sealed [ceramic] semiconductor devices, P (4) 105*e*. High temperature electrical insulating tape, P (7) 190*h*. Light-transmitting, electrically conducting element, P (5) 136*i*. Magnetic stabilization-wound cores, P (5) 136*j*. Manufacture of articles from powdered materials, P (5) 138*a*. Method and apparatus for the fabrication of alloyed transistors, P (5) 136*d*. Method and apparatus for metering slurry, P (3) 80*c*. Method of improving electroluminescent phosphor, P (7) 193*i*. Method of improving electroluminescent phosphor and electroluminescent lamp, P (2) 49*a*, P (5) 136*d*, P (7) 193*g*. Preparation of junctions in silicon carbide members, P (3) 78*d*. Press sealing process and apparatus, P (5) 131*e*. Process for the preparation of thermoelectric elements, P (8) 220*i*. Producing diffused junctions in silicon carbide, P (7) 194*g*. Semiconductor dendritic crystals, P (9) 249*f*. Solid inorganic insulation for metallic conductors, P (2) 38*c*. Surface treatment [by electrolytic etching] of silicon carbide, P (6) 176*c*. Temperature indicating device, P (4) 108*b*. Thermoelectric elements, P (7) 194*c*. Thermoelectric material, P (5) 137*f*. Tray-loading apparatus, P (2) 51*i*.
Westley, H. See Meyrowitz, R.
Westlin, K. L. Dust separator, P (5) 138*h*.
Westman, A. E. R. Glass and ceramic research at Ontario Research Foundation, (7) 184*c*.
Weston, T. B. Electromechanical properties of three experimental lead zirconate lead titanate ceramic compositions, (11) 309*i*.
Westrick, M. L. See Gross, P.
Westrum, E. F., Jr. See Groenvold, F.
Westrum, E. F., Jr., and Grimes, D. M. Low temperature heat capacity and thermodynamic properties of zinc ferrites, (10) 294*f*.
Westwood, A. R. C. Fracture of MgO bicrystals, B (3) 91*f*.
Weyer, D. E. Method of preparing ceramic-like articles, P (9) 246*d*.
Weyl, D. See Bauer, W.
Weyl, P. K. See Chave, K. E.
Weyl, W. A. Contribution to the constitution of aluminosilicate and borosilicate glasses, (3) 66*e*. Fundamentals of the attack of glasses on refractory oxides, (8) 228*a*. Nucleation, crystallization, and glass formation, (1) 8*c*. See Tcheichvili, L.
Weyl, W. A., and Marboe, E. C. Constitution of Glasses—A Dynamic Interpretation (Vol. 1) Fundamentals of the Structure of Inorganic Liquids and Solids, B (10) 298*i*.
Weymann, H. D. Thermoviscoelastic description of the tempering of glass, (1) 10*a*.
Whatley, H. F. See Martin, T. R.
Whayman, E. See Arkless, K.
Wheaton, R. M. See Asher, D. R.
Wheeler, N. J. See Norreys, J. J.
Wheeler, R. W. Method for treating [laminated curved] glass sheets, P (9) 242*j*.
Wheeler, V. J. See Dell, R. M.
Wheelock, T. D., and Boylan, D. R. Reductive decomposition of calcium sulfate, P (8) 206*e*.
Wheildon, W. M. Wear resistant ceramic tooling in the fabrication of ceramic shapes, (6) 167*e*. See Johnson, R. L.
Whelan, J. M. See Fuller, C. S.
Whipple, E., and Wold, A. Preparation of stoichiometric chromites, (9) 256*g*.
Whitaker, L. R. Phosphatic waste materials for production of ceramic wares, P (10) 279*d*.
White, A. E. S., and Blakeley, T. H. Improvement of ceramics by incorporation of metals exemplified by nickel-magnesia, (4) 97*a*.
White, A. E. S., and Brown, D. W. Molybdenum-alumina cermets, P (6) 162*j*.
White, D. See Cowan, C. T.
White, E. A. D. See Doughty, D. C.
White, G. See Carson, F. J.
White, G. D. See Handwerk, J. H.
White, G. D., and O'Rourke, D. C. Method of making spherical actinide carbide, P (4) 102*e*.
White, G. L. Method of forming multiple strands from a single bushing, P (5) 131*i*.
White, H. G. See Lee, C. A.
White, J. Basic phenomena in sintering, B (4) 123*h*. Basic refractories—a survey of present knowledge, (6) 160*g*. Symposium on economics in the enamel shop: Introduction, (2) 37*e*. See Briggs, G.; Gadalla, A. M. M.
White, J. H., Jr. See White, M. G.
White, J. L. See Bronson, R. D.; Brown, C. B.
White, J. U. Optical apparatus employing diffraction grating, P (4) 121*h*.
White, J. U., and Cary, H. H. Apparatus employing stationary optical means and diffraction grating, P (4) 121*g*.
White, M. G., and White, J. H., Jr. Treatment of lateritic ores, P (9) 254*h*.
White, P. See Halleu, I.
White, R. Polyester resin joints—how to profitably use them, (9) 243*c*.
White Sewing Machine Corp. Apparatus for making a resin-bonded fiber glass cone [by casting], P (5) 130*b*.
Whitehead Brothers Co. Cellulosic additive materials for green sand molding, P (8) 215*g*. Green molding sand additive [starch], P (8) 216*h*. Methyl cellulose additive for green molding sand, P (10) 277*j*.
Whitehurst, H. B. Bearings with journal supporting elements of glass, P (5) 130*d*.
Whitehurst, H. B., Otto, W. H., and Warthen, W. P. Method and apparatus for metal coating glass filaments, P (5) 131*e*.
Whitehurst, H. B., and Warthen, W. P. Fiber production, P (6) 157*a*.
Whitelaw, R. L. See Schluderberg, D. C.
Whiteley, R. L. See Frame, J. W.
Whiteway, S. G. Density and permeability of sintered slip-cast magnesia, (7) 187*e*.
Whiting Corp. Hydraulic classifier, P (4) 106*h*.
Whitmore, B. C. See Humphries, J. J.
Whitmore, D. H. See Greener, E. H.; Janninck, R. F.
Whitmore, R. L. See Boardman, G.
Whitney, E. D. Effect of pressure on monoclinic-tetragonal transition of zirconia—thermodynamics, (2) 56*i*.
Whittaker, E. J. W. Relations between the crystal chemistry of pyroxenes and amphiboles, (10) 297*b*.
Whittemore, O. J., Jr. Process of making a nuclear fuel element, P (7) 190*a*.
Whittemore, O. J., Jr., King, A. G., and Logan, J. C. Molded alumina articles and process of making them, P (9) 244*j*.
Wiberg, O. See Tikkanen, M. H.
Wichers, E. See Cameron, A. E.
Wichmann, D. See Hentschel, E.
Wickham, D. G. Use of lead pyrophosphate as a flux for crystal growth, (5) 147*h*.
Wicks, C. E. See Stevenson, F. D.; Welty, J. R.
Widmann, H. Manufacture of oxide magnets, (7) 192*a*.
Wiebke, G. See Dohr, H.
Wiedes Carbidwerk Freyung m.b.H. High-melting mixtures of metals and oxides for abrasive purposes, P (3) 63*i*.
Wiegand, D. A. See Smoluchowski, R.
Wiegand, F. Luminescent and phosphorescent glass, P (3) 69*d*.
Wieland-Werke A. G. Composite mold for continous casting, P (2) 45*c*.
Wiemer, H., and Strepp, N. Molds made of porous carbon for handblown glassware, (7) 184*j*.
Wierig, M. J. Simple method of measuring the water vapor permeability of mortar and concrete, (9) 237*d*.
Wierman, E. T. See Jack, M. K.
Wigginton, R. J. Manufacture of titanium dioxide, P (3) 84*a*. Process for the manufacture of titanium dioxide, P (10) 290*c*.
Wigginton, R. J., and Leighton, J. Manufacture of titanium dioxide [with 0.5 to 5%(wt) Al_2O_3], P (5) 141*d*.
Wihsmann, F. G., and Solow, G. Porous glass, (1) 8*k*.
Wijn, H. P. J. See Gorter, E. W.
Wiker, R. M. Production of sulfate opal glasses, P (6) 158*d*.
Wilburn, F. W. See Warburton, R. S.
Wilburn, F. W., and Thomasson, C. V. Application of differential thermal analysis and thermogravimetric analysis to the study of the reactions between glassmaking materials (III) calcium carbonate–silica system, (1) 5*k*.
Wilcox, D. L., and Cook, R. L. Dielectric behavior in the systems $PbHfO_3$–$BaHfO_3$ and $PbHfO_3$–$SrHfO_3$, (9) 246*h*.
Wilcox, R. J., and Martini, R. W. Investment castings for advanced aircraft, (6) 159*i*.
Wildenhain, M. Pottery: Form and Expression, B (3) 92*g*.
Wilder, D. R. See Wirkus, C. D.
Wildi, B. S., and Katon, J. E. Thermoelectric device, P (2) 50*a*.
Wilhelm, H. Glass apparatus (IV) glass instruments for gas pressure measurement, (1) 6*i*; (V) most common glass instruments for gas analysis, (2) 39*d*. History of glassblowing, (1) 7*i*.
Wilk, G. See Hegemann, F.
Wilke, H. Measurement of heat quantities, (5) 140*e*. Measuring instruments for combustion control, (5) 140*e*.
Wilke, W. P., III, Nordyke, J. S., and Johnstone, J. O. Corrosion inhibitive pigment and method of making it, P (6) 170*g*.
Wilkins, R. L. Thermodynamic properties of some gaseous alkali halides, (1) 30*j*.
Wilkinson, A. L. See Drury, V. J.
Wilkinson, B., and Proctor, B. A. Development of defects on etched glass surfaces, (7) 184*j*.
Wilkinson, W. D. Uranium Metallurgy (Vol. I), Uranium Process Metallurgy (Vol. II), Uranium Corrosion and Alloys, B (4) 124*i*.
Wilkinson, W. T. See Dinsdale, A.
Wilkinson, W. T., and Sorrell, J. Note on the thermal shock resistance of bone-china cups, (11) 309*d*.
Wilks, R. S. See Clarke, F. J. P.; Robins, R. G.
William Boulton, Ltd. See Podmore, W., and Sons, Ltd.
Williams, A. E. Air separator for sizing refractory materials, (9) 250*h*.
Williams, A. L. W., and Gravley, C. K. Method of producing cellular ceramic electromechanical transducers, transducer materials, and elements, P (1) 21*b*.
Williams, C. B., Jr. See Boicey, J. H.
Williams, D. C. Factors involved in making a sand mixture, (8) 213*a*. Stickiness of molding and core sand mixtures, (8) 214*j*.
Williams, E. C., Reid-Jones, R. C., and Dorril, D. T. Physical properties and behavior in kiln of hard electrical porcelain as interpreted from density measurements, (11) 309*e*.
Williams, E. L. Diffusion studies in glass (I); (II) permeability in various glasses; (III) ionic diffusion in glass; (IV); Appendix, (9) 239*h*.
Williams, F. V. Process for preparing boron phosphide, P (10) 277*g*. See Gruber, B. A., Ruehrwein, R. A.
Williams, H. J. See Sherwood, R. C.
Williams, J. See Barnes, E.; Christie, G.; Livey, D. T.
Williams, J. C. See Sinclair, W. R.
Williams, J. C., Sinclair, W. R., and Koonce, S. E. Preparation of thin mullite films, (6) 165*c*.
Williams, J. R. Radiant cup gas burner, P (7) 197*a*.
Williams, J. R., and Santisi, H. C. Radiant cup gas burner, P (5) 140*f*.
Williams, K. L. Preparation of small powder samples from thin and polished sections, (6) 168*f*.

Williams, L. S. Fatigue and ceramics, B (3) 92*c*. Slip casting of calcium oxide, (7) 188*h*. See Adami, A.

Williams, M. Manufacture of apparatuses including thin magnetic films, P (10) 283*a*. Thin magnetic films create logic circuits, (7) 192*g*.

Williams, R. A. Method of manufacturing semiconductive device [by jet electrolytic etching], P (10) 283*b*.

Williams, R. M. Hammer mill [with traveling breaker plate], P (11) 315*g*. See Treffner, W. S.

Williams, W. C. See Davis, R. L.

Williams Patent Crusher & Pulverizing Co., Inc. Hammer mill [with traveling breaker plate], P (11) 315*g*.

Williamsen, E. J. See Kilby, J. S.

Williamson, G. K. Electron microscope studies of radiation damage in graphite, B (8) 233*g*.

Willis, W. H., Jr. See Marzocchi, A.

Willis, W. L. Encapsulated thermoelectric elements, P (2) 48*h*.

Wilmanns, F. See Rusche, H.

Wilms, W. See Scheffer, F.

Wilsdorf, H. G. F. Observations of dislocations, B (9) 259*f*.

Wilson, A., and Leary, J. K. Occurrence of cuspidine in phosphorus furnace slag, (4) 96*g*.

Wilson, A. D. Scheme for the quantitative analysis of a phosphate rock including the use of a benzoate separation, (5) 145*f*.

Wilson, A. D., Sergeant, G. A., and Lionnel, L. J. Determination of total sulfur in silicate rocks by wet oxidation, (9) 251*a*.

Wilson, A. G., and Solvason, K. R. Performance of sealed double-glazing units, (2) 40*g*.

Wilson, A. L. See Morrison, I. R.

Wilson, C. P., Jr., Ciapetta, F. G., and Elston, J. W., Jr. Process for preparing alumina gels, P (3) 84*c*, P (4) 111*b*.

Wilson, H. H. See Buckley, J. D.

Wilson, H. S. Development of the Canadian lightweight aggregate industry, (2) 43*i*.

Wilson, L.B. See Musschoot, A.

Wilson, R. C., and Koenig, C. J. Stability of forming characteristics of bodies containing nepheline syenite, (11) 309*c*.

Wilson, W. L. Method of preparing metal oxides, P (4) 111*c*. See Strain, F.

Wiltshire, A. J. Apparatus for making a resin-bonded fiber glass cone [by casting], P (5) 130*b*.

Wimberly, S. B. Indian pottery from Clarke County and Mobile County, southern Alabama, (4) 95*i*.

Winchell, H. Computer program for handling chemical analyses of amphiboles and other minerals, (6) 167*j*.

Windle, W., and Tonkin, R. J. Removal of impurities from fluxing materials for manufacture of ceramic or glass articles, P (2) 56*a*.

Winslow, F. R. See McGeary, R. K.

Winter, A. See Hampe, R.

Winter, E. Enameling aluminum, (5) 125*j*. Enameling steel, (5) 125*j*.

Winterkorn, H. F. Behavior of moist soils in a thermal energy field, B (5) 150*d*.

Winters, C. Blast-furnace linings, P (4) 102*c*.

Wintersberger, K. See Gruber, J.

Winyall, M. E. Process for preparing low surface area silica, P (4) 111*c*.

Wirkus, C. D., and Wilder, D. R. Uranium-bearing glasses in the silicate and phosphate systems, (1) 10*e*.

Wise, B. D. See Wong, R.

Wise, H. See Wood, B. J.

Wit, Roland de. Theory of dislocation—an elementary introduction, B (9) 259*f*.

Withers, J. C., and Childers, H. M. Coating large refractory metal parts, (6) 155*b*.

Wittels, M. C. Stored energy in the Oak Ridge graphite reactor, 1960, (10) 276*j*.

Wittels, M. C., Stiegler, J. O., and Sherrill, F. A. Radiation effects in uranium-doped zirconia, (10) 275*j*.

Wittenberg, L. J. See Eichelberger, J. F.

Wittke, J. P., Kiss, Z. J., Duncan, R. C., Jr., and McCormick, J. J. Uranium-doped calcium fluoride as a laser material, (7) 192*i*.

Wittmann, A. Extrusion in ring and disk dies, (10) 284*c*.

Witzig, E. Testing of the thermal shock resistance of stoneware, (10) 279*b*.

Witzke, H. D. See Kleber, W.

Witzmann, H., Buhrow, J., and Moeller, W. New luminophors with ultraviolet emission, (6) 164*h*.

Witzmann, H., and Mueller-Buschbaum, H. K. Contribution to the fluorescence of the rare earths, (6) 163*i*.

Witzmann, H., and Schreiter, H. Luminescence of copper- and copper-lead-activated strontium borate phosphors, (6) 164*d*.

Wodtcke, F., Liebau, F., and Bunge, H.-J. Reduction of $Ag_2Si_2O_5$ and the reduction products, (4) 120*a*.

Woelk, H. Process for the preparation of multipane insulating glass, P (10) 272*j*.

Woermann, E. Decomposition of alite in technical portland cement clinker, B (5) 148*j*.

Woerner, J. J. Ceramic metalizing process, P (1) 20*b*.

Wold, A. See Heller, G. S.; Whipple, E.

Wolf, E. Crystalline stone from slag, P (4) 96*g*. Manufacture of crystalline porous stones, P (7) 187*c*. See Yano, Y.

Wolf, N. H. Process for leaching of alumina from aluminous material, P (10) 289*j*.

Wolfenden, E. B. See Wall, J. R. D.

Wolff, E. A., Jr. See Cornelison, B.

Wolff, E. G., and Alcock, C. B. Volatilization of high temperature materials in vacuo, (3) 89*g*.

Wolff, F., and Sinta, T. Factors affecting the performance and aging of filament wound fiber glass structures, (4) 98*e*.

Wolff, H. S., and Roach, S. A. Apparatus for measuring dust particles [between predetermined limits], P (9) 252*e*.

Wolff, M. F. Advances in microminiaturization, (7) 190*j*.

Wolff, R. G. Structural aspects of kaolinite using infrared absorption, (11) 319*f*.

Wolfstirn, K. B. See Fuller, C. S.

Wolke, R., Zrimsek, A., and Vingas, G. Development of Canadian bentonite for Canadian industry, (3) 82*h*.

Wolkenstein, T. Effect of ionizing radiation on the adsorptive and catalytic properties of semiconductors, (8) 219*d*.

Wolkenstein, T., and Karpenko, I. V. Theory of photoadsorptive effect on semiconductors, B (9) 260*j*.

Wollenheit, L. Glass for esthetic decoration, (10) 265*j*.

Wolten, G. M. Diffusionless phase transformations in zirconia and hafnia, (10) 291*g*.

Wondratschek, H. See Merker, L.

Wong, R. Metallized glass fibers and method, P (3) 69*f*.

Wong, R., and Wise, B. D. Surface treated glass and similar fibers, P (2) 43*a*.

Wood, B. J., and Wise, H. Kinetics of hydrogen atom recombination on Pyrex glass and fused quartz, (9) 240*g*.

Wood, D. L. Some aspects of the tensile behavior of the intermetallic compound AgMg, B (3) 92*d*.

Wood, J. G. Pyrometer [radiation], P (2) 53*c*.

Wood, O. Quality control (I) introduction; (II) averages and ranges; (III) first examples, (3) 79*i*; (IV) sampling and control; (V) understanding curves; (VI) optimum sampling, (6) 167*i*; (VII) small samples, (10) 284*c*.

Woodburn, J., Jr. Insert [refractory] core for slide shut-off device, P (9) 244*c*. Process for producing a shaped graphite article, P (9) 245*f*.

Woodcock, E. L., Dueker, G. W., and Golay, M. J. E. Radiation pyrometer, P (10) 287*c*.

Woodcock, R. F., and Snitzer, E. Neodymium glass lasers, B (11) 320*g*.

Woodrooffe, H. M. Mineral reviews—industrial minerals, (10) 298*c*.

Woodruff, R. K. Refractory-forming products, P (9) 245*a*.

Woods, R. D. See Weir, A. H.

Wooley, S. E. Different processes in the production of Johns-Manville insulating firebrick, (2) 44*g*.

Woolf, D. O. See Grieb, W. E.

Worden, E. C. See Froemel, J. G.

Workman, G. M. Symposium on high-alumina refractories: High-alumina bricks in the roofs of continuous slab reheating furnaces, (11) 306*c*.

Worksman, P. See Evans, D. N.

Worthing, H. W. See Waring, C. L.

Woulbroun, J. M. See Kingery, W. D.

Wranau, G. von. Apparatus for production of glass fibers, P (3) 68*f*.

Wranau, G. von, and Phillips, C. J. Glass compositions, P (10) 272*a*.

Wranau, G. von, Phillips, C. J., Chappell, T. T., Lamb, R. J., Meanor, H. C., and Sproule, W. A. Glass compositions, P (10) 272*a*.

Wrenn, J. See Thiess, G. H.

Wright, D. A. Ettingshausen cooling in pyrolytic graphite, (10) 280*j*.

Wright, F. S. See Johnson, J. R.

Wright, H. R. See Lowther, D. R.

Wright, R. D. See Oldfield, L. F.

Wuensch, B. J. See Buerger, M. J.

Wuesterfeld, A. Shaped bodies consisting of minerals and a binder, P (4) 104*d*.

Wuhrer, J., and Krautwurst, H. Improvement of the storage stability of unburned shapes of sintered dolomite with a tar binder, P (4) 102*c*.

Wulff, J. Friction composition and method of making, P (4) 102*b*.

Wunnik, J. van, Dennis, J. S., and Phelps, G. W. Effect of temperature on slips and molds, (2) 47*b*.

Wygant, J. F. Pneumatic gun operating variables affecting castable refractories, (6) 160*a*.

Wykes, D. H. Cyclic mechanical properties of glass cloth reinforced polyester and epoxy resin laminates, (9) 239*e*. Evaluation of quartz cloth reinforced modified phenolic resin laminate, (9) 240*c*.

Wyllie, P. J., and Tuttle, O. F. System CaO–CO_2–H_2O and the origin of carbonatites, (1) 30*j*.

Wyman, R. A. Some recent development in industrial minerals beneficiation, (3) 83*f*.

Wynne, H. C. Manufacture of flat glass in continuous ribbon form, P (7) 186*g*.

Wyss, Escher, G.m.b.H. See Escher Wyss G.m.b.H.

Wytzes, S. Device for X-ray spectrochemical analysis by means of fluorescent radiation, P (2) 60*a*.

Yaggy, L. S., Koda, N. J., and Beintema, C. D. Two-color storage tube, (9) 248*d*.

Yakhimovich, D. F. See Barke, V. N.

Yalcin, A. S., and McIntosh, R. Some rheological parameters of clays and their thixotropic behavior, (3) 83*g*.

Yamada, H. See Oki, S.; Suzuki, H.; Terada, S.

Yamada, J., and Nakayama, N. Effect of tensile creep on compressive strength of concrete, (8) 204*f*.

Yamada, K. See Kajihara, H.; Nakayama, N.; Ota, E.

Yamada, M. See Okada, K.

Yamada, T. See Ozawa, U.

Yamada, T., Shimosato, T., and Nagai, S. Modification of crystal habit of gysum with ferric ion, (9) 236*j*.

Yamaguchi, G., and Kato, K. Solid solution in the system $3CaO \cdot SiO_2$–Al_2O_3–MgO, (7) 200*f*.

Yamaguchi, G., and Ono, Y. Microscopic characteristics of belite, (7) 199*i*.

Yamaguchi, G., Ono, Y., and Kawamura, S. Solid solubility of aluminum and ferric oxides in belite, (7) 200*h*.

Yamaguchi, G., Takemoto, K., Uchikawa, H., and Takagi, S. Rate of hydration of cement compounds and portland cement estimated by X-ray diffraction analysis, B (5) 149*b*.

Yamaguchi, G., and Uchikawa, H. Alite in portland cement containing different amounts of alkalis, (7) 178*c*.

Yamaguchi, G., Uchikawa, H., Takagi, S., and Koike, H. Influence of alkalis in clinker on the hydration of tricalcium silicate solid solutions in portland cement, (11) 302*c*.

Yamaka, E., and Sawamoto, K. Electrical conductivity of NiO near the Curie temperature, (3) 86*b*.

Yamamoto, K., and Tsuchiya, M. Electric characteristics of gamma-ray irradiated shielding window glass, (2) 39*g*.

Yamamoto, R. See Kato, S.; Nishimura, Y.

Yamamoto, R., Naito, R., Nishimura, Y., and Kato, S. Effects of the particle size of raw materials in porcelain manufacturing (VII) effect of comminution of feldspar and quartz on the mechanical strength of porcelain bodies; (VIII) effect of comminution of feldspar and quartz on the pyroplastic deformation, thermal expansion, and translucency of porcelain bodies, (8) 217*h*.

Yamamoto, R., and Nishimura, Y. Testing method for water absorption of ceramic products, (9) 252*e*.

Yamamoto, T., Hayashi, S., and Fujii, J. Physical, chemical, and mineralogical studies on clays for use as cement raw mix, (7) 181*f*.

Yamasaki, K. Flocculation of cement and other fine powders and its effect on the properties of paste and mortar, (8) 205*a*. Introductory notes on the ancient glass of Japan, (11) 301*h*.

Yamasaki, K., and Saito, Y. Investigation of corroded ancient glasses by X-ray diffraction, (11) 301*i*.

Yamashita, J. Oxygen band in magnesium oxide, (4) 117*h*.

Yamauchi, T. See Suzuki, H.

Yamazaki, T. See Imaoka, M.

Yanakawa, S. See Soda, T.

Yanchuk, R. A. See Mikhnevich, G. L.

Yang, J. C.-S. Growth of synthetic chrysotile fiber, (4) 114*b*. See Meyer, J. W.

Yannaquis, N., and Guinier, A. β-γ transformation of dicalcium silicate under pressure at ordinary temperature, (8) 203*j*.

Yano, Y., and Wolf, E. Temporal coherence of black body radiation, (5) 146*i*.

Yanovskii, Yu. S. See Galdina, N. M.

Yariv, A., and Gordon, J. P. Laser, (7) 191*f*.

Yashin, E. M. See Vergunas, F. I.

Yasins'kaya, G. A. See T'ai, S.

Yaskolko, V. Ya. See Krasnaya, A. R.

Yasuda, S. Manufacturing method of magnetic focusing equipment, P (7) 193*f*.

Yatabe, Y. Method of manufacturing a grinder or hone having fine cushiony surfaces, P (9) 236*d*.

Yates, P. C. See Alexander, G. B.

Yatsuzuka, T. See Tominaga, A.

Yearian, H. J. See Derbyshire, W. D.

Yee, T. B. Mechanism of adherence of porcelain enamel to metallic surface, B (11) 322*h*.

Yeh, T. H. Thermal oxidation of silicon, (1) 30*f*.

Yeo, R. H., and Waid, D. E. Air-heating gas burner, P (1) 24*j*.

Yerrick, W. B. Extruded ribbon of fireclay, P (10) 277*a*.

Yocom, K. H. See Tarpley, W. B.

Yocum, P. N. See Herkart, P. G.

Yoda, E. Anomalous growth of MoO_3 crystals, (6) 171*i*.

Yoder, J. B. Quartz lamp sealing machine control, P (6) 158*e*.

Yoganarasimhan, S. R. Studies on the brookite-rutile transformation, (5) 146*c*. See Rao, C. N. R.

Yoganarasimhan, S. R., and Rao, C. N. R. Mechanism of crystal structure transformations (III) factors affecting the anatase-rutile transformation, (10) 295*c*.

Yokota, I. Theory of mixed conduction with special reference to the conduction in silver sulfide group semiconductors, (11) 310*f*.

Yokota, I., and Miyatani, S. Low frequency characteristics of mixed conductors, (8) 219*a*.

Yokota, R., and Nakai, Y. Infrared absorption of antimonate glass, (11) 304*b*.

Yonemochi, O., Maeda, M., Hayashi, H., Okubo, T., Noguchi, C., and Kato, K. Study of fused magnesia (I) electrical resistance-temperature relation, (9) 244*a*.

Yoneyama, Y. See Maekawa, S.

Yong, R. N. See Warkentin, B. P.

Yoshida, H. Report on the use of the Meltz type open-hearth furnace (II), (11) 306*f*.

Yoshida, I., Nomura, S., and Sawada, S. Thermal conductivity of $BaTiO_3$ ceramics, (6) 175*e*.

Yoshida, M. See Hukuo, N.

Yoshida, T. See Fujii, J.
Yoshida, Z. See Rokunohe, M.
Yoshii, T., and Sudoh, G. Hydrothermal reaction and properties of reaction products in the system CaO–SiO_2–H_2O, (7) 180*a*.
Yoshinaga, H. See Mitsuishi, A.
Yoshioka, T. See Okazaki, K.
Yoshioka, T., and Okazaki, K. Forming of powder mixtures with special reference to the manufacturing process of cylindrical piezoelectric ceramic vibrators, (1) 19*f*. Manufacturing conditions of $(Pb,Sr)(Ti,Zr)O_3$ ceramics and their electrical properties, (3) 76*c*.
Yoshizaki, K. See Nagasaki, S.
Yoshizawa, Y. See Sugawara, A.
Youcil, R. F. Electrolytic method for producing chlorite-like substances from montmorillonite, (11) 317*g*.
Young, D. K. See Holt, P. F.
Young, F. F. Method of making bifocal lenses, P (4) 100*d*.
Young, G. H., and Cone, C. Furnace roller, P (4) 108*g*.
Young, H. Egyptian paste jewelry, (5) 125*j*.
Young, L. See Masing, L.
Young, W. A. See Doehler, R. W.
Yuasa, Y. Fluidization of fine particles packed in layer condition (I), (8) 221*e*.
Yudkovskii, S. I. See Funke, V. F.
Yund, R. A. See Kullerud, G.
Yung, V. N., Butt, Yu. M., and Timashov, V. V. Investigation of solid solutions of calcium aluminoferrites, (4) 115*f*.
Yung, V. N., Kuznetsov, A. M., and Radin, A. Ya. Argillaceous cement, P (2) 36*a*.
Yurachkovskii, P. A. See Kalabukhov, N. P.
Yurchak, I. Ya. Automation and complex mechanization in the porcelain-earthenware industry, (7) 190*c*.
Yuster, P. H. See Delbecq, C. J.
Yusupova, E. N. See Zubakov, S. M.

Zaceski, C. P. See Bussy, P.
Zacpal, Z. Apparatus for preheating finely divided material, P (4) 110*c*.
Zadneprovsky, J. A. See Bezborodov, M. A.
Zagar, L. State of knowledge of the texture of ceramic raw materials and products, B (4) 124*e*.
Zaidel, A. N., and Lazeeva, G. S. Photoluminescence of solutions and crystals of gadolinium salts, (5) 145*c*.
Zaitov, F. N. See Sidlyarenko, V. I.
Zakharikov, N. A., Naidenov, V. V., Blokh, S. A., Soldatov, G. A., Levitskii, V. K., Kuznetsov, V. V., and Spektor, M. P. Radiation gas drying of structural ceramics, (7) 196*e*.
Zaklad Badan i Doswiadczen Lekkich Tworzyw, High-strength autoclaved cellular concrete, P (2) 36*c*.
Zalm, P. See Lemmens, H. J.
Zamyatin, S. R. See Benediktova, N. B.
Zander, J. M., and Delott, R. Process of preparing a ferrous surface for one-fire porcelain enameling, P (6) 155*k*.
Zanon, D. See Trupiano, R.
Zara, M. H. See Liberthson, L.
Zarinskii, V. A. See Kargin, V. A.
Zarzycki, J., and Mezard, R. Direct electron microscope study of the structure of glass, (3) 66*i*.
Zavon, M. R. Methyl Cellosolve intoxication, (9) 258*a*.
Zavt, G. S., and Kristofel, N. N. Applicability of the Condon approximation to the luminescence center, (6) 163*f*.
Zeeb, L. E. See Rozsa, J. T.
Zehms, E. H. See McClelland, J. D.
Zehms, E. H., and McClelland, J. D. Semicontinuous hot pressing, (2) 45*c*.
Zeiss, C. Means for varying the picture brightness in an electron microscope, P (8) 230*d*.
Zelikin, Ya. M., and Paracheva, G. T. Characteristics of zinc oxide thermoluminescence, (6) 163*h*.
Zellers, J. T., Jr. Apparatus for feeding glass batch materials, P (6) 157*c*.
Zen, E-an. Mineralogy and petrology of the system Al_2O_3–SiO_2–H_2O in some pyrophyllite deposits of North Carolina, (4) 109*f*.
Zet, F. Production of extruded profiles from nonplastic corundum bodies, (10) 279*a*.
Zevin, L. S. See Berkovich, T. M.
Zgraggen, R. Colored chalk for marking on ceramics, P (3) 75*j*.
Zhdanov, S. P. Low-temperature dehydration of silica hydrates, (3) 67*d*. Reversible isotherms of adsorption of water on quartz, (1) 29*d*.
Zhikharevich, S. A., and Karaulov, A. G. Graphitic refractories for mold bottoms used in top pouring killed steel, (7) 187*e*.
Zhmud, E. S. See Ostapchenko, E. P.
Zhukovskii, A. P. See Ivanova, N. I.
Zhurakovskii, E. A. See Vainshtein, E. E.
Zhurina, V. S. See Serb-Serbina, N. N.
Zickefoose, E. J. Pouring spout and method of using, P (2) 46*g*.
Ziegler, G. E., Hayes, J. C., and Gaudin, A. M. Vermiculite concentration, P (5) 141*k*.
Ziegler, H. W. See Bielenberg, W.
Ziesche, D. Experiences with the industrial enameling of aluminum, (10) 269*b*.
Zil'berman, G. E. See Kulik, I. O.
Zil'bershtein, Kh. I., Piryutko, M. M., Evtushenko, T. P., Sakharnova, I. L., and Nikitina, O. N. Spectral analysis of high-purity silicon, (4) 120*b*.
Zimmer, F. New ways to bond dissimilar materials, (7) 183*j*.
Zimmerman, D. L. See Holden, A. N.
Zincke, A., and Marcic, B. Technology of Glass Seals with an Outline of the Technology of Vacuum Tight Ceramic Metal Brazing in Electronics, B (4) 124*h*.
Zintl, G. See Schneider, A.
Zirconal Processes, Ltd. Electric arc furnaces, P (2) 45*e*. Method of manufacturing composite refractory objects, P (3) 74*c*.
Zlatkin, S. G. See Mamykin, P. S.
Zlotnick, H. Ceramic dielectric compositions and method of making them, P (6) 165*h*.
Zoellner, H. Sintering of fine-grained minerals, P (4) 111*f*.
Zollweg, R. J. Optical absorption and photoemission of barium and strontium oxides, sulfides, selenides, and tellurides, (4) 117*e*.
Zoltai, T. See Papike, J. J.
Zoltanski, E. F. Light source for photoelectric inspection of glassware, P (4) 100*b*.
Zonolite Co. Method of exfoliating vermiculite, P (3) 84*c*. Vermiculite concentration, P (5) 141*k*.
Zoranski, H. J. See Lloyd, E. C.
Zrimsek, A. See Wolke, R.
Zsoka, L. T. See Clauson, W. E.
Zubakov, S. M., and Yusupova, E. N. Composition and properties of chromite ores from new sources in Kazakhstan, (7) 197*e*.
Zubatova, I. N. Once-firing of porcelain ware made by hot casting under pressure, (7) 190*g*.
Zuev, K. P. Electrical conductivity of Cu_2O during its dissociation (1070° to 1250°C), (7) 191*f*. Electrical conductivity of Cu_2O in its stabilization region in air (1020° to 1070°C), (7) 191*g*.
Zumwalt, L. R. See Ragone, D. V.
Zussman, J. See Deer, W. A.
Zvonarev, A. V. See Aleksandrovich, E.
Zwetsch, A. Measurements of expansion in kaolin and clay parallel and perpendicular to the plane of the lamellas, B (10) 300*b*.
Zwilsky, K. M. See Grant, N. J.

SUBJECT INDEX TO CERAMIC ABSTRACTS FOR 1963

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates position on the page. For more complete indexing of papers published in the *Journal of The American Ceramic Society* and the *American Ceramic Society Bulletin*, see indexes to the *Journal* and the *Bulletin*.

Abbe number, of La borate glass, (11) 304*f*.
Abbreviations, in Russian abstract journals, (5) 148*b*.
Ablation, characteristics, of glasses, glass-reinforced plastics, graphite, and Teflon, (1) 7*g*.
of glassy material around blunt bodies of revolution, (1) 5*d*.
recent advances, (1) 8*e*.
refractory fibers for, (6) 160*c*.
theory and flight data compared, (6) 156*c*.
Abrasion, resistance, of alumina silica refractories, relation to apparent porosity and Shore hardness, (1) 15*d*.
of glazes, apparatus for determining, (3) 75*d*.
of metal press molds for refractory products, (7) 188*f*.
-resistant materials, selection and performance in mining and quarrying industries, (9) 254*h*.
-resistant molded bodies, P (6) 162*i*.
Abrasives. See also *Alumina; Carbides; Diamonds; Grinding and polishing apparatus; Silicon, carbide.*
articles, of bonded pyramidal bodies, P (1) 1*j*.
articles, steel sheet with WC grit surface, P (9) 236*e*.
bands, apparatus for skiving to form belts, P (9) 236*a*.
in barrelling chips, P (9) 236*a*.
n bearing industry, (2) 33*e*.
belt, sectional coated, P (1) 2*b*.
bonds, antiweld additives for, P (2) 33*h*.
ceramic whiteware, manufacture of, (1) 1*f*.
coated, cutting cost of, (3) 63*e*.
coated, development of resins in, (2) 33*f*.
coating for, P (9) 236*b*.
in comminuting apparatus, P (2) 55*a*.
cutting devices, P (1) 1*g*.
diamond cutting devices, P (11) 301*g*.
with diamond and thermoset resinoid, P (7) 177*g*.
disks, cut-off, P (4) 95*f*.
with noncircular backup pad, P (2) 33*g*.
packaging of, P (1) 1*j*.
with threaded inserts, P (4) 95*f*.
drilling apparatus, with telescoping divergent discharge nozzle, P (5) 138*f*.
grains, in bonded abrasive products, I, II, (9) 235*f*.
in coated abrasive manufacture, I, (10) 265*h*.
history and production, (9) 235*i*.
in manufacture of coated abrasives, II, (11) 301*f*.
of natural bauxite, P (6) 153*f*.
physical and chemical properties, II, (8) 203*i*.
silane coated, for improving wet strength of resinoid wheels, (5) 125*f*.
granulated, P (2) 33*f*.
in grinder or hone with fine cushiony surfaces, P (9) 236*d*.
grinding balls, P (3) 63*f*.
grits, factors affecting resistance to wear, (5) 125*f*.
hard, of B and Si, P (1) 1*i*.
hardness and wear, machine for testing, P (4) 108*e*.
high-melting mixtures of metals and oxides for, P (3) 63*i*.
machining, requirements for, (5) 125*h*.
manufacturers, in promotion of grinding wheel use, (8) 203*e*.
materials, P (4) 95*g*.
materials, in 1961, (1) 25*d*.
with mineral binders for wet grinding steel and iron, P (4) 95*g*.
particles, testing of toughness of, (3) 63*h*.
refractory, from ZrB_2, P (8) 216*g*.
rotary devices, segment for, P (1) 2*a*.
suspension in water for grinding and polishing composition, P (1) 1*g*.
synthetic, crushing resistance of, B (10) 300*g*.
industry in Canada, (3) 63*h*.
relative measurement of crushing resistance, (10) 265*f*.
with synthetic resins as binders, P (3) 63*g*.
ultrasonic liquid machining apparatus, P (10) 265*h*.
vitrified bonded, structure and properties, (6) 153*g*.
wheels. See *Grinding and polishing apparatus.*
Absorption, bands, of latent image centers in photosensitive glasses, (5) 128*f*.
characteristics, of ball clay minerals, (8) 225*e*.
edge, optical, of WO_3 single crystal, temperature dependence, (5) 146*f*.
of electromagnetic wave energy, material for, P (10) 282*i*.
far infrared, of ferrites, (6) 173*e*.
Absorption *(continued)*
of fine lightweight aggregate, determination by testing techniques, (10) 266*g*.
of γ-radiation and neutrons, ceramic structural materials for, (10) 274*a*.
γ-ray and neutron, of concretes, (10) 266*h*.
of gases, vapors, and fumes, vermiculite in, (2) 54*h*.
infrared, of antimonate glass, (11) 304*b*.
in checking coordination, (5) 147*g*.
frequency trends for anhydrous normal carbonates, (6) 173*i*.
and structure of glasses, (1) 7*b*.
and structure of glasses, correction, (8) 209*b*.
in study of kaolinite structure, (11) 319*f*.
liquid-phase, activated carbons for, (11) 314*g*.
of materials and coatings, determination, (8) 222*j*.
in modulation of ruby laser output, (7) 192*c*.
optical, of Ba and Sr oxides, sulfides, selenides, and tellurides, (4) 117*d*.
of Cl_3^- molecule ions in irradiated KCl, (4) 117*b*.
by F centers in alkali halides, (4) 117*c*.
fundamental, in MgO, (3) 86*g*.
in MgO crystals, (3) 88*a*.
in single-crystal SiC, (4) 115*d*.
of small thickness, means for measuring, P (3) 81*e*.
of Na silicate and Na borate glasses, ligand field theory of, (7) 184*b*.
selective, of Freons, synthetic zeolite for, P (6) 171*e*.
of AgBr doped with divalent anions, (3) 85*h*.
of AgCl crystals doped with divalent cations and anions, (3) 85*f*.
solar energy, inorganic films for, (10) 269*d*.
spectra. See *Spectra.*
ultraviolet, of glass, effect of composition and temperature, (8) 208*j*.
optical, of MgO, effect of O on, (9) 256*d*.
of X-rayed KCl crystals, (5) 147*e*.
water, of building bricks, rapid measurement, B (10) 300*b*.
water, of ceramic products, test for, (9) 252*e*.
Acetylene, production at room temperature from La and Ce carbides, (1) 28*e*.
Acidity, of oxides, process for reducing, P (2) 55*e*.
Acids. See also specific types.
-base reactions, in silicate melts, (1) 26*f*.
citric, set-retarding effects in cement, (10) 267*b*.
coal, as retarders of set of aqueous gypsum compositions, P (2) 36*a*.
earth, recovery from slag, P (11) 315*f*.
malonic, for simultaneous determination of Ti and Fe, (11) 313*c*.
metatitanous, purification by high-voltage electrodialysis, (7) 197*j*.
molybdosilicic, α- and β-, formation, stability, and reduction, (9) 250*g*.
nitric, for leaching of optical glass surfaces, I, (8) 209*i*.
phosphoric and sulfuric, metastability of gypsum hemihydrate in, (2) 35*f*.
resistance, of enamels, test for, (9) 238*j*.
salicylic, on cement, adsorption isotherms for, (10) 266*c*.
silicic, colloidal, manufacture and stabilization, P (7) 186*f*.
solution of glass fiber in, (10) 270*i*.
Acoustics. See also *Insulation, acoustical; Sound.*
in measurement of volume, P (5) 130*i*.
microwave delay line, P (4) 105*i*.
Actinide, carbide, spherical, P (4) 102*e*.
Adherence. See also *Enamels.*
nature of, in glass-to-metal bonding, (2) 57*f*.
Adhesion, of flame-sprayed coatings for Army weapons, (10) 268*j*.
of low temperature glass, measurement of, (10) 271*c*.
measurements, on small particles, (9) 250*j*.
of mortar to wall tile, (3) 75*d*.
Adhesives, adherence to glass, coatings for improving, (9) 240*c*.
Ba tetraphosphate, in lamp envelope, P (2) 42*c*.
ceramic, for high temperature bonds, (1) 4*i*.
epoxy, in bonding Teflon to metal, glass, and ceramic, (9) 258*a*.
exo-reactant inorganic, (8) 206*i*.
for glass, (1) 5*d*.
high temperature, materials for, (10) 269*d*.
for quartz glass, (5) 134*c*.
silicate, for water resistant laminates, P (9) 246*f*.
structural, high temperature, research and development of, (8) 207*h*.
on tile backs and edges, P (8) 218*c*.
Adsorption, of admixtures on portland cement, (10) 266*c*.
Adsorption *(continued)*
of Cs on clay minerals, (6) 169*g*.
of dyes by clay minerals, (6) 169*h*.
of ethylene glycol and glycerol by montmorillonite, (4) 107*b*.
gas, for rapid comparison of specific surface areas, (11) 313*b*.
of glycine and di-, tri-, and tetra-peptides by montmorillonite, (10) 290*f*.
of phosphate ion by hydrous ferric, chromic, and Al oxides, I, II, (3) 85*h*.
of phosphate by X-ray amorphous "Al hydroxide," (5) 145*j*.
of phosphorus in Manitoba soils, (5) 140*h*.
on semiconductor surfaces, (11) 309*h*.
of water on quartz, reversible isotherms of, (1) 29*d*.
of water vapor on porous glass fiber, (10) 270*g*.
of xenon and argon on graphite, (4) 100*i*.
Aeration, of granular materials, supports for, P (11) 312*f*.
Aerogels. See *Silica.*
Afterglow. See *Luminescence.*
Afwillite, as product of system CaO-SiO_2 gel-H_2O at 110°C, (4) 119*i*.
Agglomeration, spherical, process of, (1) 23*d*.
Aggregates, in concrete, shrinkage of, (10) 267*h*.
finest grain size fraction, effect on sulfate corrosion of cement mortars, (7) 180*c*.
granular slag, preparation, P (10) 268*b*.
lightweight, development of Canadian industry, (2) 43*i*.
fine, determination of absorption by testing techniques, (10) 266*g*.
method of making, P (2) 44*a*.
New Hampshire raw materials for, (8) 225*j*.
new horizons in, (8) 211*j*.
plant capacity, (6) 158*i*.
plant operations, (9) 243*a*.
production in new plant, (6) 159*b*.
for structural concrete, (11) 302*h*.
use of glacial lake and marine clays from Maine, (4) 109*b*.
metal-, product, P (2) 46*b*.
mineral, ASTM standard for, B (9) 259*b*; B (10) 298*h*.
shale, expanded plant, (6) 158*j*.
siliceous substitution of limestone in, (8) 205*b*.
veriform, in Pensauken formation of New Jersey, (4) 109*j*.
zeolite, synthetic crystalline, method of producing, P (11) 315*c*.
Aging, effect on soluble salts in Ti enamel frit, (6) 155*h*.
of ferroelectrics, (1) 19*b*.
of filament wound fiber glass structures, factors affecting, (4) 98*e*.
of porcelain bodies, for increasing green strength, (10) 278*e*.
Air, clean, in ceramic factories, (3) 90*d*.
compressed, contaminants in, (2) 50*j*.
compressor, selection of, (2) 51*d*.
cost of, effect of leaks on, (4) 106*f*.
displacement, porosity measurements by, (11) 313*d*.
entrained, effect on properties of mortar, (7) 180*f*.
entrapped in cement mortar, (8) 204*b*.
flow rate, effect on C-O_2 and Co-O_2 reaction, (6) 160*d*.
forced secondary, use in hand-fired kilns, (6) 169*e*.
hot, high velocity, for drying brick, (6) 167*c*.
pollution, copper oxide-alumina catalyst for control of, (3) 79*d*.
pollution, problems in combustion control, (5) 140*e*.
sampling, fine glass fiber paper for, (3) 90*e*.
Aircraft ceramics. See also *Cermets; Space vehicles; Turbines.*
glass, for high-speed craft, (1) 10*f*.
investment castings for, (6) 159*i*.
windshields, electrically conducting glasses for, P (6) 157*j*.
Akermanite, synthesis from molten PbO, (9) 257*h*.
Albite, crystallization of volcanic glass to, (11) 315*j*.
decomposition in hot water, (5) 142*a*.
solutions, hydrolysis of, (7) 199*e*.
Alcohol, vapor, effect on determination of fineness of cement by air elutriation method, (7) 179*j*.
Alite, in portland cement containing different amounts of alkalis, (7) 178*c*.
standard sample preparation, (7) 181*f*.
structure, determination of uniformity, (3) 64*f*.
Alkaline earths. See also specific types.
carbonates, firing and sintering of, P (3) 76*a*.

Alkaline earths (*continued*)
fluoride, production of stable coagel from, P (1) 26*d*.
metaniobates, monocrystals, Verneuil's method, B (9) 263*e*.
as modifier in optical glass, P (3) 70*b*.
rapid analysis with flame photometer, (8) 223*c*.
Alkalis. See also specific types.
in cement, effect on air content, (8) 204*b*.
in cement clinker, effect on hydration of tricalcium silicate solid solution in portland cement, (11) 302*c*.
determination with flame photometer and filters, (8) 222*g*.
effect on alite in portland cement, (7) 178*c*.
effect on hydration of tricalcium silicate, (7) 180*g*.
rapid analysis with flame photometer, (8) 223*c*.
systems. See *Systems*.
Allophane, reaction with solution containing Ca(OH)$_2$ and gypsum, (7) 181*f*.
Alloys, Al, fabricating of, I, II, (4) 97*g*.
binary U-Zr or Zr-base, dissolving process, P (1) 17*e*, *f*.
for bonding to nonmetallic refractory members, P (9) 249*g*.
Colmonoy, in glass bottle manufacturing, (4) 98*i*.
Pb-based, bonding to silicates, P (6) 165*f*.
TiC-WC-Co, structure and physical and mechanical properties, (2) 59*a*.
Alumina. See also *Aluminum, oxide; Boehmite; Corundum; Refractories*.
abrasive grains, in grinding wheel, P (10) 265*g*.
in acid refractory materials, increase of, (10) 274*d*.
α-, fibrous anhydrous, preparation, P (6) 162*b*.
radiation effects in, (8) 229*j*.
reactor-irradiated, (3) 89*g*.
refinement of crystal structure, (4) 120*d*.
single crystal, thermoluminescence and effect of γ-ray induced defects, (5) 147*b*.
Alucer MC, polycrystalline sintered compacts, deformation of, (8) 230*c*.
in aluminosilicates, accurate volumetric determination, (5) 141*i*.
applications and properties, (9) 258*b*.
arc-plasma flame melting, (8) 213*f*.
as base in ceramic body, P (8) 218*b*.
β-, role in fused cast refractories in glass tank superstructures, (2) 40*h*.
β-, trihydrate, preparation, P (9) 254*e*; P (10) 289*f*.
brown electrofused abrasive grains, lattice contraction rate of corundum of, (9) 235*f*.
calcined, removal of ionic impurities from, P (5) 141*d*.
-carbon compositions, for cutting metals and alloys, P (2) 33*g*.
ceramic, body, metallizing coating for, P (1) 20*b*.
ceramics, control of dielectric constant and loss in, correction, (6) 163*j*.
effect of composition and crystal size on metal-to-ceramic bond strength, (3) 76*d*.
metallizing of, P (5) 136*e*.
microscopy technique for, (4) 101*e*.
moly-manganese metallized, in semiconductors, (10) 280*c*.
properties and uses, (11) 306*a*.
clays of N. Dak. as potential source, (3) 82*e*.
coatings, properties and uses, (6) 155*c*.
as commercial abrasive, (8) 203*i*.
complexometric titration, (1) 28*g*.
in composite coatings, (8) 207*d*.
of controlled density, P (8) 225*d*.
of decreased pore size, preparation, P (10) 289*d*.
device, sealing method for, P (8) 220*e*.
dies, hot-pressing ceramics in, (10) 284*h*.
exothermal effects on metakaolinite, (10) 296*j*.
extraction from Hawaiian ferruginous bauxites, (1) 25*i*.
fibers, method of preparing, P (10) 277*g*.
films, in emitter cells, (5) 134*g*.
flame sprayed, uses for, (7) 183*e*.
foam, thermal and mechanical testing, (8) 215*i*.
fused, in stable aqueous suspensions, P (3) 90*a*.
gels, method of making, P (3) 84*e*.
high density process, sintering kinetics for, (1) 29*g*.
as high temperature pressure sensitive solid state materials, P (11) 311*g*.
hot-pressed, end-point density, (4) 113*f*.
hot-pressing of, mechanisms of material transport, (10) 293*d*.
hydrated, and α-, solid state reaction study with nitrates of Ni and Co, (1) 30*b*.
leaching from aluminous material, P (10) 289*j*.
low-soda, production of, P (9) 254*g*.
molded articles, hard wear-resistant, P (9) 244*j*.
monohydrate, fibrous, production process, P (2) 46*b*.
occurrence, crystal forms, production, properties, and uses, B (2) 61*i*.
polycrystalline, creep of, (9) 255*c*.
pressure sintering, mechanisms and microstructures, (11) 318*c*.
production from bauxite, by pyrogenic attack, P (3) 84*j*.
production from clay, evaluation of HCl processes, (6) 170*c*.
production from clay, sulfuric acid processes, (9) 254*e*.
pure, refractory materials from, P (3) 74*i*.
in reaction series of gibbsite heated in air, I, II, (4) 119*g*.
recovery from nepheline concentrates, P (2) 55*j*.
reduction by C in liquid iron, (1) 14*d*.
reduction cells, refractory lining for, P (9) 245*c*.
Alumina (*continued*)
region, in ternary aluminosilicate systems, II, III, (3) 89*e*.
with silicate structure, modification of, B (10) 300*g*.
single-crystal, high-temperature electrical conductivity of, (10) 280*d*.
single crystals, chemical polishing and etching techniques for, (6) 167*h*.
sintered, in ceramic tooling of ceramic shapes, (6) 167*e*.
etchant for, (11) 313*a*.
hard materials from, P (3) 75*a*.
sintering of, I, II, (7) 200*c*.
systems. See *Systems*.
translucent, strength at 3600°F, (9) 254*h*.
transverse bend strength, effect of grain size on, (7) 198*j*.
variations in ceramic properties, (2) 54*b*.
whiskers, twist in, (2) 59*e*.
Aluminates, sinters, role of sodium ferrite in extraction, (4) 120*f*.
Aluminides, in coating for large refractory metal parts, (6) 155*c*.
Aluminosilicates, accurate volumetric determination of Al_2O_3 in, (5) 141*i*.
analysis of, (3) 80*e*.
control analysis by spectrophotometric method, (3) 81*c*.
flame spectrometric determination of Fe_2O_3, CaO, MgO, and K_2O in, (10) 286*d*.
gels, ionic coordination in relation to clay mineral formation, (4) 115*j*.
systems, study of alumina region, II, III, (3) 89*e*.
X-ray diffraction of phase transformations in, (4) 118*b*.
Aluminum, alloys, fabricating of, I, II, (4) 97*g*.
alloys, surface preparation for enameling, P (4) 97*j*.
^{27}Al, quadropole splitting in spinel and corundum, I, II, (4) 119*c*.
arsenides and phosphides, method of making, P (10) 283*b*.
beryllium boride, preparation and structure, (5) 145*f*.
borate, fibrous, preparation, P (6) 162*b*.
crystals, large, method of making, B (9) 263*d*.
for decolorizing Mn glass, (6) 156*d*.
diboride, formation and stability, (4) 114*i*.
effect of clay decomposition on, (5) 142*j*.
enameled, in building construction, (10) 268*j*.
enameling, industrial, technology and quality testing, (10) 269*b*.
fluorides, preparation, P (3) 83*c*.
producing of, P (2) 55*f*.
reaction of kaolinite with, formation of amorphous metaphase, (10) 292*g*.
formation of enamel coatings on, B (11) 322*g*.
and fuel-bearing glass fiber compacts, radiation stability of, (9) 241*f*.
hard enamel for, P (10) 269*b*.
hydroxides, precipitation from aluminate solutions and aluminum salts, (4) 112*j*.
industry, chlorination of red mud from, (11) 314*h*.
ions, coordination of, in soda aluminosilicate glasses, (2) 40*g*.
ions, as replacement of K^+ ions in muscovite, (5) 146*e*.
in melting furnace refractory, P (6) 161*i*.
molten, in treatment of BN crucible, P (3) 74*c*.
nitride, analysis of dislocations in, B (9) 262*a*.
process of making, P (9) 245*b*.
in refractory materials, (6) 159*e*.
single crystals, growth and morphology, (4) 114*j*.
use in piezoelectric devices, P (9) 249*c*.
orthophosphate, melting of, (7) 183*h*.
oxide. See also *Alumina*.
abrasive grain, manufacture of, (6) 153*f*.
anodic films, dielectric properties, (9) 246*i*.
in bonded abrasive products, (9) 235*f*.
dense, in capacitor, P (8) 220*d*.
effect on adsorption of phosphate ion, (3) 85*h*.
effect of grain boundaries on diffusion-controlled processes in, (5) 142*i*; correction, (10) 292*d*.
fineness, control by use of specific surface measurements, (9) 252*j*.
fused crystals, emission spectrographic analysis of, (1) 27*f*.
-Mo silicide, for refractories, P (6) 162*d*.
and hydroxides, study under electron microscope, (4) 113*i*.
method of making, P (3) 84*a*.
phase equilibria with B oxides, (8) 229*f*.
solid solubility in belite, (7) 200*h*.
thermal expansion tests, (10) 276*c*.
-Ti_2O_3, solid solution, (3) 85*i*.
translucent, as window for visible, infrared, and microwave energy, (7) 191*b*.
in wear-resistant cermets, P (3) 75*b*.
phosphate, as bond in silica brick, (8) 214*i*.
photometric-complexometric determination in silicates, (3) 80*f*.
pretreatment for enameling, (10) 269*i*.
reduction cell, cathode bar for, P (8) 215*f*.
in refractory material for thermocouple protection, (10) 276*f*.
silicate, dehydrated, synthetic crystalline zeolite from, P (3) 85*a*.
fibers, in refractory product, P (9) 244*i*.
separation from beach sand, P (10) 289*c*.
sintered, composition, P (6) 162*i*.
sulfate, production from clay, P (6) 171*b*.
systems. See also *Systems*.
systems, phosphate reactions in, I, II, (5) 145*j*.
in ternary carbides of transition metals, (4) 101*h*.
white enamel for, P (2) 38*f*.
American Society for Testing and Materials, book of standards, including tentatives, 1962 supplements, Parts 1–5, 8, 10, 11, B (9) 259*a*.
standards on mineral aggregates and concrete, B (10) 298*h*.
Americium, separation from rare earth elements, P (6) 176*a*.
tetravalent, crystalline fluoride complex, (1) 27*f*.
Amines, aliphatic, as molding aids for ceramic powders, (8) 217*d*.
Ammonia, health damage from, (7) 202*b*.
reaction, in preparation of anhydrous $MgCl_2$, P (9) 254*d*.
in synthesis of TiN, (5) 146*i*.
Ammonium, diuranates, infrared spectra and structures of, (9) 256*a*.
nitrate, products, use in underground limestone mines, (10) 288*d*.
paratungstate, thermal decomposition of, (4) 120*h*.
metavanadate, preparation, P (3) 84*g*.
sulfate, in beneficiation of titania ores and slags, P (2) 55*g*.
Amphiboles, chemical analyses of, computer program for, (6) 167*j*.
crystal chemistry of, (10) 297*b*.
fluor-, synthetic fluor-magnesio-richterite, (7) 201*h*.
infrared spectra of, (5) 147*f*.
rapid determination of approximate composition, (4) 107*g*.
Analcites, ion-exchanged, dielectric properties of, (8) 219*a*.
self-diffusion of Na ions in, (11) 319*d*.
Analysis. See also *Chromatography; Colorimetry; Electron diffraction; Microscopy; Particles; Photometry; Quality control; Screens and sieves; Spectrography; Spectrometry; Spectrophotometry; Spectroscopy; Testing; Thermal analysis; Thermodynamics; Thermogravimetry; Titration; X rays*.
absorptiometric, for determining Si in water, III, (10) 285*i*.
of ceramic materials, accurate method, (3) 80*e*.
chemical, of argillaceous rocks, recalculation for comparative purposes, (6) 170*i*.
of basic slag, I–III, (5) 139*f*.
of fluoride-opal glass (Standard Glass No. 4), (2) 38*j*.
of glass, use of X rays in, (9) 241*d*.
of minerals, computer program for, (6) 167*j*.
of chemical sample for oxygen by radioactivity, P (9) 252*d*.
chromatographic, of multicomponent vapor, P (4) 121*j*.
complexometric, of silicate rocks, (9) 252*h*.
of continuous cement slurry stream, (2) 34*c*.
control, of high-silica and aluminosilicate materials, spectrophotometric method, (3) 81*c*.
dimensional, of models of glass tanks, (7) 184*c*.
fluorescent X-ray spectrographic, of amphibolite rocks, (4) 114*d*.
gas. See *Gases*.
mechanical, of soils, pipetting assembly for, (5) 139*d*.
methods, for ZrO_2 and Si-Si refractories, (8) 212*d*.
microspectrochemical, of minerals, I, (4) 107*c*; II, (6) 168*c*.
milli- or micro-, B (2) 60*j*.
photometric-complexometric, in determination of Al and Fe in silicates, (3) 80*j*.
pipet, comparison of techniques, (11) 312*j*.
quantitative, gasometric, of calcite and dolomite, use of Chittick apparatus, (3) 81*b*.
of minerals in process of forsterite synthesis, (1) 18*a*.
of phosphate rock, (5) 145*f*.
spectral, of minerals, method, (4) 119*e*.
semimicro, of silicate rocks for Ca, Fe, Mg, and Al employing EDTA, (3) 83*f*.
semiquantitative, of chlorites by X-ray diffraction, (6) 168*j*.
of soluble salts in clays, (2) 56*b*.
spectral, of high-purity Si, (4) 120*b*.
spectrochemical, for determining B in Si compounds, (9) 252*a*.
of nonmetallics, direct-reading semiquantitative, (1) 27*h*
of rocks, minerals, and related materials, (1) 30*e*.
X-ray, by means of fluorescent radiation, device for, P (2) 60*a*.
spectrographic, of ream knots in glass, (8) 209*e*.
statistical, binomial, Poisson, and Gaussian model distributions, (10) 298*e*.
of effect of length on strength of glass fibers, (9) 240*d*.
of factors affecting glass fiber strength, (9) 241*h*.
of fracture in concrete, II, (9) 237*g*.
in micrometrics, (5) 139*e*.
theoretical, of extrusion processes, (11) 312*b*.
Analyzers. See also *Gases*.
chromatographic, programmer-integrator for, P (1) 24*e*.
high temperature differential thermal, P (8) 224*a*.
for measurement of flux of neutrons, P (3) 69*i*.
microchrome, with photosensitive glass plate, P (5) 131*g*.
process stream, (1) 23*j*.
Anatase, -rutile, transformation, effect of SO_3, (7) 199*a*.
-rutile, transformation, factors affecting, (10) 295*c*.
structure, comparison with rutile, (10) 290*f*.
transformation to rutile, kinetics and thermodynamics of, (11) 318*b*.

Andalusite, in Georgia, mineral characteristics, locations and usages, (3) 82*e*.
stability compared to kyanite and sillimanite, (4) 118*e*.
structure, in compounds in system Al_2O_3-Fe_2O_3-GeO_2, (8) 226*g*.
Anelasticity, of glasses, correction of original paper, (8) 209*c*.
Anhydrite, hydration, mechanical phenomena in, (8) 206*d*.
insoluble, transformation of Ca sulfate hemihydrate to, (5) 147*d*.
solubility in water, determination with hydrothermal solution equipment, (5) 147*f*.
Anions, divalent, effect on absorption and photochemistry of AgCl crystals, (3) 85*f*.
divalent, effect on absorption of AgBr crystals, (3) 85*h*.
Anisotropy, constant, magnetic, of Y Fe garnet at 0° K, (3) 87*c*.
crystalline, of Mn-Zn-ferrous ferrite, (9) 247*j*.
of elastic properties of WC, (2) 56*d*.
of electric conductivity of semiconductors, measurement by 4-probe method, (7) 192*a*.
of evaporated iron films, effect of crucible materials, (10) 274*e*.
of Fe-Ni ferrite single crystals, angular dependency, (3) 85*h*.
magnetic, of evaporated Permalloy films, effect of crucible material on, (5) 132*h*.
of ferrimagnetic oxides, effect of Co^{2+} ions, (5) 144*g*.
generation in ferrites by thermomechanical treatment, (3) 86*i*.
in Ni-Fe ferrite, low-temperature transition of, (3) 87*j*.
thermal-expansion, of oxide solid solutions, (1) 30*g*.
Annealing, behavior, of MgO single crystals, explosively shocked, (9) 257*g*.
crystalline, luminescence during, (2) 48*e*.
effect, in graphite, (10) 294*g*.
effect on lattice parameters of BeO, (1) 31*b*.
effect on room temperature strength of glass fibers, (9) 239*j*.
of glass. See *Glass*.
magnetic, of ferrite material, P (2) 49*e*.
open coil, in making of decarburized enameling-grade steel, (2) 37*d*.
of radiolytic damage in nitrates, I, (10) 290*i*.
Anodes. See also *Electrodes*.
carbon, Fe stem, Al sheath, P (2) 45*i*.
Antennas, radio, ferrites for, P (3) 77*c*.
Anthophyllite, stability, in relation to talc and enstatite, (2) 58*e*.
within albite-epidote hornfels facies, (6) 169*h*.
Antiferromagnetism and antiferromagnetic materials. See *Ferromagnetism and ferromagnetic materials*.
Antimony, amorphous films of, mechanism of spherulite growth in, B (9) 262*e*.
compounds, as raw materials for majolica colors and glazes, (4) 103*e*.
oxide, systems. See *Systems*.
in solid solutions with As and semiconducting chalcogenides of group IV, (3) 89*c*.
substitution in $BaTiO_3$, (6) 165*i*.
trioxide, absorption spectra and chemical bonding, (11) 315*j*.
trioxide, thin elongated single crystals, continuous production, P (10) 285*c*.
use in ancient glass, B (11) 321*d*.
Apparatus. See *Instruments; Machinery and equipment; Testing;* and specific types.
Aquagels. See *Silica gels*.
Archeology, chemistry in, B (8) 231*a*.
criteria, for dating of ancient glass, B (11) 321*f*.
divided clay dishes from early iron age, (7) 177*i*.
evaluation, of analyses of ancient glass, B (11) 321*e*.
Japanese glass, (11) 301*h*.
Architecture, ceramic, screens, (4) 95*i*.
enameling in, B (11) 322*g*.
and lighting, B (11) 321*g*.
Argon, adsorption on graphite, (4) 100*i*.
formation of spinel in, at medium pressures and in vacuum, (1) 29*e*.
Arsenates, containing alkali and alkaline earth metals, polymorphism of, (4) 118*j*.
Arsenic, arsenious oxide, function during melting and refining of glass, (1) 9*c*.
selenide, systems. See *Systems*.
in solid solutions with Sb and semiconducting chalcogenides of group IV, (3) 89*c*.
sulfide, systems. See *Systems*.
(III) oxide, metal diaphragm apparatus for measuring, (9) 251*h*.
tribromide, immersion liquids, stability during storage, (4) 107*i*.
trioxide, absorption spectra and chemical bonding, (11) 315*j*.
Arsenides, Li-Mn, crystal structures, (4) 115*i*.
rare-earth, thermoelectric, P (8) 220*j*.
Art and artware. See also *Archeology; Artists; Decoration; Design; Majolica; Pottery; Tile*.
bowl, tiltable, P (11) 301*i*.
brushes for decorating, (6) 153*i*.
califal, from Spain, (5) 125*j*.
ceramic projects, B (11) 321*c*.
Chimu, from northern Peru, (10) 265*j*.
Chinese, of Han Dynasty, B (5) 150*d*.
and Japanese cloisonné enamels, B (11) 321*e*.
and Japanese, corroded glass, study by X-ray diffraction, (11) 301*i*.
clay testing and processing for beginners, (4) 95*i*.
contemporary form developed from traditional, (10) 265*i*.
Cordoba cathedral, Alhambra, and Spanish-Moorish faience, (10) 265*i*.
Art and artware (*continued*)
enameled Al, (5) 125*j*.
enameled steel, (5) 125*j*.
English, for collector, I-V, (2) 33*i*.
Flora Danica patterns, in Royal Porcelain Works, (2) 33*j*.
flowerpot, for nesting and tiering, P (5) 126*b*.
glass, collecting of, (6) 154*a*.
museum, in Växjö, Sweden, (2) 33*i*.
panel, with epoxy bonded colored glass shapes, P (3) 64*a*.
tools of medieval and Renaissance glassmaker, (3) 64*b*.
Tudor and early Stuart, from London, (6) 153*j*.
gold medal achievements, Munich 1962, (3) 63*j*.
Greek, chemical basis of painting, (1) 2*c*.
Habaner fayencen, B (3) 91*b*.
Indian terracotta, B (10) 299*f*.
of Iran, 7000 years of, (3) 63*i*.
from Israel, exhibition in Munich, (10) 265*j*.
of Japan and Borneo, 13th and 14th century, (9) 236*f*.
Japanese, glass beads, (11) 301*h*.
Japanese, history and problems, (7) 177*h*.
jewelry, Egyptian paste, (5) 125*j*.
jewelry, low-fire, (5) 126*a*.
Ju ware of Sung dynasty, B (3) 91*e*.
mosaic, examples of, (7) 178*a*.
mosaic, on Roman buildings, (10) 266*b*.
Parian, mystery and charm of, (1) 2*c*.
plant grower, P (2) 33*j*.
porcelain, Nymphenburg, review from 1747, (10) 266*a*.
from Fuerstenberg factory, (7) 177*j*.
Vinovo, historical review, (2) 33*j*.
of Wirkkala of Finland, (10) 266*a*.
Spanish, from diggings at Paterna, (6) 153*i*.
split flower pot, P (3) 64*c*.
stained glass, conservation of, (10) 265*j*.
contemporary, (10) 266*b*.
Swiss, medieval, (6) 153*j*.
tea ware, from Sung period to present, (3) 64*c*.
terra cotta, Indian art, B (10) 299*f*.
tile, of ancient Paterna, (9) 236*f*.
Artists, Benckgraff, Johann, (7) 177*j*.
Bernadotte, Graf Sigvard, (10) 266*a*.
Billingsley, William, (6) 153*h*.
Capacci, Bruno, (3) 63*j*.
Eeles, David, (2) 33*i*.
Grossman, H., (10) 265*j*.
Hareel, P., (10) 265*j*.
Hufnagel, Otto, (7) 178*a*.
Meyer, Hans, (10) 265*i*.
Rogers, James, (6) 153*j*.
Wirkkala, Tapio, (10) 266*a*.
Zunz, H., (10) 265*j*.
Asbestos, California, processing and equipment, (6) 169*i*.
-cement, flexible products, P (2) 36*b*.
pipe, P (10) 268*a*.
products, ASTM standard for, B (9) 259*b*.
sheets, as flue covering, P (9) 253*c*.
sheets, impact resistance and hardness, (8) 205*a*.
sheets, punch for perforating, P (6) 167*g*.
sheets, X-ray diffractometer determination of chrysotile in, (7) 179*d*.
fibers, in mine roof coatings, P (2) 55*b*.
fibers, in refractory product, P (9) 244*i*.
slurries, production of, P (3) 85*d*.
treatment process, P (3) 74*d*.
types, study by optical methods, and pathogenic action, (2) 60*g*.
Ash, of borax-impregnated timber, corrosion of firebrick by, (10) 275*i*.
coal, hot-stage microscope in study of melting, (3) 80*g*.
in coal, rapid determination with absorption method, (4) 108*g*.
fly, in concrete, (8) 206*a*.
in concrete, to replace portland blast-furnace slag cement, (1) 2*h*.
as pozzolan in dense and lightweight concrete, (4) 96*d*.
steam curing and X-ray studies of, (10) 267*j*.
from steam plant, properties and use, (10) 267*h*.
fuel oil, effect on glass tank refractories, (8) 213*e*.
in glazes for ceramics, (9) 245*i*.
soda, production from crude trona, P (7) 198*i*.
tuffaceous, treatment of, P (3) 85*d*.
volcanic, deposits and uses, (3) 83*b*.
volcanic, weathering compared to pumice, (6) 169*i*.
Atmospheres, analysis, ASTM standards for, B (9) 259*c*.
control, apparatus for, P (8) 224*j*.
corrosive, development of enamels for, (11) 302*j*.
effect on, properties of magnesia-chrome brick, (11) 305*f*.
sintering of Al_2O_3, (7) 200*c*.
sintering of Fe-C compacts, (7) 200*b*.
furnace, moisture in, effect on H defects in glass-coated steel, (1) 4*c*.
oxidizing, function of components substituted for SiO_2 in, I, (1) 27*i*.
Atomic energy. See *Energy*.
Atomic weights, report of international commission on, (5) 145*d*.
Atoms, displacement in solids by ionizing radiation, role of Auger effect, (11) 318*j*.
distribution, in high chalcocite, Cu_2S, (11) 317*a*.
heavy, X-ray study of distribution in glass, (10) 271*i*.
Attapulgite, clay dispersions, drying of, P (1) 26*c*.
as clay filter aid, P (6) 170*c*.
gel-forming, method of preparing, P (6) 170*j*.
Attrition. See *Crushing and grinding*.
Augers. See *Extrusion*.
Autoclaves, series of, in continuous digestion of bauxite, P (10) 289*e*.
Automation, of brick plant, (1) 13*b*.
in cement plant, (5) 126*c*; B (9) 261*j*.
in cement plant, including motion switching and bin level detection, (5) 125*g*.
of chemical and ceramic processes, (8) 221*h*.
in container glass plant, (10) 269*j*.
control system, for cement kilns, P (5) 127*c*.
of glass batching, I, II, (11) 303*e*.
for handling steel stampings, (6) 155*b*.
of heating schedule of tunnel driers, (6) 167*a*.
in hot extrusion, (9) 243*a*.
for improving production facilities, (3) 75*e*.
of material transport systems in structural clay products industry, (10) 284*f*.
in porcelain-earthenware industry, (7) 190*c*.
in pug mills, (10) 273*d*.
for reducing costs, in brick plant, (4) 100*h*.
in rotary cement kilns, (2) 35*h*; (5) 126*j*.
in soldering miniaturized etched circuit connections, (7) 192*a*.
in spraying enamels and glazes on dinnerware and cooking utensils, (5) 137*i*.
Autunite, X-ray study of, (5) 148*a*.

Balances. See also *Weighing*.
micro-, high sensitivity, for use in ultrahigh vacuum, (10) 286*c*.
Ball clay in barrelling chips, P (9) 236*a*.
domestic, production in 1961, (1) 25*d*.
effect of moisture on modulus of rupture of, (2) 54*f*.
Indian plastic clays as substitutes, (6) 169*j*.
mineral components, (8) 225*e*.
survey of, (9) 253*j*.
Ball mills. See *Mills*.
Barite. See *Barium, sulfate*.
Barium, $BaFe_{12}O_{19}$, cation substitution in, (11) 316*c*.
$BaTiGe_2O_9$, thermal-expansion properties of, (1) 30*i*.
chloride, as buffer in flame-spectrometric determination of Na and K, (11) 303*f*.
compounds, crystal chemistry of, (10) 291*g*.
compounds, magnetite phases, (2) 57*h*.
ferrate III, magnetization studies and magnetic structure, (4) 116*f*.
ferrite, F in, P (9) 249*a*.
as magnetic focusing device, P (7) 193*f*.
mono-, magnetic and crystallographic properties, (11) 310*g*.
in permanent magnets, P (9) 249*e*.
powders, effects of grain size on saturation magnetization, (1) 19*e*.
sinter, effect of milling on coercivity of, (3) 76*i*.
fluorides, single crystals, luminescence kinetics of Sm in, (6) 164*j*.
hafnate, systems. See *Systems*.
metaborate-silica particles, method of preparing, P (2) 55*b*.
oxide, in glassy matrix for heat-resistant coatings for metal, (9) 238*c*.
as host lattice in shallow donor thermionic emitter, (5) 135*a*.
measurement of sublimation in, (10) 281*g*.
production of, P (2) 55*g*.
sulfides, selenides, and tellurides, optical absorption and photoemission in, (4) 117*d*.
systems. See *Systems*.
silicate hydrate, solubility product, (4) 112*g*.
-SrO, cathodoluminescence of, (4) 112*j*.
sulfate, diffuse reflector, in measurement of ruby laser output, (9) 251*g*.
systems. See *Systems*.
titanate, in ceramic of high dielectric strength, P (1) 20*a*.
ceramics, firing process and electric properties, (11) 310*c*.
ceramics, high pressure study of, (3) 87*d*.
ceramics, microstructure and dielectric properties, (11) 310*b*.
ceramics, thermal conductivity of, (6) 175*e*.
crystals, growth from melt, (5) 141*j*.
crystals, step formation during growth of, (2) 58*j*.
cubic modification, DTA of, (8) 219*d*.
differential etching by H_3PO_4, (2) 56*f*.
distribution of pressure and density in pressed bodies, (1) 19*g*.
domain structure, interferometric study of, (7) 191*d*.
doped and undoped, sintering of, (2) 58*f*.
effect of polarization reversal on dielectric constant, (3) 76*j*.
electroluminescence from surface layers, (4) 113*e*.
electrophoretic deposits of, (1) 19*f*.
electrostriction in, (10) 280*f*.
as flame-sprayed ceramic coating, (1) 4*b*.
high-temperature phase transition in, B (9) 262*f*.
hydrothermal preparation, (10) 294*a*.
in junction ceramic capacitor, (9) 247*j*.
monocrystals, P (2) 55*f*.
monocrystals, production of, B (9) 263*f*.
motion of 180° domain walls in, (4) 120*j*.
O-deficient single crystals, secondary piezoresistivity in, (10) 282*c*.
properties, factors affecting, (8) 219*e*.
pure, preparation, P (3) 78*e*.
reactions in, study by infrared spectroscopy, (3) 89*f*.
Sm-doped, electrical conduction anomaly in (3) 76*f*.

Barium, titanate (*continued*)
semiconducting, effect of O partial pressure, (8) 219*f*.
semiconducting, preparation by chemical methods, (10) 281*b*.
single crystals, effect of Fe_2O_3 on properties of, (6) 172*e*.
single crystals, elastic and piezoelectric coefficients of, (4) 113*c*.
single crystals, space charge conduction in, (5) 143*b*.
sintered, grain size of, B (4) 123*h*.
stabilized, for capacitor dielectrics, (7) 192*f*.
structure, comparison with brookite, (10) 290*f*.
substitution of Sb in, (6) 165*i*.
symmetry of low temperature phase, (1) 19*b*.
thin-walled spheres, materi l constants at high pressure, (11) 310*j*.
transition to ferroelectric state, (3) 89*b*.
with UO_2, effect of varying firing temperature on dielectric properties, (10) 283*a*.
velocity of sidewise 180° domain-wall motion in, (3) 89*f*.
tungstate, pressed, in cathodes, P (2) 50*g*.
zirconate, in ferroelectric ceramics, (5) 134*d*.
zirconate, hydrothermal preparation, (10) 294*a*.
Zr borate, in pigments, P (8) 225*e*.
Zr niobate, dielectric properties of, (10) 282*h*.

Basalt, hot-stage microscope in study of, (3) 80*g*.

Base exchange. See *Cations; Ions*.

Bauxite, as abrasive grain, P (6) 153*f*.
continuous digestion in series of autoclaves, P (10) 289*e*.
Hawaiian, testing for extracting alumina, (1) 25*i*.
in 1961, (1) 25*d*.
production of alumina from, by pyrogenic attack, P (3) 84*j*.
recalcining for brick manufacturing, (4) 101*f*.
rotary dryer for, (11) 314*c*.
sludge, chlorination of, (11) 314*h*.

Bayerite, transformation to hydrargillite, (5) 142*f*.

Bearings, abrasives in, (2) 33*c*.
antifriction, formation of annular grooves in, P (4) 107*a*.
with glass journal supporting elements, P (5) 130*d*.
of polytetrafluoroethylene and phosphate glass, P (3) 69*c*.
sintered fluorocarbon as self-lubricating, (3) 79*i*.

Beidellite, term defined, (6) 169*i*.

Belite, microscopy of, (7) 199*i*.
solid solubility of Al and ferric oxides in, (7) 200*h*.

Beneficiation. See also *Classification; Classifiers; Crushing and grinding; Filters; Flotation; Screens and sieves; Separation; Separators*.
caustic, of Ti source materials, P (4) 110*e*.
clay, composition for, P (4) 110*g*.
of industrial minerals, (3) 83*f*.
of potash spar, P (5) 141*g*.
of refractory clay, (6) 169*f*.
of titania ores and slags, cyclic process using $(NH_4)_2SO_4$, P (2) 55*g*.
of vermiculite ore, P (5) 141*h*.
wet, of phosphate ores, P (8) 226*c*.

Bentonites, alkaline earth, improvement of rheological properties, P (4) 110*i*.
Canadian, development for Canadian industry, (3) 82*h*.
effect on porcelain green strength, (10) 278*e*.
in 1961, (1) 25*d*.
in protective backing for mirrors, P (4) 100*c*.

Bertrandite, concentration by flotation, P (6) 170*h*.

Beryl, iron-colored, absorption spectra of, (6) 171*f*.
ore, extraction of BeO from, (2) 54*g*.

Beryllia. See also *Beryllium, oxide*.
ceramics, thermal conductivity from −200° to 150°C, (5) 132*h*.
effect on physical properties of sintered UO_2, (10) 275*c*.
hot extruded, texture in, (1) 30*d*.
rod, determination of thermal conductivity by measuring axial temperature distribution, (11) 305*i*.
single crystals, growth of, (3) 87*c*.
sintered, (3) 72*j*.
sintered, electron microscopy of, (11) 317*i*.
technology of, (10) 273*h*.

Beryllides, of Zr, Nb, Ta, Mo, and Hf, physical and mechanical properties, (6) 161*d*.

Beryllium, and BeO, technology of, (8) 215*d*.
boride, Be_4B, preparation and structure, (5) 145*g*.
boride, with β-boron structure, (4) 112*h*.
in cubic BN, for specific resistance, P (6) 162*d*.
fluoride, systems. See *Systems*.
hazards, control of, (3) 90*g*.
hydroxide or oxide, making high purity spherical discrete particles of, P (11) 308*g*.
oxide. See also *Beryllia*.
ceramic dispersion with UO_2, (10) 298*b*.
extraction from beryl ore, (2) 54*g*.
infrared transmittance and reflectance, (4) 114*h*.
irradiated, X-ray diffraction studies of, (1) 31*b*.
or nitride, in neutron source, P (5) 133*c*.
polycrystalline, compressive creep, (6) 172*e*.
production of antibodies by, (2) 60*d*.
single-crystal elastic constants from polycrystalline measurements, (9) 257*e*.
single crystals, polar properties, (10) 281*g*.
sinterable, high purity, (8) 226*e*.
sinterable, preparation, P (11) 315*b*.

Beryllium, oxide (*continued*)
sintered, P (2) 46*e*; P (3) 74*b*.
solubility in aqueous Be sulfate solution, (3) 88*h*.
systems. See *Systems*.
recovery from acid leach solutions, P (2) 55*j*.
spectrophotometric determination, (9) 251*c*.
systems. See *Systems*.
technology of, (10) 273*h*.

Bibliographies, annotated, on oxidation-resistant refractory coatings for metals, (8) 207*f*.
on ceramic insulation, (3) 76*b*.
ceramic-metal systems and enamel, 1962, B (9) 259*c*.
enamel and ceramic-metal systems, 1959 supplement, B (1) 32*a*; 1960–61, B (1) 32*b*.
of fiber metallurgy, (8) 213*b*.
of magnesia as superrefractory, (3) 73*e*.
of rare-earth compounds as high-temperature refractories, (1) 14*j*.
on thermography, B (5) 151*b*.

Binders, Ca aluminate, heat evolution tests with, (10) 274*j*.
ceramic, for metallizing piezoelectric transducers, P (6) 166*d*.
dicalcium silicate, properties of modifications, (7) 178*h*.
of fibrous masses, heat setting of, P (10) 272*d*.
foamed, for glass fibers, P (1) 11*f*.
gypsum plaster as, P (3) 65*b*.
for high temperature radome structures, (9) 241*f*.
hydraulic, dust from cement kilns in, (11) 302*f*.
hydraulic, test specimens, (1) 3*j*.
inorganic, for C cores, (8) 207*c*.
refractory colloidal, for furnace combustion chamber, P (11) 308*e*.
for refractory materials, P (2) 45*i*.
mineral, in abrasives for wet grinding steel and iron, P (4) 95*g*.
organic, effect on glazes and engobes, (3) 75*e*.
for shaped bodies of minerals, P (4) 104*d*.
for silica refractories, (6) 161*f*.
synthetic resins, for abrasives, P (3) 63*g*.
tar, for unburned shapes of sintered dolomite, P (4) 102*c*.
for thin ceramic bodies, (10) 284*g*.

Bismuth, Bi_2O_3, preparation, (5) 144*h*.
Bi_2O_3-BiF_3, crystallization of refractory oxides from, (5) 144*a*.
kinetics of formation of anodic oxide films on, (3) 87*h*.
oxide, systems. See *Systems*.
oxides, mixed, with layer-type structure, ferroelectricity in, (2) 48*b*.
perovskites, properties of, (9) 257*f*.
telluride, low resistance bonds to, P (6) 166*j*.
trioxide, absorption spectra and chemical bonding, (11) 315*j*.

Bituminous materials, ASTM standard for, B (9) 259*b*.

Blasting, media, glass beads as, (9) 235*h*.
wet, use for ceramics, (3) 79*j*.

Bleaching, of diatomaceous earth, P (4) 110*e*.
properties, of Kansas montmorillonite, (3) 82*h*.
thermal, of V and F centers in X-irradiated KCl crystals, (11) 319*g*.

Bleeding. See *Cement, paste; Mortars*.

Blending apparatus. See *Mixers*.

Bloating, of volcanic ash, (3) 83*b*.

Bodies, ceramic. See also *Dielectrics*.
aliphatic amines as molding aids for, (8) 217*d*.
alumina-base, P (8) 218*b*.
deformations in, sources and remedies, B (2) 61*j*.
for dry pressing electric heating elements, P (6) 165*i*.
fired, preparation of mullite for electron microscope study of, (8) 229*h*.
forsterite-spinel, P (2) 49*b*.
for foundry molds, P (2) 45*j*.
gas impermeable, P (2) 45*a*.
glazed, surface treatment of, P (4) 104*d*.
hard metal carbides in, (4) 106*g*.
high strength, method of preparing, P (10) 272*d*.
at high temperatures, physical properties of, I, (11) 313*j*.
hollow sphere method for determining tensile strength, (1) 23*h*.
hot preparation and hot forming, II, (3) 79*e*.
hot spray casting, (4) 104*a*.
low expansion, uses of, I, (5) 134*c*.
metallized, method of making, P (5) 136*e*.
moisture expansion and internal surface area, (10) 278*i*.
negative and dielectric drying, (4) 108*j*.
with negative heat expansion, (4) 101*j*.
new types for electrotechnical and technical ceramics, (10) 298*f*.
phosphate wastes in, P (10) 279*d*.
polycrystalline, dislocations and strength, (8) 227*j*.
for pottery, formulas for, (2) 33*h*.
prestressed, techniques and uses, (3) 71*f*.
rheology curves of, significance in ceramic technology, (1) 29*e*.
for salt glazing, (5) 126*a*.
semiplastic, cutting apparatus for, P (8) 221*e*.
solidification range of glass phase in, (8) 229*h*.
in system UO_2-UP_2O_7, thermal expansion of, (5) 132*h*.
talc-containing, (2) 47*g*.
thermal deposition of noble metals on, (11) 312*a*.
treatment of crystalline grains in forming, P (3) 77*b*.
for wall tile, I, II, (6) 163*c*.

Boehmite, dehydration, study with X-ray heating camera, (5) 142*c*.
in clays, effect on reactions, (1) 30*f*.

Bonding. See also *Seals and sealing*.
agent, for dry air setting mortars, P (8) 215*f*.
ceramic-metal, stable to above 2248°K, (7) 183*c*.
chemical, of solids, I, (11) 315*h*.
of dissimilar materials, (7) 183*j*.
of glass fiber tape to silicone rubber, P (1) 12*b*.
of glass parts of cathode-ray tubes, P (3) 69*d*.
glass-to-metal, fundamentals of, VIII, (2) 57*f*.
of glass surfaces, P (4) 99*i*.
of glazed ceramic tile to glass-fiber backing, (7) 180*g*.
of lead based alloys to silicate based ceramic bodies, P (6) 165*f*.
materials, high-temperature, curable at low temperatures for strain gages, (9) 238*e*.
of metallic members, P (1) 5*a*.
to nonmetallic refractory members, P (9) 249*g*.
process, for joining separated areas of components, P (6) 165*g*.
of Teflon with epoxies, (9) 258*a*.
thermocompression, of gold-metal electrode to Si conductor crystal body, P (9) 249*h*.

Bonds, for abrasive articles, P (1) 1*j*.
Aotsuchi, feldspar, and Toseki, for vitrified grinding wheels, (9) 236*b*.
between gold alloys and porcelains, (7) 183*d*.
carbonaceous, for dolomite furnace lining, P (2) 45*d*.
ceramic, for refractory metals, (7) 183*a*.
of ceramic adhesives, for high temperature, (1) 4*i*.
ceramic-metal, measurement of strength of, (9) 238*d*.
coated abrasive, antiweld additives for, P (2) 33*h*.
for coated abrasives, (11) 301*f*.
exothermic metallic, Ag and Cu base, (8) 206*i*.
high temperature, between quartz and metal, P (11) 311*h*.
high temperature, method of making, P (1) 16*d*.
low resistance, to Bi telluride, method and materials for making, P (6) 166*j*.
metal-to-ceramic, effect of composition and crystal size of alumina ceramics on strength, (3) 76*d*.
organic polymeric, unsaturated, in grinding wheels, P (10) 265*g*.
solder glasses as, P (3) 69*b*.

Borates, anhydrous, KBr briquette method of studying infrared spectra of, (2) 57*b*.
calcium, hydrous, from Calif., (4) 110*c*.
chromyl, preparation and properties, (7) 199*g*.
rare earth, ABO_3 type, polymorphism of, (4) 118*j*.
rare earth, and yttrium, P (2) 50*f*.
synthetic, isostructural with huntite, (6) 170*f*.
Y, and other rare earths, crystal structure, (8) 226*h*.

Boric acid, densification of, P (10) 271*f*.

Boric oxide, rapid determination in glasses, B (11) 320*j*.
systems. See *Systems*.

Borides, alkaline-earth, preparation by reduction of oxides with C, (4) 118*c*.
metal, single crystal, P (10) 277*g*.
of Ti, Zr, Nb, and Ta, physical and mechanical properties, (6) 161*c*.
transition metal, chemical resistance of, (5) 141*j*.

Boridization, of Ni, kinetics of, (2) 37*b*.
of Ni, linear time dependence of depth of boronized layer, (2) 37*h*.

Boron, boric anhydride, as modifier in optical glass, P (3) 70*b*.
B_2O_3, interaction with $CaZrO_3$, (4) 114*i*.
carbide, applications and properties, (9) 258*b*.
in ceramic tooling of ceramic shapes, (6) 167*e*.
in graphite article, P (3) 74*i*.
layer, between Plexiglas and steel, effect on γ rays produced in steel, (10) 274*i*.
mortar, crushing SiC in, (10) 284*d*.
chloride, in boronization of Ni, (2) 37*b*.
chloride, crystalline, infrared spectrum of, (2) 57*j*.
coherent powder bodies, P (2) 45*c*.
-containing materials, radiation damage, B (8) 234*d*.
coordination, in alkali borate glasses, (2) 40*b*.
crystalline, heat content and capacity from 298° to 1700°K, (1) 28*b*.
diffusion into semiconductive wafers, (2) 36*i*.
layer, on Ni, linear time dependence of depth of, (2) 37*h*.
nitride, P (2) 55*d*.
crucible, treatment with molten Al, P (3) 74*c*.
cubic, conducting, method of making, P (6) 162*d*.
cubic form, synthesis of, (2) 54*g*.
method of making, P (2) 46*c*.
in multilayered composite metal article, P (9) 245*a*.
properties and production sizes, (10) 273*i*.
pyrolytic, for reentry applications, (10) 275*h*.
oxide, effect on scintillation properties of glasses, (11) 304*j*.
in etchant for single crystals, P (3) 89*i*.
in joining glass bodies, P (11) 305*a*.
phase equilibria with refractory oxides, (8) 229*f*.
and sulfide molecules, vibration spectra of, (5) 147*a*.
systems. See *Systems*.
use in container glass, (2) 41*g*.
vitreous, infrared spectra of, (8) 209*c*.
-oxygen bond, energy and length, (10) 292*b*.
phosphide, as abrasion and corrosion resistant coating, P (9) 239*b*.
crystalline, method of preparing, P (10) 277*g*.

Boron, phosphide (*continued*)
crystallization of, P (6) 176*a*.
single crystal, P (5) 133*h*.
spectrochemical determination in Si compounds, (9) 252*a*.
substitution, in synthetic micas and clays, (7) 198*b*.
systems. See *Systems*.
tetragonal, structure compared to BeB_{12}, (4) 112*h*.
trihalides, production of, P (10) 290*d*.
triiodide, crystal structure of, (1) 27*e*.
Brazing. See *Soldering*.
Brick. See also *Masonry; Refractories; Structural materials*.
blending of raw materials and extrusion, (5) 132*c*.
clays, anionic surface active agent for improving, (1) 12*h*.
coating for, P (1) 13*a*.
coloring, with solutions of Mn and Mn and Fe, (1) 12*i*.
construction in East Pakistan, (11) 305*d*.
dimensions, research on standardization, (2) 43*h*.
dried clay, deterioration in warm weather storage, (1) 12*h*.
drying by high velocity hot air, (6) 167*c*.
engineering design, B (10) 298*h*.
face, economy of space in plant, (6) 159*d*.
face, ideal composition, (3) 71*b*.
freezing behavior of water in, (3) 71*e*.
German factories, (10) 273*f*.
hydraulic press for, P (6) 167*c*.
-laying machine, Demarest, (8) 211*j*.
lightweight, combustion processes in firing of, (2) 53*e*.
from limey clays, coloration of, (2) 43*f*.
manufacture, problems in, (6) 158*h*.
manufacture, in Sudan, (2) 60*g*.
masonry, increased use, (7) 187*b*.
mechanical rendering of surfaces and pointing of, P (6) 159*c*.
moisture control in, (3) 71*g*.
packaging automatically, (1) 13*a*.
pallet for handling, P (8) 212*a*.
plant, Canadian, capacity, (6) 159*b*.
Danish, planning and processing in, (2) 43*e*.
modernization, (10) 273*c*.
for sand-faced and rustic bricks, (2) 43*g*.
in southern Sweden, (2) 43*i*.
at Waingroves, operation and equipment, (10) 273*f*.
preparation and application of engobes, (6) 159*c*.
prevention of lime blowing, B (10) 300*a*.
production, sampling in control of, (6) 167*c*.
pushbutton factory for, (1) 13*b*.
shipment by rail, method and container, P (2) 44*d*.
shipping, on flatcars, (8) 230*i*.
soft-mud, Va. plant, (8) 211*j*.
stack, apparatus for lifting, P (3) 71*h*.
stacks, device for handling, P (9) 250*c*.
transfer from dryer to kiln, Hulo system, (1 12*i*.
V-, fire tests on, (1) 12*h*.
veneer, construction material, P (6) 159*b*.
wage incentive plan for workers, (8) 211*j*.
walls, mortar staining in, (11) 305*e*.
wet process of material preparation, (2) 44*b*.
-work, rain penetration of, (3) 71*c*.
Brick industry. See *Structural clay products industry*.
Brickmaking apparatus and equipment. See also *Dryers; Kilns; Materials handling; Presses*.
automatic setting process for green brick, (1) 12*g*.
for handling clay, (1) 12*j*.
for shell brick, P (1) 13*c*.
12-chamber dryer in Belgium, (1) 12*j*.
Bromoform, diluent for in heavy-liquid separation of minerals, (4) 107*c*.
Bronze, lead tungstate, electrical properties, (4) 104*g*.
sodium tungsten, cubic, electrical resistivity of, (3) 86*c*.
sodium tungsten, cubic, magnetic susceptibility of, (9) 256*b*.
sodium tungsten, electric properties of, (9) 256*g*.
W, crystal structure, dielectric properties of materials with, (10) 282*h*.
Bronzite, DTA of, with and without vacuum, (10) 291*f*.
Brookite, atomic distances and bond angles in, (10) 290*f*.
-rutile transformation, (10) 295*a*.
-rutile transformation, effect of particle size and purity, (5) 146*c*.
Brucite, formation from system MgO-H_2O, (5) 146*a*.
minerals, thermal decomposition of, (11) 319*i*.
Buffing compounds. See *Grinding and polishing*.
Building materials. See also *Aggregates; Brick; Enamels; Insulation, thermal; Structural clay products; Structural materials*.
apparatus for determining thermal conductivity of, (11) 313*c*.
briquets, method and apparatus for making, P (9) 243*c*.
corrosion-resistant cementitious, P (8) 206*b*.
development in, (4) 122*c*.
elements, use of fibers in, P (1) 3*i*.
fire tests of, (2) 43*j*.
glass Microballoon particles for, (10) 270*j*.
of granulated slag and sand, (8) 203*j*.
from industrial minerals, future in Canadian industry, (3) 82*j*.
light transmitting, glass strips in, P (9) 242*c*.
manufacture by Danish plant, (2) 43*e*.

Building materials (*continued*)
panels, enameled Al, for external walls and insulation, (10) 268*j*.
plastered brickwork, waterproofing of, (9) 243*a*.
precast cored blocks, apparatus for making, P (9) 250*d*.
prestressed ceramic, fire resistance of, B (10) 300*a*.
research, 1961, B (3) 90*i*.
Section, of British Ceramic Society, visit to France, April 1961, (1) 31*g*.
selection for durability, B (8) 231*a*.
Spanish, (5) 148*d*.
stone, ASTM standards for, B (9) 259*b*.
Bulbs. See *Glass*.
Burners. See also *Flames*.
assembly, P (2) 53*i*.
combustion, P (10) 288*b*.
combustion chamber, for producing glass fiber, P (1) 11*a*.
construction, P (6) 169*c*.
control means, P (7) 197*c*.
fuel oil, lining of, (5) 140*c*.
fuel oil, for tunnel kilns, (5) 140*c*.
gas, air-heating, P (1) 24*j*.
emitting products of combustion in planar form, P (1) 11*h*.
for mixing fuel gas and O-containing gas, P (5) 140*i*.
multiple nozzle, P (5) 140*e*.
radiant, P (1) 25*c*.
radiant cup, P (5) 140*f*; P (7) 197*a*.
improved, for tunnel kilns, (6) 169*b*.
liquid fuel, for forming glass fibers, P (5) 131*b*.
oil, low pressure atomizer nozzle for, P (6) 169*e*.
for production of finely divided oxides, P (8) 224*f*.
radiant, construction, P (3) 82*b*.
radiant heat fuel, block and refractory cup combined, P (1) 16*f*.
safety control, P (5) 140*g*.
Burning. See *Calcination; Combustion; Firing; Lime*.
Burnishing. See *Polishing*.
Bushings, drill, ceramic coated, P (1) 4*i*.

Cadmium, chloride, activated with sulfides, as phosphor, (5) 135*h*.
chloride, systems. See *Systems*.
compounds, crystals, from vapor state, B (9) 263*b*.
halide, systems. See *Systems*.
metasilicate, low temperature heat capacity and entropy, (2) 57*g*.
niobate, effect of Ta, Cu, and Pb on dielectric properties, (3) 76*j*.
oxide, disorder and oxygen transport in, B (9) 261*d*.
semiconductivity and thermoelectric power, (8) 219*g*.
Ag-, bodies, attaching to supporting member, P (6) 166*h*.
systems. See *Systems*.
rhodite, structure of, (4) 120*f*.
selenide, layers, conductivity induced by cathode rays in, (5) 134*g*.
selenide, mechanism of electrical conduction in, (4) 116*j*.
sulfide, crystal growth of, (6) 172*f*.
crystals, preparation, P (8) 226*a*.
crystals, true structure of, (3) 89*d*.
crystal surface, electron processing of, P (7) 193*a*.
infrared fluorescent, activated with V,Ag and V,Cu, absolute efficiency of, (5) 134*d*.
internal photoeffect and exciton diffusion in, (4) 115*a*.
photoconducting articles, method of making, P (3) 78*g*.
photoresistance cells, oxide bases for, P (3) 77*c*.
in piezoelectric devices, P (9) 249*d*.
single crystals, effect of deuteron bombardment, (6) 173*a*.
sintered photoconductive films, effect of heat treatment on, (5) 143*a*.
systems. See *Systems*.
titanate, hydrothermal preparation, (10) 294*a*.
Calcination. See also *Firing*.
of gypsum, process, P (7) 182*i*.
of magnesite, effect of gaseous phase, (6) 159*j*.
means and method, P (1) 3*e*.
of pellets, process and apparatus, P (11) 312*a*.
plant, after 1 yr operation, (10) 288*f*.
re-, of bauxite for brick manufacturing, (4) 101*f*.
of rocks containing organic substances in annular kilns, P (3) 83*e*.
temperature, of lime, effect on react (7) 178*j*.
of ZnS concentrates, P (10) 289*e*.
Calcite, action of water on, (6) 169*f*.
elastic constants of, (1) 27*e*.
hydrothermal synthesis of, (5) 144*e*.
quantitative gasometric determination, by Chittick apparatus, (3) 81*b*.
study of dislocation etch pits in, (4) 116*g*.
Calcium, acetate, as cement grinding aid and pack set inhibitor, P (10) 268*e*.
aluminates, from slags, P (3) 64*h*.
aluminoferrites, study of solid solutions of, (4) 115*f*.
borate, compounds, synthesis by hydrothermal methods, (7) 201*g*.
$Ca_2BaSi_2O_8$, crystallographic study of, (4) 113*h*.
Ca_2BeO_3, in system BeO-CaO, (2) 58*i*.
$CaCl_2$, in formation of large crystals of $CaSO_4 \cdot 2H_2O$, (5) 126*c*.
and Ca compounds in 1961, (1) 25*d*.

Calcium (*continued*)
$Ca_{0.15}Zr_{0.85}O_{1.85}$, isothermal grain growth in, (11) 317*d*.
carboaluminate, preparation, (7) 178*b*.
carbonate, as filler for cement, (7) 178*f*.
at high pressure, thermodynamic calculation of phase equilibria, (2) 59*j*.
kinetics of thermal decomposition, (4) 115*f*; B (4) 124*a*.
production for metallurgical use, (6) 154*i*.
systems. See *Systems*.
and water, O isotope fractionation between, (2) 58*e*.
chloride, effect on structure of aqueous suspensions of tricalcium aluminate, (11) 317*d*.
dicalcium silicate, β-γ transformation under pressure, (8) 203*j*.
binding properties of modifications, (7) 178*h*.
effect of ferrous oxide on β-γ inversion temperature, (7) 179*e*.
effect of impurities on transformation of, (1) 27*i*.
hydration of, (7) 180*i*.
stabilization of, (5) 146*b*.
diferrite, crystallographic investigation, (2) 56*c*.
flame photometric determination in Ni-alumina catalysts, (10) 286*d*.
fluoride, electron spin resonance of point defects in, B (9) 260*e*.
Ho-doped, as maser material, (7) 191*b*.
optical maser, Tb- and Ce-activated, P (6) 166*g*.
O penetration into single crystals, (10) 296*f*.
sintering of, (3) 88*f*.
for slip-cast crucibles for U smelting, (10) 275*b*.
U-doped, as laser material, (7) 192*i*.
germanate, Ti-activated, P (2) 50*d*.
hexaluminate, and stability relations in system CaO-Al_2O_3-SiO_2, (4) 112*i*.
hydrochloraluminates, formation and effect on structure of cement stone, (5) 126*h*.
hydrosilicates, binding in lime, (2) 34*e*.
hydrosilicates, properties of, (1) 2*g*.
hydroxide, interaction with quartz, (5) 144*d*.
nuclear magnetic resonance determination of H positions in, (7) 199*a*.
solution with gypsum, reaction of allophane with, (7) 181*f*.
lignosulfonate, on cement, adsorption isotherms for, (10) 266*c*.
lignosulfonate, set-retarding effects in cement, (10) 267*b*.
molten, Ta borides for containing, (11) 308*i*.
oxide. See also *Lime*.
coated cathodes, coloration of, (10) 279*h*.
effect on electrical conductivity of glass containing two alkali oxides, (7) 184*d*.
flame spectrometric determination in aluminosilicates, (10) 286*d*.
-Mn oxide mixtures in air, melting relations in, (3) 87*g*.
slip casting of, (7) 188*h*.
systems. See *Systems*.
thermal expansion tests, (10) 276*c*.
phosphate, addition to molten semiconductor material, P (6) 166*h*.
as bond in silica brick, (8) 214*i*.
dibasic luminescent grade, P (4) 106*a*.
Tl-activated, ultraviolet emission of, (6) 164*h*.
salts, effect on sodium beryllate solutions, (7) 198*d*.
silicates, of cements, composition and structure of hydration products of, (1) 2*g*.
crystalline hydrous, in thermal insulating material, P (11) 308*j*.
hydrates, preparation of, (4) 112*h*.
hydration of, (11) 302*e*.
product, P (1) 25*f*.
systems. See *Systems*.
sulfate, effect on composition of portland cement clinker, (7) 179*b*.
large additions in cement, as cause of ettringite-like phase, (10) 266*d*.
in portland cement raw mix, effect on properties of cement, (7) 180*a*.
reductive decomposition, P (8) 206*e*.
systems. See *Systems*.
uncalcined impure, in producing gypsumlike products, P (10) 268*d*.
sulfate dihydrate, effect of crystal state on dehydration of, (1) 2*j*.
effect of inorganic salts on dehydration, (2) 34*e*.
infrared absorption spectra of, (2) 34*j*.
kinetic transition in liquid phase with hemihydrate, (9) 236*h*.
sulfate hemihydrate, preparation in NaCl solution, (7) 198*e*.
transformation to insoluble anhydrite, (5) 147*d*.
transition after dehydration, (9) 237*h*.
titanate, hydrothermal preparation, (10) 294*a*.
tricalcium silicate, effect of mixing water content and alkalis on hydration of, (7) 180*g*.
formation by interaction of $CaCO_3$ and SiO_2 at 840°C, (3) 86*f*.
solid solution, effect of alkalis in clinker on hydration of, (11) 302*c*.
tungstate, separation from gangue by flotation, P (10) 289*h*.
zirconate, interaction with B_2O_3, (4) 114*i*.
Calibration, external, on dial thermometer, P (10) 287*f*.
of optical pyrometers, (1) 23*i*.
of ruby laser output, simple method, (9) 251*g*.
simultaneous with dynamic differential calorimetry, (8) 228*f*.

Calibration (*continued*)
thermal, of high-temperature X-ray diffraction cameras and diffractometers, Pt expansion values for, (3) 81*a*.
of thermometer, P (3) 70*f*.
Calorimeters, dynamic differential, simultaneous calibration and thermogravimetry, (8) 228*f*.
ice, for precise measurement of heat content from 0° to 1500°K, (1) 23*i*.
Cameras. See *Photography*.
Capacitors, anisotropic dielectric as coupling between, (9) 246*g*.
Ca, Sr, and Bi titanates in, P (4) 105*b*.
of dense Al oxide, P (8) 220*d*.
dielectrics, stabilized $BaTiO_3$, (7) 192*f*.
electrical, with SiN dielectric, P (10) 282*e*.
electronic, fragile, commercial production, (5) 135*c*.
high-tension, ceramic dielectrics for, P (6) 165*i*.
junction ceramic, (9) 247*j*.
miniature, American developments, (9) 246*g*.
solid, method of making, P (11) 311*g*.
solid electrolytic, manufacture of, P (10) 283*b*.
TiO_2, Sb-doped, (9) 246*h*.
of TiO_2 film, produced by thermal decomposition of organic Ti compounds, (8) 218*f*.
Carbides. See also specific types.
cemented, of W, Ti, and Cr, properties and uses, (6) 155*c*.
as coatings, (9) 238*j*.
grinding with Man-Made diamond wheels, (11) 301*e*.
hard metal, use in ceramic fabrication, (4) 106*g*.
heat treatable, machinable, (6) 159*i*.
heavy-metal, in wear-resistant cermets, P (3) 75*b*.
metal, phase equilibrium relations at high temperatures, (10) 276*e*.
method of making, P (6) 162*f*.
in nuclear reactor fuel elements, importance, (10) 274*b*.
of Si, B, Hf, Nb, Ta, Ti, Zr, and W, physical and mechanical properties, (6) 161*c*.
spherical actinide, P (4) 102*e*.
ternary, of transition metals with Al and Mg, (4) 101*h*.
transition metal, thermodynamic properties and periodicity, (6) 175*i*.
uranium, preparation, fabrication, and properties, (8) 214*h*.
Carbon. See also *Graphite*.
activated, for liquid-phase absorption, (11) 314*g*.
alumina-, compositions, for cutting metals and alloys, P (2) 33*g*.
articles, fire tube furnace and method for baking, P (1) 16*b*.
articles, method of making, P (8) 216*a*.
atomic processes involving, (5) 143*f*.
black, composition, P (10) 289*f*.
bodies, joining process, P (2) 46*h*.
coated, for nuclear reactors, P (5) 133*c*.
deposition, on fireclay brick in CO atmosphere, I, (11) 306*c*.
dioxide, radioactive, in measurement of neutralization of concrete, (8) 205*e*.
dioxide, systems. See *Systems*.
films, for electron microscopy, (11) 312*h*.
in formation of SiC, (3) 72*f*.
of hardness equal to diamond, crystallizing out of solution, P (6) 176*a*.
with high moderating properties, preparation for use in nuclear reactors, P (1) 17*g*.
Fe-, compacts, effect of atmosphere on sintering, (7) 200*b*.
joining method, P (11) 303*c*.
in liquid iron, reduction of SiO_2 and Al_2O_3 by, (1) 14*d*.
porous, for molds for handblown glassware, (7) 184*j*.
preparation and properties of forms of, (11) 314*h*.
in reduction of oxides for preparation of alkaline-earth borides, (4) 118*e*.
refractories. See *Refractories*.
survey of forms and properties, (6) 159*f*.
systems. See *Systems*.
Carbonaceous materials, coating with SiO_2, P (10) 277*d*.
for thermal protection of fluorine-hydrogen thrust chambers, (4) 102*a*.
Carbonates, anhydrous normal, infrared absorption frequency trends for, (6) 173*i*.
skeletal, solubility in aqueous solutions, (10) 295*g*.
Carbonation, of cements and components, (8) 205*h*.
Carbonatites, origin, (1) 30*j*.
Carbonization, of plastics and refractory materials research program, II, (8) 212*f*.
of viscose rayon fibers, P (1) 26*c*.
Carboxymethylcellulose. See *Cellulose*.
Carburization, of W powder by carburizing gases, II, (6) 171*g*.
Carnegieite, crystallization of volcanic glass to, (11) 315*j*.
Castables, heat evolution tests with, (10) 274*j*.
Casting. See also *Molding; Molds; Refractories; Slip casting*.
centrifugal, of glass flake cylinders, (9) 240*b*.
of clay coating, P (2) 51*e*.
continuous, composite mold for, P (2) 45*c*.
diagram for establishing optimum formula, I,II, (4) 103*h*.
of hollow parts, core element for, P (10) 277*a*.
hot spray, of ceramic products, (4) 104*a*.
metal, destructible reinforced sand core for, P (4) 102*e*.
metal, refractories for, P (2) 46*e*.
of stainless steel alloys, ceramic cores in, (8) 212*i*.
of zircon products, (1) 14*c*.
Castings, investment, for advanced aircraft, (6) 159*i*.
quality, nondestructive sonic test for, (10) 269*h*.
Casting slips. See *Slips*.
Cast iron. See *Enameling metals; Iron*.
Catalysts, combustion, refractory bodies for, P (3) 74*g*.
copper oxide-alumina, for air pollution control, (3) 79*d*.
hydroxyl ion, of crystallization of amorphous silica, (7) 199*e*.
Ni-alumina, flame photometric determination of Na, K, and Ca in, (10) 286*d*.
permanently active, producing with neutron irradiation, P (9) 244*h*.
Cathode-ray tubes. See *Tubes*.
Cathodes, bar, for Al reduction cell, P (8) 215*f*.
Ba tungstate, pressed, P (2) 50*g*.
CaO coated, activated, coloration of, (10) 279*h*.
coated with SrO, photoelectric emission from, (5) 135*i*.
cold, noise characteristics of, (7) 192*g*.
dispenser and oxide, measuring sublimation by retarding field technique, (10) 281*g*.
for electron tubes, P (4) 105*a*.
oxide, method of making, P (8) 220*g*; P (11) 311*a*.
oxide, and Ni supports, P (2) 49*h*.
oxide-coated, drift and diffusion of activation in, (10) 280*g*.
oxide-coated, subject to strong electric field, electron emission from, (11) 310*a*.
sleeve, in electron gun assembly, P (8) 220*f*.
spraying, with emissive materials, P (7) 193*h*.
spraying, stencil for, P (1) 10*j*.
Cations, base, effect on Cs kinetics of clinoptilolite, (6) 172*c*.
divalent, effect on absorption and photochemistry of AgCl crystals, (3) 85*f*.
divalent, glass electrodes for measuring, (9) 240*j*.
effect on Young's modulus of soda-lime-silica glass, (2) 38*j*.
exchange, of inorganic materials, kinetics of Cs reactions with, (7) 199*g*.
exchangeable, effect on rheological properties and particle size distribution, of kaolinite, (3) 87*e*.
metallic, flooding solutions in determination of, (5) 139*j*.
in micalike layer silicates, substitution by Al^{3+} and Si^{4+}, (5) 146*e*.
-exchange capacity, of hydrated halloysite, (11) 316*b*.
migration, in montmorillonites, (7) 198*f*.
of noninert gas structure, in enamels, (8) 207*g*.
positions, in type A synthetic zeolite, refinement of, (10) 296*f*.
size, effects in complex fluoride compound formation, (1) 26*g*.
substitution, in $BaFe_{12}O_{19}$, (11) 316*c*.
Cells, ceramic-metal, for short-term power at high temperatures, (10) 268*h*.
dimensions, of layer-lattice silicates, I,II, (7) 198*f*; III,IV, (9) 255*d*; V,VI, (11) 316*e*.
high-pressure optical, P (6) 168*h*.
for measuring light transmission of liquid, P (7) 196*d*.
photoelectric, surface-barrier, P (1) 21*j*.
photovoltaic, in equipment for determining orientation of sapphire monocrystals, (6) 175*e*.
photovoltaic, of SiC on graphite base, P (6) 166*g*.
reduction, Al, cathode bar for, P (8) 215*f*.
thermal conductivity, in gas chromatographic apparatus, P (10) 286*i*.
Cellular materials, impregnation by implosion, P (9) 250*d*.
Cellulose, as additive for green sand molding, P (8) 215*g*.
carboxymethyl-, (glykocel), effect on porcelain green strength, (10) 278*e*.
digesters, nonporous carbon bricks for, P (4) 103*b*.
methyl, as additive for green sand molding, P (10) 277*j*.
Celsian, formation of, (10) 297*h*.
Cement. See also *Concrete; Plasters; Pozzolans*.
addition agent, P (4) 96*e*.
alumina, refractory concrete from, properties and use, (3) 72*d*.
aluminous, reactions in setting, (10) 267*a*.
aluminous, studies on, V, (11) 302*c*.
argillaceous, P (2) 36*a*.
asbestos, apparatus for shaping and compressing sheets, P (11) 312*f*.
flexible products, P (2) 36*b*.
pipe, P (10) 268*a*.
portland, steam-cured, microscopy of, (9) 236*i*.
sheet, as flue covering, P (9) 253*c*.
sheet, impact resistance and hardness, (8) 205*a*.
sheets, punch for perforating, P (6) 167*g*.
sheets, X-ray diffractometer determination of chrysotile in, (7) 179*d*.
ASTM standard for, B (9) 259*a*.
barium, effect of mineralogical constitution on hydraulic properties, (7) 180*d*.
basing, P (6) 154*i*.
behavior after curing, prediction of, (7) 182*i*.
block, efflorescence on, change in composition, (7) 178*g*.
block, physicochemical interaction with medium, (1) 2*i*.
for bonding strain gages, (9) 238*e*.
Ca silicates of, hydration products, (1) 2*g*.
cellular, method of making, P (10) 268*a*.
cementitious material, dry, P (2) 55*h*.
cementitious material, preparation, P (3) 64*j*.
chemistry, I,II, B (5) 148*i*.
as basis of chemical calculations of raw materials, (5) 126*j*.
Cement, chemistry (*continued*)
and technology of, B(9) 261*j*.
clinker, alite, uniformity of structure, (3) 64*f*.
brick, for use in rotary cement kiln, (7) 178*i*.
conveyor and cooling apparatus for, P (9) 237*e*.
cooling apparatus for, P (1) 3*a*.
determination of free lime in, (9) 236*g*.
dry process production in rotary kiln, (11) 301*j*.
effect of chemical composition on properties of portland blast-furnace slag cement, (7) 180*d*.
effect of magnesite brick containing Cr on chromate content, (3) 72*i*.
fineness, effect on drying shrinkage of mortar, (8) 204*g*.
industrial, X-ray diffraction determination of minerals in, (7) 182*e*.
manufacture, using calcined limestone, properties of minerals in, (7) 181*c*.
microstructure of, B (11) 321*a*.
minerals, microscopy of, (7) 181*c*.
preparation for finish grinding, (2) 35*c*.
relation of SO_3 in to S content in heavy oil, (7) 181*i*.
weighing apparatus for, P (9) 238*a*.
composition, P (4) 96*f*.
compounds, studies of early stages of paste hydration of, I, (1) 3*e*; comment on, (10) 266*h*.
cooler, vibrating, (9) 237*j*.
corrosion-resistant, in building materials, P (8) 206*b*.
delivery of hot kiln discharge to conveyor, P (9) 237*b*.
drying shrinkage, factors affecting, (8) 204*i*.
dust, effect on plants, (4) 96*h*.
erosion resistance, predicted and calculated values, (9) 236*a*.
ettringite-like phase with large additions of $CaSO_4$, (10) 266*d*.
false set, (8) 204*f*.
false set, relation to consistency of concrete at low temperature, (7) 181*j*.
flocculation, effect on properties of paste and mortar, (8) 205*a*.
fluorspar as admix for, (6) 154*e*.
formation processes and limiting saturation by lime, (7) 181*h*.
Formosa plant, increase in output, (7) 178*e*.
-fused silica, for thermal shock resistance and thermal insulation, (1) 4*f*.
grinding aid and pack set inhibitor, P (10) 268*e*.
in hardened wall tile, (9) 245*j*.
hardening, acceleration by crystallization nuclei, P (3) 64*h*.
high-alumina, for concrete for electric furnace roofs, (7) 188*b*.
high-MgO, stability improvement, (8) 205*f*.
high-temperature, production in blast furnace, P (1) 3*e*.
hydration and carbonation, (8) 205*h*.
hydraulic, additives for, P (9) 237*g*.
physical chemistry and technology, (8) 205*j*.
in production of synthetic stone, P (6) 154*j*.
imports, (10) 266*f*.
Japanese production increased, (9) 236*j*.
kilns. See *Kilns*.
laboratories, nephelometric and turbidimetric determinations in, (9) 237*a*.
low water-loss, for wells, P (8) 206*c*.
lumping, research on, (1) 3*c*.
making, processes, wet slurry feed vs. granulated spherical feed, (9) 250*a*.
manufacture, without dust, (3) 64*d*.
masonry, made with low-grade limestone, (7) 181*a*.
masonry, properties of, (8) 205*d*.
with microfillers, (7) 178*f*.
mills. See *Mills*.
minerals, hydrated, effect of synthetic CO_2-containing aqueous solutions on, (1) 2*f*.
mortars. See *Mortars*.
nonshrinking and low-expanding, P (9) 238*a*.
for oil and gas wells, P (6) 154*i*.
oil well, composition, P (1) 3*g*.
pack set inhibitor, P (9) 237*c*.
pastes, air-entrained, rearrangement of bubble sizes during setting, (3) 64*i*.
blast-furnace, study of liquid phase and slags used in, (7) 180*f*.
containing expanding and dispersing agents, properties of, (7) 181*b*.
dielectric study on hydration, (7) 179*g*.
early stages of hydration, II, (6) 154*c*.
hardened, factors affecting drying shrinkage, (8) 204*c*.
hardened, thermal expansion in, (7) 182*f*.
properties of, B (5) 148*i*.
volume change during hydration, (7) 182*d*.
performance in concrete, long-time study, (4) 96*c*.
plants, applications of vacuum X-ray spectrometer to operation of, (2) 34*c*.
in British Columbia, flexibility of, (6) 154*i*.
capacity increase, (2) 35*c*.
centrally controlled, instrument maintenance, (10) 267*d*.
doubling of capacity, (10) 267*g*.
expansion of, (2) 35*j*.
layout for automation, (5) 126*c*.
modernization of, (2) 35*c*.
need for expansion and improvement, (7) 178*e*.
new Indiana mill, (6) 154*h*.
in N. Y., quarry operations for, (7) 181*e*.
in Ohio, operations in, (10) 280*i*.
process sequence interlocked system in, (5) 126*g*.
profitable operation, (10) 267*i*.
selecting geared drives for, (2) 35*i*.
space age technology in, (9) 237*e*.
wet-process, in Montana, (10) 267*c*.

Cement (*continued*)
plastering, flow behavior of, (8) 205*c*.
plastic, rheology of, (8) 205*j*.
portland, adsorption of admixtures, (10) 266*c*.
clinker, effect of $CaSO_4$ on compound composition, (7) 179*b*.
clinker, oxide additions in stabilization of, (5) 146*b*.
color of, (7) 178*j*.
composition of ferrite phase, (7) 179*a*.
with different amounts of alkalis, alite in, (7) 178*c*.
DTA determination of forms of gypsum in, (7) 179*e*.
early stages of paste hydration, (8) 206*b*.
effect of alkalis in clinker on hydration of tricalcium silicate solid solution in, (11) 302*c*.
effect of gypsum anhydrite and K_2SO_4 on properties, (7) 179*i*.
effect of gypsum transformation on false set, (6) 154*f*.
effect of heat on, (8) 204*e*.
fluorescent X-ray spectrometric determination of components, (9) 236*h*.
induction period in hydration of, (5) 126*e*.
MgO in, (7) 180*i*.
as paint base, P (3) 64*i*.
phenolic compound as grinding aid, P (4) 96*i*.
rapid-hardening, formula for estimating heat of hydration and mortar strength, (8) 205*d*.
raw mix, addition of $CaSO_4$, effect on cement, (7) 180*a*.
with set-retarding agents, importance of mixing sequence, (10) 267*b*.
slurry, effectiveness of CO_2 gas on, (11) 302*a*.
portland blast-furnace slag, in concrete, fly ash as replacement, (1) 2*h*.
effect of chemical composition of slag, (7) 179*c*.
effect of gypsum on properties, (7) 179*f*.
in potting composition for electrical article, P (6) 165*j*.
powder, heating apparatus for, P (1) 3*c*.
preheating apparatus, P (7) 182*f*.
process, P (5) 127*a*.
product, composition, P (10) 268*f*.
production, interrelation of moisture reduction, fuel savings, and increased production, (11) 302*e*.
nuclear gaging systems in, (7) 182*b*.
and trends in, (7) 178*e*.
raw materials. See *Raw materials*.
raw mix, physical, chemical, and mineralogical studies on clays for, (7) 181*e*.
raw mix, X-ray analysis and control of, I, II, (6) 154*g*.
sealing, use in oil wells, (7) 182*c*.
silicate, corrosion-inhibiting, P (3) 65*a*.
slag-lime, contraction of, (7) 179*b*.
from slags containing F compounds, P (3) 65*a*.
special, B (5) 150*b*.
stone, effect of Ca hydrochloraluminates on structure of, (5) 126*h*.
strength, effect of Na and Mg oxides, (7) 179*h*.
substitution of lime for, for seawater durability, (1) 3*g*.
supersulfated, storage of, (1) 3*d*.
thermal insulating, diatomaceous silica, (2) 34*b*.
titration of alkaline salts in, (8) 222*g*.
tube socket, for high vacuum technique, B (2) 61*d*.
types, adjustment of air separator for rapid change in, (10) 266*e*.
white, clinker production for, P (8) 206*d*.
white, in coating for exterior surfaces, P (9) 237*d*.
Cement industry, computer control in, (9) 258*f*.
dust control in, (1) 2*i*.
particle size reduction in, (9) 250*b*.
process control computers in, (5) 126*j*.
process instrumentation and control computers in, (5) 126*g*.
refractories for, (10) 273*j*.
trends in, (10) 266*g*.
Centrifuges, Whitby, in rapid determination of particle size, (8) 223*b*.
Ceramic engineering. See *Engineering*.
Ceramic industry, applications of liquid gas in, (5) 140*d*.
in Brazil and Argentina, market for, (9) 258*i*.
control of technical potential in plants, (10) 298*c*.
cost reduction by consistent quality control, (4) 122*b*.
Czech, ideas for improvement, (5) 148*c*.
in developing countries, (10) 298*a*.
dust measurements in, (3) 90*b*.
effects of Anglo-Japanese trade treaty, (5) 134*a*.
electrical tunnel kilns for use in, (10) 287*h*.
financing industrial expansion in, (6) 176*f*.
foreign trade in, (1) 31*e*.
growth, in Etruria, (5) 148*c*.
industrial esthetics in, B (10) 300*c*.
of Latin America, survey, (6) 176*d*.
need for promotional work, (6) 176*f*.
particle size reduction in, (9) 250*b*.
present tendencies in, I, II, (4) 122*b*.
prospects in India, (9) 254*g*.
quality control in, (10) 298*d*.
sales-production-design, relation of, (2) 33*j*.
scientific research in, (5) 148*c*.
South African, survey of, (8) 230*h*.
special type paper for, (9) 254*g*.
standards and labels for quality, (9) 258*e*.
Sudan, open-air plants, (2) 60*g*.
use of oil gas in, (9) 253*c*.
works control in, (9) 258*h*.
Ceramic materials. See also *Bodies, ceramic; Raw materials;* and specific types.
accurate analysis of, (3) 80*e*.
applications and properties, (9) 258*b*.
Austrian deposits, (7) 197*d*.
in ball check valves, performance of, (4) 105*f*.
with dielectric constant of 10,000 at room temperature, B (4) 123*h*.
with high dielectric constants, P (6) 165*j*.
in industry, outdated?, (1) 31*e*.
lightweight, (6) 158*j*.
method for making, P (7) 193*i*.
nonoxide, mechanical properties of, B (3) 91*g*.
in pressure molded bodies, P (9) 246*d*.
radiation absorbing, containing rare earths, (10) 273*j*.
reactor irradiation of, (11) 306*i*.
for reactors, and for thermoelectric power generation, (10) 273*i*.
strength of, (7) 202*a*.
thermal conductivity of, (4) 121*i*.
thermal conductivity of, determination by temperature cycling, (10) 285*j*.
thermal shock resistance of, determination, (10) 274*f*.
thermodynamic study at high temperatures, (9) 257*c*.
torsional testing at high temperatures, (3) 81*h*.
Zr silicate in, for heat-resistant machine parts, P (4) 102*c*.
Ceramic-metal systems. See also *Enamels*.
physicochemical properties of, (5) 127*j*.
Ceramics, fundamental principles, from research standpoint, (11) 320*c*.
science of, Vol. I, B (4) 123*f*.
Ceramoplastic materials, method of making, P (2) 49*c*.
Cerium, as activator in CaF_2 optical maser, (6) 166*g*.
carbide, hydrolysis of, (1) 28*e*.
Ce^{3+}, in glass, photoionization of, (3) 67*b*.
dioxide, in grinding and polishing of eyeglass lenses, (7) 184*f*.
dioxide, thermal expansion by X-ray diffraction, (6) 175*h*.
in glasses, effect on γ-ray-induced coloring, (1) 5*e*.
ion, role in preventing γ-ray induced coloration of glass, (11) 304*h*.
nitride, magnetic susceptibility of, (4) 119*b*.
oxide, systems. See *Systems*.
sulfide, in semiconductor element, P (5) 137*e*.
tellurite, method of making, P (1) 20*c*; P (1) 21*c*.
Cermets. See also *Turbines, blades*.
coatings for high-temperature protection, (5) 127*d*.
in composite coatings, (8) 207*d*.
as core for fuel element, P (9) 244*h*.
drawplates, electrolytic treatment of, (4) 97*f*.
hard alloys, based on borides of Cr, Ti, and W, (4) 118*c*.
molecular, method of making, P (3) 74*f*.
Mo-Al_2O_3, P (6) 162*j*.
with oxides or carbides as brittle phase, review of, (1) 28*f*.
plated coatings, for heat and wear resistance, (6) 155*e*.
properties and uses, B (2) 61*i*.
rare earth oxide, in stainless steel, (8) 214*b*.
tool, ultra-high-speed cutting, (8) 203*f*.
U/UC, preparation, fabrication, and properties, (8) 214*h*.
wear-resistant, based on Al oxide and heavy-metal carbides, P (3) 75*b*.
Cesium, adsorption on clay minerals, (6) 169*g*.
analcite, dielectric properties, (8) 219*a*.
chloride, systems. See *Systems*.
chloride, transition point depression by RbCl, (2) 59*d*.
iodide, γ and photoluminescence of, (5) 135*a*.
kinetics, of clinoptilolite, effect of base cation, (6) 172*c*.
reactions with cation exchange materials, kinetics of, (7) 199*g*.
triborate, crystal structure of, (10) 291*h*.
Chalcocite, Cu_2S, distribution of atoms in, (11) 317*a*.
Chalcogenides, of group IV, semiconducting, solid solutions in, (4) 120*g*.
of group IV, semiconducting, in solid solutions with As and Sb, (3) 89*c*.
transition metal, estimation of standard entropies, (1) 27*j*.
Chalk, colored, for marking on ceramics, P (3) 75*j*.
Chamotte. See *Grog; Refractories*.
Checker-brick. See *Refractories*.
Chemical analysis. See *Analysis*.
Chemical industry, borosilicate glassware for, (1) 6*j*.
bulk handling of powders in, (1) 22*d*.
computer control in, (9) 258*f*.
dish granulation in, (9) 250*a*.
glass-lined mild-steel vessels for, (1) 4*h*.
porous materials in, (3) 83*a*.
use of refractories in, (3) 73*c*.
Chemical properties, of abrasive grain, I, (6) 153*f*; II, (8) 203*i*.
of carbon and graphite, (6) 159*f*.
of Lucalox alumina, (9) 254*h*.
of Na_2O-B_2O_3-SiO_2 glass, (6) 156*i*.
Chemicals, industrial, ASTM standard for, B (9) 259*b*.
plant, statistical maintenance control in, (3) 79*j*.
processing equipment, glass lined, P (3) 65*e*.
for quelling dust, (2) 34*i*.
Chemical transport reactions, V-VII, (5) 142*b*.
Chemistry. See also *Analysis; Crystal chemistry; Electrochemistry; Geochemistry; Magnetochemistry; Radiochemistry*.
Chemistry (*continued*)
abbreviations, in Russian abstract journals, (5) 148*b*.
analytical, of elements, B (10) 300*d*.
in archeology, building technology, and monument preservation, B (8) 231*a*.
of cement, Vols. I, II, B (5) 148*i*; B (9) 261*j*.
cement, equivalents in, as basis for chemical calculations, (5) 126*j*.
chemical transport reactions, VIII, IX, (6) 172*c*.
of difluorides of Ge and Sn, (1) 26*i*.
high-temperature, (9) 258*c*.
inorganic, Vol. III, B (3) 92*a*.
of ortho- and ring silicates, B (5) 151*g*.
photo-, of AgCl crystals doped with divalent cations and anions, (3) 85*f*.
physical, of clay suspensions, B (2) 61*j*.
of compound semiconductors, B (9) 260*f*.
of hydraulic materials, (8) 205*j*.
index of selected property values, B (4) 122*h*.
of oxide ceramics, B (2) 61*i*.
preparative inorganic, use of electrical discharges in, (9) 252*i*.
reactor vessels, bolt torques and gaskets for, (9) 238*b*.
of surface of silica, and silicosis, (3) 90*c*.
China. See also *Art and artware; Dinnerware; Porcelain*.
directory, B (8) 231*h*.
fine, role of Minton patent in, (10) 265*i*.
Herend, history of, B (10) 299*b*.
household, decal decoration line for, (9) 245*i*.
Pinxton factory, original factory records, I, II, (6) 153*h*.
China clay. See *Kaolin*.
Chlorides, aqueous solutions, crystallization of sulfides and carbonates from, B (9) 263*e*.
Chlorination, of bauxite sludge, (11) 314*h*.
of ilmenite, in rutile production, (7) 197*j*.
Chlorite, -like substances, electrolytic method for producing from montmorillonite, (11) 317*g*.
polytypism, I, (9) 255*i*.
semiquantitative analysis by X-ray diffraction, (6) 168*j*.
swelling, from basic igneous rocks, (11) 315*b*.
swelling, comparison to vermiculite, (11) 314*j*.
Chromates, (V), alkaline earth, magnetochemical and X-ray study, (4) 111*i*.
infrared spectra of, (5) 144*i*.
chromaticity. See *Color*.
Chromatographs, temperature regulator for, P (3) 90*a*.
Chromatography, analysis, P (1) 31*a*.
analysis, apparatus and method, P (10) 287*c*.
apparatus, with column of electroconductive material, P (10) 287*b*.
gas, in analysis of inorganic materials, P (1) 31*c*.
analyzer with dual columns, P (10) 287*b*.
apparatus, P (10) 286*i*.
apparatus, combined with mass spectrometer, P (7) 201*i*.
detector for, P (8) 223*f*.
microsyringe for, P (11) 320*b*.
method and apparatus, P (1) 31*a*.
thin-layer, laboratory handbook, B (8) 234*j*.
Chrome. See *Chromium; Refractories*.
Chrome-magnesite brick. See *Refractories*.
Chromia. See *Chromium, oxide*.
Chromite. See also *Refractories*.
Indian, mineralogy of, (8) 228*j*.
in Oregon, data on, (4) 109*a*.
ores, Russian, composition and properties, (7) 197*e*.
stoichiometric, preparation of, (9) 256*g*.
vanadium in, titrimetric determination, (1) 31*a*.
Chromium, behavior, in system $MgAl_2O_4$-Al_2O_3, (1) 26*f*.
boride, as base for metalloceramic hard alloy, (4) 118*c*.
interaction with Mo, (10) 294*b*.
production of, P (10) 277*g*.
production by thermite process, (9) 243*i*.
chromic oxide, effect on adsorption of phosphate ion, I, II, (3) 85*h*.
$CrO_{2.8}$, properties of, (4) 117*d*.
Cr_2O_3, magnetic property of, (4) 116*c*.
dioxide, ferromagnetic, preparation of, (4) 118*g*.
distribution, in synthetic ruby crystals, (5) 142*c*.
ductile, P (5) 133*g*.
effect on electrical conductivity of single-crystal alumina, (10) 280*d*.
effect on glass color, (8) 208*g*.
fluoride, systems. See *Systems*.
ions, in crystals, fine-line spectra of, B (9) 260*j*.
nitride, electrical and galvomagnetic properties of, (2) 57*a*.
nitride, preparation and properties, (4) 118*j*.
oxide, ferromagnetic, P (5) 137*e*; P (6) 166*c*.
ferromagnetic, containing F, preparation of, P (4) 105*c*.
method of making, P (3) 84*f*.
refinement of crystal structure, (4) 120*d*.
in refractories, P (4) 102*d*.
systems. See *Systems*.
thermal-expansion anisotropy of, (1) 30*g*.
systems. See *Systems*.
-tungsten oxide, crystalline, P (4) 105*j*.
Chromophors, inorganic, classification of, (9) 238*k*.
Chrysotile, in asbestos-cement sheets, determination with X-ray diffractometer, (7) 179*d*.
fiber, synthetic, growth of, (4) 114*b*.
Circuits, control, for automatic crushers, P (6) 170*g*.
cryogenic resonant, measurement of Q in, (7) 192*i*.
electronic, use of materials with tetragonal W bronze crystal structure, (10) 282*h*.
electronic, on wafer-thin ceramic tile, (2) 47*h*.

Circuits (*continued*)
integrated, compatible techniques for, (10) 279*i*.
integrated, in modules, (10) 281*e*.
linear dimension gage, P (8) 224*b*.
logic, from thin magnetic films, (7) 192*g*.
miniaturized etched, optical soldering of connections, (7) 192*a*.
printed, on ceramic base, P (6) 166*b*.
printed, with interconnection between pellet type components, (6) 165*a*.
thin-film, CdS TFT in, (2) 48*b*.
Classification. See also *Separation; Separators.*
air-dust, P (6) 167*f*.
crystallochemical, of simple and interstratified clay minerals, (11) 320*e*.
of diamond fines, apparatus for, P (2) 51*g*.
of glassware, (7) 184*f*.
of granular materials, by centrifugal air separation, (9) 250*h*.
of granular materials, centrifugally, P (9) 250*e*.
of inorganic chromophors, (9) 238*h*.
of methods for determining particle size, (7) 195*i*.
of montmorillonite, (4) 116*c*.
Classifiers. See also *Beneficiation.*
air-sweep, partial vacuum, P (2) 54*j*.
centrifugal, for elutriation of kaolin, (10) 288*e*.
centrifugal vortical, and stock cleaner, P (3) 83*e*.
for granular material, P (7) 197*g*.
hydraulic, P (4) 106*h*.
jet type, for classifying, dewatering, and recovering slack or other fine ore, P (2) 55*j*.
Clays. See also *Ball clay; Fireclay; Kaolin.*
Al_2O_3 production from, evaluation of HCl processes, (6) 170*c*.
alumina production from, sulfuric acid processes, (9) 254*e*.
attapulgite, dispersions, drying of, P (1) 26*c*.
beneficiation, P (4) 110*g*.
brick, chemical treatment for improvement of properties, (1) 12*h*.
brightening, by froth flotation of sulfidized clay pulp, P (5) 141*e*.
Canadian, nature and properties, (2) 54*c*.
for cement raw mix, physical, chemical, and mineralogical studies on, (7) 181*e*.
and clay minerals, proceedings of 8th national conference, B (3) 90*j*.
and clay minerals, proceedings of 9th national conference, B (5) 150*i*.
and clay products, (7) 202*a*.
of coastal plain of S. Car., use in structural clay products, (3) 82*f*.
color in, (3) 63*j*.
constitution and origin, B (2) 61*j*.
deposits, variations in, (1) 25*f*.
dispersion, action of deflocculant, (10) 286*e*.
effect on enamel properties, (7) 183*c*.
effect on set and bubble structure of enamel, (2) 37*a*.
effect of sulfur on, (1) 25*e*.
expanded, P (4) 100*h*.
expansion and contraction during firing, measurement by dilatometer, (10) 286*b*.
fractured, P (2) 55*h*.
glacial lake and glacial marine, of Maine, use as lightweight aggregate, (4) 109*b*.
highly swellable, for foundry molds, P (4) 102*c*.
kaolinite-diaspore-boehmite, structure-controlled reactions in, (1) 30*f*.
kaolinite-mica-quartz, high-temperature phases in, (11) 317*h*.
Kentucky, analyses, (8) 225*g*.
from Kerala State, DTA, X-ray analysis, base exchange, and refractoriness, (6) 170*c*.
laminations in, causes and cures, III, IV, (11) 305*e*.
limey, brick from, coloration of, (2) 43*f*.
minerals. See also specific types.
minerals, B (2) 61*j*; B (10) 299*d*.
adsorption of Cs on, (6) 169*g*.
adsorption of dyes by, (6) 169*h*.
in British Columbia subsoils, (5) 140*i*
common, as continuous series, B (4) 124*c*.
determination of surface area by heat of immersion, (6) 172*j*.
dimensions of crystals, (4) 113*a*.
expandable chioritic from carbonate rocks of Tennessee, (4) 109*h*.
formation, relation to ionic coordination in aluminosilicic gels, (4) 115*j*.
growing mullite from, (5) 143*j*.
identification by single crystal electron diffraction, (4) 107*h*.
interstratified, from basic igneous rocks, (11) 315*b*.
in Missourian stratigraphic sections, identification by DTA, (3) 82*b*.
modifications to powder cameras for use on, (11) 313*i*.
in playa sediments of Mojave Desert, Calif., (4) 109*a*.
in podzol profiles in Fennoscandia, (11) 315*c*.
simple and interstratified, crystallochemical classification, (11) 320*e*.
X-ray identification and crystal structure, B (7) 202*f*.
Montana, progress report, (3) 83*b*.
mullitization of, (9) 256*j*.
of N. Dak., as potential source of alumina, (3) 82*e*.
-organic complexes, (8) 225*c*.
from Philippines, preliminary tests on, (3) 83*a*.
plastic, automatic shaping of flowerpots and bowls from, (10) 284*a*.
effect on porcelain green strength, (10) 278*e*.
Indian, evaluation as ball clay substitutes, (6) 169*j*.

Clays, (*continued*)
moisture movement in, (11) 305*f*.
nature of dispersion of, (4) 109*j*.
plasticity of, study by symmetrical cyclic deformation, (11) 318*d*.
plastic properties, effect on design of extrusion nozzles, (3) 71*d*.
preparation for electron microscope examination, (5) 138*c*.
product, lightweight adsorbent, P (1) 25*j*.
production and uses, 1961 summary, (3) 82*d*.
properties and mineral composition, variation on firing, (7) 197*e*.
from Quetrequile, X-ray, DTA, and electron microscopy studies of, (6) 169*g*.
rapid particle-size analysis, packing-volume technique, (3) 83*c*.
of red and lateritic soils, mineralogy of, (3) 82*g*.
refractory, beneficiation of, (6) 169*f*.
deposits of Haldeman and Wrigley quadrangles, Ky., (6) 170*a*.
homogeneity tests, (10) 286*d*.
schistose, of central Europe, (4) 110*e*.
and schistous, evaluation of, B (10) 300*j*.
schistous, processing technology, B (8) 234*i*.
relation between drying rate and relative elongation during tension, (1) 23*b*.
for roofing tile, (3) 71*a*.
science of, (10) 297*g*.
screens for control of grade, (10) 284*b*.
separation of glass sand from, (10) 289*a*.
silicate, modification to produce organophilic substances, P (2) 55*d*.
soluble salts in, analysis, (2) 56*b*.
structure, acid dissolution techniques in determination, B (4) 124*e*.
synthetic, B substitution in, (7) 198*b*.
Syrian, properties of, (10) 289*b*.
-talc body, thermal shock resistance of, (10) 279*b*.
testing and processing, for art students, (4) 95*i*.
titration of, formation of double hydroxides in, (10) 293*a*.
waste, in hardened wall tile, (9) 245*j*.
wet, preparation, for brickmaking machines, (2) 44*b*.
Whitemud formation, effect of mineralogical composition on use, (10) 292*d*.
Cleaners, electrolytic, for metals, salt bath as, P (10) 269*g*.
Cleaning, processes, for borosilicate glass, (9) 239*h*.
Clinker. See *Cement; Magnesite.*
Clinoptilolite, effect of base cation on Cs kinetics of, (6) 172*c*.
Coagels. See *Colloids.*
Coal. See also *Coke; Fuels.*
ash. See *Ash.*
ASTM standard for, B (9) 259*b*.
coking, variation in fluidity at constant temperature, (7) 196*e*.
rheological properties during early stage of thermal softening, (7) 196*g*.
Coatings. See also *Enamels; Glazes; Resins.*
for abrasive articles, P (9) 236*b*.
alumina, flame-sprayed, P (2) 37*i*.
alumina, flame-sprayed, uses for, (7) 183*e*.
Al oxide, anodic, dielectric properties of, (9) 246*i*.
amorphous silica and phosphor, for fluorescent lamp tube, P (10) 272*d*.
application. See also *Electrostatic processes.*
to abrasives, (11) 301*f*.
by electrostatic spraying, P (1) 5*a*.
to glass filaments, P (7) 186*j*.
aqueous, from clay coated with polymers, P (4) 111*a*.
aqueous, for production of shell molds, P (1) 15*g*.
$BaTiO_3$, application by electrophoretic deposition, (1) 19*f*.
$BaTiO_3$ single crystal, electron microscope evidence of ferroelectric domains in, (6) 163*i*.
black emissivity, (2) 48*h*.
BN, diffusion of B into semiconductive wafers, (2) 36*i*.
BN, for refractories, reaction with Al, P (7) 189*j*.
boron phosphide, abrasion and corrosion resistant, P (9) 239*b*.
for brickwork, masonry, concrete, and wood, P (1) 13*a*.
bubble, for wire, P (4) 97*i*.
carbon, for electron microscopy, (11) 312*h*.
for carbon articles, P (6) 162*j*; P (6) 163*a*.
for carbon for nuclear reactors, P (5) 133*c*.
CdS photoconductive, effect of heat treatment on, (5) 143*a*.
carbide, for graphite, (10) 268*h*.
catalytic, for thermocouple elements, P (4) 108*d*.
cement, for exterior surfaces, P (9) 237*d*.
ceramic, II, (10) 268*j*.
cermet, and refractory, properties of, (2) 36*j*.
for drill bushings, P (1) 4*i*.
of glass, refractory particles, and flux, (1) 4*j*.
for high-temperature protection of cermets, (5) 127*d*.
for jet turbine buckets, P (4) 97*h*.
for malleable metal, P (8) 208*c*.
for metal bodies, P (3) 65*d*.
in shell molding process, (6) 159*i*.
for sponge in production of porous materials, P (9) 246*c*.
thermofluid vehicles for preparation of, P (6) 155*i*.
for tuyeres, P (4) 97*g*.
ultrathin, (5) 135*c*.
clay, method for casting, P (2) 51*e*.
composite, engineered, (8) 207*d*.

Coatings (*continued*)
conducting, for $BaTiO_3$ in electronic resistor, P (2) 50*c*.
conductive, formulation and selection, (6) 155*c*.
containing ceramic metal oxide particles, P (2) 38*a*.
Cu oxide, in composite pigment particle, P (11) 303*d*.
diffusion, for protection of refractory metals, (1) 4*d*.
for disposable pattern for metal casting molds, P (3) 73*i*.
electrical insulating, P (9) 248*j*.
electrical insulating, of MgO dispersed in aqueous solution of CaO, P (8) 220*g*.
electrically conducting, on glass, P (6) 157*i*.
for glass article, P (5) 130*c*.
for glass or ceramics, process and apparatus for, P (8) 211*i*.
heat resistant, P (11) 311*f*.
method of making, P (10) 283*f*.
method of producing on glass, P (5) 131*g*.
transparent, on glass objects, P (4) 99*e*.
electrostatic. See also *Electrostatic processes.*
apparatus for applying, P (1) 4*h*.
device for deposition control, P (2) 39*i*.
machine for deposition on heated surfaces, P (2) 38*d*.
spray gun for, P (2) 38*e*.
emissive, for spraying cathodes, P (7) 193*h*.
enamel, for hot-water heaters, corrosion testing, (2) 36*e*.
epitaxial layer, determination of thickness from interference fringes, P (11) 311*e*.
evaporated Permalloy, effect of crucible material on magnetic anisotropy of, (5) 132*h*.
for ferrous article, process, P (8) 208*b*.
for ferrous material, P (5) 128*b*.
flame-sprayed, evaluation for Army weapons applications, (10) 268*j*.
flame-sprayed ceramic, physical properties of, II, (1) 4*b*.
flow, machine, for cover-coat enamels, (5) 127*i*.
fluidized bed process, with thermosetting materials, P (9) 239*a*.
for fluorescent lamps, P (2) 42*g*; P (10) 271*h*.
flux, for granular or briquetted refractory materials, P (4) 102*f*.
glass, for chemical industry, (1) 4*h*.
effect of moisture on H defects in, (1) 4*c*.
for electric metal oxide resistor, P (4) 105*g*.
irradiation with 100 kv electron beam, (2) 40*a*.
on metal, study of crystallization by electron microscopy, (8) 207*j*.
superthin, uses of, (1) 8*i*.
thin, electron microscopic study, B (11) 320*j*.
thin, flexible, on wire or foil, P (3) 65*g*.
for glass, for improving adherence of adhesives, (9) 240*c*.
for glass, method of applying, P (9) 242*f*.
gold, application with spray guns, (10) 278*j*.
graphite, conversion to carbide by vapor deposition, (8) 206*i*,*j*.
graphite, for fibrous material for electric resistance elements, P (7) 193*i*.
heat-resistant, for basic refractories in furnace, P (9) 244*j*.
heat-resistant, development for metals, (9) 238*c*.
high-melting, on steel strip, P (6) 155*f*.
high-temperature, of five layers of metal and refractory material, P (9) 239*a*.
oxidation protective, for V-base alloys, (9) 238*h*.
oxidation-resistant, for Ta-base alloys, (8) 207*a*.
oxidation-resistant, for V-base alloys, (8) 207*i*.
for incandescent lamp envelope, P (10) 271*d*.
for inhibiting corrosion of ferrous metals, P (1) 5*b*.
inorganic, for solar energy absorption, (10) 269*d*.
insulating anodic oxide, properties, (9) 248*d*.
iron, evaporated, effect of crucible material on induced anisotropy, (10) 274*e*.
PbO_2, sputtered, physical properties of, (8) 219*j*.
PbS, effect of O on photoluminescence, (5) 135*b*.
light-reflecting, P (8) 221*j*.
light-scattering, for inside light bulbs, P (2) 60*i*.
lime, for tapping rod, P (2) 46*h*.
MgO, on Si steel, P (6) 155*f*.
MgO, thin self-supported, secondary emission of, (5) 145*h*.
magnetic, thin, making of apparatus with, P (10) 283*a*.
magnetic ferrite, method of making, P (10) 283*g*.
metal, for ceramic, glass, or mica, fluxing for, P (3) 77*d*.
-ceramic laminated, P (2) 38*f*.
for ceramic titanate body, P (1) 20*j*.
and nonmetal, deposition with plasma arc torch, (9) 238*b*.
metallizing, for Al_2O_3, P (5) 136*e*.
for alumina type ceramic body, P (1) 20*b*.
application to ceramic parts, P (7) 193*h*.
ceramic mixture, P (9) 239*b*.
for ceramics, P (2) 49*i*.
for glass fibers, P (3) 69*f*.
for glass machinery and molds, (4) 98*e*.
for piezoelectric transducers, ceramic binders for, P (6) 166*d*.
for siliceous inorganic fibers, P (6) 155*f*.
tape, method for applying ceramic-metal seals, (1) 19*j*.
metal oxide, forming on bent glass sheet, P (6) 158*d*.
mixed oxide, method of making, P (3) 65*f*.

Coatings (*continued*)
Mo, for UO_2 particles, sintering studies on, (11) 306*g*.
for muffler, P (9) 239*c*.
multilayer, strip form heaters for, P (9) 249*b*.
new types, report on, (9) 238*j*.
Ni-P alloy, for glass shaping tools, P (4) 99*j*.
Nb oxide, current-controlled negative resistance in, (10) 280*b*.
nitrate or acetate, for vitrified siliceous structures prior to melting, P (3) 70*g*.
organic, rust control with, (11) 302*i*.
organosilicon polyol, for glass fibers, P (7) 186*d*.
oxide, anodic, on Bi, kinetics of formation, (3) 87*h*.
application to nonporous refractory substrate, P (7) 183*i*.
electrically conducting, on nonglazed ceramic parts, P (3) 77*i*.
flame-sprayed, rod-type, in ceramic tooling of ceramic shapes, (6) 167*e*.
for metal particles, P (3) 74*i*.
of transition metal, for refractory oxide particles, P (4) 102*d*.
oxide glass, preparation by reactive sputtering, (3) 67*d*.
palladium, in combustible gas detector, P (9) 253*f*.
parting composition for sprayed metal shells, P (6) 162*a*.
plasma, with ZrO_2 rods, (6) 155*c*.
plastic, application to glass bottles, P (2) 42*a*.
fluid, for cleaning glass lens, P (6) 158*e*.
on glass objects, P (10) 272*i*.
plated cermet, for resistance to heat and wear, (6) 155*e*.
polyethylene derivative, for precoating and coating glass fibers, P (9) 242*g*.
powdered inorganic insulating, for electric resistors, P (2) 49*e*.
of powdered metal, in metal-to-ceramic seals, P (3) 78*a*.
process, with SiO_2, P (9) 249*e*.
for protection of refractory metals from oxidation, (3) 65*d*.
protective, for Mo, B (7) 202*c*.
for refractory metals, P (9) 239*c*.
for Ta-base alloys, (8) 206*g*.
pyrolytic deposition, new materials for, (2) 44*h*.
pyrolytic graphite, on graphite nozzles, (8) 212*j*.
reflective, electrostatic application to lamp envelope, P (10) 271*a*.
on refractories and kiln furniture to reduce dusting and spalling, (5) 132*j*.
refractory, insulating, on sheet metal, P (2) 37*h*.
multiple, for hot furnace repair, P (9) 244*i*.
oxidation-resistant, for metals 3000° to 6000°F, bibliography, (8) 207*f*.
oxide, P (1) 16*g*.
solvent-proof, and anticorrosive, P (11) 303*d*.
for refractory furnace walls, P (5) 140*d*.
for refractory metals, development of, (10) 269*f*.
removal from glass, P (6) 157*f*.
report of working group on, (9) 238*c*.
resistance, for glassware, P (9) 242*b*.
semiconductive resistive, for cathode ray tubes, (2) 48*j*.
semiconductor, production of, P (3) 78*j*.
shrinkage, in Debye patterns, eliminating effects of, (6) 168*f*.
shrinkage funnel inhibitor, casing for production in ingot or hot top, P (10) 276*j*.
SiO_2, for carbonaceous articles, P (10) 277*d*.
SiO_2, for reducing ambient sensitivity of junction detectors, (10) 282*e*.
silicate, colored, for glass, P (4) 99*a*.
silicate, thin-layer, preparation from solutions, (4) 97*b*.
Si, single crystal, method of making, P (10) 283*d*.
of Si, W, and B, fluidized bed method of applying, (6) 155*c*.
SiC, method of depositing, (2) 48*f*.
SiC, siliconized, for graphite element for nuclear reactors, P (6) 163*a*.
silicone, for frit used to decorate glassware, P (11) 305*a*.
Si oxide, for semiconductor devices, P (9) 249*h*.
Si oxide, thickness measurement, (1) 29*f*.
Si-SiO_2, laboratory study of, (1) 30*f*.
for silk screening thin mica sheets with silver paste, (9) 247*g*.
silver, for mirrors, P (4) 99*c*.
spectral data for, (8) 222*h*.
sprayed, binders for controlling application behavior, (3) 75*e*.
sputtered SiO_2, as mask for GaAs, (9) 248*d*.
stable, high-refractive-index, for glass, P (2) 43*a*.
stable, "white," for spacecraft temperature control, (8) 207*b*.
stencil screen, of polyvinyl alcohol, polyvinyl acetate, and light sensitizing agent, P (11) 312*e*.
stores, for magnetic cores, (4) 104*i*.
SrO, for cathodes, (5) 135*i*.
Ta, arc-plated and W arc-plated, for graphite, P (8) 215*h*.
Ta_2O_5 and SiO_2, rectifying action and emf at high temperatures, (10) 281*e*.
temperature control, materials for, (10) 269*d*.
thickness, deposition and measurement, P (3) 77*f*.
thin, automatic deposition control, (7) 191*g*.
magnetic, P (2) 50*c*.
magnetic, for logic circuits, (7) 192*g*.
mullite, preparation, (6) 165*c*.
with negative temperature coefficient of electrical resistance on ceramics, P (4) 106*a*.
Coatings (*continued*)
tin oxide, conducting, optical properties of, (6) 175*g*.
and Nichrome, as resistors, (10) 279*i*.
optical and electrical properties, (6) 174*e*.
titanate, for improving scratch resistance of glass, P (1) 12*d*.
TiO_2, as capacitors produced by thermal decomposition of organic Ti compounds, (8) 218*f*.
titanium boride, on metals, P (2) 38*e*.
transparent conductive reflection-reducing, for nonconductive objects, P (10) 273*b*.
WC, for thin gage metal stock, (3) 72*h*.
WC-CrC-Ni, flame spraying of, (4) 103*d*.
ultrathin, P (2) 43*b*.
uniaxial cylindrical thin, magnetization of, (9) 247*h*.
vacuum, apparatus for, P (2) 50*e*.
voltage sensitive dielectric, in TiO_2 diodes, (7) 191*c*.
wear resistant, properties and uses, (6) 155*c*.
for welding rod, P (7) 183*h*.
zirconia, flame sprayed, for fuel cell components, (2) 36*h*.
ZrC, for uranium oxide fuel particles, (11) 308*a*.
Cobalt, Co^{2+} ions, effect on magnetic anisotropy of ferrimagnetic oxides with hexagonal crystal structures, (5) 144*g*.
compounds, hydrothermal preparation, (10) 294*a*.
magnetite phases, (2) 57*h*.
stabilities of, (9) 257*g*.
difluoride, crystal structure determination, (10) 296*h*.
manganate, crystal structure and ferrimagnetism in, (4) 113*d*.
nitrate, solid state reaction with hydrated and α-alumina, (1) 30*b*.
oxide, effect of MgO on reduction of, (10) 294*g*.
electrical conductivity as function of temperature and equilibrium O pressure, (9) 247*b*.
systems. See *Systems*.
whiskers, growth of, B (9) 262*e*.
Coesite, formation from pyrophyllite at high pressures and temperatures, (4) 114*f*.
geological discovery, (7) 197*i*.
optical crystallography of, (7) 199*a*.
Coke. See also *Coal; Fuels*.
ASTM standard for, B (9) 259*b*.
properties, correlation with plastometric properties, (7) 196*i*.
semi-, rheology at high temperatures, (7) 196*i*.
Coke ovens. See *Refractories*.
Colloids. See also *Silica, gels*.
coagel, stable, production from alkaline earth fluoride, P (1) 26*d*.
gels, adsorbent, coprecipitated, (1) 27*b*.
alumina, P (4) 111*b*.
aluminosilicic, ionic coordination in relation to clay mineral formation, (4) 115*j*.
formation from attapulgite clay, P (6) 170*j*.
in glaze suspensions, measurement of critical breakdown characteristics, (3) 75*h*.
granular, method of preparing, P (2) 55*a*.
thixotropic, exchangeable ions for formation of skeleton of, (3) 88*c*.
sols, hydrous oxide, P (9) 246*e*.
sols, stable silica-clad thoria, P (10) 278*a*.
Color. See also *Pigments; Stains*.
of abrasive grain, effect on efficiency, (6) 153*f*.
in brick from limey clays, (2) 43*f*.
centers, formation in sodium silicate and quartz glasses by γ-radiation, (5) 129*e*.
centers, in KCl, (5) 142*e*.
ceramic, composition and method of applying, P (9) 239*d*.
effect of combustion gases, (2) 47*a*.
machine for continuous spreading in porcelain plant, (7) 190*f*.
and pottery decoration, B (6) 176*h*.
in ceramics, development of, (3) 63*f*.
of ceramics based on spodumene, (1) 17*i*.
control, in enameled appliances, (5) 127*i*.
of fusion melts of elements, (4) 112*j*.
γ-ray, of NaCl crystals, effect of plastic deformation on, (5) 143*g*.
γ-ray induced, in glass, Ce ion in preventing, (11) 304*h*.
of glass, Cr-containing, (8) 208*g*.
containing Ag and Ti, (8) 208*h*.
containing Ti, (11) 303*f*.
limitations, in pigments, (8) 230*f*.
mauve, in activated CaO coated cathodes, (10) 279*h*.
measurement. See *Colorimetry*.
Naples yellow, from raw glazes, (7) 177*i*.
in photosensitive glasses, by X-radiation, (6) 156*a*.
of portland cement and hardened mortar, (7) 178*j*.
red-brown, in enamels, ferric oxide for producing, (10) 269*b*.
retention, cupric sulfate test for, (9) 238*b*.
in salt glazing, (5) 126*a*.
in silica minerals, from radiation, (4) 119*f*.
sorting apparatus, photoelectric, P (3) 81*c*.
specifications, pitfalls in, (8) 230*i*.
systematic description of, (8) 230*i*.
technology, and decoration of ceramics, XV, (4) 109*b*.
Colorimeters, and photoelectric color sorting apparatus, P (3) 81*c*.
Colorimetry, continuous, for determination of components of liquid mixture, P (2) 60*b*.
Coloring materials. See *Decoration; Pigments; Stains*.
Columbite, and related minerals, treatment of, P (3) 85*c*.
Columbium. See *Niobium*.
Combustion. See also *Burners; Firing; Flames; Furnaces; Heat; Kilns*.
analysis, apparatus for, P (2) 59*j*; P (7) 196*a*.
control, measuring instruments for, (5) 140*e*.
control, secondary regeneration in, (10) 287*g*.
of gaseous and liquid fuels, in glass furnace heating, (8) 208*j*.
oxygen for, in glass industry, (2) 40*f*.
principles, in relation to product requirements and keeping stack emission to minimum, (6) 169*c*.
processes, in firing lightweight brick, (2) 53*e*.
in rapid determination of S in basic slag, (6) 154*j*.
Comminution. See *Crushing and grinding*.
Compaction. See also *Pressing*.
of powders, gas displacement during, (1) 22*j*.
of powders, radial pressures in, (1) 23*a*.
process, for separate slabs, P (8) 221*f*.
Compacts, high density, forming of, P (9) 250*f*.
Comparators, peak ac to dc, (7) 195*f*.
Composites, metal and fiber, methods of making, P (10) 272*h*.
method of making, P (11) 311*h*.
production and performance, B (5) 148*e*.
refractory, report of working group on, (9) 238*e*.
structural, material composition, P (10) 277*j*.
Computers, analog, in experimentation with rotary cement kiln, (11) 302*a*.
closed-loop, for kiln control, (2) 35*g*.
control, in cement industry, (5) 126*g*.
as controls in chemical and cement fields, (9) 258*f*.
digital process control, capabilities and types, (5) 126*e*.
for increasing kiln output and decreasing costs (6) 154*i*.
for low cost control of unit processes, (2) 51*b*.
process control, in cement industry, (5) 126*j*.
program, for chemical analyses of amphiboles, (6) 167*j*.
in simulation of wet process cement kiln operation, (5) 126*d*.
yield strength, for testing machine, P (5) 139*g*.
Concentration, electrodialysis in, (10) 284*c*.
Concentrators. See also *Separators*.
for quantitative analysis of substance in liquid, P (10) 287*c*.
Concrete. See also *Cement; Masonry; Mortars Pozzolans*.
ASTM standard for, B (9) 259*b*; B (10) 298*h*.
blocks, drying shrinkage of, (2) 34*d*.
reinforced, for tunnel kiln car lining, (7) 196*h*.
structural, equipment for making, P (2) 51*b*.
for building load supporting surfaces, P (5) 127*b*.
cellular, high-strength autoclaved, P (2) 36*c*.
cement performance in, long-time study, (4) 96*c*.
coating for, P (1) 13*a*.
compressive strength, effect of curing under pressure, (8) 204*b*.
compressive strength, effect of tensile creep, (8) 204*f*.
consistency at low temperature, relation to false set of cement, (7) 181*j*.
corrosion, effect of synthetic CO_2-containing aqueous solutions, (1) 2*f*.
cracks in, method of indicating, (2) 52*b*.
creep of, (6) 153*b*.
durability in corrosive waters, effect of porosity, (1) 3*a*.
effect of voids on neutralization of, (7) 181*d*.
efflorescence on, change in composition, (7) 178*g*.
with fly ash, neutralization, 5-yr test, (8) 204*j*.
fly ash as pozzolan in, (4) 96*d*.
fly ash as replacement for portland blast-furnace slag cement, (1) 2*h*.
fracture, statistical aspects, II, (9) 237*g*.
hardness, effect of surface-active agent, (1) 2*f*.
with high-alumina cement, service in roofs of electric furnaces, (7) 188*b*.
lightweight, aerated, P (3) 65*b*.
lightweight, method for dividing, P (3) 65*a*.
long-time deformation, rheological laws of, (7) 182*a*.
micro-, increase in corrosion resistance in, (8) 205*b*.
mixture, rheology and measurement of mixture mobility, (6) 154*b*.
neutralization, measurement with radioactive CO_2, (8) 205*e*.
physicochemical interaction with medium, (1) 2*i*.
portland cement, adjuvant, P (1) 3*h*.
coloring method, P (4) 96*h*.
rheology of, (10) 267*d*.
properties of, B (5) 148*i*.
as reactor material, (10) 266*h*.
refractory, from alumina cement, properties and use, (3) 72*d*.
hydraulic setting, P (6) 162*e*.
and insulating, effect of heat on, (8) 204*e*.
porous, P (1) 17*a*.
shrinkage of aggregates in, (10) 267*h*.
slag sand and fly ash in, (8) 206*a*.
for spray gun application, P (10) 277*e*.
steel in, rapid destruction, (8) 206*c*.
structural, lightweight aggregates for, (11) 302*h*.
structural lightweight, strength under combined stress, (4) 96*b*.
tensile strength, research on, (1) 3*i*.
test beams, field-fabricated, factors affecting strength, (2) 34*h*.
tobermorite gel in, (11) 302*c*.
water-quenched slags as additives, P (4) 96*j*.
water vapor permeability, measurement of, (9) 237*d*.
Condensers, impregnated paper as dielectric in, P (9) 249*c*.

Condensers (*continued*)
multiple layer, making by vapor deposition, P (10) 283*h*.
Conductance, ionic, of KCl in solid state, (10) 291*d*.
Conductivity, electric, and(or) **Conduction, electric,** in α-Nb_2O_5, nonstoichiometric, (9) 256*f*.
anomaly in Sm-doped $BaTiO_3$, (3) 76*f*.
of $BaTiO_3$ single crystals, (5) 143*b*.
of borosilicate glass (volume), comments on, (10) 270*a*.
of CdO, (8) 219*g*.
in CdSe, mechanism of, (4) 116*j*.
of CoO, NiO, and MnO as function of equilibrium O pressure at high temperatures, (9) 247*b*.
of Cu_2O during dissociation, (7) 191*f*.
of Cu_2O in stabilization region in air, (7) 191*g*.
dc, of Ca boroaluminate glasses, (1) 8*j*.
of earth's materials, (10) 282*g*.
electronic, in glass, (10) 280*i*.
electronic and ionic, in single MgO crystals, (9) 247*f*.
of glass, effect of γ-ray irradiation, (8) 209*a*.
relation to ductility, (7) 185*f*.
with two alkali oxides, effect of CaO on, (7) 184*d*.
high-temperature, of single-crystal alumina, (10) 280*d*.
induced by cathode rays in CdSe layers, (5) 134*g*.
ionic, of pure KCl, B (9) 261*c*.
layers, on TiO_2 ceramics, P (2) 48*e*.
mechanism in lead silicate glasses, dependence on water content, (3) 67*h*.
mixed, theory of in Ag_2S group semiconductors, (11) 310*f*.
of monocrystalline cuprous oxide, (3) 86*a*.
of near-stoichiometric α-Nb_2O_5, (2) 56*i*.
in NiO, (3) 76*g*.
of NiO near Curie temperature, (3) 86*b*.
of Nb_2O_5 as function of O pressure, (8) 229*j*.
in oxides of Mn and related compounds, (7) 191*f*.
in polycrystalline lead zirconate-titanate, (2) 47*h*.
of saline solution, effect on thermal conductivity of mixtures, (4) 112*e*.
of semiconductors, measurement of anisotropy by 4-probe method, (7) 192*a*.
of semiconductors, microwave measurement, (10) 286*j*.
super-, design and materials for, (11) 310*c*.
surface, of quartz in presence of adsorbed layers, (1) 30*h*.
of transition metal diborides, (11) 317*f*.
in WO_3, Cu-doped, (1) 26*i*.
of ZrO_2, (3) 88*c*.
Conductivity, thermal, of anisotropic solids at high temperatures, (5) 146*j*.
of $BaTiO_3$ ceramics, (6) 175*e*.
of beryllia ceramics from −200° to 150°C, (5) 132*h*.
of BeO rod, determination by measuring axial temperature distribution, (11) 305*i*.
of ceramic dielectrics, B (8) 233*e*.
of ceramic materials, (4) 121*i*.
of ceramic materials, determination by temperature cycling, (10) 285*j*.
of consolidated porous materials, (2) 44*g*.
guard-dome apparatus, effect of small temperature unbalances, (11) 313*c*.
of insulating materials, computed errors for square guarded hotplate for measurement of, (3) 72*a*.
of magnesite brick, (3) 73*a*.
of materials, apparatus for determining, P (5) 139*a*.
measurements on boiler linings, (3) 73*b*.
of mixtures of components with different conductivities, electrical analogy in study of, (4) 112*e*.
of nuclear ceramics, apparatus for measurement, (3) 71*i*.
of optical maser materials, (1) 30*e*.
as principle of gas analyzer, P (8) 223*j*.
of refractories, measurement by hot-wire method, (3) 72*a*.
of refractory castables, (4) 101*j*.
of refractory materials, (1) 15*c*.
report of French Ceramic Society Committee on, (3) 72*h*.
of solids, from 20° to 200°C, apparatus for determining, (10) 285*j*.
of tank block materials, (1) 10*a*.
of TiC, (7) 189*d*.
vacuum gages, (7) 196*a*.
Conductors, electrical. See also *Semiconductors*.
metallic, solid inorganic insulation for, P (2) 38*c*.
mixed, low frequency characteristics of, (8) 219*a*.
pinhole-free films of, vacuum evaporation deposition, (11) 311*j*.
Conferences, on aerodynamically heated structures, B (2) 61*f*.
on applications of X-ray analysis, 10th annual, B (2) 60*j*.
ceramic, 8th international, 1962, transactions of, B (10) 300*a*.
on clays and clay minerals, 8th national, proceedings of, B (3) 90*j*.
on clays and clay minerals, 9th national, B (5) 150*i*.
on direct observation of imperfections in crystals, proceedings of, B (9) 261*e*.
on glass, 6th international, papers and discussions of, B (11) 320*f*.
on ice and snow—properties, processes, and applications, B (11) 321*h*.
international, on chemical physics of nonmetallic crystals, B (9) 259*i*.
international, on properties of reactor materials and radiation damage effects, B (8) 233*b*.
Conferences (*continued*)
on mechanical properties of engineering ceramics, proceedings, B (3) 91*g*.
on nature of smooth vitreous surfaces (Paris 1959) and on polishing of glass, (Brussels 1960), B (1) 32*e*.
on Nb, Ta, Mo, and W, report of, B (7) 202*c*.
on Pu metallurgy, proceedings of 2d international conference, B (8) 231*o*.
on radiative transfer from solid materials, proceedings, B (3) 92*j*.
on science of ceramics, Oxford, June 1961, proceedings, B (4) 123*f*.
2d all-Union, on crystal growth, 1959, B (9) 262*c*.
of Spanish Ceramic Society, papers of first meeting, 1960, B (2) 61*j*.
on vitreous enameling, 3d international, papers given, B (11) 322*b*.
Congresses. See *Conferences*.
Containers. See *Glass*.
Controls. See also *Instrumentation; Temperature*.
automatic, of acid concentration in pickling system, P (5) 128*a*.
in brick plant, importance of, (2) 50*j*.
of rotary grog calcining kilns, (7) 194*h*.
for slip banding machine, (10) 284*d*.
for thin film deposition, (7) 191*g*.
for cement plant raw mix, X-ray analysis in, I,II, (6) 154*g*.
central, for cement plants, instrument maintenance, (10) 267*d*.
electrical, for glass press, P (5) 130*i*.
for electrical furnace, P (1) 24*g*.
of enamel slip, techniques for, (11) 303*b*.
in enamel slip application, (11) 303*a*.
for feed to shaft furnace, P (1) 25*a*.
low cost computer, for unit processes, (2) 51*b*.
for luminous wall furnace, (5) 140*c*.
of particle sizes, (1) 25*h*.
of plant operations, by card index system, (1) 31*f*.
process, (2) 51*c*.
process, thermal expansion apparatus for, (3) 81*g*.
sound-actuated, for ball mill, P (1) 23*g*.
of speed of tunnel kilns, (1) 24*g*.
statistical maintenance, in chemical plant, (3) 79*j*.
for unit-melter furnace, (9) 253*c*.
zone, of German tunnel kiln, I,II, (1) 24*h*.
Conveyors. See also *Materials handling*.
for coated sheets, through oven, P (8) 221*g*.
for crushed rock, 4200-ft., in cement plant, (7) 181*e*.
for feeding brickmaking units, (1) 12*j*.
fluidized, for filling talc silos, (8) 225*g*.
grate type cooling, for cement clinker, P (9) 237*e*.
hanger, as paint mask, (3) 79*g*.
horizontal, apparatus for moving powders on, P (11) 312*c*.
metal-mesh belt, long-term use in lehr, (6) 156*j*.
moving, apparatus for feeding flat triangular glass sheets onto, P (11) 304*j*.
pneumatic, and fluidized feed pressure, P (1) 22*d*.
pneumatic, with pressure vessel, for powders, P (11) 312*a*.
roll, for furnace, P (1) 24*i*.
rolls, internally cooled, P (2) 54*a*.
rotary, for granular material, P (3) 80*a*.
for slurry, P (9) 250*e*.
spacing, for glass containers, P (5) 130*h*.
speed control, by measuring material level, P (3) 80*b*.
vibratory, in sinter cooler, P (9) 253*g*.
Coolers, shaft, and crusher, P (8) 222*a*.
vibrating, for cement, (9) 237*j*.
with vibratory conveyor, for sinter, P (9) 253*g*.
Cooling, of cement clinker, P (1) 3*a*.
controlled, in mold assembly, P (10) 272*g*.
Ettingshausen, in pyrolytic graphite, (10) 280*j*.
of solid materials after grinding, P (3) 83*c*.
Copper, borate, antifouling pigment, P (11) 303*a*.
compounds, in thermoelectric body, P (10) 283*h*.
and copper(I) oxide, migration in temperature gradients, (5) 142*b*.
cuprous oxide, monocrystalline, electrical conductivity of, (3) 86*a*.
deposition from solution on glass, P (6) 157*i*.
ferrite, specific heat of, (7) 200*e*.
ferrite, transition temperature of, (6) 175*j*.
in nonwatertight drainage tile, to inhibit root growth, (11) 305*f*.
oxide, electric conductivity during dissociation, (7) 191*g*.
electric conductivity in stabilization region in air, (7) 191*g*.
reduction by molecular hydrogen, (4) 120*b*.
systems. See *Systems*.
-Ag, liquid phase sintering of, (4) 118*d*.
Cordierite, from sepiolite by solid-state reaction, B (4) 123*j*.
synthetic, miscibility and structure at low temperature and pressure, (4) 116*a*.
from volcanic xenoliths, (4) 110*f*.
Cores, C, inorganic binders for, (8) 207*c*.
coil and transformer, ferrites for, (8) 220*a*.
elements, for casting hollow parts, P (10) 277*a*.
magnetic, ferrite bodies for, P (4) 105*b*.
and film stores, (4) 104*i*.
method of making, P (5) 136*d*; P (6) 166*g*.
mixed ferrospinel, P (3) 77*h*.
stabilization-wound, P (5) 136*j*.
obtaining unaltered samples, P (3) 84*d*.
sand, destructible reinforced, for metal casting, P (4) 102*e*.
water sensitive, of fast collapsibility, P (1) 17*e*.
Corrensite, and related minerals, (11) 314*j*.
Corrosion, acid-base concept in, (1) 26*f*.
of ancient glasses, study by X-ray diffraction, (11) 301*i*.
atmospheric, protection of cold-rolled steel from, (9) 238*b*.
of checker-brick in open-hearth furnace regenerators, (8) 212*j*.
of corundum crystals, by commercial glasses, (10) 274*d*.
of dunite refractories by molten slag, radioisotope study, (1) 13*j*.
of firebrick, by ash of borax-impregnated timber, mechanism of, (10) 275*i*.
flux line, in sillimanite bricks, (3) 72*d*.
gaseous, of graphite, B (8) 234*a*.
of glass tank crowns and superstructure, effect of V in fuel oil, (8) 213*g*.
inhibiting on ferrous metals, P (1) 5*b*.
inhibition, with molecularly dehydrated phosphate glass, P (3) 69*e*.
mechanism, of enamels, data for, I, (10) 268*g*.
mechanism, of refractories in zebra roof of basic open-hearth furnace, (3) 73*i*.
pigment for inhibiting, P (6) 170*g*.
problems and solutions, (10) 298*d*.
of refractories, by glasses and slags, (8) 228*a*.
of refractories, by molten glass, (1) 5*j*.
resistance, of glass to detergents and additives, (7) 185*h*.
of microconcrete, increase in, (8) 205*b*.
of refractories to glass, stirring test of, (2) 45*g*.
of slip-cast sillimanite, relation to porosity and firing temperature, (1) 15*b*.
of transition metal borides, (5) 141*j*.
silicate cements for inhibition, P (3) 65*a*.
of steel reinforcement in concrete, (8) 206*c*.
sulfate, of cement mortars, effect of finest grain size fraction of aggregate, (7) 180*c*.
testing, of enamels for hot-water heaters, (2) 36*e*.
tests, for evaluating solution of tank block materials by molten glass, (1) 6*a*.
of zircon refractories by molten glasses, I,II, (1) 6*c*.
Corundum. See also *Alumina; Refractories*.
as addition to ramming bodies, (1) 13*f*.
Al_2O_3, quadrupole splitting of ^{27}Al in, I,II, (4) 119*c*.
crushing resistance, relative measurement, (10) 265*f*.
crystals, corrosion by commercial glasses, (10) 274*d*.
polishing ability, (1) 1*i*.
synthesis by Verneuil method, B (2) 61*i*.
high-purity, P (3) 83*i*.
microcrystalline active, B (4) 123*i*.
nonplastic bodies, pipe extrusion from, (10) 279*a*.
rate of lattice contraction in alumina abrasive grains, (9) 235*f*.
reaction with C to produce spinel, (4) 112*a*.
in reaction series of gibbsite heated in air, I,II, (4) 119*g*.
in sand marks on steel, (6) 159*h*.
single crystals, P (2) 55*f*.
single crystals, growth of, P (5) 148*a*.
special forms, P (6) 171*d*.
spin resonance of transition metal ions in, B (9) 260*g*.
synthetic, produced in solar furnace, (5) 140*h*.
thermal-expansion anisotropy of, (1) 30*g*.
Cost, of coated abrasives, reduction of, (3) 63*e*.
in enameling plants, system for comparing, (3) 65*h*.
manufacturing, reduction by work study, (7) 202*b*.
reduction, in materials handling, (11) 314*d*.
Cracking, in brittle materials, method of indicating, (2) 52*b*.
at grain boundaries due to dislocation pileup, (5) 142*h*.
of mortar, effect of admixtures on prevention of, (7) 180*c*.
wall tile, single fired, from cristobalite in intermediate layer, (3) 75*e*.
Cracks, formation, in hardened mortar, (8) 204*e*.
on surface of glass bottles steeped in soakers, (8) 208*i*.
Crazing. See *Glazes*.
Creep, of common and light concretes, (6) 154*b*.
compressive, of polycrystalline BeO, (6) 172*e*.
compressive, of UC, (11) 307*b*.
high-temperature steady-state, in rutile, (10) 293*b*.
of polycrystalline Al_2O_3, (9) 255*c*.
of portland cement mortar in bending, relation to fracture, (9) 237*g*.
tensile, effect on compressive strength of concrete, (8) 204*f*.
Cristobalite. See also *Silica*.
formation, in study of molding sand, (9) 243*f*.
in intermediate layer of wall tile as cause of cracking, (3) 75*e*.
in preventing crazing in glazes, (8) 218*e*.
quartz-, transformation, geometric model for, (6) 173*f*.
quartz transformation to, mechanism, (5) 129*h*.
reactions with alkaline-earth sulfates, (5) 145*i*.
sintering of, (10) 276*h*.
solubility, in curve gas-liquid-cristobalite, (7) 200*i*.
Crucibles. See also *Refractories*.
Ag-Pd, in study of low-melting iron silicates, (7) 200*b*.
Crushing and grinding. See also *Crushing and grinding apparatus; Mills*.
autogenous, of friable material, P (6) 171*c*.
autogenous process, P (6) 170*f*.
ball mill, I, (10) 288*h*.

Crushing and grinding (*continued*)
ball mill, of high-feldspar-iron sand for glass wool, (9) 254*b*.
in ball and pebble mills, (10) 269*e*.
calculations, I,II, (1) 22*f*.
of cement, additive for, P (10) 268*e*.
of ceramic materials in ball mills, P (2) 51*d*.
closed-circuit, calculation of, (1) 22*e*.
closed-circuit, heated screens for improvement in, (10) 273*e*.
comminution, of kaolin, P (10) 289*a*.
comminution theory and practice, I,II, (2) 50*i*.
effect on shale, (3) 82*c*.
equilibrium state of, (1) 22*j*.
of feldspar and quartzite, effect on properties of porcelain bodies, (8) 217*j*.
literature in 1960, (1) 22*f*.
medium, effect on sintering of ceramic oxides, (3) 79*f*.
moisture in, electrical measurement, P (9) 252*e*.
of ores, P (3) 83*c*.
of portland cement, phenolic compound as aid in, P (4) 96*i*.
quantitative, in characterization of granular solids, (7) 195*h*.
of quartz, effect of density, viscosity, and surface area, (3) 79*h*.
relation between particle size distribution and specific surface in, (9) 237*c*.
resistance, of synthetic abrasives, relative measurement of, (10) 265*f*.
of rock, by underground nuclear explosions, (1) 25*e*.
of SiC in BC mortar, (10) 284*d*.
at supercritical speeds, (1) 22*h*.
time, effect on soluble salts in Ti enamel frit, (6) 155*h*.
ultrafine, technology and economy of, (10) 284*d*.
vibration milling, experimental study, (1) 22*g*.
vibratory, P (8) 222*e*.
wet, of solids to extreme fineness, P (5) 138*f*.

Crushing and grinding apparatus. See also *Mills*.
breaker plate structure, P (9) 254*i*.
comminutors, P (2) 55*a*; P (11) 315*f*.
comminutors, loose strikers, impellers for, P (10) 289*f*.
construction, P (3) 84*a*.
crusher jaws, design, P (5) 138*h*.
crushers, automatic, control circuit, P (6) 170*g*.
for fine grinding, P (4) 106*i*.
gyratory, P (3) 83*i*.
hydraulic suspension system for shafts, P (2) 55*i*.
mantle structure for, P (5) 141*c*.
head and mantle assemblies for, P (10) 289*j*.
impact, breaker plate structure and retaining means for, P (8) 221*f*.
centrifugal, P (2) 55*j*.
with centrifugal impeller, P (5) 141*c*.
mills, centrifugal, in vacuum, (1) 22*e*.
for ore, with overload release, P (11) 315*e*.
pulverizers, P (2) 51*g*; P (4) 110*j*; P (9) 250*f*.
for ore, with centrifugal impact action, P (10) 289*i*.
rotor for, P (5) 141*e*.
two stage centrifugal impact, with annular elastomeric concaves, P (3) 85*e*.
for rock, P (2) 56*a*; P (10) 290*b*.
rotary impact, with overload release, P (10) 290*d*.
selection of, (9) 254*c*.
with shaft cooler, P (8) 222*a*.
for solid materials, with cooling means, P (2) 83*e*.
vibrating jaw, P (6) 170*h*.
vibratory, rotary anvil, P (8) 222*d*.

Cryogenics, hose, (9) 250*j*.

Cryolite, artificial, preparation, P (1) 26*b*.
froth flotation of, P (7) 197*h*.
recovery from waste gases and from carbon bottom of Al electrolytic furnace, P (3) 85*b*.
synthetic, method of making, P (6) 171*b*.
synthetic, process improvement, P (3) 83*i*.

Crystal chemistry, of AB_2O_4 compounds, (10) 291*g*.
of ettringite, (8) 226*i*.
of gyrolite and reyerite, (5) 146*f*.
high-temperature, in synthesis of ceramic pigments, I-IV, (9) 238*g*.
of ilmenite and hematite system, I,II, (6) 173*b*.
of pyroxenes and amphiboles, (10) 297*b*.
of rare earth iron garnets, (9) 255*d*.
of urania ceramics, I, II, (10) 279*j*.

Crystallization, of amorphous silica, hydroxyl ion catalysis of, (7) 199*e*.
artificial, of volcanic glass to carnegieite, nepheline, and albite at room pressure, (11) 315*j*.
of boron phosphide, P (6) 176*a*.
of C of hardness equal to diamond, P (6) 176*a*.
catalyzed, of glass, theory and practice, B (8) 232*e*.
crystallized materials, particle size control in, (1) 25*h*.
of glass coatings on metal, study by electron microscopy, (8) 207*j*.
of glasses, effect of molecular structure, (1) 8*c*.
of glasses in system Li_2O-Al_2O_3-SiO_2, (5) 129*a*.
of hydrothermal quartz, kinetics of, (2) 57*d*.
of lead borate glasses, thermal analysis during, (7) 185*c*.
of Mg oxalate in aqueous solution, (8) 212*f*.
nuclei, in acceleration of hardening of cements, P (3) 64*h*.
partition of soluble impurities during, B (9) 262*b*.
of perovskite lead titanate from glasses, (9) 239*h*.
of silicate glasses, (9) 241*h*.
in slag and matrix, relation to gas evolution, (10) 267*a*.
of synthetic mica glass, kinetic studies of, (11) 317*j*.
in system α-alumina–silica, II, (4) 120*i*.

Crystallography, of $Ca_2BaSi_2O_8$, (4) 113*h*.
of compounds in system MgO-Ta_2O_5, (6) 174*d*.
optical, of coesite, (7) 199*a*.
properties, of hexagonal Ba monoferrite, (11) 310*g*.
study of Ca diferrite, (2) 56*c*.
in study of irradiation defects in graphite, B (8) 234*e*.

Crystals. See also specific kinds.
aligned, with specific anisotropy constant, in ferrite isolator, P (11) 311*c*.
alkali aluminate, and potassium ferrite, (6) 169*h*.
application of ohmic contacts, P (5) 137*b*.
bi-, direct observations of grain-boundary sliding in, (5) 142*h*.
boundaries, simulation of, (2) 58*h*.
capture of polarons by F centers, (5) 141*j*.
of clay minerals, dimensions of, (4) 113*a*.
close-packed and body-centered cubic structures, relation between atomic radii in, (11) 318*i*.
cobalt ferrite, preparation from melt, (1) 19*g*.
crystalline material, deposition on seed, control by use of temperature profile curve, P (11) 320*a*.
with defects, scattering of X rays by, (2) 59*g*.
dislocation etch pits, study method, (4) 116*g*.
dislocation patterns, in graphite, (1) 27*i*.
dislocations, in alumina whiskers, (2) 59*e*.
damping, in MgO crystals at low frequencies, (5) 134*j*.
decorated, in MgO, (7) 198*h*.
effect on diffusion kinetics in alkali halides, (10) 294*d*.
effect on oxidation and reduction of $SrTiO_3$, (3) 86*j*.
effect on strength of polycrystalline ceramics, (8) 227*j*.
of MgO, (10) 291*j*.
in MgO, damage from, (9) 255*g*.
in MgO, etchant for, (11) 318*c*.
in sapphire, direct observation, (10) 291*i*.
sources, in MgO, (8) 227*h*.
theory and observations, B (9) 259*e*.
electric field in, (5) 143*h*.
ferric sulfate, roasting of in preparing ferric oxide particles, (6) 175*i*.
ferroelectric, B (4) 123*e*.
ferroelectric and antiferroelectric, growth and study, (3) 76*j*.
fluorite, X-rayed, infrared luminescence of F centers in, (5) 135*d*.
fluorophosphate, vibration spectra of, (5) 147*b*.
formation. See *Crystallization*.
furnace for growing, P (2) 53*j*.
of Gd salts, photoluminescence, (5) 145*c*.
-glass, two-phase, physical properties of, B (4) 124*a*.
growing, method and apparatus for, P (1) 16*h*.
process, P (2) 60*a*.
and treating, P (8) 225*g*.
growth, Pb pyrophosphate as flux for, (5) 147*h*.
in mica materials, control of, P (2) 55*e*.
in preparation of laser materials, (10) 281*f*.
in system FeO-MgO-Fe_2O_3, (8) 226*e*.
Verneuil, in arc-image furnace, (10) 284*g*.
Vol. 3, conference report, B (9) 262*c*.
habit, of gypsum, modification with ferric ion, (9) 236*j*.
habit, of UO_2, (1) 27*d*.
hematite, screw dislocations in, movement of, (8) 229*a*.
homologous sublattices and intracrystalline equilibria, (11) 319*f*.
hopper, mechanism for formation in flux systems, (5) 135*c*.
imperfections, direct observation, conference proceedings, B (9) 261*e*.
imperfections, in Y Fe garnet, (10) 294*c*.
ion exchange in, (4) 120*a*.
ionic, effect of grain boundaries on mechanical properties, (8) 227*d*.
ionic, sliding and wear in, (10) 297*f*.
large, of $CaSO_4 \cdot 2H_2O$ from $CaCl_2$ and Na_2SO_4, (5) 126*c*.
in laser development, (10) 280*c*.
lattice, constants, of BeO, determination by precise X-ray methods, (1) 28*b*.
defects, observation in graphite by moire patterns, (6) 174*c*.
parameters, determination from X-ray diagrams of polycrystalline substances, (5) 144*g*.
theory of rutile type, (10) 296*h*.
MgO, cracking at grain boundaries in, (5) 142*h*.
of metals, preferentially oriented single, growth of, P (2) 60*a*.
method of doping, P (6) 166*h*.
mica, growth of, (1) 19*j*.
micro-, ZnS:Cu,Pb, electroluminescence of, (6) 163*g*.
for microwave and optical masers, (2) 47*h*.
mixed, in Li_2SiO_3-Li_2GeO_3 system, vibrational spectra of, (6) 176*c*.
mixed organic, for scintillation counters, B (9) 263*a*.
mono-. See *Crystals, single*.
nonmetallic, chemical physics of, papers from conference, B (9) 259*i*.
nonmetallic, dislocation etch pits in, B (8) 232*b*.
for optical masers, (9) 255*e*.
orientation, effect on plastic deformation of MgO, (9) 256*a*.
oxide, growing of, (3) 86*j*.
phase change in, effect on luminescence, (2) 48*e*.
piezoelectric, holder for, P (1) 21*d*.
piezoelectric, as sensor for measuring film thickness, (7) 191*g*.
porous, occlusion of iodine in, I,II, (10) 295*h*.
quartz. See *Quartz*.
refractory, deformation of, (8) 227*c*.

Crystals (*continued*)
semiconductor, apparatus for pulling from molten compounds, P (5) 135*d*.
semiconductor dendritic, P (9) 249*f*.
SiC, method of growing, P (1) 16*a*.
single, apparatus for orientation of nucleus during growth, P (4) 121*g*.
apparatus for pulling in long flat strips by crucible method, P (10) 284*j*.
ceramic, fundamental mechanical properties, (8) 230*b*.
as engineering materials, (9) 258*d*.
growing from molten mass with linear isotherm, P (2) 60*b*.
growth from MgF_2, (2) 58*j*.
hydrothermal synthesis, B (3) 92*b*.
of material with high melting points, new method of growing, (10) 288*e*.
MeF_2:Eu,Sm, phototransfer of electron in, (5) 145*d*.
method of making, P (6) 167*e*; P (6) 171*e*.
properties and applications, (10) 298*e*.
refractory oxide, growth of, (5) 144*a*.
transmission electron microscopy of, (10) 286*g*.
size, and shape, control of, B (4) 123*c*.
size, and size distribution, study from measurements of X-ray line profiles, B (2) 60*j*.
sphere, orienter for, (10) 285*j*.
with spinel structure, in piezomagnetic material, P (11) 311*c*.
structure, of BI_3, (1) 27*e*.
of cement clinker constituents, B (5) 148*f*.
of Cs triborate, (10) 291*h*.
of clay minerals, B (7) 202*f*.
comparison of effect of grinding and shattering, (3) 86*i*.
determination, refinement in compounds of rutile type, I-III, (10) 296*h*.
lattice constants of synthetic lawsonite, (4) 115*g*.
of $LiScO_2$, (4) 113*e*.
of monoclinic WO_3 at room temperature, (6) 172*g*.
in $NiMnO_3$ and $CoMnO_3$, (4) 113*d*.
of NbO_2, (5) 142*i*.
of phlogopite, (8) 226*f*.
relation to surface reactivity, (11) 316*d*.
of SiC of 174 layers, (6) 172*i*.
of $Na_4Ge_9O_{20}$, (10) 291*c*.
and stability of refractory phases, B (2) 60*j*.
of $SrZnO_2$, (4) 113*f*.
of three-dimensional lattices, B (5) 151*d*.
transformation mechanisms, I, (11) 318*b*; II, III, (10) 295*a*.
of V_2O_3, (4) 113*g*.
of Y Fe garnet, (10) 291*j*.
of yttrium and other rare-earth borates, (8) 226*h*.
twinned, of precipitated gypsum, (9) 257*d*.
twinning, of cubic (β) SiC, (7) 201*d*.
polysynthetic, of mica, (4) 118*b*.
polysynthetic, in plagioclase, (4) 118*c*.
slip, and cleavage, in U_3O_8, (1) 31*a*.
twins, recognition in sections normal to composition plane, (4) 120*a*.
ultimate strength of, (9) 257*e*.
uniaxial, analysis of refraction correction, (9) 257*a*.
unit, P (5) 135*f*.
whiskers, growth by chemical reactions, (2) 57*i*.
growth on metals at high temperature, (6) 173*f*.
for reinforcement of metals, (4) 97*e*.
of SiC, (8) 229*g*.

Cummingtonite, distribution of Mg^{2+} and Fe^{2+} in, (11) 319*f*.
structure of, (7) 199*j*.

Curing, under pressure, effect on compressive strength of concrete, (8) 204*b*.

Curium, separation from rare earth elements, P (6) 176*a*.

Curtain wall. See *Walls*.

Cuspidine, in phosphorus furnace slag, (4) 96*g*.

Cutting tools. See *Tools*.

Cyclones. See *Separators*.

De-airing, vacuum, of plaster for molds, (3) 64*g*.

Decals. See *Decoration*.

Decolorization, of Mn glass, (6) 156*d*.

Decomposition, chemical, of PbI crystals by irradiation in electron beam, (10) 290*g*.
of clays, effect on Al, (5) 142*f*.
of Mg and Ca sulfates, (5) 145*i*.
of microcline, albite, and nepheline in hot water, (5) 142*a*.
radiation-induced, of inorganic nitrates, (10) 296*a*.
reductive, of $CaSO_4$, P (8) 206*e*.
of solid solutions of MgO-ZrO_2 and of CaO-ZrO_2, (1) 27*g*.
thermal, of NH_4 montmorillonites, I, (11) 320*a*.
of ammonium paratungstate, (4) 120*h*.
of glass, effect on electrical breakdown in vacuum, (10) 280*h*.
of light rare earth oxalates, (9) 257*a*.
of Mg and Ca carbonate, kinetics of, (4) 115*f*.
of $Mg(OH)_2$, (11) 319*i*.
of organic Ti compounds, in producing capacitor of TiO_2 film, (8) 218*f*.
of portlandite and xonotlite, (5) 147*a*.
of Ti ores, P (5) 141*h*.

Decoration. See also *Art and artware; Color; Engobes; Glazes*.
antique or modified gold effects, P (3) 64*a*.
back stamping, of ware, machines for, P (10) 279*c*.
ceramic, brushes for, (6) 153*i*.

Decoration (*continued*)
of ceramic body with liquid bright gold, P (10) 279*b*.
of ceramic flatware, apparatus for, P (2) 47*c*.
of ceramics, color technology in, XV, (4) 109*b*.
color in, importance, (3) 63*j*.
decal, for household china, (9) 245*i*.
esthetic, glass for, (10) 265*j*.
glass for, (10) 265*j*.
of glass, B (2) 61*c*.
and ceramic objects, by cold transfer, P (10) 272*d*.
with metal compounds, P (10) 272*f*.
method and apparatus, P (8) 210*b*.
ware, silicone-coated frit for, P (11) 305*a*.
gold films in, history and current practice, (2) 54*d*.
of hollow glasses, machine grinding for, I,II, (8) 208*e*.
of huge pots, (4) 95*j*.
machine for, P (10) 271*e*.
of pottery, ceramic colors in, B (6) 176*h*.
underglaze, of porcelain, (4) 103*j*.
De-enameling. See *Enameling*.
Defects. See *Enameling; Enamels; Glass*.
Deflocculants. See *Electrolytes*.
Deflocculation. See *Dispersion*.
Deformation, of LiF, polycrystalline, (8) 226*j*.
long-time, of concrete, rheological laws of, (7) 182*a*.
mechanisms, in ductile ceramics, (8) 226*i*.
plastic, effect on γ-ray coloration of NaCl crystals, (5) 143*g*.
plastic, of MgO, effect of crystal orientation, (9) 256*a*.
of refractory crystals, (8) 227*c*.
of structural clay body at high temperatures, (2) 43*h*.
Dehumidifiers. See *Dryers*.
Dehydration, of boehmite, study with X-ray heating camera, (5) 142*c*.
of Ca sulfate dihydrate, effect of crystal state, (1) 2*j*.
of Ca sulfate dihydrate, effect of inorganic salts, (2) 34*e*.
of calcium sulfate hemihydrate, transition after, (9) 237*h*.
of goethite and diaspore, disordered structural states in, (8) 227*c*.
of hemimorphite, (8) 227*e*.
low-temperature, of silica hydrates, (3) 66*d*.
Dehydroxylation. See *Decomposition, thermal*.
Densification, of glass, Ge oxide, SiO_2, or boric acid, P (10) 271*f*.
of SiO_2, GeO_2, and B_2O_3 glasses in rigid state, (11) 303*i*.
Densitometers, recorder for, P (11) 320*b*.
Density, of BeO, determination by precise X-ray methods, (1) 28*b*.
of borosilicate glasses, change with thermal treatment, (5) 128*h*.
bulk, determination in granular materials, (11) 308*c*.
distribution in dry-pressed compacts of ceramic powders, study by radiography of lead grids, (1) 22*h*.
effect of liquid solubility and wettability on, (4) 118*e*.
of electrical porcelain, relation to properties and kiln behavior, (11) 309*e*.
end-point, of hot-pressed Al_2O_3, (4) 113*f*.
green bulk, of alumina, correlation with strength, (2) 54*b*.
liquid, of Y and rare-earth fluorides, (1) 28*d*.
of MgO, sintered slip-cast, (7) 187*e*.
measurement of solids, pressure-differential apparatus for, P (8) 224*a*.
of powders or liquids, device for measurement, P (4) 108*e*.
of small solid samples, modified flotation method of determination, (7) 195*e*.
of solid material, apparatus and method for measuring, P (3) 81*a*.
of striae in optical glasses, (5) 130*b*.
vapor, accurate apparatus for, (9) 252*a*.
of zones, in used silica brick, (8) 212*h*.
Dental materials, crowns, device and method for making, P (2) 47*d*.
fused porcelain-to-metal teeth, P (1) 18*g*.
impression compositions, P (7) 182*h*.
porcelain, bond with gold alloys, (7) 183*d*.
porcelain, containing refractory glass fibers, P (4) 104*e*.
porcelain covered metal-reinforced teeth, P (1) 18*j*.
stone, composition, P (7) 190*h*.
Desiccators, miniature, production of units of, P (2) 50*e*.
Design. See also *Art and artware; Decoration*.
from designer's view, (1) 2*c*.
for fluidization, III, (2) 50*i*.
of glass tank furnace parts improvement, (1) 7*i*.
management, as executive function, (9) 236*g*.
for materials with superconductivity, (11) 310*c*.
and production man, (1) 2*e*.
with rate-sensitive ceramics, (10) 298*b*.
-sales-production, relation of, (2) 33*j*.
Designers, pattern for, (9) 236*g*.
Desilication, of caustic leach liquors containing Al_2O_3, (6) 154*d*.
Destabilization, of zirconia by cyclic heating, (11) 305*i*.
Detectors. See also *Tubes, electron*.
photoelectric, temperature discrimination with, (5) 138*i*.
pn junction particle, SiO_2 passivation of, (10) 282*e*.
Detergents, glass resistance to, (7) 185*h*.
Deuterons, bombardment, effect on CdS single crystals, (6) 173*a*.
Devitrification, of optical glasses, (11) 303*g*.
Dewatering. See *Water, removal*.
Deweylite, data on, (4) 110*a*.
Dew point, of multiple sheet glazing units, determination, P (3) 69*h*.
Dialysis, electro-, high-voltage, in purification of TiO_2 and metatitanous acid, (7) 197*j*.
electro-, as unit operation, (10) 284*c*.
Diamonds, abrasive cutting devices, P (11) 301*g*.
in abrasive wheels. See *Grinding and polishing apparatus*.
in atomic energy research, I, (9) 235*g*.
cutoff wheels, selection of, (9) 235*j*.
for cutting crystal glass, (6) 156*c*.
cutting and polishing device, P (10) 265*f*.
etched, method of producing, P (7) 177*g*.
fines, or extraction, apparatus for classification, P (2) 51*g*.
formation, I, (5) 143*f*.
formation, mechanism of, (1) 28*e*.
-graphite equilibrium line from growth and graphitization of diamond, (4) 113*i*.
grinding, of glass, (6) 156*b*.
grit, performance in grinding, (6) 153*e*.
growth history as revealed in etched cross sections, (10) 293*j*.
as indicator of irradiation, B (8) 233*d*.
optical and electrical effects of radiation damage in, (8) 229*c*.
substitute, for truing grinding wheels, P (2) 33*f*.
synthesis, mechanism of formation, (6) 169*h*.
synthetic, growth characteristics of, (3) 88*j*.
synthetic, interferometric studies on, (3) 87*g*.
tool, production of, P (11) 301*f*.
for tools, relation of structure to abrasive hardness, (9) 235*j*.
wheels, Man-Made, in grinding carbides, (11) 301*e*.
Diaspore, in clays, effect on reactions, (1) 30*f*.
dehydration, disordered structure in, (8) 227*c*.
Diatomaceous earth. See *Kieselguhr*.
Diatomite. See *Kieselguhr*.
Dicalcium silicate. See *Calcium*.
Dictionaries, for glass industry, B (8) 231*h*.
Dielectrics. See also *Ferrites; Ferroelectricity and ferroelectric materials; Ferromagnetism and ferromagnetic materials; Glass: Porcelain, electrical; Steatite; Titanates; Whiteware*.
anisotropic, for couplings between two capacitors, (9) 246*g*.
anomaly, in quartz for high transient stress and field, (5) 142*g*.
apparatus for measuring moisture content, P (6) 168*h*.
of $BaTiO_3$-UO_2 ceramics, (10) 279*j*.
barrier-layer, from oxide ceramics, (10) 279*i*.
behavior, in systems $PbHfO_3$-$BaHfO_3$ and $PbHfO_3$-$SrHfO_3$, (9) 246*h*.
breakdown, in microwave windows, research on, (9) 247*b*.
capacitor, materials for, (10) 279*i*.
ceramic, composition, P (4) 105*b,c*.
for high-tension capacitors, P (6) 165*i*.
intergranular barrier layer, P (5) 136*g*.
method of making, P (6) 165*h*.
parts, manufacture of, (6) 165*e*.
temperature stabilized, P (9) 248*i*.
thermal conductivity of, B (8) 233*e*.
use in capacitors, P (4) 105*b*.
constant, of ADP as function of temperature, B (9) 263*h*.
automatic bridge for measuring, (3) 76*j*.
high, ceramic bodies with, P (6) 165*j*.
high, making material with, P (6) 166*c*.
of $PbTiO_3$, effect of additives, (2) 47*i*.
and loss, control in alumina ceramics, correction, (6) 163*j*.
and loss, of synthetic mica, measurement by powder method, (8) 223*d*.
of semiconductors, microwave measurement, (10) 286*j*.
fluoaluminates as, P (10) 282*f*.
high, composition, P (10) 282*i*.
high permittivity relaxation, (9) 247*i*.
impregnated paper as, in condensers, P (9) 249*c*.
losses, of quartz crystals, relation to imperfections, (5) 143*h*.
loss factors, predicting and controlling, (6) 165*b*.
materials, developments in, report and bibliography, (3) 76*b*.
manufacturing processes, P (3) 77*g,h*.
polycrystalline, mechanisms of heat transfer through, (1) 15*c*.
as windows for microwave tubes, (10) 282*b*.
measurements, sample holder for, (10) 282*b*.
progress in, Vol. 4, B (9) 263*f*.
properties, of anodic aluminum oxide films, (9) 246*i*.
of $BaTiO_3$ ceramics, (11) 310*b*.
of $BaTiO_3$-UO_2 ceramics, effect of varying firing temperature, (10) 280*a*.
of basic sodalite and Ag nitrate-zeolite complex, (8) 218*i*.
of BeO single crystals, (10) 281*g*.
of Bi borate glasses, (3) 66*f*.
of $Bi_2Ti_4O_{11}$, (1) 29*d*.
of Ca boroaluminate glasses, relation to structure, (1) 8*b*.
of ceramic products, B (2) 61*j*.
of glasses in systems Bi_2O_3-CdO-SiO_2, Bi_2O_3-CdO-B_2O_3, and Bi_2O_3-CdO-GeO_2, relation to glass structure, (1) 6*i*.
of glasses in system Nb_2O_5-Na_2O-SiO_2, (4) 98*a*.
Dielectrics, properties (*continued*)
of glasses in system TiO_2-Na_2O-SiO_2, (1) 6*b*.
of ion-exchanged analcites, (8) 219*a*.
of materials with tetragonal W bronze crystal structure, (10) 282*h*.
of single-crystal nonstoichiometric rutile, (5) 134*i*.
of titania ceramics at microwave frequencies, (10) 280*e*.
in transformation series $Fe_3O_4 \rightarrow$ γ-$Fe_2O_3 \rightarrow$ α-Fe_2O_3, (9) 247*g*.
SiN, in electric capacitor, P (10) 282*e*.
Ag halogenides with divalent anion impurities, defect dipole in, (3) 88*e*.
study, on hydration of cement paste, (7) 179*g*.
thin film, Si_3N_4 as, (10) 276*g*.
wollastonite body for, (6) 163*d*.
Dies. See also *Extrusion*.
alumina, hot-pressing ceramics in, (10) 284*h*.
Differential thermal analysis. See *Thermal analysis*.
Diffraction. See *Electron diffraction; Neutrons; X rays*.
Diffractometers. See also *Electron diffraction; X rays*.
Diffractometers, mount, for small samples, (4) 107*f*.
X-ray, heating stage for, (6) 168*d*.
X-ray, high temperature attachment for study of solid state reaction, (2) 52*h*.
X-ray diffraction, Pt expansion values for thermal calibration of, (3) 81*a*.
Diffusion, of activation, in oxide-coated cathodes, (10) 280*g*.
exciton, in Cd and Zn sulfides, (4) 115*a*.
impurity atom, into finite slices of semiconductor material, (7) 191*c*.
inter-, of gases in low permeability graphite at uniform pressure, (1) 28*a*.
in ionic crystals, correlation effects, B (9) 261*e*.
metal, theory and uses, (4) 98*b*.
of metals, relation to glass mold equipment, (4) 98*b*.
of neon isotopes in fused quartz, (4) 113*j*.
in noncrystalline silicates, B (9) 263*i*.
O-ion coefficients, in Al_2O_3, (5) 142*i*.
of oxygen in vitreous silica, (3) 66*g*.
pattern, in system MgO-Al_2O_3, effect of time and intermittent cooling on, (5) 145*e*.
processes, governing exchange of charged particles of different mobility, B (11) 320*j*.
of protons in SiO_2-Al_2O_3 glass in electrical field, (2) 38*i*.
self-, of Na ions in analcite and anhydrous analcite, (11) 319*d*.
in semiconductor material, P (4) 105*d*.
in silica glass, after reaction with tritiated water vapor, (10) 270*c*.
studies, in dispersion-type fuels, (11) 307*j*.
studies, in glass, I-IV, (9) 230*h*.
vapor-solid, of semiconductive material, P (3) 79*c*.
Diffusivity, thermal, at high temperatures, pulse method of measuring, (10) 286*b*.
Dilatometers. See also *Expansion*.
inert-atmosphere, for use to 2000°C, (4) 107*j*.
sapphire rod, for measuring thermal expansion of refractory brick, (3) 73*d*.
use in ceramic problems, (10) 286*b*.
Dilution, method, for fluorescent X-ray spectrometry of powder sample, (2) 56*h*.
Dinnerware. See also *Art and artware; Pottery; Whiteware*.
automatic spraying of glazes on, (5) 137*i*.
cups, bone-china, thermal shock resistance of, (11) 309*d*.
method for shaping handles, P (4) 104*b*.
and saucer, nondrip, nonslip, nontip, P (4) 95*j*.
directory, B (8) 231*h*.
glass, new plant, (2) 41*j*.
glazes for, structure and calculation, (5) 134*b*.
handles, apparatus for affixing, P (1) 18*e*.
oval dishes, machine forming techniques, (3) 79*h*.
plates, manufacture by pressing, (10) 278*h*.
mechanizing production, (4) 104*c*.
shaping by mechanical pressing, (3) 79*e*.
for schools and hospitals, (4) 103*g*.
semivitreous, wollastonite body for, (6) 163*d*.
Diodes. See *Tubes, electron; Rectifiers*.
Diopside, synthesis from molten PbO, (9) 257*h*.
Directories, china, glass, and tablewares red book issue, B (8) 231*h*.
Dislocations, in crystals. See *Crystals*.
Dispersions, agents, in cement paste, effect on properties, (7) 181*b*.
aqueous, of clay coated with polymers, P (4) 111*a*.
aqueous, of high molecular weight fibrils of amorphous silicates, P (4) 104*e*.
colloidal, stable, method of preparing, P (7) 190*a*.
element, of Cr-coated UO_2 particles in Zircaloy matrix, P (8) 215*j*.
elements, theory, fabrication, and application, (10) 275*f*.
hardening, of uranium metal, P (5) 133*e*.
mechanical resonance, in quartz at audio frequencies, (3) 87*f*.
phenomena, in system γ-alumina–water, (2) 56*e*.
of plastic clays, nature of, (4) 109*j*.
of synthetic sapphire, (5) 145*b*.
Dolomite. See also *Refractories*.
action of water on, (6) 169*f*.
composition and properties, (10) 274*g*.
conversion process, P (1) 17*b*.
dead-burned, manufacture and use in steel refining furnaces, (1) 13*f*.

Dolomite (*continued*)
dry vs. wet grinding, (10) 288*h*.
effect on setting time of gypsum plaster, (10) 267*g*.
furnace lining, with carbonaceous bond, P (2) 45*d*.
new knowledge on, B (10) 300*g*.
plaster. See *Plaster*.
primary, and limestone, cyclic sedimentation, (3) 82*g*.
in production of basic pig iron, (10) 268*b*.
quantitative gasometric determination, by Chittick apparatus, (3) 81*b*.
sintered, tar binder for improvement of storage stability of unburned shapes, P (4) 102*c*.
synthetic, produced in solar furnace, (5) 140*h*.
thermoluminescence in, (2) 48*c*.
Domains. See *Ferroelectricity and ferroelectric materials; Ferromagnetism and ferromagnetic materials*.
Dosimeters, Co glass, extended application, (9) 240*f*.
γ-radiation, P (5) 136*c*.
Drilling, apparatus, with telescoping divergent discharge nozzle, P (5) 138*f*.
of holes in rock bed, P (10) 289*d*.
inclined, (9) 254*d*.
of minute holes in small ceramic wafers, P (5) 138*b*.
Dryers. See also *Drying*.
brick, Belgium installation, (1) 12*j*.
continuous and intermittent, oil-firing, (2) 53*f*.
for enameling, (8) 207*c*.
for moisture removal from analytical samples, P (8) 223*g*.
oil burners for, (10) 287*j*.
rotary, for bauxite, (11) 314*c*.
construction, P (10) 285*d*.
grizzly bar screen for discharge end, P (5) 141*b*.
rotary drum, sand or fines filter for, P (5) 140*g*.
spray, P (1) 23*g*.
supersonic vibrating, P (8) 222*b*.
tunnel, automating heating schedule of, (6) 167*a*.
Drying. See also *Dryers*.
of brick, by high velocity hot air, (6) 167*c*.
of clay, conditions of water movement in, B (10) 300*j*.
of clay products, B (2) 61*j*.
of finely divided materials, P (2) 51*e*; P (5) 141*c*.
negative and dielectric, of ceramic body, (4) 108*j*.
of pellets, process and apparatus, P (11) 312*a*.
of plaster molds, P (1) 23*c*.
radiation gas, of structural ceramics, (7) 196*e*.
rate, of ceramics, relation to relative elongation during tension, (1) 23*b*.
spray, in technical ceramics plant, (4) 104*i*.
trends in, (10) 287*f*.
Dry pressing. See *Pressing*.
Ductile ceramics, deformational mechanisms in, (8) 226*i*.
feasibility of extrusion, (8) 228*g*.
review of work on, (1) 28*f*.
Ductility, of glasses, relation to electroconductivity, (7) 185*f*.
Dunite, electrically fused, relation between structure and properties, VI, (1) 13*j*.
Dusts. See also *Air, pollution; Particles; Powders*.
apparatus for handling and wetting, P (8) 221*d*.
automatic closed-loop leaching system, (2) 34*c*.
cement kiln, effect on soil and plants, (2) 34*d*.
centrifugal separator for, P (10) 285*o*.
chemicals for quelling, (2) 34*i*.
collection equipment, developments in, (3) 79*j*.
collection system, glass fiber filter for, (2) 39*f*.
collector, P (1) 23*g*; P (2) 51*h*; P (3) 83*g*.
with continuous filter, P (7) 195*a*.
in silicate and metallurgical industries, construction, operation, and characteristics, I-III, (5) 137*j*.
concentration, methods used and dangers of, (5) 148*d*.
control, in cement industry, (1) 2*i*.
control, in cement plant, (3) 64*d*.
control, high temperature, with fiber glass fabric filters, (11) 303*i*.
Cottrell, of rotary cement kilns, tests in building materials, (8) 203*j*.
determination of minerals in with phase contrast microscope, (4) 111*i*.
-feed mechanism suitable for fibrous dust, (3) 90*d*.
fine, from cement kilns, use of, (11) 302*f*.
fractionating, for particle size analysis, (2) 52*c*.
glass, biologic effects, (2) 60*c*.
measurements, in ceramic industry, (3) 90*b*.
moistening, method and apparatus, P (9) 250*d*.
particles, apparatus for measuring, P (9) 252*e*.
prevention device for rotary hammer impactor, P (7) 195*a*.
refractory, plant control of, (11) 312*b*.
removal, from ceramic factories, (3) 90*d*.
removal, by vacuum equipment, (5) 138*d*.
sampler, slow running personal, (6) 168*e*.
separator, P (5) 138*h*; P (7) 195*b*.
silica-containing, preparation for use in biological research, (2) 60*g*.
sticking to walls during blowing, (4) 122*f*.
technology, bibliography, (3) 90*c*.
ultrafine, removal by suspension filters, (4) 108*b*.
Dyes, adsorption by clay minerals, (6) 169*h*.

Earthenware, Bavarian, from 17th century to 1853, (7) 177*j*.
Earthenware (*continued*)
biscuit oven for reducing firing time, (11) 314*c*.
body, moisture expansion and internal surface area, (10) 278*i*.
calcareous, bodies, combination of lime in, (8) 217*g*.
centrifugal pump, (5) 138*b*.
electric kiln firing of, (11) 314*e*.
industry, decorating and forming machines for, (1) 18*a*.
moisture expansion of, B (10) 300*b*.
wall tile, bodies and properties, (6) 163*d*.
Education, ceramic, U. S. vs. British, (9) 258*g*.
ceramic engineering, objective criteria in, (10) 298*c*.
licensing of ceramic technicians, (6) 176*e*.
Efficiency, absolute, of infrared fluorescent Zn and Cd sulfide activated with V,Ag and V,Cu, (5) 134*d*.
Efflorescence, in brick, causes of, (2) 43*h*.
change in composition, (7) 178*g*.
sulfur compounds as cause, (1) 25*e*.
Elasticity. See also *Anelasticity*.
axial elastic force in viscoelastic flow through tube, (10) 291*i*.
coefficients, of single-crystal $BaTiO_3$, (4) 113*c*.
of composite bodies, prediction of, (8) 228*j*.
constants, of calcite, (1) 27*e*.
of glass, determination by resistance strain gages, (9) 239*f*.
of rutile, (3) 86*j*.
single-crystal, of BeO from polycrystalline measurements, (9) 257*e*.
single-crystal, relation to polycrystalline isotropic elastic moduli of MgO, (10) 296*j*.
elastic recovery, of indentation marks on transparent substances, (6) 167*i*.
elastic stresses, from indentation of semi-infinite elastic solid, (2) 39*e*.
high, need for in concrete, (10) 266*h*.
of MgO, relation of single-crystal constants to polycrystalline isotropic elastic moduli, (10) 296*j*.
modulus, determination by resonance, (7) 195*i*.
measurement at high temperatures, (11) 313*j*.
of polycrystalline magnesia alumina spinel, (4) 101*b*.
of refractory materials, at high temperature under vacuum, (9) 243*e*.
photoelastic effects, in quartz and feldspars, (4) 112*g*.
properties, of glass, during torsion, (2) 39*d*.
properties, of WC, anisotropy of, (2) 56*d*.
Young's modulus, of glass fibers, (9) 239*g*.
measurements, above 2000°C, (10) 286*g*.
of semicoke, (7) 196*i*.
of soda-lime-silica glass, effect of cations, (2) 38*j*.
of ZrC in dispersed phase of graphite, (4) 101*b*.
Elastic materials, silicates, thermally stable, flexible, (8) 229*b*.
Elastomers. See *Elastic materials*.
Electric ceramics. See also *Electronics*.
high purity, manufacturing process, (8) 218*f,h*.
science and technology in, (9) 258*c*.
Electric components, forming of, P (8) 220*a*.
Electric conductivity. See *Conductivity, electric*.
Electric discharge devices, in producing semiconductors, P (3) 78*j*.
use in preparative inorganic chemistry, (9) 252*i*.
Electric properties, of alumina, B (2) 61*i*.
of $BaTiO_3$ ceramics, (11) 310*c*.
of $BaTiO_3$ doped with Sb_2O_3, (6) 165*i*.
of cabal glasses, correlation with structure, (3) 67*f*.
of carbon and graphite, (6) 159*f*.
of Cr nitrides, (2) 57*a*.
of dilute sodium tungsten bronzes, (9) 256*g*.
of earth's crust, (10) 282*g*.
of electronic ceramic products, (11) 310*f*.
of γ-ray irradiated shielding window glass, (2) 39*g*.
of glass, control of, (9) 240*a*.
of lead titanate zirconate ceramics, factors affecting, (3) 76*c*.
of $PbZrO_3$-$PbTiO_3$ ceramics, factors affecting, (7) 191*h*.
of LiF, effect of radiations, (10) 294*h*.
of Li silicate glasses, (7) 185*j*.
of NdBa, (11) 319*j*.
of refractory oxides, (8) 219*h*.
of SiC crystals, process for adjusting, P (5) 137*a*.
of tin oxide films, (6) 174*e*.
Electric resistance. See *Conductivity, electric; Resistance, electric*.
Electric resistors. See *Resistors, electric*.
Electroceramics. See *Electric ceramics*.
Electrochemistry. See also *Corrosion; Electrolysis*.
in determination of components in gas mixtures, P (1) 24*b*.
in determination of fluorides, P (2) 60*a*.
Electrochromatography. See *Chromatography*.
Electrodes. See also *Heating elements*.
C, expansion joint for, P (8) 225*a*.
and graphite, interconnecting, for electric furnaces, P (8) 224*j*.
screw nipple connection for, P (1) 17*c*.
composite, P (5) 135*e*.
curvature, effect on electrical breakdown in vacuum, (10) 280*h*.
discharge, for electrostatic precipitator, P (2) 51*a*.
double-baked self-channeling, P (7) 197*a*.
for electrical discharge device, P (7) 193*g*.
of electrostatic precipitator, magnetic cleaning means, P (4) 106*i*.
furnace, sealer-cooler structure for, P (2) 46*h*.
glass, P (4) 99*h*.
Electrodes, glass (*continued*)
for measurement of divalent cations, (9) 240*j*.
Na-ion responsive, properties of, (5) 129*j*.
Na-sensitive, response of Ag, Li, and Tl ions to, (5) 129*e*.
gold-metal, bonding to Si semiconductor crystal by thermocompression, P (9) 249*h*.
for high-pressure electric discharge lamps, P (1) 20*f*.
H, in determination of formation constants of $GeO_3(OH)_3^{2-}$, (10) 291*e*.
joint, carbon, P (1) 16*a*.
material, making for semiconducting devices, P (3) 78*j*.
for melting refractory metals, P (2) 45*f*.
nonconsumable, of hexaboride of rare element, P (3) 73*j*.
paste, method of making, P (3) 74*a*.
properties, of cation sensitive glasses, (3) 67*a*.
rapping device for collecting in precipitator, P (8) 222*a*.
self-baking, use of, P (5) 133*h*.
semiconductor systems, P (5) 136*h*.
storage target, P (9) 249*i*.
Electrodialysis. See *Dialysis*.
Electrodynamics, introduction to, B (10) 299*j*.
Electroluminescence. See *Luminescence*.
Electroluminescent materials. See *Luminescent materials*.
Electrolysis, in determining small amounts of moisture in solids, (6) 168*b*.
in etching semiconductor devices, P (8) 220*g*.
in production of chlorite-like substances from montmorillonite, (11) 317*g*.
in production of mixed metal oxides, P (5) 141*b*.
in removal of $Mg(OH)_2$ from seawater by precipitation, P (7) 197*j*.
of silicates, SiO_2 by, P (2) 56*a*.
of synthetic quartz, effect on resonator performance, (9) 247*c*.
in treatment of metalloceramic drawplates, (4) 97*f*.
Electrolytes, determination of O in solution in, P (8) 224*c*.
enamel-glass, in cells for short-term power, (10) 268*h*.
importance in particle size analysis, (10) 286*e*.
poly-, effect on heat evolution of binders and castables, (10) 274*j*.
Electromagnets. See *Magnets*.
Electromechanical properties, of lead zirconate-lead titanate ceramic compositions, (11) 309*i*.
Electron diffraction, in identification of sand marks in steel, (7) 195*e*.
random, and sparkling spots, (7) 192*e*.
single crystal, in clay mineral identification, (4) 107*h*.
Electronic equipment, ceramic, production of, (6) 165*e*.
ceramic wafers, drilling minute holes in, P (5) 138*b*.
components, for adaptive control systems, (7) 191*b*.
components, glass-to-Si seals for, (2) 48*d*.
continuous belt, for weighing systems, (10) 284*a*.
cool packages, (3) 76*c*.
for determining amount of ingredient in homogeneous material, P (7) 193*c*.
epitaxial mesa, field-effect transistors, and integrated circuits, growth of semiconductor crystals for, (2) 47*i*.
ferrite nanosecond memories, (2) 48*i*.
ferroelectric microwave switch, (7) 191*j*.
fiber optics for, (3) 76*j*.
gages, inhibiting line voltage variation in, P (1) 11*f*.
getters, Na_2O-B_2O_3-SiO_2 glass for, (6) 156*i*.
glass disk for generating low-frequency waveform, (2) 48*c*.
heat transfer in, (1) 19*d*.
high-speed servo positioner, for bonding mesa transistors, (7) 191*a*.
magnetic recorder powder, P (7) 194*b*.
magneto-optical information storage unit, P (2) 49*f*.
magnetoresistance microwave wattmeter, (7) 191*j*.
memory cell units, with moving quartz fibers, (2) 48*h*.
memory devices, method of making, P (6) 166*i*.
memory element, device for lowering cost, (10) 281*e*.
micromodule wafers, ceramic, connections to, (10) 281*e*.
nonreciprocal devices, use at low frequencies, (7) 192*j*.
Nuvistor, commercial and developmental status, (2) 48*j*.
pellet type components, printed circuit with interconnections between, (6) 165*a*.
potting composition for encapsulating electrical article, P (6) 165*j*.
printed circuit, method of making, P (5) 136*c*.
pyroelectric squaring element, P (8) 220*j*.
with semipermanent memory, use of twistors, (7) 192*b*.
solid-state reference junction, as thermocouple compensating devices, (9) 251*f*.
storage target, P (8) 221*b*.
Electronics. See also *Electric ceramics; Electronic equipment*.
ceramic products, properties and uses, (11) 310*f*.
crystals in, (10) 298*e*.
materials, glossary of, (4) 104*f*.
theory, of the atom and chemical bonding, B (5) 151*d*.
use of insulating anodic oxide films in, (9) 248*d*.
vacuum tight ceramic metal brazing in, B (4) 124*h*.

Electronographic studies, of structure of amorphous substances, background in, (5) 144*e*.
Electrons, energy loss passing through graphite single crystal, (6) 173*c*.
fast, luminescence from ruby excited by, (6) 164*a*.
nonthermionic emission into vacuum, (10) 281*h*.
100 kv beam, for irradiation of glass films, (2) 40*a*.
phototransfer in MeF_2:Eu,Sm monocrystals, (5) 145*d*.
self-trapping and drift motion of, B (9) 260*a*.
Electron tubes. See *Tubes*.
Electrophoresis, deposits, of $BaTiO_3$, (1) 19*f*.
in dewatering of slips for colored mosaic tile bodies, (7) 194*h*.
hardening of mica deposited by, P (4) 110*i*.
migration velocity, of particles of swelling and nonswelling layer silicate, (3) 86*c*.
Electrostatic processes, for applying reflective coatings to lamp envelopes, P (10) 271*a*.
for coating articles, apparatus for, P (1) 4*h*.
spraying, of atomized material, P (1) 5*a*.
Electrostriction, of Seignette ceramics, (10) 280*f*.
Elements, analytical chemistry of, B (10) 300*d*.
heating. See *Heating elements*.
metallic, structure of, B (5) 151*d*.
in rocks in small concentrations, extraction and usefulness, (1) 25*g*.
semimetallic, structure and properties of, XIII, (3) 89*c*.
Elutriation. See also *Beneficiation*.
air, in determining fineness of cement, effect of alcohol vapor, (7) 179*j*.
of kaolin, in centrifugal classifiers, (10) 288*c*.
Emeralds, synthetic, (6) 170*d*.
Emission, cathode, in ceramic vacuum tube, (8) 218*h*.
cold, devices, role of avalanching, (10) 281*h*.
electron, from oxide coated cathode subject to strong electric field, (11) 310*a*.
electron, from thin Al–Al_2O_3–Au structures, (5) 134*g*.
exoelectron, of phosphors $CaSO_4$,$CaSO_4$:Mn, and $CaSO_4$:Sm, (5) 134*j*.
in study of trapping levels in CaS and SrS phosphors, (5) 134*k*.
in study of ZnS:Cu phosphors, (5) 135*e*.
field, in rutile diodes, (10) 280*b*.
photo-, of Ba and Sr oxides, sulfides, selenides, and tellurides, (4) 117*d*.
photoelectric, from cathodes coated with SrO, (5) 135*i*.
secondary, of thin self-supported films of MgO, (5) 145*h*.
stimulated, of infrared radiation from Yb activated silicate glass, (5) 130*a*.
stimulated, from Nd^{3+} glass, (8) 209*e*.
ultraviolet, of Tl-activated Ca phosphates, (6) 164*h*.
Emissivity, black, coating, for metal, glass, and ceramic surfaces, (2) 48*h*.
of flames, method of obtaining, (6) 168*b*.
spectral, of materials and coatings, determination, (8) 222*h*.
thermal, device, P (4) 108*c*.
Emitters, shallow donor thermionic, (5) 135*a*.
Emulsions, polyvinyl acetate, properties of cement mortar containing, (8) 205*h*.
Enameled ware, appliances, color control in, (5) 127*i*.
bathtubs, machine for coating internal surface, P (2) 38*d*.
packing machine for, (4) 97*d*.
scrap reduction, (5) 127*f*.
steel, finishing of, (3) 65*h*.
customer-oriented product development, (4) 97*c*.
hot water tanks, bolt torques and gaskets for, (9) 238*b*.
household appliances, B (11) 322*g*.
iron, ductile, P (2) 38*a*.
laundry and refrigerator, low carbon steels for, (6) 155*g*.
panels. See *Building materials*.
refrigerators, flow coating machine for liner interiors, (5) 127*i*.
refrigerators, steps in production, (6) 155*e*.
signs, B (11) 322*h*.
steel sheet, use in limestone plant, (7) 178*f*.
washer baskets, for automatics, method of production, (4) 97*b*.
water heaters, tanks, and mufflers, property requirements, (11) 302*j*.
Enameling, chemical pretreatment in, (3) 65*d*.
conference on, 3d international, papers given, B (11) 322*b*.
conveyor hanger as mask in, (3) 79*g*.
cost practices, standard system for comparing, (3) 65*h*.
de-, system, (4) 97*c*.
defects, elimination on steel, P (10) 269*h*.
defects, fish scales, on sheet steel, (8) 207*e*.
direct-on, cover-coat, (2) 36*g*.
cover-coat, status report on, (7) 183*b*.
one-coat, in production, (5) 128*a*.
processes in, (5) 127*e*.
white, B (11) 322*h*.
dryers for, (8) 207*c*.
electro-, for glass tile, (1) 7*j*.
equipment. See also *Spraying*.
equipment, economies in, (2) 37*e*.
flow coating, of refrigerator liners, (2) 36*i*.
flow coating ground coat, (4) 97*h*.
future of, (8) 207*f*.
industry, and research, progress in India, (11) 303*b*.
low-temperature, (2) 37*d*.
low-temperature, for reducing warpage of steel stove parts, (11) 302*h*.
Enameling (*continued*)
of Mg and alloys, process, P (8) 208*b*.
materials handling in plant, (3) 65*i*.
method of, P (7) 184*a*.
mill additives, care and use, (2) 36*j*.
one-coat, advantages for appliances, (2) 37*f*.
one-fire, preparation of ferrous surface for, P (6) 155*h*.
operations, at Mississippi plant, (5) 127*g*.
plant, changeable layout for efficiency, (9) 238*d*.
infrared and radiant heat in, (8) 207*c*.
with "on-the-roof" furnace, (7) 183*i*.
for steel plumbing fixtures, (7) 183*c*.
two-story, for minimizing space requirements, (5) 128*c*.
shop, practices, (2) 36*h*.
surfacing torch, with external powder feed, P (10) 269*h*.
symposium on economies in, (2) 37*e*.
test methods, practical, (2) 37*g*.
Enameling industry, German, status and future, (8) 207*f*.
Enameling metals, Al, alloys, process of, (2) 37*f*.
alloys, surface preparation, P (4) 97*j*.
and alloys, technical hints, (10) 269*i*.
for artware, (5) 125*j*.
industrial, technology and quality testing, (10) 269*b*.
for wall panels and insulation, (10) 268*j*.
cast iron, clear primer for, P (6) 155*d*.
discussion of, (2) 36*h*.
iron, sheet, effect of minor constituents on, (3) 65*g*.
Mg, methods, (5) 127*g*.
pickling. See *Pickling*.
plant layout and furnace, (6) 155*g*.
preparation for cover coat, use of ferric sulfate, (2) 36*g*.
special steel for, (2) 37*d*.
steel, for artware, (5) 125*j*.
pickling for direct process, (1) 4*e*.
sheet, advantages of lower temperature, (2) 36*f*.
sheet, limits of deep drawing, (4) 97*h*.
Enamels. See also *Coatings*.
acid- and alkali-resistant, with cations of noninert gas structure, (8) 207*g*.
acid resistance test, (9) 238*j*.
adherence, direct-on, relation to metal and surface compositions and pickling rate, (2) 37*j*.
adhesion, problems and factors in, B (11) 322*g*.
antimony, B (11) 322*h*.
architectural porcelain, on steel, for exterior use, specification for, (7) 183*b*.
ASTM standards for, B (9) 259*b*.
automatic spraying on cooking utensils, (5) 137*i*.
bibliography and abstracts, 1959 supplement, B (1) 32*a*; 1960–61, B (1) 32*b*; 1962, B (9) 259*c*.
black, for wet application to cast iron, (8) 206*g*.
B and B-free, effect of iron oxide on viscosity, (1) 4*b*.
B and B-free, solubility of iron oxides in, (2) 37*b*.
for cast-iron chemical ware, frit compositions for, (5) 127*h*.
Chinese and Japanese cloisonné, B (11) 321*e*.
for coin-op laundry tubs, (4) 97*e*.
colored, compositions, (10) 268*i*.
colored, method of applying, P (9) 239*d*.
corrosion mechanism, data for, I, (10) 268*g*.
corrosion resistance, (10) 298*d*.
for corrosive environments, development of, (11) 302*j*.
as decoration of Avenue of Americas, (5) 127*j*.
defects. See also *Enamels, fish-scaling*.
prevention with decarburized steel, (2) 37*e*.
reduction by use of low carbon steel, (6) 155*g*.
for domestic water heaters, requirements, (5) 127*j*.
fire-resistant nontoxic yellow, P (6) 155*e*.
fish-scaling, effect of ferrous metals, B (11) 322*g*.
fish-scaling, relation of iron oxide solubility to, (1) 4*c*.
formulations and properties, (7) 183*f*.
frits. See *Frits*.
fused shock-resistant coat, for metal body, P (1) 4*j*.
fusion of, P (6) 155*e*.
gloss measurement, by Meyer method, (8) 207*f*.
ground coats, and acid-resistant, simultaneous firing on plumbing and lighting fixtures, (4) 97*e*.
flow coating, (4) 97*h*.
for sheet metal, changes in composition and application, (8) 206*h*.
high hardness, composition and application, P (10) 269*b*.
for labels on glass substrates, P (2) 38*e*.
melts, action on steel, (2) 36*e*.
for mufflers, P (9) 239*c*.
noncrizzling, for glass base, P (11) 305*a*.
powdered ground coats, for water heaters, (4) 97*f*.
properties, effect of clay on, (7) 183*c*.
properties and uses, (6) 155*c*.
red-brown, ferric oxide as colorant, (10) 269*b*.
rust control with, (11) 302*i*.
set and bubble structure, effect of clays on, (2) 37*a*.
silicate, P (2) 38*b*.
slips. See *Slips*.
Ti, with low TiO_2 contents, (7) 183*f*.
white, for Al, P (2) 38*f*.
white and black, for heavy duty sheet metal, (8) 208*a*.
with and without PbO and with phosphates, (10) 269*i*.
Energy, atomic research, diamonds in, I, (9) 235*g*.
band structure, of SiC crystal, (6) 173*b*.
of B-O bond, (10) 292*b*.
cohesive and surface, of Th and U oxides, calculation of, (3) 85*i*.
conversion process and apparatus, P (11) 303*a*.
electric, ThO_2 in thermionic conversion of heat to, (10) 279*g*.
electromagnetic wave, device for absorbing, P (10) 282*i*.
of formation and motion of vacancies in NaCl and KCl crystals, B (9) 261*b*.
free, equations for calculating, (4) 121*a*.
free, of formation of GeO_2, (1) 28*c*.
high acoustical-mechanical, transducer plate for transfer to liquids, P (5) 137*h*.
loss, of electrons passing through graphite single crystal, (6) 173*c*.
range, 0.1 to 4.0 Mev, determination of shielding factors of complex structures for, P (10) 287*e*.
solar, absorption, inorganic films for, (10) 269*d*.
solar, generating electric power from, P (4) 108*h*.
sonic, generating apparatus, P (11) 312*d*.
stored, in Oak Ridge graphite reactor, (10) 276*j*.
stored, release from neutron-irradiated U oxides, (1) 29*c*.
structure, of crystals, (10) 298*e*.
surface, of brucite, in water at 25°C, (7) 200*g*.
effect on diffusion-controlled particle growth, (3) 89*i*.
of quartz and orthoclase, direct measurements of, (8) 227*g*.
thermal, conversion to electrical with ferroelectric materials, (10) 279*i*.
thermal, device for converting into electrical, P (9) 248*h*.
ultrasonic, in casting ceramic and cermet slips, (8) 221*c*.
Engineering, ceramic, impact of materials science and materials engineering on, (2) 60*g*.
ceramic, Master and Doctor theses in, for year ending August 1962, (3) 93.
mechanical properties of, B (3) 91*g*.
objective criteria in education, (10) 298*c*.
training requirements, (6) 176*d*.
industrial, in foundry, B (9) 259*d*.
molecular, chemical vapor deposition in, (10) 284*b*.
refractory laminates in, (10) 276*c*.
temperature measurement in, Vol. II, B (2) 62*c*.
Engineers, work study, in reducing manufacturing costs, (7) 202*b*.
Engobes, for color in salt glaze, (7) 177*j*.
organic binders and other additives for, (3) 75*e*.
preparation and application to brick, (6) 159*c*.
roofing tile, effect of expansion and contraction on durability, B (10) 300*b*.
Engraving, glass, modern examples, (2) 33*j*.
Enstatite, stability, in relation to talc and anthophyllite, (2) 58*e*.
Enthalpy. See *Heat, content*.
Entropy, of crystalline lead metasilicate, lead orthosilicate, and cadmium metasilicate, (2) 57*g*.
of formation and motion of vacancies in NaCl and KCl crystals, B (9) 261*b*.
standard, of transition metal chalcogenides, estimation of, (1) 27*j*.
Environment, effect on brittle fracture of silica, (9) 240*e*.
Equations, Andrade, extension for viscosity at normal melting point, (1) 27*g*.
Equilibrium studies. See also *Systems*.
determination of phase relations of metal carbides at high temperatures, (10) 276*e*.
diffusionless phase, in ZrO_2 and HfO_2, (10) 291*g*.
of H-H_2O-SiO_2, (3) 68*f*.
phase change, in ZrC, (10) 296*a*.
phase diagrams, estimation for systems of two binary compounds, (10) 292*e*.
in study of glass structure, (7) 185*c*.
of system BaO-SiO_2, (3) 87*i*.
phase equilibria involving fused salts, thermodynamic calculations on, I, II, (2) 59*j*.
phase equilibria in portland cement clinker, B (5) 148*e*.
phase relations, in cordierite-garnet-bearing Kinsman quartz monzonite, (4) 117*j*.
phase studies, on arc-melted Pu-C alloys near monocarbide composition, (4) 117*j*.
phase transformations in SiO_2-Al_2O_3-MgO mixtures, study by X-ray diffraction, I, (6) 174*e*; II, (7) 199*d*.
phase transformations, in SiO-Al_2O_3 mixtures, continuous X-ray diffraction, (4) 118*b*.
phase transitions, in $LiAlO_2$, (10) 296*i*.
solid-liquid phase, for mixtures of Li, Na, and K carbonates, (1) 30*c*.
in system MgO-FeO-Fe_2O_3, in temperature range 1400° to 1800°C, (2) 58*f*.
ternary liquid equilibria, correlations for, (1) 27*c*.
Equipment. See *Machinery and equipment* and specific types.
Erosion, phenomena, study of, I, (9) 236*a*.
resistance, of fireclay brick to high calcareous slag, I, (1) 13*g*.
Etching, acid process, history of, (10) 265*i*.
agent, for MgO dislocations, (11) 318*c*.
agent, for sintered alumina, (11) 313*a*.
cathodic, of Pu ceramics, (11) 312*i*.
chemical, of defect structures in alumina-rich spinel single crystals, (11) 316*a*.
chemical, of Ge monocrystal, B (9) 263*c*.
differential, of $BaTiO_3$ by H_3PO_4, (2) 56*f*.
electrolytic, of SiC, P (6) 176*c*.
electrolytic and ultrasonic, of semiconductor device, P (8) 220*g*.

Etching *(continued)*
jet electrolytic, in making semiconductive device, P (10) 283*b*.
photosensitive gas phase, of semiconductors by selective radiation, P (10) 283*c*.
preferential, in making thin slices of semiconductive material, P (10) 283*i*.
of single crystals, with BO-PbO etchant, P (3) 89*i*.
of synthetic fluorphlogopite, (7) 199*c*.
techniques, for Al_2O_3 single crystals, (6) 167*h*.
techniques, in study of dislocations in rutile, (1) 27*a*.
Ethylene glycol, adsorption by montmorillonite, (4) 107*b*.
Ettringite, crystal chemistry of, (8) 226*i*.
-like phase, of cement with large additions of $CaSO_4$, (10) 266*d*.
Eucryptite, β-, ion emitter, studies of, (2) 59*c*.
ceramics, technology and behavior, (4) 101*j*.
Eutectics, in control of glaze properties, IV, V, (10) 278*g*.
Evaporation, method, P (2) 48*i*.
of subliming materials, P (10) 285*a*.
thermal, controlled, in vacuum, improved source, (1) 19*j*.
Excitation, of electroluminescence in alkali halides, (6) 163*j*.
Expansion. See also *Dilatometers*.
agents, in cement paste, effect on properties, (7) 181*b*.
-contraction curve, correct temperature for, (4) 113*j*
of ferrites, in firing process, (3) 76*h*.
of glass. See *Glass*.
of high-alumina refractories, experiments on, (11) 306*e*.
industrial, financing in ceramic industries, (6) 176*f*.
linear, of borosilicate glasses, change with time, (5) 128*g*.
moisture, of ceramic body, internal surface area, (10) 278*i*.
thermal, in air, of ceramic oxides to 2200°C, (10) 276*c*.
apparatus, for process control, (3) 81*g*.
in cabal glasses, correlation with structure and electrical properties, (3) 67*f*.
of ceramic materials, theoretical and practical, (8) 228*j*.
of CeO_2 by X-ray diffraction, (6) 175*h*.
combined with DTA in study of cement raw materials, (7) 180*h*.
data for rutile-type GeO, (6) 175*i*.
of glass, reduction near transformation range, (10) 270*g*.
of glass-ceramics, correlation with chemical composition, (5) 129*d*.
of hardened cement paste, (7) 182*f*.
linear, data for lead compounds, II, (3) 86*d*.
and moisture, effect on glaze fit, (4) 103*j*.
of oxide solid solutions, (1) 30*g*.
of Pu nitride, (10) 297*c*.
of K_2SO_4, instrument for measuring, (2) 52*h*.
properties, of $BaTiGe_2O_9$, (1) 30*i*.
of refractory brick, (3) 73*d*.
of refractory clay bodies, relation to packing of particles, (3) 72*g*.
reversible, control in pyrophyllite refractories by talc additions, (4) 100*j*.
of silica glass, as function of thermal history, (6) 156*h*.
of UP_2O_7, (5) 132*h*.
of vitreous and crystalline germania, (2) 59*i*.
Extraction, of BeO from beryl ore, (2) 54*g*.
development of methods, (9) 253*h*.
Extrusion. See also *Dies*.
apparatus, for plastic material, P (7) 195*b*.
augers, (2) 50*h*.
of BeO, effect on texture, (1) 30*d*.
of brick, South Australian, (5) 132*c*.
dies, effect of plastic properties of clay on design, B (10) 300*a*.
dies, high-pressure, P (3) 80*b*.
of ductile ceramics, feasibility, (8) 228*g*.
of glass, apparatus for, P (6) 157*a*.
hot, automation of, (9) 243*a*.
lubrication, P (2) 42*d*.
nozzles, effect of plastic properties of clays on (3) 71*d*.
processes, theoretical analysis, (11) 312*b*.
in ring and disk dies, (10) 284*e*.
of thin ceramics, (10) 284*g*.
ultrasonic, of nonclay ceramics, reduction in requirements, (8) 221*i*.

Faience, constructional, trends and possibilities, (6) 158*i*.
European, as artistic form, (10) 265*j*.
German, exhibition in Hetjens Museum, (3) 63*i*.
Habaner, B (3) 91*b*.
Niderviller, production, design, and decoration, (6) 153*h*.
Spanish-Moorish, (10) 265*j*.
Fatigue, direct-stress machine, for cumulative damage studies, (2) 52*e*.
Fayalite, DTA of, with and without vacuum, (10) 291*f*.
Feeding apparatus, circular, dual eccentric weight vibratory generator for, P (1) 23*g*.
for glass, batch materials, P (5) 131*c*; P (6) 157*c*.
for glass, with gas heating, design and calculation, (8) 224*e*.
for loose materials, P (4) 106*h*.
multiple, antisegregation charge, for shaft kilns P (4) 96*e*.
scoop, for rotary kiln, P (7) 197*b*.
vibratory, P (8) 222*d*.
vibratory bin, P (7) 195*c*.
Feldspars, melts, solution of quartz in, (4) 120*h*.
particle size, effect on properties of porcelain bodies, (8) 217*j*.
photoelastic effects in, (4) 112*g*.
potash, beneficiation of, P (5) 141*g*.
fusion and leucite formation, (1) 18*h*.
quick identification for quantitative thin section analysis, (4) 107*g*.
-quartz-kaolinite, high temperature reactions, (3) 75*g*.
reactions with NH_4Cl and $MgCl_2$ solutions, (4) 119*c*.
structure and physicochemical properties, (4) 110*g*.
Ferric, Ferrous, etc. See *Iron*.
Ferric oxide. See *Iron, oxide, ferric*.
Ferric sulfate. See *Iron, sulfate, ferric*.
Ferrimagnetism. See *Ferromagnetism and ferromagnetic materials*.
Ferrites, P (6) 166*b*. See also specific types.
alkaline earth, in variable strength permanent magnets, P (6) 166*i*.
barium, ferromagnetic, method of making, P (1) 21*h*.
bodies, for magnet cores, with rectangular hysteresis loops, P (4) 105*b*.
bodies, method of making, P (7) 194*c,d*.
Co, preparation of single crystals from melt, (1) 19*g*.
containing Nd, P (3) 77*a*.
development and applications, (8) 220*a*.
expansion and shrinkage, in firing process, (3) 76*h*.
far infrared absorption of, (6) 173*e*.
ferromagnetic, low-temperature synthesis of, (9) 247*f*.
F-containing, P (9) 249*a*.
with garnet structure, permeability and ferromagnetic resonance line width of, (9) 248*b*.
generation of magnetic anisotropy in by thermomechanical treatment, (3) 86*i*.
growth in arc-image furnace, (10) 284*g*.
high density, P (5) 136*d*.
in high power isolator, P (5) 136*e*.
impregnation with salt solution, P (5) 136*f*.
Fe-Ni single crystals, angular dependency of anisotropy induced by magnetic field, (3) 85*h*.
isolator, using aligned crystals with specific anisotropy constant, P (11) 311*c*.
laminated batt for firing without contamination, (10) 276*c*.
low loss, high Curie temperature, for high power applications, P (1) 21*e*.
as low power level limiters, (7) 192*h*.
magnetically annealed, P (2) 49*e*.
magnetostrictive, P (6) 166*e*.
magnetostrictive, small change in coupling coefficient, (6) 164*d*.
Mn, square loop magnetic, P (2) 50*a*.
valence changes of Fe and Mn in, (10) 297*g*.
-Zn, P (2) 49*h*.
Zn, micromorphological study, (10) 295*i*.
-Zn, quantifying Fe^{3+} and Mn^{2+} in, (6) 164*f*.
-Zn-ferrous, polycrystalline, properties of, (9) 247*j*.
manufacture, review of, (7) 192*a*.
memory core, high-speed, (2) 48*i*.
microwave, in magnetically tunable band-pass filters, (7) 191*j*.
microwave devices, P (2) 50*d*.
mixed, time decrease of magnetic permeability in, (11) 310*h*.
Ni-Fe, low-temperature transition of magnetic anisotropy in, (3) 87*j*.
Ni-Zn, in inductor materials, P (3) 77*e*.
orientation of, P (3) 78*b*.
for permanent magnet, P (1) 21*c*.
potassium, and alkali aluminate crystals, (6) 169*h*.
preparation for metallographic examination, (1) 19*b*.
for radio antennas, P (3) 77*c*.
with rectangular hysteresis loops, P (5) 135*j*.
remanence of, measurements on long-time magnetic aftereffects, (3) 87*e*.
sintered, study of magnetic properties using single crystal data, (1) 19*i*.
spheres, 3.5-in., preparation, (6) 164*b*.
spinel, ultrafine, formation of, (8) 219*i*.
substituted, of spinel structure, P (10) 282*f*.
as transducers, P (3) 77*a*.
use at low frequency, (7) 193*d*.
Ferroelectricity and ferroelectric materials. See also *Barium, titanate*.
and soft ferroelectrics, B (9) 263*i*.
aging of, (1) 19*b*.
$BaZrO_3$-$PbTiO_3$, hot-pressed, (5) 134*d*.
ceramics, material constants at high pressure, (11) 310*j*.
ceramics, small signal characteristics at mm wavelengths, (7) 192*c*.
in conversion of thermal to electric energy, (10) 279*i*.
crystals, B (4) 123*e*.
domains, in thin $BaTiO_3$ single crystal films, electron microscopic evidence, (6) 163*i*.
domain structure, in $BaTiO_3$, interferometric study of, (7) 191*d*.
domain-wall motion in $BaTiO_3$, velocity of, (3) 89*f*.
domain walls, in $BaTiO_3$, motion of, (4) 120*j*.
ferroelectric, and antiferroelectric crystals, growth and study, (3) 76*j*.
ceramic materials, P (4) 105*b*.
microwave switch, (7) 191*j*.
monocrystals, production by zone recrystallization, B (9) 263*f*.
phase transitions in system $PbTiO_3$-$KNbO_3$, (2) 47*j*.
solid solutions, Y-doped, with positive temperature coefficients of resistance, (6) 165*b*.
state, in $BaTiO_3$, transition to, (3) 89*b*.
Ferroelectricity *(continued)*
hot-pressing of, (4) 104*g*.
with layered structure, (7) 192*d*.
$PbNb_2O_6$, solid solutions based on, (1) 30*a*.
miniature device for computer logic and memories, (10) 281*e*.
in mixed bismuth oxides with layer-type structure, (2) 48*b*.
rare earth and Y manganates as, (9) 248*g*.
research and development, (8) 218*f,h*.
Ferromagnetism and ferromagnetic materials, P (3) 77*c*. See also *Magnetic materials*.
anti-, in $NiTiO_3$, (10) 279*f*.
CrO_2, preparation from CrO_3, (4) 118*g*.
elementary theory, design criteria, applications and limitations, (7) 193*d*.
ferrimagnetic, crystals, P (8) 220*i*.
method of making, P (3) 78*h*.
oxides, with hexagonal crystal structures, effect of Co^{2+} ions on magnetic anisotropy of, (5) 144*g*.
resonance, in $NiMnO_3$, (4) 114*c*.
ferrimagnetism, in $NiMnO_3$ and $CoMnO_3$, (4) 113*d*.
ferrimagnetism, of Y Fe garnet, (10) 291*i*.
ferromagnetic, body, from oxidic components, P (5) 136*b*.
cores, machines for testing and sorting, P (2) 49*e*.
γ ferric oxide, P (7) 194*e*.
layers, P (4) 105*e*.
oxides, method of making, P (6) 166*a*.
particles, orientation of, P (3) 78*c*.
resonance line width of ferrites with garnet structure, (9) 248*b*.
resonance-tuned microwave oscillator, (10) 280*a*.
low flux density, P (3) 77*g*.
materials, crystal structure, P (8) 220*j*.
materials, with piezomagnetic properties, P (11) 311*c*.
theory of Hall effect in, (3) 89*j*.
"weak," of antiferromagnetics, thermodynamic theory of, (11) 310*g*.
Ferrospinel. See *Spinel*.
Fertilizers, liquid, noncorrosive, molecularly dehydrated phosphate glass in, P (3) 69*e*.
Fibrous materials. See also *Aluminum, silicate fibers; Asbestos; Glass, fibers; Mineral wool; Quartz, fibers; Refractories*.
alumina, method of preparing, P (10) 277*g*.
alumina monohydrate, production, P (2) 46*b*.
bats, from pure silica, P (9) 245*d*.
coating with colloidal graphite for electric resistance elements, P (7) 193*i*.
in construction elements, P (1) 3*i*.
for filter cloth, (3) 79*f*.
heat resistant, P (9) 244*i*.
heat setting of binder for, P (10) 272*d*.
high temperature, production and use, B (5) 148*e*.
inorganic, electron micrographs of, (3) 86*e*.
inorganic oxide filaments, method of making, P (10) 277*c*.
metal, as reinforcement for slip-cast ceramics, (1) 4*e*.
mineral, mat from, P (2) 42*h*.
mineral, for paper products, P (3) 70*a*.
siliceous, in composite insulating unit, P (1) 16*e*.
siliceous inorganic, metallizing of, P (6) 155*f*.
as substrate for ferromagnetic Cr oxide, P (5) 137*e*.
as thermal insulation, advantages of, (8) 213*j*.
viscose rayon, carbonizing of, P (1) 26*c*.
water-resistant bonds for, P (9) 246*f*.
Filaments. See *Glass, fibers*.
Films. See *Coatings*.
Filters, air, cloth type, use in ceramic industry, (3) 79*f*.
in alkali determination, (8) 222*g*.
cake, shredder of rotating wires for, P (3) 80*a*.
clay, attapulgite as aid, P (6) 170*e*.
color, selective, P (5) 131*g*.
continuous, for dust collector, P (7) 195*a*.
continuous, for fluid processing system, P (10) 287*a*.
dust, sonic cleaning of, P (1) 23*e*.
electric, shaking device for, P (8) 222*a*.
electrostatic, in silicate and metallurgical industries, (5) 138*a*.
fiber glass fabric, for high temperature dust and fume control, (11) 303*i*.
gas, P (1) 23*g*.
gas, washer, P (2) 51*c*.
glass, cutoff, for radiation measurements, basic concepts, (2) 38*h*.
light, for Raman spectroscopy, Pr compounds for, (5) 147*i*.
in magnetic separator, P (3) 80*c*.
magnetically tunable microwave band-pass, (7) 191*j*.
mechanical frequency, butt joint in, P (10) 282*c*.
media, glass fibers as, (2) 39*f*.
media, near infrared spectra, P (1) 12*c*.
membrane, use in ceramics, (7) 194*i*.
mineral aids, P (6) 171*e*.
rotary, assembly, P (3) 85*e*.
rotary drum, cake removal, (3) 79*d*.
sand or fines, in rotary drum dryers, P (5) 140*g*.
suspension, for removal of fine dusts, (4) 108*b*.
Y Fe garnet band-pass, in transistor oscillator, (10) 280*a*.
Filtration, electro-, in prospecting of ceramic raw materials, (3) 83*j*.
of slurries, P (3) 84*c*.
in structural clay and whiteware industries, (3) 79*d*.
in system asbestos-cement-water, (8) 204*h*.
Financing, accounts receivable, (5) 148*c*.
Fine ceramics. See *Whiteware*.

Fineness, of cement and raw materials, determination by air elutriation, effect of alcohol vapor, (7) 179*j*.
of clinker and slag, effect on drying shrinkage of cement mortar, (8) 204*g*.
of slag and sand, effect on properties of cured specimens, (8) 203*j*.
Fire, resistance, of V-brick, (1) 12*h*.
Firebrick. See *Refractories*.
Fireclay. See also *Refractories*.
extruded ribbon, for ingot mold, P (10) 277*a*.
mineral, identification of, (4) 112*d*.
production in 1961, (3) 82*d*.
Firing. See also *Burners; Calcination; Combustion; Flames; Furnaces; Kilns; Sintering*.
of alkaline earth carbonates, P (3) 76*a*.
of brick and tile in German factories, (10) 273*f*.
of clays, reactions during, B (2) 61*j*.
combustion processes, in lightweight brick, (2) 53*e*.
effect on clay properties and mineral composition, (7) 197*e*.
gas, of intermittent kilns for stoneware pipe, (10) 287*g*.
high-temperature, of basic refractories, (8) 214*a*.
of huge pots, (4) 95*j*.
of low temperature glass, measurement, (10) 271*c*.
of porcelain, in tunnel kilns with liquefied gas, (7) 196*g*.
process, of $BaTiO_3$ ceramics, (11) 310*c*.
rapid, sandwich method, (7) 196*j*.
recuperative, advantages of, (2) 53*h*.
single, of porcelain hot cast under pressure, (7) 190*g*.
temperature, of $BaTiO_3$-UO_2 ceramics, effect of varying on dielectric properties, (10) 280*a*.
temperature, of slip-cast sillimanite, relation to porosity and corrosion resistance, (1) 15*b*.
vacuum, in high-temperature replication of kaolinite, (7) 201*f*.
Fission products, long-term storage, glasses for, (10) 270*f*.
Fixation, of K in Canadian soils, (5) 140*j*.
of radioactive wastes in glass, (11) 303*j*.
Flame photometry. See *Photometry*.
Flames. See also *Burners; Firing*.
apparatus and method for observation, P (5) 139*c*.
temperature, pyrometer for measuring, (6) 168*b*.
turbulent Bunsen, structure and propagation, (6) 169*a*.
Flocculation of cement, effect on properties of paste and mortar, (8) 205*a*.
Flotation. See also *Beneficiation*.
froth, of cryolite, P (7) 197*h*.
froth, of sulfidized clay pulp, in brightening clay, P (5) 141*e*.
index for 1961, B (5) 151*b*.
laboratory and pilot-plant studies, on mica, (9) 253*j*.
modified, in density determination for small solid samples, (7) 195*c*.
process, for calcium tungstate, P (10) 289*h*.
process, for concentration of phenacite and bertrandite, P (6) 170*h*.
Flow, apparatus, for separating granular particles, P (9) 250*b*.
behavior, of plastering cement, (8) 205*c*.
of dust, method of improving, P (9) 250*d*.
effect of structure of matter on, II, (9) 240*h*.
of gas, in lime shaft kiln, resistance to, (8) 205*e*.
of granular solids through orifices, (11) 313*a*.
heat, in glass tank, calculation of radiation flux in, (11) 314*c*.
measurement, B (10) 300*e*.
measuring and dividing system, P (2) 51*b*.
meter, selection of, (7) 195*d*.
of molten glass in glass tank, study by model techniques, (1) 9*h*.
of molten glass in tank furnace, experimental formulas, (8) 208*g*.
plastic, below melting point in oxide ceramics, B (2) 61*i*.
properties, of clay-chamotte bodies, relation to properties of slip cast bodies and particle size distribution of chamotte, (3) 73*f*.
viscoelastic, normal stress measurement in, (10) 295*f*.
viscoelastic, through tube, dimensionless groups in, (10) 291*i*.
Flowerpots, automatic shaping of, (10) 284*a*.
Flues covering process, P (9) 253*c*.
Fluidity, of coking coal, variation at constant temperature, (7) 196*e*.
Fluidization, design for, I,II, (1) 22*j*; III, (2) 50*i*.
of fine particles packed in layers, I, (8) 221*e*.
Fluids. See also *Liquids*.
Bingham, behavior in cone-and-plate viscometer, (10) 278*c*.
hydrothermal, ideality and ionization in, (6) 173*g*.
low-temperature, preventing loss of, (9) 250*j*.
measuring cells, reducing thermal variation in, P (10) 287*e*.
processing system, with continuous filter apparatus, P (10) 287*a*.
testing for particle contamination, P (10) 287*a*.
thermo-, as vehicles for preparation of ceramic coatings, P (6) 155*i*.
Fluoaluminates, as dielectric materials, P (10) 282*f*.
Fluorescence, of Mg phthalocyanine adsorbates on MgO, Al_2O_3, ZnO glass, (5) 130*f*.
of rare earths, (6) 163*i*.
Fluoridation, of water, P (3) 80*c*.
Fluorides, alkali and alkaline earth metal, relaxation luminescence spectra, (6) 165*g*.
alkaline earth, Eu,Sm-activated, color changes in, (5) 145*d*.
as base for ceramics, B (4) 124*g*.
compound, complex, cation size effects in formation of, (1) 26*g*.
Fluorides (*continued*)
content, safe limit for direct silica determination, (5) 145*e*.
crystalline complex of tetravalent americium, (1) 27*f*.
di-, of Ge and Sn, (1) 26*i*.
di-, of Mn, Fe, Co, Ni, and Zn, (10) 296*h*.
electrochemical determination, P (2) 60*a*.
ions, as mineralizer for $MgCO_3$ and MgO, (6) 159*j*.
ions, precipitation from solutions, P (9) 254*c*.
of Mg, Sr, Ca, or Ba, as covering for thermocouples, P (2) 38*c*.
3*d* transition metal double, magnetic structures of, (10) 294*i*.
Fluorination, high pressure, of U oxides, (7) 199*d*.
hydro-, of UO_2, kinetics of, (10) 294*d*.
of oxidic nuclear fuel, P (10) 289*i*.
Fluorine, in Ba ferrite, P (9) 249*a*.
compounds, production from F-containing minerals, P (3) 84*i*.
compounds, in slags for cement, P (3) 65*a*.
effect on growth of gypsum crystal and its prevention, (5) 126*f*.
in ferromagnetic chromium oxides, P (4) 105*c*.
harmful properties, (8) 230*g*.
in opaque glasses, analytical determination, (3) 65*f*.
small quantities, determination by pyrohydrolysis, (11) 312*j*.
Fluorites, crystals, X-rayed, infrared luminescence of F centers in, (5) 135*d*.
phase, in system CdO-UO_2-O_2, (5) 143*e*.
Fluormica. See *Mica*.
Fluorocarbons, sintered, as self-lubricating bearing material, (3) 79*i*.
Fluoroscopy, fundamentals of, (2) 52*g*.
Fluorphlogopite. See *Mica*.
Fluorspar, as admix for strengthening cement, (6) 154*e*.
Fluxes, for ceramic or glass articles, removal of impurities, P (2) 56*a*.
for crystal growth, Pb pyrophosphate as, (5) 147*h*.
ingredients, effect on properties of Mg-Ca-aluminosilicate glasses, (6) 156*h*.
magnetic granular, for gas shielded electric arc welding, P (10) 269*d*.
mechanism for formation of hopper crystals in, (5) 135*c*.
for metal coatings on ceramics, glass, or mica, P (3) 77*d*.
in operating core, semiconductor for measuring, (3) 76*g*.
radiation, calculation for heat flow in glass tank, (11) 314*c*.
for sewer-pipe bodies, (7) 187*c*.
in three phase coatings, (1) 4*j*.
Fly ash. See *Ash*.
Foamed ceramics, based on petalite and beta spodumene, (4) 101*a*.
silicate, for structural elements for rural and housing construction, (1) 6*h*.
Formation, of AlB_2, (4) 114*i*.
of anodic oxide films on Bi, kinetics of, (3) 87*h*.
constants, of $GeO_2(OH)_2^{2-}$, determination by use of H electrode, (10) 291*e*.
of double hydroxides and titration of clays, (10) 293*a*.
of glass, theory and data, (1) 8*c*.
of mullite crystals, (9) 256*j*.
of small balls of ceramic materials, P (1) 23*a*.
of thin ceramics, (10) 284*g*.
of yttrium orthosilicate, (4) 114*g*.
Forsterite. See also *Refractories*.
crystals, synthesis of, (6) 175*d*.
fused, specific heat of, (3) 73*d*.
as raw material for electron tubes, (11) 310*b*.
-spinel, ceramic bodies, P (2) 49*b*.
synthesis from molten PbO, (9) 257*h*.
synthesis, quantitative analysis of minerals in, (1) 18*a*.
systems. See *Systems*.
whiskers, ultimate strength of, (9) 257*e*.
Foundry, industrial engineering in, B (9) 259*d*.
shell process practice, B (9) 259*g*.
Fractionation. See *Separation*.
Fracture, brittle, of silica, effect of environment, (9) 240*e*.
in concrete, statistical aspects, II, (9) 237*g*.
effect of structure of matter on, II, (9) 240*h*.
of LiF, polycrystalline, (8) 226*j*.
mechanisms in crystalline ceramics, B (9) 259*e*.
propagation, in glass under varying strain, B (11) 321*b*.
strengths, of commercial glasses, (7) 184*d*.
by thermal shock, basic mechanisms, B (4) 124*b*.
Freezing, behavior, of water in brick, (3) 71*e*.
Freezing and thawing, tests. See *Frost resistance*.
Freons, synthetic zeolite for selective absorption of, P (6) 171*e*.
Friction, compositions, metal-ceramic, fasteners and mounting processes for, P (3) 73*j*.
composition, method of making, P (4) 102*h*.
effect of surface finish on, (3) 90*g*.
element, wear part, P (5) 133*e*.
internal, of quartz, (6) 173*j*.
internal, role in piezoelectric quartz crystals, (10) 282*b*.
metallic member, P (4) 95*h*.
Frits, compositions for cast-iron chemical ware enamels, (5) 127*h*.
enamel, for Al-coated and Al-rich alloy coated steel, P (3) 65*h*.
composition, P (10) 269*g*.
with titania base, P (2) 38*a*.
glass, in enamel slip, P (6) 155*g*.
low temperature-low expansion heterogeneous frit, (5) 134*c*.
for opaque white ceramic glazes, P (4) 104*b*.
Frits (*continued*)
silicone-coated, in decorating glassware, P (11) 305*a*.
of system SiO_2-BaO-TiO_2-Cr_2O_3, in coatings for high-temperature protection of metals, (10) 268*j*.
Ti enamel, soluble constituents leached from, (6) 155*h*.
Frost, damage, to porous solids, thermodynamics of, (8) 212*b*.
Frost resistance, determination by panel test, (3) 71*i*.
Fuels. See also *Ash, fly; Coal; Coke; Combustion; Gases; Oil*.
arrangement for nuclear reactors having vertical channels, P (8) 216*b*.
cell components, flame sprayed zirconia films for, (2) 36*h*.
ceramic, pins, transient heat transfer from, (4) 102*b*.
Core I assemblies, for gas-cooled reactor, materials development, (4) 101*b*.
dispersion, diffusion studies in, (11) 307*j*.
fabrication, properties, and irradiation stability, (11) 307*d*.
irradiation stability of, (11) 307*h*.
EGCR, irradiation effects in, (4) 101*g*.
elements, with cermet core of fissionable meta oxide particles, P (9) 244*h*.
dispersion of nuclear fuel in by pelletizing, (10) 275*a*.
dispersion type, (8) 213*d*.
dispersion-type materials in, (10) 275*f*.
for neutronic reactors, P (11) 308*c*.
nuclear, P (7) 190*a*; P (8) 216*i*.
nuclear reactor, P (8) 216*b*; P (10) 277*b*.
nuclear reactor, importance of oxides and carbides, (10) 274*b*.
nuclear reactor, temperature measurement for, P (8) 224*b*.
PuO_2 microspheres as, (3) 82*j*.
recovery process, P (8) 216*d*.
semihomogeneous, for gas-cooled reactor, (4) 100*i*.
UC for, (10) 275*f*.
UO_2, manufacture by vibration and swaging, (10) 275*g*.
gaseous, ASTM standard for, B (9) 259*b*.
gaseous, for firing porcelains, C_4 hydrocarbons as, (3) 81*j*.
mineral, B (6) 176*h*.
monocarbide, irradiation behavior, (11) 307*i*.
nuclear, ceramic, in system UO_2-ZrO_2-CaO, (3) 71*j*.
compact, P (8) 216*d*.
dispersion in fuel elements by pelletizing, (10) 275*a*.
method of making, P (9) 245*e*.
oxidic, fluorination of, P (10) 289*i*.
system for supporting in atomic reactors, P (11) 308*j*.
U compounds for, (10) 275*a*.
nuclear-reactor, P (11) 308*c*.
fuel-breeder, P (1) 16*j*.
used, fused-salt process for recovery of values from, P (6) 167*b*.
for Rapsodie fast reactor, B (8) 232*i*.
UO_2, fission products and Pu migration in, (4) 101*c*.
UO_2 pellets, low-temperature sintering of, (5) 132*j*.
Fuller's earth, production in 1961, (3) 82*d*.
Furnaces. See also *Burners; Fuels; Glassmaking apparatus and equipment; Kilns; Ovens; Refractories*.
Ajax, refractories in, (6) 161*b*.
all-basic, lightweight refractories for, (1) 13*i*.
Al electrolytic, recovery of cryolite from carbon bottom, P (3) 85*b*.
arches, stress measurement in, (8) 214*g*.
arc-image, Verneuil crystal growth in, (10) 284*g*.
atmospheres. See *Atmospheres*.
automatic glass bending and tempering, P (8) 210*j*.
basic refractories in, heat resistant coating for, P (9) 244*j*.
blast, evolution of, (10) 273*j*.
measurement of brickwork wear with radioactive isotope, I,II, (6) 159*j*.
production of high-temperature cement in, P (1) 3*e*.
refractories for air heaters for, P (3) 74*h*.
refractory linings for, P (4) 102*c*.
thickness gage for wall, P (6) 169*e*.
block, with hanger socket, P (4) 102*j*.
cement, shaft, supply apparatus for, P (6) 155*a*.
coating for refractory walls, P (5) 140*d*.
combustion chamber, P (11) 308*e*.
continuous slab reheating, high-alumina bricks in roofs, (11) 306*d*.
conveyor roll, P (1) 24*i*.
cooled transport rollers, P (11) 314*e*.
Cu refining, silica brick from roof, (8) 214*j*.
counterflow radiant-tube, in porcelain metals plant, (6) 155*g*.
crystal growing, P (2) 53*j*.
for dilatometry, P (8) 224*h*.
dolomite refractories in, (10) 274*g*.
electric, concrete with high-alumina cement for, (7) 188*b*.
control for, P (1) 24*g*.
interconnecting electrodes for, P (8) 224*j*.
for melting quartz or quartz glasses, P (4) 99*f*.
for melting or refining glass, P (10) 271*j*.
for steelmaking, refractories for, (6) 160*e*.
steel-melting, tar-dolomite brick in, (7) 187*h*.
electric arc, P (2) 45*e*.
electric resistance, installations for heating, (5) 140*f*.
electrodes, sealer-cooler structure for, P (2) 46*h*.

Furnaces (*continued*)
electron-beam, with opposed-field magnetic beam guidance, P (8) 223*h*.
for expanding perlite, P (10) 288*b*.
fire tube, for baking carbon articles, P (1) 16*b*.
fountain-type, for expansion of perlite, (2) 54*d*.
gas-fired panel, radiation characteristics of, (10) 287*i*.
glass, apparatus for mixing colorant in forehearth, P (2) 41*g*.
bakor-33, highly resistant electrofused refractory for, (1) 13*j*.
effect of operation on quality and quantity of glass, (3) 66*b*.
gas heated feeder for, (8) 224*e*.
heating of, (8) 208*j*.
for making fibers, P (10) 272*g*.
melting, P (2) 42*j*.
modifications to allow drawing of fibers at high temperature, (9) 240*d*.
oil-fired, operation of, (1) 6*f*.
operation control, P (1) 11*b*.
rational parameters for regenerator checkers in, (8) 224*h*.
sillimanite tank blocks for, (3) 73*j*.
testing of refractories for, (4) 101*i*.
with tube for directing glass current, P (8) 211*e*.
glass bending, P (8) 210*d*.
in glass container plant, (6) 156*e*.
glass tank, batch feeder as sintering chamber in, (1) 5*e*.
calculating with developed working installations, (1) 8*a*.
calculation of basic convection stream of glass in, (1) 5*f*.
calculation of radiation flux in, (11) 314*c*.
corrosion tests for block materials, (1) 6*a*.
direct-heated, refractories service in, (1) 8*i*.
flux line corrosion in, (3) 72*d*.
formulas for flow in, (8) 208*g*.
fused-cast blocks for, (7) 187*h*.
improving design of parts, (1) 7*i*.
instrumentation of, (8) 208*h*.
melting capacity, in Germany, (1) 7*i*.
models of, dimensional analysis of, (7) 184*c*.
recovery of waste heat to reduce cost, (3) 67*h*.
refractories for blocks for, P (6) 162*b*.
role of β-alumina in superstructures, (2) 40*h*.
study of flow by model techniques, (1) 9*h*.
superrefractories for, (6) 161*f*.
thermal conductivity of block materials, (1) 10*a*.
throats, I,II, (1) 7*b*; III, (3) 72*h*; IV, (8) 208*i*.
use of vitreous silica in, P (7) 187*e*.
zirconia-alumina-silica fusion cast refractories for, (10) 275*j*.
for heat cleaning glass cloth, P (10) 271*b*.
high pressure, introduction of power feeds and thermocouples, (2) 53*j*.
high temperature, with sharp temperature gradient, (11) 314*f*.
hot repair, sprayable basic refractory for, P (9) 245*e*.
hot repair, spraying of multiple coatings for, P (9) 244*i*.
image, arc, as research tool, (1) 28*i*.
imaging, heating of materials in, B (10) 300*f*.
induction, electric device for regulation of voltage and power factor, P (4) 108*g*.
industrial, expansion joint for wall construction in, P (8) 225*b*.
I.D. in Austria, refractory linings for, (6) 161*c*.
linings. See also *Refractories*.
with interconnected cooling tubes, P (1) 16*b*.
metal encased refractory unit for, P (8) 217*a*.
luminous wall, controls for, P (5) 140*c*.
melting, Al refractory for, P (6) 161*i*.
melting, refractories with no glassy phase for, (10) 274*i*.
metal ore reduction, brick lining for, P (7) 189*b*.
metal ribbon, use in high-temperature X-ray diffraction, (9) 252*c*.
movable, short, for sintering long ceramic compacts, P (2) 51*g*.
open-hearth, and Ajax, sampling of waste gas for analysis, (8) 224*i*.
basic metal-cased brick for roof, P (9) 244*g*.
bottoms, phase changes during forming and destruction of working layer, (1) 14*h*.
construction and operation, (11) 305*h*.
corrosion of checker-brick in regenerators, (8) 212*j*.
corrosion mechanism in zebra roof in, (3) 73*i*.
design, P (3) 74*h*.
door design, P (7) 189*j*.
effect of height increase in roof, (11) 305*i*.
high-forsterite brick in, (8) 215*c*.
high-load, using oxygen, forsterite checkers in, (7) 187*j*.
Meltz type, II, (11) 306*f*.
refractory silica brick for, P (6) 162*i*.
repair problems in, (11) 306*h*.
roof design, (1) 14*b*.
tests of brick after service in, (11) 305*g*.
unburned chrome-magnesia brick after service in, (11) 306*a*.
pot, melting of quality utility glasses in, (7) 184*i*.
pouring spout for, P (8) 224*g*.
for producing double sheet glazing units, P (11) 304*h*.
radiant, continuous sintering machine, P (7) 197*c*.
radiant tube, "on-the-roof," in enameling plant, (7) 183*i*.
recuperative firing, advantages of, (2) 53*h*.
refractories for. See *Refractories*.
regenerative, British, instrumentation, (3) 66*h*.
roller for, P (4) 108*g*.
roof block, P (8) 216*e*.
roofs. See also *Refractories*.
high-fired basic brick for, (8) 213*c*.

Furnaces, roofs (*continued*)
suspended by interconnected metal encased brick hanger extensions, P (5) 133*h*.
salt-bath, ceramic containers for, P (6) 169*e*.
shaft, control of feed to, P (1) 25*a*.
shaft, dual, endothermic processes in, P (5) 127*a*.
sintering, P (9) 253*e*.
for sintering magnesite, dolomite, or cement, heat exchangers in, P (4) 108*g*.
solar, pure synthetic minerals produced in, (5) 140*h*.
solar, temperature measurement in, I, (2) 52*a*.
steel, dead-burned dolomite in, (1) 13*f*.
steel, rotary, service conditions and nature of wear of refractories in, (7) 188*d*.
structures, refractories for, P (6) 162*c*.
superrefractories for, from oxynitride bonded SiC, (10) 276*b*.
tapping pots, slag-lined, P (3) 75*b*.
temperature of charge, measurement by radiation, P (9) 252*g*.
for thermal analysis of 6 mineral samples in one run, (5) 144*c*.
tube, alumina coatings for, (7) 183*e*.
unit-melter control equipment, (9) 253*e*.
U-type continuous, simultaneous firing of plumbing and lighting fixtures in, (4) 97*e*.
vacuum, resistance heating element for, P (2) 54*a*.
walking beam mechanism for, P (9) 253*f*.
walls, refractory bricks for, P (8) 217*c*.
world's largest, for water heater tanks, (5) 128*d*.
X-ray diffractometer, sample holder for, (3) 80*j*.
Fusion, behavior, of ceramic mixtures in eutectic areas, IV,V, (10) 278*g*.
characteristics and ranges, of Lakefield nepheline syenite, effect of grain size and iron oxide, (2) 54*h*.
machine, single station, for making semiconductor device, P (7) 194*c*.
temperatures, determination by penetration plastometer, (7) 196*i*.

Gadolinium, salts, photoluminescence of solutions and crystals of, (5) 145*c*.
Gages, Bourdon, quartz as, (6) 168*h*.
γ-ray, for measuring sheet glass thickness, (2) 39*c*.
linear dimension, P (8) 224*b*.
nuclear systems, in cement production, (7) 182*b*.
strain, in determination of glass elasticity constant, (9) 239*f*.
of fused quartz, P (10) 287*f*.
high-temperature bonding materials curable at low temperatures, IV,V, (9) 238*e*.
high temperature resistance, (6) 159*j*.
as pressure transducers, (7) 195*f*.
thickness, for blast furnace wall, P (6) 169*e*.
vacuum, thermal conductivity, (7) 196*a*.
Gallium, arsenide, high purity, P (6) 166*c*.
increasing donor concentration, P (8) 221*a*.
and phosphides, method of making, P (10) 283*b*.
in semiconductor body, P (5) 137*h*.
treatment of, P (4) 106*a*.
oxide, relaxation spectra and reabsorption, (6) 164*g*.
single crystals, growth of, P (5) 148*a*.
temperature and concentration dependence of luminescence spectra, (6) 164*e*.
phosphide, preparation of, (4) 118*h*.
sulfide dioxide, method of making, P (4) 105*h*.
Gamma rays, secondary, effect of boron carbide on yield of, (10) 274*i*.
Ganister, quarrying, for silica brick plant, (11) 314*h*.
Garnets, crystals, magnetic, P (1) 21*a*.
gemstone, synthetic, P (9) 249*b*.
polycrystalline ferrimagnetic, properties of, (1) 19*c*.
rare earth iron, crystal chemical study of, (9) 255*d*.
region, of system Y_2O_3–Fe_2O_3–FeO–Al_2O_3, (5) 144*i*.
single crystal, P (1) 21*i*.
Y Fe, crystal structure and ferrimagnetism of, (10) 291*j*.
effect of O pressure on incongruent melting temperature, (7) 199*f*.
ferrimagnetic resonance at liquid He temperatures, (2) 57*e*.
imperfections in crystals, (10) 294*c*.
magnetic anisotropy constant of, at 0°K, (3) 87*c*.
magnetostriction of, (4) 116*h*.
providing smooth magnetic surface on, P (8) 220*i*.
rotation of ultrasonic waves in, (6) 164*c*.
single crystal, research on, (8) 229*c*.
Zr, kimzeyite, from Arkansas, (4) 109*c*.
Gases, analyzers, (2) 39*d*; P (10) 286*i*.
automatic, using liquid reagent, P (1) 24*j*.
based on thermal conductivity, P (8) 223*j*.
chromatographic, (1) 23*i*.
infrared, two path, P (9) 253*b*.
for paramagnetic constituent, P (3) 89*i*.
resistance type, P (2) 53*c*.
split flow, P (8) 224*b*.
for toxic particles, P (8) 224*c*.
bubbles, formation in glass at high temperature, (3) 66*c*.
CO_2, effectiveness on cement slurry, (11) 302*a*.
carburizing, in carburization of W powder, II, (6) 171*g*.
combustible, apparatus for detecting, P (9) 253*f*.
combustion, effect on ceramic colors, (2) 47*a*.
dispersion and absorption of microwaves in, B (9) 263*h*.
displacement from powders during compaction, (1) 22*j*.
filtering method and apparatus, P (1) 23*g*.

Gases (*continued*)
filters, washer, P (2) 51*c*.
flowmeters for, (7) 195*d*.
furnace, condensed, sampling device and method, P (4) 108*i*.
gaseous blast, method of producing for glass fiber manufacture, P (8) 211*g*.
heat exchangers, of cellular Pyroceram, (6) 169*b*.
industrial, in stoneware industry, (10) 287*i*.
installations, in potteries, (6) 169*b*.
interdiffusion, in low permeability graphite at uniform pressure, (1) 28*a*.
light, detector, with thin-walled glass tubes, P (11) 304*j*.
liquefied, for firing porcelain in tunnel kiln, (7) 196*g*.
liquefied, for industrial use, (5) 140*d*.
meter, for low rates of flow, (5) 139*c*.
mixtures, electrochemical determination of components in, (1) 24*b*.
moisture measurement in, (8) 223*e*.
multicomponent, heat transfer in hypersonic environment, (10) 294*b*.
O in, electrical measurement of, P (5) 139*h*.
pressure, glass instruments for measurement, (1) 6*i*.
radiolytic, in thorium oxide slurries, catalytic recombination, P (1) 15*i*.
rare, radioactive fission product, in study of phase change in fine particles, (6) 176*a*.
reactions, milieu for, P (8) 224*j*.
solubility in glass, (3) 68*b*.
streams, analyzers for, (1) 23*j*.
streams, thermocouple performance, (4) 108*a*.
use in potteries, (6) 169*a*.
vermiculite in absorption of, (2) 54*h*.
waste, from furnaces, sampling systems for analysis, (8) 224*i*.
waste, recovery of cryolite from, P (3) 85*b*.
Gelometers, for measuring gelling time of fluids, (4) 107*g*.
Gels. See *Colloids; Silica; Tobermorite*.
Gems. See also *Stones*.
artificial, P (4) 121*h*.
with garnet structure, P (9) 249*b*.
particles, shaping and polishing, P (10) 285*b*.
synthetic, (7) 202*a*.
Generators, alkali metal, P (10) 269*a*.
Hall, magnetically responsive resistance device, P (7) 193*d*.
infrared, gas-fueled, P (8) 224*h*.
thermoelectric, P (5) 137*e*.
with encapsulated arms, P (4) 106*c*.
with graded energy gap, P (1) 22*a*.
power, development of, (10) 280*e*.
Geochemistry, physical, B (10) 299*j*.
sedimentary, environmental studies in, (4) 109*d*.
Geology, of Haldeman and Wrigley quadrangles, Ky., (6) 170*a*.
photo-, use of, (8) 225*h*.
specimens, microanalysis by emission spectroscopy, (8) 223*c*.
Geophysics, techniques, for prospecting, use o electric properties in, (10) 282*g*.
Germanates, with ring anions, spectra of, (5) 147*f*.
spinels, (10) 293*i*.
Germania. See *Germanium, dioxide*.
Germanium, Cu and O in, kinetics and equilibria of, B (9) 260*g*.
crystal, deuteron-irradiated, small angle scattering of X rays by, (7) 200*f*.
difluorides, chemistry of, (1) 26*i*.
dioxide, heats and free energies of formation, (1) 28*c*.
dioxide, vitreous and crystalline, thermal-expansion properties of, (2) 59*i*.
films, monocrystalline, deposition from vapor, B (9) 263*c*.
hyperpure, method of producing, P (11) 311*b*.
irradiated, carrier recombination and trapping processes, (8) 226*e*.
light induced plasticity in, (6) 174*h*.
oxide, densification of, P (10) 271*f*.
effect on antimonate glass properties, (11) 304*b*.
refinement of crystal-structure determination, (10) 296*h*.
rutile-type, thermal-expansion data, (6) 175*i*.
systems. See *Systems*.
single crystal, epitaxial vapor growth of, (4) 113*i*.
telluride, systems. See *Systems*.
Gibbsite, μ-sized powders, reactions when heated in air, I,II, (4) 119*g*.
transformation of bayerite into, (5) 142*f*.
vermiforms, in Pensauken formation of New Jersey, (4) 109*j*.
Glass. See also *Art and Artware; Furnaces; Glass industry; Glassmaking apparatus and equipment; Vitreous state*.
on ablating and radiating blunt body, mathematical analysis of conditions occurring in, (1) 5*d*.
acid-base concept in, (1) 26*f*.
adhesives for, (1) 5*d*.
in aircraft, high-speed, (1) 10*f*.
alkali borate, boron coordination in, (2) 40*b*.
alkali borate, NMR study of structure, (9) 240*i*.
alkali–B_2O_3–SiO_2, and PbO–B_2O_3–SiO_2, solubility in water, (10) 278*g*.
alkali germanate, Raman spectra of, (5) 129*c*.
Al_2O_3, structure and fluorescence of Mg phthalocyanine adsorbates on, (5) 130*f*.
aluminosilicate, constitution of, (3) 66*e*.
aluminosilicate, irradiated, electron-spin resonance studies of, (2) 39*i*.
ampul, abraded neck, P (3) 70*e*.
anelasticity, correction of original paper, (8) 209*c*.
in analyzer for measurement of flux of neutrons, P (3) 69*i*.

Glass (*continued*)
ancient, analyses of, B (3) 90*h*.
corroded, study by X-ray diffraction, (11) 301*i*.
of Japan, (11) 301*h*.
annealing, effect and advantages of convection heated lehrs, (1) 6*c*.
antimonate, infrared absorption of, (11) 304*b*.
apparatus, for gas analysis, (2) 39*d*.
for gas pressure measurement, (1) 6*i*.
and instrument industry, history of, (4) 98*i*.
scientific, joints for use in, P (6) 157*e*.
applications and properties, (9) 258*b*.
As_2O_3, infrared absorption and structure of, (1) 7*b*.
As_2Se–As_2Se_3, absorption spectra of, (5) 128*g*.
arsenic-sulfur-iodine, chemical durability of, (3) 66*b*.
art and crystal, ultrasonic cleaning, (7) 184*g*.
articles, with electrically conductive coating, P (5) 130*c*.
hollow, method of making, P (5) 131*a*.
increasing chemical resistance, P (11) 305*a*.
with metallic luster, P (3) 70*b*.
aspheric surfaces, polishing method, P (1) 10*h*.
ASTM standards for, B (9) 259*b*.
attack, electrophilic and nucleophilic mechanisms, (4) 98*a*.
attack, on refractory oxides, (8) 228*a*.
automatic batching, I,II, (11) 303*e*.
barium borate, X-ray study of, (7) 185*e*.
Ba borosilicate, radial distribution study, (6) 156*f*; B (11) 320*i*.
batch, calculating composition from, (3) 65*j*.
melting of, P (6) 157*i*.
preparation of ingredients, P (7) 186*d*.
beads, as blasting media, (9) 235*h*.
beads, composition, P (4) 99*g*.
bending, method, P (8) 210*e*.
bismuth borate, dielectric properties of, (3) 66*f*.
blisters, in Fourcault process, (1) 8*d*.
blocks, catadioptric electroluminescent, P (8) 210*b*.
blowing, history of, (1) 7*i*.
blowing, proceedings of 7th symposium on art of, B (5) 151*f*.
blown, articles, control of wall thickness, P (1) 12*b*.
blown, elimination of neck flash, P (7) 185*j*.
bodies, method of joining, P (11) 305*a*.
Bohemian, history and contribution, (7) 177*h*.
borate, measurement of infrared spectra in, (3) 66*d*.
optical, P (7) 186*e*.
optical properties of, (8) 209*f*.
boric acid-phosphate, melting and processing technology, (8) 208*i*.
boric oxide and borate, structure of, (3) 68*f*.
borosilicate, I,II, (5) 128*h*.
breaking strengths, (7) 184*d*.
cause of optical anisotropy in, (10) 270*g*.
for chemical ware, (1) 6*j*.
cleaning processes for, (9) 239*h*.
constitution of, (3) 66*e*.
glazes for, (5) 134*c*.
H atom recombination on, (9) 240*g*.
"pireksil" from, (1) 7*f*.
sorption and desorption of water on, (8) 209*d*.
in spark plug resistor, P (8) 221*a*.
spheres, use in building materials, (10) 270*j*.
volatilization of constituents at high temperatures, (2) 41*j*; correction, (8) 209*j*.
volume conductivity of, comments on, (10) 270*a*.
bottles. See also *Glass, containers*.
application of plastic coatings, P (2) 42*a*.
hypochlorite bleach, P (5) 131*b*.
increasing life of molds for, (4) 98*i*.
industry in Sweden 1870–1920, I–III, (1) 5*f*.
infusion, defects in, (1) 8*g*.
loading apparatus for, P (4) 100*b*.
soda-lime-silica, improvement of chemical durability, (2) 39*g*.
steeped in soakers, surface cracks on, (8) 208*i*.
breaking strength, effect of heat treatment, (10) 270*e*.
breaks. See *Glass, fractures*.
bubbles, formation and growth in melting, (11) 303*h*.
bubbles in, in Japanese glass, (1) 7*c*.
bulbs, with layer of expanded synthetic resin, P (3) 69*e*.
bulbs, light-scattering coatings for inside, P (2) 60*i*.
bulk strand, integrated at spaced zones, method of producing, P (2) 42*d*.
button, analysis, (9) 251*c*.
button stems, improved strain settings in, (2) 39*g*.
cabal, thermal expansion in, correlation with structure and electrical properties, (3) 67*f*.
Cd phosphate, composition, P (7) 185*i*.
CdS- and CdS,CdSe-colored, spectral study of, (5) 129*f*.
Cd sulfoselenide, chemical potential of oxygen in, (3) 67*j*.
Ca aluminoborosilicate, corrosion of zircon refractories by, (1) 6*c*.
Ca boroaluminate, dc conductivity and structure, (1) 8*j*.
Ca boroaluminate, relation of dielectric properties to structure, (1) 8*b*.
cast, reinforced, continuous manufacture, P (8) 211*a*.
cation sensitive, study of electrode properties of, (3) 67*a*.
cemented optics or lenses, delaminating of, P (1) 12*c*.
cementing of, (1) 5*d*.
-ceramics, catalyzed with zirconia, B (11) 320*g*.

Glass, ceramics (*continued*)
fine grained crystalline, containing Cr_2O_3, I–III, (5) 129*a*.
Japanese technology, (1) 7*c*.
with low thermal expansion, in system Li_2O–Al_2O_3–SiO_2–CaO, (5) 129*b*.
Ce-containing, γ-ray-induced coloring of, (1) 5*e*.
chemical, fused to metal alloy for chemical processing equipment, P (3) 65*e*.
chemical durability, (3) 66*b*.
chemical durability, improvement in, (2) 39*g*.
chemically stable, P (2) 41*j*.
for chemical plant, (1) 6*j*.
chemical resistance, increasing, P (11) 305*a*.
Christmas tree balls, packaging of, P (9) 242*a*.
Cr-containing, color of, (8) 208*g*.
clarifying, P (2) 41*j*.
cloth, heat cleaning apparatus, P (10) 271*b*.
cloth, as reinforcement for polyester and epoxy resin laminates, (9) 239*e*.
coating method, P (9) 242*f*.
coatings for, colored silicate, P (4) 99*a*.
electrically conducting, P (6) 157*i*.
electrically conductive, apparatus for producing, P (8) 211*i*.
for exerting fluxing effect on revitrification, P (1) 12*f*.
transparent electrically conducting, P (4) 99*e*.
Co, in dosimeters, (9) 240*f*.
Co, for safety goggles, P (2) 41*j*.
colorant, apparatus for mixing in furnace forehearth, P (2) 41*g*.
coloration, γ-ray induced, Ce ion in preventing, (11) 304*h*.
colored, P (2) 41*j*.
crystal, and technical, melting in pot furnace, (7) 184*i*.
ligand field theory in, (7) 184*b*.
transition metals, application of ligand field theory to, B (11) 320*g*.
coloring, P (2) 42*a*; P (4) 99*b*.
action of Fe in, magnetic properties in relation to, IV, (2) 41*d*.
relation of magnetic properties of iron to, III, (1) 9*i*.
commercial, in corrosion of corundum crystals, (10) 274*d*.
composition, P (4) 99*g*; P (7) 186*b*.
additions to increase Young's modulus, P (2) 42*g*.
constants for calculating from batch, (3) 65*j*.
determination from physical property measurements, (9) 241*j*.
effect on ultraviolet absorption, (8) 208*j*.
high chemical durability, P (2) 42*f*.
of high Young's modulus glasses, I, II, (1) 9*c*.
of medieval glasses, (1) 7*g*.
polishing-etching-interferometric determination, (1) 7*h*.
for wire-drawing lubricants, P (6) 157*b*.
congress, 6th international, papers and discussions of, (11) 320*f*.
constitution, dynamic interpretation, Vol. I, B (10) 298*i*.
constitution, knowledge of, (9) 240*h*.
construction units, bonding method, P (4) 99*i*.
container, cast iron for molds, (3) 65*j*.
chemical surface resistance, (1) 5*g*.
industry, statistical quality control in, (9) 241*j*.
plant, automation in, (10) 269*j*.
use of boric oxide in, (2) 41*g*.
containers, detection of flaws in, P (4) 99*c*.
evaluation of cords in, (1) 6*f*.
method of flame treating exterior, P (1) 11*g*.
of opal glass, for marketing toiletries, (3) 67*b*.
production, (6) 156*e*.
volumetric measurement, P (3) 70*h*.
contamination, effect on electrical breakdown in vacuum, (10) 280*b*.
contour polished, manufacture of, P (3) 69*d*.
convection stream, in tank furnace, calculation of, (1) 5*f*.
copper, chemical potential of oxygen in, (3) 67*i*.
cords, evaluation in containers, (1) 6*f*.
cords, and knots, (1) 7*k*.
corrosion resistance, (10) 298*d*.
craft, designing, forming, and decorating, B (2) 61*c*.
crystal, cutting with diamond, (6) 156*c*.
goblets, ring of, (1) 8*f*.
melting and production, (1) 7*i*.
method of making pattern and product, P (3) 70*i*.
striae during melting, (1) 9*b*.
crystallization ,catalyzed, B (8) 232*e*.
crystallization, effect of molecular structure, (1) 8*c*.
crystallization of perovskite lead titanate from, (9) 239*h*.
crystallized, heat exchange material of, (3) 66*b*.
curved, shipping container for, P (3) 70*e*.
decoration. See *Decoration*.
decorative panels, producing from fibrous glass, P (2) 42*e*.
defects, apparatus for detecting, (9) 239*f*.
development on etched glass surfaces, (7) 184*j*.
pathologic technology of, (1) 8*f*.
striae in crystal glass melting, (1) 9*b*.
densification of, P (10) 271*f*.
deposition of metal on for decoration, P (10) 272*f*.
designing, B (2) 61*c*.
devitrified, as aggregate for road surface, P (5) 131*f*.
dictionary, B (8) 231*h*.
for dielectric uses, P (5) 130*i*.
diffusion studies in, I-IV, (9) 239*h*.
directory, B (8) 231*k*.
disk, for generating low-frequency waveform, (2) 48*c*.

Glass (*continued*)
distribution of heavy atoms in, X-ray study, (10) 271*i*.
double-glazed units. See *Glass, glazing units*.
double plane, for highway use, (9) 240*e*.
ductility, relation to electroconductivity, (7) 185*f*.
dulling, possible use of screen printing, (11) 304*e*.
dust, biologic effects, (2) 60*c*.
effect of very high pressures, tests by tetrahedral anvil apparatus, (8) 208*f*.
elasticity constant, determination by resistance strain gages, (9) 239*f*.
elastic properties during torsion, (2) 39*d*.
electrical conductivity, effect of γ-ray irradiation, (8) 209*a*.
electrically conductive, P (3) 70*g*; P (9) 241*h*.
for aircraft windshields, P (6) 157*j*.
multilayer, P (1) 11*e*.
electric properties of, control, (9) 240*a*.
electrodes. See *Electrodes*.
electronic conduction in, (10) 280*i*.
with electronic conductivity, B (11) 321*a*.
for electronic getters, (6) 156*i*.
engraving, modern examples, (2) 33*j*.
equipment, graphic symbols for, (5) 139*c*.
exhibit, at U. S. National Museum, B (11) 321*d*.
expansion, at annealing temperature, measurement by dilatometer, (10) 286*b*.
fenestration structure, for control of daylighting, P (10) 271*g*.
Fiberglas plastic, effect on health, (2) 60*h*.
fibers, P (6) 157*c*. See also *Mineral wool*.
in abrasive wheel, P (7) 177*f*.
from aqueous compositions, P (2) 42*h*.
board, with plastic coating, for sound absorption, P (9) 242*e*.
cleaning and coating, P (3) 70*b*.
coated with organosilicon polyol, P (7) 186*d*.
combination with synthetic resin fibers, P (9) 242*b*.
composite, P (5) 130*g*.
composition, P (1) 11*j*; P (8) 210*f*; P (10) 272*a*.
crystalline, P (3) 69*f*.
cushion material, P (2) 42*c*.
in decorative panels, P (2) 42*e*.
effect of annealing on room temperature strength, (9) 239*f*.
effect of length on strength properties, (9) 240*d,e*.
filaments, forming and collecting, P (9) 242*e*.
filaments, metallic-coated in making pressure vessel, P (8) 211*f*.
filaments, method of coating, P (7) 186*j*.
as filter media, (2) 39*f*.
filters, for high temperature dust and fume control, (11) 303*i*.
forming for gas plating of metal on, P (10) 272*i*.
fuel-bearing, and Al, in compacts, radiation stability of, (9) 241*f*.
furnace for making, P (10) 272*g*.
geometry, effect on composite material strength, (6) 156*g*.
in grommeted jacket for handlers of glass, (11) 304*f*.
as gypsum reinforcing, P (3) 65*b*.
highly refractory, in dental porcelain, P (4) 104*e*.
high strength, development of, (9) 240*c,d*.
high temperature, techniques and materials for forming, (8) 214*e*.
high temperature properties, (9) 241*e*.
history and progenosis, B (11) 321*g*.
impregnated, for making tanks, P (1) 12*d*.
insulation, heat loss data for, (9) 250*j*.
laminates, P (4) 99*f*.
light-conducting, P (3) 69*b*.
making resin-bonded products from, P (1) 12*e*.
mat, P (7) 186*a*.
mat formation from, P (2) 42*h*.
in metal and fiber composite, P (10) 272*h*.
metallized, P (3) 69*f*.
method of making, P (1) 11*i*; P (7) 186*g,i*; P (8) 211*c*; P (11) 305*b*.
optical device, method for shaping, P (1) 12*a*.
optical measurement of diameters, P (4) 100*e*.
panels, color-patterned, P (3) 70*c*.
paper, for air sampling, (3) 90*e*.
in paper products, P (3) 70*a*.
porous, transformation by heat treatment, (10) 270*d*.
precoating and coating method, P (9) 242*g*.
pressure vessels, filament wound, factors affecting performance and aging, (4) 98*e*.
processing high-feldspar-iron sand for, (9) 254*b*.
producing gaseous blast for forming, P (8) 211*g*.
production, P (6) 157*a,b*; P (6) 158*f*.
products, (1) 8*h*; P (3) 69*h*.
products, with foamed binder, P (1) 11*f*.
reconstitution of, P (2) 42*c*.
reinforcement, P (7) 186*a*.
reinforcement, applications of, B (3) 92*g*.
reinforcement, in heat shield, (8) 214*c*.
reinforcement, in liner for steel pipe, P (4) 100*c*.
reinforcement, in plastics, (1) 7*a*.
reinforcement, radioactively determining uniformity of finish, P (4) 100*f*.
resilient corrosion-resistant attenuated, P (7) 186*c*.
in separator plate, P (8) 211*f*.
silica, Japanese production, (1) 7*c*.
size, composition, P (7) 186*d*.
sized, composition, P (10) 273*c*.
strength, statistical study of factors affecting, (9) 241*h*.
structural, high modulus, (9) 239*g*.
study of factors affecting strength and properties, (2) 38*i*.
surface treated, P (2) 43*a*.
tape, bonding to silicone rubber, P (1) 12*b*.

Glass, fibers (*continued*)
treatment, II-VII, (10) 270*c*.
twisted yarn package, P (3) 70*h*.
uniform, drawing apparatus, P (2) 41*a*.
vapor coated, P (5) 131*f*.
yarn, dying of, P (4) 100*f*.
fibrous board, rigid laminated, P (7) 186*d*.
filamentous mats, apparatus for spinning, P (10) 271*c*.
film, superthin, uses of, (1) 8*i*.
fine holes formed in, (11) 313*f*.
firing over clay forms, (5) 126*b*.
firing on metals, (5) 126*b*.
flake, effect on health, (2) 60*h*.
as electrical insulation, P (3) 69*h*.
as reinforcement, potential in engineering structural materials, (9) 240*b*.
flat. See also *Glass: plate, sheet, window*.
making in continuous ribbon form, P (7) 186*g*.
method of making, P (7) 186*f*.
processes, evolution during 20th century, (2) 39*c*.
vertical washer for, P (10) 273*c*.
flaws, causes of, (10) 270*e*.
flexible, for protection against atomic, bacterial, or chemical warfare, P (4) 99*f*.
float, development of technology, (2) 39*c*.
float, molten tin as mold for, (5) 129*j*.
flow, in tank, experimental formulas, (8) 208*g*.
flow, in tank, study by model techniques, (1) 9*h*.
fluoride-opal, (Standard Glass No. 4), chemical analysis of, (2) 38*j*.
foam, raw materials, processing, and properties, (1) 8*h*.
foamed, production, properties, and use, B (8) 231*i*.
formation, in Li metasilicate region of system Li_2O–Al_2O_3–SiO_2, (4) 98*g*.
theory and data, (1) 8*c*.
by vapor deposition, B (11) 320*g*.
forming, B (2) 61*c*.
-forming, systems, compatibility in, (1) 5*h*.
fossil, produced by meteorites and asteroids, B (11) 321*h*.
Fourcault process, open blisters in, (1) 8*d*.
fracture, (2) 39*j*.
supervelocity of, (8) 209*i*.
surface, structure of, (4) 99*a*.
fracture strength of, (7) 184*d*.
frit, vehicle, composition, P (7) 186*e*.
fused, conversion to porcelain by crystallization after shaping and solidification, P (2) 42*b*.
fused fabric, in high strength material, P (10) 272*d*.
fusion of, P (6) 155*e*.
γ radiation dosage-measuring, P (9) 241*j*.
γ-ray gage for measuring thickness, (2) 39*c*.
gas bubble formation in at high temperature, (3) 66*c*.
germanium, physicochemical properties, B (11) 321*a*.
glazing units, double sheet, furnace for producing, P (11) 304*h*.
multiple sheet, P (8) 211*d*.
multiple sheet, inspecting dew point of, P (3) 69*h*.
multiple sheet, method of making, P (6) 158*a,b*.
multiple sheet, method of treating, P (4) 100*g*.
multiple sheet, production by fusion bonding, P (10) 271*b*.
sealed double, performance of, (2) 40*g*.
gold, chemical potential of oxygen in, (3) 67*i*.
gold-ruby, composition, (7) 185*a*.
granule, on metal filament, for miniature desiccator unit, P (2) 50*e*.
gray ophthalmic, composition, P (10) 272*h*.
grinding of. See *Grinding and polishing*.
gypsum in, (7) 184*f*.
hardness, and thermal stability, increasing of, (7) 185*e*.
heating mantle, with Al shield, (3) 67*g*.
heterogeneities in, (1) 7*h*.
heterogeneity, assessment of, (1) 5*j*.
high-melting point, containing UO_2 particles, (11) 308*f*.
history of, B (3) 90*h*.
hollow, articles, blow molding of, P (8) 211*e*.
articles, manufacture of, P (8) 211*b*.
determination of wall thickness and glass distribution in, (1) 6*h*.
history and technical problems, (1) 7*f*.
homogeneous batch, for mechanical production of sheet glass, (8) 209*a*.
homogenization, method of, P (1) 10*g*.
homogenization, strioscopic apparatus for study of degree of, (8) 209*d*.
honeycomb, of crystallized glass, for heat exchange, (3) 66*b*.
in hot extrusion of metals, (1) 10*i*.
illuminating, B (11) 322*h*.
infrared absorption spectra of, changes on crystallization, (5) 128*h*.
inhomogeneity, and phonon scattering, (5) 129*j*.
inorganic metal oxides, P (1) 11*f*.
insulating, multipane, preparation, P (10) 272*j*.
irradiation damage to, (9) 240*g*.
Jena, history of, (4) 98*i*.
journal supporting elements, for bearings, P (5) 130*d*.
kiln-formed, designing with wire, (4) 126*a*.
kiln-formed, firing of, (7) 177*i*.
laminated, P (2) 42*i,j*.
articles, P (9) 242*b*.
safety, P (3) 69*b*.
and toughened, production methods, (7) 185*j*.
lamps, base, assembly, P (2) 42*a*.
electric gas discharge, luminescent layer, P (2) 42*c*.
envelope, producing light-diffusing layer on, P (2) 42*e*.

Glass, lamps (*continued*)
fluorescent, methods of coating, P (2) 42*g*.
He-Ar fluorescent, P (1) 11*e*.
incandescent, miniature, linings for, P (6) 157*g*.
lanthanum, effect of impurities, (5) 129*h*.
La borate, refractive index and Abbe number of, (11) 304*f*.
lead, breaking strengths, (7) 184*d*.
lead borate, conducting, for solder, P (6) 157*h*.
NMR study of structure, (9) 241*a*.
thermal analysis during crystallization, (7) 185*c*.
lead-crystal, melting and production, (1) 7*i*.
PbO–B_2O_3–SO_3, properties of, (6) 156*j*.
lead silicate, mechanism of electric conduction in, (3) 67*h*.
lenses. See *Glass, optical*.
light scattered by, depolarized components of, III, (5) 128*i*.
Li borosilicate cerium activated, scintillation properties, (11) 304*j*.
Li-K silicate, effect of CaO on conductivity, (7) 184*d*.
Li_2O-containing, effect on properties of lithia ceramics, (8) 209*g*.
Li silicate, structural and electrical properties, (7) 185*j*.
for long-term storage of fission products, (10) 270*j*.
low-silica, as hard materials, P (3) 69*c*.
low temperature, IV, measurements of adhesion, firing, and soldering temperature, (10) 271*c*.
luminescent and phosphorescent, P (3) 69*d*.
MgO, structure and fluorescence of Mg phthalocyanine adsorbates on, (5) 130*f*.
Mg-Ca-aluminosilicate, effect of fluxing ingredients on properties of, (6) 156*h*.
-making, ancient techniques and history of, B (11) 321*c*.
British 17th century literature, (7) 185*a*.
of hollow glass, (1) 7*f*.
materials, DTA and TGA study of reactions between, III, (1) 5*h*; IV, (10) 269*j*.
use of metallic materials, (1) 5*j*.
Mn, decolorizing of, (6) 156*d*.
mantle, use in chemical processing, (3) 67*g*.
manufacturing process, P (3) 69*d*.
marking ink, composition, P (10) 272*b*.
mechanical strength, literature review, B (1) 31*h*.
mechanical strength studies, (3) 68*g*.
medieval, chemical composition and characteristics, (1) 7*g*.
melting, discussions from symposium on, (4) 98*c*.
effect of raw materials size on rate of, (3) 66*e*.
formation and growth of bubbles in, (11) 303*h*.
function of arsenious oxide, (1) 9*c*.
methods for increasing speed of, (3) 66*b*.
observation with controlled atmosphere hot stage microscope, I, II, (7) 184*g*.
reactions in red lead-potash-sand batch, (2) 40*e*.
or refining, electric furnace for, P (10) 271*j*.
selective oxygen enrichment for, (2) 41*f*.
-to-metal sealing. See *Seals and sealing*.
Microballoon, particles, for construction materials, (10) 270*j*.
microhardness measurements on, (6) 156*d*.
microheterogeneity, electron microscopy of, B (11) 320*j*.
microspheres, in $AlPO_4$ laminates, (9) 241*f*.
mirrors, continuous coating with Ag, P (4) 99*e*.
optical, P (3) 70*b*.
polishing defects in, (1) 9*a*.
protective backing for, P (4) 100*c*.
solution for treating, P (2) 43*d*.
molds. See *Molds*.
molten, corrosion of refractories by, (1) 5*j*.
in corrosion of zircon refractories, I, II, (1) 6*c*.
material for handling, P (3) 69*e*.
processes, P (7) 187*a*.
stirring test for evaluation of resistance of refractories to corrosion by, (2) 45*g*.
multilayer, effect of solar heat on opalescence, (1) 7*e*.
multilayer, electrically conductive, P (1) 11*e*.
museum, in Växjö, Sweden, (2) 33*i*.
National Productivity Year, importance of, (9) 241*j*.
natural, water minus in, (7) 185*d*.
Nd^{3+}, stimulated emission from, (8) 209*e*.
Nb_2O_5–Na_2O–SiO_2, dielectric properties of, (4) 98*a*.
nonsilicate, infrared transmission of, (7) 184*g*.
nucleation, mechanisms of, (1) 8*c*.
objects, apparatus for detecting streaks and latent defects in, (9) 239*f*.
old, preservation of, (1) 10*d*.
opal, MS14, spectrophotometry and photometry of, (5) 129*i*.
for packaging, (3) 67*b*.
-96% silica, P (2) 42*i*.
opaque, analytical determination of F in, (3) 65*j*.
optical, aspheric elements, P (3) 70*f*.
cemented, delaminating of, P (1) 12*c*.
composition, P (7) 186*g*.
containing silica and boric anhydride and La oxide and alkaline earth as modifiers, P (3) 70*b*.
crown, composition, P (11) 305*c*.
determination of specific heat by DTA, (10) 271*g*.
devitrification of, (11) 303*g*.
in heat resistant structure, P (10) 272*c*.
instrument, for group vision screening, (10) 271*h*.
fiber, method for shaping, P (1) 12*a*.
with high F and Ti content, P (4) 100*a*.
lens, bevel-edged, P (3) 69*d*.
lens, bifocal, method of making, P (4) 100*d*.
lens, cleaning apparatus, P (6) 157*f*.
lens, manufacture of, (9) 241*d*.

Glass, optical (*continued*)
lens, one piece multifocal, P (3) 70*g*.
lens, pressing of, (10) 271*a*.
lens, protection and cleaning, P (6) 158*e*.
mirrors, P (3) 70*b*.
spectral transmittance of, (5) 129*h*.
stable against devitrification, P (5) 131*c*.
striae in, I,II, (5) 130*b*.
studies of pot for melting, V,VI, (3) 73*c*.
study of surface by leaching with nitric acid, I, (8) 209*i*.
Th-free, P (6) 158*g*.
optical quality, method of controlling, (7) 185*j*.
oxide, high-pressure effects on, I,II, (11) 303*i*.
panels, acoustical, resin bonded fibrous, P (6) 156*j*.
large rectangular, strength and deflection under uniform pressure, (3) 68*b*.
prismatic light transmitting, P (4) 100*b*.
permeation of He through, (8) 209*h*.
pharmaceutical, consumer's viewpoint, (1) 8*g*.
phase, in ceramic bodies, solidification range of, (8) 229*h*.
-phenolic plastic composites, ablation studies, (1) 8*e*.
phosphate, in bearings, P (3) 69*c*.
with high-V content, electric properties of, (11) 310*d*.
molecularly dehydrated, for corrosion inhibition, P (3) 69*e*.
phosphorescent, method of making, P (6) 158*h*.
photosensitive, absorption bands of latent image centers in, (5) 128*f*.
photosensitive, coloring by X-radiation, (6) 156*a*.
pipe. See *Pipe*.
"pireksil," heat resistant, (1) 7*f*.
plant, for handmade ware, position of technologist in, (7) 185*c*.
in New Orleans, (6) 156*f*.
position of foreman, (1) 8*i*.
plastic coating of, P (10) 272*i*.
-plastic sandwiches, apparatus for pressing, P (11) 304*f*.
as plastics reinforcement, B (1) 32*c*.
plate. See also *Glass: flat, sheet, window*.
attaching metal channel to, P (10) 272*b*.
bedding for grinding and polishing, P (6) 157*f*.
infinite, tempering stresses in, (1) 9*h*.
inhomogeneous, optical path differences in, (10) 270*b*.
for portholes of undersea vessel, strength of, (1) 9*f*.
production in largest integrated plant, (4) 98*f*.
toughened, uses of, (1) 10*c*.
Pt alloy and, composite material, P (3) 77*d*.
polishing of. See *Grinding and polishing; Grinding and polishing apparatus*.
porous, raw materials, processing, and properties, (1) 8*h*.
portholes, for undersea vessel, strength of, (1) 9*f*.
K_2O–PbO–SiO_2–TiO_2, effect of TiO_2 on properties and relation to structure, (5) 129*f*.
pots. See *Glassmaking apparatus and equipment; Refractories*.
powder, heating to produce foamed glass, B (8) 231*i*.
powder, low melting, in precision glaze resistors, (10) 281*i*.
preparation of, P (3) 70*h*; P (10) 272*f*.
preservation of, (1) 10*d*.
pristine bulk, effect of heat treatment on strength, B (11) 320*h*.
properties, effect of thermomechanical history, (10) 270*g*.
properties, in system CaO–B_2O_3–Al_2O_3, I,II, (1) 8*j*.
protection from, grommeted jacket for, (11) 304*f*.
Pyrex, process and handling, (7) 194*i*.
quality, and quantity, effect of furnace operation on, (3) 66*b*.
quartz, P (2) 43*b*.
adhesives for, (5) 134*c*.
formation of color centers in by γ-radiation, (5) 129*e*.
quenched, internal stresses in, (10) 271*b*.
radiation sensitive, P (10) 273*a*.
with rare earth ions, absorption and emission characteristics, B (11) 320*j*.
reaction with water, I, II, (2) 40*a*.
ream knots, rapid analysis of, (8) 209*e*.
reboil, factors affecting, (3) 66*c*.
recrystallization, in Li metasilicate region of system Li_2O–Al_2O_3–SiO_2, (4) 98*g*.
red lead-potash-sand, reactions in batch during melting, (2) 40*e*.
refining, effect of small additions of sodium sulfate, (3) 66*j*.
modern process and installation, (1) 8*b*.
study of, II, correction of original paper, (8) 209*j*.
study of, III, (1) 9*c*.
reflection, for highway use, P (9) 240*e*.
reflectors, comparison of metal reflectors for locomotive head light, (11) 304*d*.
as reinforcement for articles, P (2) 43*a*; P (6) 157*c*.
research, at Ontario Research Foundation, (7) 184*e*.
resistance to alkali metal vapors, determination of, P (2) 38*a*.
resistance to detergents and detergent additives, (7) 185*h*.
rods, continuous spinning of glass from, P (2) 42*a*.
rods, spinning of glass from, P (2) 43*d*.
rolled, meter for measuring thickness without direct contact, (5) 129*d*.
roving, method of producing, P (3) 70*j*.
ruby, chemical potential of oxygen in, I, (2) 40*j*; (4) 99*a*; II,III, (3) 67*i*.
safety. See also *Glass, laminated*.

Glass, safety (*continued*)
for cars and airplanes, (7) 185*j*.
glazing unit, P (7) 187*a*.
goggles, cobalt glass for, P (2) 41*j*.
interlayers for, P (6) 157*e*.
laminated, pioneer producer, (9) 241*d*.
for vehicle windscreens, (1) 8*g*.
sand. See *Sands*.
schlieren, thermal and chemical, in crystal glass, (1) 9*b*.
scintillating, (11) 304*j*.
scintillation counter, composition, P (1) 11*j*.
sealing. See *Seals and sealing*.
semiconducting oxide, principle of preparation, B (11) 320*j*.
sheaths, as protection for fissionable fuel elements of nuclear reactors, P (3) 70*c*.
sheet. See also *Glass: flat, plate, window*.
bricks, or blocks, transparent, P (8) 211*e*.
bricks, or blocks, with variable transparency or color, P (8) 210*i*.
curved, laminated, method for treating, P (9) 242*j*.
drawing process, P (10) 272*j*.
equipment for transporting, P (6) 157*j*.
handling equipment for, P (8) 210*i*.
homogeneous batch for mechanical production, (8) 209*a*.
mat, silk screening for surface, (11) 304*e*.
matching, method of making, P (1) 12*d*.
method of treating, P (4) 100*f*.
multiple break sources in laths of, B (11) 320*i*.
tempered, P (7) 187*a*.
tongs for handling, P (8) 210*j*.
tongs for supporting, P (9) 242*h*.
ultrathin, flexible, P (9) 242*h*.
silica, diffusion of water in, tritiated water as tracer, (10) 270*c*.
GeO_2, and B_2O_3, densification in rigid state, (11) 303*i*.
Libyan Desert, terrestrial origin of, (1) 9*i*.
low-temperature excess specific heat of, (3) 67*e*.
96%, opal, P (2) 42*i*.
structure of, B (10) 300*e*.
thermal expansion behavior as function of thermal history, (6) 156*h*.
water in, (8) 210*a*.
silica-alumina, in electrical field, diffusion of protons in, (2) 38*h*.
silicate, borate, and phosphate, containing U, infrared spectra of, (9) 239*i*.
crystallization and composition, (9) 241*h*.
effect of Zr and Ti properties, (2) 38*j*.
information on structure from transport measurements, (3) 68*e*.
interpretation of infrared spectra, (3) 66*j*.
mechanism of chemical reaction with attacking agents, I-III, (4) 98*a*.
sensitive to sunlight, variable transmission in, (2) 41*h*.
structure in fracture surface, (4) 99*a*.
Yb-activated, stimulated emission of infrared radiation from, (5) 130*a*.
from silicates, P (2) 42*i*.
siliceous structures, coating prior to melting, P (3) 70*g*.
silver or copper deposition on, from solutions, P (6) 157*i*.
Ag- and Ti-containing, color of, (8) 208*h*.
sintered, raw materials, processing, and properties, (1) 8*h*.
slabs, for sound absorption, P (9) 242*d*.
smelting, observation in high temperature microscope, (8) 209*j*.
soda aluminosilicate, properties of, III, (2) 40*g*.
soda-lime, effect of boric oxide on melting and refining of, (2) 41*g*.
fracture velocity in, (8) 209*i*.
in tableware, (2) 41*j*.
soda-lime-silica, beam-bending viscosity measurements, (4) 98*d*.
breaking strengths, (7) 184*d*.
effect of cations on Young's modulus of, (2) 38*j*.
equilibrium pH relation to chemical reactivity, (4) 98*c*.
fracture strength from −100° to 700°C, (10) 270*h*.
sodium aluminosilicate, Ni ion as indicator of structure, (3) 67*j*.
sodium borate, infrared spectra of, (8) 209*c*.
sodium borosilicate, orientational effect and shape birefringence, B (11) 321*b*.
sodium phosphate, iron in, relation of magnetic properties to coloring action, IV, (2) 41*d*.
Na-K, effect of CaO on conductivity, (7) 184*d*.
Na and K in, quantitative determination by X-ray diffraction, (2) 40*i*.
Na_2O–B_2O_3–SiO_2, physical and chemical properties, (6) 156*i*.
Na_2O–SiO_2, quantitative relationship between the ordered and disordered phases in, (6) 156*f*.
sodium silicate, effect of iron in sulfur-amber coloration in, (1) 9*i*.
formation of color centers in by γ-radiation, (5) 129*e*.
glass fibers from, (10) 270*c*.
molten, bonding to Pt, Au, Fe, and oxidized Fe, (2) 57*f*.
soft, with high electrical resistivity, P (6) 158*f*.
solder, for carbon to metal bonding, P (5) 130*e*.
internally nucleated devitrified, P (3) 69*b*.
method of making, P (6) 158*h*.
solubility of gases in, (3) 68*b*.
-solution interfaces, chemical equilibria, (4) 98*b*.
as solvent for ferric oxide, (9) 239*f*.
S 109, resistance to solarization, (11) 304*d*.
sorters, selection and training, (9) 241*j*.
specific heat of, I,II, (10) 271*g*.
spectacle blanks, rationalization of manufacture, (1) 8*d*.

Glass (*continued*)
spheres, hollow, acid treating of, P (3) 69*g*.
spheres, hollow, in lightweight structural unit, P (8) 210*j*.
spheroidal particles containing fissionable materials, P (6) 158*f*.
spinning, continuous, from rods, P (2) 42*a*.
spinning, from rods, P (2) 43*d*.
stability. See *Glass, chemical stability*.
stained, conservation of, (10) 265*j*.
contemporary, (10) 266*b*.
handblown decorative, (6) 156*j*.
medieval Swiss, historical, (6) 153*j*.
staining method, and material, P (6) 157*d*.
Standard No. 4, chemical analysis of, (2) 38*j*.
stopcock, assembly, P (9) 242*f*.
stopcock, for laboratory glassware, P (9) 242*g*.
strains in, effect on mechanical strength, (1) 7*c*.
strands, metallized flattened, P (9) 242*d*.
strength, effect of HF etching, (2) 39*a*.
effect of internal strains on, (1) 7*c*.
of hollow ware, (1) 6*g*.
mechanical, symposium on, B (1) 31*h*.
in undersea portholes, (1) 9*f*.
strengthening of, P (2) 43*a*.
stresses in, analysis of, P (1) 10*c*.
stresses, tempering, in infinite glass plate, (1) 9*h*.
striae, density and refractive index of, (5) 130*b*.
striae, surface tension of, (5) 130*d*.
structural, colored, wall panel, P (5) 130*f*.
structural unit, lightweight, of hollow spherical particles, P (8) 210*j*.
structure, direct electron microscope study of, (3) 66*i*.
experimental evidence for concept, (9) 240*h*.
of high Young's modulus glasses, I,II, (1) 9*c*.
information rom transport measurements, (3) 68*e*.
and infrared absorption, (1) 7*b*.
and infrared absorption, correction, (8) 209*b*.
phase diagrams in study of, (7) 185*c*.
rearrangement during heating, (2) 39*d*.
relation to dielectric properties of glasses in systems Bi_2O_3–CdO–SiO_2, Bi_2O_3–CdO–B_2O_3, and Bi_2O_3–CdO–GeO_2, (1) 6*i*.
of thin films, (2) 41*b*.
sulfate opal, method of making, P (6) 158*d*.
surfaces, electron microscope studies of, (1) 6*d*.
etched, development of defects on, (7) 184*j*.
as factor in good labeling, (9) 240*c*.
increase in chemical durability, (1) 5*g*.
leakage resistance, (11) 304*a*.
light-dispersing layers on, P (3) 69*c*.
producing light-diffusing layer on, P (2) 42*e*.
smooth, conference on nature of, B (1) 32*e*.
study by schlieren-optical instrument, (1) 9*a*.
texture, effect of metal roughness on, (3) 66*d*.
in vacuum apparatus, sorption of water on, (8) 209*d*.
symmetry and compressibility, pressure in study of, (9) 241*b*.
synthetic mica, kinetic studies of crystallization, (11) 317*j*.
in system CaO–B_2O_3–Al_2O_3, properties of, III, (3) 67*f*.
tableware, new plant, (2) 41*j*.
target, image orthicon, P (4) 100*a*.
for technical ware, properties of, (7) 185*h*.
technology, advances in, Part 2, B (11) 320*f*.
in Japan, (1) 7*c*.
"pathology" in, (1) 8*f*.
television tubes. See *Tubes*.
temperature, effect on ultraviolet absorption, (8) 208*j*.
temperature, pyrometers for measuring, (9) 239*e*.
tempering, thermoviscoelastic description, (1) 10*a*.
thermal stability, relation to structure, (7) 185*b*.
thin films, structure of, (2) 41*b*.
in three-phase coating, (1) 4*j*.
tile, enameled, manufacture of, (1) 7*j*.
TiO_2–Na_2O–SiO_2, dielectric properties of, (1) 6*b*.
Ti-containing, coloration of, (11) 303*f*.
toughened, production of, (1) 10*c*.
transition-metal ions in, ligand field theory and absorption spectra of, B (9) 263*j*.
transmission, calculation vs. thickness, (7) 184*e*.
transparency, variable, (1) 7*e*.
tubes. See *Tubes*.
ultraviolet transmitting, (11) 304*d*.
U-bearing, in silicate and phosphate systems, (1) 10*e*.
in vacuum techniques, B (2) 61*b*.
vanadia-silica, refractory behavior of, (2) 40*g*.
V, high-, preparation of ceramic semiconductors from, (11) 310*d*.
variable transmission in, (2) 41*h*.
as viscoelastic material, (1) 9*h*.
viscosity, apparatus for measuring at high temperatures, P (2) 41*f*.
effect in hot extrusion of metals, (1) 10*i*.
NBS sample, (1) 7*d*.
in range 10^8 to 10^{15} poises, evaluation of beam-bending method of determining, (4) 98*d*.
study with parallel-plate plastometer, (1) 10*j*.
theory of, (11) 304*b*.
volatilization of fluorine crowns in, (1) 10*a*.
volcanic. See *Volcanic glass*.
Vycor-type, raw materials, processing, and properties, (1) 8*h*.
wall thickness, control in blown articles, P (1) 12*b*.
ware, automatic loading machine for, P (11) 305*b*.
classification of, (7) 184*f*.
handblown, porous carbon molds for, (7) 184*j*.
import quotas, as solution for trade problems, (2) 40*a*.
increasing output of abrasive wheels for cutting, (7) 177*f*.
package construction for, P (3) 70*c*.
quality, symposium on control of, (9) 241*j*.

Glass, ware (*continued*)
removal of impurities from fluxing materials for, P (2) 56*a*.
resistance coating for, P (9) 242*b*.
volumetric, method of making, P (2) 43*c*.
water-repellent, P (6) 157*d*.
wicks, or threads, method of making, P (7) 186*h*.
window. See also *Glass: flat, sheet, plate*.
Bulgarian production, (1) 7*a*.
determination of variations in composition, (1) 7*h*.
γ-ray irradiated shielding, electric properties of, (2) 39*g*.
hand-fashioning processes, B (11) 321*b*.
windshield, safety glass for, (1) 8*g*.
wired, preparation of wire for, P (1) 12*a*.
wool. See *Glass, fibers*.
X-ray study of, (9) 241*d*.
Young's modulus. See *Glass, elasticity*.
Zn borate, in making synthetic mica, P (9) 249*b*.
Zn nucleation on, (9) 241*c*.
ZnO, structure and fluorescence of Mg phthalocyanine adsorbates on, (5) 130*f*.
ZnO-B_2O_3-SO_3, properties of, (6) 156*j*.
Glass industry, British, international trade in, (1) 31*g*.
in Bulgaria, (1) 7*a*.
Japanese, history of, B (11) 321*b*.
Japanese, technology in, (1) 7*c*.
nepheline syenite from North Cape for, (1) 25*j*.
oxygen for combustion and heating flames in, (2) 40*f*.
problem of Japanese-American relations in (2) 40*a*.
refractories for, (6) 160*f*; (10) 275*j*.
science and, (5) 129*f*.
science and technology in, (9) 258*c*.
selective oxygen enrichment for, (2) 41*f*.
in Smaland, Kosta Glassworks, I–III, (1) 7*c*.
standardization of cutting wheels in, (5) 129*j*.
Swedish, handblown glass, historical review, I,II, (7) 184*h*.
1962, (1) 9*g*.
window glass, 1927–1939, (1) 9*g*.
Glassmaking apparatus and equipment, for accurate photographic reproduction of eyeglass lenses, P (7) 185*g*.
for applying pressure to curved glass sheets, P (1) 11*c*.
for attenuating fibers, P (3) 68*d*.
automatic, for ware loading, P (11) 305*b*.
automatic, for working ends of long tubes, P (3) 69*c*.
batch feeder, as sintering chamber in glass tank furnaces, (1) 5*e*.
for bending glass, P (6) 157*j*.
for bending glass sheets, P (3) 68*e*; P (8) 210*c,d,e*; P (8) 211*h*; P (9) 242*a,b*.
with heat shield, P (4) 100*d*.
nonuniformly curved, P (4) 99*c*.
for blow molding hollow articles, P (9) 241*c*.
bobbins, apparatus for automatically loading and changing, P (5) 130*i*.
for breaking glass strands, P (3) 68*c*.
for casting resin-bonded fiber glass cone, P (5) 130*b*.
for cleaning glass sheets, P (5) 130*j*.
for cleaning small glass containers, P (4) 100*b*.
combustion chamber burner, for producing fibers, P (1) 11*a*.
for continuously gathering fibers, P (5) 131*c*.
for controlling formation of blown glass articles P (6) 157*a*.
crucible, for melting, P (2) 42*j*.
cutting machines, automotive, P (1) 11*a*.
for detecting imperfections in glass containers P (4) 99*c*.
for drawing, fibers, P (4) 99*b*; P (8) 210*e,g*.
glass rod and tubing, P (3) 68*i*.
sheet from molten glass, P (10) 272*a*.
for extruding glass, P (6) 157*a*.
for feeding, batch materials, P (6) 157*c*.
flat triangular sheets onto moving conveyor, P (11) 304*j*.
glass batch materials, P (5) 131*c*.
multifilament strand, P (4) 99*d*.
for finishing and mounting terminals on lamp bulbs, P (6) 157*d*.
for flame treating exterior surfaces of containers, P (1) 11*g*.
for forming, cased glassware, P (7) 186*c*.
and collecting filaments, P (9) 242*e*.
fibers, P (1) 11*g*; P (3) 68*h,j*; P (3) 70*a*; P (6) 157*e*; P (7) 185*g*; P (7) 186*g,i*; P (8) 211*b*.
filaments, P (3) 68*e*; P (3) 69*j*.
glass articles, P (5) 131*h*.
machine improvement, P (4) 99*i*.
multiple sheet glazing units, P (6) 158*b*.
multiple strands from single bushing, P (5) 131*i*.
and processing fibers, P (6) 158*b*.
products from resin-impregnated long fiber filaments, P (8) 210*g*.
profiled glass sheets, P (6) 157*d*.
strands of filaments, P (4) 100*c*.
furnaces. See *Furnaces*.
gaging, for bottles, P (5) 130*i*.
for gaging curvature of sheet material, P (1) 10*e*.
for gaging glassware diametrically, P (3) 68*g*.
gas burner for making glass fibers, P (1) 11*h*.
for gas plating of metal on glass fibers, P (10) 272*i*.
for grinding. See *Grinding and polishing apparatus*.
for handling, bottles, P (4) 99*j*.
containers, P (5) 130*h*.
glass sheet, P (10) 273*b*.
glassware articles, P (5) 130*a*.
glassware, P (10) 272*e*.

Glassmaking apparatus and equipment (*continued*)
hot articles, P (3) 68*g*.
hot deformable ware, P (3) 70*d*.
sheet material, P (4) 99*e*.
ware, P (7) 185*i*.
or heat conditioning and feeding heat-softenable materials, P (2) 42*b*.
for heating glass before delivery, P (7) 186*j*.
for homogenizing glass, P (1) 10*g*.
for inspecting, bottles, P (5) 130*d;* P (7) 186*e*
containers, P (4) 100*e;* P (11) 304*i*.
glassware, P (8) 210*h*.
optically, glass sheets, P (7) 186*a*.
jar washer, rotary, P (10) 273*b*.
lehrs, convection heated, effect and advantages in glass annealing, (1) 6*c*.
liquid fuel burner, for forming glass fibers, P (5) 131*b*.
for making, all-glass multiple sheet glazing units, P (6) 158*a*.
condensed filamentous mat, P (9) 242*e*.
fibrous glass mats, P (1) 10*f*.
filmed bent glass sheets, P (6) 158*d*.
glass beads, P (5) 131*d*.
mats of blown fibers, P (5) 130*b*.
multiple sheet glazing units, P (1) 10*j*.
multiple sheet glazing units, with access opening, P (1) 10*i*.
neck ring blanks on turret lathe, (4) 98*i*.
wicks or threads, P (7) 186*h*.
material for handling molten glass, P (3) 69*e*.
of medieval and Renaissance times, (3) 64*b*.
for melting and feeding glass materials, P (1) 11*h*.
melting pots, defects in, (1) 6*g*.
for metal coating glass filaments, P (5) 131*e*.
metallic materials in, (1) 5*j*.
metallizing of, (4) 98*e*.
molding machines, safety device for, P (3) 70*d*.
molds. See *Molds, glass.*
for packaging bottles with metal loops, P (5) 131*a*.
for packaging strands, P (1) 10*i*.
photoelectric, for inspection of ware, P (4) 100*b*.
photoelectric, for shape and height detection, P (9) 242*d*.
plastic glass breaker depositor, P (3) 70*c*.
plunger, for forming articles, P (2) 42*j;* P (6) 158*a*.
for polishing. See *Grinding and polishing apparatus.*
pot, for melting optical glasses, V,VI, (3) 73*e*.
for pressing, curved glass-plastic assemblies, P (9) 241*f*.
curved laminated safety glass, P (2) 41*i*.
glass-plastic sandwiches, P (11) 304*f*.
glass sheet and plastic assemblies, P (4) 99*e*.
or processing fiber glass materials, P (1) 11*i*.
for producing charges of molten glass, P (4) 99*f*.
for producing fibers from molten material, P (4) 99*g,h*.
quartz lamp sealing machine control, P (6) 158*e*.
for reconstituting fibrous material, P (2) 42*c*.
for reshaping cylindrical tubes, P (3) 69*a*.
rod and tube cutter, P (8) 210*g*.
for rupturing glass seals, P (1) 11*d*.
safety manostat for glassblower, P (1) 11*d*.
scoring machine, P (2) 42*i*.
setting up forming machine and sampling plan, (9) 241*a*.
for shaping edges of eye glasses, P (8) 211*a*.
for shaping mouth of vials, P (1) 10*j*.
shaping tools, with Ni-P alloy coating, P (4) 99*j*.
for shrinking tubular glass blank, P (9) 241*f*.
for snapping glass sheet, P (5) 131*a*.
for sorting balls, P (5) 131*f*.
spinnerette, with extrusion orifices, P (1) 12*e*.
stencil, for spraying cathodes, P (1) 10*j*.
submachine chambers for drawing sheet glass without a debiteuse, (7) 184*h*.
for supporting glass sheets, P (2) 41*i*.
for supporting optical elements, P (3) 70*b*.
with synchromesh drive system, P (10) 272*i*.
tongs, for gripping and supporting glass sheets, P (9) 241*f*.
tongs, for supporting glass sheets, P (9) 242*h*.
transfer and inspection, for glass jars, P (5) 130*j*.
transfer and invert-revert, mechanism, P (3) 70*g*.
for traverse of strand material, P (10) 272*j*.
tube feeding machine, P (4) 100*a*.
for tubes, partially automatic equipment, (1) 8*e*.
vertical washer for flat glass, P (10) 273*c*.
for withdrawing mandrels from tubes, P (3) 69*a*.

Glazes. See also *Decoration.*
as adsorbent of thermoplastic bond in porcelain, (7) 190*g*.
ash, in ceramics, (9) 245*i*.
automatic spraying on dinnerware, (5) 137*i*.
basic, for potters, (7) 178*a*.
on califal ceramics, (5) 125*j*.
celadon, for stoneware, (7) 177*i*.
on ceramic bodies, surface treatment, P (4) 104*d*.
for china, structure and calculation, (5) 134*b*.
colored, effect of combustion gases on, (2) 47*a*.
cone 010, (7) 177*j*.
containing Cu, reduction of, B (4) 124*c*.
containing zirconia, X-ray study of, B (4) 124*b*.
crazing of, cristobalite in preventing, (8) 218*c*.
defects, from automatic sprayer, avoiding of, (11) 309*c*.
with different stress degrees, effect on body strength, B (10) 300*c*.
effect of opacifiers on properties, (9) 245*i*.
effect of sulfur compounds on, (1) 25*e*.

Glazes (*continued*)
faulty brown, with metallic luster effect, (10) 278*i*.
fit, factors affecting, (4) 103*j*.
formation and elimination of bubbles, (6) 163*e*.
fusion, of, P (6) 155*e*.
for German pottery, (4) 95*i*.
hardness of, apparatus for determining, (3) 75*d*.
hard porcelain, zircon as opacifier, (10) 279*c*.
hot-stage microscope in study of melting, (3) 80*g*.
iron, effect of MgO on, (1) 18*d*.
lava, formulas for, (4) 95*i*.
lime-zinc, softening and melting process, (11) 309*g*.
majolica, Sb compounds as raw materials for, (4) 103*e*.
marbleized, method of producing, P (8) 218*d*.
mat, for Seger cone 05a, higher ZnO content, (10) 278*c*.
opaque, boron-calcium, for steatite, (11) 309*d*.
recrystallized, scattering coefficient, reflectivity, and covering power of, (3) 75*i*.
white ceramic, frit for, P (4) 104*b*.
organic binders and other additives for, (3) 75*e*.
over-, for decorated ceramic body, P (10) 279*b*.
porcelain, composition and properties, (7) 190*d*.
properties, control by eutectics, IV,V, (10) 278*g*.
raw, Naples yellow from, (7) 177*i*.
red and yellow, from uranium, (7) 178*a*.
salt, engobes for color in, (7) 177*j*.
salt, introduction to, (5) 125*j*.
sanitary ware, control of viscosity and fusibility in, (10) 278*d*.
semiconducting, for insulating bodies, P (3) 79*a*.
stain for, P (1) 18*i*.
Sr crackle, (1) 2*d*.
surface, study by light interference, (10) 278*f*.
suspensions, gel strength and Bingham concept, (3) 75*h*.
terra sigillata, preparation and firing, (7) 178*a*.
tin, defects with, (4) 103*g*.
for wall tile, I,II, (6) 163*c*.
yellow, fire-resistant, nontoxic, P (6) 155*e*.

Glazing units, double sheet, furnace for producing, P (11) 304*h*.
multiple sheet, P (8) 211*d*.
method and apparatus for making, P (6) 158*a,b*.
production by fusion bonding, P (10) 271*b*.
safety glass, P (7) 187*a*.

Gloss, of enamels, measurement by Meyer method, (8) 207*f*.

Glossaries. See *Nomenclature.*

Glycerol, adsorption by montmorillonite, (4) 107*b*.

Goethite, dehydration, disordered structure in (8) 227*c*.

Gold, acid, in acid etch process, history of, (10) 265*i*.
alloys, bond with porcelains, (7) 183*d*.
in decorating ceramics, history and current practice, (2) 54*d*.
films, in emitter cells, (5) 134*g*.
in light-transmitting, electrically conducting element, P (5) 136*i*.
liquid bright, in decoration of ceramic body, P (10) 279*b*.
plating, with spray guns, (10) 278*j*.

Goniometers, interference, P (8) 224*b*.

Grain boundaries, effect on diffusion-controlled processes in Al_2O_3, correction, (10) 292*d*.

Grain growth, in $Ca_{0.18}Zr_{0.84}O_{1.84}$, (11) 317*d*.
critical, of special low-carbon metals, (2) 36*f*.
effect of control during UO_2 sintering, (11) 307*d*.
of UO_2, (10) 293*i*.
of UO_2, effect of stoichiometry on rate, (10) 294*b*.

Grains. See *Particles.*

Granular materials. See also *Powders.*
apparatus for discharging, P (1) 23*e*.
apparatus for handling, P (5) 138*g*.
blender for, P (3) 80*a;* P (4) 106*i*.
in bulk, apparatus for sampling, (3) 81*b*.
bulk density determination in, (11) 308*c*.
characterization by quantitative attrition, (7) 195*h*.
classifier for, P (7) 197*g*.
drying of, P (2) 51*e;* P (5) 141*c*.
electrostatic separation, (8) 221*e*.
feeder for, P (4) 106*h*.
flow apparatus for separating, P (9) 250*b*.
flow through orifices, (11) 313*a*.
gravity actuated apparatus for weighing, P (9) 250*c*.
heating apparatus for, P (1) 3*c*.
measurement of bin loads by radiation indicators, (5) 138*d*.
mixer for, P (8) 222*a,d*.
moisture content, instrument for measuring, P (6) 168*i*.
moisture indicator for, P (9) 252*h*.
particle size control in, (1) 25*h*.
preheating apparatus, P (4) 110*c*.
rotary conveyor for, P (3) 80*a*.
separation in fluidized liquid medium, P (5) 141*a*.
sizing centrifugally, P (9) 250*e*.
supports for aerating, P (11) 312*f*.
transporting means with reciprocating blade, P (3) 80*b*.
uraniferous, of uniform particle size, P (10) 277*e*.

Granulation. See also *Crushing and grinding.*
dish, in chemical industry, (9) 250*a*.
of dust from cement kilns, (11) 302*f*.
of fine ceramic powder for pressing, (10) 284*j*.

Granulometry. See *Particle size.*

Graphite. See also *Carbon.*
adsorption of xenon and argon on, (4) 100*i*.
as aerospace material, (10) 288*g*.
article, oxidation-resistant, P (3) 74*i*.
bodies, coated, P (8) 215*h*.
carbide coatings for, (10) 268*h*.
channels, oxidation and heat transfer studies in, I–IV, (6) 160*d*.
coatings, conversion to carbides by vapor deposition, (8) 206*i,j*.
colloidal, for surface treatment of molds, (4) 99*a*.
corrosion resistance, (10) 298*d*.
crystals, analysis of dislocations in, B (9) 262*a*.
diamond-, equilibrium line from growth and graphitization of diamond, (4) 113*i*.
-diamond reaction, metal catalyzed, (5) 143*f*.
dislocation patterns in, (1) 27*i*.
galvanomagnetic de Haas-van Alphen type oscillations in, (4) 112*c*.
gaseous suspensions, as reactor coolant, (4) 101*e*.
high density, at high temperatures, sorption of xenon in, (4) 101*g*.
high-purity, method for producing, P (9) 244*f*.
impregnated with U, in nuclear reactor, P (5) 133*d*.
lattice defects, observation by moire patterns, (6) 174*c*.
low permeability, interdiffusion of gases at uniform pressure, (1) 28*a*.
low temperature irradiation and annealing effects in, (10) 294*g*.
materials, research and development on, (10) 276*e*.
mechanical properties of, B (3) 91*g*.
moderator structures, for nuclear reactors, P (8) 216*f*.
molded and pyrolytic, thermal conductivity of, (5) 146*j*.
multicarrier galvanomagnetic data for, analysis of, (3) 85*j*.
pile-irradiated, small angle X-ray scattering in, B (8) 233*j*.
plates, for providing reducing atmosphere for firing porcelain, (8) 218*a*.
polycrystalline and pyrolytic, for thermal protection, of rocket-motor structures, (10) 276*e*.
preparation and properties, (11) 314*h*.
properties for new uses, (6) 160*b*.
properties and uses, (6) 155*c*.
pyrolytic, in anisotropic heat-controlling body, P (10) 276*i*.
characteristics and properties, (1) 25*j*.
Ettingshausen cooling in, (10) 280*j*.
evaluation for use in rocket nozzles, (4) 97*c*.
manufacturing methods and residual stress problem, (10) 275*i*.
for reentry applications, (10) 275*h*.
refractory metal alloys of, (8) 212*j*.
as thermal protection for fluorine-hydrogen thrust chambers, (4) 102*a*.
radiation damage, (8) 214*g*.
dark field electron microscopy in, B (8) 233*e*.
electron microscopy of, B (8) 233*g*.
reactions of H_2 with, (8) 214*d*.
reactor, Oak Ridge, stored energy in, (10) 276*j*.
in reactors, P (8) 216*j*.
shaped article, P (9) 245*f*.
single crystal, energy loss of electrons passing through, (6) 173*c*.
single crystals, magnetic field dependence of Hall effect and magnetoresistance in, (4) 115*f*.
spheres, irradiated alumina-coated UO_2 particles dispersed in, (8) 213*j*.
strain in, effect of irradiation, B (8) 233*g*.
surfaces, joining methods, P (10) 269*e*.
surfaces, protection of, P (4) 103*a*.
survey of forms and properties, (6) 159*f*.
X-flow polybloc system of construction, (5) 140*j*.
ZrC in, Young's modulus of, (4) 101*b*.

Greases. See *Lubricants.*

Grinding (size reduction). See *Crushing and grinding.*

Grinding and polishing. See also *Abrasives.*
ability of corundum, mullite, and spinel crystals, (1) 1*i*.
of aspheric surfaces, P (1) 10*h*.
of cement clinker, preparation for, (2) 35*c*.
chemical, techniques for Al_2O_3 single crystals, (6) 167*h*.
chemical, of UO_2, (11) 312*j*.
composition, P (6) 153*g*.
compositions, method of making, P (1) 1*g*.
defects, in mirror glasses, (1) 9*a*.
diamond grit for, (6) 153*e*.
effect on luminescent properties of tungstate phosphors, (5) 134*d*.
electro-, of semiconductor surfaces, P (5) 137*c*.
of glass, with diamond, (6) 156*b*.
improved method, P (1) 11*a*.
with nonfoaming oiliness agent, P (3) 69*i*.
plates, method of bedding, P (6) 157*f*.
rotary disk and felt pad for, P (4) 99*j*.
roundtable on, Brussels 1960, B (1) 32*e*.
study of morphological processes by electron microscope, (3) 67*d*.
study of polishing lines, (8) 209*i*.
by ultrasonics, (7) 185*e*.
of lenses for eyeglasses, (7) 184*f*.
polishing material, P (4) 95*g;* P (10) 265*g*.
surface, basics of, (3) 79*d*.
techniques, for alumina radomes, (3) 63*g*.
techniques, for UO_2 to minimize stresses in, (11) 306*d*.
wet surface, of carbides, with Man-Made diamond wheels, (11) 301*e*.

Grinding and polishing apparatus. See also *Abrasives,*
automatic, for glass, I,II, (8) 208*e*.
diamond, device, P (10) 265*f*.
for facets of precious stones, P (5) 125*g*.
with fine cushiony surfaces, method of making, P (9) 236*d*.
for glass, P (5) 131*a*.
for green ceramic insulators, (10) 265*g*.
polytetrafluorethylene laps impregnated with diamond for preparation of ferrites for metallographic study, (1) 19*b*.
rotary, for brush polishing glassware, P (8) 210*h*.
for spectacle glasses, P (1) 11*e*.
ultrasonic lapping, P (10) 285*g*.
wheel, with brown alumina grains, firing schedules for, (9) 235*f*.
commercial abrasive, measured properties of, (6) 153*g*.
cut-off, P (4) 95*g*.
for cutting glassware, increasing output, (7) 177*f*.
diamond, composition, P (8) 203*h*.
diamond, film for recording reactions in structure, (3) 63*f*.
diamond cut-off, P (3) 63*g*.
diamond substitute for truing, P (2) 33*f*.
electrically conductive organic bonded, P (3) 63*g*.
graphs showing sfpm produced, (9) 235*i*.
history and production, (9) 235*i*.
industry, potential of, (8) 203*e*.
internal, performance test of, I, (8) 203*f*.
with layers of fiber glass fabric, P (7) 177*f*.
magnetic abrasive, production and use, P (9) 236*c*.
Man-Made diamond, in grinding carbides, (11) 301*e*.
manufacture and bonding of, (9) 235*f*.
nonvolatile resin in, P (5) 125*f*.
radius dressing, I,II, (9) 236*b*.
resinoid bonded for wet applications, (5) 125*f*.
static and dynamic balancing arrangement for, P (10) 265*f*.
types needed for abrasive machining, (5) 125*h*.
with unsaturated organic polymeric bonds, P (10) 265*g*.
use of SiC papers and diamond paste, (8) 228*i*.
vitrified, with bonds of Aotsuchi, feldspar, and Toseki, (9) 236*b*.

Grog, calcining kilns, rotary, automatic control of, (7) 194*h*.
mullite, synthetic, (1) 15*b*.
particle size, effect on properties of sanitary ware, (1) 17*i*.
particle size distribution, relation to flow property of clay-grog mixtures and physical properties of body, (3) 73*f*.

Grout. See *Mortars.*

Guns. See also *Spraying.*
for atomization and electrostatic spraying of materials, P (5) 138*h*.
electron, cathode-ceramic assembly for, P (8) 220*f*.
electron, supplementary, use in electron-diffraction reflection, (7) 195*e*.
pneumatic, operating variables affecting castable refractories, (6) 160*a*.
pneumatic, for placement of refractory castables, I, (10) 275*d*.
spray, concrete for application by, P (10) 277*e*.
with fixed electrostatic head, P (8) 222*b*.
for gold plating, (10) 278*j*.
with laterally deflecting air cap, for molten material, P (8) 208*a*.

Gypsum. See also *Plaster.*
anhydrite, effect on portland cement properties, (7) 179*i*.
aqueous compositions, retardation of set time, P (2) 36*a*.
artificial, P (2) 36*a*.
ASTM standard for, B (9) 259*a*.
Blaine specific surface area, determination, (5) 138*j*.
board, forming machine, P (7) 182*g*.
board, manufacture of, P (1) 3*e*.
by-product, from phosphoric acid manufacture, quality test of, (2) 35*d*.
calcination, for plaster of Paris, (9) 237*b*.
calcination, process, P (7) 182*i*.
crystal habit, modification with ferric ion, (9) 236*j*.
crystals, effect of F on growth, (5) 126*f*.
and dehydration products, simultaneous DTA and TGA, (11) 302*b*.
effect on early stages of paste hydration of cement compounds, (1) 3*e*.
effect on properties of portland blast-furnace slag cement, (7) 179*f*.
in glass, (7) 184*f*.
glass reinforced, P (3) 65*b*.
and gypsum products, 1961, (3) 82*e*.
hardening, control by multicomponent admixtures, (10) 266*i*.
hemihydrate, metastability in mixed acids, (2) 35*f*.
-like products, composition of, P (10) 268*d*.
in portland cement, DTA determination of forms of, (7) 179*e*.
precipitated, twinned crystals, (9) 257*d*.
setting of, topochemical hydration processes, (5) 126*i*.
solution with $Ca(OH)_2$, reaction of allophane with, (7) 181*f*.
transformation, effect of time and temperature, (6) 154*f*.
vacuum mixers, P (10) 268*c*.

Gyrolite, synthesis and crystal chemistry, (5) 146*f*.

Hafnium, oxide, diffusionless phase transformations in, (10) 291*g*.
systems. See *Systems.*
in zircon, determination with Zr by paper chromatography, (5) 142*f*.

Halides, alkali, crystals, theory of β band in, (4) 121*h*.
effect of dislocations on diffusion kinetics in, (10) 294*d*.
effect of ionizing radiations, B (9) 259*i*.
excitation of electroluminescence in, (6) 163*j*.
formation of interstitials and vacancies in, (10) 293*d*.
optical absorption by *F* centers in, (4) 117*c*.
gaseous alkali, thermodynamic properties of, (1) 30*i*.

Hall effect, in ferromagnetic substances, theory of, (3) 89*j*.
in point-by-point measurement of magnetic fields, (9) 246*j*.
of transition metal diborides, (11) 317*f*.

Halloysite, formation as result of differential weathering of volcanic ash and pumice, (6) 169*i*.
hydrated, cation-exchange capacity and formation of halloysite-salt complexes, (11) 316*b*.
identification of, (4) 112*d*.
strange mineral, (3) 82*c*.

Handbooks, laboratory, of rheology, B (10) 300*e*.
quality control, revised and enlarged, (6) 176*i*.
reactor, Vol. III, Part B, B (10) 299*j*.
shock and vibration, Vols. I–III, B (5) 151*c*.
on thin-layer chromatography, B (8) 234*j*.

Hardening, of blanks for smelter blocks with glass-containing ground slag, P (3) 74*a*.
of cement, acceleration by crystallization nuclei, P (3) 64*h*.
dispersion, of uranium metal, P (5) 133*e*.
of gypsum, control by multicomponent admixtures, (10) 266*i*.
of mica deposited by electrophoresis, P (4) 110*i*.

Hardness, abrasive, of diamonds, relation to structure, (9) 235*j*.
of abrasive materials, machine for testing, P (4) 108*e*.
of asbestos-cement sheets, (8) 205*a*.
of ceramic tools at high temperature, (1) 1*f*.
concrete, effect of surface-active agent, (1) 2*f*.
of glass, increasing of, (7) 185*e*.
of glazes, apparatus for determining, (3) 75*d*.
micro-, measurements on transparent substances, direct measurement of elastic recovery of indentation marks, (6) 167*i*.
micro-, preparing glass for measurement, (6) 156*d*.
pyramidal impressions on glass, creation and stability, B (11) 320*j*.
Shore, of alumina silica refractories, relation to apparent porosity and abrasion resistance, (1) 15*d*.
uniform, in sintered MgO, P (4) 103*d*.

Health. See also *Air, pollution; Dusts; Safety; Silicosis.*
antibody production by quartz and BeO, (2) 60*d*.
bagassosis and silicosis, in Philippine mining company, (11) 320*d*.
chronic shortness of breath, aerosol therapy for, (3) 90*c*.
damage by use of ammonia, (7) 202*b*.
effect of asbestos on, (2) 60*g*.
effect of F compounds on, (8) 230*g*.
effect of glass dust on, (2) 60*c*.
eyesight, instrument for checking, (10) 271*h*.
hygiene characteristics of mica dust, (2) 60*f*.
industrial hygiene design in raw materials handling systems, (9) 258*f*.
methyl Cellosolve intoxication, (9) 258*a*.
of porcelain workers, effect on iron deposits, (2) 60*e*.

Heat. See also *Conductivity, thermal; Temperature.*
capacity, of Cu ferrite, (7) 200*c*.
of glass, I,II, (10) 271*g*.
of Fe disulfide, Fe diselenide, and Ni diselenide, from 5° to 350°K, (1) 27*j*.
low-temperature, of crystalline lead metasilicate, lead orthosilicate, and cadmium metasilicate, (2) 57*g*.
low-temperature, of pure and reduced rutile, (3) 87*i*.
low-temperature excess, of SiO_2 glass, (3) 67*e*.
low-temperature, of zinc ferrites, (10) 294*f*.
of refractory materials, (3) 73*d*.
conductor, BN as, (10) 273*i*.
content, and capacity, of crystalline B from 298° to 1700°K, (1) 28*b*.
of SeO_2 formation, (5) 143*i*.
of TeO_2 formation, (4) 113*h*.
from 0° to 1500°K, ice calorimeter for precise measurement, (1) 23*i*.
-controlling body, anisotropic, P (10) 276*i*.
effect on refractory and insulating concretes, (8) 204*e*.
engineering, charts for air heated enclosures, (4) 106*e*.
evolution, tests, with Ca aluminate binders and castables, (10) 274*j*.
exchanger, of cellular Pyroceram, (6) 169*b*.
in furnaces for sintering magnesite, dolomite, or cement, P (4) 108*g*.
and method, P (5) 140*e*.
multistage, graphical method for determining performance, (2) 53*j*.
multistage, optimum economic size for, (3) 81*j*.
shaft counterflow, for rotary cement kiln, (11) 301*j*.
of formation, of GeO_2, (1) 28*c*.
of formation, of transition metal carbides, (6) 175*i*.

Heat (*continued*)
of hydration, of rapid-hardening portland cement, formula for estimating, (8) 205*d*.
infrared and radiant, in porcelain steel company, (8) 207*c*.
processes, colored wax or resin indicator for, P (8) 224*b*.
protection, of satellites, materials for, (1) 7*g*.
quantities, measurement and control, (5) 140*e*.
of reaction, methods of determination by DTA, (6) 167*i*.
-resistant structure, optical glass in, P (10) 272*c*.
responsive devices, apparatus for testing, P (4) 108*c*.
setting, of binder of fibrous masses, P (10) 272*d*.
shields, for reentry vehicles, ceramic materials in, (4) 97*a*.
sinks, for quartz crystal oscillators, P (4) 105*e*.
of solution, of solids in molten reciprocal salt systems, (10) 293*j*.
supplying to grinding mills, P (6) 171*a*.
thermionic conversion to electrical energy, ThC_2 in, (10) 279*g*.
transfer, in fluidized beds, (1) 22*j*.
in multicomponent gases, hypersonic environment, (10) 294*b*.
in resin-impregnated porous ceramics, (9) 243*i*.
solutions for problems of, (1) 19*d*.
studies in graphite channels, I-IV, (6) 160*d*.
transient, from ceramic fuel pins, (4) 102*b*.
of transformation of Se modifications, (5) 143*i*.
treatment, effect on breaking strength of glass, (10) 270*e*.
effect on sintered CdS photoconductive films, (5) 143*a*.
of oxide glasses, effect on densification in rigid state, (11) 304*a*.
waste, recovery to reduce glass tank operating cost, (3) 67*h*.

Heat conductivity. See *Conductivity, thermal.*

Heaters, air, for blast furnaces, refractories for, P (3) 74*h*.
for cement powder or granular materials, P (1) 3*c*.
electric, with plate-clamping reflector, P (3) 69*g*.
electrically insulated, P (1) 18*h*.
for multilayer films, P (9) 249*b*.
water, corrosion testing of enamels for, (2) 36*e*.
glass lining requirements for, (5) 127*j*.
powdered ground coat enamels for, (4) 97*f*.
world's largest furnace for, (5) 128*d*.

Heating, of body for hot forming, Perio-Kontinu process, (3) 79*e*.
cyclic, in destabilization of ZrO_2, (11) 305*i*.
of kaolinite, effect on physical properties, (3) 82*d*.
pre-, of finely divided material, apparatus for, P (4) 110*c*.
radiation, thermal shock by, (7) 189*d*.
schedule, of tunnel driers, automating of, (6) 167*a*.
stage, for X-ray diffractometer, (6) 168*d*.

Heating elements. See also *Electrodes.*
electric, ceramic bodies for dry pressing, P (6) 165*i*.
of high positive specific resistance, (5) 140*f*.
resistance, for vacuum furnaces, P (2) 54*a*.
SiC resistance, P (10) 278*a*.
sintered electric resistance, methods of producing, P (1) 17*d*.

Heavy clay industry. See *Structural clay industry.*

Helium, permeation through glass, (8) 209*h*.

Hematite. See also *Iron, oxide, α-.*
crystal structure change of γ- to α-, (6) 176*a*.
screw dislocation movement in, (8) 229*a*.
single-crystal, extinction coefficient in region 3600 to 7000 A, (5) 143*d*.
systems. See *Systems.*
vibration spectra in infrared region, (5) 147*c*.

Hemimorphite, dehydration of, (8) 227*e*.

Hercynite, in sand marks on steel, (6) 159*h*.

History, of glass apparatus and instrument industry, (4) 98*i*.

Holmium, as dope for CaF_2 in maser material, (7) 191*b*.

Homogenization, of molten glass, strioscopic apparatus for study of degree of, (8) 209*d*.

Hot tops. See *Refractories.*

Humidity. See also *Moisture; Water.*
sensors, (9) 251*e*.

Humidostat, feeler element for, P (2) 53*b*.

Humus, effect on porcelain green strength, (10) 278*e*.

Huntite, synthetic borates isostructural with, (6) 170*f*.

Hydrargillite. See *Gibbsite.*

Hydration, of anhydrite, mechanical phenomena in, (8) 206*d*.
of cement, chemistry of, B (5) 148*i*.
paste, dielectric study, (7) 179*g*.
paste, early stages, (8) 206*b*.
and components, (8) 205*h*.
of dicalcium silicate, (7) 180*i*.
of gypsum plaster, mechanism of, III, (10) 267*e*.
heat of. See *Heat.*
paste, of cement compounds, early stages, I, (1) 3*e*; II, (6) 154*c*; comment on, (10) 266*h*.
of portland cement, induction period in, (5) 126*e*.
processes, topochemical, in setting of gypsum, (5) 126*i*.
products, of Ca silicates of cements, composition and structure, (1) 2*g*.
of tricalcium silicate, effect of mixing water content and alkalis, (7) 180*g*.
of tricalcium silicate solid solution in portland cement, effect of alkali in clinker, (11) 302*c*.

Hydration (*continued*)
volume change of cement paste during, (7) 182*d*.
Hydrides, transition metal, nonstoichiometry and lattice defects in, B (9) 260*a*.
Hydrocarbons, C_4, as gaseous fuels for firing porcelain, (3) 81*j*.
industrial aromatic, ASTM standard for, B (9) 259*b*.
Hydrochloric acid, in cleaning of borosilicate glass, (9) 239*h*.
as means of transport of TiN in Mo tube, (6) 172*d*.
processes, in production of Al_2O_3 from clay, (6) 170*c*.
rate of solution of glass fiber in, (10) 270*f*.
Hydrofluoric acid, etching, effect on strength of glasses, (2) 39*a*.
mechanism for solution of ground quartz powders in, (10) 295*g*.
in mineral separation, (4) 107*b*.
Hydrogen, in α-quartz, (5) 144*d*.
atoms, recombination on borosilicate glass and fused quartz, (9) 240*g*.
defects, in glass-coated steel, effect of moisture in furnace atmosphere, P (1) 4*c*.
fluoride, production, P (8) 226*b*.
formation of spinel in, at medium pressures and in vacuum, (1) 29*e*.
impurity, in α-quartz crystals, occurrence and properties, (4) 114*e*.
ions, exchangeable, in kaolinite and montmorillonite, (4) 115*d*.
molecular, in reduction of copper oxides, (4) 120*b*.
-montmorillonite suspensions, chemical stability of, (3) 86*a*.
positions, in $Ca(OH)_2$, determination by nuclear magnetic resonance, (7) 199*a*.
reduction, of low-surface area UO_2, (10) 293*f*.
reduction, of solid NiO-CoO-MgO solutions, (10) 293*h*.
sulfide, in preparation of US and ThS, (6) 160*d*.
systems. See *Systems*.
Hydrogen ion concentration, as criterion for evaluation of foundry sand mixtures, (8) 213*a*.
equilibrium, of Na_2O-CaO-SiO_2 glasses, relation with chemical reactivity, (4) 98*c*.
of suspensions of clay mineral containing raw materials, (4) 117*j*.
Hydrolysis, of albite solutions, (7) 199*c*.
homogeneous, in preparation of γ-(Al,Cr)OOH and H(Cr,Al)O_2, (7) 199*h*.
of La and Ce carbides, (1) 28*c*.
properties, of UC and UC_2, (10) 293*j*.
of thorium carbide, (1) 28*f*.
of titanium(III), (1) 28*g*.
of U carbides between 25° and 100°, I, (1) 28*h*.
Hydrophobation, of shaped glass parts, P (6) 157*d*.
Hydrophones, piezoelectric ceramics for, (2) 48*a*.
Hydrothermal synthesis. See *Synthesis*.
Hydroxides, double, formation of and titration of clays, (10) 293*a*.
Hygrometers, electrical, P (7) 196*c*.
elements, P (2) 53*d*.
for measuring moisture content of materials with very high ohmic values, P (2) 53*d*.

Ice, properties, processes, and applications, B (11) 321*h*.
Illumination, intensity, of light from locomotive head light with metal reflector, (11) 304*d*.
Ilmenite, chlorination, in rutile production, (7) 197*j*.
systems. See *Systems*.
Immiscibility, liquid, in system BaO-SiO_2, B (11) 320*h*.
Impact, Griffith flaws produced by, B (11) 320*g*.
resistance, of asbestos-cement sheets, (8) 205*a*
test, of porcelain plates, (9) 246*a*.
testing, of cylindrical ceramic rods, (9) 256*h*.
use of gray iron under, (4) 97*j*.
Impedance, changes, induced by photoconductive effect in ZnS:Cu,Cl phosphors, (1) 19*h*.
Impregnation, of cellular material, by implosion, P (9) 250*d*.
of slip-cast fused SiO_2, (8) 213*f*.
Impurities, role in radiation effects in ionic solids, (11) 319*b*.
Indexes, of selected property values in physical chemistry and thermodynamics, B (4) 122*h*.
Index of refraction. See *Refractive index*.
Indium, antimonide, transistor, P (11) 311*h*.
phosphide, high purity, P (6) 166*c*.
Infiltration, of metals. See *Impregnation*.
Infrared, far-, properties, of quartz and sapphire, (4) 114*b*.
optical constants of MgO in, (9) 256*d*.
properties, of sapphire at high temperatures, (4) 114*g*.
radiation. See *Radiation*.
transmittance, and reflectance, of BeO, (4) 114*h*.
Infrared absorption. See *Absorption*.
Infrared spectra. See *Spectra*.
Ink, glass marking, P (10) 272*b*.
Inorganic compounds, structural principles in, B (5) 151*d*.
Inspection. See *Quality control*.
Instrumentation. See also *Controls*.
automatic electronic, in bottom lift kiln for firing special refractory shapes, (10) 287*g*.
for control of heat quantities, (5) 140*e*.
of glass tank furnaces, (8) 208*h*.
process, in cement industry, (5) 126*g*.
of regenerative furnaces in British glass industry, (3) 66*h*.
of rotary kilns, (5) 126*j*.
for temperature control of tunnel kilns, (6) 169*b*.

Instruments. See also specific types.
automatic, for measuring specific surface of powders, (8) 222*g*.
recorder, for particle size distribution determined by sedimentation, (8) 222*h*.
for recording of attenuation data, (9) 257*f*.
recording, for X-ray diffraction patterns, P (1) 23*j*.
Blaine apparatus, for measurement of specific surface, (4) 116*h*.
ferroelectric bolometer, with Pb–Sr titanate ceramic element, (6) 164*h*.
gas meter, for low flow rates, (5) 139*c*.
glass, for gas analysis, (2) 39*d*.
for gas pressure measurements, (1) 6*i*.
graphic symbols for, (5) 139*c*.
hydrostatic tester, for determining tensile strength of brittle materials, (4) 108*a*.
maintenance, for centrally controlled cement plants, (10) 267*d*.
for measuring ac voltage on true rms basis, (7) 196*a*.
microsyringe, for gas chromatography, P (11) 320*b*.
permeameter, "variable volume-decay rate," with restricted outflow, (3) 81*h*.
plastometer, parallel-plate, in study of glass viscosity, (1) 10*j*.
pressure-box type, for measuring rain penetration of brickwork, (3) 71*c*.
programmer-integrator, for chromatographic analyzer, P (1) 24*e*.
recorder, for densitometer, P (11) 320*b*.
Rotoscribe, for recording rotary kiln shell positions, (9) 253*c*.
schlieren-optical, for study of glass surfaces, (1) 9*a*.
for specimen identification, P (3) 89*j*.
strain bridge, direct current, (3) 80*i*.
strioscopic, for study of homogenization of molten glass, (8) 209*d*.
tetrahedral anvil, in tests of high pressures on glass, (8) 208*f*.
Insulation, acoustical, ASTM standard for, B (9) 259*b*.
compressed resin bonded fibrous glass panel, P (6) 156*j*.
panel, construction, P (8) 218*a*.
Insulation, electrical. See also *Dielectrics; Glass; Porcelain*.
coating, of MgO dispersed in aqueous solution of CaO, P (8) 220*g*.
for coil for aircraft generator, alumina coating as, (7) 183*e*.
composite, molecular behavior, (3) 76*e*.
developments in, report and bibliography, (3) 76*b*.
fibrous inorganic, or potted electrical members, P (9) 248*j*.
of glass flakes, P (3) 69*h*.
of glasslike ferromagnetic materials, P (4) 105*i*.
for heating units, P (1) 18*h*.
light-transmitting, with electrically conducting coating, P (5) 136*i*.
semiconducting ceramic glazes for, P (3) 79*a*.
solid inorganic, for metallic conductors, P (2) 38*c*.
tape, high temperature, P (7) 190*h*.
Insulation, thermal. See also *Glass, fibers; Mineral wool; Refractories, insulating*.
ASTM standard for, B (9) 259*b*.
board, composition, P (10) 277*b*.
ceramic, injection molding of, (2) 47*d*.
chamber construction, P (6) 162*d*.
composition with inorganic filler, P (7) 186*b*.
computed errors for square guarded hotplate for measurement of thermal conductivity of, (3) 72*a*.
construction, P (8) 208*c*.
costs for process vessels, (8) 221*g*.
cryogenic and high temperature, materials for, B (2) 61*f*.
of diatomaceous silica, (2) 34*b*.
fused silica ceramics for, (1) 4*f*.
handleable shapes, P (2) 45*g*.
heat loss data for, (9) 250*j*.
high temperature, for pipe, P (1) 16*e*.
low density high temperature, (8) 213*j*.
method for making, P (11) 308*j*.
mica brick, factors affecting properties, (3) 72*c*.
multipane glass as, P (10) 272*j*.
particular, lightweight ceramic materials as, (6) 158*j*.
refractory fibers for, (6) 160*c*.
Insulators, electrical, BN as, (10) 273*i*.
constructions, P (10) 279*c*.
ferrite isolator, using aligned crystals with specific anisotropy constant, P (11) 311*c*.
green ceramic, machine for grinding, (10) 265*g*.
high frequency, alumina porcelain as, II, effect of metal oxides, (1) 17*h*.
high frequency, forsterite porcelain as, XI, (1) 18*a*.
mechanization of production, (10) 281*b*.
pinhole-free film of, vacuum evaporation deposition, (11) 311*j*.
porcelain, strength-determining factors, B (10) 300*c*.
suspension, with core and envelope, P (5) 137*c*.
suspension, with improved pin, P (2) 47*e*.
wet-shaped, device for sponging, P (4) 104*a*.
Interferometers, with diffraction grating, P (9) 252*f*.
Michelson and polarization, comparative studies of optical path difference measurement with, (10) 270*b*.
in study of pressure effects, (4) 107*d*.
in studies on synthetic diamonds, (3) 87*g*.
Interferometry, of domain structure in $BaTiO_3$, (7) 191*d*.

Interferometry (*continued*)
in measurement of indented contour in glass, (2) 39*e*.
polarization, in incident-light microscopy for material testing, (11) 313*b*.
Intermetallic compounds, selection and fabrication, (6) 161*c*.
sputtered SiO_2 films as mask for, (9) 248*d*.
Iodides, alkali, γ and photoluminescence of, (5) 135*a*.
Iodine, introducing into lamp envelope, P (3) 70*d*.
occlusion in porous crystals, I, II, (10) 295*h*.
Ionization, in hydrothermal fluids, (6) 173*g*.
photo-, of Ce^{3+} in glass, (3) 67*b*.
vacuum measurement by, (7) 196*d*.
Ions. See also *Cations*.
adsorption, determination by radioactive tracer technique, III, (3) 86*d*.
complex, in molten salts, galvanostatic study, (10) 291*c*.
emission, materials, for energy converters, B (3) 92*g*.
exchange, B (3) 91*e*.
capacity, X-ray spectrographic measurement, (6) 168*g*.
chromatographic process, in isolation of Y compounds, (11) 315*d*.
of clay from Kerala State, (6) 170*c*.
in crystals, (4) 120*a*.
effect on shale, (3) 82*c*.
of phosphorus in Manitoba soils, (5) 140*h*.
role in slip casting, (7) 190*f*.
in separating rare earths and Y, P (2) 60*a*.
exchangeable, significance for formation of skeleton of thixotropic gels, (3) 88*c*.
exchangers, for separation of rare earths (5) 145*i*.
foreign, effect on valence of coloring elements, (9) 238*i*.
function in structure of high Young's modulus glasses, (1) 9*c*.
impurities, removal from calcined alumina, P (5) 141*d*.
Iron. See also *Enameling metals; Steel*.
alcoholate, in magnetic ferrite films, P (10) 282*g*.
alloy with Y or Gd for ferromagnetic oxide, P (6) 166*a*.
α-Fe_2O_3 whiskers, growth on pure iron in oxygen, (6) 173*f*.
basic pig, dolomite in production of, (10) 268*b*.
-C compacts, effect of atmosphere on sintering, (7) 200*b*.
cast, black enamel for direct application, (8) 206*g*.
effect of impurities in relation to metal diffusion, (4) 98*b*.
enameling, clear primer for, P (6) 155*d*.
for glass container molds, (3) 65*j*.
-containing materials, removal from sand, P (3) 85*c*.
difluoride, crystal-structure determination, (10) 296*h*.
ductile, enameled, P (2) 38*a*.
electromagnetic removal from ceramic powders in free fall, P (3) 83*g*.
in ferromagnesian silicate minerals, magnetic susceptibility as measure of, (4) 116*e*.
ferrous, article, coating process, P (8) 208*b*.
materials, coating process for, P (5) 128*b*.
semimicrovolumetric determination in nonrefractory silicate minerals, (11) 313*g*.
γ-Fe_2O_3, as cause of luster effect in brown glazes, (10) 278*i*.
γ-Fe_2O_3, magnetic structure and vacancy distribution by neutron diffraction, (3) 87*d*.
γ-iron(III) oxide, acicular, P (5) 141*b*.
gray, under impact, (4) 97*j*.
Fe^{2+}, quantifying in sintered Mn-Zn ferrites, (6) 164*f*.
Fe^{3+}, in modification of crystal habit of gypsum, (9) 236*j*.
Fe^{4+}, effect in system $SrFeO_3$–$SrTiO_3$, (7) 191*c*.
Fe_2O_3, flame spectrometric determination in aluminosilicates, (10) 286*d*.
liquid, reduction of SiO_2 and Al_2O_3 by C in, (1) 14*d*.
magnetic properties of, relation to coloring action in glass, III, (1) 9*i*; IV, (2) 41*d*.
making, oxygen process, I, II, (6) 160*j*.
making, use of high-alumina refractories in, (11) 306*g*.
in Mn ferrite, valence changes, (10) 297*g*.
molten, effect of elements in on SiO_2 reduction, (1) 14*f*.
molten high carbon, rate of reaction with silica or alumina crucible, (1) 14*a*.
nonmetallic inclusions in, electron microscope study of, I, (6) 155*j*.
oxide, as decolorizer for Mn glass, (6) 156*d*.
effect on fusion of nepheline syenite, (2) 54*h*.
effect in mullite solid solution, (11) 306*c*.
effect in phosphate glass, B (11) 320*h*.
effect on properties of $BaTiO_3$ single crystals, (6) 172*e*.
effect on refractories for checker-brick, (11) 305*f*.
effect on viscosity of B and B-free enamels, (1) 4*b*.
ferric, as colorant for red-brown enamels, (10) 269*b*.
ferric, effect on sintering of Zr bodies, (7) 188*b*.
ferric, hydrous, effect on adsorption of phosphate ion, (3) 85*h*.
ferric, solid solubility in belite, (7) 200*h*.
ferrous, effect on β-γ inversion temperature of dicalcium silicate, (7) 179*e*.
γ-ferric, isometric ferromagnetic, P (7) 194*e*.
solubility in B and B-free silicate melts, (2) 37*b*.
systems. See *Systems*.

Iron (*continued*)
phosphate, systems. See *Systems*.
phosphate, white, preparation, P (4) 111*e*.
photometric-complexometric determination in silicates, (3) 80*j*.
powdered, penetration of glass melt by, (9) 239*f*.
removal from glass sands in mill with abrasive action, (1) 25*d*.
removal, from Izumiyama pottery stone, I, (8) 225*c*.
sheet, effect of minor constituents on enameling of, (3) 65*g*.
in silicosis, histology of, (2) 60*e*.
sulfate, ferric, in preparation of metal for cover coat direct-on steel enameling, (2) 36*g*.
surface preparation for one-fire enameling, P (6) 155*h*.
transport by chemical reaction, (5) 142*b*.
wet grinding of, abrasive for, P (4) 95*g*.
Irradiation. See *Radiation*.
Isolators. See *Insulators, electrical*.
Isotopes, ^{60}Co, in study of mortar segregation, (10) 268*a*.
in crystal growth studies, B (9) 263*a*.
in determination of ion adsorption, III, (3) 86*d*.
neon, diffusion in fused quartz, (4) 113*j*.
radio-, in study of resistance of dunite refractories to corrosion by molten slag, (1) 13*j*.
radioactive, in bin and level indication of granular materials and liquids, (5) 138*d*.
for measurement and control of material in lime shaft kiln, (7) 197*a*.
in measurement of UO_2 particle size distribution, (6) 173*f*.
in measurement of wear of blast-furnace brickwork, I,II, (6) 159*j*.
in study of wear of refractory lining in converters, (3) 72*b*.

Jewelry. See *Art and artware*.
Joints, carbon electrode, P (1) 16*a*.
expansion, screw nipple, for C electrodes, P (8) 225*a*.
expansion, for wall construction in industrial furnaces, P (8) 225*b*.
metal-ceramic, P (2) 38*e*.
metal-to-ceramic, with titanium insert, P (2) 38*g*.
polyester, for clay pipe, (1) 13*a*.
polyester resin, for sewer pipe, (9) 243*c*.
for scientific glass apparatus, P (6) 157*e*.
tapered, for bell and spigot tile, P (5) 132*c*.

Kalsilite, hydrothermal conversion of muscovite to, (4) 114*c*.
Kaolin, in barreling chips, P (9) 236*a*.
batch calculation, formulations for, (11) 309*b*.
comminuting method, P (10) 289*a*.
elutriation, in centrifugal classifiers, (10) 288*e*.
expansion measurement parallel and perpendicular to lamellas, B (10) 300*b*.
grain size analysis, by pipet method, (3) 80*g*.
meta-, existence of, (10) 292*f*.
morphology, (11) 316*h*.
in 1961, (1) 25*d*.
in refractory material for thermocouple protection, (10) 276*f*.
in rounded contact masses, P (6) 171*b*.
systems. See *Systems*.
Kaolinite, acid-treated, electronoscopic studies, (7) 199*c*.
in clays, effect on reactions, (1) 30*f*.
DTA determination of heats of reaction in, (6) 167*i*.
effect of exchangeable cations on rheological properties and particle size distribution, (3) 87*e*.
effect of purity on refractory properties, (6) 170*a*.
exchangeable H ions in, (4) 115*d*.
Hirschau, microscopic study of, (4) 109*f*.
identification of, (4) 112*d*.
meta-, existence and exothermal effects of alumina, (10) 296*j*.
meta-, phase, existence of, (10) 295*d*.
minerals, B (10) 299*d*.
monoclinic, from Yugoslavia, (4) 109*j*.
physical properties, changes on heating, (3) 82*d*.
quantitative determination by X-ray diffraction, (4) 107*d*; (6) 168*g*.
-quartz-feldspar, high temperature reactions, (3) 75*g*.
reaction with Al fluoride, formation of amorphous metaphase in, (10) 292*g*.
structure, study with infrared absorption, (11) 319*f*.
talc-, compositions, study of phase transformations by X-ray diffraction, (6) 174*e*.
vacuum-firing and high-temperature replication of, (7) 201*f*.
Kieselguhr, bleaching of, P (4) 110*e*.
in 1962, (9) 253*j*.
Kiln furniture, cars, increasing working capacity, (8) 224*g*.
lining with reinforced-concrete blocks, (7) 196*h*.
top with interlocking tile, P (10) 288*c*.
tops, concrete, installation, (3) 72*d*.
sagger, for firing glazed ceramic machine parts, (8) 218*a*.
Kilns. See also *Burners; Furnaces; Instrumentation; Ovens*.
annular, calcination of rocks containing organic substances in, (3) 83*e*.
atmosphere, effect in ceramic firing, B (2) 61*j*.
automatic vertical, history of, (10) 266*i*.
bottom lift, advantages for special refractory shapes, (10) 287*f*.

Kilns (*continued*)
brick, producing 99% good brick, (2) 43*g*.
cement. See also *Kilns, rotary cement*.
automatic controls, P (5) 127*c*; P (9) 237*k*.
automatic vertical, modern use of, (2) 34*d*.
delivery of hot discharge to conveyor, P (9) 237*b*.
dust return system for, (2) 34*c*.
effect of Cr in refractories on clinker, (3) 72*i*.
effect of dust on soil and plants, (2) 34*d*.
and lime, solution of hot zone problems, (2) 35*i*.
preheating apparatus, P (7) 182*f*.
refractory problems in, (1) 2*h*.
shaft, multiple feeder for, P (4) 96*e*.
2.7 million-bbl, (10) 267*g*.
use of fine dust from, (11) 302*f*.
vertical, remote control sintering in, (10) 287*j*.
wet process operation, computer simulation of, (5) 126*d*.
ceramic, construction, P (10) 288*a*.
closed-loop computer control for, (2) 35*g*.
concrete linings and car tops, installation, (3) 72*d*.
continuous and intermittent, oil-firing, (2) 53*f*.
continuous and periodic, oil burner for, (10) 287*j*.
electric, Top Hat, for firing of sanitary ware, electrical porcelain, and earthenware, (11) 314*e*.
envelope, in brick plant, (4) 100*h*.
gas-fired, intermittent, for stoneware pipe, (10) 287*g*.
for stoneware, (10) 287*i*.
two-car intermittent, in pottery, (6) 169*a*.
uncovered, in cement plant, (6) 154*h*.
grate-, systems, for lime production, (10) 288*g*.
hand-fired, use of forced secondary air in, (6) 169*e*.
Hoffmann, improving fire travel in, (1) 24*h*.
intermittent downdrafts, reduction of stack emissions, I,II, (6) 169*c*.
lightweight refractories as hot-face insulation, (7) 196*h*.
lime, high capacity vertical, (11) 314*e*.
for increase in recovery and production, (2) 35*b*.
shaft, fundamental studies, III, (8) 205*e*.
shaft, measurement and control of material level by radioactive isotopes, (7) 197*a*.
vertical, electronic control of, (6) 154*f*.
linings. See *Refractories*.
multipassage, electric, evaluation of, (2) 53*e*.
oil-fired, for lightweight aggregate, (9) 243*a*.
for porcelain industry, (4) 103*j*.
portland cement, dolomite refractories in, (10) 274*g*.
rotary, gas-fired, in shale aggregate plant, (6) 158*j*.
lining of, (1) 24*i*.
method of burning material in, P (5) 140*f*.
for producing expanded shale, (6) 159*b*.
Rotoscribe for recording shell position, (9) 253*c*.
scoop feeder for, P (7) 197*b*.
seal for, P (4) 108*j*.
sealing unit for, P (8) 225*a*.
spiraling brick arch for, P (2) 46*h*.
rotary cement, automatic controls for, (2) 35*b*.
clinker brick for use in, (7) 178*i*.
computer control, (6) 154*i*.
control for, P (9) 237*k*.
control by on-line digital computers, (5) 126*e*.
instrumentation and automatic control of, (5) 126*j*.
periclase chrome-magnesite lining for, (7) 188*g*.
refractory magnesite linings for, P (3) 74*g*.
with shaft counterflow heat exchanger, (11) 301*j*.
slagging failure of refractories in, (2) 45*e*.
thermal physics of, (7) 182*k*.
wet-process, use of analog computer with, (11) 302*a*.
wire rope connector, P (10) 268*e*.
rotary grog calcining, automatic control of, (7) 194*h*.
rotary lime, for improving production, (9) 236*i*.
round, oil-fired, performance of, (2) 53*g*.
shaft, construction, P (11) 314*e*.
off-gas collector for, P (3) 82*a*.
with orifice controlled combustion, P (1) 3*j*.
tunnel, car top with interlocking tile, P (10) 288*c*.
castable refractories for car tops, (3) 71*i*.
control of speed, (1) 24*g*.
design developments, (6) 169*b*.
design improvements, (7) 190*e*.
device for localizing rapid variations of temperature at predetermined points, P (1) 24*h*.
efficiency in sandwich method of rapid firing, (7) 196*j*.
electric, heat recovery in, (2) 53*h*.
electric, with heat recovery system, (10) 287*h*.
firing of pipe in, (10) 279*a*.
firing porcelain in with liquefied gas, (7) 196*g*.
fuel oil burners for, (5) 140*c*.
German, zone control, I,II, (1) 24*h*.
increasing working capacity, (8) 224*g*.
operation in German brick and tile plants, (10) 273*f*.
salt glazing, for pipe production, (2) 43*f*.
twin tunnel, P (9) 253*d*.
Kimzeyite, Zr garnet from Arkansas, (4) 109*c*.
Kinetics, Cs, of clinoptilolite, effect of base cation (6) 172*c*.
of Cs reactions with cation exchange materials, (7) 199*g*.
of crystallization around impurity particles, B (9) 262*d*.

Kinetics (*continued*)
of crystal structure transformation of anatase to rutile, (11) 318*b*.
diffusion, in alkali halides, effect of dislocations, (10) 294*d*.
of formation, of anodic oxide films on bismuth (3) 87*h*.
of gas boronizing of Ni, (2) 37*b*.
of hydrofluorination of UO_2, (10) 294*d*.
of H atom recombination on Pyrex glass and fused quartz, (9) 240*g*.
of hydrothermal quartz crystallization, (2) 57*d*.
of intracenter luminescence in region of temperature quenching of activator, (5) 135*f*.
luminescence, of Cr luminophors, I–IV, (6) 164*e*.
methods, for characterization of point defects in crystals, B (9) 259*a*.
of phase transformations, in production of fused-cast refractories, (10) 274*i*.
sintering, for high density alumina process, (1) 29*g*.
of slip casting, (5) 144*c*.
solid-state reaction, equations and tables for analyzing, (10) 292*c*.
studies, of crystallization of synthetic mica glass, (11) 317*j*.
of thermal decomposition of Mg and Ca carbonate, (4) 115*f*.
of transformation of quartz, mechanism of, (5) 129*h*.
Kyanite, as addition to ramming bodies, (1) 13*f*.
formation from pyrophyllite at high pressures and temperatures, (4) 114*f*.
in Georgia, mineral characteristics, locations, and uses, (3) 82*e*.
and related minerals, 1962, (9) 253*j*.
stability compared to andalusite and sillimanite (4) 118*e*.

Laboratories. See also *Research and research laboratories*.
high-temperature, in Nova Scotia, (9) 258*b*.
mobile microwave standards, (9) 251*j*.
Ladles. See *Refractories*.
Laminations, causes in clay, III,IV, (11) 305*e*.
in clay products, cause of, (9) 243*b*.
in material, process for making, P (9) 250*f*.
Lamps. See also *Glass*.
base, end structure, P (9) 241*i*.
bulbs, apparatus for finishing and mounting terminals on, P (6) 157*d*.
constant lumen maintenance, P (9) 241*g*.
electric, mount making method, P (5) 130*h*.
electric, with reflectors, P (4) 99*d*.
electroluminescent, P (1) 21*a*.
electroluminescent, phosphor for, P (7) 193*g*.
envelope, method for introducing iodine, P (3) 70*d*.
fluorescent, P (10) 271*h*.
aperture, P (3) 68*c*.
coating with amorphous silica and phosphor, P (10) 272*d*.
construction, P (3) 77*d*.
multiple arc, P (7) 186*e*.
high pressure electric discharge, electrode or, P (1) 20*f*.
incandescent, bent end, P (6) 157*g*.
incandescent, coated, P (10) 271*d*.
method of making, P (6) 157*f*.
quartz, sealing machine control, P (6) 158*e*.
shades, fluorescent, manufacture of, (9) 241*d*.
Lanthanons. See *Rare earths*.
Lanthanum, borates, viscosity, density, and electrical resistivity of, B (11) 320*j*.
carbide, hydrolysis of, (1) 28*e*.
compound, in junction ceramic capacitor, (9) 247*j*.
nitride, magnetic susceptibility of, (4) 119*b*.
oxide, as modifier in optical glass, P (3) 70*b*.
oxide, systems. See *Systems*.
in preparation of semiconducting barium titanates, (10) 281*b*.
Lasers, (8) 228*b*. See also *Masers*.
CaF_2 doped with divalent Dy, (2) 48*d*.
continuous, sun-pumped, (10) 282*j*.
continuous operation, power and efficiency factors, (10) 281*k*.
development of, (10) 280*c*.
introduction to, (10) 280*i*.
materials, research on, (10) 281*f*.
modulation, method of, (7) 190*j*.
neodymium glass, B (11) 320*g*.
operation without spikes in ruby ring, (10) 280*j*.
optical, review of, (7) 191*f*.
quartz ultraviolet, (7) 192*a*.
ruby, in high-speed photography, (10) 279*f*.
modulation of output by absorption, (7) 192*c*.
simple method for calibration of output, (9) 251*g*.
as source in emission spectroscopy, (8) 223*c*.
U-doped CaF_2 as, (7) 192*i*.
Laterites, aluminous, Philippine deposits as refractory raw material, (9) 253*h*.
ores, treatment of, P (9) 254*h*.
Lattice constants. See *Crystals, structure*.
Lattice defects. See *Crystals*.
Lawsonite, synthetic, lattice constants of, (4) 115*g*.
Leaching, of alumina from aluminous material, P (10) 289*f*.
liquors, caustic, Al_2O_3-containing, desilication of (6) 154*d*.
nitric acid, in study of optical glass surfaces, I (8) 209*i*.
pressure, of titaniferous material, P (3) 84*h*.
of soluble constituents from Ti enamel frit, (6) 155*h*.
solutions, acid, recovery of Be from, P (2) 55*j*.

Lead. See also *Glass.*
borate, as solvent for fluorphlogopite mica, (1) 20*a*.
cadmium titanate, hysteresis behavior, (3) 76*j*.
chloride, systems. See *Systems.*
chromate, systems. See *Systems.*
compounds, crystal chemistry of, (10) 291*g*.
compounds, dilatometric and X-ray data for, II, (3) 86*d*.
effect on $(Ba,Pb)(Ti,Zr)O_3$ system in $BaTiO_3$ region, (7) 200*i*.
fluoride, and chloride, growth of crystals, B (9) 263*b*.
hafnate, systems. See *Systems.*
iodide crystals, chemical decomposition by irradiation in electron beam, (10) 290*g*.
$Pb_2NiNb_2O_9$ and $Pb_2MgNb_2O_9$, monocrystals, growth and electrical properties, B (9) 263*f*.
$Pb_2NiNb_2O_9$ and $Pb_2MgNb_2O_9$, polarization mechanism of solid solutions of, (7) 192*b*.
metasilicate, and orthosilicate, low temperature heat capacities and entropies, (2) 57*g*.
molybdate, systems. See *Systems.*
niobate, ferroelectric, solid solutions based on, (1) 30*a*.
niobate, modified, dielectric properties of, (10) 282*h*.
nitrate, annealing of radiolytic damage in, (10) 290*i*.
oxide, effect of excess in lead-zirconate-titanate compositions, (1) 19*f*.
in enamels for Al, (10) 269*i*.
in etchant for single crystals, P (3) 89*i*.
–PbF_2, growth of single-crystal $MgGa_2O_4$ spinel from, (5) 144*b*.
–PbF_2, molten, crystallization of refractory oxides from, (5) 144*a*.
molten, synthesis of forsterite, diopside, akermanite, and wollastonite from, (9) 257*h*.
-rich, side, of system PbO–TiO_2, (10) 296*g*.
-silica, composite, P (1) 25*h*.
systems. See *Systems.*
phosphate, systems. See *Systems.*
pyrophosphate, as flux for crystal growth, (5) 147*h*.
selenide, systems. See *Systems.*
solubility in molten silicates, (3) 64*e*.
solubility from on-glaze decorated porcelain, Austrian regulations of, (3) 90*b*.
sulfate, systems. See *Systems.*
sulfides, crystallization from chloride aqueous solutions, B (9) 263*e*.
systems. See *Systems.*
telluride, in thermoelectric devices, P (5) 136*h*.
titanate, effect of additives on properties, (2) 47*i*.
in ferroelectric ceramics, (5) 134*d*.
hydrothermal preparation, (10) 294*a*.
-lead zirconate ceramic compositions, electromechanical properties, (11) 309*i*.
perovskite, crystallization from glasses, (9) 239*h*.
structure, comparison with brookite, (10) 290*f*.
systems. See *Systems.*
thermal conductivity compared to $BaTiO_3$, (6) 175*e*.
zirconate ceramics, factors affecting electromechanical properties, (3) 76*c*.
zirconate, lead titanate ceramics, factors affecting, (7) 191*h*.
titanate compositions, preparation of, I,II, (1) 19*d*.
-titanate, polycrystalline, electric conduction in, (2) 47*h*.
-titanate, thin-walled spheres, material constants at high pressure, (11) 310*j*.

Lehrs. See *Furnaces; Glassmaking apparatus and equipment.*

Lens. See *Glass, optical.*

Leucite, formation, in fusion of potash feldspar, (1) 18*h*.

Light, beam, in potentiometer control, (10) 280*j*.
day-, artificial, apparatus for producing, P (9) 252*f*.
day-, glass sheet for control of, P (10) 271*g*.
guide, use in flame spectrophotometry, (1) 23*j*.
infrared, effect on luminescence of silver halide phosphors, (5) 134*e*.
interference, in study of glaze surface, (10) 278*f*.
from locomotive head light with metal reflector intensity of illumination of, (11) 304*d*.
modulation, wide-band microwave, (7) 193*d*.
moving sources, optical potentiometer for sensing position of, (9) 251*d*.
output, of alkaline earth halophosphates, method of increasing, P (2) 49*b*.
rays, piezoelectric materials for controlling, (10) 280*e*.
scattered by glasses, depolarized components, III, (5) 128*i*.
scattering, from heat treated synthetic quartz, (4) 115*g*.
source, luminescent halophosphate single crystal, P (1) 21*d*.
sums, stored in ZnS:Cu,Al phosphors, (5) 135*f*.
transmission, by translucent Al_2O_3, (7) 191*b*.

Lighting, glass for, B (11) 322*h*.

Lignosulfonates, as cement grinding aid and pack set inhibitor, P (10) 268*e*.

Lime. See also *Calcium, oxide; Glass.*
activity in blast-furnace slag, I, (7) 178*b*.
ASTM standard for, B (9) 259*a*.
binding in Ca hydrosilicate under normal conditions, (2) 34*e*.
burning, effect of mineralizers on, (11) 302*f*.
combination in calcareous earthenware bodies, (8) 217*g*.

Lime (*continued*)
effect on paste hydration of cement compounds, (1) 3*e*.
effect on siliceous refractories, B (10) 300*h*.
free, determination in clinker, (9) 236*g*.
hydration of, apparatus for, P (3) 64*h*.
hydraulic, producing from oil shale, P (10) 290*b*.
limiting saturation of portland cement clinkers by, (7) 181*h*.
physicochemical properties of, (5) 126*h*.
plant, increased production in, (9) 236*i*.
in Ohio, operations in, (10) 289*a*.
200-tpd, (10) 288*e*.
production, grate-kiln systems for, (10) 288*g*.
production for metallurgical and chemical purposes, (10) 288*h*.
raw materials, in Kansas City area, (3) 64*h*.
recovery and production, increase by new kiln, (2) 35*b*.
slaked, for use as plaster, plasticity figure of, (1) 2*j*.
slaking, apparatus for, P (3) 64*h*.
-soda, sinters, desilication of solutions from leaching of, (6) 154*d*.

Limestone, calcined, in cement clinker manufacture, properties of minerals in, (7) 181*c*.
and dolomite, cyclic sedimentation of, (3) 82*g*.
dolomitic, inclined drilling in, (9) 254*d*.
low-grade, in masonry cement, (7) 181*a*.
metallurgical grade, production in Pa. plant, (7) 178*f*.
mines, underground, use of ammonium nitrate in, (10) 288*d*.
producers, percentage depletion for, (10) 288*j*.
as substitute for cement for seawater durability, (1) 3*g*.
substitution in siliceous aggregates, (8) 205*b*.
washing of, (10) 289*d*.

Linings. See also *Refractories.*
for miniature incandescent lamps, P (6) 157*g*.

Liquids. See also *Fluids.*
$AsBr_3$ immersion, stability during storage, (4) 107*i*.
concentrator for quantitative analysis of substance in, P (10) 287*c*.
dispersion and absorption of microwaves in, B (9) 263*h*.
electrostatic spraying or atomizing heads for, P (7) 195*b*.
flowmeters for, (7) 195*d*.
formation, in initial stage of liquid phase sintering, (4) 118*g*.
inorganic, fundamentals of structure, B (10) 298*i*.
measurement of level by radioactive isotopes, (5) 138*d*.
measurement of moisture in, (7) 195*d*.
mixture, continuous colorimetric determination of components, P (2) 60*b*.
-solid interfaces, controlling by Peltier heat, P (8) 222*b*.
streams, analyzers for, (1) 23*j*.
vapor density apparatus for, (9) 252*a*.
vapor pressure data for, (5) 147*j*.

Liquor. See *Sulfite liquor.*

Lithia. See *Lithium, oxide.*

Lithium, aluminates, I, modification, (4) 115*g*.
borate, in treating alumina ceramic article, P (1) 16*g*.
carbonate, production, P (1) 26*a*.
production from spodumene, P (5) 141*g*.
solid-liquid phase equilibria with Na and K carbonates, (1) 30*c*.
systems. See *Systems.*
ceramics, negative heat expansion in, (4) 101*j*.
chloride, systems. See *Systems.*
ferrites, dispersion of complex permeability of, (3) 86*f*.
ferrites, with square hysteresis loop, P (9) 249*d*.
fluoride, crystals, U-activated, piezospectroscopic effect in, (6) 165*a*.
effect of radiations on electrical and optical properties, (10) 294*h*.
formation of interstitials and vacancies in, (10) 293*d*.
neutron-irradiated, V-type center resonance at room temperature, (2) 59*i*.
polycrystalline, deformation and fracture, (8) 226*j*.
germanate, systems. See *Systems.*
hydride, properties of, B (9) 261*h*.
importance in Canadian mining industry, (3) 82*e*.
ion emission, physical properties of β-eucryptite associated with, (2) 59*c*.
ions, response of electrode glass to, (5) 129*e*.
ions, in staining paste for glass, P (6) 157*d*.
liquid, electric resistivity of, (2) 57*c*.
$LiAl_5O_8$, phase transitions in, (10) 296*i*.
$LiSeO_3$, crystal structure of, (4) 113*e*.
materials survey, (10) 288*j*.
metasilicate region, in system Li_2O–Al_2O_3–SiO_2, glass formation and recrystallization in, (4) 98*g*.
minerals and compounds, for special glasses and ceramics, (7) 197*g*.
nitrate, molten, in treatment of muscovite, removal of reaction products, (6) 170*i*.
oxide, ceramics, effect of Li_2O-containing glass on, (8) 209*g*.
systems. See also *Systems.*
use in enamels, B (11) 322*g*.
silicate, systems. See *Systems.*

Lubricants, as aids in manufacture of SiO_2 and MgO refractories, (1) 13*i*.
for glass mold, P (1) 11*b*.
high temperature, and techniques, (10) 269*d*.
for high-temperature metalworking processes, (7) 183*f*.
for hot-working of titanium, P (3) 65*f*.
silicone, for glass molds, (4) 99*a*.

Lubricants (*continued*)
wire-drawing, glass compositions for, P (6) 157*b*.

Lubrication, effect of surface finish on, (3) 90*g*.
extrusion, P (2) 42*d*.
of hot-extrusion press, P (10) 269*c*.
of mold box liners, (4) 101*j*.

Luminescence, bands, blue and green, of ZnS:Cu,Cl phosphor, final stages of buildup, (6) 164*c*.
of CdS crystals, (6) 172*f*.
cathodo-, of SrO, (BaSr)O, and MgO, (4) 112*j*.
centers, of alkali halide phosphors doped with divalent metals, (5) 135*g*.
applicability of Condon approximation, (6) 163*f*.
in crystalline phosphors, structure of, (5) 144*i*.
proximity of trapping centers, (6) 163*h*.
in ZnS:Cu phosphor, role of impurities in formation, (6) 165*g*.
of Cu– Cu–Pb-activated Sr borate phosphors, (6) 164*d*.
during annealing and phase change in crystals, (2) 48*c*.
electro-, in alkali halides, excitation of, (6) 163*j*.
of crystal phosphors, effect of bond type on, (6) 163*j*.
and infrared quenching, (5) 135*b*.
from surface layers of $BaTiO_3$, $SrTiO_3$, (4) 113*c*.
of ZnO single crystals, (5) 134*f*.
of ZnS:CuAl excited at high frequencies, I, (10) 292*a*.
of ZnS phosphors, under excitation by square pulses, (6) 163*h*.
of ZnS single crystals with cathode barriers, (2) 57*d*.
of ZnS:Cu,Cl single crystals, temperature dependence of, (6) 165*j*.
of ZnS:Cu,Pb microcrystals, (6) 163*g*.
γ and photo-, of alkali iodides, (5) 135*a*.
infrared, of F centers in X-rayed fluorite crystals, (5) 135*d*.
intracenter, in region of temperature quenching of activator, kinetics of, (5) 135*f*.
kinetics, of Cr luminophors, I–IV, (6) 164*e*.
of Sm in Sr and Ba fluorides, (6) 164*j*.
of ZnS:Cu crystal phosphor under pulse excitation, (6) 164*i*.
phenomena, in ZrO_2 research, (10) 286*h*.
photo-, of PbS films, effect of oxygen on, (5) 135*b*.
of Ag-containing crystalline quartz, (6) 164*j*.
of solutions and crystals of Gd salts, (5) 145*c*.
polarization of, B (9) 260*h*.
radical-recombination, of ZnS,CdS:Cu, effect of electric field, (5) 134*j*.
from ruby excited by fast electrons, (6) 164*a*.
of self-activated sublimed ZnS phosphor, (6) 164*b*.
of silver halide phosphors, effect of infrared light on, (5) 134*e*.
steady-state, of ZnS phosphors, I,II, (5) 135*a* III, (6) 165*i*.
thermo-, in dolomite, (2) 48*c*.
of single crystal α-Al_2O_3, (5) 147*b*.
of X-rayed synthetic quartz, B (9) 263*g*.
of tungstate phosphors, effect of grinding on, (5) 134*d*.
of ZnS phosphors, decrease in luminescence intensity by mechanical crushing, II, (5) 134*f*.

Luminescent materials, calcium phosphate, dibasic, P (4) 106*a*.
electro-, breakdown protected cell, P (1) 20*g*.
cell, P (1) 20*g,h;* P (5) 135*g*.
device, P (1) 20*j;* P (2) 48*e;* P (2) 49*a;* P (4) 105*j*.
flexible strand, P (1) 21*b*.
lamps, P (1) 21*a*.
system, electrically nonlinear element, P (5) 135*j*.
as layer in electric gas discharge lamp, P (2) 42*c*.
light source of, P (1) 21*d*.
red, for cathode-ray tubes, P (1) 21*f*.

Luminophors. See *Phosphors.*

Lutetium, diborides, and antimonide, preparation and structure, (11) 318*b*.

Machinability, study, of ceramic tools, X, (1) 1*f*.

Machinery and equipment. See also *Materials handling* and specific types.
air compressors, selection of, (2) 51*d*.
for automatic shaping of flowerpots, bowls, etc., (10) 284*a*.
for automation of chemical and ceramic processes, (8) 221*h*.
for bending sheet metal hanger tabs away from ends of metal-cased refractory brick, P (1) 15*i*.
for cutting clay pipe, P (8) 212*a*.
for forming clay spheres, P (4) 106*e,f,g*.
for forming oval dishes and pottery, (3) 79*h*.
geared drives, for cement plants, (2) 35*i*.
heat-resistant parts, ceramic materials with Zr silicate for making, P (4) 102*c*.
for loading bulk materials into side-by-side compartments, P (1) 24*j*.
in porcelain factories, physicochemical mechanical analysis of work of, (1) 18*b*.
rotary hammer impactor, dust prevention device for, P (7) 195*a*.
for slicing semihardened materials, P (2) 51*h*.
for slip banding, of flatware, automatic controls, (10) 284*d*.
upender mechanism, for tile machines, P (1) 13*c*.

Magnesia. See also *Magnesium, oxide; Refractories.*
addition of Ni for strength improvement, (4) 97*a*.
as additive, effect on sintering of Al_2O_3, (7) 200*e*.

Magnesia (*continued*)
bicrystals, direct observations of grain-boundary sliding in, (5) 142*h*.
B-X systems of, Franck-Condon factors and γ-centroids for, (5) 143*h*.
coarse grains, effect on basic open-hearth furnace roof brick, (11) 305*j*.
coatings, on Si steel, P (6) 155*f*.
crystals, decorated dislocations in, (7) 198*k*.
dislocation damping at low frequencies, (5) 134*j*.
mechanical properties of, (8) 230*b*.
single, electronic and ionic conductivity, (9) 247*c*.
single, explosively shocked, structure and annealing behavior, (9) 257*g*.
sliding and wear in, (10) 297*f*.
dead-burned, production, P (2) 46*d*; P (9) 245*g*.
effect on grain growth of high density alumina, (1) 29*g*.
effect on iron glazes, (1) 18*d*.
films, thin self-supported, secondary emission of, (5) 145*h*.
flame spectrometric determination in aluminosilicates, (10) 286*d*.
free, effect on reactions in magnesiochromite brick, (9) 243*j*.
fused, electrical resistance-temperature relation, (9) 244*a*.
fused, specific heat of, (3) 73*d*.
-Mn oxide mixtures in air, melting relations of, (3) 87*g*.
moving dislocations in, damage from, (9) 255*g*.
optical constants in infrared region, (9) 256*d*.
oxychloride, (2) 35*j*.
plastic deformation, effect of crystal orientation, (9) 256*a*.
porous sorbent, for removal of silicates from water, P (3) 84*g*.
in portland cement, (7) 180*i*.
pressure sintering, mechanisms and microstructures, (11) 318*c*.
refractory composition, P (9) 244*c*.
relation of single-crystal elastic constants to polycrystalline isotropic elastic moduli, (10) 296*j*.
seawater, clinker, comparison with magnesite for basic open-hearth furnace brick, II, (11) 305*g*.
Indian, refractory properties of, (6) 170*h*.
refractory bricks from, (9) 243*h*.
sintered, of uniform hardness, P (4) 103*d*.
sintered slip-cast, density and permeability, (7) 187*e*.
as superrefractory above 1500°C, (3) 73*e*.
synthetic, sintering process of, (3) 72*j*.
systems. See *Systems*.
transverse bend strength, effect of grain size on, (7) 198*j*.
ultraviolet optical absorption bands, effect of O on, (9) 256*d*.

Magnesite. See also *Refractories*.
action of water on, (6) 169*f*.
Austrian deposits, (7) 197*e*.
calcination, effect of gaseous phase, (6) 159*j*.
clinker, comparison with seawater MgO clinker for basic open-hearth furnace brick, II, (11) 305*g*.
DTA determination of heats of reaction in, (6) 167*i*.
natural, effect of impurities on sintering, (3) 73*h*.
ores and refractories, nature and properties, (3) 82*f*.

Magnesium, alcoholate, in magnetic ferrite films, P (10) 283*g*.
aluminate, systems. See *Systems*.
carbonate, as filler for cement, (7) 178*f*.
carbonate, kinetics of thermal decomposition, (4) 115*f*.
chloride, anhydrous, preparation by ammonia reaction, P (9) 254*d*.
anhydrous, process and apparatus for manufacture, P (3) 84*i*.
making from seawater, P (2) 55*a*.
compounds, recovery from ores, P (8) 226*c*.
cordierites, anhydrous, compositions and structural states, (2) 56*g*.
enameling of, (5) 127*g*.
enameling process for, P (8) 208*b*.
fluoride, purification, growth of single crystals, and selected properties, (2) 58*j*.
fluoride, refinement of crystal-structure determination, (10) 296*h*.
hydroxide, electrolytic removal from seawater, P (7) 197*j*.
production of, P (6) 171*c*.
thermal decomposition of, (11) 319*i*.
oxalate, crystallization in aqueous solution, (8) 212*f*.
oxide. See also *Magnesia*.
and aluminate, thermal expansion tests, (10) 276*c*.
cathodoluminescence of, (4) 112*j*.
crystals, optical absorption and photoconductivity in, (3) 88*a*.
dislocation etchant for, (11) 318*c*.
dislocations and tensile strength of, (10) 291*j*.
effect on cement strength, (7) 179*k*.
effect on reduction of Co and Ni oxides, (10) 294*g*.
in electrical insulating coating, P (8) 220*g*.
fundamental optical absorption in, (3) 86*g*.
method of making, P (7) 189*i*.
oxygen band in, (4) 117*h*.
pellets, production for burning, P (11) 308*f*.
single crystals, dislocation sources and strength, (8) 227*h*.
solubility in molten salts, (9) 257*e*.
spin resonance of point defects in, B (9) 259*h*.

Magnesium, oxide (*continued*)
of submicron grain size and high density, preparation, (11) 318*g*.
phthalocyanine adsorbates, on MgO, Al_2O_3, ZnO glass, structure and fluorescence, (5) 130*f*.
silicate, systems. See *Systems*.
in silicate rocks, screened Eriochrome indicator for determining, (3) 81*d*.
in ternary carbides of transition metals, (4) 101*h*.

Magnetic materials. See also *Ferrites; Ferromagnetism and ferromagnetic materials*.
cores, mixed ferrospinel, P (3) 77*k*.
digest, 1961, B (3) 91*f*.
electro-, nonlinear, wave propagation in, (7) 193*b*.
garnet crystals, P (1) 21*a*.
in orienting articles of nonmagnetic material, P (8) 210*b*.
oxides, of Mo(V) and W(V), with ordered perovskite structure, (7) 191*k*.
process and apparatus for producing, P (3) 78*f*.
recorder powder, P (7) 194*b*.

Magnetic properties. See also *Anisotropy; Resonance*.
of Cr_2O_3, (4) 116*c*.
field dependence of Hall effect, in graphite single crystals, (4) 115*j*.
fields, application of Hall effect for point-by-point measurement, (9) 246*j*.
galvano-, analysis of data for graphite, (3) 85*j*.
galvano-, of Cr nitrides, (2) 57*a*.
galvanomagnetic de Haas-van Alphen type oscillations, in graphite, (4) 112*c*.
of hexagonal Ba monoferrite, (11) 310*g*.
of ilmenite and hematite system, I,II, (6) 173*b*.
of iron, relation to coloring action in glass, III, (1) 9*i*; IV, (2) 41*d*.
of $FeTiO_3$-Fe_2O_3 solid solution series, (6) 174*g*.
long-time aftereffects of remanence of ferrites, measurements on, (3) 87*e*.
magnetic field, in rotation of ultrasonic waves, (6) 164*c*.
magnetoelastic force, measuring device, P (10) 282*j*.
magnetostriction, of Mn-Zn-ferrous ferrite, polycrystalline, (9) 247*j*.
magnetostriction, of Y Fe garnet, (4) 116*h*.
measurements, of Fe-Cr spinels, (5) 147*g*.
of sintered ferrites, study using single crystal data, (1) 19*i*.
susceptibility, of cubic sodium tungsten bronzes, (9) 256*b*.
as measure of total Fe plus Mn in ferromagnesian silicate minerals, (4) 116*e*.
of nitrides of La, Ce, Pr, and Nd, (4) 119*b*.
in transformation series $Fe_3O_4 \rightarrow \gamma\text{-}Fe_2O_3 \rightarrow \alpha\text{-}Fe_2O_3$, (9) 247*g*.

Magnetite, phases, of perovskite type, (2) 57*h*.

Magnetization, saturation, of barium ferrite powders, effect of grain size, (1) 19*e*.
studies, of Ba ferrate III, (4) 116*f*.
of uniaxial cylindrical thin films, (9) 247*h*.

Magnetochemistry, in study of alkaline earth chromates(V), (4) 111*i*.

Magnetoresistance. See *Resistivity, electric*.

Magnets, ceramic, mounting structure, P (9) 248*f*.
electro-, high power, design of, (8) 218*j*.
focusing equipment, method of making, P (7) 193*f*.
magnetically anisotropic elongated, P (4) 105*g*.
oxide, manufacture of, (7) 192*a*.
permanent, Ba ferrite in, P (9) 249*e*.
composition, P (1) 21*c*.
ferrites for, (8) 220*a*.
modified Sr ferrite as, (10) 281*d*.
oxide-base, P (4) 105*j*.
variable strength, P (6) 166*i*.

Maintenance, of plant operations by card index system, (1) 31*f*.

Majolica, colors and glazes, Sb compounds as raw materials for, (4) 103*e*.

Management, of glass plant, position of foreman, (1) 8*i*.

Manganese, difluoride, crystal-structure determination, (10) 296*h*.
ferrites, composition, P (3) 77*i*.
in ferromagnesian silicate minerals, magnetic susceptibility as measure of, (4) 116*e*.
ions, trapping along dislocation lines in NaCl, B (9) 260*g*.
Mn^{4+}, quantifying in sintered Mn-Zn ferrites, (6) 164*f*.
$MnAl_2$, thermodynamics of ferromagnetic phase formation in, (8) 220*c*.
in Mn ferrite, valence changes, (10) 297*g*.
Mn_5Si, martensitic transformation in, (2) 57*j*.
ore, as pigment in structural clay products, (1) 12*i*.
oxide, CaO-, and MgO-, mixtures in air, melting relations of, (3) 87*g*.
electric conductivity in, (7) 191*f*.
electric conductivity as function of temperature and equilibrium O pressure, (9) 247*b*.
preparation and properties, I-III, (3) 88*a*.
systems. See *Systems*.
titanate, antiferromagnetic, neutron diffraction study, (6) 173*j*.
use in ancient glass, B (11) 321*d*.
zinc ferrites, micromorphological study, (10) 295*i*.

Manganin, in high-pressure sensors, (2) 52*a*.

Manufacturers association, formation, for producers of ceramic production equipment, (9) 258*h*.

Masers, (8) 228*b*.
four-level K_μ-band, (7) 191*j*.
Ho-doped CaF_2 as, (7) 191*b*.
iron sapphire, with no magnetic field, (7) 191*e*.
microwave and optical, crystals for, (2) 47*h*.
optical, CaF_2, Tb- and Ce-activated, P (6) 166*g*.
rystals for, (9) 255*e*; (10) 298*e*.

Masers, optical (*continued*)
flux-grown ruby in, (10) 280*b*.
thermal conductivity of, (1) 30*e*.
ruby optical, continuously operating, (5) 134*h*.
70-Ge, (10) 282*e*.

Masonry, brick, research on, (2) 43*h*.
clay, increased use of, (7) 187*b*.
coating for, P (1) 13*a*.
units, ASTM standard for, B (9) 259*b*.
water repellent, compositions for, P (10) 268*c*.

Mass, transport, through solid substance, (1) 29*a*.

Materials, advanced, B (5) 148*e*.
aerospace, graphite as, (10) 288*g*.
brittle, testing with ultrasonics, (7) 195*j*.
composite, effect of glass fiber geometry on strength of, (6) 156*g*.
of earth's crust, electric properties, (10) 282*g*.
engineering, single crystals as, (9) 258*d*.
with high melting point, method of growing single crystals from, (10) 288*e*.
high temperature, crystal structure and stability, B (2) 60*j*.
determination of thermophysical constants, (8) 223*j*.
service, (10) 269*d*.
in vacuo, volatilization of, (3) 89*g*.
for high vacuum technique, Vol. III, B (2) 61*d*.
hydraulic, physical chemistry and technology, (8) 205*j*.
measurement of capacitivity, P (9) 252*h*.
for packaging, (1) 23*c*.
porous. See *Porous materials*.
pyrolytic, for reentry applications, (10) 275*h*.
pyrolytic, for thermal protection systems, (10) 275*i*.
for reentry heat protection of satellites, (1) 7*g*.
science and materials engineering, impact on ceramic engineering, (2) 60*g*.
science and technology, for advanced applications, B (3) 92*g*.
selection of, (3) 90*h*.
sorting apparatus, P (5) 141*d*.
spectral data for, (8) 222*h*.
subliming, evaporation of, P (10) 285*a*.
thermosetting, fluidized bed process for coating with, P (9) 239*a*.
transparent, temperature measurement in, B (2) 62*c*.
ultrafine-grained, formation for ceramics or metallurgy by use of thixotropic layers, P (3) 83*g*.
wear resistant, properties and uses, (6) 155*c*.

Materials handling. See also *Conveyors; Feeding apparatus; Machinery and equipment*.
apparatus for lifting stack of building units, P (3) 71*h*.
apparatus for loading bottles, P (4) 100*b*.
bags, multiply, P (2) 51*g*.
of brick, Hulo system, (1) 12*i*.
of brickmaking materials, Knotts method, (1) 12*j*.
of brick stacks, apparatus for, P (9) 250*c*.
bulk, apparatus for loading into side-by-side compartments, P (1) 25*f*.
of phosphate rock, (11) 314*g*.
of powders in chemical industry, (1) 22*d*.
of cement and carbon black, blowing by hose (3) 79*e*.
in enamel plant, (3) 65*i*.
of glass sheet, P (10) 273*b*.
equipment for, P (8) 210*i*.
for railroad flatcar, P (6) 157*j*.
with tongs, P (8) 210*j*.
of glassware, P (7) 185*i*.
of granular materials, P (5) 138*g*.
industrial hygiene design in, (9) 258*f*.
multiple unitizer, P (5) 138*c*.
new methods, (4) 106*g*.
pallets, for brick, P (8) 212*a*.
pallets, supporting uniform load-units stacked in layers, P (6) 167*f*.
of powders, unloading apparatus, P (4) 110*h*.
in Pyrex glass factory, (7) 194*i*.
stacking and strapping machine, P (10) 273*g*.
of stored tile, (6) 159*a*.
Tote System, for bulk materials, (11) 314*d*.
tray-loading apparatus, P (2) 51*i*.
unloading bulk materials from hopper cars, P (4) 110*d*.
of volatile solvents, (1) 31*e*.

Measurement devices, for combustion control, (5) 140*e*.
compensated gravity, P (5) 139*d*.
multifilar, for microscope tube, P (10) 287*b*.

Mechanical properties, of ceramic single crystals, (8) 230*b*.
of crystalline solids, symposium proceedings, B (9) 259*e*.
of crystals, (10) 298*e*.
cyclic, of glass cloth reinforced polyester and epoxy resin laminates, (9) 239*e*.
effect on refractories in glass tank, (8) 208*i*.
of engineering ceramics conference proceedings, B (3) 91*g*.
of ionic crystals, effect of grain boundaries, (8) 227*d*.
of irradiated graphite, B (8) 234*h*.
of Lucalox alumina, (9) 254*h*.
of NaCl single crystals in flexure, (2) 58*b*.
of TiC-WC-Co alloys, (2) 59*a*.

Mechanics, classical, B (10) 299*j*.

Mechanization. See also *Automation*.
of plate production, (4) 104*c*.
of technical porcelain production, (10) 281*b*.

Meetings. See *Conferences*.

Melilite, crystals, in blast-furnace slags and matrix, (10) 267*a*.

Melting, of Al orthophosphate, (7) 183*h*.
behavior, in system UO_2-PuO_2, (9) 243*g*.

Melting (*continued*)
capacity, of glass tank furnaces in Germany, (1) 7*i*.
of crystal and lead-crystal glass, (1) 7*i*.
of glass batch, P (6) 157*i*.
point, depression, in sodium borate system, structural interpretation, (4) 120*d*.
temperatures, discrepancy in conversion of, (9) 255*i*.
viscosity at, extension of Andrade equation for, (1) 27*g*.
process, of lime-zinc glazes, (11) 309*g*.
of quality utility glasses in pot furnaces, (7) 184*i*.
of refractory metals, electrodes for, P (2) 45*f*.
relations, of CaO-manganese oxide and MgO-manganese oxide mixtures in air, (3) 87*g*.
zone, and resolidifying of pure substances, P (8) 220*d*.
Melts, B and B-free silicate, solubility of iron oxides in, (2) 37*b*.
enamel, action on steel, (2) 36*e*.
fluorophosphate, vibration spectra of, (5) 147*b*.
fusion, of elements, color of, (4) 112*j*.
techniques of growing crystals from, B (9) 262*j*.
Mercury, crystal, temperature at growth front, B (9) 262*f*.
Metallizing. See *Coatings*.
Metalloceramic compositions. See *Cermets*.
Metallography, of arc-melted and sintered alloys in Hf-O system, (11) 316*b*.
examination, of ferrites, rapid preparation of specimens, (1) 19*b*.
in observing morphology of sintered alumina, (11) 313*a*.
technique, in study of TiB_2, (8) 228*i*.
technique, for UO_2, (11) 306*d*.
Metallurgy, batch preparation, automatic weighing units for, (8) 225*c*.
fiber, state of art and bibliography, (8) 213*b*.
industry, dust collectors in, I-III, (5) 137*j*.
powder. See *Powder metallurgy*.
uranium, Vols. I,II, B (4) 124*i*.
Metals. See also *Enameling metals; Rare earths*.
-aggregate product, P (2) 46*b*.
alkali, in generators, P (10) 269*a*.
alkali, vapors, determination of glass resistance to, P (2) 38*a*.
bonding method, P (1) 5*a*.
casting, preformed ceramic cores in, (8) 212*i*.
casting, refractories for, P (2) 46*c*.
ceramic coatings for, P (3) 65*d*.
-ceramic friction compositions, fasteners and mounting processes for, P (3) 73*j*.
-ceramic joints, P (2) 38*c*.
-ceramic materials. See *Cermets*.
coatings for high-temperature oxidation protection, (10) 268*j*.
composition, relation to surface composition, pickling rate, and direct-on enamel adherence, (2) 37*j*.
corrosion, importance in glass industry, (1) 5*j*.
crystals, single preferentially oriented, growth of, P (2) 60*a*.
cutting of, Al_2O_3-C compositions for, P (2) 33*g*.
depositing on glass for decoration, P (10) 272*f*.
dispersion hardened, production of, P (4) 103*c*.
dispersion of refractory metal oxide in, P (8) 217*a*.
dispersion strengthened, processing method, P (4) 102*i*.
dispersion strengthened, production of, P (4) 103*b*.
electrolytic cleaning, salt bath for, P (10) 269*g*.
enamels for, (7) 183*f*.
ferrous and nonferrous, ASTM standards for, B (9) 259*a*.
fibers, as reinforcement, I, (8) 213*b*.
fibers, as reinforcement in ceramics, (1) 4*e*.
fibers in, for composite materials, P (10) 272*h*.
fibrous, production and performance, B (5) 148*e*.
firing glass on, (5) 126*b*.
gas plating on glass fibers, P (10) 272*i*.
glass coatings on, study of crystallization by electron microscopy, (8) 207*j*.
heat-resistant paints for, (9) 238*c*.
hot extrusion, use of glass, (1) 10*i*.
incorporation in ceramics, (4) 97*a*.
intermetallic compounds, for aerospace systems, (10) 276*b*.
iron group, with submicron particles of refractory oxides dispersed in, P (8) 216*i*.
low-carbon, critical grain growth of, (2) 36*f*.
magnetic, deposition in thin film on nonferromagnetic base, P (10) 283*a*.
mechanism of vacuum condensation in, B (9) 262*f*.
molten, refractory materials for containers for, (6) 159*e*.
molten, refractory nipple for dipping into, P (2) 46*g*.
noble, thermal deposition on ceramics, (11) 312*a*.
oxides. See *Oxides*.
and oxides, high-melting mixtures for abrasives, P (3) 63*i*
oxide whisker growth on, (6) 173*f*.
polishing, corundum, mullite, and spinel crystals for, (1) 1*i*.
porous bodies of, method of making, P (4) 102*d*.
powders, apparatus for oxidation, P (8) 221*e*.
powders, forming by use of plaster mold in steel mold, (11) 312*a*.
preparation for cover coat direct-on steel enameling, use of ferric sulfate, (2) 36*g*.
preparation for direct-on enamel application, B (11) 322*h*.
reference book, B (3) 92*f*
Metals (*continued*)
refractory, ceramic adhesive bonding of, (7) 183*a*.
coatings for protection from oxidation, (3) 65*d*.
deposition of metallic and nonmetallic coatings on with plasma arc torch, (9) 238*b*.
electrodes for melting, P (2) 45*f*.
large parts, fluidized method of coating, (6) 155*c*.
properties and protection, (10) 269*f*.
protection with diffusion coatings, (1) 4*d*.
protective coating for, P (9) 239*c*.
reinforcement with ceramic whiskers, (4) 97*e*.
requirements and treatment for enameling, B (11) 322*b*.
roughness, effect on surface texture of glass, (3) 66*d*.
samples, miniature ceramic crucibles for burning, P (11) 308*i*.
semimetallic elements, structure and properties, XIV, (4) 120*g*.
sheet, heavy duty, white and black enamels for, (8) 208*a*.
sheet, method of coating, P (2) 37*h*.
sintered, effect of porosity on structure, (6) 172*i*.
systems. See *Systems*.
thin gage, WC coatings for, (3) 72*h*.
titanium boride coatings on, P (2) 38*c*.
transition, diborides of, Hall effect and electrical conductivity of, (11) 317*f*.
transition, ternary carbides of, with Al and Mg, (4) 101*h*.
-working processes, high-temperature, lubricants for, (7) 183*f*.
Methylcellulose. See *Cellulose*.
Mica. See also *Vermiculite*.
crystals, optimum temperature for growing, (1) 20*e*.
deposited by electrophoresis, hardening of, P (4) 110*i*.
dioctahedral, determination in submicroscopic grain sizes, (6) 167*j*.
dust, effect on health of workers, (2) 60*f*.
fine, concentration of, (9) 253*j*.
flakes, P (3) 84*d*.
fluor-, -fluoramphibole ceramics, method of making, P (2) 49*a*.
Pb and Ba disilic, synthesis of, (9) 247*b*.
synthesis and properties, (7) 201*e*.
fluorphlogopite, isomorphous substitution for Si in, (4) 115*b*.
making lamellar sheets of, P (11) 315*h*.
synthetic, etching of, (7) 199*c*.
formation of fine holes in, (11) 313*f*.
iron-rich, hydrothermal conversion of muscovite to, (4) 114*c*.
materials, control of crystal growth in, P (2) 55*e*.
minerals, B (10) 299*d*.
muscovite, alteration of absorption spectrum by KBr pellet preparation, (6) 171*g*.
hydrothermal conversion to kalsilite and iron-rich mica, (4) 114*c*.
structure, (11) 319*h*.
treated with molten $LiNO_3$, removal of reaction products, (6) 170*i*.
in 1961, (3) 82*e*.
nonhydroxyl, in ceramoplastic material, P (2) 49*c*.
phlogopite, crystal structure of, (8) 226*f*.
plate, substage, in study of interference figures, (4) 107*c*.
polysynthetic twinning of, (4) 118*b*.
reactions with NH_4Cl and $MgCl_2$ solutions, (4) 119*c*.
sheet, synthetic, reconstituted, P (8) 220*c*.
survey of, (8) 225*d*.
synthetic, B substitution in, (7) 198*b*.
crystal growth program, (1) 19*j*; (1) 20*a,c,e*.
from low cost materials, (8) 225*j*.
method of making, P (8) 220*f*; P (9) 249*b*.
powder method for measuring dielectric constant and loss, (8) 223*d*.
reducing thermal gradients in hot-pressing of, P (11) 313*i*.
thin sheets, machine for silk screening with silver paste, (9) 247*g*.
Micanite, Indian, properties of, (3) 82*f*.
Microcline, decomposition in hot water, (5) 142*a*.
Microhardness. See *Hardness*.
Microlites, in glassy volcanic rocks, (6) 170*d*.
Micromeritics. See *Particles*.
Micrometers, comparison, infrared, P (11) 320*d*.
Microminiaturization, advances in, (7) 190*j*.
Microscopes, as control in mineral dressing, (8) 225*e*.
with controlled atmosphere hot stage, for observing glass melting, I,II, (7) 184*g*.
electron, application to ceramics, B (4) 124*e*.
emission, in study of ceramic material, B (10) 300*f*.
means for varying picture brightness, P (8) 230*d*.
and optical, in study of morphological properties of UO_2, (7) 201*b*.
polystyrene-silica replica technique for relocating areas for examination, (10) 286*a*.
preparation of clays for study by, (5) 138*c*.
in study of Al oxides and hydroxides, (6) 113*i*.
in study of ceramic surfaces, (9) 251*j*.
in study of dissolution of metal at anode, B (9) 262*f*.
in study of ferroelectric domains in thin $BaTiO_3$ single crystal films, (6) 163*i*.
in study of glass surfaces, (1) 6*d*.
in study of morphological processes in glass polishing, (3) 67*d*.
in study of mullite, (8) 229*h*.
Microscopes, electron (*continued*)
in study of nonmetallic inclusions in iron and steel, I, (6) 155*j*.
in study of structure of glass, (3) 66*i*.
in study of superlattice in serpentine, (6) 173*b*.
in study of thin films of laboratory glasses, (2) 41*b*.
high temperature, in observation of glass melting, (8) 209*j*.
hot-stage, application to technical problems, (3) 80*g*.
microhot stage, (11) 313*h*.
petrographic, crystal sphere orienter for, (10) 285*j*.
phase contrast, for accurate determination of minerals in combating dust and silicosis, (4) 111*i*.
pyrometer, direct-reading radiation type, P (7) 196*b*.
spindle stage, temperature control, (6) 168*d*.
spindle stage, using hypodermic syringe, (6) 168*c*.
tube, multifilar measuring attachment, P (10) 287*b*.
universal stage, measurements, refraction corrections for, (9) 257*a*.
Microscopy, of belite, (7) 199*i*.
of clinker minerals, (7) 181*c*.
electron, carbon films for, (11) 312*h*.
dark field, in radiation damage in graphite, B (8) 233*e*.
and optical, in observation of crystal imperfections, B (9) 261*e*.
of Quetrequile clay deposit, (6) 169*g*.
of radiation damage in graphite, B (8) 233*g*.
of sintered beryllia, (11) 317*i*.
study of acid-treated kaolinite, (7) 199*c*.
in study of crystallization of glass coatings on metal, (8) 207*j*.
transmission, of ceramic single crystals, (10) 286*g*.
electron probe, in research on refractory materials, (1) 13*e*.
hot-stage, in study of mineralogy of low-shaft furnace slags, (2) 44*f*.
incident-light, polarization interferometric methods in, (11) 313*b*.
in investigation of Hirschau kaolinite, (4) 109*f*.
optical and electron, in study of cleaning processes for borosilicate glass, (9) 239*h*.
replica, high-temperature, of kaolinite, (7) 201*f*.
replica method, polystyrene-silica, for relocating areas for examination in electron microscope, (10) 286*a*.
replicas, obtaining in selected areas, (9) 251*h*.
of steam-cured asbestos portland cement products, (9) 236*i*.
technique, for alumina ceramics, (4) 101*e*.
thin sections, quick identification of potash feldspar, plagioclase, and quartz for, (4) 107*g*.
universal stage, errors in measurement of $2V$ with, (11) 317*j*.
Microstructure. See *Structure*.
Milling. See *Crushing and grinding*.
Mills. See also *Crushing and grinding apparatus*.
abrasive, for removing iron from glass sands, (1) 25*d*.
for autogenous grinding, P (6) 170*f*.
for autogenous grinding of friable material, P (6) 171*c*.
ball, abrasive grinding balls for, P (3) 63*f*.
batch, small-ball, for dispersing pigments in liquid vehicles, P (2) 51*a*.
effect of grinding ball size on output, (1) 22*e*.
grinding in, I, (10) 288*h*.
for milling catalysts under pressure of reactive gas, P (2) 51*i*.
pebble, and vibratory, (10) 269*c*.
sound actuated control system for, P (1) 23*g*.
for finish grinding of cement clinker, (2) 35*c*.
grinding, ceramic balls for, P (4) 106*h*.
effect of, study by magnetic measurements, (3) 76*i*.
parameters of, (10) 284*d*.
segregating and recombining feed for, P (6) 171*a*.
supplying heat to, P (6) 171*a*.
swinging type with plurality of drums, P (7) 197*i*.
hammer, with traveling breaker plate, P (11) 315*g*.
pug, automatic, (10) 273*d*.
reduction, synthetic charge for, P (2) 51*h*.
with rollers and grinding disk, P (7) 195*a*.
rotary drum, for comminuting ores, P (3) 83*c*.
tube, for grinding moist solid material, trunnion for, P (10) 285*c*.
turbo, P (9) 254*j*.
vibration, P (11) 315*h*.
vibratory, for refractory raw materials, (10) 284*h*.
Mineral fibers. See *Glass, fibers; Mineral wool*.
Mineralizers. See also *Fluxes*.
effect on lime burning process, (11) 302*f*.
for $MgCO_3$ and MgO, F ion as (6) 159*j*.
for silica refractories, (6) 161*f*.
Mineralogy, of Al_2O_3-SiO_2-H_2O in pyrophyllite deposits of N. Car., (4) 109*f*.
of barium cements, effect on hydraulic properties, (7) 180*d*.
of chromites, Indian, (8) 228*j*.
clay, of carboniferous sediments, relation to chemical data, (11) 314*j*.
in petroleum industry, recent advances, I, (3) 83*c*; II, (6) 170*h*.
of clays of red and lateritic soils, (3) 82*g*.
of commercial vermiculites, (11) 314*h*.
composition, of $BaTiO_3$, effect on physical properties, (8) 219*e*.

Mineralogy, composition (*continued*)
of kaolinite-mica-quartz clays, (1) 317*h*.
of western Canadian clays, (2) 54*c*.
of Whitemud formation clays, effect on use, (10) 292*d*.
Dana's System of, Vol. III, Silica Minerals, B (4) 122*h*.
of low-shaft furnace slags, determination by hot stage microscopy, (2) 44*f*.
mineralogical composition, of reaction products in system $CaO-SiO_2$, (8) 204*j*.
Minerals. See also *Raw materials; Rocks;* and specific types.
accurate determination with phase contras microscope in combating dust and silicosis (4) 111*i*.
apparatus for thermally working, P (9) 254*a*.
Brazilian, DTA of, I,II, (3) 82*i*.
cement, anhydrous and hydrated, thermochemistry and thermodynamics of, (7) 182*i*.
in cement clinker manufacture, properties of, (7) 181*c*.
chemical analysis of, computer program for, (6) 167*j*.
clay. See *Clays*.
clinker, microscopy of, (7) 181*c*.
clinker, synthesis and X-ray diffraction, (7) 182*e*.
components, of ball clays, (8) 225*c*.
compos tion, of clays, variation on firing, (7) 197*e*.
constitution, of Ordivician shales of Ontario, (10) 295*a*.
dressing, microscope as control in, (8) 225*c*.
ferromagnesian silicate, Mg^{2+}-Fe^{2+} distribution in, (7) 199*j*.
ferromagnesian silicate, magnetic susceptibility as measure of total Fe and Mn in, (4) 116*e*.
filter aids, P (6) 171*e*.
fine-grained, sintering of, P (4) 111*f*.
F-containing, production of fluorine compounds from, P (3) 84*i*.
heavy, epoxy resin for study of, (6) 167*j*.
heavy, rapid studies by liquid immersion, (1) 29*j*.
hydrated cement, effect of synthetic CO_2-containing aqueous solutions on, (1) 2*f*.
identification, Scifax DTA index as aid in, B (2) 62*h*.
industrial, beneficiation methods, (3) 83*f*.
Canadian developments, (10) 298*c*.
future of construction products from, in Canadian industry, (3) 82*j*.
long-spacing mica-like, structure, genesis, and composition, (8) 170*a*.
machine for processing, P (3) 83*j*.
materials, sorptive, ASTM standard for, B (9) 259*c*.
microspectrochemical analysis, (4) 107*c*; II, (6) 168*c*.
in mines and quarries, loading and transport, P (2) 55*j*.
mixtures, X-ray determination of quartz in, (9) 252*b*.
nonmetallic, direct-reading semiquantitative spectrochemical analysis of, (1) 27*h*.
high temperature, (10) 269*d*.
inclusions in iron and steel, study with electron microscope, I, (6) 155*j*.
mechanism of wear of, (8) 228*c*.
pure synthetic, produced in solar furnace, (5) 140*h*.
quantitative spectral, method, (4) 119*e*.
rock-forming, dissolved products of, I,II, (11) 316*f*.
Vol. I, ortho- and ring silicates, B (5) 151*g*; Vol. 2, B (9) 264*d*; Vol. 3, B (10) 299*d*.
separation, heavy-liquid, diluent for bromoform in, (4) 107*c*.
separation, using hydrofluoric acid, (4) 107*b*.
shaped bodies of, binder for, P (4) 104*d*.
silica, B (4) 122*h*.
silica, radiation coloration of, (4) 119*f*.
silicate, formation of fine holes in, (11) 313*f*.
spectrochemical analysis of, (1) 30*e*.
thermal analysis of, (5) 144*c*.
Virginia, localities, (10) 289*c*.
yearbook, 1961, Vol. I-III, B (6) 176*h*.
Mineral wool. See also *Glass, fibers*.
fibers, apparatus for making, P (1) 10*f*; P (2) 41*c,d*.
refining method and apparatus, P (2) 43*b*.
rotors for apparatus for making, P (1) 12*e*.
Mines and mining, abrasion-resistant materials and equipment for, (9) 254*h*.
Canadian, importance of lithium in, (3) 82*e*.
loading and transport of minerals in, P (2) 55*j*.
mine roof coatings, asbestos fibers in, (2) 55*b*.
modernization of methods, (9) 253*h*.
in potash operations, (10) 288*i*.
Russian, for refractories industry, (7) 197*h*.
stabilization of rock roofs, P (9) 254*h*.
underground limestone, use of ammonium nitrate in, (10) 288*d*.
underground nuclear explosions for, (1) 25*e*.
Western Australia Government Chemical Laboratories Report for year 1961, B (11) 322*i*.
Miscibility. See also *Solubility*.
of synthetic cordierite at low temperature and pressure, (4) 116*a*.
Missiles. See *Space vehicles*.
Mixers, with air jets, for pulverulent material, P (10) 285*g*.
continuous dry, P (9) 250*a*.
for discrete materials, P (4) 106*i*.
double cone, P (10) 285*d*.
glass, in feeder channel, (8) 224*e*.
for granular materials, P (8) 222*a*.
horizontal drum, variation of operating conditions, (3) 79*j*.
Mixers (*continued*)
liquid-solids, for batch mixing, (6) 167*b*.
with mulling wheels, P (8) 222*e*.
for particulate materials, P (3) 89*a*.
for powdered or granular materials, P (8) 222*d*.
rotor for, P (5) 141*e*.
vacuum gypsum, P (10) 268*c*.
Mixing, conditions for providing optimum degree, (3) 79*j*.
determination of proportions of mortars, (3) 64*e*.
direct, in structural clay products batch preparation, (10) 284*f*.
ideality of, in hydrothermal fluids, increase with temperature and concentration, (6) 173*g*.
of multicomponent bodies, apparatus for continuous proportioning, P (7) 194*j*.
ratio, of fine powders, methods for estimating, (7) 181*b*.
sequence, importance in using set-retarding agents with portland cement, (10) 267*b*.
Mobility, of concrete mixtures, device for measuring, (6) 154*b*.
of free charges, mechanisms for, (7) 192*h*.
in polar semiconductors, (8) 219*b*.
Models, geometric, for quartz-cristobalite transformation, (6) 173*f*.
of glass tanks, dimensional analysis, (7) 184*c*.
kinetic, for solid-state reactions, (2) 57*c*.
statistical, for crystalline structure of mullite, (3) 89*a*.
structural, testing of, (7) 195*h*.
structural, testing, compensation for time effect in plastics, (4) 107*i*.
for study of glass flow in tank, (1) 9*h*.
Modernization, of cement plant, (2) 35*e*.
Modulus of elasticity. See *Elasticity*.
Modulus of rupture. See *Rupture*.
Moisture. See also *Humidity; Steam; Water*.
apparatus for measuring, radiant energy source, P (2) 53*b*.
content, measuring and controlling in materials, P (9) 250*d*.
control, for ceramic products, improved method, (3) 71*g*.
effect on modulus of rupture of ball clays, (2) 54*f*.
in furnace atmosphere, effect on H defects in glass-coated steel, (1) 4*c*.
in gases, measurement, (8) 223*e*.
of granular materials, indicator for, P (9) 252*h*.
of granular materials, instrument for measuring, P (6) 168*i*.
in liquids, measurement of, (7) 195*d*.
in milling, electrical measurement, P (9) 252*e*.
movement, in plastic clay, (11) 305*f*
removal, from analytical samples, dryer for, P (8) 223*g*.
in solids, apparatus for measuring, P (6) 168*h*.
measurement techniques, (6) 168*b*.
nuclear measurement and control, (9) 251*a*.
Molding, aids, for ceramics, aliphatic amines as, (8) 217*d*.
blow, of hollow glass articles, P (9) 241*e*.
green sand, cellulosic additives, P (8) 215*g*.
green sand, starch as additive, P (8) 216*h*.
injection, of ceramic insulating materials, (2) 47*d*.
injection, machine, P (1) 23*a*.
materials and methods, B (3) 92*f*.
method and apparatus, P (3) 80*d*.
mixtures, stickiness of, (8) 214*j*.
plastic, of refractory brick, (6) 160*a*.
pressure, of bodies of low uniform shrinkage, P (9) 246*d*.
of refractory brick, P (1) 17*c*.
of saddles, apparatus for, P (3) 74*j*.
shell process, B (9) 259*g*.
Molds. See also *Slip casting; Slips*.
blow, P (9) 250*a*.
bottoms, for top pouring killed steel graphite refractories for, (7) 187*e*.
box, liners, lubrication of, (4) 101*j*.
casting, ceramic fibers in, P (6) 161*j*.
casting, hot top casing for, P (5) 133*i*.
ceramic-coated, ultrasonics for stripping, (2) 37*g*.
cleaning, maintenance, and storage, (4) 98*g*.
composite, for continuous casting, P (2) 45*c*.
effect of temperature on, (2) 47*b*.
foundry, highly swellable clays for, P (4) 102*c*.
foundry, improvement of, P (1) 16*c*.
glass, automatic contour superfinishing of, (4) 98*a*.
care, cleaning and maintenance, (6) 156*a*.
clamping mechanism for, P (4) 99*a*.
with controlled cooling, P (10) 272*g*.
diffusion of metals in relation to, (4) 98*b*.
increasing life of, (4) 98*i*.
lubricant for, P (1) 11*b*.
metallizing of, (4) 98*c*
selective cooling means, P (6) 157*a*.
silicone lubricants and colloidal graphite for surface treatment, (4) 99*a*.
glass bending, P (9) 242*a,b*.
with movable sections, P (10) 271*j*.
with shaping rail sections, P (10) 272*b*.
glass container, cast iron for, (3) 65*j*.
ingot, extruded fireclay ribbon for, P (10) 277*a*.
ingot casting, forming hot top at different levels, P (6) 162*h*.
inspection techniques, (4) 98*h*.
mixture, for foundry process, P (4) 102*g*.
with movable sections, for bending glass sheets, P (9) 242*a*.
multiple injection apparatus, P (11) 312*a*.
perforated metal, for slip casting, (8) 221*i*.
plaster, drying of, P (1) 23*c*.
plaster for, vacuum de-airing of, (3) 64*g*.
plaster insert for steel mold, for forming meta powders, (11) 312*a*.
of porous carbon, for handblown glassware, (7) 184*j*.
Molds (*continued*)
press, for pressing fireclay products, strength and abrasion resistance, (7) 188*j*.
press, for pressing MgO and fireclay refractories, (7) 189*a*.
for refractories, acid hydrolyzed isopropyl silicates as binders, P (4) 103*b*.
sag, for bending glass sheets, P (4) 100*d*.
segment, forming process, P (2) 45*j*.
shell, aqueous coatings for production of, P (1) 15*g*.
ceramic coatings for, (6) 159*i*.
multilayer, P (6) 162*j*.
parting agent for, P (6) 162*a*.
refractory, P (1) 16*f*.
testing of tensile strength, P (2) 46*f*.
steel, silica flour as wash for, (1) 15*e*.
of water-receptive ceramic body, fired at high temperature, P (5) 133*b*.
water sensitive, of fast collapsibility, P (1) 17*e*.
Molybdates, of divalent metal ions, single crystals, preparation, (11) 318*a*.
Molybdenum, boride, production of, P (10) 277*g*.
disilicide, process for producing, P (2) 46*a*.
disulfide, reduction of silica content, P (11) 315*d*.
(V) oxide, magnetic, with ordered perovskite structure, (7) 191*h*.
foil, soldering by means of Mo carbide, P (2) 50*b*.
as high temperature pressure sensitive material, P (11) 311*g*.
interaction with CrB_2, (10) 294*b*.
in metal-to-ceramic seal, P (9) 249*a*.
nitrides, preparation and properties, (4) 118*j*.
oxide, crystals, growth mechanism of, (6) 171*i*.
properties, constitution, and fabrication, B (7) 202*c*.
reaction tube, for high temperature technique, (6) 172*d*.
silicide, -Al oxide, sintered, for refractories, P (6) 162*d*.
sulfide, analysis of dislocations in, B (9) 262*a*.
Montmorillonite, adsorption of ethylene glycol and glycerol by, (4) 107*b*.
adsorption of glycine and di-, tri-, and tetrapeptides by, (10) 290*f*.
cation migration in, (7) 198*f*.
electrolytic production of chlorite-like substances from, (11) 317*g*.
exchangeable H ions in, (4) 115*d*.
high temperature reactions and classification, (4) 116*c*.
H-, suspensions, chemical stability of, (3) 86*a*.
Kansas, occurrence and bleaching properties, (3) 82*h*.
minerals, B (10) 299*d*.
NH_4, thermal decomposition of, I, (11) 320*a*.
in rocks of Missourian stratigraphic sections (3) 82*b*.
Mortars. See also *Pozzolans*.
additives, P (9) 237*j*.
adhesion to wall tile, (3) 75*d*.
ASTM standard for, B (9) 259*a*.
cement, containing polyvinyl acetate emulsion, properties of, (8) 205*h*.
effect of aggregate grain size on sulfate corrosion, (7) 180*c*.
entrapped air in, (8) 204*b*.
percentage of voids in, (7) 181*d*.
relation between fracture and creep properties, (9) 237*g*.
cracks, effect of admixtures in prevention, (7) 180*c*.
determination of mixing proportions, (3) 64*e*.
dry air setting, bonding agent for, P (8) 215*f*.
efflorescence on, change in composition, (7) 178*g*.
hardened, color of, (7) 178*j*.
hardened, formation of cracks in, (8) 204*e*.
heat of hydration, drying shrinkage, and chemical resistance, (7) 180*d*.
lime, P (4) 96*g*.
lime, economics of promotion of, (2) 35*d*.
long-aged, prediction of mechanical strength, (11) 302*c*.
portland blast-furnace slag cement, effect of fineness of clinker and slag on drying shrinkage, (8) 204*g*.
properties, effect of entrained air, (7) 180*f*.
properties, effect of flocculation of cement, (8) 205*a*.
segregation, study by injection of ^{60}Co isotope (10) 268*a*.
specimens for measuring volume change and strengths of, (1) 3*j*.
staining, in brick walls, (11) 305*e*.
strength, effect of curing water, (8) 204*d*.
effect of media, (8) 206*a*.
of rapid-hardening portland cement, formula for estimating, (8) 205*d*.
structural, physicochemical interaction with medium, (1) 2*i*.
water vapor permeability, measuring of, (9) 237*d*.
Muds, ceramic, dispenser for, P (11) 309*g*.
red, from Al industry, chlorination of, (11) 314*h*.
Mufflers glass coated, P (9) 239*c*.
Mullite. See also *Refractories*.
bodies, torsional behavior at high temperature, (7) 196*b*.
conversion of veszpremite to, (10) 295*d*.
crystalline structure, statistical model for, (3) 89*a*.
crystals, formation of, I, (9) 256*j*.
crystals, polishing ability, (1) 1*i*.
effect of chemical additives on formation of B (2) 60*j*.

Mullite (*continued*)
formation, importance of reaction of kaolinite with Al fluoride to form amorphous metaphase, (10) 292*g*.
formation from sericite and mixtures with alumina and kaolin, B (4) 123*j*.
grogs, synthetic, (1) 15*b*.
growing from clay minerals, (6) 143*j*.
increase in acid refractory materials, (10) 274*d*.
oriented formation from Al-Si spinel, (3) 72*c*.
preparation for electron-optical study, (8) 229*h*.
solid solution, effect of iron oxide in, (11) 306*c*.
synthesis of, P (5) 136*h*.
synthetic, production of, (11) 306*j*.
thermal transformation of mullite to, (7) 201*d*.
thin films, preparation, (6) 165*c*.
Muscovite. See *Mica*.

Neodymium, in ferrites, P (3) 77*a*.
hexaboride, synthesis and properties, (11) 319*j*.
nitride, magnetic susceptibility of, (4) 119*b*.
oxide, systems. See *Systems*.
Nepheline, concentrates, recovery of alumina from, P (2) 55*j*.
crystallization of volcanic glass to, (11) 315*j*.
crystal structure and composition, (11) 314*i*.
decomposition in hot water, (5) 142*a*.
syenite, bodies, stability of forming characteristics (11) 309*c*.
effect of grain size and iron oxide on fusion (2) 54*h*.
as mullite builder, (9) 256*j*.
North Cape, for glass industry, (1) 25*j*.
Norwegian, B (10) 300*c*.
Neptunium, (IV), peroxide, solubility of, (7) 200*a*.
Neutralization, of concrete with fly ash, 5-yr tests, (8) 204*j*.
of concrete, measurement with radioactive CO_2, (8) 205*e*.
Neutrons, absorption, ceramic structural materials for, (10) 274*a*.
diffraction, pattern, of γ-Fe_2O_3, (3) 87*d*.
diffraction, in study of antiferromagnetic $MnTiO_3$ and $NiTiO_3$, (6) 173*j*.
fast, damage, at surface of metal oxides, (8) 227*j*.
flux of, measurement of, P (3) 69*i*.
long-wavelength transmission, in determination of defects in α-Al_2O_3 single crystal, (3) 89*g*.
in measuring moisture in solids, (9) 251*a*.
source, method of making, P (5) 133*c*.
Nickel, addition to MgO for strength improvement (4) 97*a*.
boronization, linear time dependence of depth (2) 37*h*.
difluoride, crystal structure determination, (10) 296*h*.
film, for attaching W carbide particles to ferrous metal surface, P (1) 2*a*.
germanate, systems. See *Systems*.
ion, as indicator of structure of Na aluminosilicate glasses, (3) 67*j*.
kinetics of gas boronizing of, (2) 37*b*.
manganate, crystal structure and ferrimagnetism in, (4) 113*d*.
$NiMnO_3$, ferrimagnetic resonance in, (4) 114*c*.
nitrate, solid state reaction with hydrated and α-alumina, (1) 30*b*.
oxide, alkali- and iron-doped, physicochemical properties, (8) 219*d*.
effect of MgO on reduction of, (10) 294*g*.
electric conductivity as function of temperature and equilibrium O pressure, (9) 247*b*.
electric conductivity and thermodynamic equilibrium in, (3) 76*g*.
electrical conductivity near Curie temperature, (3) 86*b*.
p-conducting, effect of added oxides, B (9) 260*e*.
systems. See also *Systems*.
thermodynamics of vaporization, (3) 89*j*.
plating, galvanic, cleaning and pickling methods in, (3) 65*d*.
in protection of graphite surfaces, P (4) 103*a*.
solution, in composite coatings, (8) 207*d*.
supports, for oxide cathodes, P (2) 49*h*.
surface, joining of graphite surface to, P (10) 269*e*.
systems. See *Systems*.
titanate, antiferromagnetic, neutron diffraction study of, (6) 173*j*.
titanate, antiferromagnetism in, (10) 279*f*.
transport by chemical reaction, (5) 142*c*.
Niobates, as ferroelectrics with layered structure (7) 192*d*.
as high-temperature piezoelectric ceramics, (9) 248*f*.
Niobium, α-Nb_2O_5, electrical conduction in, (9) 256*f*.
α-Nb_2O_5, near-stoichiometric, electric conductivity of, (2) 56*i*.
boride, production of, P (10) 277*g*.
dioxide, crystal structure of, (5) 142*i*.
fluoride-free, production of, P (5) 141*a*.
hydroxide, complexes with dials, (10) 291*a*.
monoxide, structure of, (4) 115*g*.
nitride phases of, (4) 117*a*.
oxidation, low temperature, (10) 296*e*.
oxide, of ABO_4 type, (4) 121*g*.
electrical conductivity as function of O pressure, (8) 229*j*.
preparation and transport in temperature gradient, (6) 172*c*.
systems. See *Systems*.
thin films, current-controlled negative resistance in, (10) 280*b*.
oxonitrides of, (4) 117*g*.
pentoxide, systems. See *Systems*.

Niobium (*continued*)
properties, constitution, and fabrication, B (7) 202*c*.
separation from Ta, P (3) 89*j*.
systems. See *Systems*.
-1% Zr alloy, oxidation characteristics, (11) 302*j*.
Nitrates, annealing of radiolytic damage in, I, (10) 290*i*.
inorganic, radiation-induced decomposition in, (10) 296*a*.
Nitrides, of B, Al, Si, and Ti, physical and mechanical properties, (6) 161*c*.
cerium earth, (4) 119*b*.
of Cr, Mo, and W, preparation and properties, (4) 118*j*.
of Nb, B (7) 202*d*.
oxo-, of Nb, (4) 117*g*.
phases, of Nb, (4) 117*a*.
Nitrogen, reaction with Ta at 800° to 1300°C, (11) 318*f*.
in synthesis of TiN, (5) 146*i*.
systems. See *Systems*.
Nobleite, hydrous calcium borate from Calif., (4) 110*c*.
Noise, characteristics, of cold cathodes, (7) 192*g*.
Nomenclature, electrical, (3) 80*g*.
of materials with electronic or electrical properties, (4) 104*f*.
trade, for floor and wall tile, (4) 103*f*.
of viscosity, (2) 52*j*.
Nomographs, for giving equivalent lengths of pipe, (2) 51*a*.
Nonmetallic compounds, selection and fabrication, (6) 161*d*.
Nonmetals. See *Minerals, nonmetallic*.
Norstrandite, from Borneo soil, origin and properties, (10) 288*h*.
from Guam limestone, properties and occurrence, (10) 288*g*.
Nozzles, low pressure atomizer, for oil burners, P (6) 169*e*.
Nuclear industry, powder metallurgy in, Plansee Proceedings, 1961, B (3) 92*j*.
Nuclear materials, ceramic, measurement of thermal conductivity of, (1) 71*i*.
ceramic, symposium on, (11) 306*h*.
Nucleation, in supercooled iron alloys, effect o oxides, B (9) 262*c*.
surface, of glass fibers, B (11) 320*i*.
of Zn on glass, (9) 241*c*.
Oils, fuel, in ceramic industry, (5) 140*c*.
fuel, peculiarities of, (2) 53*g*.
gasification of, for ceramic industry, (9) 253*c*.
heavy, determination of S in by tritium bremsstrahlung absorption method, (4) 108*f*.
heavy, relation between sulfur content and SO_3 in cement clinker, (7) 181*i*.
immersion, epoxy resin for, (6) 167*j*.
Olefins, polymerization of, inhibition by treatment of zeolitic molecular sieves, P (2) 60*b*.
Olivine, DTA of, with and without vacuum, (10) 291*f*.
solid solutions, applications of thermodynamic calculations on, (2) 59*a*.
Opacifiers, in oriental glass, B (11) 321*e*.
in porcelain glazes, zircon as, (10) 279*c*.
SnO_2, $ZrSiO_4$, and TiO_2, for glazes for steatite, (11) 309*d*.
Zr compounds as, (9) 245*i*.
Optical materials, fibrous, applications for electronics, (3) 76*j*.
Optical properties, of borate glass, (8) 209*f*.
of conducting tin oxide films, (6) 175*g*.
constants, of MgO in infrared region, (9) 256*d*.
constants, of ortho- and ring silicates, B (5) 151*g*.
of LiF, effect of radiations, (10) 294*h*.
of synthetic ruby, (2) 58*f*.
of tin oxide films, (6) 174*c*.
Ores, analysis, spectrophotometric, (3) 81*e*.
apparatus for comminuting, P (3) 83*c*.
crusher, with overload release, P (11) 315*c*.
electrostatic separators for, P (10) 289*g*.
excavation by blasting, charge holder for, P (11) 315*h*.
fine, jet type apparatus for classifying, dewatering, and recovering, P (2) 55*j*.
Mg compound recovery from, P (8) 226*c*.
phosphate, wet beneficiation of, P (8) 226*c*.
pulverizer, with centrifugal impact action, P (10) 289*i*.
quantitative photometric sorter, P (10) 290*e*.
sinter, cooling of, P (1) 3*a*.
sorting machine, P (10) 289*j*.
Organic compounds, as additives for lightweight refractories, P (2) 46*g*.
as additives for steatite bodies, P (2) 47*g*.
in decoration of ceramics, (4) 109*b*.
halogenated solvents, ASTM standard for, B (9) 259*c*.
use in forming inorganic fibers, (8) 214*e*.
Orientation, of diamonds for tools, (9) 235*j*.
effects, in perthites, (4) 114*b*.
of ferrites, P (3) 78*b*.
of ferromagnetic particles, P (3) 78*c*.
Orthoclase, surface energy, direct measurements, (8) 227*g*.
Oscillations, de Haas-van Alphen type, in graphite, (4) 112*c*.
oscillator phenomena in extrinsic semiconductors, (4) 117*g*.
Oscillators, ceramic, 3-terminal, (7) 192*c*.
microwave, ferromagnetic resonance-tuned, (10) 280*a*.
quartz crystal, heat sinks for, P (4) 105*e*.
Osmium, compounds, with ordered perovskite structure, (1) 26*j*.
Osumilite, -type phase, in system MgO-Al_2O_3-SiO_2, (6) 173*h*.

Ovens. See also *Furnaces; Kilns*.
biscuit, reduction of firing time in, (11) 314*c*.
continuous pin-type conveyor for, P (9) 250*e*.
Oxidation, behavior, of Nb-Cr alloys, B (7) 202*g*.
characteristics, of Nb-1% Zr alloy, (11) 302*j*.
in graphite channels, I-IV, (6) 160*d*.
low temperature, of Nb and Ta, oxides of, (10) 296*e*.
of metal powders, apparatus for, P (8) 221*e*.
resistance, of refractory metals, B (7) 202*i*.
-resistant coatings, for refractory metals, (3) 65*d*.
of $SrTiO_3$, single-crystal, effect of dislocations, (3) 86*j*.
thermal, of silicon, (1) 30*f*.
of UC, (10) 296*c*.
wet, in determination of S in silicate rocks, (9) 251*a*.
Oxides. See also *Rare earths* and specific types.
of Al, Mg, Th, Be, and Zr, physical and mechanical properties, (6) 161*d*.
as bases for CdS photoresistance cells, (3) 77*c*.
ceramics, as barrier-layer dielectrics, (10) 279*i*.
effect of grinding method and medium on sintering of, (3) 79*f*.
mechanical properties of, B (3) 91*g*.
physical chemistry and technology, B (2) 61*i*.
thermal expansion in air to 2200°C, (10) 276*c*.
classification according to effect on surface tension of silicate melts, B (11) 321*a*.
as coatings, (9) 238*j*.
crystals, growing of, (3) 86*j*.
crystals, refractory, preparation, P (3) 74*j*.
double, with layer structures related to perovskite, II, (11) 317*b*.
double, structural studies, (1) 29*b*.
for ferromagnetic body, P (5) 136*b*.
films, reaction with supporting ceramic substrates, (6) 165*c*.
finely divided, burner for production, P (8) 224*f*.
fused, study by physicochemical methods, B (10) 300*f*.
glass-forming, criteria of, (9) 240*h*.
inorganic metal, composition, P (1) 11*f*.
of low-temperature oxidation of Nb or Ta, (10) 296*e*.
metal, composition of, P (10) 298*f*.
effects on alumina porcelain, (1) 17*h*.
fast neutron damage to surface, (8) 227*j*.
formed by explosives, properties of, (6) 174*i*.
infrared spectra of, (5) 144*i*.
method of preparing, P (4) 111*b,c*.
preparation of gels of bivalent and trivalent, (1) 27*b*.
and metals, high-melting mixtures, for abrasives P (3) 63*i*.
mixed, in coatings, P (3) 65*f*.
mixed metal, electrolytic production, P (5) 141*b*.
molten, counterbalanced sphere viscometer for use with, (11) 313*d*.
in nuclear reactor fuel elements, importance (10) 274*b*.
reducing acidity of, P (2) 55*e*.
reduction by phosphine, for producing phosphides, (7) 192*e*.
refractory, single crystal, growth of, (5) 144*a*.
refractory mixed, with perovskite structure, synthesis of, (9) 257*i*.
surface area, determination by heat of immersion, (6) 172*j*.
whisker growth, on metals at high temperature (6) 173*f*.
Oxometallates, studies of structure, (1) 29*b*.
Oxygen, band, in MgO, (4) 117*h*.
B-, bond, energy and length of, (10) 292*b*.
in chemical sample, determination by radioactivity, P (9) 252*d*.
for combustion and heating flames in glass industry, (2) 40*f*.
concentration, change with temperature of Ni and Co oxide solid solutions, (6) 171*i*.
concentration, in solution in electrolyte, P (8) 224*c*.
determination, P (8) 224*d*.
diffusion in vitreous silica, (3) 66*g*.
effect on photoluminescence of PbS films, (5) 135*b*.
refractories in fixed basic open-hearth furnaces, (6) 161*a*.
ultraviolet optical absorption bands of MgO, (9) 256*d*.
excess, in glass, effect of, B (11) 320*g*.
in gas, electrical measurement of, P (5) 139*h*.
in glass, chemical potential, I, (4) 98*j*; II,III (3) 67*i*.
isotope, fractionation between $CaCO_3$ and water, (2) 58*e*.
partial pressure, determination, P (8) 224*d*.
penetration into single CaF_2 crystals, (10) 296*f*.
pressure, Nb_2O_5 electrical conductivity as function of, (8) 229*j*.
process, for iron and steel making, I, II, (6) 160*j*.
in ruby and related glasses, chemical potential, I, (2) 40*j*.
selective enrichment for glass melting, (2) 41*f*.
sensor, electrolytic, P (4) 121*i*.
systems. See *Systems*.

Packaging. See also *Shipping*.
of bricks, automatically, (1) 13*a*.
construction, for glassware, P (3) 70*c*.
of hollow glass articles, P (9) 242*a*.
modern materials for, (1) 23*c*.
of sheet abrasive disks, P (1) 1*j*.
of stranded material, P (1) 10*i*.
of toiletries, in opal glass containers, (3) 67*b*.
Packing, of bathtubs, machine for, (4) 97*d*.
ceramic, hot-pressing of, (10) 275*d*.
Painting, conveyor hanger as mask in, (3) 79*g*.

Paints, ASTM standard for, B (9) 259*b*.
cement base, P (3) 64*i*.
heat-resistant, development for metals, (9) 238*c*.
Palladium, powder, in precision glaze resistors, (10) 281*i*.
Pallets. See *Materials handling*.
Panels. See *Building materials; Glass*.
Paper, special type for ceramic industry, (9) 254*g*.
Paraffin, wax, -UO_2 mixtures, enriched, production, (1) 29*i*.
Paragenesis, of ortho- and ring silicates, B (5) 151*g*.
Particles. See also *Colloids*.
classification, vortical, P (1) 23*d*.
clay, effect of configuration on properties, (1) 25*f*.
clay, relation to laminations, (9) 243*b*.
contaminant, in fluids, method of testing, P (10) 287*a*.
counters, light scattering, (8) 223*a*.
counting, scanning apparatus, P (8) 224*a*.
density, of porous solids, apparatus for determination, (7) 195*d*.
differentially heated, separation method, P (10) 289*h*.
disintegration apparatus, P (5) 140*j*.
division of, in initial stage of liquid phase sintering, (4) 118*g*.
dust, apparatus for measuring, P (9) 252*e*.
fine, packed in layers, fluidization of, I, (8) 221*c*.
fine, radioactive fission product rare gases in phase change study in, (6) 176*a*.
growth, diffusion-controlled, surface energy effect, (3) 89*i*.
microscopic, analysis of, P (1) 24*c*.
packing, of refractory clay bodies, relation to thermal expansion, (3) 72*g*.
size, of abrasives, (6) 153*f*.
of aggregate, effect on sulfate corrosion of cement mortars, (7) 180*c*.
of Al_2O_3, control by use of specific surface measurements, (9) 252*j*.
average, determination, P (8) 224*d*.
of brucite, effect on solubility, (7) 200*g*.
of chamotte, effect on sanitary ware properties, (1) 17*i*.
classification of methods for determining, (7) 195*i*.
control in ground solid or crystallized materials, (1) 25*h*.
determination, precision of air permeability methods in, (6) 174*h*.
determination, variance analysis in, (5) 139*e*.
effect on saturation magnetization of barium ferrite powders, (1) 19*c*.
effect on sintering of Al_2O_3, (7) 200*c*.
effect on thermal properties of serpentine minerals, (5) 143*c*.
effect on transverse bend strength of Al_2O_3 and MgO, (7) 198*j*.
measurement, I-V, (8) 223*g*; VI, (10) 286*i*.
measurements, membrane filters for, (7) 194*i*.
of nepheline syenite, effect on fusion, (2) 54*h*.
of raw materials, effect in porcelain manufacture, V-VIII, (8) 217*j*.
reduction, I,II, (10) 269*e*.
reduction, literature for 1961–62, (9) 250*b*.
reduction, methods and equations, (1) 22*f*.
and size distribution, apparatus for determining, P (10) 287*a*.
and size distribution, effect on properties of $BaTiO_3$, (8) 219*e*.
Whitby centrifuge in determining, (8) 223*b*.
size analysis, device for fractionating deposits of dust for, (2) 52*c*.
importance of deflocculant, (10) 286*e*.
of kaolins by pipet method, (3) 80*g*.
rapid, of ceramic clays, packing-volume technique, (3) 83*c*.
of soils, (2) 54*j*.
size distribution, determined by sedimentation, automatic recorder for, (8) 222*h*.
of dispersed phases, automatic apparatus for measuring, (7) 195*g*.
of kaolinite, effect of exchangeable cations, (3) 87*e*.
relation to specific surface in comminution, (9) 237*c*.
of UO_2, measurement by radioactivation, (6) 173*f*.
small, adhesion measurements of, (9) 250*j*.
spherical discreet, high purity, of $Be(OH)_2$ or BeO, P (11) 308*g*.
toxic, in gas, apparatus for analysis, P (8) 224*c*.
width, microscope attachment for measuring, P (10) 287*b*.
Patents, European, on vitreous silica ware, review of, (7) 184*i*.
Minton, role in fine china, (10) 265*i*.
report of patent committee, (9) 258*c*.
Pegmatites, electrical separation of, (7) 197*f*.
Pelletization, to disperse nuclear fuel in fuel elements, (10) 275*a*.
of molten slag, P (2) 46*c*.
of shale fines, (11) 302*a*.
in structural clay products batch preparation, (10) 284*f*.
Pellets, ceramic, ultrasonic vibration in cold pressing of, (8) 221*d*.
drying and burning apparatus, P (11) 312*a*.
MgO, production for burning, P (11) 308*f*.
PuO_2-UO_2 irradiation, production of, B (8) 231*j*.
spherical, of dielectric material, for radomes, P (6) 166*c*.
Periclase, crystal growth, effect of impurities, (3) 73*h*.
formation from system MgO-H_2O, (5) 146*a*.
Perlite, expanded, dimensionally stable P (3) 83*f*.
expanded, in patching plaster, P (11) 302*g*.
furnace for expanding, P (10) 288*b*.
industry, review of, (6) 170*g*.
Oneida deposit, geology, processing and use of, (4) 110*d*.
as raw material, uses and properties, (10) 288*j*.
roasting, developments in, (2) 54*d*.
Permeability. See also *Porosity*.
air, methods in particle size determination, precision of, (6) 174*h*.
apparatus for measuring, (3) 81*h*.
of ferrites with garnet structure, (9) 248*b*.
in glasses, (9) 239*h*.
of Li ferrites, dispersion of, (3) 86*f*.
of MgO, sintered slip-cast, (7) 187*e*.
magnetic, time decrease in mixed ferrites, (11) 310*h*.
of Mn-Zn-ferrous ferrite, polycrystalline, (9) 247*j*.
in porous rock, rapid determination, (6) 168*h*.
of porous solids, (10) 296*g*.
properties, of porous material, apparatus for determining, P (3) 81*a*.
relation of pore size in materials for chemical industry, (3) 83*a*.
water vapor, measurement in mortar and concrete, (9) 237*d*.
Permittivity. See *Dielectrics, constant*.
Perovskites, Bi, properties of, (9) 257*f*.
double oxides with layer structures related to, II, (11) 317*b*.
structure, in hexavalent and pentavalent U compounds, (7) 198*g*.
structure, in synthesized refractory mixed oxide, (9) 257*i*.
-type $A^{II}{}^{+}B^{I}{}^{+}O_3$ solid solutions, quaternary systems of, (6) 175*a*.
Perthites, strain and orientation effects in, (4) 114*b*.
Petalite, in foamed ceramics, (4) 101*a*.
in sintered ceramic article, P (10) 277*f*.
-type phase, in system MgO-Al_2O_3-SiO_2, (6) 173*h*.
Petrography, in determining properties of asbestos cement, (9) 236*i*.
quantitative, of Paleozoic carbonate rocks of N. Mex., (4) 110*e*.
of shales from W. Va., (3) 82*i*.
Petroleum industry, clay mineralogy in, (3) 83*c*; II, (6) 170*k*.
Petrology, of Al_2O_3-SiO_2-H_2O in pyrophyllite deposits of N. Car., (4) 109*f*.
pH. See *Hydrogen ion concentration*.
Phase diagrams. See *Equilibrium studies*.
Phenacite, concentration by flotation, P (6) 170*h*.
Phenols, fused quartz- and nylon-reinforced, as thermal protection for fluorine-hydrogen thrust chambers, (4) 102*a*.
Phlogopite. See *Mica*.
Phonons, scattering, and glass inhomogeneity, (5) 129*j*.
Phosphates. See also *Glass* and specific types.
alkali metal, aqueous solution, for treating asbestos, P (3) 74*d*.
containing alkali and alkaline earth metals, polymorphism of, (4) 118*j*.
in enamels for Al, (10) 269*i*.
fluoro-, melts and crystals, vibration spectra of (5) 147*b*.
glassy, study of structure by use of Raman spectra, (6) 156*b*.
halo-, alkaline earth, increasing light output of, P (2) 49*b*.
infrared spectra of, (5) 144*i*.
ions, adsorption by hydrous ferric, chromic, and Al oxides, I,II, (3) 85*h*.
reactions in Al systems, I,II, (5) 145*j*.
rock, economical bulk handling, (11) 314*g*.
rock, quantitative analysis of, (5) 145*f*.
systems. See *Systems*.
waste materials, in production of ceramic ware, P (10) 279*d*.
white iron, preparation, P (4) 111*e*.
Phosphides, Li-Mn, crystal structures, (4) 115*i*.
obtaining by reduction of oxides by phosphine, (7) 192*e*.
transition, preparation and properties, (11) 318*i*.
Phosphorescence, of fused quartz and sapphire, (5) 145*b*.
spectro-, measuring instrument, P (9) 252*k*.
Phosphoric acid, in differential etching of $BaTiO_3$, (2) 56*f*.
manufacture, quality test of by-product gypsum from, (2) 35*d*.
Phosphors, alkali halide, doped with divalent metals, luminescence centers of, (5) 135*g*.
alkali halide, F centers with different thermal stability in, (6) 164*a*.
Ba pyrophosphate, Ti-activated, P (3) 78*h*.
Cd and Zn chlorides, activated with sulfides, (5) 135*h*.
Ca silicate, Sn-activated, P (3) 79*c*.
$CaSO_4$, $CaSO_4$:Mn, and $CaSO_4$:Sm, exoelectron emission of, (5) 134*j*.
CaS and SrS, exoelectron emission study of trapping levels in, (5) 134*h*.
Cr, luminescence kinetics of, I-IV, (6) 164*e*.
crystal, effect of bond type on electroluminescence, (6) 163*j*.
crystalline, intracrystalline reactions in, (5) 144*i*.
electroluminescent, finely divided, P (7) 193*i*.
improvement for lamp, P (5) 135*i*; P (5) 136*d*.
for lamp, P (7) 193*g*.
method of improving, P (2) 49*a*.
method of making, P (5) 137*c*.
Phosphors (*continued*)
for fluorescent screens, growing single crystals for, (4) 104*g*.
halophosphate, P (9) 249*j*.
for high vacuum technique, B (2) 61*d*.
infrared stimulable, quenching, stimulation and exhaustion studies on, (2) 58*a*.
metal sulfides for, P (2) 50*g*.
radiationless recombination in, (4) 119*a*.
scintillators, materials for use in, B (9) 263*a*.
silver halide, effect of infrared light on luminescence of, (5) 134*e*.
Sr borate, Cu- and Cu-Pb-activated, luminescence of, (6) 164*d*.
tungstate, effect of grinding on luminescent properties of, (5) 134*d*.
with ultraviolet emission, (6) 164*k*.
ZnS, decrease in luminescence intensity by crushing of, II, (5) 134*f*.
electroluminescence under excitation by square pulses, (6) 163*h*.
electroluminescent, improved maintenance for, P (6) 166*f*.
recalcined, preparation, P (1) 21*e*.
self-activated sublime, luminescence of, (6) 164*b*.
steady-state luminescence of, I,II, (5) 135*a*; III, (6) 165*i*.
treatment of, P (3) 79*a*.
ZnS:Cu, role of impurities in luminescence center formation, (6) 165*g*.
ZnS:Cu, study by exoelectron emission, (5) 135*e*.
ZnS:Cu,Al, light sums stored in, (5) 135*f*.
ZnS:Cu,Cl, buildup of blue and green luminescence bands in, (6) 164*c*.
ZnS:Cu,Cl, impedance changes induced by photoconductive effect in, (1) 19*h*.
ZnS:Cu crystal, photoconductivity and luminescence kinetics under pulse excitation, (6) 164*i*.
ZnS:Cu,Pb, regularities in optical flash in, (6) 163*f*.
ZnS,CdS:Cu, effect of electric field on radical-recombination luminescence of, (5) 134*j*.
ZnS:CuAl, excited at high frequencies, electroluminescence of, I, (10) 292*a*.
Phosphorus, adsorption and exchange in Manitoba soils, (5) 140*h*.
pentoxide, systems. See *Systems*.
vitreous, comparison with other forms, (7) 201*f*.
Photoconductive effect, CdS photoconducting articles, P (3) 78*g*.
in Cd and Zn sulfides, (4) 115*a*.
photoconductivity, in MgO crystals, (3) 88*a*.
photoconductivity, of ZnS:Cu crystal phosphor under pulse excitation, (6) 164*i*.
in ZnO single crystals, (3) 88*i*.
in ZnS single crystals, (4) 117*e*.
in ZnS:Cu,Cl phosphors, impedance changes induced by, (1) 19*h*.
Photoelectric cells. See *Cells*.
Photography, accurate reproduction of eyeglass lenses, P (7) 185*g*.
cameras, eliminating effect of improper diameter in Debye patterns, (6) 168*f*.
Philips powder, modifications for clay mineral work, (11) 313*i*.
for recording wear in grinding wheel, (3) 63*f*.
television, for remote viewing of flame, P (5) 139*c*.
X-ray diffraction, Pt expansion values for thermal calibration of, (3) 81*a*.
X-ray heating, in study of dehydration of boehmite, (5) 142*c*.
X-ray powder diffraction attachment, P (6) 176*c*.
high-speed, ruby laser in, (10) 279*f*.
multiple image masks, fly's-eye lens technique for, (9) 247*h*.
Photoionization. See *Ionization*.
Photometers. See also *Spectrophotometers*.
flame, in alkali determination, (8) 222*g*.
sample holder for, P (1) 31*d*.
Photometry, flame, in determination of Na, K, and Ca in Ni-Al_2O_3 catalysts, (10) 286*d*.
flame, for quantitative determinations, P (8) 223*i*.
of opal glass MS14, (5) 129*i*.
Photovoltaic effect, in ZnS single crystals, (4) 117*e*.
Physical chemistry. See *Chemistry*.
Physical properties, of abrasive grain, I, (6) 153*f*; II, (8) 203*i*.
of $BaTiO_3$, effect of composition, crystal phases, particle size and distribution, (8) 219*e*.
of carbon and graphite, (6) 159*f*.
of ceramic bodies at high temperatures, I, (11) 313*f*.
of flame-sprayed ceramic coatings, II, (1) 4*b*.
of graphite materials, (10) 276*e*.
of hard electrical porcelain, interpretation from density measurements, (11) 309*e*.
of kaolinite, changes on heating, (3) 82*d*.
of $PbZrO_3$-$PbTiO_3$ ceramics, factors affecting, (7) 191*k*.
of Lucalox alumina, (9) 254*b*.
of nonsilicate glasses in infrared region, (7) 184*g*.
of refractories, changes in, (3) 72*h*.
of sintered uranía bodies containing BeO, (10) 275*c*.
of Na_2O-B_2O_3-SiO_2 glass, (6) 156*i*.
of sputtered PbO_2 films, (8) 219*j*.
of TiC-WC-Co alloys, (2) 59*a*.
of UC, (11) 307*b*.
Physicochemical properties, of ceramic-meta systems, (5) 127*f*.
of clays, engineering aspects, B (5) 150*i*.
of feldspars, (4) 110*g*.
of ferric oxide particles prepared by roasting ferric sulfate crystals, (6) 175*i*.

Physicochemical properties (*continued*)
interaction of medium with hardened cement block, structural mortars, and concretes, (1) 2*i*.
of lime, (5) 126*h*.
of NiO, alkali- and iron-doped, (8) 219*d*.
of plastic Indian clays compared with ball clays, (6) 169*j*.
of yttrium orthosilicate, (4) 114*g*.
Physics, chemical, of nonmetallic crystals, papers from conference, B (9) 259*i*.
National Physical Laboratory, 1962 report, B (8) 231*a*.
theoretical, introduction to, B (10) 299*j*.
thermal, of rotary cement kiln, (7) 182*h*.
Pickling, automatic control of acid concentration, P (5) 128*a*.
for direct to steel enameling methods, (1) 4*e*.
economics in, (2) 37*e*.
effective, II, (3) 65*f*.
ferric sulfate addition, (2) 36*g*.
machine, automatic, schedule for, (2) 36*g*.
method of, P (7) 184*a*.
rate, relation to metal and surface compositions and direct-on enamel adherence, (2) 37*j*.
of sheet steel and Al sheet, (3) 65*d*.
of steel, for bathtubs, (3) 65*h*.
techniques, for enameling, (2) 36*d*.
Piezoelectricity, coefficients, of single-crystal $BaTiO_3$, (4) 113*c*.
device, P (2) 49*f*.
using AlN, P (9) 249*c*.
use of CdS in, P (9) 249*d*.
use of ZnO in, P (9) 249*d*.
materials, accurate machining of, P (10) 283*e*.
control of effective resistance, P (2) 49*h*.
in control of light rays, (10) 280*e*.
hot-pressing of, (4) 104*g*.
lead titanate-lead zirconate series, (11) 309*i*.
longitudinal prepolarization of bodies containing, P (5) 136*e*.
research and development, (8) 218*f,h*.
piezoelectric ceramics, in circuit element transducer, P (9) 248*g*.
fundamentals of, (9) 247*b*.
for hydrophones, (2) 48*a*.
niobate high-temperature, (9) 248*f*.
parts, manufacture of, (6) 165*e*.
vibrators, cylindrical, forming of powder mixtures for, (1) 19*g*.
piezoelectric crystal holder, P (1) 21*d*.
piezoelectric effect, in zinc blende structure, theory of, (2) 59*f*.
piezoelectric pressure transducers, (6) 165*a*.
principles and uses, (4) 104*i*.
properties, of BeO single crystals, (10) 281*g*.
quartz element, P (5) 137*g*; P (10) 283*f*.
secondary piezoresistivity, in O-deficient $BaTiO_3$, (10) 282*c*.
Pigeonite, structure of, (7) 199*j*.
Pigments. See also *Stains*.
antifouling, P (11) 303*a,d*.
ball mill for dispersing in liquid vehicles, P (2) 51*a*.
with Ba Zr borate, P (8) 225*e*.
ceramic, synthesis of, high-temperature crystal chemistry of, I-IV, (9) 238*g*.
chromate, P (4) 110*f*.
corrosion inhibitive, P (6) 170*g*.
finely divided, production, P (4) 111*g*.
for glaze stain, P (1) 18*i*.
inorganic blue to green, P (6) 167*c*.
metallic, gold-colored, P (3) 83*h*.
method of producing, P (4) 111*d*.
mixed-phase, with rutile structures, (1) 18*i*.
organic, limitations of, (8) 230*f*.
photoconductive zinc oxide, P (2) 55*d*.
siliceous, preparation, P (8) 225*i*.
TiO_2, compositions containing, P (3) 85*b*.
method of making, P (6) 171*b*.
plant layout and manufacture, (10), 288*d*.
treatment, P (8) 226*b*.
two-stage acid process for making, P (9) 254*b*.
vanadium zirconium, P (3) 84*e*.
Pipe. See also *Tile*.
asbestos-cement, method of making, P (10) 268*a*.
ASTM standards for, B (9) 259*b*.
ceramic, coupling for, P (2) 44*c*.
clay, cutting machine for, P (1) 13*c*; P (8) 212*a*.
clay, polyester joints for, (1) 13*a*.
equivalent lengths, nomograph for, (2) 51*a*.
extrusion from nonplastic corundum bodies, (10) 279*a*.
glass, device for rupturing seals, P (8) 210*c*.
high temperature insulation for, P (1) 16*e*.
liquid transport of solids in, (10) 284*e*.
refractory fiber covering for, P (3) 74*c*.
salt glazed, production, (2) 43*f*.
sewer, basic research in, (10) 273*f*.
developments in manufacture, (6) 159*c*.
manufacture in Sudan, (2) 60*g*.
preparation and properties, (7) 187*c*.
steel, with thermoplastic liner with glass fiber reinforcement, P (4) 100*c*.
stoneware, gas-fired intermittent kilns for, (10) 287*g*.
stoneware, strength of, (8) 212*a*.
Pipets, assembly, for mechanical analysis of soils, (5) 139*d*.
Pirekail. See *Glass*.
Plagioclase, polysynthetic twinning in, (4) 118*c*.
quick identification for quantitative thin section analysis, (4) 107*g*.
twins, recognition in sections normal to composition plane, (4) 120*a*.
Plasma, coatings, application of, (9) 238*j*.
coatings, use of ZrO_2 rods, (6) 155*c*.
gaseous, apparatus for producing, P (5) 140*e*.
hypersonic, experiments with, (8) 227*i*.
jet, ceramic uses of, (3) 81*j*.
Plasters, calcium sulfate, P (5) 127*a*.
dolomite, flow behavior, (8) 205*c*.
gypsum, hydration mechanism, III, (10) 267*e*.
increased capacity in French plant, (6) 154*b*.
method of making, P (3) 65*b*.
setting time in presence of dolomite plaster, (10) 267*g*.
molds. See *Molds*.
for molds, vacuum de-airing of, (3) 64*g*.
of Paris, production of B.P.C. grade, (9) 237*b*.
patching, composition, P (11) 302*g*.
sand-cement, waterproofing for buildings and roofs, (9) 243*a*.
slaked lime as, plasticity figure of, (1) 2*j*.
wall, preparation, P (2) 36*b*.
Plaster of Paris. See *Gypsum; Plaster*.
Plasticity, Brabender Plastograph for assessing, (2) 51*e*.
of ceramic bodies, B (2) 61*j*.
of clays, (1) 25*f*.
figure, of slaked lime for use as plaster, (1) 2*j*.
light induced, in germanium, (6) 174*h*.
model, for clay, (11) 318*d*.
of mono-ionic clays, study of, B (4) 124*f*.
study of, B (10) 300*e*.
Plasticizers, hydrophilic, as addition in hydration of portland cement, (5) 126*e*.
Plastics. See also *Resins*.
application to glass bottles, P (2) 42*a*.
glass fiber reinforced, (1) 7*a*.
glass reinforced, B (1) 32*c*.
glass reinforced, pathogenicity of, (2) 60*h*.
polystyrene, as package for glassware, P (3) 70*c*.
reinforcement media, (10) 269*d*.
uses in pottery processing, (1) 18*a*.
Plastometry, penetration, apparatus and use, (7) 196*i*.
Plating. See *Coatings*.
Platinum, alloy, and glass, composite material, P (3) 77*d*.
expansion values, for thermal calibration of high-temperature X-ray diffraction cameras and diffractometers, (3) 81*a*.
with W, for strain gages up to 800°C, (6) 159*j*.
Plutonium, carbide, solid solutions, preparation of, (9) 256*h*.
-C alloys, arc-melted, phase studies near monocarbide composition, (4) 117*j*.
ceramics, cathodic etching of, (11) 312*i*.
ceramics, irradiation effects in, (11) 307*f*.
dioxide, melting point in He atmosphere, (9) 243*g*.
metallurgy, proceedings of 2d international conference on, B (8) 231*b*.
nitride, thermal expansion of, (10) 297*c*.
oxide, microspheres, for fuel elements, (3) 82*j*.
oxide, systems. See *Systems*.
$(PuU)O_2$ solid solutions, sintering behavior and stability, (11) 306*j*.
systems. See *Systems*.
Podzol, profiles, clay mineralogy in, (11) 315*c*.
Polarimeters, in study of pressure effects, (4) 107*d*.
Polarization, mechanism, in solid solutions of $Pb_2NiNb_2O_9$ and $Pb_2MgNb_2O_9$, (7) 192*b*.
pre-, of bodies containing piezoelectric material, P (5) 136*e*.
relation to space-charge-limited currents in rutile single crystals, (5) 145*c*.
Polarography, in determination of Ti in presence of Fe-malonate complexes of Ti, (11) 313*c*.
method and apparatus, P (5) 139*i*.
Polarons, capture by F centers, (5) 141*j*.
Polishing. See *Grinding and polishing*.
Polyelectrolytes. See *Electrolytes*.
Polymerization, in olefins, inhibition by treatment of zeolitic molecular sieves, P (2) 60*b*.
Polymers, quaternary ammonium or sulfonium, in water loss control of aqueous cement slurries, P (10) 268*e*.
semiconduction in, B (9) 263*i*.
Polymorphism, of ABO_3 type rare earth borates, (4) 118*j*.
of $Bi_2Ti_4O_{11}$, (1) 29*d*.
of phosphates, arsenates, and vanadates containing alkali and alkaline earth metals, (4) 118*j*.
Porcelain, alumina, as high frequency insulator, II, effect of metal oxides, (1) 17*h*.
applications and properties, (9) 258*b*.
art. See *Art and artware*.
black, sagger for firing, (8) 218*a*.
body, composition, P (10) 279*a*.
microstress in, B (10) 300*d*.
microstructure of, XII, (1) 18*h*.
C_4 hydrocarbons as gaseous fuels for firing, (3) 81*j*.
Chinese, in Danish collections, (6) 153*j*.
color mixtures for, machine for continuous spreading, (7) 190*f*.
compositions, P (4) 104*c*.
conversion of fused glass to, by crystallization, P (2) 42*b*.
decorating and forming machines, (1) 18*a*.
decoration, electric tunnel kiln for firing, (2) 53*h*.
dental. See *Dental materials*.
-earthenware industry, automation and mechanization in, (7) 190*c*.
effect of quartz on texture of, (3) 75*f*.
electrical. See also *Insulators, electrical*.
electrical, electric kiln firing of, (11) 314*e*.
electrical, vitrification and fired properties, (11) 309*e*.
electrotechnical, causes and prevention of manufacturing defects, (9) 247*g*.
factories, physicochemical mechanical analysis of work of equipment in, (1) 18*b*.
firing behavior, effect of additives, (10) 278*h*.
forsterite, as high frequency insulator, XI, (1) 18*a*.
green strength, increasing of, (10) 278*e*.
Porcelain (*continued*)
hard electrical, properties and behavior in kiln, interpretation from density measurements, (11) 309*e*.
Herend factory, history of, B (10) 299*b*.
hot cast under pressure, single firing, (7) 190*g*.
industry, development, future, and requirements, (4) 103*j*.
industry, layout of working sequence, (4) 104*c*.
manufacture, errors in, (5) 133*j*.
on-glaze decorated, Austrian regulations for Pb solubility from, (3) 90*b*.
painted, of James Rogers, (6) 153*j*.
plates, impact test for, (9) 246*a*.
production technology, (7) 190*d*.
raw materials, effect of particle size on manufacture, V-VIII, (8) 217*j*.
relation between stressed state and damping of vibrations excited in it, (4) 120*e*.
Royal Danish and C. L. David collection, (6) 153*j*.
scope and limitation of term, (9) 246*b*.
slip casting problems, (10) 278*j*.
soft, technical applications, B (4) 124*g*.
technical, mechanization of production, (10) 281*b*.
torsional behavior at high temperature, (7) 196*b*.
workers, histology of iron deposits in silicosis in, (2) 60*e*.
zircon glazes for, (10) 279*c*.
Pores, gas, in structure of blast-furnace slags and matrix, (10) 267*a*.
in refractories, strength and structure as function of, (1) 15*a*.
size, relation to permeability, in materials for chemical industry, (3) 83*a*.
Porosity. See also *Permeability; Pores*.
apparent, of alumina silica refractories, relation to Shore hardness and abrasion resistance, (1) 15*d*.
effect on concrete durability in corrosive waters, (1) 3*a*.
effect on structure of sintered metals, (6) 172*i*.
of fireclay brick, effect on erosion by calcareous slag, (1) 13*g*.
measurement, by air displacement, (11) 313*d*.
of sillimanite, slip-cast, relation to firing temperature and corrosion resistance, (1) 15*b*.
of zircon refractories, effect on resistance to corrosion by glass, (1) 6*c*.
Porous materials. See also *Cements; Concretes; Insulation, thermal*.
ceramic, method of making, P (9) 246*c*.
ceramic, resin-impregnated, structural and heat transfer characteristics, (9) 243*i*.
in chemical industry, (3) 83*a*.
consolidated, thermal conductivity of, (2) 44*g*.
interdiffusion of gases in at uniform pressure, (1) 28*a*.
permeability properties, apparatus for determining, P (3) 81*a*.
theory of swelling in, B (8) 234*g*.
water movement in, I, (11) 320*b*.
Portland cement. See *Cement, portland*.
Portlandite, thermal decomposition of, (5) 147*a*.
Potash, plant operations, (10) 288*i*.
Potash feldspar. See *Feldspar*.
Potassium. See also *Alkalis*.
analcite, dielectric properties, (8) 219*a*.
bromide, briquette method, for studying infrared spectra of anhydrous borates, (2) 57*b*.
formation of nuclei in aqueous solutions, B (9) 262*c*.
pellet preparation, in alteration of muscovite absorption spectrum, (6) 171*g*.
carbonate, purification of, P (6) 171*c*.
solid-liquid phase equilibria with Li and Na carbonates, (1) 30*c*.
systems. See *Systems*.
chloride, color centers in, (5) 142*e*.
crystals, X-irradiated, thermal bleaching of V and F centers in, (11) 319*g*.
crystals, X-rayed, ultraviolet absorption of, (5) 147*e*.
inversion symmetry of M and R centers in, (4) 115*e*.
irradiated, optical absorption of Cl_2^- molecule ions in, (4) 117*b*.
recovery of, P (10) 290*e*.
in solid state, conductance of, (10) 291*d*.
feldspar, determination in submicroscopic grain sizes, (6) 167*j*.
fixation in Canadian soils, (5) 140*j*.
flame photometric determination in catalysts, (10) 286*d*.
flame-spectrometric determination with $BaCl_2$ as buffer, (11) 303*f*.
fluoaluminate, as dielectric material, P (10) 282*f*
fluoride, solution, growth behavior of $BaTiO_3$ crystals from, (2) 58*j*.
fluoride, systems. See *Systems*.
fluosilicate, production of, P (7) 198*b*.
hydroxide, solution, effect on formation of tobermorite phase at room temperature, (4) 114*f*.
iodide, γ and photoluminescence of, (5) 135*a*.
iodide, single crystals, Gyulai-Hartly effect in, B (9) 261*g*.
niobates, systems. See *Systems*.
nitrate, crystals, growth and formation of inclusions, B (9) 262*e*.
oxide, flame spectrometric determination in aluminosilicates, (10) 286*d*.
oxide, systems. See *Systems*.
KCl-KBr, defects in mixed crystals of, B (9) 260*h*.
$KMeF_3$, magnetic structures of, (10) 294*i*.
quantitative determination in glasses and silicates by X-ray diffraction, (2) 40*i*.

Potassium (*continued*)
-sodium niobate, for transducers, P (6) 166*b*.
sulfate, effect on portland cement properties, (7) 179*i*.
Potentiometers, contact isolated, P (3) 77*e*.
light beam controls, (10) 280*j*.
photopot optical, (9) 251*d*.
Potteries, English, gas installations in, (6) 169*b*.
gas kilns for, (6) 169*a*.
Scandinavian, (5) 126*a*.
Potters, ceramics for, I–V, (2) 33*i*.
in Crete, Messenia, and Cyprus, B (9) 263*b*.
folk, of Mashiko, (7) 177*j*.
Hohlt, Otto and Albrecht, (3) 64*c*.
modern, David Eeles, (2) 33*i*.
Reuss, Gusso, life and work, (3) 64*a*.
Scandinavian, (5) 126*a*.
workshop, Canadian Guild of, (2) 33*h*.
Pottery. See also *Archeology; Art and artware; Bodies, ceramic; Design; Dinnerware; Earthenware; Stoneware; Terra cotta; Whiteware.*
bodies, measurement of elasticity modulus and rupture modulus at high temperatures, (11) 333*j*.
British industry, schools, and factories, B (3) 92*g*.
Chinese, of Han Dynasty, B (5) 150*d*.
Chinese, tea ware, history and qualities, (9) 236*f*.
clays for making large pots, (4) 95*j*.
in Crete, Messenia, and Cyprus, B (9) 263*b*.
decoration. See *Decoration.*
English, at Newark Museum, (3) 63*j*.
form and expression, B (3) 92*g*.
glazing, decorating, and firing huge pieces, (4) 95*j*.
Indian, from Alabama, (4) 95*i*.
machine forming techniques, (3) 79*h*.
manufacture, salvage of clay from drainage from, (1) 31*e*.
Niderviller, production, design, and decoration, (6) 153*h*.
Old World, decoration of, (4) 95*i*.
plant, Haeger, philosophy and organization, (6) 163*c*.
printing, roller press to multilith, (10) 266*a*.
processing, plastic pieces for separating ware, (1) 18*a*.
Thai, 14th and 15th century stoneware, (9) 236*f*.
Pottery industry, trends in, (8) 218*d*.
U.S., impressions of, (8) 218*d*.
Potterymaking apparatus and equipment. See *Dryers; Kiln furniture; Kilns; Materials handling; Molds.*
Powder metallurgy, in bonding of materials of similar thermal expansion, (7) 183*j*.
friction element wear part, P (5) 133*e*.
Hahn emanation method in study of, (6) 175*b*.
in manufacture of massive bodies of ZrH_4, (10) 275*g*.
in nuclear age, Plansee Proceedings 1961, B (3) 92*j*.
processes and products, P (3) 74*i*.
Powders. See also *Granular materials.*
apparatus for compacting in separate slabs, P (8) 221*f*.
apparatus for discharging, P (1) 23*e*.
in bulk, apparatus for sampling, P (3) 81*b*.
bulk handling, in chemical industry, (1) 22*d*.
ceramic, electromagnetic removal of Fe in free fall, P (3) 83*g*.
ceramic, vacuum treatment during pressing, (4) 106*g*.
compaction, radial pressure in, (1) 23*a*.
container for and method and apparatus for unloading, P (4) 110*h*.
device for simultaneously measuring density and humidity, P (4) 108*e*.
electrostatic spraying or atomizing heads for, P (7) 195*b*.
fine, methods for estimating mixing ratio, (7) 181*b*.
gas displacement from during compaction, (1) 22*j*.
making of articles from, P (5) 138*a*.
metal, forming by use of plaster mold in steel mold, (11) 312*a*.
mixer for, P (8) 222*d*.
mixing with air jets, P (10) 285*g*.
mixtures, forming for cylindrical piezoelectric ceramic vibrators, (1) 19*g*.
pneumatic conveyor with pressure vessel for, P (11) 312*a*.
preparation of small samples from thin and polished sections, (6) 168*f*.
pressing, for fine ceramics, preparation by granulation, (10) 284*j*.
pump for moving on conveyor, P (11) 312*c*.
sample, mull technique for preparation for X-ray diffraction, (9) 251*e*.
sintering of, P (2) 51*h*.
specific surface of, automatic device for measuring, (8) 222*g*.
vibrating trough for moving, P (2) 51*d*.
X-ray diffraction of, rapid change rotating sample holder for, (11) 313*f*.
Power. See also *Energy.*
electrical, generating from solar energy, P (4) 108*h*.
factors, in continuous laser operation, (10) 281*h*.
limiters, low threshold level ferrimagnetic, (7) 192*h*.
short-term, at high temperature, ceramic-metal cells for, (10) 268*h*.
thermoelectric, of CdO, (8) 219*g*.
ceramic materials for generation, (10) 273*i*.
generators, (10) 280*e*.
in polar semiconductors, (8) 219*b*.
Pozzolans. See also *Cement; Mortars.*
fly ash as, in dense and lightweight concrete, (4) 96*d*.
Praseodymium, compounds, for light filters for Raman spectroscopy, (5) 147*i*.
nitride, magnetic susceptibility of, (4) 119*b*.
oxides, structure and properties, B (9) 260*e*.
trifluoride, liquid density of, (1) 28*d*.
Precipitation, of Al hydroxides from aluminate solutions and Al salts, (4) 112*j*.
of phosphate by exchangeable Al on cation exchange resin, (5) 145*a*.
of readily filterable rare earth hydroxides, P (1) 26*a*.
of Zr and F ions from solutions, P (9) 254*c*.
Precipitators, electrostatic, discharge electrode for, P (2) 51*a*.
electrostatic, high temperature, P (2) 51*d*.
electrostatic, magnetic means for cleaning electrodes, P (4) 106*i*.
Presses, brick, hydraulic, P (6) 167*c*.
for briquets, P (9) 243*c*.
for curved glass-plastic assemblies, P (9) 241*f*.
diaphragm filter, P (10) 285*d*.
filter, hydraulic, installation for automatic operation, P (6) 167*d*.
friction, with improved shaping surfaces, P (10) 284*j*.
glass, with electrical measuring and control apparatus, P (5) 130*i*.
hot-extrusion, lubrication method, P (10) 269*c*.
hydraulic, press stand for, P (3) 80*d*.
hydraulic horizontal, with two series of multiple chambers, P (5) 138*a*.
hydrostatic, for elongated object, P (9) 250*c*.
mechanical, use in refractories industry, (10) 276*g*.
plural reaction chamber, for high pressures, P (5) 138*e*.
roller, briquetting, with roll adjustment, P (5) 141*a*.
rotary, automatic taking-off machine, (1) 22*c*.
Pressing, of ceramic powders, vacuum treatment, (4) 106*g*.
cold, of ceramic pellets, ultrasonic vibration in, (8) 221*d*.
defects, in ceramic tile, (9) 245*j*.
dry, of electric heating elements, ceramic bodies for, P (6) 165*i*.
of dry compacts, density distribution study by radiography of lead grids, (1) 22*h*.
of fine-ceramics, preparation of powders by granulation, (10) 284*j*.
of flat products, automatic thickness control, P (6) 167*g*.
hot, of alumina, mechanisms of material transport, (10) 293*d*.
of ceramics in alumina dies, (10) 284*h*.
effect on properties of $PbZrO_3$-$PbTiO_3$ ceramics, (7) 191*k*.
semicontinuous, (2) 45*c*.
of superrefractories, V, (10) 275*d*.
of synthetic mica, reducing thermal gradients, P (11) 313*i*.
mechanical, for shaping of plates, P (3) 79*e*.
methods, for whiteware, (7) 190*d*.
of plates, (10) 278*h*.
of powdered material, P (5) 138*a*.
process, for spectacle lenses, (10) 271*a*.
techniques, for refractory brick, (6) 160*a*.
Pressure, apparatus, multi-anvil force compensating, P (1) 23*d*.
applied, effect on densification during sintering in presence of tight phase, (10) 292*i*.
-differential type apparatus, in density and volume measurements of solids, P (8) 224*a*.
effect, on β-γ transformation of dicalcium silicate, (8) 203*j*.
on monoclinic-tetragonal transition of zirconia—thermodynamics, (2) 56*i*.
on nucleation and linear growth rate for betol, B (9) 262*c*.
optical methods for studying, (4) 107*d*.
forming, effect on strength of mica brick, (3) 72*c*.
high, apparatus, P (8) 221*i*.
device for generating, P (8) 222*b*.
dual-wedge apparatus, P (11) 312*g*.
effect on glass, tests by tetrahedral anvil apparatus, (8) 208*f*.
effects on oxide glasses, I, II, (11) 303*i*.
Manganin sensors, (2) 52*a*.
multiple-anvil apparatus for, P (8) 222*e*.
reaction vessel, two-terminal end cap for, P (8) 222*c*.
sensing device for, P (4) 108*a*.
vessel with punch, P (10) 285*f*.
hydrostatic, compact apparatus, P (10) 285*c*.
hydrostatic, effect on dielectric constant and loss tangent of $BaTiO_3$ ceramics, (3) 87*d*.
oxygen, effect on incongruent melting temperature of Y Fe garnet, (7) 199*f*.
oxygen partial, effect on properties of semiconducting $BaTiO_3$, (8) 219*j*.
radial, in powder compaction, (1) 23*a*.
sensors, quartz, temperature range, (4) 104*j*.
in study of local symmetry and compressibility in glass, (9) 241*b*.
superhigh, multi-anvil apparatus for, P (7) 195*a*.
uniform, effect on strength and deflection of large rectangular glass panels, (3) 68*b*.
vapors, data, for solid and liquid, (5) 147*j*.
measurements in molten salt systems, activity determinations from, (10) 295*b*.
metal diaphragm apparatus for measuring, (9) 251*h*.
vessel, with metallic-coated glass filaments, P (8) 211*f*.
Proceedings, of Am. Ceram. Soc. symposium on mechanical behavior of crystalline solids, B (9) 259*e*.
Proceedings (*continued*)
of conference, on aerodynamically heated structures, B (2) 61*f*.
on direct observation of imperfections in crystals, B (9) 261*e*.
on ice and snow, B (11) 321*h*.
on mechanical properties of engineering ceramics, B (3) 91*g*.
at Oxford, June 1961, on science of ceramics, B (4) 123*f*.
on properties of reactor materials and radiation damage effects, B (8) 233*b*.
on radiative transfer from solid materials, B (3) 92*f*.
8th national conference on clays and clay minerals, B (3) 90*j*.
of 4th international symposium Oct. 1960, B (5) 148*i*.
of international conference on Pu metallurgy, B (8) 231*b*.
of 9th national conference on clays and clay minerals, B (5) 150*i*.
Plansee, 1961, 4th seminar, B (3) 92*j*.
of 2d conference on rare earth research, B (5) 151*f*.
of 7th symposium on art of glassblowing, B (5) 151*f*.
of 10th annual conference on applications of X-ray analysis, B (2) 60*f*.
Protons, diffusion in silica-alumina glass in electrical field, (2) 38*h*.
Pugging, semiplastic, in structural clay products batch preparation, (10) 284*f*.
Pug mills. See *Mills.*
Pulverizers. See *Crushing and grinding apparatus.*
Pulverizing. See *Crushing and grinding.*
Pulverulent materials. See *Powders.*
Pumice, weathering, compared to volcanic ash, (6) 169*i*.
Pumps, earthenware centrifugal, (5) 138*b*.
getter-ion, for analytical mass spectrometer, P (2) 60*c*.
getter-ion, connection to analytical mass spectrometer, P (1) 31*c*.
for moving powders, P (11) 312*c*.
Purification, of MgF_2, (2) 58*j*.
of potassium carbonate, P (6) 171*c*.
of sand containing color-imparting impurities P (1) 26*d*.
of Si by transport reactions, (4) 119*b*.
of TiO_2 by high-voltage electrodialysis, (7) 197*j*.
Pyroelectricity, properties, of BeO single crystals, (10) 281*g*.
Pyrometers, arc-lamp mechanism for calibration of, (9) 250*i*.
for glass temperature measurement, P (9) 239*e*.
immersion, with expendable plug-in temperature sensing unit, P (1) 24*b*.
immersion, for use in molten steel, B (2) 62*c*.
optical, P (6) 168*j*.
calibration of, (1) 23*i*.
as measuring and comparing device, P (4) 108*e*.
with photoelectric detector, P (2) 53*c*.
radiation, P (2) 53*c*; P (10) 287*c*.
single beam two-frequency, for measuring flame temperatures, (6) 168*b*.
Pyrometry, optical, detection limits in, (5) 138*i*.
Pyromorphite, oxy-, cell dimensions, (4) 117*i*.
Pyrophyllite, formation of coesite and kyanite from at high pressures and temperatures, (4) 114*f*.
mill, (7) 197*i*.
to mullite, thermal transformation, (7) 201*d*.
N. Car. deposits, mineralogy and petrology of, (4) 109*f*.
Pyroxenes, crystal chemistry of, (10) 297*b*.
in glassy volcanic rocks, (6) 170*d*.
rapid determination of approximate composition, (4) 107*g*.
Pyroxenoids, infrared spectra of, (5) 147*e*.

Quality control, I-III, (3) 79*i*; IV-VI, (6) 167*c*; VII, (10) 284*c*.
in ceramic industries, (10) 298*d*.
of glass containers, machine for inspecting, P (4) 100*e*.
of glassware, light source for photoelectric inspection, P (4) 100*b*.
in glassware, symposium on, (9) 241*j*.
graduation method for improved accuracy, (2) 51*c*.
handbook, revised and enlarged, B (6) 176*i*.
in lightweight aggregates, (11) 302*h*.
in molds, (4) 98*h*.
photoelectric inspection of glassware, P (5) 131*d*.
plant organization for, (2) 60*d*.
of raw materials, financial benefits, (9) 253*j*.
in reducing production costs, (4) 122*b*.
statistical, case histories in ceramics, (4) 122*e*.
system, reliability of human element, (9) 241*a*.
for 12 enameling plants, coordination of, (5) 127*f*.
Quantum efficiency, of ruby, (10) 281*e*.
Quantum theory, of nonmetallic crystals, B (9) 259*i*.
Quartz. See also *Glass; Refractories; Silica.*
adsorption of water on, reversible isotherms of, (1) 29*d*.
α-, H in, (5) 144*d*.
α-, hydroxyl groups in, (4) 114*e*.
as Bourdon gage, (6) 168*h*.
cloth, as reinforcement for modified phenolic resin laminate, (9) 240*e*.
colored, growth and properties, (4) 114*a*.
containers, for melting Si, recovery and reuse, P (9) 244*i*.
coordination in, relation of infrared spectra, (2) 58*c*.

Quartz (*continued*)
-cristobalite transformation, geometric model for, (6) 173*f*.
crystalline, Ag-containing, photoluminescence, (6) 164*j*.
crystals, electronic grade, in 1961, (1) 25*d*.
for forming stable Al-plated quartz resonator, P (1) 21*f*.
growing of, P (6) 171*a*.
in microwave delay line, P (4) 105*i*.
oscillators, heat sinks for, P (4) 105*e*.
piezoelectric, control of effective resistance, P (2) 49*h*.
piezoelectric, for microbalance, (10) 286*c*.
piezoelectric, role of internal friction in, (10) 282*b*.
relation of dielectric losses to imperfections, (5) 143*h*; B (11) 320*j*.
dielectric anomaly in for high transient stress and field, (5) 142*g*.
DTA of, (2) 56*f*.
effect on porcelain texture, (3) 75*f*.
far-infrared properties, (4) 114*b*.
fibers, in memory cell units, (2) 48*h*.
fused, diffusion of neon isotopes in, (4) 113*j*.
H atom recombination on, (9) 240*g*.
phosphorescence of, (5) 145*b*.
in strain gage, P (10) 287*f*.
ultraviolet lasers, (7) 192*a*.
Ge-doped, paramagnetic color centers and ionic mobility in, B (11) 320*i*.
ground and shattered powders, X-ray diffractometry of disturbed layer on, (3) 86*i*.
homogeneity, testing for, B (9) 263*g*.
hydrothermal, kinetics of crystallization, (2) 57*d*.
hydrothermal synthesis of, P (1) 25*i*.
interaction with Ca hydroxide, (5) 144*d*.
internal friction of, (6) 173*j*.
-kaolinite-feldspar, high temperature reactions, (3) 75*g*.
mechanical resonance dispersion in, at audio frequencies, (3) 87*f*.
melting, furnace for, P (4) 99*f*.
in mineral mixtures, X-ray determination, (9) 252*c*.
monzonite, Kinsman, cordierite-garnet-bearing, phase relations in, (4) 117*j*.
opaque, ablation data on, (6) 156*c*.
photoelastic effects in, (4) 112*g*.
piezoelectric element, P (5) 137*g*; P (10) 283*f*.
powders, ground, mechanism for dissolution in HF, (10) 295*g*.
powders, ground, of respirable size, disturbed layer on, (10) 292*b*.
pressure sensors, temperature range, (4) 104*j*.
production of antibodies by, (2) 60*d*.
pure, in silica brick, (6) 161*h*.
quick identification for quantitative thin section analysis, (4) 107*g*.
removal, effect on shale, (3) 82*c*.
sealed vessel, for pulling semiconductor crystals, P (5) 135*d*.
secondary overgrowth in, crystal-optic study, (8) 226*f*.
sintering of, (10) 276*h*.
solution in feldspar melts, (4) 120*h*.
structure in terms of directed bond, (4) 115*j*.
surface activity, relation to development of silicosis, (2) 60*f*.
surface conductivity, in presence of adsorbed layers, (1) 30*h*.
surface energy, direct measurements, (8) 227*g*.
synthetic, effect of electrolysis on resonator performance, (9) 247*c*.
growth of, recent developments, (9) 248*j*.
heat treated, light scattering from, (4) 115*g*.
X-ray study of, B (9) 263*g*.
transformation, to cristobalite, mechanism of, (5) 129*h*.
transformation, X-ray study of, (4) 121*c*.
Quartzite, particle size, effect on properties of porcelain bodies, (8) 217*j*.
Quenching, effect on ionic conductivity and dislocation decorability in AgCl, B (9) 261*c*.
infrared, and electroluminescence, (5) 135*b*.
studies, on infrared stimulable phosphors, (2) 58*a*.
studies, in system CaO–ZnO–Al_2O_3–SiO_2, (2) 59*b*.

Radiation, absorption, by ceramic materials containing rare earths, (10) 273*j*.
behavior, of monocarbide fuels, (11) 307*i*.
black body, temporal coherence of, (5) 146*i*.
characteristics, of gas-fired panel, (10) 287*i*.
coefficients, of refractory compounds, (1) 14*i*.
coloration, of silica minerals, (4) 119*f*.
damage, B (8) 232*j*.
in diamond, optical and electrical effects, (8) 229*c*.
effects on dispersed fuel materials, (8) 213*d*.
effects in reactor materials, B (8) 233*b*.
to glass, (9) 240*g*.
to graphite, (8) 214*g*.
in nonfissile ceramics, (11) 306*i*.
in UC, (11) 307*c*.
in decomposition of inorganic nitrates, (10) 296*a*.
detection limits in, (5) 138*i*.
devices, design and use, B (2) 62*c*.
effect, on alkali halide crystals, (10) 293*d*.
in doped fused silica, (4) 119*h*.
in EGCR fuel, (4) 101*g*.
on electrical and optical properties of LiF, (10) 294*h*.
on electrical resistivity of cast UC_2, (11) 308*d*.
in fused silica and α-Al_2O_3, (8) 229*j*.
in ionic solids, role of impurities, (11) 319*b*.
Radiation, effect (*continued*)
on reactivity of solid surfaces, (2) 58*b*.
in semiconductors, (3) 76*e*.
in U-doped ZrO_2, (10) 275*j*.
in U and Pu ceramics, (11) 307*f*.
in electron beam, in chemical decomposition of PbI crystals, (10) 290*g*.
fluorescent, in X-ray spectrochemical analysis, P (2) 60*a*.
γ-, ceramic structural materials for absorption of, (10) 274*a*.
in coloring of Ce-containing glasses, (1) 5*e*.
dosage-measuring glasses, P (9) 241*j*.
dosimeter, P (5) 136*c*.
effect on electrical conductivity of glass, (8) 209*a*.
in formation of color centers in Na silicate and quartz glasses, (5) 129*e*.
of ZnO, effect on adsorbed layers, (10) 293*g*.
of glass films with 100 kv electron beam, (2) 40*a*.
glass sensitive to, P (10) 273*a*.
infrared, from Yb activated silicate glass, stimulated emission of, (5) 130*a*.
ionizing, displacement of atoms in solids by, role of Auger effect, (11) 318*j*.
ionizing, effect on adsorptive and catalytic properties of semiconductors, (8) 219*d*.
low temperature, in graphite, (10) 294*g*.
in measurement of temperature of furnace charge, P (9) 252*g*.
measurements, basic concepts of cutoff glass filters in, (2) 38*h*.
of metal-fiber-reinforced ThO_2–UO_2, (7) 188*d*.
neutron, effect on crystalline and glassy inorganic solids, (10) 292*f*.
in elimination of defects from silica glass, (3) 67*e*.
in producing permanently active catalyst, P (9) 244*h*.
penetrative, in conveyor speed control, P (3) 80*b*.
in processes on silica gel surface, (10) 296*b*.
selective, in photosensitive gas phase etching of semiconductors, P (10) 283*c*.
source, for infrared spectrophotometers, P (11) 320*b*.
stability, of compacts of Al and fuel-bearing glass fibers, (9) 241*f*.
standard, carbon-arc, (9) 250*i*.
thermal neutron, effect on thermocouples and resistance thermometers, (5) 139*a*.
transfer, from solid materials, B (3) 92*j*.
of U metal and U oxide fuel pins, (10) 274*g*.
X, in coloring of photosensitive glasses, (6) 156*a*.
X, fractional, of NaCl crystals, effect on F-center density, (4) 113*b*.
Radioactive materials. See also *Isotopes*.
contaminants, removal from surface, P (6) 176*f*.
fission product rare gases, in study of phase change in fine particles, (6) 176*a*.
waste, in glass, fixation by Fingals Cave, (11) 303*j*.
waste, method for disposal, P (9) 246*b*.
Radioactive tracers. See *Isotopes*.
Radioactivity. See also *Isotopes*.
in analysis of chemical sample for O, P (9) 252*d*.
Radiography, of lead grids, in study of density distribution in dry-pressed compacts of ceramic powders, (1) 22*h*.
Radioisotopes. See *Isotopes*.
Radomes, alumina, production grinding techniques for, (3) 63*g*.
high-alumina, firing at lower temperature than use temperature, (8) 213*b*.
high-temperature, binder techniques for, (9) 241*f*.
material for, P (6) 166*c*.
pressure casting from fused silica slips, (8) 213*h*.
Rare earths (lanthanons). See also specific types.
compounds, as high-temperature refractories, bibliography, (1) 14*j*.
concentration of, P (9) 254*j*.
effect on radiation absorption of ceramic materials, (10) 273*j*.
fluorescence of, (6) 163*i*.
hydroxides, readily filterable, precipitation of, P (1) 26*a*.
infrared absorption spectra of, (8) 228*f*.
manganate, as ferroelectrics, (9) 248*g*.
oxalates, thermal decomposition of, (9) 257*a*.
oxides, vaporization of, (2) 59*h*.
oxides, X-ray study of phase transformations in, (9) 257*h*.
research, proceedings of 2d conference, B (5) 151*f*.
separation, of Am and Cm from, P (6) 176*a*.
by ion exchangers, (5) 145*i*.
of Y from, P (6) 176*b*.
from Y by ion exchange, P (2) 60*a*.
silicates, high-temperature solid solutions of, B (10) 300*g*.
Rationalization, of manufacture of spectacle glass blanks, (1) 8*d*.
Raw materials. See also *Sands; Rocks*.
cement, in Kansas, (3) 64*e*.
cement, study by combined thermal expansion and DTA, (7) 180*h*.
ceramic, Austrian deposits, (7) 197*d*.
background of, XII–XVI, (1) 25*e*.
collection from drainage from potteries and clayworks, (1) 31*e*.
electrofiltration in prospecting of, (3) 83*j*.
photogeology in search for, (8) 225*h*.
preparation of mullite for electron microscope study of, (8) 229*h*.
survey and examination, B (4) 124*c*.
clay mineral containing, pH measurements of suspensions of, (4) 117*j*.
for electron tubes, differences in, (11) 310*b*.
glass. See *Sands*.
Raw materials (*continued*)
for lightweight aggregates, (2) 43*i*.
for lightweight aggregate, in New Hampshire, (8) 225*j*.
lime, in Kansas City area, (3) 64*h*.
for magnesite brick, (2) 44*e*.
perlite as, uses and properties, (10) 288*j*.
porcelain, inspection for metal contamination, (5) 133*j*.
processing, in Germany, (2) 50*j*.
quality control in, (10) 298*d*.
refractory, Philippine aluminous laterite deposits as, (9) 253*h*.
refractory, vibratory mills for, (10) 284*h*.
for silica refractories, (6) 161*f*.
size, effect on glass melting rate, (3) 66*e*.
South Australian, for brick, (5) 132*c*.
for synthetic mica, low cost, (8) 225*j*.
Reactivity, chemical, of BNL graphite, effect on length of channel cooled by air, (6) 160*h*.
chemical, of UO_3, I, (10) 290*i*.
of lime, effect of calcining temperature, (7) 178*j*.
of solid surfaces, radiation effects on, (2) 58*b*.
surface, role of crystalline structure in, (11) 316*d*.
Reactors, atomic, system for supporting nuclear fuel in, P (11) 308*j*.
BeO applications in, (8) 215*d*.
ceramic materials for, (10) 273*i*.
control rod materials, (8) 214*b*.
fuel assay, P (4) 102*i*.
fuel elements, recovery process, P (8) 216*d*.
gas-cooled, materials for Core I fuel assemblies for, (4) 101*b*.
gas-cooled, semihomogeneous fuel element for, (4) 100*i*.
gaseous suspensions of graphite as coolant, (4) 101*e*.
graphite, Oak Ridge, stored energy in, (10) 276*j*.
graphite-moderated, method of making, P (8) 216*j*.
Handbook, Vol. III, Part B, Shielding, B (10) 299*j*.
material, concrete as, (10) 266*h*.
materials, properties of and radiation damage effects, B (8) 233*b*.
neutronic, fuel element for, P (11) 308*c*.
nuclear, coated carbon element for, P (5) 133*c*.
control rod, P (8) 215*j*.
element for, P (6) 163*a*.
fuel-breeder fuel element, P (1) 16*j*.
fuel composition for, P (11) 308*c*.
fuel element, P (8) 216*b*; P (10) 277*b*.
fuel elements, importance of oxides and carbides for, (10) 274*b*.
of graphite impregnated with U compounds, P (5) 133*d*.
graphite moderator structures for, P (8) 216*f*.
moderator structures, P (4) 121*i*.
preparation of C with high moderating properties for use in, P (1) 17*g*.
protective glass sheaths for fissionable fuel elements for, P (3) 70*c*.
recovery of values from used fuels for, P (6) 167*b*.
refractory insulator as safety device, P (4) 103*c*.
use of ceramics in, (11) 306*h*.
with vertical channels, fuel for, P (8) 216*b*.
with vitreous silica guide tube, P (9) 245*b*.
nuclear power, dispersion-type materials in, (10) 275*f*.
possible fuels for, (10) 274*g*.
power, fast breeder, Pu fuel systems for, B (8) 232*j*.
Reagents. See also specific types.
tritium bremsstrahlung, use in absorption method for determining S in heavy oil and ash in coal, (4) 108*f*.
Reflectance. See *Reflection*.
Reflection, of BeO, (4) 114*h*.
of materials and coatings, determination, (8) 222*h*.
of recrystallized opaque glazes, (3) 75*i*.
standard, opal glass MS14 as, (5) 129*i*.
Reflectivity. See *Reflection*.
Reflectometers, tristimulus 45° 0°, uniformity tests, (6) 168*e*.
Refraction, corrections, for universal stage measurements, I, (9) 257*a*.
laws of, graph for calculation of, (4) 107*h*.
molar, in checking coordination, (5) 147*g*.
of rutile, effect of electric field, (5) 143*h*.
of synthetic sapphire, (5) 145*b*.
Refractive index, of borosilicate glasses, change with thermal treatment, (5) 128*h*.
of La borate glass, (11) 304*f*.
of morinite crystal, new values, (6) 168*d*.
of striae in optical glasses, (5) 130*b*.
of synthetic quartz crystals in ultraviolet, B (9) 263*h*.
Refractivity. See *Refraction*.
Refractories. See also *Aircraft ceramics; Insulation, thermal; Kiln furniture; Silicon, carbide*.
abradable, composition, P (1) 15*g*.
acid, increase in Al_2O_3 content or mullite quantity (10) 274*d*.
in Ajax furnace, (6) 161*b*.
alkali-bonded unfired, P (2) 45*i*.
alumina, β-, fused cast, role in glass tank superstructures, (2) 40*h*.
brick, evaluation, (8) 213*h*.
in cement kilns, (1) 2*h*.
composition, P (3) 73*f*.
fusion-cast, stability of, (1) 14*j*.
for glass tank throats, (1) 7*b*.
high-, bricks, in roofs of continuous slab reheating furnaces, (11) 306*d*.
high-, in ironmaking, (11) 306*g*.
high-, laboratory experiments on, (11) 306*e*.
high-, symposium on, (11) 306*j*.

Refractories, alumina (*continued*)
ramming nonshrinking bodies, (1) 13*f*.
treatment with Li borate, P (1) 16*g*.
alumina silica, relation between apparent porosity, Shore hardness, and abrasion resistance, (1) 15*d*.
aluminosilicate, brick, specific heat of, (3) 73*d*.
aluminosilicates, quantitative X-ray study, (11) 306*b*.
aluminum, for melting furnace, P (6) 161*i*.
Al-resistant, electrically conductive, P (3) 73*g*.
asbestos-bentonite, method of making, P (10) 277*h*.
Association, visit of team to U.S.S.R., (1) 15*e*.
ASTM standard for, B (9) 259*b*.
bakor-33, for glass furnaces, (1) 13*j*.
basic. See also *Refractories, chrome-magnesite*.
brick, burned, for front furnace wall, (11) 306*f*.
brick, high-fired, for open-hearth roofs, (8) 213*c*.
brick, metal-encased, P (9) 244*g*.
brick, molding with metallic hanger, P (1) 17*c*.
brick, reactions in, (9) 243*j*.
composition and method of making, P (2) 46*j*.
evaluation of testing methods, B (10) 300*i*.
heat resistant coating for, P (9) 244*j*.
high-temperature firing of, (8) 214*a*.
lightweight, experimental production, (1) 13*i*.
metal-cased brick, for open-hearth roof, P (9) 244*g*.
open-hearth furnace, loss of hearth in, (11) 306*a*.
open-hearth furnace, magnesite vs. seawater magnesia clinker for, II, (11) 305*g*.
oper-hearth furnace roof brick, effect of coarse MgO grains, (11) 305*j*.
specific heat of, (3) 73*d*.
sprayable, for repairing hot furnace linings, P (9) 245*e*.
survey of present knowledge, (6) 160*g*.
in basic open-hearth furnaces, effect of oxygen on, (6) 161*a*.
basic seawater magnesia-dolomite, for LD converters, (6) 161*f*.
blast-furnace, linings. See *Refractories, linings*.
blocks, for glass tanks, thermal conductivity of, (1) 10*a*.
body, coating with BN and reacting with Al, P (7) 189*j*.
high density, P (1) 17*a*.
method of making, P (9) 244*d*.
bonding to metals, P (9) 249*g*.
B-Si, analytical methods for, (8) 212*d*.
bottom rings, for composite hot tops, P (3) 73*h*.
bottoms, in VLN steelplant, (6) 161*j*.
brick. See also *basic* and specific types under *Refractories*.
comolding metal insert in, P (7) 189*h*.
as furnace block, hanger socket in, P (4) 102*j*.
for furnace wall, P (8) 217*c*.
geometrical metal tube for making, P (11) 308*g*.
improved method of laying in checker chambers, (11) 306*a*.
metal-cased, P (5) 133*a*.
metal-cased, apparatus for bending sheet metal hanger tabs away from ends of, P (1) 15*i*.
method of adding casing, P (7) 189*g*.
method of making, P (4) 103*c*; P (6) 160*a*.
molding apparatus for incorporating metal inserts, P (5) 133*b*.
molding with metallic hanger, P (1) 17*c*.
package for storing and transporting, P (3) 73*h*.
Philippine clays for, (3) 83*a*.
presses for and machine for automatic removal from press, (10) 276*g*.
process control at press, (11) 311*i*.
recalcining of bauxite for, (4) 101*f*.
from seawater magnesia, (9) 243*h*.
spiraling arch, for rotary kiln, P (2) 46*h*.
thermal expansion of, (3) 73*d*.
briquetted materials, flux coating of, P (4) 102*f*.
burner block, with refractory cup, P (1) 16*f*.
calcium boride, brick, neutron-absorbing, P (9) 244*e*.
calcium zirconate, P (3) 73*i*.
carbides, applications of, B (3) 92*g*.
carbon, bricks, nonporous, for cellulose digesters, P (4) 103*b*.
joining process, P (2) 46*h*.
method of coating surfaces, P (6) 162*j*.
castable, effect of batch temperature and curing time on transverse strength, (11) 305*h*.
lightweight, P (6) 162*e*.
pneumatic gun operating variables affecting, (6) 160*a*.
pneumatic placement of, I, (10) 275*d*.
spodumene-based, (9) 243*h*.
thermal conductivity of, (4) 101*j*.
for tunnel kiln car tops, (3) 71*i*.
casting compositions, P (5) 133*i*.
cellular, uniform, manufacture of, P (2) 46*a*.
in cement kilns, problems in, (1) 2*h*.
Cerac, preparation of, (6) 159*e*.
ceramic bodies, P (4) 103*c*.
ceramics, for aerospace systems, (10) 276*b*.
checker-brick, in furnace with rotating specimen holder, slagging tests, (7) 188*f*.
checker chambers, improved method of laying brick in, (11) 306*a*.
checker chambers, sillimanite brick for, (11) 306*g*.
in chemical processes, (3) 73*c*.
chromate content, effect on clinker in cement kiln, (3) 72*i*.

Refractories (*continued*)
chrome-magnesia, brick, unburned, for open-hearth roof, (11) 306*a*.
chrome-magnesite. See also *Refractories, magnesite-chromite*.
brick, hot strength tests, (2) 52*i*.
for pouring nozzle, P (10) 278*b*.
chrome silica, brick, P (7) 189*i*.
chromite, high-temperature firing, (8) 214*a*.
chromium oxide, P (4) 102*d*.
clays. See *Clays*.
coatings. See *Coatings*.
coatings over, to reduce dusting and spalling, (5) 132*j*.
for combustion catalysts, P (3) 74*g*.
commercial, compatibility of 11 types, (1) 14*j*.
composite, method of making, P (3) 74*c*.
composition, P (8) 217*a*.
containing SiO_2 and SiC, P (2) 46*g*.
and properties, (9) 243*d*.
compound parts, P (3) 74*a*.
compounds, radiation coefficients of, (1) 14*i*.
concrete. See *Concrete*.
containers, method of making, P (3) 74*e*.
for converters, in Japan, (6) 161*h*.
converters, study of lining wear by use of radioactive isotopes, (3) 72*b*.
core, insert, for slide shut-off device, P (9) 244*c*.
cores, preformed, in metal casting, (8) 212*i*.
corrosion, B (4) 123*j*.
mechanism of, in zebra roof of basic open-hearth furnaces, (3) 73*i*.
by molten glass, (1) 5*j*; (1) 6*a*.
corrugated sheets, as milieu for gaseous reactions, P (8) 224*j*.
cradle, zirconia setter, P (9) 244*g*.
crucibles, Be, in making neutron source, P (5) 133*c*.
boron nitride, treatment with molten Al, P (3) 74*c*.
CaO, casting method, (5) 132*d*.
for controlled thermal evaporation in vacuum, (1) 19*j*.
corrosion by Na_2O, (4) 117*g*.
effect of material on magnetic anisotropy of evaporated Permalloy films, (5) 132*h*.
for growing Ba titanate crystals, (5) 141*j*.
materials for, P (1) 15*j*.
materials, effect on induced anisotropy of evaporated iron films, (10) 274*e*.
for melting Si, lining of, P (4) 102*c*.
for melting silicon of highest purity, P (1) 20*d*.
miniature, for burning metal samples and ceramic material, P (11) 308*i*.
silica or alumina, reaction rate with molten high carbon iron, (1) 14*a*.
slip-cast, of CaF_2, in U smelting, (10) 275*b*.
of slip-cast urania, (11) 307*c*.
dead-burned grain, production, P (2) 46*c*.
diatomite, brick, specific heat of, (3) 73*d*.
Dinas, brick, highly tridymitized glass, production of, (7) 189*b*.
dolomite, brick, package for storing and transporting, P (3) 73*h*.
in cement kilns, (1) 2*h*.
in oxygen steelmaking units, (6) 160*i*.
process, P (5) 133*f*.
properties and applications, (10) 274*g*.
stabilized, blocks, P (3) 74*b*.
doors, for open hearth furnace, P (7) 189*j*.
dust, control in plant, (11) 312*b*.
electrically melted, with mineral oxides, P (6) 162*g*.
for electric furnace steelmaking, (6) 160*e*.
electrocast, for direct-heated tank furnaces, (1) 8*i*.
electrofused, for glass furnaces, (1) 13*j*.
evaluation by chemical and physical tests, (3) 72*e*.
fibers, for ablation and thermal insulation, (6) 160*c*.
Al borate, P (6) 162*b*.
in casting mold, P (6) 161*j*.
filaments, method of making, P (10) 277*c*.
forming and collecting into improved pipe covering, P (3) 74*c*.
forming process, P (7) 189*a,b*.
in furnace combustion chamber, P (11) 308*e*.
high viscosity, (8) 214*c*.
oxide, P (7) 189*f,g*.
production and performance, B (5) 148*c*.
in refractory-forming mat, P (9) 245*a*.
fibrous, method of making, P (9) 244*i*.
firebrick, corrosion by ash of borax-impregnated timber, (10) 275*i*.
firebrick, insulating, production processes, (2) 44*g*.
fireclay, brick, C deposition in CO atmosphere, I, (11) 306*c*.
brick, erosion resistance to high calcareous slag, I, (1) 13*g*.
ladle bricks, reactions with basic slags, (8) 214*a*.
strength of press-mold plates for pressing, (7) 188*j*; (7) 189*a*.
foamed, SiC, P (11) 308*a*.
foamed plastic sponge shape, P (10) 277*e*.
-forming products, P (9) 245*a*.
forsterite, brick, in open-hearth furnace, (8) 215*c*.
forsterite, checkers, in high-load open-hearth furnaces working with oxygen, (7) 187*j*.
fused-cast, B (4) 123*c*.
β-alumina, role in glass tank superstructures, (2) 40*h*.
for glass tank blocks, (7) 187*k*.
kinetics of phase transformations in production of, (10) 274*i*.
fused corundum, production and service in Hungary, (7) 188*k*.
fused silica, B (10) 300*j*.
glass furnace, testing of, (4) 101*i*.
for glass industry, (6) 160*f*; (10) 275*j*.

Refractories (*continued*)
glass tank, effect of fuel oil ash on, (8) 213*e*.
in glass tank throats, changes in physical properties, (3) 72*h*.
in glass tank throats, effect of mechanical properties, (8) 208*i*.
granular materials, flux coating of, P (4) 102*f*.
graphite, for mold bottoms for top pouring killed steel, (7) 187*e*.
hangers, roof brick, snapping of, (11) 306*h*.
hearths, brick vs. ramming materials, (11) 306*a*.
heat shield, hinged, for ladle bottoms, P (8) 216*h*.
high-temperature, rare-earth compounds as, bibliography, (1) 14*j*.
homogeneous composition, P (4) 102*g*.
hot tops, bottom rings for, P (3) 73*h*.
casing, for casting molds, P (5) 133*i*.
casing for production of shrinkage funnel inhibitor coating in, P (10) 276*j*.
with exothermic inserts, P (3) 74*b*.
ingot mold design, P (5) 133*a*.
method of making, P (6) 162*h*.
seal for, P (9) 244*b*.
tightening device for, P (9) 245*g*.
Indian seawater magnesia for making, (6) 170*h*.
insulating. See also *Refractories, firebrick*.
board, composition, P (10) 277*b*.
lightweight fibrous porous, P (9) 245*b*.
for process vessel, cost of, (8) 221*g*.
unusual shapes, vermiculite in, (10) 276*h*.
insulator, as safety device for nuclear reactor, P (4) 103*c*.
for iron and steel industries, problems and developments, (5) 132*g*.
key brick cases, apparatus for making tapered metal blanks for, P (8) 215*e*.
for kiln furniture. See *Kiln furniture*.
"korvishit," production and service in Hungary (7) 188*h*.
ladle, bottoms, hinged heat shield for, P (8) 216*h*.
casting, semiacid refractories for, (3) 72*h*.
rammed, tests of Belgian Ladelit, (11) 308*h*.
Ladelit, for Belgian rammed ladle, (11) 308*h*.
laminates, in refractory technology and engineering, (10) 276*c*.
for LD converters, in Japan, (6) 161*e*.
lightweight, as hot-face insulation in kilns, (7) 196*h*.
lightweight, organic additives for, P (2) 46*g*.
linings, for Al_2O_3 reduction cells, P (9) 245*c*.
for blast furnace, P (4) 102*c*.
boiler, thermal conductivity measurements on, (3) 73*b*.
brick, for metal ore reduction furnace, P (7) 189*b*.
in converters, study of wear by use of radioactive isotopes, (3) 72*b*.
for crucibles for melting Si, P (4) 102*c*.
dolomite, with carbonaceous bond, P (2) 45*d*.
enclosing studs in furnace, P (1) 16*b*.
for furnace, modern plant production, (2) 44*j*.
in Kaldo process, (6) 161*j*.
for kilns, B (10) 300*h*.
for LD furnaces in Austria, (6) 161*c*.
for LDAC converter, (6) 161*h*.
magnesite, for rotary cement kilns, P (3) 74*g*.
periclase chrome-magnesite, for rotary cement kiln, (7) 188*g*.
for pressure vessels, gastight seal in, P (1) 16*i*.
of rotary kilns, (1) 24*i*.
in Rotor process, (6) 161*a*.
for vertical limekiln, (11) 314*e*.
magnesia, above 1500°C, (3) 73*e*.
brick, unburned, for basic open hearth, (11) 305*h*.
in cement kilns, (1) 2*h*.
high-, roof brick, trial results, (11) 308*h*.
impervious high-density, P (9) 244*c*.
lubricant aids in manufacture of, (1) 13*i*.
strength of press-mold plates for pressing, (7) 189*a*.
magnesia-chrome, coarse grain, quality change in, (11) 305*f*.
magnesia-chrome, effect of atmosphere on properties, (11) 305*f*.
magnesia-dolomite, for LD converters, (6) 161*f*.
magnesite. See also *Refractories, chrome-magnesite*.
brick, effect of Cr in on cement clinker, (3) 72*i*.
brick, hot strength tests, (2) 52*i*.
brick, manufacture of, (2) 44*e*.
brick, manufacture of, II, (4) 101*b*.
brick, thermal conductivity of, (3) 73*a*.
magnesite-chromite, comolded tuyere, P (8) 215*h*.
molded, P (4) 102*b*.
used arch, chrome spinellids in, (5) 132*e*.
masses, P (6) 162*h*.
materials, for air heaters for blast furnaces, P (3) 74*h*.
air separator for sizing, (9) 250*h*.
apparatus for measuring modulus of rupture (2) 52*i*.
from Bansi and Bmlo, properties and mineralogical nature, (2) 54*f*.
consolidating, P (6) 162*a*.
in dies, high-pressure, P (3) 80*b*.
inorganic binder for, P (2) 45*i*.
moduli of elasticity at high temperatures under vacuum, (9) 245*e*.
process, P (3) 74*g*.
and product, method of making, P (6) 162*d*.
from pure Al_2O_3, P (3) 74*i*.
pyrolytic, for solid-fuel rocket motors, (8) 212*j*.
rapid analysis, (1) 13*e*.
reactions between, (1) 14*j*.
research, (8) 212*f*.
resistance to corrosion by molten glass, stirring test for, (2) 45*g*.
sintered hard, from alumina and Zr nitride, P (3) 75*a*.

Refractories, materials (*continued*)
specific heat of, (3) 73*d*.
thermal conductivity of, (1) 15*c*.
vaporization of, (7) 189*e*.
metal-aggregate, readily sawn, P (2) 46*b*.
for metal casting, P (2) 46*e*.
metal-encased unit, for furnace lining, P (8) 217*a*.
metallized, porous, apparatus for making, P (5) 133*a*.
mica, brick, factors affecting properties, (3) 72*c*.
microstructures of, B (11) 321*a*.
mixture, exothermic, P (7) 189*j*.
molded bodies, abrasion-resistant, P (6) 162*i*.
molds. See *Molds*.
mold top brick, wear of, (11) 308*a*.
Mo silicide-Al oxide, P (6) 162*d*.
mullite, brick, evaluating, (8) 213*h*.
mullite, high-, P (3) 74*f*.
mullite-Carborundum and corundum-Carborundum, spalling resistant, B (10) 300*h*.
multilayered composite metal, with BN layer, P (9) 245*a*.
nipple, for lipping into molten metal, P (2) 46*g*.
nipple connection, screw, for carbon electrodes, P (1) 17*c*.
nozzles, of chrome-magnesite mix, P (10) 278*b*.
nozzles, service for continuous pouring of steel, (1) 15*g*.
in OLP process applied to high-P iron, (6) 161*i*.
oxides, applications of, B (3) 92*g*.
as basic raw materials, B (4) 123*i*.
coating with oxide of transition metal, P (4) 102*d*.
crystals, preparation, P (3) 74*j*.
dispersed in iron group metals, P (8) 216*i*.
dispersion in another metal, P (8) 217*a*.
dispersion for hardening metals, P (4) 103*e*.
dispersion for strengthening metals, P (4) 102*i*; P (4) 103*b*.
electric behavior, (8) 219*h*.
glass attack on, (8) 228*a*.
phase equilibria with B oxides, (8) 229*f*.
in oxygen process for iron and steel making, I, II, (6) 160*j*.
for oxygen steelmaking, (6) 160*g*.
particles, in three-phase coating, (1) 4*j*.
pattern, disposable, with lower melting external coating, P (3), 73*i*.
periclase, brick, low-iron, spalling-resistant, P (6) 162*f*.
periclase, effect of additions on sintering and properties, (7) 187*h*.
periclase chrome-magnesite, lining, for rotary cement kiln, (7) 188*g*.
physical properties, changes in, (3) 72*h*.
plant, modern layout, equipment, and operation, (2) 44*j*.
porous, metallized, apparatus for making, P (5) 133*a*.
porous foamed silicate, P (10) 277*c*.
pots, from Grossalmerode clay and chamotte, (10) 274*d*.
pouring-pit, erosive effect of molten steel on, (11) 305*j*.
pouring pit, status in Japan, (6) 160*c*.
pouring spout, P (2) 46*g*.
processing at temperatures lower than use temperature, (8) 213*b*.
pyrolytic deposition, advantages of, (2) 44*h*.
pyrophyllite, control of reversible thermal expansion by talc additions, (4) 100*j*.
quality, determination of, (9) 243*d*.
ramming bodies, high alumina nonshrinking, (1) 13*f*.
ramming compositions, P (5) 133*i*.
raw materials. See *Raw materials*.
reaction with molten steel, VII–IX, (1) 14*i*.
regenerators, checkers, in glass furnaces, rational parameters for, (8) 224*h*.
of open-hearth furnaces, corrosion of checker-brick in, (8) 212*j*.
secondary, in combustion control, (10) 287*g*.
relining, in VLN steelplant, (6) 161*j*.
research on, (1) 15*e*.
for rocket nozzles, research on materials for, (8) 214*d*.
roofs, basic, ribbed, P (10) 277*h*.
block, P (8) 216*e*.
brick hangers, snapping of, (11) 306*h*.
design for open hearth furnace, (1) 14*b*.
high magnesia brick, trial results, (11) 308*h*.
open-hearth, effect of height increase, (11) 305*i*.
open-hearth, high-fired basic brick for, (8) 213*c*.
open-hearth, unburned chrome-magnesia brick for, (11) 306*a*.
suspended, P (9) 245*d*.
with suspended arch, P (3) 74*i*.
zebra, of open-hearth furnace, corrosion mechanism of, (3) 73*i*.
semiacid, for casting ladles, (3) 72*h*.
saddles, apparatus for molding, P (3) 74*j*.
service in direct-heated tank furnaces, (1) 8*i*.
silica, brick, from northern Ill. silica sand, (8) 214*i*.
brick, for open-hearth furnaces, P (6) 162*i*.
brick, pure quartz in, (6) 161*h*.
brick, from roof of Cu furnaces, (8) 214*j*.
brick, specific heat of, (3) 73*d*.
brick, used, density of zones in, (8) 212*h*.
brick plant, ganister quarrying for, (11) 314*h*.
effect of V compounds on, (8) 213*g*.
lubricant aids in manufacture of, (1) 13*i*.
review of, (6) 161*f*.
and silicon carbide, P (2) 46*g*.
silicoaluminous, effect of technological factors on properties of, (3) 72*j*.
Si-B-O, in sintered article, P (10) 277*j*.
SiC, P (3) 75*a*.
sillimanite as, I, (3) 73*j*.
brick, flux line corrosion in, (3) 72*d*.

Refractories, sillimanite (*continued*)
brick, for slag chamber and checker chamber, (11) 306*g*.
for glass tank furnaces, (6) 161*f*.
sintered, article, method of making, P (10) 276*f*.
porous shape, method of making, P (10) 277*e*.
in pouring nozzle for molten metal, P (10) 278*b*.
slag. See *Slags*.
slag chamber, sillimanite brick for, (11) 306*g*.
slagging failure, in cement rotary kilns, (2) 45*e*.
sleeve brick, tentative plan for standardization, (11) 308*h*.
smelter blocks, with glass-containing ground slag, hardening of blanks for, P (3) 74*a*.
Na_2O-Al_2O_3-ZrO_2, studies of, (4) 121*c*.
spalling cracks in, mechanism of formation, (9) 244*d*.
spalling-resistant, for steel-casting plugs, (7) 188*a*.
special shapes, bottom lift kilns for firing, (10) 287*f*.
spinel, unburned, trial for open-hearth furnace roofs, (11) 308*i*.
for stationary boiler service, moderate duty, (3) 72*e*.
steel-casting plugs, spalling-resistant, (7) 188*a*.
in steel melting furnace, rotary, (7) 188*d*.
steelplant, testing, research, and development, B (10) 299*j*.
stopper, for ladle, P (9) 245*f*.
strength, effect of batch temperature and curing time, (11) 305*h*.
strength, as function of pore content, (1) 15*a*.
structures, for furnace, P (6) 162*c*.
structures, high temperature, methods of making, (8) 213*f*,*h*,*i*.
substrate, nonporous, application of oxide coating, P (7) 183*i*.
super-, hot-pressing of, V, (10) 275*d*.
super-, products, of oxynitride bonded SiC, (10) 276*b*.
of system Na_2O–Al_2O_3–ZrO_2, II, (4) 121*c*.
tank blocks, sillimanite for, (3) 73*j*.
for tank blocks for glass furnaces, P (6) 162*b*.
tapping rod, with lime coating, P (2) 46*h*.
tar-dolomite, brick, preparation and testing, (7) 187*h*.
technology, background of, (10) 273*j*.
test data, statistical evaluation, B (10) 300*h*.
testing, review of, (1) 13*e*.
thermal conductivity of, measurement by hot-wire method, (3) 72*a*.
thermal expansion, relation to packing of particles, (3) 72*g*.
thermal properties of, (8) 215*b*,*c*.
thermite material, for thermocouple protection, (10) 276*f*.
thermoplastic, P (6) 163*a*.
for throat of glass tank furnace, I,II, (1) 7*b*.
tuyeres, ceramic coated, P (4) 97*g*.
magnesite-chromite, comolded, P (8) 215*h*.
with preformed refractory nose and sleeve, P (4) 75*a*.
reinforcing insert for, P (8) 217*b*.
use, problems in, (3) 72*e*.
vermiculite, brick, specific heat of, (3) 73*d*.
ware setter, ceramic, P (2) 45*b*.
zircon, brick, specific heat of, (3) 73*d*.
corrosion by molten glasses, I,II, (1) 6*c*.
resistance to slag attack, (7) 188*f*.
suitability as glass-contact or superstructure refractories, (7) 189*h*.
technology of casting, (1) 14*c*.
ZrO_2, analytical methods for, (8) 212*d*.
for crucibles, P (1) 15*j*.
setter, P (9) 244*g*.
zirconia-alumina-silica, fusion cast tank block (10) 275*j*.
ZrB_2-silicide, P (8) 217*b*.

Refractories industry, in Argentina, market for, (9) 258*i*.
Russian, mining concerns in, (7) 197*h*.
Russian, visit of Refractories Assn. team to, (1) 15*e*.

Refractoriness, of clay from Kerala State, (6) 170*c*.

Regenerators. See *Refractories*.

Replica method. See *Microscopy*.

Research and research laboratories, in clay pipe plant, benefits of, (10) 273*f*.
fundamental principles of ceramics from standpoint of, (11) 320*e*.
image furnace as tool in, (1) 28*i*.
on lasers, (2) 48*d*.
National Physical, 1962 report, B (8) 231*a*.
Ontario Research Foundation, glass and ceramic research, (7) 184*e*.
scientific, present and future in ceramic industry, (5) 148*c*.
U.S. vs. British, (9) 258*g*.
value and planning of, (1) 15*e*.

Resins. See also *Plastics*.
Al, with exchangeable Al^{3+}, for precipitation of phosphate, (5) 145*a*.
as bond for glass fibers, P (1) 12*e*.
in coated abrasives, (2) 33*f*.
epoxy, as impregnant in preparation of thin sections of asbestos cement, (9) 236*i*.
epoxy, for oil immersion and heavy mineral studies, (6) 167*j*.
inorganic, high-temperature stable, research on, (8) 229*b*.
modified phenolic laminate, quartz cloth reinforced, (9) 240*c*.
polyester, and epoxy laminates, glass cloth reinforced, (9) 239*e*.
polyester, in sewer-pipe joints, (9) 243*c*.
resilient synthetic, for clay pipe joint, P (2) 44*c*.
synthetic, as binders for abrasives, P (3) 63*g*.
expanded, as layer on glass bulb, P (3) 69*e*.

Resins, synthetic (*continued*)
fibers, combination with glass fibers, P (9) 242*b*.
in grinder or hone with fine cushiony surfaces, P (9) 236*d*.

Resistance, electric. See also *Conductivity, electric*.
control element, temperature responsive, P (8) 224*c*.
device, magnetically responsive, P (7) 193*d*.
effective, of piezoelectric quartz crystals, control of, P (2) 49*h*.
elements, mounting for, P (1) 16*h*.
of fused magnesia, relation to temperature, (9) 244*a*.
of glass, relation to relative humidity, (11) 304*a*.
of metallic oxide thermistors, method of adjusting, P (6) 166*f*.
negative, current-controlled, in thin Nb oxide films, (10) 280*b*.
nonmetallic elements, P (7) 193*i*.
photo-, CdS cells, oxide bases for, P (3) 77*c*.
thin films with negative temperature coefficient of, P (4) 106*a*.

Resistivity, electric, of cast UC_2, effect of irradiation, (11) 308*d*.
of cubic sodium tungsten bronze, (3) 86*c*.
of lead tungstate, (4) 104*g*.
of liquid Na, liquid Li, and dilute liquid Na solutions, (2) 57*c*.

Resistors, electric, apparatus for cutting helix in, P (3) 77*a*.
bolometers, method of making, P (3) 78*g*.
with CdS powder, P (1) 21*g*.
with ceramic core tube, P (4) 106*b*.
conductive components for, P (1) 21*h*.
construction, P (4) 105*h*.
covered, method of making, P (2) 49*e*.
edge wound, alumina coatings for mounting bar for, (7) 183*e*.
fixed and variable, developments in, (9) 248*j*.
with glass-silicone seal, P (1) 21*f*.
high voltage, recent developments, (9) 248*a*.
integral, in spark plugs, P (8) 221*a*.
long-term stability of, (9) 247*c*.
mass production, P (10) 283*c*.
with memory, in components for adaptive control systems, (7) 191*b*.
metal oxide, adjusting resistance of, P (6) 166*f*.
metal oxide, with glass coating, P (4) 105*g*.
method of making, P (7) 183*j*.
micromolecular, P (2) 50*c*.
precision, from glazes, (10) 281*i*.
pyrolytically decomposed, from C, O, and Si, P (5) 137*f*.
tin oxide and Nichrome films as, (10) 279*i*.
from valency-controlled ferroelectric solid solutions, (6) 165*b*.

Resonance, adsorption, zero-field, in determination of effective internal field in $NiTiO_3$, (10) 279*f*.
in determining elastic moduli, (7) 195*i*.
dielectric, in system γ-alumina–water, (2) 56*e*.
dispersion, mechanical, in quartz, at audio frequencies, (3) 87*f*.
electron paramagnetic, of defects in irradiated silicon, (8) 227*g*.
electron spin, paramagnetic, in study of irradiated aluminosilicate glasses, (2) 39*i*.
ferrimagnetic, in Y Fe garnet at liquid He temperatures, (2) 57*e*.
nuclear, of ^{27}Al, in spinel, (4) 119*c*.
nuclear magnetic, in determination of H positions in $Ca(OH)_2$, (7) 199*a*.
in study of alkali borate glass structure, (9) 240*i*.
in study of lead borate glass structure, (9) 241*a*.
optical and magnetic, in study of substructure of crystals, B (9) 260*i*.
spin, of ion pairs in crystal lattices, B (9) 260*d*.
thin rod, in determining Young's modulus, (10) 286*g*.
V-type center, of neutron-irradiated LiF at room temperature, (2) 59*i*.

Resonators, Al-plated quartz, stable, P (1) 21*f*.
ceramic, 3-terminal, as oscillator circuit, (7) 192*c*.
synthetic quartz, effect of electrolysis on performance, (9) 247*c*.

Reyerite (=truscottite), synthesis of, (4) 112*h*.
synthesis and crystal chemistry, (5) 146*f*.

Rhenium, compounds, with ordered perovskite structure, (1) 25*j*.

Rheology, of coal in early stage of thermal softening, (7) 196*g*.
concrete mixture, (6) 154*b*.
curves, of ceramic bodies, significance in ceramic technology, (1) 29*e*.
of kaolinite, effect of exchangeable cations, (3) 87*c*.
laboratory handbook of, B (10) 300*e*.
laws, of long-time deformation of concrete, (7) 182*a*.
parameters, of clays, thixotropic behavior, (3) 83*g*.
of plastic cement, (8) 205*j*.
of portland-cement concrete, (10) 267*c*.
properties, of alkaline earth bentonites, improvement of, P (4) 110*i*.
of semicoke, at high temperatures, (7) 196*i*.

Roasting, of perlite, fountain-type furnace for, (2) 54*d*.

Rockets. See *Space vehicles*.

Rocks. See also *Phosphates; Silicates*.
amphibolite, fluorescent X-ray spectrographic analyses, (4) 114*d*.
argillaceous, recalculating chemical analyses for comparative purposes, (6) 170*i*.
basic igneous, interstratified clay minerals from, (11) 315*b*.
bed, method of making holes in, P (10) 289*d*.
calcination in annular kilns, P (3) 83*e*.
carbonate, of Missourian stratigraphic sections in New Mexico, (3) 87*b*.

Rocks (*continued*)
carbonate, of Tennessee, expandable chloritic clay minerals from, (4) 109*h*.
chemical composition, estimation of, (4) 107*g*.
crusher, P (2) 56*a*.
difficultly spallable, apparatus for thermally working, P (9) 254*a*.
excavation by blasting, charge holder for, P (11) 315*h*.
free silica in, quantitative determination by X ray, (9) 251*i*.
grinding apparatus for, P (10) 290*b*.
igneous, titanomaghemite in, (4) 110*j*.
glassy volcanic, microlites in, (6) 170*d*.
Paleozoic carbonate, of N. Mex., quantitative petrographic study of, (4) 110*e*.
porous, rapid determination of permeability in, (6) 168*h*.
silicate, complexometric analysis, (9) 252*h*.
determination of sulfur in by wet oxidation, (9) 251*a*.
semimicroanalysis for Ca, Fe, Mg, and Al employing EDTA, (3) 83*f*.
spectrochemical analysis of, (1) 30*e*.
stabilization of mine roofs, P (9) 254*h*.
subalkaline igneous, with different O pressure conditions, reaction series for, (7) 199*i*.
Virginia, (10) 289*c*.
Rock wool. See *Mineral wool*.
Rotors, in apparatus for making mineral wool, P (1) 12*e*.
for mixing and pulverizing machines, P (5) 141*e*.
Rubidium, analcite, dielectric properties, (8) 219*a*.
chloride, systems. See *Systems*.
chloride, transition point depression of CsCl by, (2) 59*d*.
fluoaluminate, as dielectric material, P (10) 282*f*.
Ruby. See also *Lasers; Masers*.
anomalous *g* shifts of excited states of Cr^{3+} in, (6) 171*h*.
crystals, synthetic, Cr distribution in, (5) 142*c*.
flux-grown, low radiation loss in, (10) 280*b*.
giant optical pulsations from, (7) 190*j*.
growth in arc-image furnace, (10) 284*g*.
luminescence and relaxation spectrum, (6) 164*h*.
quantum efficiency of, (10) 281*e*.
ring, laser operation in without spikes, (10) 280*j*.
synthetic, optical and stress-optical properties, (2) 58*f*.
thermal conductivity of, (1) 30*e*.
vibration spectra in infrared region, (5) 147*c*.
Rupture, modulus, of refractory materials, apparatus for measuring, (2) 52*i*.
Rust, control of, (9) 238*b*.
control with organic and enamel coatings, (11) 302*i*.
Ruthenium, oxide, hydrous, preparation and properties, (11) 318*g*.
Rutile. See also *Titanium, dioxide*.
anatase-, transformation, effect of SO_3, (7) 199*a*.
anatase-, transformation, factors affecting, (10) 295*c*.
brookite-, transformation, (10) 295*a*.
brookite-, transformation, effect of particle size and purity, (5) 146*c*.
crystals, dislocations, etch-pit technique, (1) 27*a*.
defect structure, thermogravimetric studies, (8) 230*a*.
diodes, field emission in, (10) 280*b*.
elastic constants of, (3) 86*j*.
growth in arc-image furnace, (10) 284*g*.
high-temperature steady-state creep in, (10) 293*b*.
as host crystal for construction of 70-Ge laser, (10) 282*e*.
nonstoichiometric, dielectric properties, (5) 134*i*.
production from ilmenite, (7) 197*j*.
pulse currents in, (10) 281*c*.
pure and reduced, low-temperature heat capacity of, (3) 87*i*.
refractivity of, effect of electric field, (5) 143*h*.
seed, P (4) 111*e*.
single crystal, anisotropic, in active solid-state devices, P (11) 311*a*.
optical and infrared absorption spectra, (4) 121*b*.
reduced, in point contact diodes, (10) 281*f*.
relation between polarization and space-charge-limited currents, (5) 145*c*.
structure, comparison with brookite, (10) 290*f*.
structures, in mixed-phase pigments, (1) 18*i*.
thermal-expansion anisotropy of, (1) 30*g*.
transformation of anatase to, kinetics and thermodynamics of, (11) 318*b*.
-type compounds, refinement of crystal-structure determination in, I–III, (10) 296*h*.

Safety. See also *Health*.
control, for burners, P (5) 140*g*.
device, for molding machines, P (3) 70*d*.
jacket, for handlers of glass loads, (11) 304*f*.
Saggers. See *Kiln furniture*.
Salts, bath, for electrolytic cleaning of metals, P (10) 269*g*.
content, of acidic silica hydroorganosol, decreasing of, P (1) 26*a*.
fused, thermodynamic calculations on phase equilibria involving, I, II, (2) 59*j*.
inorganic, effect on dehydration of calcium sulfate dihydrate, (2) 34*e*.
metal, reduction of, I, (4) 113*b*.
molten, complex ions in, galvanostatic study, (10) 291*c*.
mixtures, V, (10) 295*b*.
mixtures, thermodynamics of activities in, (10) 297*d*.
solubility of MgO in, (9) 257*e*.
NaCl. See *Sodium, chloride*.
soluble, in clays, analysis of, (2) 56*b*.

Salts (*continued*)
systems, molten reciprocal, heats of solution of solid in, (10) 293*j*.
Samarium, divalent, in Sr and Ba fluorides, luminescence kinetics of, (6) 164*j*.
effect on electrical conduction in $BaTiO_3$, (3) 76*f*.
oxide, systems. See *Systems*.
(III), fluorescence of, in study of phosphors, (6) 163*i*.
trifluoride, liquid density of, (1) 28*d*.
Sampling, of air, fine glass fiber paper for, (3) 90*e*.
automatic volumetric, and automatic material transfer, P (5) 139*d*.
continuous, for X-ray analysis, (5) 142*e*.
in control of brick production, (6) 167*c*.
device and method, for condensed furnace gases, P (4) 108*i*.
dust, slow running instrument, (6) 168*e*.
of glassware, plan for, (9) 241*a*.
of granular material in bulk, apparatus for, P (3) 81*b*.
of industrial atmospheres, by light scattering particle counters, (8) 223*a*.
method of clay deposits, (1) 25*f*.
sample splitter, P (5) 140*b*.
statistical evaluation, (10) 298*e*.
systems, for waste gas analysis from furnaces, (8) 224*i*.
Sands, in building materials, (8) 203*j*.
calcareous, substitution for siliceous sand, (1) 3*g*.
with color-imparting impurities, purification of, P (1) 26*d*.
core, mixtures, stickiness of, (8) 214*j*.
foundry, mixture, factors involved in making, (8) 213*a*.
glass, iron removal in abrasive mill, (1) 25*d*.
of Libyan Desert, (1) 9*i*.
separation from clay, (10) 289*a*.
green molding, methyl cellulose additive for, P (10) 277*j*.
high-feldspar-iron, processing for glass wool manufacture, (9) 254*b*.
marks, on steel, identification by electron-diffraction reflection, (6) 159*h*.
removal of iron-containing materials, P (3) 85*e*.
silica, from Ill., silica brick from, (8) 214*i*.
silica, reaction with steel, (9) 243*f*.
Sandstones, ultrasonic wave velocities in, effect of texture, (11) 317*f*.
Sanitary ware, effect of grog particle size on properties, (1) 17*i*.
electric kiln firing of, (11) 314*e*.
manufacture in Russia, (6) 163*c*.
manufacturing controls, (10) 278*d*.
plant, Canadian, (6) 163*d*.
setter, with perforations, P (11) 308*j*.
Sapphire, crystal, in ruby optical maser, (5) 134*h*.
dislocations in, direct observation, (10) 291*i*.
far-infrared properties of, (4) 114*b*.
fibers, preparation, P (6) 162*b*.
formation of spinel on in hydrogen and argon, (1) 29*e*.
growth in arc-image furnace, (10) 284*g*.
infrared properties at high temperatures, (4) 114*g*.
machining of, for tensile testing, (9) 235*g*.
monocrystals, rapid orientation of, (6) 175*e*.
phosphorescence of, (5) 145*b*.
properties, comparison with Al_2O_3 properties, (9) 258*d*.
synthetic, refraction and dispersion of, (5) 145*b*.
Scandium, dodecaboride, preparation and structure, (11) 318*b*.
Scapolite, indexed powder diffraction data, (4) 114*f*.
Scattering, chamber, continuous rotation, for nuclear reaction, P (11) 320*c*.
coefficient, of recrystallized opaque glazes, (3) 75*i*.
small angle, of X rays by deuteron-irradiated Ge crystal, (7) 200*f*.
Schlieren, in glass. See *Glass: cords, schlieren*.
Schools. See *Education*.
Science, application in industry, (8) 230*g*.
of ceramics, Vol. I, B (4) 123*f*; Vol. II, B (8) 232*b*.
of clays, (10) 297*g*.
in glass and electrical industries, (9) 258*c*.
and glass industry, (5) 129*f*.
temperature measurement and control in, B (9) 259*h*.
Scintillation, properties, of Li borosilicate cerium activated glasses, (11) 304*j*.
Screen process printing, possible use for dulling glass, (11) 304*c*.
Screens, cathode-ray, preparation and requirements, B (2) 61*d*.
cathode ray, structure, P (1) 20*i*.
electroluminescent, phosphors in, P (4) 105*a*.
luminescent, in color television picture tube, P (6) 166*e*.
phosphor, silica coated, in cathode ray tube, P (11) 311*b*.
stencil, coating for, P (11) 312*e*.
television, color, (9) 248*d*.
Screens and sieves, cation, properties of open zeolites, (4) 112*b*.
for clay, types used, (8) 225*j*.
cloth for, procedure for specifying, (9) 250*b*.
device, P (4) 111*f*.
electrically heated, P (6) 167*a*.
grizzly bar, on discharge end of rotary dryer, P (5) 141*b*.
heated, for closed circuit grinding, (10) 273*e*.
lateral gyrating, P (11) 312*g*.
molecular, process for producing, P (11) 315*e*.
molecular, sodium aluminosilicate, P (4) 111*a*.
probability, construction and operation, (10) 284*b*.
rotary, for separating different kinds of materials in mixtures, P (3) 85*e*.

Screens and sieves (*continued*)
tensioning device, P (7) 195*c*.
vibratory, deck construction, P (11) 312*d*.
pedestal supports for, P (7) 195*b*.
screening process for, P (1) 23*e*.
for separating fine and coarse materials, P (8) 221*h*.
zeolitic, reactivation of, P (4) 104*d*.
zeolitic molecular, treatment to inhibit polymerization of olefins, P (2) 60*b*.
Seals and sealing. See also *Bonding; Soldering*.
balanced and unbalanced, thermoelastic stresses in, (1) 20*h*.
carbon-to-metal, solder glass for, P (5) 130*e*.
ceramic-metal, high quality, metallizing tape for (1) 19*f*.
method of making, P (3) 78*e*; P (8) 220*e*.
review of, (3) 79*k*.
gastight, between vessel wall and refractory lining of synthesis gas generator, P (1) 16*i*.
glass, or ceramic-to-metal, (10) 280*c*.
composition, P (8) 211*e*.
device for rupturing, P (1) 11*d*.
devitrified, method of separating, P (2) 42*f*.
for sealing to metals, properties of, (7) 185*h*.
technology of, B (4) 124*h*.
thermally devitrifiable, P (8) 211*g,h*.
use of volatile compound in oxide, P (11) 305*a*.
glass-to-copper, method, P (4) 100*d*.
glass-to-metal, with hollow tubular hard glass body, P (3) 69*j*.
glass-to-metal, use of fibrous material, P (8) 208*d*.
glass-to-silicon, for components, (2) 48*d*.
glass-silicone, for resistors, P (1) 21*f*.
of glass tube, P (6) 158*e*.
hermetic, transistor's leads as, (2) 48*c*.
high temperature antifriction, P (2) 45*h*.
hot-pressing of stationary ring for, (10) 275*d*.
for hot tops, P (9) 244*b*.
labyrinth-type fluid, high temperature, P (4) 102*a*.
machine control, by phototube, P (6) 158*e*.
materials, for high vacuum technique, B (2) 61*d*.
metal-to-ceramic, P (2) 49*i*; P (3) 78*a*; P (9) 249*a*.
metal-to-glass, for printed circuits, P (5) 136*c*.
press, process and apparatus, P (5) 131*e*.
quartz-to-metal, P (11) 311*f*.
for rotary kilns, P (4) 108*j*.
of semiconductors to conductors, P (3) 78*c*.
system, for double-glazing units, (2) 40*g*.
of thin- and thick-walled glasses, (1) 7*f*.
ultrasonic, of hermetic ceramic transistor packages, (3) 76*j*.
unit, for rotary kiln, P (8) 225*a*.
vacuum, for receiving tube, (8) 218*h*.
vacuumproof, by fusion of silvered Cr-Fe disks to glass, P (3) 79*b*.
Sedimentation, apparatus, automatic recording, (7) 195*g*.
cyclic, of primary dolomite and limestone, (3) 82*g*.
method, for determining particle size distribution, automatic recorder for, (8) 222*h*.
in rapid particle-size analysis of clays, (3) 83*c*.
rate, increasing, P (5) 138*d*.
Sediments, carboniferous, relation of chemical data to clay mineralogy, (11) 314*j*.
homogenous, X-ray radiography in structure study, (1) 31*d*.
playa, of Mojave Desert, clay minerals in, (4) 109*a*.
silt-size, rapid studies by liquid immersion, (1) 29*j*.
Selenides, for direct generation of electrical energy from nuclear energy heat, (10) 275*a*.
inorganic, preparation, P (2) 49*i*.
Selenium, oxide, enthalpy of formation of, (5) 143*i*.
systems. See *Systems*.
Semiconductors, adsorption and charge transfer on surfaces, (11) 309*h*.
adsorptive and catalytic properties, effect of ionizing radiation, (8) 219*d*.
alloying jig for alloying contacts to, P (7) 193*f*.
ASTM standard for, B (9) 259*a*.
bodies, accurate machining of, P (10) 283*e*.
apparatus for drawing from melt, P (6) 165*d*.
formation, P (5) 137*h*.
ceramic, preparation from high-V glasses, (11) 310*d*.
compound, ceramic materials for, B (3) 92*g*.
compound, material control method, P (3) 77*d*.
conductivity and dielectric constant, microwave measurement, (10) 286*j*.
crystalline and amorphous materials, (7) 192*h*.
crystals, apparatus for pulling from molten compounds, P (5) 135*d*.
dicing, P (7) 193*j*.
for electronic devices, (2) 47*i*.
large, method of making, P (3) 78*i*.
preparation of multiple *pn* junction, P (3) 78*e*.
in tunnel diode, P (8) 220*g*.
degeneratively doped group III–V compound, P (9) 249*i*.
dendritic crystals as, P (9) 249*f*.
device fabrication masks, fly's-eye lens technique for, (9) 247*h*.
devices, apparatus for making, P (4) 104*j*.
contact, P (5) 137*a*.
control of surface characteristics, P (10) 283*f*.
electric, P (4) 105*f*.
formation of, P (11) 311*d*.
glass encapsulated, contacts for, P (3) 70*d*.
hermetically sealed, P (4) 105*e*.
hermetically sealed, protective element for, P (7) 194*b*.
with hermetically sealed envelopes, P (3) 77*i*.
making electrode materials for, P (3) 78*j*.
making by jet electrolytic etching, P (10) 283*b*.
masking and fabrication technique, P (8) 220*a*.

Semiconductors, devices (*continued*)
materials and manufacturing methods, P (5) 136*a*.
method of contacting, P (2) 49*a*.
method of making, P (3) 79*b*; P (4) 106*b*.
with Si oxide coating, P (9) 249*h*.
single station fusion machine for making, P (7) 194*c*.
electric conductivity of, measurement of anisotropy of by 4-probe method, (7) 192*a*.
electric spark discharge in making of, P (3) 78*j*.
electrode systems, P (5) 136*h*.
electrolytic and ultrasonic etching of, P (8) 220*g*.
electron processing of, P (7) 193*a*.
extrinsic, oscillator phenomena in, (4) 117*g*.
films, production of, P (3) 78*j*.
finite slices, impurity atom diffusion into, (7) 191*c*.
for flux measurements in operating core, (3) 76*g*.
formation of, P (10) 282*g*.
germanium device, finishing treatment for, P (3) 77*j*.
heavily doped, vapor deposition, P (3) 79*c*.
joining to conductor, P (3) 78*c*.
leads, method of positioning and holding without flux, P (3) 78*f*.
low resistance contact for, P (4) 105*f*.
machining of, P (3) 78*d*.
many-valley, hot electron nonequilibrium carrier distribution in, (11) 310*g*.
material, diffusion in, P (4) 105*d*.
high purity, for electrical purposes, P (11) 311*d*.
with high surface tension in molten state, method for treating in crucible, P (3) 78*a*.
making thin slices by preferential etching, P (10) 283*i*.
moly-manganese metallized high alumina ceramics in, (10) 280*c*.
nonstoichiometric, electrical properties of, B (9) 260*g*.
photoadsorptive effect on, theory of, B (9) 260*j*.
photosensitive gas phase etching by selective radiation, P (10) 283*c*.
pinhole-free films of, vacuum evaporation deposition, (11) 311*j*.
polar many-valley, mobility and thermoelectric power in, (8) 219*b*.
preparation by precipitation on hot carrier rod, P (11) 311*b*.
properties, of Ag_2Te, (4) 104*j*.
radiation effects in, (3) 76*e*.
Si, bonding gold-metal electrode by thermocompression, P (9) 249*h*.
SiC, SiN-bonded, P (1) 16*d*.
Ag_2S group, theory of mixed conduction in, (11) 310*f*.
sintered bodies, P (2) 50*a*.
structure, making of, P (5) 137*b*.
surfaces, electropolishing of, P (5) 137*c*.
temperature calculation in, (9) 251*b*.
Tl_2Te_3, method of making, P (10) 283*g*.
thin layer, P (7) 193*j*.
units, apparatus for making, P (6) 165*e*.
with U, emf developed during irradiation in reactor, (10) 280*g*.
vapor-solid diffusion of, P (3) 79*c*.
wafers, diffusion of B into from BN coatings, (2) 36*i*.
wafers, machine for measuring and sorting, P (6) 166*e*.

Separation. See also *Beneficiation; Classification; Flotation.*
of Al silicates and zircon from beach sand, P (10) 289*c*.
of Am and Cm from rare earths, P (6) 176*a*.
benzoate, in quantitative analysis of phosphate rock, (5) 145*f*.
of differentially heated particles, P (10) 289*h*.
electrical, of pegmatites, (7) 197*f*.
electrodialysis in, (10) 284*c*.
electrostatic. See also *Electrostatic processes.*
of granular materials, (8) 221*e*.
in nonuniform field, P (2) 55*h*.
of fine from coarse materials, vibratory screen for, P (8) 221*h*.
of glass sand from clay, (10) 289*a*.
of granular particles, flow apparatus, P (9) 250*b*.
magnetic, in processing high-feldspar-iron sand for glass wool, (9) 254*b*.
of minerals, diluent for bromoform in, (4) 107*c*.
paper chromatographic, in determination of Zr with Hf in zircon, (5) 142*f*.
of particles of differing refractive index, P (1) 11*j*.
of particles of molecular size, for increasing sedimentation rate, P (5) 138*d*.
pyrohydrolytic, in determination of small quantities of fluorine, (11) 312*j*.
of rare earths, P (9) 254*j*.
by ion exchangers, (5) 145*i*.
and Y by ion exchange [resin], P (2) 60*a*.
and recombination of feed for grinding mill, P (6) 171*a*.
of silica from Zr sulfate solutions, P (10) 289*h*.
of solid particle material in fluidized liquid medium, P (5) 141*a*.
of Ta and Nb, P (3) 89*j*.
of Y from rare earths, P (6) 176*b*.

Separators, air, adjustment for rapid change of cement types, (10) 266*e*.
air, for sizing refractory materials, (9) 250*h*.
battery, method of making, P (8) 211*f*.
centrifugal, for dust, P (10) 285*b*.
cyclone, P (3) 83*f*.
dust, P (5) 138*h*; P (7) 195*b*.
electrostatic, P (2) 51*a*.
electrostatic, for ores, P (10) 289*g*.
gas-material, P (10) 285*e*.
hydraulic cyclone, for removal of iron from pottery stone, (8) 225*c*.
magnetic, P (3) 80*c*; P (10) 289*a*.

Separators (*continued*)
magnetic, in ceramic industry, (2) 50*i*.
sonic, P (5) 141*f,g*.

Serpentine, minerals, effect of particle size on thermal properties, (5) 143*c*.
morphology, (11) 316*h*.
six-layer orthohexagonal, from Labrador trough, (4) 110*g*.
superlattice in, electron microscopic study, (6) 173*b*.

Settling. See *Sedimentation.*

Sewer pipe. See *Pipe.*

Shale, aggregate, expanded plant, (6) 158*j*.
coal-washery, use in heavy-clay industry, B (10) 300*j*.
effect of milling, ion exchange, and removal of quartz on, (3) 82*c*.
fines, pelletizing of, (11) 302*a*.
Kentucky, analyses, (8) 225*g*.
Montana, progress report, (3) 83*b*.
oil, production of hydraulic limes from, P (10) 290*b*.
Ordivician, of Ontario, mineral constitution of, (10) 295*a*.
Queenston, plastic and related properties, (2) 51*e*.
sandy, slightly carbonaceous, for light weight aggregate, (6) 158*i*.
W. Va., petrography and origin, (3) 82*i*.

Sheathing, ceramic, continuous manufacture, P (10) 285*g*.

Shipment. See *Transportation.*

Shock, handbook, Vols. I–III, B (5) 151*c*.
thermal, analysis, of spherical shapes, II, (10) 297*c*.
by radiation heating, (7) 189*d*.
-resistant ceramics in Li_2O-Al_2O_3-SiO_2 system, I, (8) 209*g*.

Shock resistance, thermal, of bone-china cups, (11) 309*d*.
of ceramic materials, determination of, (10) 274*f*.
of fused silica ceramics, (1) 4*f*.
and mechanical, enamel coat for, P (1) 4*j*.
of stoneware, testing of, (10) 279*b*.
testing refractories for, B (10) 300*i*.

Shrinkage, drying, of cement, factors affecting, (8) 204*i*.
of concrete block, (2) 34*d*.
of hardened cement paste, factors affecting, (8) 204*c*.
of mortar, effect of fineness of clinker and slag, (8) 204*g*.
during sintering in presence of liquid phase, effect of applied pressure, (10) 292*i*.
of ferrites, in firing process, (3) 76*h*.
of natural aggregates in concrete, (10) 267*h*.
of neat cement pastes, effect of fineness and content of slag and curing conditions, (7) 179*b*.
nonuniform, in sintering, (9) 243*i*.

Sieves. See *Screens and sieves.*

Silica. See also *Coesite; Cristobalite; Glass; Quartz; Quartzite; Refractories; Sand; Tridymite.*
ablation resistance, additives for increasing, (8) 214*c*.
acidic hydroorganosol, decreasing salt content of, P (1) 26*a*.
aerogels, method of preparing, P (2) 55*b*.
amorphous, hydroxyl ion catalysis of crystallization, (7) 199*e*.
Ba metaborate-, particles, methods of preparing, P (2) 55*b*.
brittle fracture of, effect of environment, (9) 240*e*.
cellular, in γ-radiation dosimeter, P (5) 136*c*.
as cladding for thoria sols, P (10) 278*a*.
comparative concentration in parent material and in airborne particulate matter, (3) 90*e*.
components substituted for in oxidizing atmosphere, function of, I, (1) 27*f*.
content, of MoS_2, method of reducing, P (11) 315*d*.
core, in composite pigment particle, P (11) 303*a,d*.
crystalline, in whiteware bodies, (11) 309*b*.
of decreased pore size, preparation, P (10) 289*d*.
densification of, P (10) 271*f*.
diatomaceous, in thermal insulating cement, (2) 34*b*.
direct determination, safe limit of fluoride content for, (5) 145*e*.
doped fused, radiation effects in, (4) 119*h*.
effect on antimonate glass properties, (11) 304*b*.
effect of temperature on elastic moduli, (7) 195*i*.
fibers, effect of temperature on strength, (9) 241*e*.
fibers, making from sodium silicate glass, (10) 270*c*.
films, rectifying action and emf at high temperatures, (10) 281*e*.
fine size, preparation, P (7) 198*a*.
flour, use in steel foundries, (1) 15*e*.
in formation of SiC, (3) 72*f*.
free, in rocks, quantitative determination by X ray, (9) 251*i*.
fused, low-temperature excess specific heat of, (3) 67*e*.
in paint for spacecraft temperature control, (8) 207*b*.
radiation effects in, (8) 229*j*.
thermal shock resistance and thermal insulation of, (1) 4*f*.
with water and alumina impurities, in electrical field, diffusion in, (2) 38*h*.
gels, radiation-induced processes on surface of, (10) 296*b*.
high-pressure polymorphs, relation of infrared spectra to, (2) 58*c*.
hydrates, low-temperature dehydration of, (3) 67*d*.
industrial deposits of Pacific Northwest, (6) 170*b*.
interaction with $CaCO_3$ in formation of tricalcium silicate, (3) 86*f*.
isotypes, high-pressure region of, (4) 114*b*.

Silica, deuices (*continued*)
in joining glass bodies, P (11) 305*a*.
lead oxide-, composite, P (1) 25*h*.
low surface area, P (4) 111*c*.
materials, analysis of, (3) 80*e*.
materials, control analysis by spectrophotometric method, (3) 81*c*.
in optical glass, P (3) 70*b*.
pebbles, use in ball mills, (1) 22*e*.
in permanently active catalyst, P (9) 244*h*.
plant, Canadian, production expansion, (2) 54*e*.
properties and uses, B (4) 122*h*.
pure, fiber bats, P (9) 245*d*.
reduction, by C in liquid iron, (1) 14*d*.
reduction, effect of elements in molten iron, (1) 14*f*.
samples, upgrading by glass button analysis, (9) 251*c*.
slip-cast fused, sealing method, (8) 213*f*.
sols, aqueous, process of concentrating, P (3) 84*j*.
-spinel, compositions, X-ray diffraction of phase transformations in, (7) 199*d*.
surface, chemistry of, and silicosis, (3) 90*c*.
systems. See *Systems.*
vitreous, diffusion of oxygen in, (3) 66*g*.
effect of V_2O_5 on viscosity, (2) 40*g*.
in guide tube for nuclear reactor, P (9) 245*b*.
manufacture of ware, review of European patent literature, (7) 184*i*.
neutron-damaged, effect of elastic strains, (5) 128*i*.
use in tank furnaces, (7) 187*e*.
water in, I, II, (3) 68*i*.

Silicates, acid hydrolyzed isopropyl, as binders for molds for refractories, P (4) 103*b*.
alkali metal, aqueous solution for treating asbestos, P (3) 74*d*.
alkali metal, reacting to form aerogels, P (2) 55*b*.
Al and Fe in, photometric-complexometric determination, (3) 80*j*.
amorphous, aqueous dispersions of high molecular weight fibrils of, P (4) 104*e*.
analysis, by flame photometry in oxine medium, B (10) 300*f*.
analysis, rapid methods, (5) 145*h*.
aqueous solutions, preparation, P (9) 254*f*.
bonding of Pb-based alloys to, P (6) 165*f*.
chain, pyroxene and amphibole groups, B (9) 264*d*.
chemical investigations of, XXV, XXVI, (4) 112*g*.
dicalcium. See *Calcium, dicalcium silicate.*
elastic, thermally stable flexible, (8) 229*b*.
electrolysis of, in production of SiO_2, P (2) 56*a*.
foam, in structural elements for rural and housing construction, (1) 6*h*.
industry, dust collectors in, I–III, (5) 137*j*.
iron, low-melting, Ag-Pd alloys as crucible material in study of, (7) 200*b*.
layer, changes from heating below 550°C, (11) 316*j*.
layer, micalike, substitution of exchangeable cations by Al^{3+} and Si^{4+}, (5) 146*e*.
layer-lattice, cell dimensions and symmetry, I, II, (7) 198*f*; III, IV, (9) 255*d*; V, VI, (11) 316*e*.
liquid, acid-base equilibria in, (4) 111*j*.
melts, acid-base reactions in, (1) 26*f*.
bond development in, study by infrared spectrometry, B (11) 322*f*.
determination of water solubility in, (5) 144*f*.
minerals, nonrefractory, semimicrovolumetric determination of ferrous iron in, (11) 313*g*.
minerals and rocks, artificially pulverized, dissolved products of, I, II, (11) 316*f*.
molten, solubility of lead in, (3) 64*e*.
ortho- and ring, B (5) 151*g*.
porous foamed, products, P (10) 277*c*.
removal from water by porous MgO sorbent, P (3) 84*g*.
rocks, screened Eriochrome indicator for determining Mg in, (3) 81*d*.
sheet, B (10) 299*d*.
slags, ionic concepts, (10) 297*a*.
Na Al, scale, method for removing, P (5) 138*b*.
Na and K in, quantitative determination by X-ray diffraction, (2) 40*i*.
SO_3 in, nephelometric and turbidimetric determination, (9) 237*a*.
swelling and nonswelling layer, comparison of electrophoretic migration velocity of particles, (3) 86*c*.
synthetic, produced in solar furnace, (5) 140*h*.
systems. See *Systems.*
thermal reduction, in synthesis of fibrous SiC, (9) 244*f*.
thin-layer coatings, preparation from solutions, (4) 97*b*.
thio-, preparation of, (4) 121*b*.
tricalcium, formation by interaction of $CaCO_3$ and SiO_2 at 840°C, (3) 86*f*.
vibration spectra of, III–V, (5) 147*e*.
yearbook, Sprechsaal, B (5) 151*c*.

Silicides, in coating for large refractory metal parts, (6) 155*c*.
as coatings for Ta-base alloys, (8) 206*g*.
of Mo, Ta, and W, physical and mechanical properties, (6) 161*d*.
ZrB_2-, bodies, P (8) 217*b*.

Silicon, boride, production of, P (10) 277*g*.
carbide. See also *Refractories.*
abrasive grain, in grinding wheel, P (10) 265*g*.
abrasive grain, manufacture of, (6) 153*f*.
applications and properties, (9) 258*b*.
in bonded abrasive products, (9) 235*f*.
coatings, method of depositing, (2) 48*f*.
as commercial abrasive, (8) 203*i*.
in composite coatings, (8) 207*d*.
crushing in BC mortar, (10) 284*d*.
crushing resistance, relative measurement, (10) 265*f*.

Silicon, carbide (*continued*)
crystals, adjusting electric properties, P (5) 137*a*.
crystals, energy band structure of, (6) 173*b*.
crystals, method of growing, P (1) 16*a*.
cubic (β), twinning study, (7) 201*d*.
effect of gas atmospheres on, B (10) 300*i*.
electrolytic etching of, P (6) 176*c*.
fibrous, synthesis by thermal reduction of silicates and Si compounds, (9) 244*f*.
foamed, process, P (11) 308*a*.
formation from SiO_2 and C, (3) 72*f*.
in graphite article, P (3) 74*i*.
as irradiation indicator, B (8) 233*d*.
method of making, P (8) 216*c*.
of 174 layers, crystal structure of, (6) 172*i*.
oxynitride bonded, for superrefractories, (10) 276*b*.
in polishing material, P (4) 95*g*.
preparation of junctions in, P (3) 78*d*.
producing diffused junctions in, P (7) 194*g*.
properties and uses, (6) 155*c*.
resistance heating element, P (10) 278*a*.
semiconductors, SiN-bonded, P (1) 16*d*.
SiN bonded, in furnace pouring spout, P (8) 224*g*.
single crystals, apparatus for cutting, (8) 230*b*.
single crystals, growth patterns on, (8) 229*b*.
single crystals, optical absorption in, (4) 115*d*.
solid solutions in AlN, (6) 159*e*.
tubes, collapse under reactor coolant pressure, (10) 274*c*.
whiskers, (8) 229*g*.
wurtzite form, synthesis of, (2) 59*e*.
compounds, spectrochemical determination of B in, (9) 252*a*.
crystals, dislocation-free, observation of layer structure by X-ray anomalous transmission, (6) 174*b*.
diffusion into surface layer of refractory metal for silicide coating, (1) 4*d*.
dioxide. See also *Silica*.
by electrolysis of silicates, P (2) 56*a*.
high purity B- and B-free, method of making, P (3) 84*h*.
hydrophilic, production of, P (1) 26*d*.
passivation, of *pn* junction particle detectors, (10) 282*e*.
process for coating with, P (9) 249*e*.
structures, as host components in crystalline solid solutions, P (9) 246*c*.
films, polycrystalline, morphology of, B (9) 263*c*.
in fluorphlogopite, isomorphous substitution for, (4) 115*b*.
forming of *pn* junction devices, P (7) 193*b*.
high purity, crucible for melting, P (1) 20*d*.
high purity, preparation by decomposition of SiN powder with graphite target, P (11) 311*e*.
high-purity, spectral analysis of, (4) 120*b*.
ions, as replacement for K^+ ions in muscovite, (5) 146*c*.
-Fe single crystal, growth in high temperature furnace, (11) 314*f*.
irradiated, electron paramagnetic resonance of defects in, (8) 227*g*.
monoxide, solid, particulate, P (8) 225*f*.
nitride, dielectric, in electrical capacitor, P (10) 282*e*.
foamed, P (8) 216*c*.
for high temperatures, (10) 276*g*.
self-bonded, preparation, properties, and fabrication into ware, (1) 15*g*.
n-type, α trapping centers in, (4) 111*j*.
oxide, film, thickness measurement, (1) 29*f*.
oxide, phase equilibria with B oxides, (8) 229*f*.
production of, P (2) 49*j*.
purification by chloride and iodide transport reactions, (4) 119*b*.
reactive, determination in power-station waters, (9) 250*h*.
and SiC, hyperpure, method of making, P (11) 311*b*.
single crystals, dislocations in, (6) 172*b*.
single crystal surface layers, method of making, P (10) 283*d*.
systems. See *Systems*.
tetrachloride, production of, P (10) 290*e*.
tetrachloride, vapor, in treatment of gallium arsenide, P (8) 221*a*.
thermal oxidation of, (1) 30*f*.
in water, absorptiometric determination, I, II, (9) 250*g*; III, (10) 285*i*.
Silicosis, determination of minerals with phase microscope in combating, (4) 111*i*.
etiology, preparation of dusts for study of, (2) 60*g*.
in Philippine mining company, (11) 320*d*.
in porcelain workers, histology of iron deposits in, (2) 60*e*.
prevention in sanitary ware plant, (10) 278*d*.
relation of activity in quartz to development of, (2) 60*f*.
relation of chemistry of surface of silica, (3) 90*c*.
Silikose-Forschungs Institut formula, (5) 148*d*.
Sillimanite. See also *Refractories*.
in Georgia, mineral characteristics, locations, and uses, (3) 82*e*.
as refractory material, I, (3) 73*j*; II, (6) 161*f*.
slip-cast, relation between porosity, firing temperature, and corrosion resistance, (1) 15*b*.
stability compared to andalusite and kyanite, (4) 118*c*.
from volcanic xenoliths, (4) 110*f*.
Silver, bromide, defect structures and transport matter in, B (9) 261*a*.
bromide, doped with divalent anions, absorption of, (3) 85*h*.
-CdO, bodies, attaching to supporting member, P (6) 166*h*

Silver (*continued*)
chloride, crystals, doped, absorption and photochemistry of, (3) 85*f*.
crystals, equilibrium properties of solid solutions of Cu ions in, B (9) 260*b*.
crystals, growth and pressure treatment, B (9) 263*b*.
glass flakes or fibers as reinforcement, P (6) 157*c*.
systems. See *Systems*.
compounds, in thermoelectric body, P (10) 283*h*.
Cu-, liquid phase sintering of, (4) 118*d*.
deposition from solution on glass, P (6) 157*i*.
effect on glass color, (8) 208*h*.
halogenides, with divalent anion impurities, changing dipoles in, (3) 85*j*.
halogenides, with divalent anion impurities, simplest defect dipole in, (3) 88*e*.
iodide, precipitates, coagulating ion adsorption-desorption equilibria on, (3) 86*d*.
ions, response of electrode glass to, (5) 129*e*.
nitrate, -zeolite complex, dielectric properties of, (8) 218*i*.
-Pd alloys, as crucible material in study of low-melting iron silicates, (7) 200*b*.
powder, in precision glaze resistors, (10) 281*i*.
AgCl and AgBr single crystals, distribution of impurities dissolved during growth from melt, (3) 86*g*.
$Ag_2Si_2O_5$, reduction and reduction products, (4) 120*a*.
sulfate, bromide, or chloride, as interlayer in glass laminate, P (9) 242*b*.
telluride, semiconducting properties, (4) 104*j*.
Single crystals. See *Crystals*.
Sintering, of alkaline earth carbonates, P (3) 76*a*.
of Al_2O_3, I, II, (7) 200*c*.
basic phenomena in, B (4) 123*g*.
behavior and stability, of $(PuU)O_2$ solid solutions, (11) 306*j*.
of calcium fluoride, (3) 88*f*.
of ceramic oxides, effect of grinding method and medium, (3) 79*f*.
chamber, in glass tank furnace, batch feeder as, (1) 5*e*.
of doped and undoped $BaTiO_3$, (2) 58*f*.
equipment, of thoria and thoria gels, (8) 227*i*.
of fine-grained minerals, P (4) 111*f*.
furnaces, heat exchangers in, P (4) 108*g*.
of Fe-C compacts, effect of atmosphere, (7) 200*b*.
kinetics, for high density alumina process, (1) 29*g*.
liquid phase, phenomenological study, I–III, (4) 118*d*.
of long ceramic compacts, in movable, short furnace, P (2) 51*g*.
low-temperature, of UO_2, (5) 132*j*.
machine, continuous radiant furnace, P (7) 197*c*.
in $MnFe_2O_4$ and $Y_3Fe_5O_{12}$, B (4) 123*h*.
of natural magnesites, effect of impurities, (3) 73*h*.
nonuniform shrinkage in, (9) 243*i*.
of Pu/U oxides, B (8) 232*b*.
of powders, P (2) 51*h*.
in presence of liquid phase, effect of applied pressure on densification during, (10) 292*i*.
pressure, mechanisms and microstructures for Al_2O_3 and MgO, (11) 318*c*.
process, of chemically prepared magnesia, (3) 72*i*.
of quartz and cristobalite, (10) 276*h*.
of refractory periclase ceramics, effect of additions, (7) 187*h*.
remote control, in vertical cement kilns, (10) 287*j*.
steam, of UO_2, (1) 15*j*.
studies, on Mo-coated UO_2 particles, (11) 306*g*.
studies, on talc-kaolin and forsterite-kaolin systems, (5) 145*j*.
in system ZnO-TiO_2, (1) 29*i*.
of UO_2, P (8) 216*h*.
of uranias, (10) 276*i*.
of UO_2, effect of grain growth control during, (11) 307*d*.
of ZnO, (10) 297*d*.
Size reduction. See *Crushing and grinding*.
Slags, acid-base concept in, (1) 26*f*.
basic, chemical analysis of, I-III, (5) 139*f*.
pig iron, effect of dolomite on use in road construction, (10) 268*b*.
rapid determination of S in by combustion method, (6) 154*j*.
reaction with fireclay ladle bricks, (8) 214*a*.
blast-furnace, lime activity in, I, (7) 178*a*.
blast-furnace, thermal treatment, P (4) 96*i*.
in blast-furnace cement pastes, (7) 180*f*.
calcareous, erosion resistance of fireclay brick to, I, (1) 13*g*.
Ca aluminates from, P (3) 64*h*.
CaO-Al_2O_3-SiO_2, DTA study of activation of, (6) 154*g*.
chemical composition, effect on properties of portland blast-furnace slag cement, (7) 179*c*.
containing F compounds, cements from, P (3) 65*a*.
crystalline stone from, P (4) 96*g*.
effect on checker-brick in furnace with rotating specimen holder, (7) 188*f*.
fine, in concrete, (8) 206*a*.
fineness, effect on drying shrinkage of cement mortar, (8) 204*g*.
foamed, raw materials, processing, and properties, (1) 8*h*.
furnace, phosphorus, cuspidine in, (4) 96*g*.
furnace, solubility of S in, (7) 182*d*.
granulated, in building materials, (8) 203*j*.
as lining for furnace tapping pots, P (3) 75*b*.

Slags (*continued*)
low-shaft furnace, mineralogy and liquidus determination by hot stage microscopy, (2) 44*f*.
microstructure of, B (11) 321*a*.
molten, corrosion of dunite refractories by, (1) 13*j*.
molten, method and apparatus for pelleting, P (2) 46*c*.
portland blast-furnace slag, contraction of, (7) 179*b*.
recovery of earth acids from, P (11) 315*f*.
silicate, ionic concepts of, (10) 297*a*.
water-quenched, as concrete additives, P (4) 96*j*.
wool. See *Mineral wool*.
Slaking. See *Lime, hydration of*.
Slip casting, of CaO, (7) 188*h*.
kinetics of, (5) 144*c*.
of porcelain, problems in, (10) 278*j*.
ultrasonic, of ceramics and cermets, (8) 221*c*.
of urania and thoria, (8) 215*f*.
vacuum-assisted, (8) 221*i*.
Slips. See also *Suspensions*.
for colored mosaic tile bodies, electrophoretic dewatering of, (7) 194*h*.
decorative, formulas for, (2) 33*h*.
effect of temperature on, (2) 47*b*.
enamel, consistency of, (8) 206*h*.
control of application, (11) 303*a*.
measurement of properties with rotating cylinder viscometer, (8) 207*f*.
preparation of, P (6) 155*g*.
techniques for controlling, (11) 303*b*.
pour-controlling device for box containing, P (11) 309*g*.
terra sigillata, preparation and firing, (7) 178*a*.
tile, equipment for continuous dewatering, (7) 194*h*.
viscous, knife coating on impervious carrier film, to form thin ceramics, (10) 284*g*.
Slurry, apparatus and method for conveying, P (9) 250*e*.
aqueous cement, water loss control of, P (10) 268*e*.
asbestos, production of, P (3) 85*d*.
cement, thinning with Na tripolyphosphate, (11) 302*e*.
diffusing machine, P (5) 138*g*.
filtration means, P (3) 84*c*.
method and apparatus for metering, P (3) 80*c*.
in systems cement-water and asbestos-cement-water, viscosity measurement in, (8) 205*g*.
Smelting, of glass, from normal batch constituents, observation in high temperature microscope, (8) 209*j*.
Snow, properties, processes, and applications, B (11) 321*h*.
Soapstone. See *Steatite; Talc*.
Societies, British Ceramic, visit of Building Materials Section to France, April 1961, (1) 31*g*.
Canadian Ceramic, education committee, discussion of certification of ceramic technicians, (6) 176*e*.
French Ceramic, report of committee on thermal conductivity, (3) 72*h*.
Soda. See *Sodium, carbonate*.
Sodalite, basic, dielectric properties of, (8) 218*i*.
Sodium. See also *Alkalis*.
aluminosilicate, synthetic crystalline zeolitic, P (2) 55*f*.
aluminosilicate, systems. See *Systems*.
aluminum fluorides, preparation, P (3) 83*e*.
beryllate, solutions, chemical nature of, (7) 198*d*.
borates, of lowered iron content, electrolytic production, P (3) 84*b*.
carbonate, increasing whiteness, P (7) 198*a*.
solid-liquid phase equilibria with Li and K carbonates, (1) 30*c*.
systems. See *Systems*.
chloride, bicrystals, direct observations of grain-boundary sliding in, (5) 142*h*.
crystals, effect of fractional X-irradiation on F-center density, (4) 113*b*.
crystals, effect of plastic deformation on γ-ray coloration of, (5) 143*g*.
formation of interstitials and vacancies in, (10) 293*d*.
inversion symmetry of M and R centers in, (4) 115*e*.
single crystals, mechanical behavior in flexure, (2) 58*b*.
solution, Ca sulfate hemihydrate prepared in, (7) 198*c*.
systems. See *Systems*.
ferrite, role in extraction of aluminate sinters, (4) 120*f*.
flame-photometric determination in Ni-alumina catalysts, (10) 286*d*.
flame-spectrometric determination with $BaCl_2$ as buffer, (11) 303*f*.
fluoride, systems. See *Systems*.
germanate, crystal structure of, (10) 291*c*.
hydroxide, in cleaning of borosilicate glass, (9) 239*h*.
hydroxide, systems. See *Systems*.
liquid, and dilute solutions, electric resistivity of, (2) 57*c*.
niobate, K-, for transducers, P (6) 166*b*.
oxide, effect on cement strength, (7) 179*h*.
oxide, systems. See *Systems*.
quantitative determination in glasses and silicates by X-ray diffraction, (2) 40*i*.
silicate, as bond for sillimanite refractories, (6) 161*f*.
bonding to Pt, Au, Fe, and oxidized Fe, (2) 57*f*.
free-flowing powder, P (1) 25*i*.
$NaInS_2$ and $NaInSe_2$, preparation and crystal structure, (4) 116*e*.

Sodium (*continued*)
sulfate, effect on melting and refining of glass, (7) 184*h*.
effect of small additions on refining of glass, (3) 66*j*.
in formation of large crystals of $CaSO_4 \cdot 2H_2O$, (5) 126*c*.
systems. See *Systems*.
tripolyphosphate, as additive in cement slurries, (11) 302*e*.
tungsten bronze, cubic, electrical resistivity of, (3) 86*c*.
zirconate, systems. See *Systems*.
Softening, process, of lime-zinc glazes, (11) 309*g*.
Soils, ASTM standard for, B (9) 259*b*.
Canadian, fixation of K in, (5) 140*j*.
grain-size analysis of, (2) 54*j*.
Manitoba, adsorption and exchange of P in, (5) 140*h*.
mechanical analysis, pipetting assembly for, (5) 139*d*.
sub-, British Columbia, clay minerals in, (5) 140*i*.
Solar cells. See *Cells, photovoltaic*.
Solar furnaces. See *Furnaces*.
Solar rays, concentrated, for treatment of zircon after fusion, P (3) 75*c*.
Soldering. See also *Seals and sealing*.
Mo foil by means of Mo carbide, P (2) 50*b*.
optical, in automated packaging, (7) 192*a*.
temperature, of low temperature glass, (10) 271*c*.
vacuum tight ceramic metal, in electronics, B (4) 124*h*.
Solders, glass compositions, conducting, P (6) 157*h*.
Solidification, range, of glass phase in ceramic bodies, (8) 229*h*.
Solids, absorption spectra and chemical bonding, I, (11) 315*j*.
blowing by hose, (3) 79*e*.
brittle amorphous, weakness and strength, sources of, B (9) 263*i*.
ceramic, study of reactions in by infrared spectroscopy, (5) 89*f*.
crystalline, and glassy inorganic, effect of neutron irradiation, (10) 292*f*.
crystalline, mechanical behavior of, symposium proceedings, B (9) 259*e*.
determination of surface area and quality by gas chromatography, B (10) 300*g*.
displacement of atoms by ionizing radiations, role of Auger effect, (11) 318*j*.
fundamentals of structure, B (10) 298*i*.
ionic, effect of environment on strength, (8) 226*i*.
ionic, role of impurities in radiation effects, (11) 319*b*.
-liquid interfaces, controlling by Peltier heat, P (8) 222*b*.
liquid transport in pipelines, (10) 284*e*.
moisture in, measurement techniques, (6) 168*b*.
nuclear measurement and control of moisture in, (9) 251*a*.
porous, apparatus for determining particle density, (7) 195*d*.
permeability of, (10) 296*g*.
thermodynamics of frost damage to, (8) 212*b*.
pulverizing apparatus, P (4) 111*j*.
radiative transfer from, B (4) 92*j*.
spectrum analysis of, P (6) 168*k*.
surfaces, radiation effects on reactivity of, (2) 58*b*.
thermal conductivity of, apparatus for determining at 20° to 200°C, (10) 285*j*.
thermodynamics of, B (4) 124*e*.
vapor pressure data for, (5) 144*j*.
volume and density of, apparatus for measuring, P (3) 81*a*.
wet grinding to extreme fineness, P (5) 138*f*.
Solid solutions. See *Solutions, solid*.
Solid state, devices, active, using anisotropic single crystal rutile, P (11) 311*a*.
epitaxial growth of spinel by reaction in, (5) 143*j*.
equilibria, for system SrO–MgO–SiO_2, (10) 297*g*.
material, high temperature pressure sensitive, P (11) 311*g*.
processes of plastic yielding, in MgO, (10) 297*f*.
reactions, (1) 29*a*.
high temperature attachment to X-ray diffractometer for study of, (2) 52*h*.
kinetic model for, (2) 57*c*.
kinetics, equations and tables for analyzing, (10) 292*c*.
study, of hydrated and α-aluminas with nitrates of Ni and Co, (1) 30*b*.
in system BaO–Al_2O_3–SiO_2, II, (10) 297*h*.
relations, in system Cr_2O_3–UO_2–O_2, (7) 201*i*.
study, of $BaTiO_3$–UO_2 ceramics, (10) 279*j*.
Sols. See *Colloids*.
Solubility, of anhydrite in water, determination by hydrothermal solution equipment, (5) 147*f*.
of BeO in aqueous Be sulfate solution, (3) 88*h*.
of cristobalite, in curve gas-liquid-cristobalite, (7) 200*i*.
of gases in glass, (3) 68*b*.
of glasses of systems alkali–B_2O_3–SiO_2 and PbO–B_2O_3–SiO_2 in water, (10) 278*g*.
of iron oxides in B and B-free silicate melts, (2) 37*b*.
of lead, in molten silicates, (3) 64*e*.
of Pb from on-glaze decorated porcelain, Austrian regulations of, (3) 90*b*.
liquid, effect on microstructure and densification, (4) 118*c*.
of MgO, in molten salts, (9) 257*e*.
of neptunium(IV) peroxide, (7) 200*a*.
product, of barium silicate hydrate, (4) 112*g*.
of quartz powders, effect of disturbed layer on, (10) 292*b*.
of skeletal carbonates in aqueous solutions, (10) 295*g*.
solid, of Al and ferric oxides in belite, (7) 200*k*.
Solubility (*continued*)
solid, of $MgSiO_3$ in Ni_2GeO_4, as function of pressure, (11) 319*d*.
of sulfur in furnace slags, (7) 182*d*.
of water in silicate melts, determination, (5) 144*f*.
Solutions, aqueous, crystallization of Mg oxalate in, (8) 212*f*.
aqueous, solubility of skeletal carbonates in, (10) 295*g*.
flooding, in determination of metallic exchangeable cations, (5) 139*j*.
of Gd salts, photoluminescence of, (5) 145*c*.
of ground quartz powders, in dilute HF, mechanism for, (10) 295*g*.
hot, chemical resistance of enamel to, (10) 268*g*.
sucrose, crystallization during latent period, B (9) 262*d*.
Solutions, solid. See also *Equilibrium studies*.
Al_2O_3–Ti_2O_3, (3) 85*i*.
applications of thermodynamic calculations on phase equilibria to olivines, (2) 59*a*.
based on ferroelectric $PbNb_2O_6$, (1) 30*a*.
of Ca aluminoferrites, study of, (4) 115*f*.
in cement, B (5) 148*i*.
crystalline, conditions for obtaining in system Al^{3+}–Cr^{4+}–H_2O, (7) 199*h*.
crystalline, with SiO_2 structures as host components, P (9) 246*c*.
dilute, equilibrium properties of, B (9) 259*a*.
dilute, statistical mechanics of, B (9) 260*d*.
formation between As and Sb and semiconducting chalcogenides of group IV, (3) 89*c*.
$FeTiO_3$–Fe_2O_3, order-disorder transformation phenomenon in, (6) 174*g*.
of $Pb_2NiNb_2O_9$ and $Pb_2MgNb_2O_9$, polarization mechanism in, (7) 192*b*.
Ni and Co oxide, change of O concentration with temperature, (6) 171*i*.
NiO–CoO–MgO, hydrogen reduction of, (10) 293*h*.
oxide, thermal-expansion anisotropy of, (1) 30*g*.
perovskite type $A^{2+}B^{4+}O_3$, quaternary systems of, (6) 175*a*.
in system, CaO–MgO, (9) 256*e*.
$3CaO \cdot SiO_2$–Al_2O_3–MgO, (7) 200*f*.
ZrO_2–SiO_2, (7) 201*a*.
in systems between semiconducting chalcogenides of group IV, (4) 120*g*.
UC–PuC, method of making, P (7) 189*d*.
US–ThS, preparation, (6) 160*d*.
Y-doped ferroelectric, with positive temperature coefficients of resistance, (6) 165*b*.
Solvents, volatile, handling of, (1) 31*e*.
Sonics, in cleaning of dust filters, P (1) 23*e*.
energy generating apparatus, P (11) 312*d*.
hyper-, environment, in heat transfer in multicomponent gases, (10) 294*b*.
materials separation apparatus, P (5) 141*f,g*.
super-, in vibrating drying system, P (8) 222*b*.
testing, nondestructive, for casting quality, (10) 269*h*.
ultra-, in casting of ceramic and cermet slips, (8) 221*c*.
for cleaning art and crystal glass, (7) 184*g*.
delay line, P (1) 22*c*.
in etching semiconductor devices, P (8) 220*g*.
in examination of bodies with nonplanar surface, P (8) 223*i*.
high frequency, in testing brittle materials, (7) 195*j*.
in lapping machines, P (10) 285*g*.
liquid, abrasive machining apparatus, P (10) 265*h*.
in measurement of elastic constants of calcite, (1) 27*e*.
in polishing of glass, (7) 185*e*.
rotation of waves by magnetic field, (6) 164*c*.
for sealing of hermetic ceramic transistor packages, (3) 70*j*.
for stripping ceramic-coated molds and ingots, (2) 37*g*.
in study of phase change and Curie temperature of $SrTiO_3$, (9) 257*f*.
vibration, conversion to rotation, (6) 165*a*.
wave velocities, in sandstones, effect of texture, (11) 317*f*.
Sorption. See also *Absorption; Adsorption*.
of water vapor on glass surface in vacuum apparatus, (8) 209*d*.
of xenon in high density graphite at high temperatures, (4) 101*g*.
Sorters, for ores, P (10) 289*j*.
quantitative photometric, for ore, P (10) 290*e*.
Sound, absorption, fibrous board with plastic coating for, P (9) 242*e*.
absorption, glass slabs for, P (9) 242*d*.
vibrated material, for cutting and removing devices, P (5) 138*f*.
waves, large-amplitude, for producing physical, chemical, and physicochemical effects, P (8) 222*c*.
Space vehicles, aerodynamically heated, materials for, B (2) 61*f*.
ceramic materials for use in, (10) 276*b*.
composite structural materials for, (4) 97*e*.
graphite as material in, (6) 160*b*; (10) 288*g*.
nose cones, grinding techniques for, (3) 63*g*.
pyrolytic materials for thermal protection in, (10) 275*i*.
reentry, ceramic materials in heat shields for, (4) 97*a*.
composites of foamed ceramics and organic resins for, (9) 243*i*.
pyrolytic materials for, (10) 275*h*.
rocket-motor structures, thermal protection, (10) 276*e*.
rocket-motor thrust chamber, thermal protection for, (4) 102*a*.
rocket nozzles, evaluation of pyrolytic graphite for, (4) 97*c*.
Space vehicles (*continued*)
rockets, pyrolytic refractory materials for solid-fuels for, (8) 212*j*.
research on high temperature materials for, (8) 214*d*.
solid-propellant motors, refractory composite-materials for, (8) 206*i,j*.
satellite reentry and rocket nozzles, use of ablation principles in, (1) 8*e*.
satellites, materials for reentry heat-protection, (1) 7*g*.
temperature control in, fused silica and silicone varnish for, (8) 207*b*.
Spalling. See *Refractories*.
Spark plugs, construction, P (3) 76*a*.
with integral resistors, P (8) 221*a*.
Specifications, for architectural porcelain enamel on steel for exterior use, (7) 183*b*.
color, pitfalls in, (8) 230*i*.
Indian Standard, for refractory brick from sea-water MgO, (9) 243*h*.
Specific gravity. See *Density*.
Specific heat. See *Heat, capacity*.
Specific surface. See *Surface*.
Spectra, absorption, of glasses of system As_2S_3–As_2Se_3, (5) 128*g*.
of iron-colored beryls, (6) 171*f*.
and luminescence, of CdS- and CdS, CdSe-colored glasses, (5) 129*f*.
of muscovite, alteration by KBr pellet preparation, (6) 171*g*.
of ruby, Zeeman effects on, (6) 171*h*.
of Na–Al–Si glasses, (3) 67*j*.
of solids and chemical bonding, I, (11) 315*j*.
of transition-metal ions in glasses, B (9) 263*j*.
analysis, in far ultraviolet region, methods and devices for, P (1) 31*d*.
analysis, of solids, device for, P (6) 168*h*.
infrared, of anhydrous borates, KBr briquette method for studying, (2) 57*b*.
of crystalline BCl_3, (2) 57*j*.
of dilute solid solutions, B (9) 260*f*.
of hydrated U trioxides and ammonium diuranates, (9) 256*a*.
measurement in borate glasses, (3) 66*d*.
of metallic oxides, phosphates, and chromates, (5) 144*i*.
relation to coordination in quartz and high-pressure polymorphs of SiO_2, (2) 58*c*.
of silicate, borate, and phosphate glasses with U, (9) 239*i*.
of silicate glasses, interpretation of, (3) 66*j*; B (11) 320*i*.
of vitreous boron oxide and sodium borate glasses, (8) 209*c*.
infrared absorption, of Ca sulfate dihydrate, hemihydrate, and soluble and insoluble anhydrites, (2) 34*j*.
of glasses, change on crystallization, (5) 128*k*.
of rare earths, (8) 228*f*.
near infrared, filter media, P (1) 12*c*.
optical and infrared absorption, of rutile single crystals, (4) 121*b*.
Raman, of alkali germanate glasses, (5) 129*c*.
Raman, in study of structure of glassy phosphates, (6) 156*b*.
reflection, of cubic ZnS in interband transition region, (6) 175*f*.
relaxation, of gallium oxide, (6) 164*g*.
relaxation luminescence, of U-activated alkali and alkaline earth metal fluorides, (6) 165*g*.
vibration, of B_2O_3 and B_2S_3 molecules, (5) 147*a*.
of fluorophosphate melts and crystals, (5) 147*b*.
of mixed crystals in Li_2SiO_3–Li_2GeO_3 system, (6) 176*c*.
of ruby and hematite in infrared region, (5) 147*c*.
of silicates, III–V, (5) 147*e*.
X-ray K-absorption, of metal in range of homogeneity of TiN, microstructure of, (2) 58*c*.
Spectrochemical analysis. See *Analysis*.
Spectrographs, beryllium, direct reading, (5) 138*j*.
electron probe X-ray, design and construction, (5) 222*j*.
with ionic separation, P (3) 81*g*.
Spectrography, emission, in analysis of fused Al or Sn oxide crystals, (1) 27*f*.
X-ray, for measuring base exchange capacity, (6) 168*g*.
Spectrometers, infrared, with LiF optics, in study of stretching vibrations of kaolinite, (11) 319*f*.
infrared recorder, with spectra recorded on linear wave-number scale, P (11) 320*a*.
mass, analytical, connecting getter-ion pump to, P (1) 31*c*.
analytical, operation with getter-ion pump, P (2) 60*c*.
apparatus for presenting source particles, P (5) 148*a*.
combined with gas chromatograph, recording apparatus, P (7) 201*i*.
in portable ultrahigh-vacuum system, (2) 52*f*.
with rotating diffraction grating, P (6) 176*b*.
vacuum X-ray, applications to cement plant operations, (2) 34*c*.
X-ray, P (1) 24*e*.
X-ray beam intensity responsive sequential, P (6) 176*c*.
Spectrometry, flame, in determination of Fe_2O_3, CaO, MgO, and K_2O in aluminosilicates, (10) 286*d*.
flame, in determination of Na and K with $BaCl_2$ as buffer, (11) 303*f*.
fluorescent X-ray, in determination of portland cement components, (9) 236*h*.
fluorescent X-ray, of powder sample, dilution method, (2) 56*h*.
mass, in analysis of vaporization products in systems Pb–Se and Pb–Te, (2) 58*h*.

Spectrophotometers. See also *Photometers.*
flame, P (5) 139*f*.
flame, Beckman DU, in determination of metallic exchangeable cations, (5) 139*j*.
infrared, radiation source for, P (11) 320*b*.
ratio measuring, P (4) 121*i*.
Unicam SP600, in control analysis of high-silica and aluminosilicate materials, (3) 81*c*.
Spectrophotometry. See also *Photometry.*
in analysis of ores, (3) 81*e*.
in control analysis of high-silica and aluminosilicate materials, (3) 81*c*.
in determination of Be, (9) 251*c*.
flame, use of light guide in, (1) 23*j*.
of opal glass MS14, (5) 129*i*.
Spectroscopes, P (1) 24*f*; P (2) 53*d*; P (3) 90*a*.
with automatic correction of misalignment, P (7) 201*i*.
Spectroscopy, emission, laser as source in, (8) 223*c*.
infrared, in study of reactions in $BaTiO_3$, (3) 89*f*.
magnetic resonance, (8) 223*b*.
Raman, Pr compounds for light filters for, (5) 147*i*.
Spheres, ceramic, thermal shock analysis of, II, (10) 297*c*.
Spinel. See also *Refractories.*
alumina-rich, single crystals, chemical etching of defect structures in, (11) 316*a*.
aluminous, $AlO \cdot Al_2O_3$, (4) 112*a*.
Al–Si, oriented formation of mullite from, (3) 72*c*.
$CdRh_2O_4$, formation of, (4) 120*f*.
chrome spinellids, in used arch magnesite-chromite refractory, (5) 132*e*.
crystals, polishing ability, (1) 1*i*.
epitaxial growth by reaction in solid state, (5) 143*j*.
ferrimagnetic, body, P (10) 282*f*.
ferro-, mixed, with rectangular hysteresis loop, P (2) 50*f*.
forsterite-, ceramic bodies, P (2) 49*b*.
germanate, (10) 293*i*.
Fe–Cr, X-ray diffraction and magnetic measurements, (5) 147*g*.
made by vapor transport and diffusion in system $MgO–Al_2O_3$, II, (1) 29*e*; III, (5) 145*e*
$MgO–Al_2O_3$, method of making, P (7) 189*c*.
polycrystalline, elastic moduli of, (4) 101*b*.
quadrupole splitting of ^{27}Al in, I,II, (4) 119*c*.
unburned, in trial for open-hearth roof brick, (11) 308*i*.
$MgGa_2O_4$, single-crystal, growth from molten $PbO–PbF_2$ solutions, (5) 144*b*.
-silica, compositions, X-ray diffraction of phase transformations in, (7) 199*d*.
synthetic, monocrystals, stability of, B (9) 262*c*.
synthetic, produced in solar furnace, (5) 140*h*.
Spodumene, altered, Brazilian, DTA of, (3) 82*i*.
β-, as base for castable refractory, (9) 243*h*.
in foamed ceramics, (4) 101*a*.
in sintered ceramic article, P (10) 277*f*.
ceramics, technology and behavior, (4) 101*j*.
ceramics based on, color of, (1) 17*i*.
ore, production of Li_2CO_3 from, P (5) 141*g*.
Spraying, automatic, of glazes, avoiding defects in, (11) 309*c*.
of cathodes with emissive materials, P (7) 193*h*.
electrostatic. See also *Electrostatic processes.*
fixed head for, P (8) 222*b*.
gun for, P (5) 138*h*.
for liquids or powders, P (7) 195*b*.
spray heads for, P (8) 221*h*.
flame, of alumina for coating articles, P (2) 37*i*.
flame, of WC–CrC–Ni coating, P (4) 103*d*.
guns, for electrostatic coating, P (2) 38*e*.
of multiple refractory coatings for hot furnace repair, P (9) 244*i*.
Sprechsaal Silikat Jahrbuch, B (5) 151*c*.
Sputtering, reactive, in preparation of oxide glass films, (3) 67*d*.
Stability, of AlB_2, (4) 114*i*.
of andalusite, kyanite, and sillimanite, (4) 118*e*.
of $AsBr_3$ immersion liquids during storage, (4) 107*i*.
of brucite in water at 25°C, (7) 200*g*.
of $Ca_2Be_2C_5$, in system BeO–CaO, (2) 58*i*.
chemical, of H-montmorillonite suspensions, (3) 86*a*.
of $CoO \cdot Al_2O_3$, $CoO \cdot Cr_2O_3$, and $2CoO \cdot SiO_2$, (9) 257*g*.
of forming characteristics of nepheline syenite bodies, (11) 309*c*.
of gaseous molecules in Pb–Se and Pb–Te systems, (2) 58*h*.
long-term, of fixed resistors, (9) 247*c*.
meta-, of gypsum hemihydrate in mixed acids, (2) 35*f*.
of portland cements, improvement of, (8) 205*f*.
radiation, of dispersion fuels, (11) 307*h*.
relative, of talc, anthophyllite, and enstatite, (2) 58*e*.
thermal, in alkali halide phosphors, (6) 164*a*.
thermal, of glass, increasing of, (7) 185*e*.
Stabilization, of dicalcium silicate, (5) 146*b*.
of pure titania, additions for, (1) 29*g*.
of ZrO_2, conditions of, (4) 121*e*.
of ZrO_2, effect of Fe_2O_3, (7) 188*b*.
Stains. See also *Figments.*
in mortar, removal and prevention, (11) 305*e*.
vanadium zirconium, P (3) 84*e*.
Standardization, of cutting wheels in glass industry, (5) 129*j*.
Standards, ASTM, on mineral aggregates and concrete, B (10) 298*h*.
ASTM, 1962 supplements, for ferrous and nonferrous metals, electron tube materials, semiconductors, testing metals, cement, lime, gypsum, mortar, concrete, mineral aggregates, bituminous materials, soils, asbestos-cement
Standards, ASTM (*continued*)
products, masonry units, pipe and drain tile, refractories, whitewares, enamel, glass, building stone, thermal and acoustical insulation, sandwich and building constructions, fire tests, paint, naval stores, coal and coke, gaseous fuels, industrial aromatic hydrocarbons, antifreezes, industrial chemicals, textiles, soap, sorptive mineral materials, halogenated organic solvents, industrial water, atmospheric analysis, wax polishes, and rubber, electrical insulation, B (9) 259*a*.
British, for quality control methods, (10) 284*c*.
mobile microwave laboratory, (9) 251*j*.
for quality of ceramic products, (9) 258*e*.
of temperature measurement and control, B (9) 259*h*.
tentative, for shape and dimensions of sleeve brick, in Japan, (11) 308*h*.
Stannic oxide. See *Tin, oxide.*
Starch, as additive for green molding sand, P (8) 216*h*.
Static electrification, B (9) 264*b*.
Statistical analysis. See *Analysis.*
Statistics, in optimum sampling, (6) 167*d*.
procedures, in quality control of ceramics, (4) 122*e*.
statistical maintenance control, in chemical plant, (3) 79*j*.
Staurolite, from Northern Rhodesia, optically negative, (6) 170*f*.
Steam. See also *Moisture; Water.*
curing, of fly ashes, (10) 267*j*.
plant, operating under variable load, properties and use of fly ash from, (10) 267*h*.
sintering, of UO_2, (1) 15*j*.
Steatite. See also *Talc.*
bodies, organic additives for, P (2) 47*g*.
hydrothermal synthesis of, P (4) 110*i*.
loss factors, relation to microstructure, (6) 165*b*.
opaque boron-calcium glaze for, (11) 309*d*.
Steel. See also *Enameling metals; Iron.*
action of enamel melts on, (2) 36*e*.
Al-coated and Al-rich alloy coated, frit as protective coating for, P (3) 65*h*.
boron, irradiated, gas bubble formation in, B (8) 234*e*.
B in, fabrication procedures and tensility, (8) 214*b*.
cold-rolled, protection from atmospheric corrosion, (9) 238*b*.
in concrete, rapid destruction, (8) 206*e*.
continuous pouring, service of nozzles for, (1) 15*g*.
decarburized enameling-grade, open coil annealing in process of making, (2) 37*d*.
enameling of, elimination of defects, P (10) 269*h*.
foundries, use of silica flour in, (1) 15*e*.
γ-rays produced in, effect of boron carbide on, (10) 274*i*.
glass-coated, effect of moisture in furnace atmosphere on H defects in, (1) 4*c*.
glassed, equipment, bolt torques and gaskets for, (9) 238*b*.
identification of sand marks on by electron-diffraction reflection, (6) 159*h*.
low carbon, for enameling for laundry and refrigerator equipment, (6) 155*g*.
making, converter, in Japan, (6) 161*h*.
oxygen, grate-kiln production of pebble lime for, (10) 288*g*.
oxygen, refractories for, B (10) 299*j*.
oxygen process for, I,II, (6) 160*j*.
oxygen, refractories for, (6) 160*g*.
refractories for electric furnace, (6) 160*e*.
molten, erosive effects on pouring-pit refractories, (11) 305*j*.
molten, reaction with refractories, VII–IX, (1) 14*a*.
nonmetallic inclusions in, electron microscope study, I, (6) 155*j*.
production, refractories requirements, (10) 273*j*.
reaction with silica sand, (9) 243*f*.
sand marks in, identification by electron diffraction, (7) 195*e*.
sheet, advantages of lower temperature enameling on, (2) 36*f*.
drawability for enameling, (4) 97*h*.
economy in enameling, (2) 37*e*.
fish scaling in enameling, (8) 207*e*.
special, for enameling, (2) 37*d*.
stainless, rod for welding, P (4) 102*g*.
stampings, automatic handling, (6) 155*b*.
strip, high-melting coatings on, P (6) 155*f*.
wet grinding of, abrasives for, P (4) 95*g*.
zero-carbon, for one-coat enameling, (2) 37*f*.
Stoichiometry, effect on rate of grain growth of UO_2, (10) 294*b*.
sub-, high temperature, in UO_2, (1) 28*d*.
Stones. See also *Gems; Rocks.*
crystalline, porous, manufacture of, P (7) 187*c*.
crystalline, from slag, P (4) 96*g*.
Izumiyama pottery, iron removal from, I, (8) 225*c*.
precious, machine for grinding and polishing facets of, P (5) 125*g*.
synthetic, production with controlled properties, P (6) 154*j*.
Stoneware, Bavarian, from 17th century to 1853, (7) 177*j*.
celadon glazes for, (7) 177*i*.
corrosion resistance, (10) 298*d*.
gas-fired kilns for, (10) 287*i*.
salt-glazed, (5) 126*a*.
thermal shock resistance, testing of, (10) 279*b*.
Storage, of dried clay brick, deterioration during, (1) 12*h*.
new methods, (4) 106*g*.
of supersulfated cement, (1) 3*d*.
Storage (*continued*)
of unburned shapes of sintered dolomite, improvement with tar binder, P (4) 102*c*.
Strains, bridge, direct current, (3) 80*i*.
internal, and changes in mechanical strength of glass, (1) 7*c*.
in perthites, explanation of, (4) 114*b*.
settings, in glass button stems, (2) 39*g*.
Strength, breaking, of glass, effect of heat treatment, (10) 270*e*.
breaking, of soda-lime-silica glass from −100° to 700°C, (10) 270*h*.
of ceramic materials, (7) 202*a*.
compressive, of concrete, effect of curing under pressure, (8) 204*b*.
compressive, of concrete, effect of tensile creep, (8) 204*f*.
crushing, tests, control charts for, (3) 79*i*.
as function of pore content, (1) 15*a*.
of glass fibers, statistical study, (9) 241*h*.
green, of porcelain, increasing of, (10) 278*e*.
internal compressive, of hollow glasses, determination, (1) 6*g*.
mechanical, of glass, (3) 68*g*.
mechanical, of refractories, B (10) 300*i*.
of polycrystalline ceramics, effect of dislocations, (8) 227*j*.
of reaction products in system $CaO–SiO_2$, factors affecting, (8) 204*j*.
of stoneware pipe, (8) 212*a*.
tensile, of ceramics, hollow sphere method for determining, (1) 23*h*.
of concrete, research on, (1) 3*i*.
determination by hydrostatic tester, (4) 108*a*.
of MgO, effect of crystal dislocations, (10) 291*j*.
transverse, measurement at high temperatures, (11) 313*a*.
transverse bend, of Al_2O_3 and MgO, effect of grain size on, (7) 198*j*.
Stresses, in furnace arches, measurement of, (8) 214*g*.
in glasses, analysis, P (1) 10*c*.
internal, in quenched glasses, (10) 271*b*.
normal, measurement in viscoelastic flow, (10) 295*f*.
optical determination, apparatus, P (7) 196*b*.
relaxation, in transformation range, B (11) 320*h*.
-strain behavior, of TiO_2 single crystals, (7) 200*g*.
thermal, and mechanical properties of ceramics, B (3) 91*g*.
thermal, methods and apparatus for determination, P (5) 139*h*.
thermoelastic, in balanced and unbalanced seals, (1) 20*h*.
Strontium, compounds, crystal chemistry of, (10) 291*g*.
compounds, magnetite phases, (2) 57*h*.
crackle glaze, (1) 2*d*.
ferrate, systems. See *Systems.*
ferrite, modified, as permanent magnet material, (10) 281*d*.
fluoride, single crystal, luminescence kinetics of Sm in, (6) 164*j*.
hafnate, systems. See *Systems.*
oxide, and (BaSr)O, cathodoluminescence of, (4) 112*j*.
as coating for cathodes, photoelectric emission from, (5) 135*i*.
sulfides, selenides, and tellurides, optical absorption and photoemission in, (4) 117*d*.
systems. See *Systems.*
salts, effect on sodium beryllate solutions, (7) 198*d*.
selectivity, of zeolite, (7) 198*j*.
silicides, (4) 120*c*.
$SrZnO_2$, crystal structure of, (4) 113*f*.
systems. See *Systems.*
titanate, electroluminescence from surface layers, (4) 113*e*.
hydrothermal preparation, (10) 294*a*.
monocrystals, nonstoichiometric, growth of, B (9) 263*f*.
single crystal, acoustic attenuation and velocity in, (9) 257*f*.
single-crystal, effect of dislocations on oxidation and reduction, (3) 86*j*.
systems. See *Systems.*
thermal conductivity compared to $BaTiO_3$, (6) 175*e*.
Structural clay products. See also *Brick; Pipe; Structural materials; Tile.*
batch preparation, (10) 284*f*.
clays of coastal plain of S. Car. in, (3) 82*f*.
deformation at high temperatures, (2) 43*h*.
filtration in, (3) 79*d*.
laminations in, I,II, (9) 243*b*.
Mn ore as pigment in, (1) 12*i*.
masonry structure design, B (10) 298*h*.
Philippine clays for, (3) 83*a*.
pink centers and black cores in, (3) 71*c*.
radiation gas drying, (7) 196*e*.
vitreous, cellular, P (1) 13*d*.
Structural materials. See also *Aggregates; Brick; Building materials; Cement; Concrete; Enameled ware; Glass; Insulation, thermal; Masonry; Roofing materials; Structural clay products.*
ceramic, for γ-radiation and neutron absorption, (10) 274*a*.
composite, for space vehicles, (4) 97*e*.
foam silicate, for rural and housing construction, (1) 6*h*.
fused silica-hydrated cement compositions as, (1) 4*f*.
glass, lightweight, P (8) 210*j*.
glass flakes, as reinforcement in, (9) 240*b*.
of granular slag aggregate, P (10) 268*b*.
Structure, of AlBeB, (5) 145*f*.
of amorphous substances, background in electronographic studies, (5) 144*c*.

Structure (*continued*)
atomic, of ortho- and ring silicates, B (5) 151*g*.
atomic and molecular, of composite insulating materials, relation to properties, (3) 76*e*.
of Be_4B, (5) 145*g*.
of blast-furnace slags and matrix, gas pores as, (10) 267*a*.
of boric oxide and borate glasses, theories of, (3) 68*f*.
of cabal glasses, correlation with thermal expansion, (3) 67*f*.
of cement stone, effect of Ca hydrochloraluminates on, (5) 126*h*.
crystalline, of mullite, statistical model for, (3) 89*a*.
of crystals. See *Crystals*.
determination of shielding factors in energy range 0.1 to 4.0 Mev, P (10) 287*e*.
development, in aqueous suspensions of tricalcium aluminate, effect of $CaCl_2$, (11) 317*d*.
electronic, of defects, optical studies of, B (8) 234*c*.
electronic, of point defects in crystals, B (9) 260*j*.
of feldspars, (4) 110*g*.
of glass, relation to thermal history, (7) 185*b*.
of glasses in system K_2O–PbO–SiO_2–TiO_2, effect of TiO_2 on, (5) 129*f*.
of glassy phosphates, study by use of Raman spectra, (6) 156*b*.
of inorganic liquids and solids, B (10) 298*i*.
of kaolinite, study with infrared absorption, (11) 319*f*.
of long-spacing mica-like minerals, (6) 170*a*.
of MgO single crystals, explosively shocked, (9) 257*g*.
magnetic, of barium ferrate III, (4) 116*f*.
of γ-Fe_2O_3, neutron diffraction pattern of, (3) 87*d*.
of 3*d* transition metal double fluorides, (10) 294*i*.
micro-, of $BaTiO_3$ ceramics, (11) 310*b*.
of cement clinkers, refractories, and slags, B (11) 321*a*.
changes in UO_2 from irradiation and high temperature gradients, (11) 307*g*.
effect of liquid solubility and wettability on, (4) 118*e*.
effect on mechanical behavior of polycrystalline ceramics, B (9) 259*e*.
of porcelain bodies, XII, (1) 18*h*.
of pressure sintered Al_2O_3 and MgO, (11) 318*c*.
of X-ray K-absorption spectra of the metal in range of homogeneity of TiN, (2) 58*c*.
of muscovite, (11) 319*h*.
of NbO, (4) 115*g*.
principles, in inorganic compounds, B (5) 151*d*.
of reaction products in system CaO–SiO_2, factors affecting, (8) 204*j*.
regular and semirandom, in chlorite, (9) 255*i*.
of resin-impregnated porous ceramics, (9) 243*i*.
of semimetallic elements, XIII, (3) 89*c*.
of sintered metals, effect of porosity on, (6) 172*i*.
of synthetic cordierite at low temperature and pressure, (4) 116*a*.
of TiC–WC–Co alloys, (2) 59*a*.
of turbulent Bunsen flames, (6) 169*a*.

Sublimation, from dispenser and oxide cathodes, retarding field technique for measuring, (10) 281*g*.
in preparation of uranium oxide single crystals, (1) 29*h*.

Sulfates, alkaline-earth, reactions with cristobalite, (5) 145*i*.
ions, addition to UO_3 to increase surface area, (10) 293*f*.
systems. See *Systems*.

Sulfides, metal, phosphor grade, P (2) 50*g*.
refractory, preparation, P (8) 216*i*.

Sulfite liquor, waste solids, as additives in mortar, P (9) 237*j*.

Sulfite lye, effect on porcelain green strength, (10) 278*e*.

Sulfur, in basic slag, rapid determination by combustion method, (6) 154*j*.
compounds, effect on clays and glazes, (1) 25*c*.
content, in heavy oil, relation to SO_2 in cement clinker, (7) 181*i*.
determination in silicate rocks by wet oxidation, (9) 251*a*.
in electron processing of CdS crystal, P (7) 193*a*.
in heavy oil, determination by tritium bremsstrahlung absorption method, (4) 108*f*.
solubility in furnace slags, (7) 182*d*.
systems. See *Systems*.
trioxide, effect on anatase-rutile transformation, (7) 199*a*.
effect on lead and ZnO glasses, (6) 156*j*.
nephelometric and turbidimetric determination in silicates, (9) 237*a*.
systems. See *Systems*.

Sulfuric acid, in etchants and electrolytes, (8) 228*i*.
nitrate-activated, for economy in pickling, (3) 65*f*.

Sun, as pumping source for continuous laser, (10) 282*j*.

Supersonics. See *Sonics*.

Surface, area, Blaine specific, of gypsum, determination, (5) 138*j*.
area, of oxides and clay minerals, determination by heat of immersion, (6) 172*j*.
ceramic, electron microscopic study of, (9) 251*j*.
of ceramic materials, environmental effects, (8) 230*c*.
composition, relation to metal composition, pickling rate, and direct-on enamel adherence, (2) 37*j*.
curved, device for forming, P (10) 285*e*.
finish, effect on friction, wear, and lubrication, (3) 90*g*.

Surface (*continued*)
fracture, of sintered UO_2, (11) 306*i*.
grinding, basics of, (3) 79*d*.
nonplanar, examination by ultrasonics, P (8) 223*i*.
phenomena, Hahn emanation method in study of, (6) 175*b*.
properties, of porous titania, (1) 29*g*.
specific, in control of Al_2O_3 fineness, (9) 252*j*.
gas adsorption method for rapid comparison, (11) 313*b*.
measurement with Blaine apparatus, (4) 116*h*.
of powders, automatic device for measuring, (8) 222*g*.
relation to particle size distribution in comminution, (9) 237*c*.
treatment, of SiC, by electrolytic etching, P (6) 176*c*.

Surface-active substances, effect on hardness of concrete, (1) 2*f*.
for improving properties of brick clays, (1) 12*h*.
role in slip casting, (7) 190*f*.

Surface tension, of striae in optical glasses, (5) 130*d*.

Suspensions. See also *Slips*.
ceramic, viscosity measurement by capillary viscosimeters, (6) 168*a*.
stable aqueous, based on fused alumina, P (3) 90*a*.

Symmetry, inversion, of M and R centers, in NaCl and KCl, (4) 115*e*.
of layer-lattice silicates, I,II, (7) 198*f*; III,IV, (9) 255*d*; V,VI, (11) 316*e*.
of transition metal impurity sites in crystals, B (9) 260*c*.

Symposiums, Am. Ceram. Soc., on mechanical behavior of crystalline solids, proceedings of, B (9) 259*e*.
on control of glassware quality, (9) 241*j*.
on economies in enamel shop, (2) 37*e*.
on glass melting, discussions from, (4) 98*c*.
4th international, on chemistry of cement, proceedings, B (5) 148*i*.
on high-alumina refractories, (11) 306*j*.
on mechanical strength of glass and ways of improving it, 1961, Florence, B (1) 31*h*.
on nuclear ceramics, (11) 306*h*.
7th, on art of glassblowing, proceedings of, B (5) 151*f*.

Syngenite, effect on lumping of cements, (1) 3*c*.

Synthesis, of Ca borate compounds by hydrothermal methods, (7) 201*g*.
of ceramic pigments, high-temperature crystal chemistry of, I–IV, (9) 238*g*.
chemical, in preparation of laser materials, (10) 281*f*.
of clinker minerals, possibility of, (7) 182*e*.
of cubic form of boron nitride, (2) 54*g*.
of diamond, mechanism of formation, (6) 169*h*.
of fibrous SiC, by thermal reduction of silicates and Si compounds, (9) 244*f*.
of fluormica, (7) 201*e*.
of forsterite, diopside, akermanite, and wollastonite, from molten PbO, (9) 257*h*.
of forsterite crystals, (6) 175*d*.
of gyrolite and reyerite, (5) 146*f*.
hydrothermal, of calcite, (5) 144*e*.
of quartz, P (1) 25*i*.
of single crystals, B (3) 92*b*.
of steatite, P (4) 110*i*.
of Pb and Ba disilic fluormicas, (9) 247*b*.
low-temperature, of ferromagnetic ferrites, (9) 247*f*.
of minerals and compounds from system NaAlSiO$_4$–NaAlSi$_3$O$_8$–H_2O, (5) 146*e*.
of monocrystals of Zn_2SiO_4/Mn and $(Zn,Be)_2SiO_4$/Mn, (4) 104*g*.
of mullite, P (5) 136*h*.
of pure neodymium hexaboride, (11) 319*j*.
pyro-, differential thermal, (4) 107*d*.
pyrolytic, of TiB_2, (11) 306*e*.
of refractory mixed oxide with perovskite structure, (9) 257*i*.
of refractory U compounds, (9) 257*h*.
of single crystal bodies, P (6) 167*e*.
of TiN from TiH_2 powder and N or ammonia, (5) 146*i*.
of UC and UC_2, (5) 146*a*.
of wurtzite form of SiC, (2) 59*e*.

Systems. See also *Equilibrium studies*.
alkali–B_2O_3–SiO_2, solubility of glasses in, (10) 278*g*.
alkali oxide-boric oxide-silica, and alkali oxide-alumina-silica, screening concept of behavior in, (3) 66*e*.
Al–Be–B, idealized composition in, (5) 145*g*.
Al^{3+}–Cr^{3+}–H_2O, conditions for obtaining crystalline solid solutions in, (7) 199*h*.
Al_2O_3–Cr_2O_3, Vegard's law and, comment on, (3) 86*b*.
Al_2O_3–Fe_2O_3–GeO_2, compounds in with andalusite structure, (8) 226*g*.
Al_2O_3–Nb_2O_5, (11) 319*c*.
α-alumina-silica, crystallization in, II, (4) 120*i*.
Al_2O_3–SiO_2–H_2O, in pyrophyllite deposits, mineralogy and petrology of, (4) 109*f*.
γ-Al_2O_3–H_2O, dielectric resonance and dispersion phenomena in, (2) 56*e*.
β-Al_2O_3–ZrO_2, refractories in, (4) 121*c*.
Sb_2O_3–Al_2O_3–R_2O, effect of SiO_2 or GeO_2 on glass-forming region, (11) 304*b*.
aqueous, at high temperature, III, (9) 255*a*.
As_2S_3–As_2Se_3, absorption spectra of glasses in, (5) 128*g*.
asbestos-cement-water, filterability in, (8) 204*h*.
(Ba,Pb)(Ti,Zr)O_3, structure and phase diagram, (7) 200*i*.
BaO–Al_2O_3–SiO_2, solid state reactions in, II, (10) 297*h*.
BaO–SiO_2, liquid immiscibility in, B (11) 320*h*.

Systems (*continued*)
BaO–SiO_2, phase diagram data, (3) 87*i*.
Be–B, softening temperatures in Be-rich range, (5) 142*e*.
BeO–Al_2O_3–SiO_2, alumina region in, (3) 89*e*.
BeO–CaO, stability of $Ca_3Be_2O_5$ in, (2) 58*i*.
BeO-metal oxide, phase studies using porous-collector technique, (6) 174*b*.
Bi_2O_3–CdO–SiO_2, Bi_2O_3–CdO–B_2O_3, and Bi_2O_3–CdO–GeO_2, relation of dielectric properties to structure of glasses in, (1) 6*i*.
B–C, high temperature phase equilibria, (10) 276*e*.
B_2O_3–CdO–La_2O_3, devitrification of glasses in, (11) 303*g*.
B_2O_3–Na_2O, melting point depression in, (4) 120*d*.
Cd–Cd halide, (2) 56*e*.
$CdCl_2$–AgCl, $CdCl_2$–Na_2SO_4, and $CdCl_2PbSO_4$–Na_2SO_4, thermodynamic activities in, (10) 295*b*.
CdO–B_2O_3, compound formation in, (7) 198*f*.
CdO–UO_3–O_2, fluorite phase in, (5) 143*e*.
$CaCO_3$–SiO_2, DTA and TGA study of reactions in, (1) 5*h*.
$CaCO_3$–SiO_2–Al_2O_3, DTA and TGA study of reactions, (10) 269*j*.
CaO–Al_2O_3, thermodynamics of solid-phase reactions in, (4) 121*a*.
CaO–Al_2O_3–SiO_2, DTA study of activation of slags of, (6) 154*g*.
furnace slags in, solubility of S in, (7) 182*d*.
stability relations of Ca hexaluminate in, (4) 112*i*.
CaO–B_2O_3–Al_2O_3, properties of glasses in, III, (3) 67*f*.
CaO–CO_2–H_2O, and origin of carbonatites, (1) 30*j*.
CaO–MgO, phase equilibria in, (9) 256*e*.
CaO–MgO–Al_2O_3–SiO_2, at atmospheric pressure, bearing of join $Ca_2Al_2Si_2O_{12}$–$MgAl_2Si_2O_{12}$ on, (2) 57*a*.
CaO–SiO_2, activity of CaO in, (7) 178*b*.
CaO–SiO_2, factors affecting reaction products in, (8) 204*j*.
3CaO·SiO_2–Al_2O_3–MgO, solid solution in, (7) 200*f*.
CaO–SiO_2 gel-H_2O, at 110°C, reaction in, (4) 119*i*.
CaO–SiO_2–H_2O, hydrothermal reaction and properties of reaction products in, (7) 180*a*.
CaO–ZnO–Al_2O_3–SiO_2, three planes in, (2) 59*b*.
$CaSiO_3$–SiO_2–H_2O, hydrothermal determination of phase equilibria in, (5) 146*f*.
$CaSO_4$–H_2O, phase diagram of, (5) 144*i*.
cement-water and asbestos-cement-water, viscosity measurement of slurry in, (8) 205*g*.
ceramic-metal, bibliography and abstracts, 1962, B (9) 259*c*.
CsCl-$TiCl_3$, compounds in, (4) 115*i*.
Cr-O, phase diagram at high O pressure, (4) 117*d*.
CrF_2–CrF_3, phase equilibria in, (1) 28*j*.
Cr_2O_3–UO_2–O_2, solid state relations in, (7) 201*i*.
clay-water, role in ceramics, (1) 25*g*.
Co_2O_4–Mn_3O_4, phase relations in air, (11) 318*d*.
Cu oxide–Al_2O_3, (11) 319*c*.
CuO–Cu_2O–SiO_2, equilibrium relations in, (11) 317*b*.
fluorphlogopite-KF, reaction products in, (4) 119*d*.
forsterite-kaolin, sintering studies, (5) 145*j*.
GeTe-SnSe, formation of solid solutions in, (4) 120*g*.
glass forming, compatibility in, (1) 5*h*.
Hf-O, constitution of, (11) 316*b*.
ilmenite-hematite, magnetic property and crystal chemistry, I, II, (6) 173*b*.
FeO-Fe_2O_3-TiO_2, liquidus temperatures in, (9) 228*c*.
Fe_2O_3-$FePO_4$, reduction of metal salts in, I, (4) 113*b*.
FeO-MgO-Fe_2O_3, crystal growth in, (8) 226*e*.
iron oxide-manganese oxide, in air, (5) 146*d*.
FeO-NiO-Fe_2O_3, crystal growth in, (8) 226*e*.
iron oxide–titanium oxide, phase equilibria at liquidus temperatures and low O pressures, (4) 117*h*.
La_2O_3-Fe_2O_3, phase diagram of, (6) 174*i*.
Pb-Se and Pb-Te, stabilities of gaseous molecules in, (2) 58*h*.
$PbCl_2$-Na_2SO_4, thermodynamic activity in, (10) 295*b*.
$PbCrO_4$-$PbMoO_4$, new phase in, (1) 28*g*.
$PbHfO_3$-$BaHfO_3$, and $PbHfO_3$-$SrHfO_3$, dielectric behavior in, (9) 246*h*.
PbO-B_2O_3, glasses in, B and Pb atoms as function of composition in, (9) 241*a*.
PbO-B_2O_3-SiO_2, solubility of glasses in, (10) 278*g*.
PbO-B_2O_3-SO_3, clear and stable glasses in, (6) 156*j*.
PbO-SiO_2-UO_3, glasses in, (9) 239*i*.
PbO-SrO-ZrO_2-TiO_2, determination of unreacted constituents of binary compositions in, (1) 19*d*.
PbO-P_2O_5, region $Pb_4P_2O_9$-$Pb_3(PO_4)_2$, (4) 117*i*.
PbO-SiO_2, acid-base equilibria in, (4) 111*j*.
PbO-TiO_2, PbO-rich side, (10) 296*g*.
PbO-ZnO, (7) 201*b*.
PbSe-SnSe, formation of solid solutions in, (4) 120*g*.
$PbTiO_3$-KNbO$_3$, ferroelectric phase transitions in, (2) 47*j*.
LiCl-$TiCl_3$, formation of solid solutions in, (4) 115*i*.
Li_2CO_3-Na_2CO_3, Li_2CO_3-K_2CO_3, Li_2CO_3-Na_2CO_3-K_2CO_3, solid-liquid phase equilibria in, (1) 30*c*.

Systems (*continued*)
Li_2O-Al_2O_3-SiO_2, crystallization of glasses in, (5) 129*a*.
glass formation and recrystallization in Li metasilicate region, (4) 98*g*.
thermal shock resistant ceramics in, I, (8) 209*g*.
Li_2O-Al_2O_3-SiO_2-CaO, glass-ceramics with low thermal expansion in, (5) 129*b*.
Li_2O-K_2O-ZnO-SiO_2, chemically machinable photosensitive glasses in, B (11) 320*k*.
Li_2O-ZnO-SiO_2, phase relationships in, (3) 88*k*.
Li_2SiO_3-Li_2GeO_3, vibrational spectra of mixed crystals in, (6) 176*c*.
$MgAl_2O_4$-Al_2O_3, Cr behavior in, (1) 26*f*.
MgO-Al_2O_3, spinel made by vapor transport and diffusion in, (1) 29*e*.
MgO-Al_2O_3, spinel made by vapor transport and diffusion in, III, (5) 145*e*.
MgO-Al_2O_3-SiO_2, metastable osumilite- and petalite-type phases in, (6) 173*k*.
MgO-Al_2O_3-SiO_2, reinvestigation of central part, (2) 56*g*.
MgO-CaO-FeO-Fe_2O_3-SiO_2, reaction series for subalkaline igneous rocks, (7) 199*i*.
MgO-FeO-Fe_2O_3, phase equilibria in temperature range 1400° to 1800°C, (2) 58*f*.
MgO-Ta_2O_5, phase studies in, (6) 174*d*.
MgO-H_2O, reactions in, (5) 146*a*.
MgO-H_2O-NaOH, phase relations in low NaOH portion, (6) 173*g*.
MgO-ZrO_2-BeO, solid solubility region in, (6) 174*b*.
Mg_2SiO_4-Ni_2GeO_4, at 600°C and 0 to 90 kb, (11) 319*d*.
(MnO, FeO, MgO, CaO)-Al_2O_3-SiO_2-H_2O, synthetic cordierite in, miscibility and structure, (4) 116*a*.
melted ceramic, wollastonite in, (2) 47*b*.
Nd_2O_3-Sm_2O_3 and Nd_2O_3-CeO_2, phase transformation in, (9) 257*h*.
Ni-S, from 200° to 1030°C, (4) 116*h*.
Nb-N, to 1500°C, (4) 117*a*.
Nb-N-O, tentative phase diagram, (4) 117*g*.
Nb_2O_5-Na_2O-SiO_2, dielectric properties of glasses in, (4) 98*a*.
Pu-C, phases in, B (8) 231*b*.
PuO_2-ZrO_2, (6) 175*e*.
$4K_2O$-B_2O_3-UO_2, glasses in, (9) 239*i*.
K_2O-PbO-SiO_2-TiO_2, glasses in, effect of TiO_2 on properties and structure, (5) 129*f*.
K_2O-SiO_2-TiO_2, dual role of Ti in, (9) 255*j*.
quaternary, of perovskite type $A^{2+}B^{4+}O_3$ solid solutions, (6) 175*a*.
RbCl-$TiCl_2$, compounds in, (4) 115*i*.
SiO_2-BaO-TiO_2-Cr_2O_3, frits of, in high-temperature coatings for metals, (10) 268*j*.
SiO_2 (quartz)-H_2O, phase diagram of, (5) 144*i*.
SiO_2-H_2O, upper three-phase region in, (2) 59*f*.
silicate, submicroliquefaction zones in phase diagrams of, (5) 146*d*.
silicate and phosphate, U-bearing glasses in, (1) 10*e*.
Si-O-C, stable compounds in, (5) 144*j*.
$NaAlSiO_4$-$NaAlSi_2O_6$-H_2O, minerals and compounds synthesized from, (5) 146*e*.
NaCl-Na_2O, phase diagram of, (4) 117*g*.
NaCl-H_2O, phase diagram of, (5) 144*i*.
NaF-BeF_2-UF_4, phase equilibria for, (8) 229*e*.
NaF-ThF_4-UF_4, phase equilibria in, (3) 88*e*.
Na_2O-$4B_2O_3$-SiO_2, submicroliquefaction zones in, (5) 146*d*.
Na_2O-P_2O_5-UO_2, glasses in, (9) 239*i*.
Na_2O-SiO_2-UO_2, glasses in, (9) 239*i*.
Na_2SO_4-Na_2CO_3, phase transformations in, (1) 29*c*.
Na_2SO_4-H_2O, phase diagram of, (5) 144*i*.
Na_2ZrO_3-Al_2O_3, refractories in, (4) 121*c*.
Sr-Si, Sr-rich side, (4) 120*c*.
$SrFeO_3$-$SrTiO_3$, effect of Fe^{4+} in, (7) 191*c*.
SrO-MgO-SiO_2, solid-state equilibria for, (10) 297*g*.
talc-kaolin, sintering studies, (5) 145*j*.
Ta-C, high temperature phase equilibria, (10) 276*e*.
Th-H-C, H equilibrium pressures in, (7) 201*b*.
SnTe-GeTe, SnTe-SnSe, formation of solid solutions in, (4) 120*g*.
TiO_2-Al_2O_3-SiO_2, alumina region in, (3) 89*e*.
TiO_2-Na_2O-SiO_2, dielectric properties of glasses in, (1) 6*b*.
of two binary compounds, estimation of phase diagrams for, (10) 292*e*.
UC, UC_2, and UN with transition metals, phase equilibrium in, (11) 307*f*.
UO_3-CuO-NiO-SO_2-H_2O, studies at 300°C, (9) 255*a*.
UO_2-PuO_2, melting behavior in, (9) 243*g*.
UO_2-Na_2O-SiO_2, region of glass formation in, (9) 239*j*.
UO_2-UP_2O_7, thermal expansion of bodies in, (5) 132*k*.
UO_2-ZrO_2-CaO, ceramic nuclear fuels in, (3) 71*j*.
H_2O-Al_2O_3, formation of crystalline Al(OH)$_3$, (5) 142*f*.
H_2O-Al_2O_3, formation of crystalline Al hydroxides, (4) 112*j*.
Y_2O_3-Fe_2O_3-FeO-Al_2O_3, phase relations in garnet region, (5) 144*i*.
ZnO-B_2O_3-SO_3, clear and stable glasses in, (6) 156*j*.
ZnO-TiO_2, sintering in, (1) 29*i*.
Zr-C, high temperature phase equilibria, (10) 276*e*.
ZrO_2-SiO_2, solid solution region in, (7) 200*a*.

Talc. See also *Steatite*.
Austrian deposits, (7) 197*e*.

Talc (*continued*)
clay-, body, thermal shock resistance of, (10) 279*b*.
crystals, analysis of dislocations in, B (9) 262*a*.
-kaolinite, compositions, study of phase transformations by X-ray diffraction, (6) 174*e*.
in pyrophyllite refractories for control of reversible thermal expansion, (4) 100*j*.
stability, in relation to anthophyllite and enstatite, (2) 58*e*.
systems. See *Systems*.
tremolitic, role in ceramics, (2) 47*g*.
uniformity, improvement by storage method, (8) 225*g*.

Tanks. See *Furnaces, glass*.

Tantalum, -base alloys, high-temperature oxidation-resistant coatings for, (8) 207*a*.
-base alloys, protective coatings for, (8) 206*g*.
borides, for containing molten U and Ca, (11) 308*i*.
borides, production of, P (10) 277*g*.
carbide, high-temperature crystalline modifications, (6) 159*g*.
carbide, in thermal protection of rocket-motor structures, (10) 276*e*.
hydroxide, complexes with dials, (10) 291*a*.
oxidation, low temperature, (10) 296*e*.
oxide, of ABO_4 type, (4) 121*g*.
films, rectifying action and emf at high temperatures, (10) 281*e*.
systems. See *Systems*.
oxidized films, current-controlled negative resistance in, (10) 280*b*.
pentoxide, fluoride-free, production of, (5) 141*a*.
properties, constitution, and fabrication, B (7) 202*c*.
reaction with N at 800° to 1300°C, (11) 318*f*.
separation from Nb, P (3) 89*j*.
in solid electrolytic capacitor, P (10) 283*b*.
systems. See *Systems*.
Technical ceramics, and electro-, development trends, (10) 298*f*.
spray drying process, (4) 104*i*.
Technologists, position in glassworks for handmade ware, (7) 185*c*.
Technology, of cement, B (9) 261*j*.
glass, advances in, Part 2, B (11) 320*f*.
of glass seals, B (4) 124*h*.
Teflon, bonding with metal, glass, and ceramic, (9) 258*a*.
Tektites, relation of meteoritic craters of Germany to, (4) 109*c*.
Television, in automation of cement plant, B (9) 261*j*.
Television screens. See *Screens*.
Television tubes. See *Tubes*.
Tellurates, Al, Cr, and Ga, P (4) 104*j*.
Tellurides, for direct generation of electrical energy from nuclear energy heat, (10) 275*a*.
heavy metal, method of making, P (3) 84*g*.
inorganic, preparation, P (2) 49*i*.
Tellurites, Ti, Zr, and Sn, composition, P (1) 22*b*.
Ti, Zr, and Sn, method of making, P (1) 21*j*.
Tellurium, dioxide, enthalpy of formation of, (4) 113*h*.
systems. See *Systems*.
in Tl_2Te_3, P (10) 283*a*.
Temperature, calculation in laminated systems, (9) 251*b*.
changes, effect on chipping and cracking of wall and floor tile, (7) 190*g*.
configuration, of glasses of high Young's modulus, effect of changes, (1) 9*f*.
control. See also *Controls*.
control, in spacecraft, fused silica and silicone varnish for, (8) 207*b*.
dependence, of electroluminescence of ZnS:Cu,Cl single crystals, (6) 165*j*.
detector, P (9) 252*j*.
distribution, axial, in determination of thermal conductivity of beryllia rod, (11) 305*i*.
effect on gypsum transformation, (6) 154*f*.
effect on slips and molds, (2) 47*b*.
firing, of grog and body of glass melting pot, effect on physical properties, (3) 73*e*.
of fused magnesia relation to electric resistance, (9) 244*a*.
of glass, pyrometers for measuring, (9) 239*e*.
gradients, migration of copper(I) and copper in, (5) 142*b*.
high, apparatus, P (8) 221*i*.
apparatus for generating, P (5) 140*e*.
apparatus for measuring, P (10) 286*j*.
evaluation of instruments for measuring, (2) 52*e*.
Nova Scotia College laboratory for, (9) 258*b*.
reactions of quartz-kaolinite-feldspar mixtures, (3) 75*g*.
reaction vessel, two-terminal end cap for, P (8) 222*c*.
indicator, P (4) 108*b*.
indicator, colored wax or resin, P (8) 224*b*.
liquidus, in system FeO-Fe_2O_3-TiO_2, (8) 228*c*.
low, measurement with semiconductor resistance thermometers, (10) 281*a*.
measurement. See also *Pyrometers; Thermocouples; Thermometers*.
apparatus for generating neutrons, P (11) 313*f*.
apparatus for nuclear reactor fuel element, P (8) 224*b*.
and control in science and industry, Vol. III, Part I, B (9) 259*h*.
in engineering, Vol. II, B (2) 62*c*.
importance in high-temperture chemistry, (9) 258*c*.
instrument for, P (11) 313*j*.
in solar furnace, I, (2) 52*a*.
in strong fields, (9) 251*g*.
measuring apparatus, P (1) 24*g*.

Temperature (*continued*)
measuring cell, reducing thermal variation in, P (10) 287*c*.
melting, incongruent, of Y Fe garnet, effect of O pressure, (7) 199*f*.
melting-point, discrepancy in conversion of, (9) 255*i*.
profile curve, in controlling deposition of crystalline materials from solution on seed, P (11) 320*a*.
reference block, P (4) 108*c*.
regulator, for chromatographs, P (3) 90*a*.
sensors, bonded-wire, (9) 250*h*.
for high pressure apparatus, P (4) 108*a*.
solid differential expansion, P (3) 81*f*.
softening, for system Be-B in Be-rich range, (5) 142*e*.
surface, of thin sheets and filaments, (2) 52*h*.
transition, of copper ferrite, (6) 175*j*.
variations, in tunnel kiln, device for localizing at predetermined points, P (1) 24*h*.
Tempering, of glass. See *Glass*.
Tephroite, from New Jersey, (4) 110*i*.
Terbium, as activator in CaF_2 optical maser, P (6) 166*g*.
Terminology. See *Nomenclature*.
Terra cotta. See *Art and artware*.
Terra sigillata, slips, preparation and firing, (7) 178*a*.
Testing. See also *Analysis* and specific types.
of brittle materials, by ultrasonics, (7) 195*j*.
of clays. See *Clays*.
of concrete. See *Concrete*.
cupric sulfate, for color retention, (9) 238*b*.
equipment, yield strength computer for, P (5) 139*g*.
of ferromagnetic cores, machines for, P (2) 49*e*.
fire, ASTM standard for, B (9) 259*b*.
material, polarization interferometric methods in incident-light microscopy for, (11) 313*b*.
of metals, ASTM standards for, B (9) 259*a*.
methods, for ceramics and refractory clays, (10) 286*d*.
nondestructive, by sonics, for casting quality, (10) 269*h*.
preliminary, of clay from Philippines, (3) 83*a*.
quality, of Al enameling, (10) 269*b*.
of refractories. See *Refractories*.
specimen identification apparatus, P (3) 89*j*.
stirring, for evaluation of resistance of refractories to corrosion by molten glass, (2) 45*g*.
structural model, compensation for time effect in plastics, (4) 107*i*.
techniques, for determining absorption of fine lightweight aggregate, (10) 266*g*.
tensile, high speed, (3) 80*h*.
thermal and mechanical, of foam alumina and foam zirconia, (8) 215*i*.
torsional, of ceramic materials at high temperatures, (3) 81*h*.
Textiles, ASTM standard for, B (9) 259*b*.
Texture, effect on ultrasonic wave velocities in sandstones, (11) 317*f*.
in hot extruded BeO, (1) 30*d*.
Thallium, halide, glass flakes or fibers as reinforcement, P (6) 157*c*.
ions, response of electrode glass to, (5) 129*e*.
telluride, method of making, P (10) 283*a*.
telluride, semiconductor, method of making, P (10) 283*g*.
Thermal analysis, differential, of Brazilian minerals, I, II, (3) 82*i*.
of clay from Kerala State, (6) 170*c*.
combined with thermal expansion in study of cement raw materials, (7) 180*h*.
correct temperature for expansion/contraction curve, (4) 113*j*.
of cubic modification of $BaTiO_3$, (8) 219*d*.
in determination of forms of gypsum in portland cement, (7) 179*e*.
for determining heats of reaction, methods compared, (6) 167*i*.
in determination of specific heat of glass, (10) 271*g*.
of dye-clay complexes, B (10) 300*a*.
effects of controllable variables, (6) 167*j*.
of gypsum and dehydration products, simultaneous TGA, (11) 302*b*.
high temperature apparatus, P (8) 224*a*.
of Mexican clay, (2) 52*e*.
of pure ZrO_2, (3) 88*c*.
pyrosynthesis as modification of, (4) 107*d*.
of quartz, (2) 56*f*.
of Quetrequile clay deposit, (6) 169*g*.
review of, (5) 142*h*.
Scifax data index, B (2) 62*h*.
in study of activation of CaO-Al_2O_3-SiO_2 slags, (6) 154*g*.
in study of glass systems, I, (9) 239*f*.
in study of reactions between glassmaking materials, III, (1) 5*h*; IV, (10) 269*f*.
with and without vacuum, of olivine, fayalite, and bronzite, (10) 291*f*.
of hard-to-analyze minerals, (5) 144*c*.
of lead borate glasses during crystallization, (7) 185*c*.
Thermal conductivity. See *Conductivity, thermal*.
Thermal decomposition. See *Decomposition*.
Thermal expansion. See *Expansion*.
Thermal properties, of refractories, (8) 215*b,c*.
of serpentine minerals, effect of particle size, (5) 143*c*.
Thermal shock resistance. See *Shock resistance, thermal*.
Thermistors. See *Resistors, electric*.
Thermochemistry. See *Thermodynamics*.
Thermocouples, P (3) 81*h*. See also *Controls; Temperature*.
and accessories, unusual, I, (9) 252*g*.

Thermocouples (*continued*)
bonded-wire, correction for system errors, (9) 250*h*.
bonding of thin film resistance element to refractory support, P (11) 314*a*.
catalyst coated elements, P (4) 108*d*.
compensating devices, reference junctions as, (9) 251*f*.
from composite material, P (1) 24*a*.
composition of elements, P (3) 81*g*.
compound unit, P (1) 24*e*.
construction of, P (4) 108*e*.
effect of thermal neutron irradiation on, (5) 139*a*.
electronegative element in, P (1) 24*b*.
expendable, quick disconnecting means for, P (2) 53*c*.
high-pressure feed through, (2) 53*j*.
high-temperature, P (4) 108*a*.
high-temperature, graphite-Rh, P (6) 168*i*.
with junction formed from boronized metals, P (8) 224*d*.
measuring circuit, P (5) 140*a*.
metal sheathed, (9) 251*i*.
multiple circuit, P (1) 24*c*.
noble metal, thermoelectric instability at high temperatures, (5) 139*h*.
performance in gas streams, (4) 108*a*.
probe, for measuring surface temperature of thin sheets and filaments, (2) 52*h*.
probe, spring-loaded, evaluation under transient temperatures, (2) 52*e*.
protection, thermite refractory material for, (10) 276*f*.
with protective sheath of fluoride of Mg, Sr, Ca, or Ba, P (2) 38*c*.
reference junction, P (9) 253*a*.
surface, for rapidly changing temperatures, (9) 252*a*.
thermoelectric element of, P (2) 50*a*.
unit, construction, P (3) 81*h*.
wave ring, P (11) 314*a*.

Thermodynamics, of activities in molten mixtures of reciprocal salt systems, (10) 297*d*.
of anhydrous and hydrated cement minerals, (7) 182*i*.
calculations, on phase equilibria involving fused salts, I, II, (2) 59*j*.
of ceramic materials at high temperatures, (9) 257*c*.
of crystal structure transformation of anatase to rutile, (11) 318*b*.
equilibrium, in NiO, (3) 76*g*.
of ferromagnetic phase formation in $MnAl_2$, (8) 220*c*.
of frost damage to porous solids, (8) 212*b*.
functions, of Fe disulfide, Fe diselenide, and Ni diselenide from 5° to 350°K, (1) 27*j*.
index of selected property values, B (4) 122*h*.
in molten salt systems, (10) 295*b*.
of monoclinic-tetragonal transition of zirconia, (2) 56*i*.
properties, of gaseous alkali halides, (1) 30*j*.
of transition metal carbides, (6) 175*i*.
of zinc ferrites, (10) 294*f*.
of solid-phase reactions in system CaO-Al_2O_3, (4) 121*a*.
of solids, B (4) 124*c*.
theory, of "weak" ferromagnetism of antiferromagnetics, (11) 310*g*.
of vaporization of NiO, (3) 89*j*.

Thermoelectricity, of Cd oxide, (8) 219*g*.
device, P (2) 50*a*; P (8) 221*c*.
instability, of noble metal thermocouples at high temperatures, (5) 139*h*.
thermoelectric body, composition, P (10) 283*h*.
thermoelectric couple, of BP, P (6) 166*h*.
thermoelectric device, P (7) 194*e,f*.

Thermoelectric materials, ceramic, P (5) 137*c*.
composition, P (5) 137*g*.
and devices, P (3) 79*b*; P (5) 137*e*.
and devices, flexible high temperature, P (3) 81*d*.
devices and thermoelements, P (1) 24*b*.
elements, P (7) 194*c*; P (8) 220*i*.
encapsulated elements, P (2) 48*h*.
PbTe-SnTe, P (5) 136*h*.
P-type, P (2) 50*b*.
of pseudobinary alloy of Sb_2Te_3 and Ag_2Te, P (5) 137*f*.
radiation compensating device, P (1) 24*e*.
as semiconductor element, P (5) 137*e*.
uranium compounds as, (10) 282*a*.

Thermography, introduction to, B (5) 151*b*.

Thermogravimetry, of defect structure of TiO_2, (8) 230*a*.
in determining small amounts of water in solids, (6) 168*b*.
of gypsum and dehydration products, simultaneous DTA, (11) 302*b*.
simultaneous with dynamic differential calorimetry, (8) 228*f*.
in study of reactions between glassmaking materials, III, (1) 5*h*; IV, (10) 269*j*.

Thermometers, design problems for high temperatures, (7) 185*b*.
dial, with external calibration, P (10) 287*f*.
with emitter-collector path of transistor, P (5) 140*a*.
geologic, use of nepheline as, (11) 314*i*.
manual operations in production of, (1) 7*f*.
manufacture, P (10) 273*a*.
method of making and calibrating, P (3) 70*f*.
Pt resistance, design and use, B (2) 62*c*.
pulsed resistance, P (5) 139*j*.
remote reading, P (5) 131*h*.
resistance, direct reading, P (8) 223*f*.
effect of thermal neutron irradiation on, (5) 139*a*.
probe, P (5) 140*a*.

Thermometers, resistance (*continued*)
probe type, P (3) 81*f*.
with semiconductor diode, P (9) 253*a*.
semiconductor resistance, for measurement of low temperatures, (10) 281*a*.

Thermophysical properties, constants, determination at high temperatures, (8) 223*j*.
high-temperature, of UC, (8) 228*e*.

Thermostats, hydraulic, protector for, P (1) 25*a*.

Theses, Master and Doctor, in ceramics, for year ending August 1962, (3) 93.

Thickness, of coatings, measurement, P (3) 77*f*.
control, for flat products, P (6) 167*g*.
of deposit, apparatus for measuring, P (2) 53*b*.
epitaxial layer, growing and determining, P (11) 311*e*.
of glass, effect on light transmission, (7) 184*e*.
meter, for measuring thickness of rolled glass without direct contact, (5) 129*d*.
optical, of small specimens, means for measuring, P (3) 81*e*.
sonic measuring apparatus, visible indicator for, P (3) 81*i*.
wall, of hollow glasses, determination, (1) 6*h*.

Thin sections. See *Microscopy*.

Thixotropy, of clays, and rheological parameters, (3) 83*g*.
definition and characterization, (3) 89*a*.

Thoria. See *Thorium, oxide*.

Thorium, carbide, hydrolysis of, (1) 28*f*.
carbide, in thermionic conversion of heat into electrical energy, (10) 279*g*.
dioxide, calculation of cohesive and surface energies, (3) 85*i*.
fluoride, systems. See *Systems*.
monocarbide, and Th dihydride, ternary compounds between, (7) 201*b*.
monosulfide, preparation and properties, (6) 160*d*.
oxide, recovery, P (10) 290*d*.
slurries, catalytic recombination of radiolytic gases in, P (1) 15*i*.
sols, stable silica-clad, P (10) 278*a*.
technology of, (8) 215*f*.
and thoria gels, sintering equipment for, (8) 227*i*.
-urania, metal-fiber-reinforced, irradiation of, (7) 188*d*.
powders, and oxide, properties of, (6) 175*b*.
systems. See *Systems*.

Tile. See also *Pipe*.
architectural, Hufnagel's work, (7) 178*a*.
bell and spigot, tapered joint for, P (5) 132*c*.
building, light transmitting, P (9) 242*c*.
ceramic, interlocking elements, P (2) 45*j*.
pressing defects in, (9) 245*j*.
technical and economic importance, (8) 217*f*.
clay, of ancient Paterna, (9) 236*f*.
drain, ASTM standard for, B (9) 259*b*.
Cu in to prohibit root growth, (11) 305*f*.
simultaneous production of 4- and 6-in. from same die, (9) 243*a*.
enameled glass facing, manufacture of, (1) 7*j*.
engineering design, B (10) 298*h*.
face, Russian production techniques, (7) 190*c*.
factories, German, (10) 273*f*.
floor and wall, cracking and chipping from temperature changes, (7) 190*g*.
floor and wall, practice recommendations, (4) 103*f*.
glazed, bonding to glass-fiber backing, (7) 190*g*.
machines, upender mechanism for, P (1) 13*c*.
with masked adhesive on backs and edges, P (8) 218*c*.
measuring machine, P (11) 312*f*.
mosaic, colored, electrophoretic dewatering of slips for, (7) 194*h*.
mosaic, mechanized production, (1) 18*g*.
panels, apparatus and method for making, P (4) 104*d*.
plant, automation in, (3) 75*e*.
expansion program, (1) 17*j*.
warehouse for, (6) 159*a*.
production, increasing, (7) 190*f*.
punching apparatus, P (2) 44*b*.
radiation gas drying, (7) 196*e*.
roof, or wall, interlocking, P (2) 46*g*.
roofing, clay used for, (3) 71*a*.
saturated, panel test for frost resistance, (3) 71*i*.
sheet-metal ring for, P (2) 44*c*.
slips, equipment for continuous dewatering, (7) 194*h*.
stoneware, flaw detection by ultrasonics, (7) 195*j*.
stoneware, uniformity of pressing, B (10) 300*a*.
wafer-thin, electronic circuits printed on, (2) 47*h*.
wall, adhesion of mortar to, (3) 75*d*.
bodies, glazes, and processes, I, II, (6) 163*c*.
ceramic vs. plastic, (9) 245*h*.
single-fired, cracking from cristobalite in intermediate layer, (3) 75*e*.
steam pressure hardened, (9) 245*j*.
wollastonite body for, (6) 163*d*.

Time, decrease, of magnetic permeability in mixed ferrites, (11) 310*h*.
effect on gypsum transformation, (6) 154*f*.

Tin, as activator for Ca silicate phosphor, P (3) 79*c*.
difluorides, chemistry of, (1) 26*i*.
in glazes, defects, (4) 103*g*.
grain growth during selective recrystallization, effect of impurities, B (9) 262*g*.
molten, as mold for float glass, (5) 129*j*.
oxide, conducting films, optical properties of, (6) 175*g*.
films, optical and electrical properties, (6) 174*e*.
films, as resistors, (10) 279*i*.

Tin, oxide (*continued*)
fused crystals, emission spectrographic analysis of, (1) 27*f*.
refinement of crystal-structure determination, (10) 296*h*.
thermal-expansion anisotropy of, (1) 30*g*.
selenide, systems. See *Systems*.
telluride, systems. See *Systems*.
telluride, in thermoelectric devices, P (5) 136*h*.
tellurites, composition, P (1) 22*b*.
tellurites, method of making, P (1) 21*j*.

Titanates. See also *Dielectrics* and specific types.
applications and properties, (9) 258*b*.
Ba-Sr, in low-loss rapid switch for microwave energy, (7) 191*j*.
Bi-Sr, dielectric properties of, (9) 247*i*.
Ca, Sr, and Bi, in capacitors, P (4) 105*b*.
ceramic, enclosed by thin metal sheet coating, P (1) 20*j*.
laminated batt for firing without contamination, (10) 276*c*.
Pb-Sr, in ferroelectric bolometer, (6) 164*h*.
-lead-zirconate, compositions, preparation of, I, II, (1) 19*d*.
lead-zirconate-, modified, hot-pressing of, (4) 104*g*.
pure, preparation, P (3) 78*e*.
structures, relation to perovskite, ferroelectricity in, (11) 317*b*.

Titania. See also *Rutile; Titanium, dioxide*.
as base for enamel frits, P (2) 38*a*.
ceramics, dielectric properties at microwave frequencies, (10) 280*e*.
distribution of pressure and density in pressed bodies, (1) 19*g*.
effect on properties of glasses of system K_2O-PbO-SiO_2-TiO_2, relation to structure, (5) 129*f*.
fibers, crystalline, P (3) 69*f*.
impurities in, determination, (5) 138*i*.
ores and slags, cyclic beneficiation using $(NH_4)_2SO_4$, P (2) 55*g*.
porous, preparation and surface properties, (1) 29*g*.
refinement of crystal structure, (4) 120*d*.
refinement of crystal-structure determination, (10) 296*h*.
systems. See *Systems*.

Titanium, -activated, calcium germanate, P (2) 50*d*.
as activator in Ba pyrophosphate phosphor, P (3) 78*h*.
boride, as base for metalloceramic hard alloy, (4) 118*c*.
boride, production of, P (10) 277*g*.
carbide. See also *Cermets*.
Ferro-, composites, (6) 159*i*.
in graphite article, (3) 74*i*.
in iron and steel, electron microscope study of, (6) 155*j*.
reactions of H_2 with, (8) 214*d*.
thermal conductivity of, (7) 189*d*.
chloride, systems. See *Systems*.
compounds, production, P (3) 85*a*.
diboride, as addition to WC, (8) 212*i*.
pyrolytic synthesis of, (11) 306*e*.
study by metallographic procedures, (8) 228*i*.
dioxide. See also *Rutile; Titania*.
ceramics, conducting layers on, P (2) 48*e*.
manufacture of, P (3) 84*a,c*; P (10) 290*c*.
nacreous material from, P (4) 111*d*.
pigment, and compositions containing, P (3) 85*b*.
pigment, method of preparing, P (4) 111*b,c,d*; P (6) 171*b*.
pigment, plant layout and manufacture, (10) 288*d*.
pigment, treatment, P (8) 226*b*.
pigment, two-stage acid process for making, P (9) 254*b*.
preparation of, P (10) 289*i*.
purification by high-voltage electrodialysis, (7) 197*j*.
single crystals, stress-strain behavior, (7) 200*g*.
transition rate, instrument for measuring, (2) 52*h*.
treatment with B compound, P (8) 226*a*.
with 0.5 to 5% Al_2O_3, P (5) 141*d*.
dispersion-hardened alloys, P (4) 103*a*.
dual role in system K_2O-SiO_2-TiO_2, (9) 255*j*.
effect on glass color, (8) 208*h*.
effect on silicate glass properties, (2) 38*j*.
excess, effect on electrical properties of $BaTiO_3$, (10) 281*b*.
in glass, effect on color, (11) 303*f*.
insert, for bonding metal to ceramic, P (2) 38*g*.
lubricants for hot-working of, P (3) 65*f*.
monoxide or carbide, method of making, P (6) 162*h*.
nitride, microstructure of X-ray K-absorption spectra of metal in range of homogeneity of, (2) 58*c*.
synthesis from TiH_2 powder and N or ammonia, (5) 146*i*.
transport by HCl in Mo tube, (6) 172*d*.
ores, decomposition of, P (5) 141*k*.
organic compounds, in production of capacitor of TiO_2 film, (8) 218*f*.
oxide, -Al_2O_3, solid solution, (3) 85*i*.
Sb-doped, as capacitor, (9) 246*h*.
measurement of sublimation in, (10) 281*g*.
oxidized films, current-controlled negative resistance in, (10) 280*b*.
in presence of iron-malonate complexes of Ti, polarographic determination, (11) 313*c*.
reactions with ZrO_2 at high temperatures, (9) 256*i*.
source materials, caustic beneficiation, P (4) 110*e*.
systems. See *Systems*.

Titanium (*continued*)
tellurite, composition, P (1) 22*b*.
tellurite, method of making, P (1) 21*j*.
(III), hydrolysis of, (1) 28*g*.
titaniferous material, pressure leaching of, P (3) 84*k*.
Titanomaghemite, in igneous rocks, (4) 110*y*.
Titration. See also *Analysis*.
of clays, formation of double hydroxides in, (10) 293*a*.
complexometric, of alumina, (1) 28*g*.
in determination of V in chromite, (1) 31*a*.
Karl Fischer, in determining small amounts of water in solids, (6) 168*b*.
Tobermorite, formation at room temperature, effect of KOH solution, (4) 114*f*.
gel, use in concrete, (11) 302*e*.
as product of system CaO-SiO_2 gel-H_2O at 110°C, (4) 119*i*.
Tools, ceramic, machinability study, X, (1) 1*f*.
ceramic, wear resistant, in making ceramic shapes, (6) 167*e*.
cutting. See also *Abrasives*.
with abrasive and metal particles, P (5) 125*g*.
acoustically vibrated, P (5) 138*f*.
cermet, ultra-high-speed, (8) 203*f*.
diamond, P (10) 265*f*; P (11) 301*g*.
diamond, with edge thickness of 0.001 to 0.01μ, P (3) 81*c*.
in glass industry, standardization of, (5) 129*j*.
for metals and alloys, Al_2O_3-C compositions for, P (2) 33*g*.
pneumatic abrasive, P (1) 23*e*.
with Ni-coated W carbide on ferrous metal surface, P (1) 2*a*.
with preformed abrasive members, P (1) 1*g*.
for tile pipe, P (1) 13*c*.
wires, for semiplastic bodies, P (8) 221*e*.
diamond, production of, P (11) 301*f*.
diamond engraving, electromagnetically pulsed, for decorating glass and ceramics, P (10) 272*d*.
grinding. See *Grinding and polishing apparatus*.
machine, magnetic abrasive wheels for use in, P (9) 236*c*.
orientation of diamonds for, (9) 235*j*.
for slicing semihardened materials, P (2) 51*h*.
Toughness, test, for abrasive particles, (3) 63*h*.
Trade, foreign, in ceramic products, (1) 31*e*.
international, review of, (1) 31*g*.
Transactions, of ceramic congress, 8th international 1962, B (10) 300*a*.
Transducers, Al_2O_3 and Mo as, P (11) 311*g*.
cellular ceramic electromechanical, P (1) 21*b*.
ceramic, P (2) 48*d*.
circuit element, P (9) 248*g*.
composite, technique for making, (6) 164*d*.
electromechanical, P (2) 48*g*.
ferrites as, P (3) 77*a*.
ferrites, in butt joint for unweldable vibratory bodies, P (10) 282*c*.
for high acoustical-mechanical energy transfer to liquids, P (5) 137*h*.
multiple thermocouple junction, for measuring temperature in strong fields, (9) 251*g*.
piezoelectric, P (5) 136*i*.
ceramic binders for metallizing, P (6) 166*d*.
electromechanical, P (9) 249*d*.
pressure, (6) 165*a*.
piezoresistive, P (8) 220*h*.
pressure, strain-gage, (7) 195*f*.
radially vibratile, P (2) 50*a*.
rare earth pressure, (6) 165*f*.
Transfers. See *Decoration*.
Transformers, anisotropy, (9) 246*g*.
Transistors, alloyed, method and apparatus for making, P (5) 136*d*.
crystal growth method of making, P (3) 78*b*.
discovery of, (9) 247*h*.
hermetic ceramic, ultrasonic sealing of, (3) 76*j*.
heterojunction, method of making, P (2) 49*c*.
indium antimonide, P (11) 311*h*.
leads, as hermetic seals, (2) 48*c*.
mesa, high-speed servo positioner for bonding, (7) 191*a*.
method of making, P (5) 136*g*.
thin-film, CdS TFT, (2) 48*b*.
unipolar monocrystal, P (5) 137*e*.
Transmission, of glasses of various thickness, calculation, (7) 184*e*.
infrared, of nonsilicate glass systems, (7) 184*g*.
optical, in ZnS single crystals, (4) 117*e*.
Transmittance, spectral, of optical glasses, (5) 129*h*.
Transportation, of brick, by rail, method and container, P (2) 44*d*.
of brick, use of flatcars, (8) 230*i*.
bulk, of cement, reduction of pack set in, P (9) 237*c*.
container, for curved glass, P (3) 70*e*.
of granular materials, with reciprocating blade, P (3) 80*b*.
inflatable dunnage in, (8) 230*h*.
of minerals in mines and quarries, P (2) 55*j*.
Trapping, levels, in crystal phosphors, exoelectron emission study of, (5) 134*h*.
Tricalcium silicate. See *Calcium*.
Tridymite, low form, in opal of New Mex., (6) 170*d*.
Trona, crude, soda ash from, P (7) 198*a*.
Tubes, cathode-ray, bonding of glass parts of, P (3) 69*d*.
envelope, P (4) 99*j*.
improvement in, (6) 156*i*.
red luminescent material for, P (1) 21*f*.
resistive semiconductive internal coating for, (2) 48*j*.
screen structure for, P (2) 42*c*.
with silica coated phosphor screen, P (11) 311*b*.
ceramic-metal, receiving, Nuvistor family, (2) 48*j*.

Tubes (*continued*)
ceramic sheathing, continuous manufacture, P (10) 285*g*.
electron, ambient insensitive, methods of making, (10) 282*e*.
cathodes for, P (4) 105*a*.
high power, P (1) 21*c*.
materials, ASTM standard for, B (9) 259*a*.
point contact, using single-crystal reduced rutile, (10) 281*f*.
I, properties of ceramic parts in, (11) 310*b*.
rutile, field emission in, (10) 280*b*.
semiconductor point contact, negative resistance in forward direction, (8) 219*d*.
thin film TiO_2, compound barriers in, (7) 191*c*.
tunnel, P (4) 106*c*.
tunnel, of semiconductor crystal, P (8) 220*g*.
electronic, calculation of temperature distribution in, (9) 251*b*.
electronic, negative-resistance device, (7) 192*f*.
Esaki or tunnel diode, formation by vapor deposition, P (11) 311*d*.
fluorescent lamp, coating with amorphous silica and phosphor, P (10) 272*d*.
glass, flame sealing of, P (6) 158*e*.
in light gas detector, P (11) 304*j*.
partially automatic equipment for producing, (1) 8*e*.
preform, method for shaping, P (9) 242*g*.
microwave, high-power, window materials for, (10) 282*b*.
miniature, metal-ceramic, (2) 48*g*.
receiving, development and operation, (8) 218*h*.
storage, storage target for, P (8) 221*b*.
storage, two-color, (9) 248*d*.
television, color picture, luminescent screen for, P (6) 166*e*.
manufacture of, (1) 7*f*.
picture, film covering for, P (2) 42*e*.
television camera, P (3) 70*e*.
U and SiC, collapse under reactor coolant pressure, (10) 274*c*.
viscoelastic flow through, dimensionless groups in, (10) 291*i*.
Tungstates, of divalent metal ions, single crystals, preparation, (11) 318*a*.
Tungsten, (B), oxide, magnetic, with ordered perovskite structure, (7) 191*h*.
boride, as base for metalloceramic hard alloy, (4) 118*c*.
boride, production of, P (10) 277*g*.
bronze, electric resistivity of, (3) 86*c*.
carbide, grit, as work surface of abrasive article, P (9) 236*e*.
particles, application to workpiece surface, P (1) 2*a*.
with TiB_2 additions, (8) 212*i*.
monocarbide, anisotropy of elastic properties, (2) 56*d*.
nitrides, preparation and properties, (4) 118*j*.
oxide, Cr-, crystalline, P (4) 10*3j*.
oxides, compounds formed with Y oxides, (7) 201*g*.
powder, carburization by carburizing gases, II, (6) 171*g*.
properties, constitution, and fabrication, B (7) 202*c*.
in thermal protection of rocket-motor structures, (10) 276*e*.
WO_3, Cu-doped, carrier characterisitics in, (1) 26*i*.
formation and reduction of, I, II, (4) 120*h*.
monoclinic, crystal structure at room temperature, (6) 172*g*.
single crystal, temperature dependence of optical absorption edge of, (5) 146*f*.
Turbines, blades. See also *Aircraft ceramics*.
blades, structural composite material for, P (10) 277*j*.
jet, ceramic coating for buckets, P (4) 97*h*.
Tuyeres. See *Refractories*.
Twinning, of crystals. See *Crystals*.

Ultrasonics. See *Sonics*.
Urania. See *Uranium, oxide*.
Uranium, carbide, effect of irradiation on electrical resistivity, (11) 308*d*.
in nuclear fuel, P (9) 245*e*.
in nuclear reactor fuel elements, (10) 274*b*.
synthesis of, (5) 146*a*.
systems. See *Systems*.
ceramics, irradiation effects in, (11) 307*f*.
compounds, as possible nuclear fuels, (10) 275*a*.
compounds, as thermoelectric materials, (10) 282*a*.
dioxide, calculation of cohesive and surface energies, (3) 85*i*.
chemical polishing baths for, (11) 312*j*.
Cr-coated, in Zircaloy matrix as dispersion element, P (8) 215*j*.
crystal habit of, (1) 27*d*.
effect of stoichiometry on rate of grain growth, (10) 294*b*.
in fuel assay reactor, P (4) 102*i*.
fuel elements, manufacture by vibration and swaging, (10) 275*g*.
grain growth of, (10) 293*i*.
high temperature substoichiometry in, (1) 28*d*.
kinetics of hydrofluorination, (10) 294*d*.
low-temperature sintering of, (5) 132*j*.
measurement of particle size distribution by radioactivation, (6) 173*f*.
melting point in He atmosphere, (9) 243*g*.
metallographic technique for, (11) 306*d*.
Mo-coated particles, sintering studies on, (11) 306*g*.
morphological properties, (7) 201*b*.

Uranium, dioxide (*continued*)
particles, formation of fission-gas bubbles in, (11) 307*h*.
particles, irradiated alumina-coated, dispersed in graphite spheres, (8) 213*j*.
physical properties and oxidation states, (8) 215*a*.
Pu and fission product migration in, (4) 101*c*.
single crystals, transmission electron microscopy of, (10) 286*g*.
sinterable, preparation of, (5) 140*i*.
sintered, BeO-containing, physical properties of, (10) 275*c*.
sintering of, P (8) 216*h*.
spherical particles, P (8) 216*j*.
steam sintering of, (1) 15*j*.
dispersion, of UO_2 in, P (5) 133*e*.
in dispersion-type materials, (10) 275*f*.
-doped CaF_2, as laser material, (7) 192*i*.
(V), oxides, I, (1) 30*c*.
fluoride, systems. See *Systems*.
glasses, infrared spectra of, (9) 239*i*.
granular material, preparation with uniform particle size, P (10) 277*e*.
hexavalent and pentavalent, compounds with ordered perovskite structure, (7) 198*g*.
incorporation in discrete areas in Be or Zr matrix, P (10) 277*b*.
metal, and UO_2 fuel pins, irradiation of, (10) 274*g*.
metallurgy, Vols. I, II, B (4) 124*i*.
molten, Ta borides for containing, (11) 308*i*.
monocarbide, compressive creep and physica properties, (11) 307*b*.
and dicarbide, hydrolysis properties of, (10) 293*j*.
for fuel elements, (10) 275*f*.
high-temperature thermophysical properties of, (8) 228*e*.
hydrolysis between 25° and 100°, (1) 28*h*.
irradiation behavior of, (11) 307*i*.
irradiation damage in, (11) 307*c*.
oxidation of, (10) 296*c*.
properties of, (11) 307*j*.
monosulfides, preparation and properties, (6) 160*d*.
nitride, in ductile Cr, P (5) 133*g*.
nitride, systems. See *Systems*.
ores, sorting according to radioactivity, P (5) 141*d*.
oxide, ceramic dispersion of BeO with, (10) 298*b*.
ceramics, crystal chemistry of, I, II, (10) 279*j*.
effect of grain growth control during sintering, (11) 307*d*.
effect of small additions of yttria at 940°C, (1) 27*d*.
fuel, fluorination of, P (10) 289*i*.
fuel particles, ZrC coated, (11) 308*a*.
high density sintered, P (3) 74*e*.
high density stoichiometric, P (10) 277*i*.
in high-melting point glasses, (11) 308*f*.
high pressure fluorination, (7) 199*d*.
low sulfate, P (11) 315*e*.
microstructural changes from irradiation and high temperature gradients, (11) 307*g*.
neutron-irradiated, release of stored energy from, (1) 29*c*.
-paraffin wax mixtures, enriched, processing of, (1) 29*i*.
pure, P (4) 111*g*.
recovery, P (10) 290*d*.
single crystals, preparation by sublimation, (1) 29*h*.
sintered, preparation of, (7) 188*h*.
sintered, study of fracture surfaces, (11) 306*i*.
sintering of, (10) 276*i*.
slip-cast ceramics, fabrication of, (11) 307*c*.
systems. See *Systems*.
technology of, (8) 215*f*.
ThO_2-, metal-fiber-reinforced, irradiation of, (7) 188*d*.
particles in fused UO_2, optical and electron microscopic study of, (1) 28*i*.
phosphate, systems. See *Systems*.
pyrophosphate, thermal expansion of, (5) 132*h*.
red and yellow glazes from, (7) 178*a*.
refractory compounds, synthesis and fabrication of, (9) 257*h*.
in semiconductors, emf developed during irradiation in reactor, (10) 280*g*.
smelting, CaF_2 slip-cast crucibles for, (10) 275*b*.
trioxide, chemical reactivity of, I, (10) 290*i*.
hydrated, infrared spectra and structures of, (9) 256*a*.
low-surface area, hydrogen reduction of, (10) 293*f*.
tube, collapse under reactor coolant pressure, (10) 274*c*.
UC-PuC solid solutions, preparation of, (9) 256*h*.
UO_2, in glasses in silicate and phosphate systems, (1) 10*e*.
U_3O_8, twinning, slip, and cleavage in, (1) 31*a*.
-Zr, alloys, process for dissolving, P (1) 17*e*,*f*.

Vacuum, apparatus, sorption of water vapor on glass surface in, (8) 209*d*.
deposition, of pinhole-free films of insulators, semiconductors, and conductors, (11) 311*f*.
electrical breakdown in, effect of glass contamination and electrode curvature, (10) 280*h*.
equipment, for dust removal, (5) 138*d*.
high-, technique, materials for, Vol. III, B (2) 61*d*.
impact crushing in, economy of, (1) 22*e*.
measurement, by ionization, (7) 196*d*.
techniques, (6) 168*f*.
techniques, glass and ceramics in, B (2) 61*b*.
treatment, of ceramic powders during pressing, (4) 106*g*.
ultrahigh, high sensitivity microbalance for use in, (10) 286*c*.

Vacuum (*continued*)
ultrahigh, portable system for lab experiments, (2) 52*f*.
volatilization of high temperature materials in, (3) 89*g*.
Vanadates, containing alkali and alkaline earth metals, polymorphism of, (4) 118*j*.
Vanadium, -base alloys, high-temperature oxidation protective coatings for, (9) 238*h*.
-base alloys, high-temperature oxidation-resistant coatings, (8) 207*i*.
boride, production of, P (10) 277*g*.
in chromite, titrimetric determination, (1) 31*a*.
compounds, effect on silica refractories, (8) 213*g*.
oxide, as corrosive of fuel oil ash, (8) 213*e*.
effect on viscosity of vitreous silica, (2) 40*g*.
refinement of crystal structure, (4) 120*d*.
pentoxide, crystal structure of, (4) 113*g*.
pentoxide, high purity, from oxidic V materials, P (8) 225*h*.
Vaporization, of NiO, thermodynamics of, (3) 89*j*.
of rare earth oxides, (2) 59*h*.
of refractory materials, (7) 189*e*.
Vapors, alkali metal, determination of glass resistance to, P (2) 38*a*.
deposition, of carbide coatings to graphite, (10) 268*h*.
chemical, in molecular engineering, (10) 284*b*.
glasses formed by, B (11) 320*g*.
in making multiple layer condensers, P (10) 283*h*.
of metals from iodide compounds, (8) 206*i*, *j*.
flowmeters for, (7) 195*d*.
growth of ice crystals from, B (9) 262*d*.
multicomponent, chromatographic analysis of, P (4) 121*j*.
pressure, of PuO_2, B (8) 231*h*.
vermiculite in absorption of, (2) 54*h*.
water, isothermal transfer, (11) 320*b*.
Vegard's law, comment on, (7) 198*e*.
and system alumina-chromia, comment on, (3) 86*b*.
Vermiculite, in absorption of gases, vapors, and fumes, (2) 54*h*.
apparatus for exfoliating, P (4) 110*c*.
commercial, mineralogy of, (11) 314*h*.
concentration, P (5) 141*h*.
exfoliation of, P (3) 84*c*.
expanded, in cement coating for exterior surfaces, P (9) 237*d*.
Indian, evaluation for insulating material, (11) 319*i*.
in insulating refractory shapes, (10) 276*h*.
Veszpremite, conversion to mullite, (10) 295*d*.
proposed name for supermetafluorkaolinite, (10) 292*g*.
Vibration, effect on properties of pressure cast fused silica, (8) 213*i*.
excited in porcelain, damping of, relation to stressed state, (4) 120*c*.
handbook, Vols. I–III, B (5) 151*c*.
ultrasonic, in cold pressing ceramic pellets, (8) 221*d*.
Vibrators, cylindrical piezoelectric ceramic, forming of powder mixtures for, (1) 19*g*.
dual eccentric weight, for circular feeder, P (1) 23*g*.
Viscometers, P (1) 24*d*; P (3) 80*b*.
cone-and-plate, behavior of Bingham fluid in, (10) 278*c*.
counterbalanced sphere, for use to 1750°C, (11) 313*d*.
manual force, (9) 251*f*.
manual time-measuring, (4) 107*j*.
rotating cylinder, in measurement of properties of enamel slips, (8) 207*f*.
rotational, concentric cylinder method, (6) 168*i*.
types, (2) 52*j*.
Viscosity, of B and B-free enamels, effect of iron oxide, (1) 4*b*.
of ceramic suspensions, measurement by capillary viscosimeters, (6) 168*a*.
dynamic and kinematic, terminology and equations, (2) 52*j*.
of glass. See *Glass*.
measurement, B (10) 300*e*.
at normal melting point, extension of Andrade equation for, (1) 27*g*.
of semicoke, (7) 196*i*.
of slurry, measurement in systems cement-water and asbestos-cement-water, (8) 205*g*.
of vitreous materials, increase by addition of dispersions of refractory materials, (8) 214*c*.
Vitreous state, modern aspects of, Vol. 2, B (9) 263*h*.
Vitrification, of electrical porcelain body, (11) 309*e*.
mechanical and structural, (5) 130*h*.
Volatilization, of constituents from borosilicate glass at high temperatures, (2) 41*j*.
of constituents from borosilicate glass at high temperatures, correction, (8) 209*j*.
of fluorine crown glasses, (1) 10*a*.
of high temperature materials in vacuo, (3) 89*g*.
Volcanic glass, artificial crystallization to carnegieite, nepheline, and albite, (11) 315*j*.
Volume, acoustical measurement of, P (5) 130*i*.
change, of cement paste during hydration, (7) 182*d*.
measurements, of solids, pressure-differential apparatus for, P (8) 224*a*.
of solid material, apparatus and method for measuring, P (3) 81*a*.

Walls, curtain, construction, P (2) 37*j*.
Warpage, of steel stove parts, reduction by low-temperature porcelain enameling, (11) 302*h*.
Washing, of limestone, (10) 289*d*.
Water. See also *Humidity; Moisture; Steam*.
absorptiometric determination of Si in, III, (10) 285*i*.
Water (*continued*)
absorption, of ceramic products, test for, (9) 252*e*.
action on calcite, magnesite, and dolomite, (6) 169*f*.
adsorption, on quartz, reversible isotherms of, (1) 29*d*.
in brick, freezing behavior, (3) 71*e*.
content, effect on electric conduction mechanism in lead silicate glasses, (3) 67*h*.
curing, effect on mortar strength, (8) 204*d*.
fluoridation of, P (3) 80*c*.
hardness, effect on consistency of enamel slip, (8) 206*h*.
hot, decomposition of microcline, albite, and nepheline in, (5) 142*a*.
industrial, ASTM standard for, B (9) 259*c*.
loss, control, of pumpable aqueous cement slurries, P (10) 268*e*.
movement, in porous materials, I, (11) 320*b*.
reaction with glass, I, II, (2) 40*a*.
removal, continuous, from tile slips, (7) 194*h*.
removal, electrophoretic, from slips for colored mosaic tile bodies, (7) 194*h*.
removal of silicates from by porous MgO sorbent, P (3) 84*g*.
repellent, shaped glass parts, P (6) 157*d*.
role in ceramics, (1) 25*g*.
sea, electrolytic removal of $Mg(OH)_2$, P (7) 197*j*.
sea, making potable water and $MgCl_2$ from, P (2) 55*a*.
in silica glass, (8) 210*a*.
Si in, absorptiometric determination, I, II, (9) 250*g*.
solubility, in silicate melts, determination, (5) 144*f*.
systems. See *Systems*.
vapor, adsorption on porous glass fiber, (10) 270*g*.
sorption on glass surface in vacuum apparatus, (8) 209*d*.
tritiated, diffusion in silica glass after reaction with, (10) 270*c*.
in vitreous silica, I, II, (3) 68*i*.
Water glass. See *Sodium, silicate*.
Waterproofing, of sand-cement plaster of buildings and roofs, (9) 243*a*.
Wax, polishes, ASTM standard for, B (9) 259*c*.
Wear, of abrasives, factors affecting, (5) 125*f*.
of blast-furnace brickwork, measurement with radioactive isotope, I, II, (6) 159*j*.
effect of surface finish on, (3) 90*g*.
mechanism, in nonmetallic materials, (8) 228*c*.
-resistant materials and coatings, (6) 155*c*.
Weathering. See also *Frost resistance*.
artificial, of aluminous cement mortar, relation to natural aging, (11) 302*c*.
differential, of volcanic ash and pumice, in formation of halloysite, (6) 169*i*.
Weighing. See also *Balances; Thermogravimetry*.
apparatus, for cement clinker, P (9) 238*a*.
apparatus, for determining molecular weight, P (8) 230*c*.
automatic, in metallurgy batch preparation, (8) 225*c*.
automatic, uses of, (7) 195*f*.
of granular materials, gravity actuated apparatus for, P (9) 250*c*.
systems, electronic continuous belt, for accurate weights, (10) 284*a*.
Weight, changes, in samples as function of temperature, apparatus for measuring, P (2) 53*a*.
Welding, electric arc, of carbon surfaces, P (11) 303*c*.
metal arc, composition and process, P (1) 5*c*.
metal arc, magnetic flux-gas shielded, P (10) 269*d*.
rod, coating for, P (7) 183*h*.
submerged-arc, free-peeling composition, P (4) 102*g*.
submerged-melt, composition for, P (11) 303*d*.
submerged-melt, process and composition, P (6) 155*i*.
submerged-melt arc, composition and process, P (5) 128*c*.
Wells, cement for, low-water-loss, P (8) 206*c*.
oil, use of cements in, (7) 182*c*.
oil and gas, cement for, P (6) 154*i*.
Wettability, effect on microstructure and densification, (4) 118*e*.
Wetting, of body for hot forming, Perio-Kontinu process, (3) 79*e*.
nature of, in glass-to-metal bonding, (2) 57*f*.
Whiskers. See *Crystals*.
Whiteware. See also *Art and artware; Bodies, ceramic; Dielectrics; Dinnerware; Faience; Heating elements; Insulators, electrical; Porcelain; Pottery; Tile*.
abrasive products, manufacture of, (1) 1*f*.
apparatus for affixing handles, P (1) 18*e*.
ASTM standard for, B (9) 259*b*.
bodies, crystalline silica in, (11) 309*b*.
bodies, torsional behavior at high temperature, (7) 196*b*.
colored chalk for marking on, P (3) 75*j*.
crockery for schools and hospitals, (4) 103*g*.
filtration in, (3) 79*d*.
flatware, decorating apparatus for, P (2) 47*c*.
Japanese competition, (5) 134*a*.
plant, history and operation, (6) 163*b*.
shaping methods, (7) 190*d*.
support plate, for packed treating tower, P (3) 76*a*.
turning and handling machine, P (5) 134*b*.
ultrafine grinding in, (10) 284*d*.
Windows. See also *Glass*.
materials, for high-power microwave tubes, (10) 282*b*.
Wire, bubble insulated, method of making, P (4) 97*i*.
preparation for wired glass, P (1) 12*a*.
Wollastonite, ceramic bodies, for tile dinnerware, and dielectrics, (6) 163*d*.
Wollastonite (*continued*)
in melted ceramic systems, (2) 47*b*.
synthesis from molten PbO, (9) 257*h*.
Wurtzite, synthesis, (2) 59*e*.

Xenoliths, volcanic, sillimanite and cordierite from, (4) 110*f*.
Xenon, adsorption on graphite, (4) 100*i*.
sorption in high density graphite at high temperatures, (4) 101*g*.
Xonotlite, thermal decomposition of, (5) 147*a*.
X rays, analysis, advances in, Vol. 5, B (2) 60*j*.
apparatus, with comparative detector channels, P (11) 320*c*.
of clay from Kerala State, (6) 170*c*.
continuous sampling for, (5) 142*e*.
and control of cement plant raw mix, I, II, (6) 154*g*.
fluoroscopic, P (5) 140*b*.
spectral, P (5) 148*a*.
apparatus, with diffraction grating, P (4) 121*h*.
apparatus, with stationary optical means and diffraction grating, P (4) 121*g*.
beam intensity responsive sequential spectrometer, P (6) 176*c*.
Benford plate in study of interference figures, (4) 107*c*.
β-ray excited, industrial applications, VIII, IX, P (4) 108*f*.
in ceramics, B (2) 61*j*.
comparator, for analyzing elements of cement, (9) 237*e*.
data, for lead compounds, II, (3) 86*d*.
in determination of quartz in mineral mixtures, (9) 252*c*.
diffraction, analysis, of Al-silicone emissivity coating, (2) 48*h*.
apparatus and use of, P (4) 121*h*.
in determination of minerals in industrial clinkers, (7) 182*e*.
diagrams, indexing of and determination of lattice paramters, (5) 144*g*.
high temperature, using metal ribbon furnaces, (9) 252*c*.
of Fe-Cr spinels, (5) 147*g*.
micrography, of Al_2O_3 single crystals, B (9) 262*b*.
of morphological properties of UO_2, (7) 201*b*.
mull technique of sample preparation, (9) 251*e*.
of phase transformations in SiO_2-Al_2O_3 mixtures, (4) 118*b*.
of phase transformations in SiO_2-Al_2O_3-MgO mixtures, II, (7) 199*d*.
of powders, rapid change rotating sample holder for, (11) 313*f*.
of pure ZrO_2, (3) 88*c*.
in quantitative determination of kaolinite, (4) 107*d*; (6) 168*g*.
in quantitative determination of Na and K in glasses and silicates, (2) 40*i*.
in semiquantitative analysis of chlorites, (6) 168*j*.
of SiC structure types, (5) 147*j*.
study, of Ba borosilicate glass, (6) 156*f*.
in study of corroded ancient glasses, (11) 301*i*.
in study of irradiated BeO, (1) 31*b*.
in study of phase transformations in SiO_2-Al_2O_3-MgO mixtures, I, (6) 174*e*.
study, of portland cement clinker, B (5) 148*g*.
in study of reactions in basic brick, (9) 243*j*.
in study of setting reactions in aluminous cement, (10) 267*a*.
in thermal expansion of CeO_2, (6) 175*h*.
topographical methods, in observation of crystal imperfections, B (9) 261*e*.
diffraction patterns, automatic recording system, P (1) 23*j*.
diffraction patterns, of layer silicates, changes by heating below 550°C, (11) 316*j*.
diffraction system, P (1) 24*d*.
fluorescence, in research on refractory materials, (1) 13*e*.
in identification of clay minerals, B (7) 202*f*.
methods, for determination of lattice constants and density of BeO, (1) 28*b*.
photography. See *Photography*.
powder diffraction, camera attachment, P (6) 176*c*.
data, in determination of crystal structure of BI_3, (1) 27*e*.
data, indexed, for scapolite, (4) 114*f*.
radiography, in study of structure in homogenous sediments, (1) 31*d*.
scattering, by crystals containing defects, (2) 59*g*.
scattering, small angle, by pile-irradiated graphite, B (8) 233*j*.
simplified method for quantitative determination of free SiO in rocks, (9) 251*i*.
small angle scattering by deuteron-irradiated Ge crystal, (7) 200*f*.
spectrometer. See *Spectrometers*.
study, of alkaline earth chromates(V), (4) 111*i*.
of arc-melted and sintered alloys in Hf-O systems, (11) 316*b*.
of autunite, (5) 148*a*.
of barium borate glasses, (7) 185*e*.
of $BaTiO_3$ doped with Sb_2O_3, (6) 165*i*.
of dehydration of hemimorphite, (8) 227*e*.
of distribution of heavy atoms in glass, (10) 271*i*.
of fly ashes, (10) 267*j*.
of glass, (9) 241*d*.
high-temperature, B (2) 60*j*.
of phase transformations in some rare-earth oxide systems, (9) 257*h*.
quantitative, of aluminosilicates, (11) 306*b*.

X rays, study (*continued*)
of quartz-cristobalite transformation, (4) 121*c*.
of Quetrequile clay deposit, (6) 169*g*.
of ZrO_2·2TeO formed by diffusion of Zr and Te in air, (4) 121*e*.
transmission, anomalous, in observation of layer structure of Si crystals, (6) 174*b*.

Young's modulus. See *Elasticity*.
Yttria. See *Yttrium, oxide*.
Yttrium, ferrite, monocrystals with garnet structure, B (9) 263*e*.
manganates, as ferroelectrics, (9) 248*g*.
orthosilicate, formation and physicotechnical properties, (4) 114*g*.
oxide, compounds formed with tungsten oxides, (7) 201*g*.
effect of small additions on U oxides at 940°C, (1) 27*d*.
high purity, (11) 315*d*.
systems. See *Systems*.
and rare earth borates, P (2) 50*f*.
separation from rare earths, P (6) 176*b*.
separation from rare earths by ion exchange, P (2) 60*a*.
trifluoride, liquid density of, (1) 28*d*.

Zeolites, Brazilian, DTA of, (3) 82*j*.
chabazite, mordenite, erionite, and clinoptilolite, cation sieve properties, (4) 112*b*.
crystalline, K-G, method of making, P (3) 84*j*.
method of making, P (4) 111*a*.
S, synthetic, P (2) 55*f*.
synthetic, P (6) 171*e*; P (11) 315*c*.
synthetic, from dehydrated Al silicate, P (3) 85*a*.
sodium, A, P (3) 84*j*.
Sr-selective, characterization of, (7) 198*j*.
synthetic, method for making, P (10) 289*f*.
for selective absorption of Freons, P (6) 171*e*.
type A, refinement of cation positions in, (10) 296*f*.
Zinc, blende, theory of piezoelectric effect in, (2) 59*f*.
chloride, activated with sulfides, as phosphor, (5) 135*h*.
difluoride, crystal structure determination, (10) 296*h*.
ferrite, formation by explosive compression, (11) 310*d*.
ferrites, low temperature heat capacity and thermodynamic properties, (10) 294*f*.
nucleation on glass, (9) 241*c*.

Zinc (*continued*)
oxide, effect of γ-irradiation on adsorbed layers, (10) 293*g*.
in mat glazes for Seger cone 05a, (10) 278*c*.
photoconductive pigment, P (2) 55*d*.
in piezoelectric devices, P (9) 249*d*.
single crystals, electroluminescence of, (5) 134*f*.
single crystals, photoconduction and surface effects, (3) 88*i*.
sintering of, (10) 297*d*.
systems. See *Systems*.
thermoluminescence, characteristics of, (6) 163*h*.
thin elongated single crystals, continuous production process, P (10) 285*c*.
sulfate concentrates, calculation of, P (10) 289*e*.
sulfide, crystal, etch pits on, (5) 143*a*.
crystallization from chloride aqueous solutions, B (9) 263*e*.
cubic, reflection spectrum in interband transition region, (6) 175*f*.
in electroluminescent phosphors, P (5) 137*c*.
infrared fluorescent, activated with V,Ag and V,Cu, absolute efficiency of, (5) 134*d*.
internal photoeffect and exciton diffusion in, (4) 115*a*.
single crystals with cathode barriers, electroluminescence of, (2) 57*d*.
single crystals, optical transmission and photoconductive and photovoltaic effects in, (4) 117*e*.
telluride, method of making, P (3) 84*g*.
Zircon. See also *Refractories*.
fibers, crystalline, P (3) 69*f*.
as opacifier in hard porcelain glazes, (10) 279*c*.
polycrystalline oxides, for fibers for ablation and thermal insulation, (6) 160*c*.
separation from beach sand, P (10) 289*c*.
treatment after fusion by concentrated solar rays, P (3) 75*c*.
washes, for refractories and kiln furniture, to reduce dusting and spalling, (5) 132*j*.
Zirconate, -lead-titanate, compositions, preparation of, I, II, (1) 19*d*.
Zirconia. See also *Refractories; Zirconium, oxide*.
destabilization by cyclic heating, (11) 305*i*.
diffusionless phase transformations in, (10) 291*g*.
effect of Fe_2O_3 on properties, (7) 188*b*.
fibers, for ablation and thermal insulation, (6) 160*c*.
fibers, crystalline, P (3) 69*f*.
foam, thermal and mechanical testing, (8) 215*j*.
granular, production of, P (5) 133*f*.
literature, inconsistencies in, (2) 57*j*.
monoclinic-tetragonal transition, effect of pressure, (2) 56*i*.

Zirconia (*continued*)
O-deficient, pure, stabilized, electric processes in, (8) 219*h*.
phase change of, (3) 88*c*.
reactions with Ti at high temperatures, (9) 256*i*.
research, luminescence phenomena in, (10) 286*h*.
rods, for plasma coating, (6) 155*c*.
setter, P (9) 244*g*.
stabilization, conditions of, (4) 121*e*.
stabilized, growth in arc-image furnace, (10) 284*g*.
systems. See *Systems*.
U-doped, radiation effects in, (10) 275*j*.
Zirconium, boride, method of making, P (4) 102*f*; P (10) 277*g*.
boride, -silicide bodies, P (8) 217*b*.
carbide, as coating for U oxide fuel particles, (11) 308*a*.
in dispersed phase of graphite, Young's moduli of, (4) 101*b*.
high-temperature crystalline modifications, (6) 159*g*.
compounds, Hf-free, production, P (2) 55*h*.
compounds, as opacifiers, (9) 245*i*.
determination with Hf in zircon by paper chromatography, (5) 142*f*.
diboride, abrasive and refractory material, P (8) 216*g*.
dioxide, cubic form, destabilization of, (1) 27*g*.
dioxide, recovery, P (9) 254*j*.
effect on $(Ba,Pb)(Ti,Zr)O_3$ system in $BaTiO_3$ region, (7) 200*i*.
effect on silicate glass properties, (2) 38*j*.
hydride, massive bodies, manufacture by powder metallurgical methods, (10) 275*g*.
ions, precipitation from solution, P (9) 254*c*.
monocarbide, phase change in, (10) 296*a*.
-Nb alloy, oxidation characteristics, (11) 302*j*.
nitride, sintered hard materials from, P (3) 75*a*.
oxide. See also *Zirconia*.
oxide, effect of excess in lead-titanate-zirconate compositions, (1) 19*f*.
silicate, in Ca aluminoborosilicate glass, effect on rate of corrosion of zircon refractories, (1) 6*e*.
silicate, in ceramic materials for heat-resistant machine parts, P (4) 102*c*.
sulfate, solutions, separation of SiO_2 from, P (10) 289*h*.
surface, joining graphite surface to, P (10) 269*c*.
systems. See *Systems*.
tellurites, composition, P (1) 22*b*.
tellurites, method of making, P (1) 21*j*.
and Te, in formation of ZrO_2·2TeO by diffusion in air, (4) 121*e*.
tetrachloride, in pressure transducers, (6) 165*f*.
U-, or Zr-base alloys, process for dissolving, P (1) 17*e,f*.

Ceramic-Metal Systems and Enamel Bibliography with Abstracts and Indexes (1960–1969)

A looseleaf volume of abstracts pertaining to ceramic-metal systems, ceramic systems and porcelain enamels, including materials, processes, properties and patents. This valuable ready reference for researchers, engineers and plant operators is sponsored by the Ceramic-Metal Systems Division of the American Ceramic Society.

Annual supplements to the 1960–1969 edition cost $3 each. The combined 1960 and 1961 supplements with cumulative author and subject indexes, edited and compiled by Gordon H. Johnson, are now available for $6. Looseleaf binders for the edition sell for $2 each.

Enameling literature published before 1960 is indexed and abstracted in three volumes:

"Enamel Bibliography and Abstracts, 1928–1939" at $5 per copy.
"Enamel Bibliography and Abstracts, 1940–1949" at $8 per copy.
"Enamel Bibliography and Abstracts, 1956–1959" at $2 per year.
(The 1950–1955 supplements are out of print.)

American Ceramic Society
4055 N. High St.
Columbus 14, Ohio

DIVISION OFFICERS AND COMMITTEES • 1963-64 • THE AMERICAN CERAMIC SOCIETY

	BASIC SCIENCE	CERAMIC-METAL SYSTEMS	DESIGN	ELECTRONICS	GLASS	MATERIALS & EQUIPMENT	REFRACTORIES	STRUCTURAL CLAY PRODUCTS	WHITE WARES
Trustee	H. F. McMurdie	B. J. Sweo	Jules R. Gulden	W. W. Coffeen	N. J. Kreidl	S. W. Enloe, Jr.	R. R. Rhodes	A. J. Blume	Arno M. Illing
Chairman	Ivan B. Cutler	George Warren	J. Russell Price	W. E. Hauth, Jr.	F. W. Mowrey	J. R. McLaren	T. S. Shevlin	A. J. Jabbusch	F. P. Fonvielle, Jr.
Chairman-Elect	J. H. Westbrook					N. T. Morrison		Paul Martino	W. W. Perkins
Vice-Chairman	J. B. Wachtman, Jr.	Grant E. Miller	Alfred Dube Robert Turner	A. G. Pincus	R. D. Maurer H. E. Simpson	W. G. Coulter	S. D. Stoddard	George Bishop	Alfredo Polar
Secretary	A. E. Paladino, Jr.	J. D. Walton, Jr.	Vivika P. Heino	Seymour Blum	F. V. Tooley	George Wieand	R. W. Limes	Harold Emrich	G. J. Hund
Papers and Programs	D. H. Whitmore Alan D. Franklin J. H. Westbrook	Grant E. Miller	J. Russell Price	A. G. Pincus	J. L. Rood D. A. McGraw V. E. J. Chiochetti	F. J. Zvanut W. K. Burriss Richard Hommel	G. R. Rigby T. J. M. Planje J. H. Handwerk Ralph Padfield	Paul Martino	Fred G. Simmen Milan Vukovich W. B. Campbell D. L. Heath
Membership	L. H. Van Vlack S. C. Carniglia Cyrus Klingsberg	B. G. Craig J. H. Bliton J. H. Lauchner	Alfred Dube Kenneth E. Smith	Bernard Schwartz	W. H. Manring				R. C. Phoenix
Division Nominations	W. J. Smothers Daniel E. Rase Fred Ordway	R. S. Sheldon H. S. Saunders L. S. O'Bannon	J. R. Gulden Kenneth Gale	H. H. Frahme	G. E. Rindone J. R. Hensler R. E. Mould		O. J. Whittemore Edwin Ruh R. J. McEvoy	Forest Paschal R. J. Galvin John Brown	
Classification & Nomenclature	W. G. Lawrence	E. E. Howe W. B. Anderson J. C. Richmond		R. M. Pinkham	H. R. Swift	G. W. Phelps	A. W. Allen		S. F. Etris
Research	R. J. Stokes	H. C. Wilson Samuel Sklarew S. W. Bradstreet	F. J. Von Tury	W. E. Hauth, Jr.	C. R. Kurkjian J. R. Hutchins, III Robert Gardon Eugene Sucov		K. H. Sandmeyer	Hugh Wilson	R. L. Green
Rules	P. J. Jorgensen	R. L. Hadley G. E. Terry George Landis	Don Schreckengost	E. C. Henry	F. W. Mowrey J. W. Michener F. V. Tooley		T. A. Willmore		M. W. Parcel
Standards	R. M. Spriggs			J. L. Pentecost	L. G. Ghering F. V. Tooley W. R. Prindle				Jack F. Day
Bibliography		W. J. Plankenhorn G. H. Johnson J. H. Terry		Walter H. Kohl					W. C. Mohr

NATIONAL INSTITUTE OF CERAMIC ENGINEERS

Trustee	Edward C. Henry
President	William W. Coffeen
President-Elect	Winston Duckworth
Vice-President	Edward E. Mueller
Secretary-Treasurer	William O. Brandt

CERAMIC EDUCATIONAL COUNCIL

Trustee	Gilbert C. Robinson
President	Willis E. Moody
President-Elect	G. Edwin Lorey
Vice-President	Floyd A. Hummel
Secretary-Treasurer	Paul R. Jones

CERAMIC ABSTRACTS

1963

CHARLES S. PEARCE, *Editor*
MARY J. GIBB, *Associate Editor*
M. GERALDINE SMITH, *Assistant Editor*
GERTRUDE M. BUSICK, *Editorial Assistant*
BARBARA L. WHITE, *Editorial Assistant*

Committee on Publications: W. J. SMOTHERS, *Chairman;*
PAUL R. JONES, EDWARD E. MUELLER, AND HOWARD F. MCMURDIE

Technical Adviser: R. S. SHELDON

Compiled by

The American Ceramic Society, Inc.
4055 North High Street
Columbus 14, Ohio

ABSTRACTERS FOR 1963

A. Aladjem—Israel
M. J. Albinak—U. S.
Eugene Aleshin—U. S.
Wilfred Ashworth—England
D. J. Barbour—U. S.
M. P. Bauleke—U. S.
G. Bayer—Switzerland
K. E. Bell—Canada
A. C. Bevan—U. S.
J. G. Brady—Canada
W. B. Campbell—U. S.
T. L. Charland—U. S.
J. J. Diamond—U. S.
Alfred Dube—U. S.
J. R. Fisher—U. S.
J. H. Fishwick—U. S.
C. E. L. Franklin—England
Kanekoto Fujii—Japan
J. E. Gillott—Canada
Francis W. Glaze—U. S.
J. L. Hargrove—U. S.
H. T. Harrison—U. S.
H. S. Hartmann—U. S.
M. P. Haydon—U. S.
R. H. Insley—U. S.
B. Z. Kamich—U. S.
M. J. Kerper—U. S.
A. M. Lacy—U. S.
B. B. Lane—U. S.
S. A. Lindroth—Sweden
J. R. Little—U. S.
L. Luciani—Italy
P. L. Melville—U. S.
V. V. Mirkovich—Canada
Sylva Modry—Czechoslovakia
L. Mordecai—England
R. W. Morgan—U. S.
Taro Moriya—Japan
L. J. Murray—South Africa
M. K. Murthy—Canada
I. Niemeyer—U. S.
A. W. Norris—England
L. S. O'Bannon—U. S.
V. R. Palmeri—U. S.
J. L. Pentecost—U. S.
Walter W. Perkins—U. S.
G. A. Pickup—England
V. S. Ramachandran—Canada
P. E. Rempes, Jr.—U. S.
J. O. Semmelman—U. S.
N. W. Severin—U. S.
Kenneth Shaw—England
Bo Simmingskold—Sweden
W. K. Soderstrum—U. S.
Shigeyuki Somiya—Japan
J. A. Sugden—England
Y. Suzukawa—Japan
V. D. Svikis—Canada
J. W. Taylor—Scotland
R. L. Thakur—India
R. E. Thoma, Jr.—U. S.
A. C. C. Tseung—England
Shigekazu Udagawa—Japan
F. F. Y. Wang—U. S.
R. K. Ware—U. S.
T. B. Weston—Canada
J. H. Weymouth—Australia
J. B. Whitney—U. S.
D. T. Williams—U. S.
W. O. Williamson—U. S.
Hisao Yamada—Japan
Kazuo Yamasaki—Japan